

SAS® 9.2 Intelligence Platform Installation and Configuration Guide



SAS® Documentation

The correct bibliographic citation for this manual is as follows: SAS Institute Inc. 2009. SAS[®] 9.2 Intelligence Platform: Installation and Configuration Guide. Cary, NC: SAS Institute Inc.

SAS® 9.2 Intelligence Platform: Installation and Configuration Guide

Copyright © 2009, SAS Institute Inc., Cary, NC, USA

ISBN 978-1-59994-329-9

All rights reserved. Produced in the United States of America.

For a hard-copy book: No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc.

For a Web download or e-book: Your use of this publication shall be governed by the terms established by the vendor at the time you acquire this publication.

The scanning, uploading, and distribution of this book via the Internet or any other means without the permission of the publisher is illegal and punishable by law. Please purchase only authorized electronic editions and do not participate in or encourage electronic piracy of copyrighted materials. Your support of others' rights is appreciated.

U.S. Government Restricted Rights Notice. Use, duplication, or disclosure of this software and related documentation by the U.S. government is subject to the Agreement with SAS Institute and the restrictions set forth in FAR 52.227–19 Commercial Computer Software-Restricted Rights (June 1987).

SAS Institute Inc., SAS Campus Drive, Cary, North Carolina 27513.

1st electronic book, February 2009

2nd electronic book, June 2009

3rd electronic book, September 2009

4th electronic book, November 2009

5th electronic book, May 2010

6th electronic book, November 2010

7th electronic book, June 2011

1st printing, March 2009

2nd printing, June 2009

SAS Publishing provides a complete selection of books and electronic products to help customers use SAS software to its fullest potential. For more information about our e-books, e-learning products, CDs, and hard-copy books, visit the SAS Publishing Web site at **support.sas.com/publishing** or call 1-800-727-3228.

 $\rm SAS^{\circledast}$ and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. $^{\circledast}$ indicates USA registration.

Other brand and product names are registered trademarks or trademarks of their respective companies.

Contents

What's New v Overview v New SAS Deployment Tools v Security Enhancements v **Deployment Enhancements** vi SAS Port Changes vi Third-Party Software Port Changes vii Changes to Groups for Third-Party Software vii **Documentation Enhancements** vii

Chapter 1 \triangle Introduction to Installing the SAS Intelligence Platform 1

What is the SAS Intelligence Platform?1What Is Covered in This Document?2Deploying the SAS Intelligence Platform2Accessibility Features in the SAS Intelligence Platform Products3

Chapter 2 riangle Setting Up Users, Groups, and Ports 5

Overview of Users, Groups, and Ports5Defining User Accounts6Defining Groups14Additional z/OS Pre-Installation Tasks17Designating Ports and Multicast Addresses19

Chapter 3 riangle Creating a SAS Software Depot 25

Overview of SAS Software Depots25About SAS Software Depots25Benefits of a SAS Software Depot27Best Practices for SAS Software Depots29Creating SAS Software Depots29Managing SAS Orders46

Chapter 4 \triangle Installing Third-Party Products 53

Overview of Installing Third-Party Products 53 **About Installing Third-Party Products** 54 **Review Web Application Server Configuration Documentation** 55 Choose Whether to Automatically Configure Your Web Application Server 55 Choose Whether to Automatically Deploy the SAS Web Applications 56 Install Third-Party Products Using the SAS Software Depot 56 Install Third-Party Products Using the Software Web Site 57 Installing Platform Suite for SAS 58 Pre-installation Checklists for Third-Party Products 59

Chapter 5 riangle Installing and Configuring Your SAS Software 65

Overview of Installing and Configuring Your SAS Software65Preparing to Install and to Configure66Install and Configure SAS Interactively87Validate the SAS 9.2 Servers106About SAS Deployment Tester108Automating the SAS Installation on Multiple Machines109

Chapter 6 \triangle What to Do Next: Administration Tasks 117

Overview of Administration Tasks117First-Priority Setup Tasks118Standard Setup Tasks121Optional Setup Tasks122Ongoing System Administration Tasks124Best Practices for Ensuring the Integrity of Your System125

Appendix 1 △ Troubleshooting Your Initial SAS 9.2 Deployment127Overview of Troubleshooting Your Initial SAS 9.2 Deployment127Review SAS Deployment Tool Documents, Reports, and Logs128Troubleshooting the SAS Server Tier129Troubleshooting SAS Web Applications131

Appendix 2 \triangle Managing Your SAS Deployment 135

Overview of Managing Your SAS Deployment 135 Adding, Updating, and Upgrading SAS Software 136 Adding SAS Products 141 Configuring SAS Products 153 Updating the SID File in Metadata for SAS Solutions 165 Removing a SAS Configuration 169

Appendix 3 \triangle Uninstalling the SAS Intelligence Platform 177

Overview of Uninstalling the SAS Intelligence Platform177Stopping SAS Servers That Are Running178Uninstalling Your SAS Software178Uninstalling Third-Party Software179Uninstalling the SAS JRE and the JDK180

Appendix 4 △ Recommended Reading 181 Recommended Reading 181

Glossary 183

Index 191

What's New

Overview

The SAS Intelligence Platform: Installation and Configuration Guide explains how to install and initially configure the SAS Intelligence Platform.

V

This document contains new material on the following enhancements and changes to the SAS Intelligence Platform:

- \square new SAS deployment tools
- \Box security enhancements
- \Box deployment enhancements
- \square SAS port changes
- $\hfill\square$ third-party software port changes
- $\hfill\square$ changes to groups for third-party software

New SAS Deployment Tools

SAS 9.2 has new deployment tools:

- □ The SAS Download Manager enables you to download your SAS order by using an HTTP connection over the Internet.
- The SAS Deployment Wizard combines SAS installation and initial configuration into one wizard, replacing the SAS Software Navigator and the SAS Configuration Wizard.
- □ In the second maintenance release for SAS 9.2, the SAS Update File Cleanup Utility removes backup copies of SAS software that the deployment wizard automatically creates when in update mode.

Security Enhancements

SAS 9.2 has the following security enhancements:

- \Box Fewer operating system accounts are required to run SAS 9.2.
- $\hfill\square$ Internal accounts are new to SAS 9.2 and are used by default for some of the required users (such as sastrust and sasadm).

- Integrated Windows authentication (IWA) provides single sign-on functionality for Windows desktop users.
- □ You no longer have to manually grant the Windows user right Log on as a batch job to the sassrv user account. The SAS Deployment Wizard automatically does this for you.
- □ On Windows platforms supported by SAS 9.2, the Windows permission Act as part of the operating system is no longer required for SAS server users or the Platform Suite for SAS administrator.

Deployment Enhancements

SAS 9.2 has the following deployment enhancements:

- □ Automated, initial SAS configuration eliminates most post-installation manual configuration scripts.
- □ Up-front user inputs enable you to avoid having to monitor the entire wizard session.
- □ Installation includes an automated check for required third-party software.
- An electronic product registration feature sends customer installation data to SAS in order to better assist customers if they call SAS with problems or questions. Electronic registration is optional and secure, and does not impact the licensing or use of the software. For more information, see: http://support.sas.com/legaldocs/eregistration.html.
- □ The initial SAS installation data file is contained within the SAS Software Depot.
- □ Automated deployment is possible across multiple machines (capture-replay feature).
- □ Space and time estimates are provided for SAS software depot creation.
- □ You can create disc images of your SAS order, so that you can burn to CDs or DVDs at a later time.
- □ On z/OS, you no longer need to define a SAS/C executable library to be program controlled.
- □ In the October 2009 release, the ability to renew your software license for SAS solutions with the SAS Deployment Manager is new.

SAS Port Changes

The following SAS port changes have been made:

- □ A SAS Pooled Workspace Server port has been added: 8701.
- $\hfill\square$ A SAS Table Server port has been added: 2171.
- □ Three new SAS Object Spawner port banks have been added: 8801, 8811, and 8821.
- □ The SAS Remote Services Application port has been changed from 5099 to 5091.
- $\hfill\square$ The SAS Object Spawner load balancing port has been removed.
- □ A metadata utilities SAS Workspace Server port has been added: 8591.
- \square A SAS Deployment Tester Server port has been added: 10021.

In the November 2010 release of SAS 9.2, the following SAS port changes have been made:

□ The RMI port for the BI Portlets registry has been removed: 9000.

□ Three UDP ports for SAS Web Report Studio IP Scheduling have been added: 7570, 7571, and 7572.

Third-Party Software Port Changes

The following Platform LSF ports in the Platform Suite for SAS have been added or changed: 6878, 6881, 6882, 7869, 7870, 7871, 7872.

The following changes have been made to JBoss Web application server ports:

- □ RMI ports for managed servers have been added: 1099, 1199, (additional managed servers increment by 100).
- □ Listen ports for managed servers have been added: 8080, 8180, (additional managed servers increment by 100).
- □ Secure listen ports for managed servers have been added: 8443, 8543, (additional managed servers increment by 100).

The following changes have been made to Oracle WebLogic Web application server ports:

- \square A WebLogic Nodemanager port has been added: 5556.
- □ Secure listen ports for managed servers have been added: 7002, 7102, (additional managed servers increment by 100).

The following changes have been made to IBM WebSphere Web application server ports:

- \Box A SOAP port for administrative console has been added: 8879.
- □ SOAP ports for application servers have been added: 8880, 8881, (additional application servers increment by one).
- □ Secure HTTPS port for administrative console has been added: 9043.
- □ A non-secure HTTP port for administrative console has been added: 9060.
- □ Secure HTTPS ports for application server administrative console have been added: 9044, 9045, (additional administrative consoles increment by one).
- \Box An RMI port for administrative console has been added: 9809.
- □ RMI ports for application servers have been added: 9811, 9812, (additional application servers increment by one).

In the November 2009 release of SAS 9.2, the IBM WebSphere Portal Server listening port 10040 was added.

Changes to Groups for Third-Party Software

In the third maintenance release for SAS 9.2, for UNIX and z/OS it is recommended that the SAS Installer and the WebSphere Application Server installer be in the same operating system group in order to have the necessary permissions for writing to installation directories.

Documentation Enhancements

SAS deployment troubleshooting information is now contained in the SAS Intelligence Platform: Installation and Configuration Guide. In the November 2010 release of SAS 9.2, the following major documentation enhancements were made:

- $\hfill\square$ Data direction was documented for SAS and required third-party software ports.
- □ Instructions were added for how to install SAS Web Parts for Microsoft SharePoint.
- □ Instructions were added for how to deploy SAS BI Lineage when LSF Scheduler is on a separate machine from the workspace server.



Introduction to Installing the SAS Intelligence Platform

What is the SAS Intelligence Platform? 1
What Is Covered in This Document? 2
Deploying the SAS Intelligence Platform 2
Overview of Deploying the SAS Intelligence Platform 2
Step 1: Review Additional Documentation 2
Step 2: Create Operating System Users and Groups and Designate Ports 3
Step 3: Create a SAS Software Depot 3
Step 4: Install Required Third-Party Software 3
Step 5: Install and Configure SAS 3
Accessibility Features in the SAS Intelligence Platform Products 3

What is the SAS Intelligence Platform?

The SAS Intelligence Platform is a comprehensive, end-to-end infrastructure for creating, managing, and distributing enterprise intelligence. The SAS Intelligence Platform comprises four software offerings:

- \square SAS BI Server
- □ SAS Enterprise BI Server
- □ SAS Data Integration Server
- □ SAS Enterprise Data Integration Server

Solutions for enterprise intelligence, customer intelligence, and financial intelligence are built on the Intelligence Platform, as well as turnkey solutions for specialized markets in life sciences, health care, retail, manufacturing, and others. Therefore, if your SAS deployment plan includes a SAS solution, then the SAS Intelligence Platform documentation also pertains to you.

The SAS Intelligence Platform library provides information for the four platform offerings, which include products and components such as the SAS Metadata Server, SAS Integration Technologies, and the SAS OLAP Server. See http://support.sas.com/92administration for more information about these four software offerings and their components.

What Is Covered in This Document?

This document begins where you and your SAS representative have decided what software you need and on what machines you will install the software. At this point, you can begin performing some pre-installation tasks, such as creating operating system user accounts and designating the ports that you will use during installation.

This document covers all of the pre-installation, installation, and configuration tasks that you must perform to deploy the SAS Intelligence Platform on either a single machine or in a distributed, mixed operating system environment. By the time you reach the end of this document, all of your SAS servers, middle-tier servers, and clients will be functional.

Installing the software will be easier if you read the following documents as well:

- □ SAS Intelligence Platform: Overview to understand the architecture of the system.
- configuration documentation for SAS solutions. Many of the solutions leverage the functionality of the SAS Intelligence Platform. If your SAS deployment plan includes a solution, then you might also be referred to additional solution-specific configuration information.

Note: If you have licensed SAS solutions, consult with your SAS representative for more information. \triangle

Deploying the SAS Intelligence Platform

Overview of Deploying the SAS Intelligence Platform

The following list summarizes the steps required to install and configure the SAS Intelligence Platform on a single machine or in a distributed, heterogeneous environment. The first three steps are pre-installation tasks and can be performed in any order. Perform step 4 after steps 1 through 3 are completed:

- 1. Review additional documentation.
- 2. Create operating system users and groups and designate ports.
- 3. Create a SAS Software Depot.
- 4. Install required third-party software.
- 5. Install and configure SAS.

The sections below provide a brief description of each of these tasks. Subsequent chapters in the guide provide the step-by-step instructions that you will need to perform them.

Step 1: Review Additional Documentation

Review the QuickStart Guide that is shipped with your SAS software. Follow its instructions, including reviewing the system requirements and any alert-level SAS Notes. If you are deploying a SAS solution, review any solution-specific installation documents.

These documents are also available online:

QuickStart Guides:

http://support.sas.com/documentation/installcenter/92/documents

 \Box SAS 9.2 system requirements:

http://support.sas.com/documentation/installcenter/92/documents

 \Box Alert-level SAS Notes:

http://support.sas.com/kb/?ct=51000

(Click "Search Problem Notes" in the left-hand navigation pane.)

 \Box SAS solution installation guide:

Installation Instructions–Release 5.1 of the SAS Performance Management Solutions

Available at any of these locations:

- http://support.sas.com/documentation/onlinedoc/fm/
- http://support.sas.com/documentation/onlinedoc/hcm/
- http://support.sas.com/documentation/onlinedoc/stm/

Step 2: Create Operating System Users and Groups and Designate Ports

Create a set of operating system users and groups that will be required during the installation and configuration of your system, and designate a set of ports to use.

For more information, see "Overview of Users, Groups, and Ports" on page 5.

Step 3: Create a SAS Software Depot

Create a SAS Software Depot, which enables you to install the SAS software over your site's network, rather than from the installation media.

Note: If you have elected to receive SAS through Electronic Software Delivery, a SAS Software Depot is automatically created for you. \triangle

For more information, see "Overview of SAS Software Depots" on page 25.

Step 4: Install Required Third-Party Software

Install any third-party products, such as a Java Development Kit and a Web application server, that are necessary for your installation. These products are identified in your deployment plan.

For more information, see "Overview of Installing Third-Party Products" on page 53.

Step 5: Install and Configure SAS

Install and configure your SAS software using the SAS Deployment Wizard, an installation and configuration tool that is supplied by SAS.

For more information, see "Overview of Installing and Configuring Your SAS Software" on page 65.

Accessibility Features in the SAS Intelligence Platform Products

For information about accessibility for any of the products mentioned in this book, see the documentation for that product. If you have questions or concerns about the accessibility of SAS products, send e-mail to accessibility@sas.com or visit the SAS accessibility site at: http://www.sas.com/govedu/accessibility.html.

CHAPTER

Setting Up Users, Groups, and Ports

Overview of Users, Groups, and Ports 5 Defining User Accounts 6 Overview of Defining User Accounts 6 Internal User Accounts 6 Required External User Accounts for SAS 7 Rights Required by External User Accounts for SAS 9 Required External User Accounts for Third-Party Software 9 Rights Required by External User Accounts for Third-Party Software 10 Local or Directory Service Accounts? 10 Password Policies 11 Pre-installation Checklist for External User Accounts for SAS on Windows and UNIX 11 Pre-installation Checklist for External User Accounts for Third-Party Software 12 Pre-installation Checklist for External User Accounts for SAS on z/OS 13 Defining Groups 14 Overview of Defining Groups 14 The SAS Server Users Group (Windows) 14 The sas Group (UNIX) 15 The SASGRP Group (z/OS) 15 Pre-installation Checklist for Groups for SAS on Windows and UNIX 15 Pre-installation Checklist for Groups for Third-Party Software 16 Pre-installation Checklist for Groups for SAS on z/OS 16 Additional z/OS Pre-Installation Tasks 17 About Additional z/OS Pre-Installation Tasks 17 Create a Configuration Directory and Define the SAS Library on z/OS 17 Install the SAS 9.2 SVC Routine 18 Install the SASCP Module 18 Designating Ports and Multicast Addresses 19 About Ports and Multicast Addresses 19 Multicast Address Considerations 19 Pre-installation Checklist for Ports for SAS 21

Overview of Users, Groups, and Ports

Before you begin installing and configuring your software, you must create a set of required users and groups at the operating system level, and you must designate a set of TCP/IP ports for the servers to use. This is the second of five tasks required to install and configure the SAS Intelligence Platform.

- 1. Review additional documentation.
- ▶ 2. Create operating system users and groups and designate ports.
 - 3. Create a SAS Software Depot.
 - 4. Install required third-party software.
 - 5. Install and configure SAS.

Defining User Accounts

Overview of Defining User Accounts

There are two types of user accounts to understand when deploying SAS:

- □ *Internal user accounts* are accounts known only to SAS and are created and authenticated internally in metadata rather than externally.
- □ *External user accounts* are user accounts defined outside of SAS metadata. These accounts are local to a machine or are defined in a network directory service of which the machine is a member, such as LDAP.

The following sections describe the user accounts that SAS and third-party software require, and provide information to help you answer these questions:

- \Box What are internal and external user accounts?
- □ What user rights or to what groups must each account be assigned?
- □ Should I create local or network directory service accounts?
- □ What password policies should I enforce?

Internal User Accounts

Internal user accounts are accounts known only to SAS and are created and authenticated internally in metadata rather than externally. SAS identifies internal accounts by appending a special string to the user ID. This string begins with an at sign (@) and contains *saspw*: **@saspw**. For two of the required user accounts, the SAS Administrator and the SAS Trusted User, the SAS Deployment Wizard prompts you by default to create *internal* user accounts.

The following table shows the default internal user accounts required by SAS. (SAS internal accounts are authenticated on the metadata server.)

Table 2.1	SAS	Internal	User	Accounts

Description	User ID
SAS Administrator—	sasadm@saspw
The user account that has privileges associated with the SAS Metadata Unrestricted Users role.	
SAS Trusted User—	sastrust@saspw
The user account that can impersonate other users on connections to the metadata server. Some SAS processes use this account to communicate	

with the metadata server on a client's behalf.

For more information about SAS internal user accounts and their purposes, see "Understanding the State of Your System" in the SAS Intelligence Platform: System Administration Guide.

Here are some benefits of internal accounts:

 \Box less maintenance.

The account is defined only once in SAS, and you do *not* define this account externally using the authentication provider.

 \Box isolation from the host machine security policy.

The SAS Administrator and the SAS Trusted User credentials are referenced in many locations within SAS. For example, forcing a recurring password change (a common security policy) might make unnecessary work for the person administering SAS.

 \Box independence from IT.

You can create additional SAS unrestricted user and administrative user accounts for metadata management without involvement of your IT department.

 $\hfill\square$ reduced "headless" external user accounts.

The SAS Trusted User is an account used for SAS inter-process communication, and it will not be mistaken for a human user.

□ minimal security exposure to your enterprise.

The SAS Administrator and the SAS Trusted User are highly privileged accounts and only provide access to SAS—not to operating system resources.

Required External User Accounts for SAS

External user accounts are user accounts defined outside of SAS metadata. These accounts are local to a machine or are defined in a network directory service of which the machine is a member, such as LDAP. SAS requires certain *external* user accounts for two purposes: installation and running certain SAS server processes.

During installation and configuration, the SAS Deployment Wizard must run under an external account with the necessary privileges on the target machine to write SAS program and log files. To run servers such as the stored process server and the pooled workspace server, SAS requires an external user account to be the server process owner. For more information about external user accounts and their purposes, see the SAS Intelligence Platform: System Administration Guide.

As you set up external accounts, remember to use different external accounts for the SAS First User and the SAS Spawned Servers user. Otherwise, your configuration will end in errors and the SAS pooled workspace server will not be functional.

As you create these external user accounts, record information about them in "Pre-installation Checklist for External User Accounts for SAS on Windows and UNIX" on page 11 or in "Pre-installation Checklist for External User Accounts for SAS on z/OS" on page 13. You will need this information when you run the SAS Deployment Wizard later.

Note: To validate your SAS deployment, you will need an external user account that is representative of a SAS client user, such as SAS Data Integration Studio, that must be the temporary process owner when its jobs are run on a standard workspace server. If Integrated Windows authentication (IWA) is *not* being implemented, it can be helpful to have the SAS Deployment Wizard create a SAS First User account in metadata during deployment for validation purposes. The wizard will also assign the required **Log on as a batch job** Windows user right for you. \triangle

The following table shows external user accounts required by SAS and the machines on which they are authenticated.

 Table 2.2
 Required External User Accounts for SAS

Description	Recommended User ID	Machine Where Authenticated
SAS Installer—	sas	Every machine
The account used to install SAS.		
SAS Spawned Servers account—	sassrv	Stored process server
The process owner for stored process servers and pooled workspace servers.		Pooled workspace server

Note:

- □ For information about the user rights that each external account requires, see "Rights Required by External User Accounts for SAS" on page 9.
- UNIX: the SAS Installer generally overrides the default configuration directory with the site's preferred location (for example, /opt/sas/config). The installer must have Write permission on this path.
- □ Windows: The SAS Installer user ID must be available in the long term for future SAS maintenance.
- □ UNIX: Do not use root for the SAS Installer user ID.
- □ AIX: For both user IDs, make sure that the **User can LOGIN**? setting is set to **true**.
- □ z/OS: The SAS Installer and the SAS Spawned Servers account must have a TSO segment defined.
- $\hfill\square$ z/OS: By default, the SAS Installer:
 - $\hfill\square$ is the started task owner for the servers.
 - \Box is the owner of the configuration directory structure.
 - $\hfill\square$ must have a writable home directory in the UNIX file system.
 - □ must have an OMVS segment definition with the following *minimum* settings:
 - \square ASSIZEMAX of at least 2 GB
 - □ CPUTIMEMAX of at least 5000 seconds
 - □ PROCUSERMAX of at least 50 users

Rights Required by External User Accounts for SAS

Operating systems require that you assign certain rights to the external user accounts used to deploy and to run SAS.

The following table describes the user rights needed by the required external user accounts to deploy and run SAS.

External User Account	Operating System	User Rights Needed
SAS Installer	Windows	Administrator rights
	UNIX	Member of a group that is the <i>primary</i> group for the SAS Spawned Servers account
	z/OS	Default member of a group that also includes the SAS Spawned Servers account
SAS Spawned	$Windows^1$	Log on as a batch job
Servers account	UNIX	Member of a group that is the <i>primary</i> group for the SAS Installer
	z/OS	Member of a group that also includes the SAS Installer user

 Table 2.3
 Rights Required by External User Accounts for SAS

1 The SAS Deployment Wizard automatically assigns the Windows user right Log on as a batch job to the SAS Spawned Servers account.

On Windows, if you choose how to run your SAS servers using management scripts—instead of running them as Windows services—then the user account that runs the object spawner must meet the following requirements on the object spawner machine:

- $\hfill\square$ be the administrator or a member of the Windows Administrator's group
- $\hfill\square$ have the following Windows local user rights:
 - □ Adjust memory quotas for a process
 - Replace a process level token

Required External User Accounts for Third-Party Software

The following table describes the external user accounts required by third-party software and the machines on which they are authenticated—either as local accounts or in a network directory service that the machine can access.

Description	Recommended User ID	Machine Where Authenticated
LSF Administrator— Process owner for Platform LSF services and daemons. Required if you install Platform Suite for SAS to support scheduling or grid computing. Also owns the LSF configuration and log files and has permission to perform cluster-wide operations, edit configuration files, and reconfigure a cluster.	lsfadmin	Every Platform Process Manager and Platform LSF machine
LSF User— Sometimes referred to as the scheduling user. Required by SAS Web Report Studio to run the Output Generation Tool, which creates scheduled reports in batch mode.	lsfuser	Platform Process Manager

 Table 2.4
 Required External User Accounts for Third-Party Software

As you create these external user accounts, record information about them in "Pre-installation Checklist for External User Accounts for SAS on Windows and UNIX" on page 11. You will need this information when you run the SAS Deployment Wizard (in Chapter 6).

Note: For information about the user rights that each account requires, see "Rights Required by External User Accounts for Third-Party Software" on page 10. \triangle

Rights Required by External User Accounts for Third-Party Software

The following table describes the user rights needed by the required external user accounts to deploy and run third-party software:

External User Account	Operating System	User Rights Needed
LSF	Windows	Administrator rights
Administrator		Adjust memory quotas for a process
		Debug programs
		Log on as a service
_		Replace a process level token
LSF User	Windows	Log on as a batch job or Log on locally

 Table 2.5
 Rights Required by External User Accounts for Third-Party Software

Local or Directory Service Accounts?

SAS relies on its various server machines to authenticate external user accounts. In turn, the SAS server machine authenticates user accounts using an authentication provider. An *authentication provider* refers to an authentication service that is one of the following:

 \Box local to a machine and used to authenticate local host user accounts

□ available to a machine through a computer network and used to authenticate directory service accounts such as LDAP or Active Directory

You can create either local or directory service accounts for external users. The only requirement is that each user shown in Table 2.2 on page 8 can be authenticated by the machine's authentication provider—be that an authentication provider that is local to the machine, or an authentication provider that is available to the machine through a directory service.

The main advantage of local accounts is that if account information were to get into the wrong hands, the credentials could be used only to log on to the machine or machines that can authenticate the credentials. A secondary benefit is that the host could continue to authenticate users even if the directory service authentication provider were unavailable.

The advantage of directory service accounts is that you do not have to create the same accounts on multiple machines or keep the account information synchronized across machines—the directory service authentication provider does this for you.

For example, setting up the SAS Spawned Server user account is usually straightforward. The spawned server account must be able to be authenticated by the pooled workspace server and stored process server machine. If these servers are distributed on more than one machine, then each machine must be a member of the same directory service or in different directory services between which a trust has been established.

Password Policies

Note: In this section, we are talking only about the passwords for the few external user accounts SAS requires, not the passwords for regular users of the system. \triangle

When you set up passwords for your SAS system users, we *highly recommend* that these passwords do not have to be reset when a user first logs on. If, for some reason, it is required that you create passwords that have to be reset, you will have to log on using each account and change the password before you install and configure your software. And, of course, you will need to know the changed password for each account.

By default, passwords for internal accounts are set not to expire. When passwords for system accounts change, you must update a set of configuration files and some metadata objects. SAS provides instructions for updating these files and metadata objects. However, you can save yourself some time if the passwords do not expire.

Pre-installation Checklist for External User Accounts for SAS on Windows and UNIX

Use the following pre-installation checklist to create the necessary external user accounts to deploy and run SAS on Windows and UNIX.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Account	Recommended User ID	Actual User ID	
SAS Installer	Windows: <i>my-domain\installer-ID</i> ¹ UNIX: sas ^{2,3}		
SAS Spawned Servers account	Windows: <i>my-domain</i> \sassrv UNIX: sassrv ²		

 Table 2.6
 Pre-installation Checklist for External User Accounts for SAS on

 Windows and UNIX
 Image: Comparison of Compar

1 On Windows, the user ID should be available in the long term for future SAS maintenance.

2~ On AIX, make sure that the User can LOGIN? setting is set to true for the user.

3 On UNIX, do not use root.

Note these important items:

- □ For information about the user rights that each external account requires, see "Rights Required by External User Accounts for SAS" on page 9.
- □ The SAS Deployment Wizard prompts you for the Installer account and the SAS Spawned Servers account information, and you cannot complete the installation without supplying it.
- □ On UNIX systems, the SAS Deployment Wizard requires that you supply the root password during configuration. Certain SAS products and features use functionality that requires SAS to check user ID authentication and file access authorizations. This in turn necessitates that certain files within your SAS installation have setuid permissions and be owned by root.
- □ If your UNIX system uses an authentication method other than /etc/passwd or / etc/shadow, then you must configure authentication before you begin your SAS software deployment, or SAS 9.2 will not function properly. For more information, see the *Configuration Guide for SAS 9.2 Foundation for UNIX Environments* available at http://support.sas.com/installcenter.

Pre-installation Checklist for External User Accounts for Third-Party Software

Use the following pre-installation checklist to create the necessary external user accounts to deploy and run third-party software.

Note: The SAS Deployment Wizard prompts you for this information, and you cannot complete the installation without it. \triangle

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Account	Recommended User ID	Actual User ID
LSF	Windows: my-domain \lsfadmin	
Administrator	UNIX: lsfadmin	
LSF User	Windows: my-domain \lsfuser	
	UNIX: lsfuser	

 Table 2.7
 Pre-installation Checklist for External User Accounts (Third-Party)

Note: For information about the user rights that each account requires, see "Rights Required by External User Accounts for Third-Party Software" on page 10. \triangle

Pre-installation Checklist for External User Accounts for SAS on z/OS

Use the following pre-installation checklist to create the necessary external user accounts to deploy and run SAS on z/OS.

Note: The SAS Deployment Wizard prompts you for this information, and you cannot complete the installation without it. \triangle

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

 Table 2.8
 Pre-installation Checklist for External User Accounts for SAS on z/OS

Account	Recommended User ID	Actual User ID
SAS Installer	sas	

SAS Spawned sassrv Servers account

Note:

- □ For information about the user rights that each external account requires, see "Rights Required by External User Accounts for SAS" on page 9.
- □ The SAS Installer and the SAS Spawned Servers account must have a TSO segment defined.
- $\hfill\square$ By default, the SAS Installer:
 - $\hfill\square$ is the started task owner for the servers.
 - $\hfill\square$ is the owner of the configuration directory structure.
 - □ must have a writable home directory in the UNIX file system.
 - \Box must have an OMVS segment definition with the following *minimum* settings:
 - □ ASSIZEMAX of at least 2 GB
 - □ CPUTIMEMAX of at least 5000 seconds

□ PROCUSERMAX of at least 50 users

Δ

Defining Groups

Overview of Defining Groups

On UNIX, adding users to a group is required to assign the necessary operating system privileges to deploy and run SAS. Using a group is one method for granting the corresponding user rights needed on Windows.

The SAS Server Users Group (Windows)

To deploy SAS on Windows, the user must have certain local user rights on the machine hosting the server. These rights are required before the user can start a process for a stored process server, a pooled workspace server, or a standard workspace server. One suggestion for giving a user these rights is to create a group, add users to the group, and then assign the rights to the group. (The scheduling user, lsfuser—which is required if you are scheduling reports—also must have this same right.)

Note: Not all of these user accounts will exist in every installation. You add only those that you have created. In addition, if you are working in a multi-machine environment and are using local groups, not all of the users that you have created need to be included in every local group. You need only include the users who will be authenticated by a stored process server, pooled workspace server, or standard workspace server on a given machine. On some machines (for example, a machine hosting middle-tier components) there might be no need for the group at all. \triangle

To set up a group, complete these steps:

- 1 Create a SAS server users group. This can be a local group or a group with domain scope.
- 2 Add the following users to the group:
 - □ SAS Spawned Servers account
 - □ SAS First User (optional account)
 - \Box LSF User
 - \Box any other external users that need to access a standard workspace server

Note: The SAS Deployment Wizard automatically grants the Windows user right **Log on as a batch job** to the SAS Spawned Servers account. If you choose to have the wizard create the optional SAS First User account in metadata, the wizard also automatically grants the **Log on as a batch job** Windows user right to this First User account. If Integrated Windows authentication (IWA) is implemented, this user right is not required for the SAS First User and other regular SAS users who access standard workspace servers, such as SAS Data Integration Studio or SAS Enterprise Guide users. \triangle

3 Finally, grant the user right Log on as a batch job to the group. For information about setting local user rights, see your Microsoft Windows documentation. If the users in the group need that right on more than one Windows machine, the right needs to be assigned specifically on each machine.

The sas Group (UNIX)

To deploy SAS on UNIX, you should create an operating system group and make this the *primary* group for the UNIX SAS Installer user. The SAS Spawned Servers account should also be made a member of the sas group. (Members of this group will be given access to certain directories and files created by the SAS Deployment Wizard.)

For information about creating groups and adding user accounts, see your UNIX documentation.

The SASGRP Group (z/OS)

To deploy SAS on z/OS, you should create a RACF group named SASGRP. This group is used to control access to directories and files in the configuration directory created in the HFS file system. The definition of this RACF group must include an OMVS segment and must be set as the default group for the SAS Installer and the SAS Spawned Servers account.

For information about creating groups and adding user accounts, see your IBM z/OS documentation.

Pre-installation Checklist for Groups for SAS on Windows and UNIX

Use the following pre-installation checklist to make sure that you have created the necessary groups to deploy and run SAS on Windows and UNIX:

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Recommended Group Name	Group Members	Operating System and Purpose	Actual Group Name
SAS Server Users ¹	SAS Spawned Servers account	Windows— Suggested method for assigning the Log on as a batch job user right to the SAS Spawned Servers account for the stored process server and pooled workspace server.	
	SAS First User Any other users	Suggested method for assigning the Log on as a batch job user right to the SAS First User and any other standard workspace server users.	

Table 2.9 Pre-installation Checklist for Groups for SAS on Windows and UNIX

Recommended Group Name	Group Members	Operating System and Purpose	Actual Group Name
sas ²	SAS Installer	UNIX—	
		Primary group for the SAS Installer user. Enables the SAS Deployment Wizard to create the necessary log and configuration directories required by SAS.	
	SAS Spawned Servers account	Through group membership, grants Write permissions to the SAS Spawned Server account for modifying SAS log and configuration directories.	

1 Unless Integrated Windows authentication (IWA) is implemented, add any other any external users accessing standard workspace servers.

2 Limit membership because this privileged group has operating system access to certain configuration files.

Pre-installation Checklist for Groups for Third-Party Software

Use the following pre-installation checklist to create the necessary groups to deploy and run third-party software.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

 Table 2.10
 Pre-installation Checklist for Groups for Third-Party Software

Recommended Group Name	Group Members	Operating System and Purpose	Actual Group Name
SAS Server Users	Scheduling user (lsfuser)	Windows— Suggested method for assigning the Log on as a batch job user right to scheduling users.	
sas	SAS Installer (sas) WebSphere Application Server Installer	UNIX— Suggested method for assigning required permissions to write to certain installation directories.	
SASGRP	SAS Installer (sas) WebSphere Application Server Installer	z/OS— Suggested method for assigning required permissions to write to certain installation directories.	

Pre-installation Checklist for Groups for SAS on z/OS

Use the following pre-installation checklist to create the necessary groups to deploy and run SAS on z/OS:

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Table 2.11 Pre-installation Checklist fo	or Groups	for SAS	on z/OS
--	-----------	---------	---------

Recommended Group Name	Group Members	Purpose(s)	Actual Group Name
$SASGRP^1$	SAS Installer	Default group for the SAS Installer user.	
	SAS Spawned Servers account	Through group membership, grants write permissions to the SAS Spawned Server account for modifying SAS log and configuration directories.	

1 The definition of this RACF group must include an OMVS segment. Limit membership because this privileged group has operating system access to certain configuration files.

Additional z/OS Pre-Installation Tasks

About Additional z/OS Pre-Installation Tasks

In addition to creating the necessary users, groups, and ports, to deploy the SAS Intelligence Platform on z/OS, you must also do the following:

- □ Create a directory that will serve as the configuration directory for the SAS server tier on the z/OS machine.
- $\hfill\square$ Define the SAS executable library to be program-controlled.
- $\hfill\square$ Install the SAS 9.2 SVC routine
- $\hfill\square$ Install the SASCP module

Create a Configuration Directory and Define the SAS Library on z/OS

In addition to creating the necessary users, groups, and ports, to deploy the SAS Intelligence Platform on z/OS, you must also do the following:

- □ Create a directory that will serve as the configuration directory for the SAS server tier on the z/OS machine.
- □ Define the SAS executable library to be program-controlled.

Record this information in the following checklist:

 Table 2.12
 Configuration
 Directory and SAS Executable Library Checklist on z/OS

ask	Actual Directory or Library Name

Create a configuration directory $^{1}% ^{1}$ for the SAS server tier

Define the SAS executable library to be program-controlled

1 A typical path is /usr/lpp/SAS/SAS_9.2/config-directory.

Install the SAS 9.2 SVC Routine

In addition to creating the necessary users, groups, and ports, to deploy the SAS Intelligence Platform on z/OS, you must also install the SAS 9.2 SVC routine. To install the SAS 9.2 SVC routine, follow these steps:

- 1 Download the instsvc.xmit file from the SAS FTP Web site at ftp:// ftp.sas.com/techsup/download/mvs/.
- **2** Using FTP, transfer the instsvc.xmit file (in binary mode) to your z/OS system. You should preallocate the target data set with the following DCB characteristics:

LRECL=80

BLKSIZE=3120

RECFM=FB

3 Use the following RECEIVE command to create a PDS that will contain the JCL members that are required to install the SVC routine, where sas92.instsvc.xmit is the name of the file to which you transferred the instsvc.xmit file, using FTP.

receive indataset(sas92.instsvc.xmit)

Respond with the name of a data set that will contain the JCL members (that you will use to complete the installation) by issuing the following command:

da(sas92.instsvc.cntl)

4 Create the library that will contain the load modules by issuing the following command, where SAS92.INSTSVC.CNTL is the data set that you created in the previous step:

```
receive indataset(sas92.instsvc.cntl(svcmod))
```

5 Respond with the name of a data set that will contain the load modules by issuing the following command:

da(sas92.instsvc.library)

- **6** Continue your SVC installation by following the instructions in "Installing the SAS 9.2 SVC Routine" in the *Configuration Guide for SAS 9.2 Foundation for* z/OS, with the following exceptions:
 - □ Anywhere that the documentation references the BAMISC data set, use the CNTL data set that you created in step 3.
 - □ Anywhere that the documentation refers to the SAS.LIBRARY data set, use the data set that you created in step 4.

The Configuration Guide for SAS 9.2 Foundation for z/OS is located on the SAS Install Center Web site at http://support.sas.com/idsearch?ct=200000 (search for the document title).

Install the SASCP Module

In addition to creating the necessary users, groups, and ports, to deploy the SAS Intelligence Platform on z/OS, you must also install the SAS 9.2 SASCP module. To install the SAS 9.2 SASCP module, follow these steps:

1 Download the instsascp.xmit file from the SAS FTP Web site at ftp:// ftp.sas.com/techsup/download/mvs/. 2 Using FTP, transfer the instsascp.xmit file (in binary mode) to your z/OS system.

You should preallocate the target data set with the following DCB characteristics:

LRECL=80 BLKSIZE=3120 RECFM=FB

3 Use the following RECEIVE command to create a PDS that will contain the SASCP load module, where sas92.insascp.xmit is the name of the file to which you transferred the instsascp.xmit file, using FTP.

receive indataset(sas92.insascp.xmit)

Respond with the name of the target data set to contain the SASCP load module by issuing the following command:

da(sas92.insascp.load)

4 Copy the SASCP module to a load library that contains TSO commands.

This can be a STEPLIB library defined in a LOGON procedure, a system link list library, or a link pack area library.

For more information about the SASCP module see "Implementing SAS TSO Support" in the *Configuration Guide for SAS 9.2 Foundation for z/OS* located on the SAS Install Center Web site at http://support.sas.com/ idsearch?ct=200000 (search for the document title).

Designating Ports and Multicast Addresses

About Ports and Multicast Addresses

While you are creating operating system user accounts and groups, you need to review the set of ports that the SAS servers, third-party servers, and spawners in your system will use by default. If any of these ports is unavailable, select an alternate port, and record the new port on the following ports pre-installation checklists:

- "Multicast Address Considerations" on page 19
- □ "Pre-installation Checklist for Ports for SAS" on page 21

For third-party software ports, see "Pre-installation Checklists for Third-Party Products" on page 59.

You also need to plan for designating Internet Protocol (IP) multicast addresses for the all the machines in your SAS deployment. Multicasting simplifies the on-going management and deployment of SAS Web applications, by providing the flexibility to customize the SAS middle-tier, and to distribute SAS Web components to implement load balancing.

Multicast Address Considerations

The SAS Deployment Wizard prompts you to supply a multicast address for inter-machine communication. The wizard supplies you with a default multicast address that it generates based on the machine's IP address and the admin local scope that is recommended in RFC 3171 (IPv4) or RFC 4291 (IPv6).

A multicast group communications protocol is used to communicate among middle-tier SAS applications in a single SAS deployment (the set of applications connected to the same SAS Metadata Server). The combination of multicast IP address and multicast UDP port should be different for each SAS deployment and also different from those used by other multicast applications at your site.

The multicast group communication includes all information needed to bootstrap SAS middle-tier applications. Because this includes sending the SAS environment credentials (such as the sasadm account name and its password), scoping and encryption options are provided. The defaults are most appropriate for deployments in a firewall, isolated data center environment.

The IP multicast address must be valid for IP multicasting and should be in the range 224.0.0.0 to 239.255.255 for IPv4 or have the prefix ff00::/8. Typically, the chosen address will be in the admin-local scoped block which corresponds to 239/8 for IPv4 and ff14::/8 for IPv6. The sample address provided during configuration by the SAS Deployment Wizard conforms to these standards. The address should be unique to SAS applications for the subnet they are installed on.

The IP Multicast UDP port should be open and usable on any machine a middle-tier application is to be installed. This is a UDP port and does not conflict with any previous TCP port definitions such as the metadata server. The multicast group communication is intended to be used only within your data center environment. Many sites keep their data center network separated from end users via a firewall that will automatically isolate the multicast protocol. Alternatively, the time to live (TTL) parameter can be used to restrict the scope of multicast communication. Your network administrator can suggest a TTL setting to limit the scope of the multicast. The TTL option and the authentication token option both have security implications.

The multicast TTL property (default = 1) affects the number of network hops a multicast packet will take before being dropped. This TTL value must be greater than or equal to the largest number of hops between any two servers containing SAS products. In addition, some network router documentation recommends that multicast datagrams with initial TTL=0 are restricted to the same host, multicast datagrams with initial TTL=1 are restricted to the same subnet, and multicast datagrams with initial TTL=32 are restricted to the same site. Consult your network router documentation or your network administration staff to determine the correct values for your environment.

Note: You must make sure that all of the machines in your SAS 9.2 deployment are members of the same subnet, or be sure to set the default TTL value to a number higher than 1. The deployment wizard gives you the opportunity to set the TTL value during SAS 9.2 deployment. For information about how to change these options after deployment, see "Administering Multicast Options" in the SAS Intelligence Platform: Web Application Administration Guide. \triangle

Because the multicast protocol conveys credentials, it is protected via encryption. By default, group communication is protected only with a fixed encryption key that is built into the software. If your middle-tier is not running in an environment that is well-isolated from end-user access, then you might want better protection against eavesdroppers and unauthorized group participants. For such situations, choose a multicast authentication token known only to your SAS middle-tier administrative staff. The authentication token is a password-like string needed to connect to the group and create a site-specific encryption key.

The deployment wizard default simplifies configuration using the authentication token that is built into the software. This option is best used in development and other low-security environments. It might also be appropriate in higher-security environments where the multicast group communication is isolated from the end-user community, either via firewall or TTL option, and where all data center administrative and operations staff have sufficient security approval. If your multicast group communication is not contained within an isolated data center environment, or if the security procedures at your site require protections among administrative and operational staff in various roles, you should specify an authentication token that is known only to the administrators of the SAS environment. The same token string must be supplied on each tier in the configuration.

By default, there is a code level authentication token shared between all SAS middle-tier applications to prevent access to the multicast group from unauthorized listeners. If you choose to use a customized authentication token, use the deployment wizard to enter an authentication token value that meets your organization's security guidelines. The authentication token can be any password-like string. In a multi-tier configuration, this prompt appears on each tier that has an application participating in the SAS multicast groups. You must provide the same authentication token string to each tier in the same SAS deployment (that is, each tier associated with the same metadata server).

For more information about configuring Web application servers to use with SAS 9.2, go to the Third-Party Software Downloads site at http://support.sas.com/ resources/thirdpartysupport/v92 and search for the product name of your Web application server.

Pre-installation Checklist for Ports for SAS

The following checklist indicates what ports are used for SAS by default, and gives you a place to enter the port numbers that you will actually use.

Note: The SAS Deployment Wizard prompts you for this information, and you cannot complete the installation without it. \triangle

On UNIX and z/OS, we recommend that you document each SAS port that you reserve in the following standard locations on each machine:

- UNIX—/etc/services
- □ z/OS—your TCP/IP PROFILE data set

This practice will help to avoid port conflicts on the affected machines.

On z/OS, the SAS servers are configured and initially started as TSO processes invoked from the USS shell using /bin/tso. When these servers are started under tso, the job name is the user ID that is starting the server with a character appended to the end. If your site makes use of the reserved ports facility in TCP/IP, each port definition should include the started task and this SAS installer ID job name as valid users of this port. You can use an asterisk (such as, sas*) in this definition.

On all operating systems, the last digit of the default port number reflects the configuration level that you select in the SAS Deployment Wizard. For example, when you select **Lev1**, the default port for the metadata server is 8561. If you choose another level, such as **Lev2**, the wizard changes the default port to 8562.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. If you are a SAS solutions customer, consult the pre-installation checklist provided by your SAS representative for a complete list of ports that you must designate. \triangle

Table 2.13 Pre-installation Checklist for Ports (SAS)

Server or Spawner	Default Port	Data Actual Direction Port
E-mail server	25	Outbound
HTTP server	80	Inbound
		and
HTTP server (secure port)	443	Inbound
iiiii server (secure port)	110	and
		outbound
SAS Table Server	2171	Inbound
SAS Remote Services application	5091	Inbound
SAS OLAP Server	5451	Inbound
Event Broker administration	6051	Inbound
	0001	Insound
SAS/CONNECT server and snawner	7551	Inbound
	1001	and
		outbound
Web Report Studio IP Scheduling UDP Port 1	7570	Inbound
		and
Web Report Studio IP Scheduling UDP Port 2	7571	Inbound
web heport Studio II Scheduning ODI 10172	1011	and
		outbound
Web Report Studio IP Scheduling UDP Port 3	7572	Inbound
		and
Event Broker HTTP	8111	Inhound
	0111	Insound
Operating System Services scheduler	8451	Inbound
operating offerent controls constants	0101	11100 0110
SAS/SHARE server	8551	Inbound
Multicast (UDP nort)	8561	Inbound
	0001	and
		outbound
SAS Metadata Server	8561	Inbound
		ana
SAS object spawner: operator port	8581	Inbound
openator operator pero	555 1	

	Default	Data Actual
Server or Spawner	Port	Direction Port
SAS Workspace Server	8591	Inbound
Metadata utilities SAS Workspace Server ¹	8591	Inbound
SAS Stored Process Server: bridge connection	8601	Inbound
SAS Stored Process Server: load balancing connection 1 (MultiBridge)	8611	Inbound
SAS Stored Process Server: load balancing connection 2 (MultiBridge)	8621	Inbound
SAS Stored Process Server: load balancing connection 3 (MultiBridge)	8631	Inbound
SAS Pooled Workspace Server	8701	Inbound
SAS object spawner: pooled workspace server port bank 1	8801	Inbound
SAS object spawner: pooled workspace server port bank 2	8811	Inbound
SAS object spawner: pooled workspace server port bank 3	8821	Inbound
SAS Deployment Tester server	10021	Inbound

1 In SAS 9.2, two or more workspace servers can share the same port even if they are running at the same time.

CHAPTER 3

Creating a SAS Software Depot

Overview of SAS Software Depots 25 About SAS Software Depots 25 Benefits of a SAS Software Depot 27 Best Practices for SAS Software Depots 29 Creating SAS Software Depots 29 Overview of Creating SAS Software Depots 29 Prerequisites for Creating a SAS Software Depot 30 Create a Depot by Using the SAS Download Manager 30 Create a Depot by Using the SAS Deployment Wizard 40 Managing SAS Orders 46 Overview of Managing SAS Orders 46 Change Order Details 46 Delete an Order 48 Create a Disc Image of Your Order 50

Overview of SAS Software Depots

One prerequisite for deploying SAS is to create a special file system of SAS product and order data—a SAS Software Depot—that the SAS Deployment Wizard then uses to install and configure SAS.

Creating a SAS Software Depot is the third of five steps required to install and configure the SAS Intelligence Platform:

- 1. Review additional documentation.
- 2. Create operating system users and groups and designate ports.
- ▶ 3. Create a SAS Software Depot.
 - 4. Install required third-party software.
 - 5. Install and configure SAS.

About SAS Software Depots

A SAS Software Depot is a file system that consists of a collection of SAS installation files that represents one or more orders. The depot is organized in a specific format that is meaningful to the SAS Deployment Wizard, which is the tool that is used to install and initially configure SAS. The depot contains the SAS Deployment Wizard executable, one or more deployment plans, a SAS installation data file, order data, and product data.

Figure 3.1 SAS Software Depot File Structure

😂 C:\SAS Software I)epot			_ 🗆 ×
<u> </u>	F <u>a</u> vorites	<u>T</u> ools	<u>H</u> elp	27
Address 🛅 C:\SAS S	ioftware Dep	oot	•	> 60
Folders				×
⇒ SAS Sol ⇒ inst ⇒ med ⇒ c→ ord ⇒ c→ plar ⊕ c→ pro ⊕ c→ pro c→ sid_ c→ thir	tware Depo all_doc dia_data er_data n_files duct_data ducts files d_party			

Before you can install SAS, you must first have a software depot to install from. During a SAS software download, the SAS Download Manager downloads your order, verifies it, and automatically creates a SAS Software Depot. If you receive your SAS order in the form of physical media, then you create a depot using the SAS Deployment Wizard.



Figure 3.2 Methods for SAS Software Depot Creation

Benefits of a SAS Software Depot

The main advantage of a SAS Software Depot is that it resides on the network at a location that you can share access to. Thus it provides a faster and more reliable means of installation compared to traditional removable media (cartridges, CDs, DVDs, and so on).



Figure 3.3 Shared SAS Software Depot Model

If you have remote sites running SAS without access to the network on which your depot resides, you can use the SAS Deployment Wizard to create your own SAS media image to write to the removable media of your choice.

Here are some other benefits of using a SAS Software Depot:

 $\hfill\square$ centralizes SAS orders.

The depot enables you to place multiple SAS orders in one location to simplify initial SAS deployment and future maintenance.

□ makes applying maintenance and upgrades easier.

You only need to download the changed depot files instead of having to download an entire SAS order.

 \Box saves disk space.

Storing multiple orders in a single depot saves disk space, as any content shared between orders is not duplicated, but rather shared, in the depot.

A single depot in SAS 9.2 can store SAS software installation files for more than one operating system, making the single, multi-system SAS 9.2 depot cumulatively smaller than the multiple, single-system depots in SAS 9.1.3.

 \Box saves download time.

Because there is a shared copy of common files, the SAS 9.2 single, multi-operating system depot requires smaller amounts to download.

□ organizes license keys (also known as SAS installation data files).

The depot enables you to place SAS installation data files in a standard location to better associate license keys with their corresponding orders. (These files are stored in the **sid files** directory, directly under the depot's root.)

 \Box identifies multiple orders.

The depot supports the SAS Deployment Wizard's feature that enables you to customize order descriptions and enter notes to better identify multiple orders residing in a single depot.
Because depots contain your personal SAS software order, it is important to use the following best practices for securing and backing up your depot.

Best Practices for SAS Software Depots

For customers who download SAS, their SAS Software Depot is the only copy of their SAS order. The depot contains the files from which SAS is initially installed. For this reason, it is important to use these best practices when managing your depot:

 \Box Keep your depot.

When you keep your SAS 9.2 depot, applying maintenance and upgrades becomes easier because you only need to download the changed depot files instead of having to download an entire SAS order.

 \Box Perform routine backups.

As with your SAS production system, it is important to routinely back up your SAS Software Depot and verify the integrity of these backups.

Note: Another important reason for securing and backing up your SAS Software Depot is that there are limits on the number of times that you can download your order from SAS. \triangle

 \Box Secure the depot location.

Problems such as data loss, virus infection, and file corruption can compromise your investment in SAS. It is thus imperative that you have a comprehensive security policy in place to protect your depot.

□ Store SAS installation data files with your depot.

The SAS installation data file for your orders contains information that is integral to successfully deploying SAS. As you get these data files from SAS—such as the file that contains your permanent SAS license key—it is important that you store them with your depot in the **sid files** directory.

CAUTION:

If you do not use the installation data file that supports the products you are planning to install and configure on this machine, you might experience errors later when you are trying to use the products. \triangle

□ Create a depot administrator.

Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. Separating depot administration from routine depot usage is a best practice that will further protect your SAS Software Depot.

Creating SAS Software Depots

Overview of Creating SAS Software Depots

There are two ways you can create a SAS Software Depot:

 $\hfill\square$ Download SAS software.

When you download a SAS order, the SAS Download Manager automatically creates a SAS Software Depot on your system.

 \Box Run the SAS Deployment Wizard.

Creating SAS Software Depots is an option on one of the wizard pages.

Before creating a depot, make sure that you have met the necessary requirements described in the following section.

Prerequisites for Creating a SAS Software Depot

Before you start creating a SAS Software Depot, make sure that you have met the following prerequisites:

- \Box Choose a machine that has the following:
 - \Box Internet access:

If you are downloading your SAS order, you will need a machine that can access the SAS download Web site. Also, ideally this machine should be networked so that you can perform deployments directly from the machine, without having to physically relocate the depot to another machine.

 \Box Java SDK for z/OS installed (z/OS only):

For more information, go to http://support.sas.com/ thirdpartysupport.

 \square a Windowing environment:

If you will be creating the depot on a UNIX or a z/OS system, make sure that a windowing environment—such as the Common Desktop Environment or X11—is installed. The program that you use to create the depot has a graphical user interface.

□ Designate a target directory.

Decide where you will create the SAS Software Depot. It is helpful if this directory can be shared on a network and accessible to all of the machines on which you will be installing software from the depot.

Note: SAS recommends that you not copy a depot from one location to another. Choose a permanent location before you create the depot. \triangle

□ Grant required access permissions.

The SAS installer user must have Write access on the depot target directory.

Windows Vista and later requires that you run the SAS Download Manager installation program using administrator privileges.

□ Check disk space requirements.

Make sure you have enough free disk space available on the target directory.

Finally, just before creating a depot, the SAS Deployment Wizard and the SAS Download Manager both present you with an estimate for required disk space.

Create a Depot by Using the SAS Download Manager

A SAS Software Depot contains SAS order data, an initial SAS installation data file, one or more deployment plan files, order data, and product data. The depot also contains the SAS Deployment Wizard executable—the tool required to install and initially configure SAS. *Note:* There is no expiration date for downloading your SAS order. However, if the time period for your initial SAS installation data file has expired, you will have to obtain a current SAS installation data file before you can run the SAS Deployment Wizard. \triangle

Before you can create a depot by using the SAS Download Manager, you must first download and install the manager itself. The installer automatically launches the SAS Download Manager after installing it. Therefore, the following procedure actually consists of three logical sections:

- 1 downloading the SAS Download Manager
- 2 installing the SAS Download Manager
- **3** downloading a SAS order and creating a software depot using the SAS Download Manager

Although these sections flow one after the other, at the end of each section, you can stop and resume the process later.

Follow these steps to download a SAS software order and automatically create a depot by using the SAS Download Manager:

1 Locate your software order e-mail sent by SAS. In this e-mail, find the URL for the SAS Web site from where you will download the SAS Download Manager.

Note: It is very important that you locate your original software order e-mail for the correct order and SAS installation key to download the software. You *cannot* use a renewal order number. The renewal order is a license update and it cannot be used to download software. If you cannot locate your original software order e-mail, contact your SAS Installation Representative or SAS Contracts at the following URLs:

```
http://support.sas.com/adminservices/contact.html
http://support.sas.com/adminservices/sasrep.html
http://support.sas.com/techsup/license \triangle
```

- **2** Ensure that you have fulfilled the necessary requirements described in "Prerequisites for Creating a SAS Software Depot" on page 30.
- **3** Log on to the machine as a SAS Software Depot administrator or a user with depot Read, Write, and Execute privileges.

Note: Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. Windows Vista and later requires that you run the SAS Download Manager installation program using administrator privileges. \triangle

- 4 Launch a Web browser and navigate to the URL specified in your software order e-mail.
- 5 At the prompt in the dialog box, select Save it to disk.

🖗 Opening Setup_Solaris_Sparc				
The file "Setup_Solaris_Sparc" is of type application/force-download, and Web Browser does not know how to handle this file type. This file is located at: http://image1.example.com				
What should Web Browser do with this file?				
Open it with		<u>C</u> hoose		
• Save it to disk				
$\hfill\square$ Always perform this action when handling files of this	type			
	ОК	Cancel		

6 Choose a path accessible to the machine to save the download and click Save.

🎉 Enter name of file to save to			×
Look in: /export/home/sas			- 💈 🔯 💈
Name	✓ Size	Last Modified	ra
Setup_Solaris_Sparc	73209856	10/12/07 11:21:51	
local.cshrc	136	08/23/07 13:42:15	
local.login	157	08/23/07 13:42:15	
local.profile	174	08/23/07 13:42:15	
File <u>n</u> ame: Setup_Solaris_	Sparc		
Files of type: All Files (*)			•
[□] Show hidden files and dire	ctories	Save	Cancel

Your download begins.

🐹 Download Manager							_ [] >	1
Propert <u>i</u> es	<u>Cancel</u> <u>R</u> emove fr	om List	Show <u>F</u> ile Loc	ation				
Name		Progres	s	Δ.	Time Left	Transfe	Speed 🛛	1
Setup_Solar	ris_Sparc	11111			Unknown	64800KB	20636.1K	
/export/hom	ne/sas/Setup_Solaris	_Sparc						Ī

- 7 When your browser has finished downloading the SAS Download Manager, you can install it. Perform the step appropriate for your operating system:
 - \Box Windows:

In Windows Explorer, navigate to the download path and double-click the download's filename. For example, on Windows machines: **esdclient.exe**.

Note: Windows Vista and later requires that you run the SAS Download Manager installation program using administrator privileges. Right-click esdclient.exe, select **Run as administrator**. A standard user account requires administrative credentials. \triangle

□ UNIX and z/OS:

In a console, navigate to the download path and type the download's filename. On 64-bit enabled Solaris, for example: **./Setup_Solaris_Sparc**.

Note: Remember to assign execute permissions before running the downloaded file. For more information, refer to your UNIX or z/OS documentation. \triangle



You should see the SAS Download Manager installer welcome page.

8 Choose a path where you want to install the SAS Download Manager.

Note: If you are reinstalling the download manager to a different location, you must uninstall the existing download manager. (On Windows, use Add and Remove Programs. On UNIX, use the uninstall program *install-directory*/__uninstESD/UninstESD, which SAS supplies.) When you are upgrading to a newer version of the download manager, you do not need to uninstall first. However, you will not be prompted for an installation location. \triangle



- **9** Review the path and disk space requirements, and make one of the following choices:
 - □ Click **Next** to begin installing the SAS Download Manager in the target directory.
 - □ Click **Back** to navigate to earlier pages to change installation information previously entered.

□ Click **Cancel** to terminate the install session. Note that you will lose the information previously entered.

<u>§</u> Installer	
Installer	SAS Download Manager 1.43 will be installed in the following location: /export/home/sas/SAS/SASDownloadManager/1.4 with the following features: SAS Download Manager 1.43 for a total size: 205.5 MB
InstallShield	
	< Back Next > Cancel

The installation begins.

S. Installer		5W_0×
6636	Installing SAS Download Manager 1.43. Please wait	
J. 5005.	/export/home/sas/SAS/SASDownloadManager/1.4/jre/lib/charsets.jar	
THE POWER TO KNOW.	11%	
InstallShield		
	< Back Next >	Cancel

10 When you see a page similar to the following, the installation is complete. Click **Finish** to dismiss the installation program.



The installer automatically launches the SAS Download Manager.

Note: If you want to run the download manager at a later time, you can run it using the method appropriate for your operating system:

 \Box Windows:

```
Start ► Programs ► SAS ► SAS Download Manager 1.4
```

 \Box UNIX and z/OS:

installation-directory/SAS/SASDownloadManager/1.4/esdclient.sh&



11 Run the SAS Download Manager and choose the language in which the SAS Deployment Wizard will display messages and prompts.

Choose Language	5 W X
Select a language in which to view the SAS Download Manager.	
English	∇
OK	

12 At some sites, you might see the page that prompts for proxy information. If so, supply the necessary proxy server settings for the SAS Download Manager to access the Internet. If needed, contact your site's system administrator for help with these settings.

SAS Downloa	d Manager	SW_D×
HTTP Proxy Ir Specify you	nformation r HTTP proxy server and login information.	
Specify your HT provide login in	TTP proxy settings so that the SAS Download Manager can access the Internet. You m formation depending on your proxy server settings.	nay need to
Contact the ad	ministrator of this computer for assistance determining these settings.	
HTTP Server:		
Port:		
_Log in to p	roxy server	
User name:	sas	
Password:		
<u>H</u> elp	< Back	Cancel

13 When prompted, enter your order number and SAS installation key.

SAS Download Manager	<u> 5 W _ C ×</u>
Order Information Specify your order information.	PB
Order Number: 034526	
SAS Installation Key: - Paste From Clipboard	
Help < B:	ack Next > Cancel

14 Confirm the list of SAS offerings contained in your order. If you want, you can update the description for your order and include any notes to distinguish it from

other SAS orders. The SAS Deployment Wizard will display this order information during the SAS installation.

<u>§</u> SAS Downloa	d Manager	SW_D×
Specify Order Edit the des	Details cription and add notes for this order to aid with future tracking.	
You must insta Depot or addin with. You can o Depot.	I your software from a SAS Software Depot, and this is the first step in creating a SAS g software to one from media you have created. Review the contents of the order you reate a custom description and notes to differentiate this order from others in your SA	3 Software I are working AS Software
<u>O</u> rder number:	034526	
Description:	S64, EBI, EDI, EG, WLS	
No <u>t</u> es:		
Click to see the	e contents of your order that correspond with the SAS Products to Install below	
SAS <u>P</u> roducts t	o Install:	
1. SAS 2. Repo 3. SAS 4. SAS	Foundation rt Fonts for Clients Vdd-in for Microsoft Office 31 Dashboard	
Help	< <u>B</u> ack <u>N</u> ext >	Cancel

Note: At any time after the download, you can run the SAS Deployment Wizard to add or modify SAS order information details. For more information, see "Change Order Details" on page 46. \triangle

15 Specify a location where you want to download SAS and build the SAS Software Depot.

For more information, see "Prerequisites for Creating a SAS Software Depot" on page 30.

SAS Download Manager Specify SAS Software Depot Directory Specify the directory for your SAS Software Depot.	
SAS Software Depot Directory:	BIowse
Help	< Back Next > Cancel

16 If the directory you specify does not exist, the wizard prompts you. If you want it to create the directory for you, click **Yes**.



17 The SAS Download Manager has finished collecting order input. This is your last opportunity to change any information before downloading the SAS order and writing files to the target directory.

Make one of the following choices:

- □ Click **Download** to begin downloading the SAS order and writing files in the target directory.
- □ Click **Back** to navigate to earlier pages to change order information previously entered.
- □ Click **Cancel** to terminate the SAS Download Manager session. Note that you will lose the information previously entered.

Note: SAS tracks downloads and counts only a *complete* download toward your download limit. \triangle

SAS Download Manager			<u> 5 W _ D ×</u>
Final Review Confirm the following informatior	l.		
When you click Download, the SAS D Internet and add it to the specified S/	ownload Manager will start down AS Software Depot.	loading the requested softwa	are from the
You are creating a new SAS Softwar	e Depot.		
SAS Software Depot location: Order number: Order description: Disk space available (GBs): Disk space required (GBs): Number of files to be downloaded:	/export/home/sas/sas_92_depo 034526 S64, EBI, EDI, MYSQL, SNA, WB 35.7 18.4 347	t A, WLS	
Print			
Help		< Back Download	Cancel

The SAS Download Manager begins downloading, uncompressing, and creating a depot of your SAS order.

SAS Download Manager	5 W _ 🗆 🗙
Download in Progress Software download in progress.	
To stop downloading software, select the Stop Download Process button. You will be able to resul downloading process the next time you start the SAS Download Manager.	me the
3%	
Estimated time remaining: 28 minutes, 19 seconds	
Download Status Downloaded: 693.7 of 18,369.3 MB Rate: 11.8 MB/sec Control Control Con	В
[13:09:43]:Finished extraction on file 118 [13:09:49]:Finished download of file 119. [13:09:49]: Starting extraction on file 119 of 347 files [13:09:49]: Starting download of file 120 of 347 files [13:09:50]:Finished extraction on file 119 [13:09:53]:Finished download of file 120. [13:09:53]: Starting extraction on file 120 of 347 files [13:09:53]: Starting extraction on file 120 of 347 files [13:09:54]:Finished extraction on file 120 of 347 files [13:09:54]:Finished extraction on file 121 of 347 files	
Help Stop Download Process	Cancel

When you see a page similar to the following with the progress indicator at 100%, the SAS Download Manager is finished:

💁 SAS Download Manager	
Download Complete Software download is complete.	80
The software has been successfully downloaded. The deployment.	e next wizard dialog provides details to continue with your
	100%
Total time: 25 minutes, 17 seconds Download Status Downloaded: 18,369.3 of 18,369.3 MB	File Extraction Status Extracted: 18,830.1 of 18,830.1 MB
Rate: 0.0 KB/sec	Rate: 0.0 KB/sec
[13:35:04]:Finished download of file 348. [13:35:04]: Starting extraction on file 346 of 347 files [13:35:04]:Finished extraction on file 346 [13:35:05]: Starting download of file 347 of 347 files [13:35:05]:Finished download of file 347 of 347 files [13:35:05]:Finished download of file 347 of 347 files [13:35:05]: Starting extraction on file 347 of 347 files [13:35:05]:Finished download of file 347. [13:35:05]:Finished straction on file 347 of 347 files [13:35:05]:Finished straction on file 347. [13:35:05]:Finished straction on file 347. [13:35:05]:Finished straction on file 347. [13:35:05]: Finished	
Help	< <u>Back</u> Cancel

18 Click Next to go to the final page, which describes post-download instructions.

🕥 SAS Download Manager	5 W _ 🗆 🗙
Download Complete Software download is complete.	
You can print these instructions using the Print button below.	
You have successfully added order 034526 (S64, EBI, EDI, MYSQL, SNA, WBA, WLS) to your SAS from which you should run the SAS Deployment Wizard to deploy your software.	Software Depot,
The following index page provides summary and QuickStart information for all the SAS Software of Software Depot: <u>/tmp/depot/depot/summary.html</u>	Orders in the SAS
To launch the SAS Deployment Wizard from your SAS Software Depot, go to the location listed be of the following commands based on the operating system you are currently running.	low and use one
SAS Software Depot Location: /export/home/sas/sas_92_depot	
Windows: setup.exe	
UNIX: setup.sh	
OpenVMS: setup_vms.exe	
The process of downloading your software from SAS should not be used as a mechanism for dis software across your organization. Instead, users should install from the SAS software depot in a your licensed number of users or copies.	tributing your ccordance with
Print	
<u>Help</u>	Cancel

19 Click Finish to close the SAS Download Manager.

20 To continue with the software installation, proceed to Chapter 4, "Installing Third-Party Products," on page 53.

After you finish your SAS 9.2 deployment, be sure to keep your depot, as this will make applying maintenance and future upgrades easier.

Create a Depot by Using the SAS Deployment Wizard

You can use the SAS Deployment Wizard to create a copy of your SAS Software Depot in another directory. If the new depot location is a remote directory on another machine, the directory must be on a shared network drive accessible from the machine running the wizard.

To create a depot on a machine that does not have shared network storage, you must use another mechanism such as SFTP or SCP to copy the depot. (For more information about these programs, refer to your operating system documentation.)

To create a SAS Software Depot by using the SAS Deployment Wizard, follow these steps:

1 Log on to the machine that will contain the depot as a SAS Software Depot administrator or a user with depot Read, Write, and Execute privileges.

Note: Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. \triangle

- 2 Ensure that you have fulfilled the necessary requirements described in "Prerequisites for Creating a SAS Software Depot" on page 30.
- 3 Start the SAS Deployment Wizard, using one of two methods:

□ If you are starting the wizard from removable media, proceed as follows, depending on your operating system:

```
\Box Windows:
```

The **setup.exe** program starts automatically when the media is inserted into the drive.

Note: If the SAS Deployment Wizard does not start automatically, open Windows Explorer, navigate to the root of the DVD, and double-click <code>setup.exe</code>. \triangle

 \Box UNIX:

Navigate to the media's root directory, and type **./setup.sh** at a command prompt.

```
\Box z/OS:
```

Navigate to the media's root directory, and type **./setup.rexx** at a command prompt.

□ If you are starting the wizard from an existing SAS Software Depot, proceed as follows:

Navigate to the depot's root directory and do one of the following, depending on your operating system:

- \Box Windows:
 - Double-click setup.exe.

```
\Box UNIX:
```

Type ./setup.sh at a command prompt.

```
\Box z/OS:
```

Type ./setup.rexx at a command prompt.

- 4 Choose the language in which the SAS Deployment Wizard will display messages and prompts.
- 5 Select Create a New SAS Software Depot. Do not select Install SAS Software.

SAS Deployment Wizard	_ 🗆 ×	
Select Deployment Task Select the deployment task you would like to perform.		
End User Tasks		
🔿 Install SAS software		
Choose this option to install SAS software on this machine.		
Administrator Tasks		
O Manage this SAS Software Depot		
Choose this option to manage this SAS Software Depot. You can view	and remove SAS software orders with this option.	
Create a new SAS Software Depot		
Choose this option to create a new SAS Software Depot from this SAS Software Depot.		
Help	< Back Next > Cancel	

6 Confirm the list of SAS offerings contained in your order.

If you want, you can update the description for your order and include any notes to distinguish it from other SAS orders. The SAS Deployment Wizard will display this order information during the SAS installation.

SAS Deployment Wizard	
Specify Order Details Edit the description and add notes for this order to aid with future tracking.	
Review the contents of the order you are working with. You can create a custom description and notes to differentiate this o from others in your SAS Software Depot.	rder
Order number: 012265	
Description: EBI+Platform Suite for SAS	
Notes:	4
Click to see the contents of your order that correspond with the SAS Products to Install below. SAS Products to Install:	
SAS Foundation Report Fonts for Clients SAS Add-in for Microsoft Office SAS BI Dashboard SAS BI Dashboard Help and Documentation SAS BI Dashboard Services SAS BI Web Services for .NET	
Help Cancel	

Note: At any time after the download, you can rerun the SAS Deployment Wizard to add or modify SAS order information details. For more information, see "Change Order Details" on page 46. \triangle

- 7 If you have multiple orders in your depot, you must pick the order for which you want to create a new depot.
- 8 Specify a location where you want to download SAS and build the software depot. (This location can be shared storage that physically resides on another machine.)

For more information, see "Prerequisites for Creating a SAS Software Depot" on page 30.



9 If the directory you specify does not exist, the wizard prompts you. If you want it to create the directory for you, click **Yes**.



10 The SAS Deployment Wizard has finished collecting order input. This is your last opportunity to change any information you have provided before the wizard begins writing files to the target directory.

Make one of the following choices:

- □ Click **Start** to begin creating the depot in the target directory.
- □ Click **Back** to navigate to earlier wizard pages to change order information previously entered.
- □ Click **Cancel** to terminate the wizard session. Note that you will lose order information previously entered.

SAS Deployment Wizard		
Final Review Confirm the following inform	stion.	
When you click Start, the SAS D	ployment Wizard will begin adding this SAS Software Order to the specified locat	ion.
This SAS Software Order will be	added to the new SAS Software Depot.	
SAS Software Depot location: Order number: Order description: Disk space available (GBs): Disk space required (GBs):	C:\SA5 Software Depot 012265 EBI+Platform Suite for SA5 85.9 13.8	
Print		
Нер	< Back Start	Cancel

11 If you are running the SAS Deployment Wizard from removable media, the SAS Deployment Wizard prompts you for a DVD. Continue to supply discs as prompted.

Note: If you are working on a UNIX system without an automounter, mount the DVD drive. For information about the privileges required to mount a device and the syntax of the **mount** command for your system, see the SAS Deployment Wizard User's Guide, which is available on the Install Center:

```
http://support.sas.com/documentation/installcenter/. (Search for SAS Deployment Wizard User's Guide.) \triangle
```

The SAS Deployment Wizard begins creating a depot of your SAS order.

🛐 SAS Download Manager	<u>sw_ox</u>
Download in Progress Software download in progress.	
To stop downloading software, select the Stop Download Process button. You will be able to resu downloading process the next time you start the SAS Download Manager.	me the
3%	
Estimated time remaining: 28 minutes, 19 seconds	
Download Status Downloaded: 693.7 of 18,369.3 MB Rate: 11.8 MB/sec File Extraction Status Extracted: 713.3 of 18,839.7 M Rate: 0.0 KB/sec	В
[13:09:43]:Finished extraction on file 118 [13:09:49]:Finished download of file 119. [13:09:49]: Starting extraction on file 119 of 347 files [13:09:49]: Starting extraction on file 110 of 347 files [13:09:40]: Starting extraction on file 120 of 347 files [13:09:50]:Finished extraction on file 120 [13:09:53]: -Finished download of file 120. [13:09:53]: Starting extraction on file 120 of 347 files [13:09:53]: Starting download of file 120. [13:09:53]: Starting download of file 121 of 347 files [13:09:54]:Finished extraction on file 120 of 347 files [13:09:54]:Finished extraction on file 120 of 347 files [13:09:54]:Finished extraction on file 120 of 347 files	
Help	Cancel

12 When you see a page similar to the following with the progress indicator at 100%, the SAS Deployment Wizard is finished:

SAS Download Manager	5W_0×
Download Complete Software download is complete.	
The software has been successfully downloaded. The next wizard dialog provides details to con deployment.	tinue with your
100%	
Total time: 25 minutes, 17 seconds Download Status Downloaded: 18,369.3 of 18,369.3 MB Rate: 0.0 KB/sec File Extracted: 18,830.1 of 18,830 Rate: 0.0 KB/sec [13:35:04]: -Finished download of file 346. [13:35:04]: Starting extraction on file 346 of 347 files [13:35:04]: Starting extraction on file 346 [13:35:04]: Starting extraction on file 347 of 347 files [13:35:05]: Starting extraction on file 347 of 347 files [13:35:05]: Starting extraction on file 347 of 347 files [13:35:06]: -Finished extraction on file 347 [13:35:06]: Starting extraction on file 347 [13:35:06]: Starting extraction on file 347 [13:35:06]: Starting extraction on file 347 [13:35:06]: Finished extraction on file 347 [13:35:06]: Starting extraction on file 347 [13:35:06]: Finished extraction on file 347 [13:35:06]: Starting extraction on file 347 [13:35:06]: Finished extraction on file 347).1 MB
Help Sack Next >	Cancel

- 13 Click Next to go to the final page, which contains instructions for what to do after creation of the software depot.
- 14 Click the depotsummary.html link on the page to review the SAS QuickStart Guide.

SAS Download Manager	5 W _ D ×
Download Complete Software download is complete.	00
You can print these instructions using the Print button below.	
You have successfully added order 034526 (S64, EBI, EDI, MYSQL, SNA, WBA, WLS) to from which you should run the SAS Deployment Wizard to deploy your software.	your SAS Software Depot,
The following index page provides summary and QuickStart information for all the SAS S Software Depot: <u>/tmp/depot/depotsummary.html</u>	oftware Orders in the SAS
To launch the SAS Deployment Wizard from your SAS Software Depot, go to the location of the following commands based on the operating system you are currently running.	listed below and use one
SAS Software Depot Location: /tmp/depot	
Windows: setup.exe UNIX: setup.sh	
OpenVMS:setup_vms.exe z/OS: setup.rexx	
The process of downloading your software from SAS should not be used as a mechanis software across your organization. Instead, users should install from the SAS software o your licensed number of users or copies.	sm for distributing your Jepot in accordance with
Print	
Help < Back	Finish Cancel

- 15 Click Finish to close the SAS Deployment Wizard.
- 16 If you are using removable media on a UNIX system where an automounter is being used, use the eject command to remove the DVD. On a UNIX system without an automounter, you must unmount the drive by using the umount command and then manually opening the drive. For information about the umount command that is needed to unmount a device on your system, see the SAS Deployment Wizard User's Guide, which is available on the Install Center: http://support.sas.com/documentation/installcenter/. (Search for SAS Deployment Wizard User's Guide.)
- 17 To continue with the software installation, proceed to Chapter 4, "Installing Third-Party Products," on page 53.

After you finish your SAS 9.2 deployment, be sure to keep your depot, as this will make applying maintenance and future upgrades easier.

Managing SAS Orders

Overview of Managing SAS Orders

Using the SAS Deployment Wizard, you can do the following with your SAS order:

- \Box change order details
- \Box delete an order
- □ create an image of your order to write to CDs or DVDs

Change Order Details

Being able to identify a SAS order is important, especially when your SAS Software Depot contains multiple orders. To change the details of a SAS order, follow these steps:

1 Log on to the depot machine as a SAS Software Depot administrator or a user with depot Read, Write, and Execute privileges.

Note: Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. \triangle

- 2 Start the SAS Deployment Wizard. Navigate to the SAS Software Depot's root directory and, depending on your operating system, do the following:
 - \square Windows:

Double-click setup.exe.

 \Box UNIX:

Type ./setup.sh at a command prompt.

 \Box z/OS:

Type ./setup.rexx at a command prompt.

- **3** Choose the language in which the SAS Deployment Wizard will display messages and prompts.
- 4 Select Manage this SAS Software Depot.

SAS Deployment Wizard		
Select Deployment Task Select the deployment task you would like to perform.		
End User Tasks		
🔿 Install SAS software		
Choose this option to install SAS software on this machine.		
Administrator Tasks		
Manage this SAS Software Depot		
Choose this option to manage this SAS Software Depot. You can view a	and remove SAS software orders with this option.	
C Create a new SAS Software Depot		
Choose this option to create a new SAS Software Depot from this SAS Software Depot.		
Help	<back next=""> Cancel</back>	

5 Choose the order for which you want to change details, and then select Change Details.

<u> S</u> AS Deployr	ment Wizard	
Manage SAS Review SAS administrativ	Software Depot Software Orders present in your SAS Software Depot and perform ve tasks.	
Select a SAS Sof	ftware Order:	
Order Number	Order Description	
010616	EBI+EDI+EG win32	
085794	EG	
Change Deta	asis for the selected SAS Software Order: alls Delete Order Create Media-Ready Image Install:	
Click to see the full contents of your selected order which includes the SAS products listed below. 1. SAS Foundation 2. Report Fonts for Clients 3. SAS Add-in for Microsoft Office 4. SAS BI Dashboard 5. SAS BI Dashboard Help and Documentation 6. SAS BI Report Services 7. SAS BI Web Services for .NET 8. SAS Client Connection Profile Configuration		
Help	< Back Finish Cancel	

6 Update the description for your order and include any notes about your order that might help you to distinguish it from any other SAS orders. The SAS Deployment Wizard will display this order information during the SAS installation.

Order Details X		
D <u>a</u> te Added:	Dec 10, 2008 4:14 PM	
Description:	EBI+EDI+EG win32	
<u>N</u> otes:		
	l	
	OK Cancel	

- 7 When you are finished adding order details, select OK.
- 8 Select Finish to close the SAS Deployment Wizard.

Delete an Order

To delete a SAS order, follow these steps:

CAUTION:

It is a best practice to always make sure that you have backed up the SAS Software Depot before deleting an order. Keep in mind that there are limits on the number of times you can download an order from SAS. \triangle

1 Log on to the depot machine as a SAS Software Depot administrator or a user with depot Read, Write, and Execute privileges.

Note: Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. \triangle

- 2 Start the SAS Deployment Wizard. Navigate to the SAS Software Depot's root directory, and, depending on your operating system, do the following:
 - \square Windows:
 - Double-click setup.exe.
 - \Box UNIX:

Type ./setup.sh at a command prompt.

 \Box z/OS:

Type ./setup.rexx at a command prompt.

- **3** Choose the language in which the SAS Deployment Wizard will display messages and prompts.
- 4 Select Manage this SAS Software Depot.

SAS Deployment Wizard		
Select Deployment Task Select the deployment task you would like to perform.		
End User Tasks		
🔿 Install SAS software		
Choose this option to install SAS software on this machine.		
Administrator Tasks		
Manage this SAS Software Depot		
Choose this option to manage this SAS Software Depot. You can view and remove SAS software orders with this option.		
C Create a new SAS Software Depot		
Choose this option to create a new SAS Software Depot from this SAS Software Depot.		
Help	< Back Next > Cancel	

5 Choose the order you want to delete, and then select **Delete Order**.

	rd .	AS Deployr
	Depot Irders present in your SAS Software Depot and perform	anage SAS Review SAS administrativ
	r:	ect a SAS Sof
	Order Description	rder Number
	EG win32	0616
		5794
		5 Products to
<u> </u>	ts of your selected order which includes the SAS products listed below.	<u>ick to see the</u>
		1. SAS I
	r Clients Aicrosoft Office	2. Repo
	rd	4. SAS
	rd Help and Documentation	5. SAS I
	ervices	
	vices for NET	6. SASI 7. SASI
	r Clients flicrosoft Office rd rd Help and Documentation ervices	1. SAS 2. Repo 3. SAS 4. SAS 5. SAS

 $\mathbf{6}$ Confirm that you want to delete the order by selecting $\mathbf{Yes}.$



The SAS Deployment Wizard begins to delete your order. When all the order's files have been removed, the Manage SAS Software Depot page appears again, without the deleted order listed.

7 Select Finish to close the SAS Deployment Wizard.

Create a Disc Image of Your Order

If you have SAS running on remote sites that don't have access to the network on which your SAS Software Depot resides, you can use the SAS Deployment Wizard to create an ISO image of your SAS software order. Then, using a media creation tool of your choice, you can write the image to the removable media format that you specify: either CDs or DVDs.

You can create a disc image on a per order basis only. If your SAS Software Depot consists of more than one order, then you have to make multiple disc images.

To create a disc image of your SAS order, follow these steps:

1 Log on to the depot machine as a SAS Software Depot administrator or a user with depot Read, Write, and Execute privileges.

Note: Consider designating one or a few users to serve as SAS Software Depot administrators. Persons needing to deploy SAS software or to apply future SAS software maintenance require depot Read and Execute privileges. Depot administration tasks such as initially creating the depot, storing SAS installation data files, and updating order details require depot Write privileges. \triangle

- 2 Start the SAS Deployment Wizard. Navigate to the SAS Software Depot's root directory, and, depending on your operating system, do the following:
 - \Box Windows:

Double-click setup.exe.

 \Box UNIX:

Type ./setup.sh at a command prompt.

 \Box z/OS:

Type ./setup.rexx at a command prompt.

- **3** Choose the language in which the SAS Deployment Wizard will display messages and prompts.
- 4 Select Manage this SAS Software Depot.

SAS Deployment Wizard	
Select Deployment Task Select the deployment task you would like to perform.	
End User Tasks	
🔿 Install SAS software	
Choose this option to install SAS software on this machine.	
Administrator Tasks	
Manage this SAS Software Depot	
Choose this option to manage this SAS Software Depot. You can view	v and remove SAS software orders with this option.
C Create a new SAS Software Depot	
Choose this option to create a new SAS Software Depot from this SAS	5 Software Depot.
Help	< Back Next > Cancel

5 Choose the order for which you want to create a disc image, and then select Create Media-Ready Image.

SAS Deployment Wizard	
Manage SAS Software Depot Review SAS Software Orders present in your SAS Software Depot and perform administrative tasks.	
Select a SAS Software Order:	
Order Number Order Description	
010616 EBI+EDI+EG win32	
085794 EG	
Administrative tasks for the selected SAS Software Order: Change Details Delete Order Create Media-Ready Image SAS Products to Install: Sas Products to Install:	
Click to see the full contents of your selected order which includes the SAS products listed below. 1. SAS Foundation 2. Report Fonts for Clients 3. SAS Add-in for Microsoft Office 4. SAS BI Dashboard 5. SAS BI Dashboard 5. SAS BI Report Services 7. SAS BI Web Services for .NET 8. SAS Client Connection Profile Configuration	*
<u>H</u> elp < <u>B</u> ack Fi <u>n</u> ish	Cancel

6 Choose the type of media (CDs or DVDs) for which you want to create an image of your SAS software order. Also, provide the path where you want the SAS Deployment Wizard to write this image. When you are ready, select Start.

Create Media-R	eady Image for 010616		X
<u>M</u> edia Type:	DVD-R SL	T	
Target Directory	C:\media		Browse
	0%		
0 bytes copied	Estimated time remain	ing:	
	<u>S</u> tart Cancel		

The SAS Deployment Wizard begins writing SAS order files to the target directory.

7 When the progress indicator displays 100%, the image is complete and you can select \mathbf{ok} .

Create Media-R	eady Image for 01	0616	×
Media Type:	DVD-R SL		-
Target Directory	; C:\media		Browse
		100%	
10,058,846,346	bytes copied	Total time: 19 minutes, 26 seconds	
		Cancel	

8 Select Finish to close the SAS Deployment Wizard.

The file system that the SAS Deployment Wizard has created is an ISO image of your SAS order that is logically arranged into directories that map to either CD-ROM or DVD disc. Each directory also contains a summary to enable you to maintain media labels.



9 Using a media creation tool of your choice, you can now write the installable image of your SAS order to the type of removable media that you specified earlier: either CDs or DVDs.



Installing Third-Party Products

Overview of Installing Third-Party Products 53 About Installing Third-Party Products 54 Review Web Application Server Configuration Documentation 55 Choose Whether to Automatically Configure Your Web Application Server 55 Choose Whether to Automatically Deploy the SAS Web Applications 56 Install Third-Party Products Using the SAS Software Depot 56 Install Third-Party Products Using the Software Web Site 57 Installing Platform Suite for SAS 58 What Is Platform Suite for SAS? 58 Where to Install Platform Suite for SAS 58 Install Platform Suite for SAS 58 Pre-installation Checklists for Third-Party Products 59 Java Development Kit (JDK) 59 JUNIT 59 WebLogic Server 59 WebSphere Application Server 60 JBoss Application Server 62 Platform Suite for SAS 63

Overview of Installing Third-Party Products

Third-party products play an important role in the SAS Intelligence Platform. For example, if your system includes Web applications such as SAS Web Report Studio or the SAS Information Delivery Portal, you will need to install third-party products such as a Java Development Kit (JDK) and a Web application server in order to compile and execute these applications.

Installing required third-party software is the fourth of five steps in deploying SAS:

- 1. Review additional documentation.
- 2. Create operating system users and groups and designate ports.
- 3. Create a SAS Software Depot.
- ▶ 4. Install required third-party software.
 - 5. Install and configure SAS.

About Installing Third-Party Products

The SAS desktop client applications and majority of Java applications are supported on Microsoft Windows systems only. The exception is SAS Management Console, which also runs on several UNIX platforms. All of the Java applications require the Java Runtime Environment (JRE), which includes a Java Virtual Machine (JVM) that executes the application and a set of standard Java class libraries. The SAS Deployment Wizard will install the default version of the JRE with which SAS has been tested. If a different version of the JRE is required, it can be obtained from the appropriate vendor's Web site. Links to the appropriate JRE vendor's Web site can be found on the SAS 9.2 third-party support site located at http://support.sas.com/ resources/thirdpartysupport/v92.

Note: Microsoft Windows 7 requires a different JRE, (version 1.6.0_14 or later), than what the SAS Deployment Wizard prompts for. If you are deploying on a Windows 7 machine, ensure that the machine has JRE 1.6.0_14 or later installed and that you use the SAS Deployment Wizard to point to the location where that JRE can be found. For more information on the SAS Baseline and Higher policy, please see http://support.sas.com/resources/thirdpartysupport/baseline_plus.html. \triangle

During a first-time SAS 9.2 deployment, the SAS Deployment Wizard prompts you for the version of the JRE that you want to use with the SAS Java applications. Your options are to have the deployment wizard install a JRE that SAS has certified to run with SAS 9.2, or to point to a JRE that you have already installed. (In most situations where you are updating or adding a product to SAS 9.2, the deployment wizard does not prompt you for a JRE. However, you can override this behavior. For more information, see "Specify a Different JRE" on page 140.)

On z/OS only, your options are to point to a JRE that you have already installed, or install your software without a JRE.

Before you can install and configure a SAS 9.2 middle tier, you must have installed one of the Web application servers supported by SAS. If you are using the JBoss Application Server or the WebLogic Server, then you must have the Java Development Kit (JDK) installed. (The WebSphere Application Server ships with its own version of the JDK which is installed when you install the WebSphere Application Server.) The SAS Deployment Wizard prompts you for paths to these third-party software products, and will not allow you to complete the SAS deployment without this software installed. The deployment wizard checks to make sure that the JDK version you have installed is supported by the Web application server that you are using.

Use the manufacturer's distribution package to install the JDK. Make sure that you have a properly defined Java environment. (On Windows, a reboot of the machine might be required.) Open a DOS command prompt on Windows, or a console on UNIX, and at the operating system prompt, type the following command to validate the Java environment and return the version information for the installed package: java -version.

Use the manufacturer's distribution package to install your Web application server, applying any necessary hotfixes and verifying the server's operation.

For more information about configuration steps for your Web application server, go to http://support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.

Review Web Application Server Configuration Documentation

SAS provides post-installation documentation that describes how to configure your Web application server. For example, some of the topics include information about how to run your Web application server on different ports, install SAS with one user account, install your Web application server with a different user account, and so on. For more information about configuration steps for your Web application server, go to http://support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.

Choose Whether to Automatically Configure Your Web Application Server

The SAS Deployment Wizard gives you the option of automatically building and configuring the SAS Web applications as well as configuring a Web application server for use with SAS 9.2. (To use this wizard feature, make sure that your Web application server is not running before you start the wizard. For WebSphere, it's necessary to stop all deployment manager servers, all node agent servers, and all application servers before running the wizard. The one exception is on z/OS, where the WebSphere Web application server should be running.)

When the SAS Deployment Wizard configures the SAS 9.2 middle tier, by default, it automatically creates and configures an instance of a Web application server to host the SAS Web applications. The wizard creates a series of configuration files that enable you to run an instance of your Web application server with the SAS Web applications. The automatic configuration feature and the automatic deployment feature (described later) provide the opportunity to enable the automatic configuration of your Web application server, but not deploy the applications if you prefer to review the configuration to ensure it meets your site's needs. You can then deploy the SAS Web applications afterward.

Some of the configuration tasks performed by the SAS Deployment Wizard include setting options such as the following:

- □ HTTP ports
- optimized JVM options
- \square a mail session
- □ JAAS login modules for SAS services
- \Box JMS queues
- \square a JDBC data source

Depending on the Web application server you are using, the SAS Deployment Wizard modifies your Web application server configuration differently:

WebLogic

makes no changes to the WebLogic installation directory. The deployment wizard creates a sample domain in the SAS configuration directory.

WebSphere

creates deployment manager and application server profiles in the WebSphere installation directory.

Note: On z/OS systems, the SAS Deployment Wizard cannot automatically create a server profile. You must do this manually. For more information, go to

<code>http://support.sas.com/resources/thirdpartysupport/v92</code> and search for "WebSphere". \triangle

Note: When installing SAS Enterprise BI server to use a WebSphere Base Server, make sure that you choose *not* to have the SAS Deployment Wizard automatically configure your Web application server. \triangle

JBoss

creates a Web application server instance in the JBoss installation directory. The deployment wizard adds a start-stop script to the JBoss bin directory. JAR files for the SAS Drivers for JDBC are copied to the JBoss lib directory.

If you choose to disable this feature during SAS Deployment Wizard execution, the wizard generates instructions that describe how to perform these configuration steps manually after you finish running the wizard.

To disable the auto configuration feature, run the wizard using either the Typical or Custom prompting levels. For more information, see "Interactive Prompting Levels" on page 69.

For samples of the instructions that describe how to manually configure your Web application server for SAS Web applications, go to the Third-Party Software Web site at http://support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.

Choose Whether to Automatically Deploy the SAS Web Applications

In addition to the automatic configuration feature, the SAS Deployment Wizard offers a feature to automatically start the Web application server and deploy the SAS Web applications. (This feature is turned on by default.)

Regardless of whether you choose to automatically deploy your SAS Web applications, when building Web applications, the wizard also automatically explodes Web application archive files (.ear files).

For more information, go to http://support.sas.com/resources/ thirdpartysupport/v92.

To disable the auto deployment feature, run the wizard using either the Typical or Custom prompting levels. For more information, see "Interactive Prompting Levels" on page 69.

Install Third-Party Products Using the SAS Software Depot

Some third-party products ship with SAS 9.2. Such products' installation files and documentation are located in the SAS Software Depot under the **third party** directory.



Figure 4.1 third_party Directory in the SAS Software Depot

Platform Suite for SAS is an example of one third-party application that you install in this way. To determine whether any of your third-party software is distributed with your order, refer to your SAS Software Summary that resides in your SAS Software Depot in your order_number directory under install doc. For example:

C:\SAS Software Depot\install doc\order_number\ordersummary.html

Install Third-Party Products Using the Software Web Site

SAS maintains a third-party software Web site to help you do the following:

- $\hfill\square$ determine what version of the product to install
- □ obtain the product, if you don't already have it
- \Box find installation instructions
- \Box learn about any patches required

Note: Some third-party software ships with your SAS order. For more information, see "Install Third-Party Products Using the SAS Software Depot" on page 56. If you are installing Platform Process Manager, Platform LSF, or Platform Grid Management Service, you must use the installation instructions and installation programs provided in your SAS order. For more information, see "Installing Platform Suite for SAS" on page 58. \triangle

To install the Java Development Kit or a Web application server, complete these steps:

1 Go to the Third-Party Software Web site at http://support.sas.com/ resources/thirdpartysupport/v92.

- 2 Select the link for the product (or type of product) that you are installing. There are columns that either have links directly to the vendor's site, or an indication that the third-party software ships with SAS.
- **3** Install the product.

For most installations, you can use the instructions provided by the vendor. For products that are more complex to install—such as the Web application servers—the Third-Party Software Web site contains links to brief installation instructions. These instructions are not meant to replace the vendor documentation. However, they will enable you to create a simple configuration that will work well with your SAS software.

Note to users in Russia: SAS cannot export the Java Runtime Environment (JRE) to Russia. You will need to locate the appropriate link on the Third-Party Software Web site and download the JRE. Install it in the default location, and it will be ready for use when you install your SAS software.

Installing Platform Suite for SAS

What Is Platform Suite for SAS?

If you will use products from Platform Computing Incorporated either for scheduling or for grid computing, you must install several of the products from the Platform Suite for SAS offering. Platform Suite for SAS includes three products:

Platform Process Manager

provides scheduling capabilities. Process Manager submits jobs to Platform LSF and manages dependencies between jobs.

Platform LSF (Load Sharing Facility)

manages resource requirements and provides for load balancing.

Platform Grid Management Service

includes a monitoring daemon that enables administrators to monitor the load on machines running Platform LSF.

Where to Install Platform Suite for SAS

If you are interested in using the Platform Suite for SAS to perform scheduling tasks for objects like SAS Data Integration Studio jobs or SAS Web Report Studio reports, then you must install Platform Process Manager on the machine that you want to use as your scheduling server. When you install Platform Process Manager, Platform LSF will be installed as well.

If you will be using the Platform Suite for SAS for grid computing, you must install Platform LSF and the Platform Grid Management Service. If you want to schedule jobs to run on the grid, you must install Platform Process Manager as well. For information about where to install each of these products, see "SAS Grid Topology" in *Grid Computing in SAS*.

Install Platform Suite for SAS

Platform Suite for SAS is distributed with SAS. You install these products directly from the SAS Software Depot, using the installation instructions and installation programs that reside in your depot under the **third_party** directory.

You can also find the Platform Suite for SAS installation instructions on the SAS Scalability and Performance focus area on the Web at http://support.sas.com/rnd/scalability/grid/gridinstall.html.

Pre-installation Checklists for Third-Party Products

As you install third-party products, print and fill out the appropriate third-party software checklists.

Note: You must have the necessary third-party software installed on the current machine, or the utility that you use to deploy SAS, the SAS Deployment Wizard, will not let you complete your SAS deployment. \triangle

Java Development Kit (JDK)

For more information about JDK version requirements, go to http:// support.sas.com/thirdpartysupport/ and locate "Other Third Party Software Products "under the applicable SAS release.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Iable 4.1 Java Developilielit K	Table 4.1	Java	Develo	pment	Kit
---------------------------------	-----------	------	--------	-------	-----

Description	Default Value	Actual Value	
Product version	Dependent on the Web application server and the operating system.		
	See http://support.sas.com/ thirdpartysupport/.		
Installation directory	Not applicable		

JUNIT

JUNIT is an open-source software testing framework for Java, and the defacto standard for writing unit and regression tests. Some of the tests shipped with SAS products run under the SAS Deployment Tester framework and require JUNIT. For more information about JUNIT version requirements, go to http://support.sas.com/ thirdpartysupport/ and locate "Other Third Party Software Products "under the applicable SAS release.

WebLogic Server

For more information about pre- and post-installation configuration steps for the Oracle WebLogic Server, go to http://support.sas.com/thirdpartysupport/ and locate "Web Application Servers and HTTP Servers" under the applicable SAS release.

To change the default port, you must use the SAS Deployment Wizard **Typical** or **Custom** prompting level. For more information, see the reference to selecting the configuration prompting level in "Install and Configure SAS Interactively" on page 87.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Table 4.2 Webl	oaic	Server
----------------	------	--------

Description	Default Value	Actual Value
Product version	9.2	
Installation directory	Not applicable	
Name of domain	SASDomain	
Name of managed servers	SASServer1, SASServer2, and so on	
WebLogic Nodemanager port	5556 (inbound and outbound)	
Non-secure listen port for managed servers	7001, 7101, (inbound and outbound) (additional managed servers increment by 100)	
Secure listen port for managed servers	7002, 7102, (inbound and outbound) (additional managed servers increment by 100)	
Listen port for administration server	7501 (inbound and outbound)	

WebSphere Application Server

For more information about pre- and post-installation configuration steps for the IBM WebSphere Application Server, go to http://support.sas.com/thirdpartysupport/ and locate "Web Application Servers and HTTP Servers" under the applicable SAS release. To change the default port, you must use the SAS Deployment Wizard Typical or Custom prompting level. For more information, see the reference to selecting the configuration prompting level in "Install and Configure SAS Interactively" on page 87.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Description	Default Value	Actual Value
Product version	7.0	
Name of application servers	SASServer1, SASServer2, and so on	
Profile name for managed nodes (contains node agent and Web application server)	SASlocal-hostname01, SASlocal-hostname02, and so on	
Node name for managed nodes	SAS <i>local-hostname</i> 01Node, SAS <i>local-hostname</i> 02Node, and so on	
Profile name for deployment manager	SASDmgr01 (on z/OS, DEFAULT)	
Cell name for deployment manager	SASDmgr01Cell	
Node name for deployment manager	SASDmgr01Node	
SOAP port for administrative console	8879 (inbound and outbound)	
SOAP ports for application servers	8880, 8881 (inbound and outbound) (additional application servers increment by one)	
Secure HTTPS port for administrative console	9043 (inbound)	
Secure HTTPS ports for application server	9044, 9045 (inbound) (additional application servers increment by one)	
Non-secure HTTP port for administrative console	9060 (inbound)	
Non-secure HTTP ports for application server	9080, 9081, (inbound) (additional application servers increment by one)	
RMI port for administrative console	9809 (inbound and outbound)	

Table 4.3 WebSphere Application Server

Description	Default Value	Actual Value
RMI ports for application servers	9811, 9812, (inbound and outbound) (additional application servers increment by one)	
WebSphere Portal Server (WPS) listening port	10040 (inbound and outbound)	

JBoss Application Server

For more information about pre- and post-installation configuration steps for the JBoss Application Server, go to http://support.sas.com/thirdpartysupport/ and locate "Web Application Servers and HTTP Servers" under the applicable SAS release. To change the default port, you must use the SAS Deployment Wizard Typical or Custom prompting level. For more information, see the reference to selecting the configuration prompting level in "Install and Configure SAS Interactively" on page 87.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Description	Default Value	Actual Value
Product version	4.3	
Name of managed servers	SASServer1, SASServer2, and so on	
RMI port for managed servers	1099, 1199, (inbound and outbound) (additional managed servers increment by 100)	
Listen port for managed servers	8080, 8180, (inbound and outbound) (additional managed servers increment by 100)	
Secure listen port for managed servers	8443, 8543, (inbound and outbound) (additional managed servers increment by 100)	

Table 4.4 JBoss Application Server

Platform Suite for SAS

For more information about Platform Suite for SAS version requirements, go to http://support.sas.com/thirdpartysupport/ and locate "Other Third Party Software Products "under the applicable SAS release.

Note: These checklists are superseded by more complete and up-to-date checklists that can be found at http://support.sas.com/installcenter/plans. This Web site also contains a corresponding deployment plan and an architectural diagram. \triangle

Description	Default Values	Actual Values
Platform Process Manager port	1966 (inbound)	
Product version	7.0	
Platform LSF ports	6878, 6881, 6882, 7869, 7870, 7871, 7872 (inbound)	
Product version	7.02	
Platform Grid Management Service port	1976 (inbound)	
Product version	7.0	

Table 4.5 Platform Suite for SAS
CHAPTER

Installing and Configuring Your SAS Software

Overview of Installing and Configuring Your SAS Software 65 Preparing to Install and to Configure 66 SAS Deployment Wizard Options 66 About Deployment Plans 66 Content Repository Considerations 67 Installation Order Rules for Multiple Machine Deployments 67 How the Deployment Wizard Names SAS Web Application Servers 67 IPv6 Windows Machines that Communicate with SAS Foundation Servers 68 Interactive Prompting Levels 69 Installing SAS OnlineDoc for the Web 75 Deploy SAS BI Lineage When LSF Scheduler Is on a Separate Machine from the Workspace Server 77 Installing SAS Web Parts for Microsoft SharePoint 82 What Is SAS Web Parts for Microsoft SharePoint? SAS Web Parts for Microsoft SharePoint Architecture 82 Automatically Deploy SAS Web Parts for Microsoft SharePoint 82 Manually Deploy SAS Web Parts for Microsoft SharePoint and Move It 85 Configure HTTPS Connections for SAS Web Parts for Microsoft SharePoint 86 Configure User Access for SAS Web Parts for Microsoft SharePoint 86 Install and Configure SAS Interactively 87 Validate the SAS 9.2 Servers 106 About SAS Deployment Tester 108 Automating the SAS Installation on Multiple Machines 109 Overview of Automating the SAS Installation on Multiple Machines 109 Recording a SAS Deployment Wizard Response File 109 Playing Back a SAS Deployment Wizard Response File 110 Overview of Playing Back a SAS Deployment Wizard Response File 110 Installing SAS in Quiet Mode 111 Managing a Machine Reboot During Playback (Windows) 112 Installing SAS in Partial Prompt Mode 112 Installing SAS in Full Prompt Mode 113 Verifying the Playback Install 114 Monitoring the SAS Deployment Wizard During Playback 114 More About Monitoring the SAS Deployment Wizard on UNIX and z/OS 115

Overview of Installing and Configuring Your SAS Software

This chapter describes how to use the SAS Deployment Wizard to install and configure all of the SAS software components called for in your deployment plan on each host in your environment.

Installing and configuring SAS is the fifth and final step in deploying SAS.

- 1. Review additional documentation.
- 2. Create operating system users and groups and designate ports.
- 3. Create a SAS Software Depot.
- 4. Install required third-party software.
- ▶ 5. Install and configure SAS.

Preparing to Install and to Configure

SAS Deployment Wizard Options

The SAS Deployment Wizard is a cross-platform utility that installs and configures many SAS products. Using a SAS installation data file (SID file) and a deployment plan (plan.xml) for its initial input, the wizard is designed to prompt the customer for all of the remaining input at the start of the session so that the customer does not have to monitor an entire deployment.

There are two major ways that you can run the SAS Deployment Wizard:

 \Box interactively

a standard method of providing input via fields on wizard pages with a Back and Next button navigation method. You can choose from three levels of configuration prompting: Express (minimum set of prompts), Typical (basic set of prompts), and Custom (all prompts). For more information, see "Install and Configure SAS Interactively" on page 87.

 \Box non-interactively

a record and playback feature that enables you to automate a SAS installation for use on multiple machines. This feature is designed for large-scale enterprise deployments to prevent users from having to manually provide input on every page each time the SAS Deployment Wizard is run on a machine. For more information, see "Automating the SAS Installation on Multiple Machines" on page 109.

About Deployment Plans

A *deployment plan* describes what software should be installed and configured on each machine in a SAS deployment. A deployment plan is an XML file that is used as input to the SAS Deployment Wizard. There are two types of deployment plans: standard and custom. A standard deployment plan describes a common configuration. Standard plans are stored by default in the SAS Software Depot. A custom deployment plan is created by a SAS representative specifically for a site.

- □ If a SAS representative created a custom plan for you, an XML file (or a ZIP file containing an XML file) will have been e-mailed to you.
- □ If your SAS representative recommended that you use a standard plan, you just need the name of the plan that you will use; you will download the actual plan with your SAS custom order (or included in your custom media that is shipped to

you.) During the installation, the standard plan will be available from a drop-down list in the SAS installation program.

At the end of the SAS deployment, the SAS Deployment Wizard makes a copy of the deployment plan it used. The deployment plan can be helpful when you want to add another SAS product or change your SAS configuration. The wizard stores a copy of the deployment plan in the SAS configuration directory in the utilities directory, and inserts a date and time stamp to the deployment plan filename. For example:

C:\SAS\Config\Lev1\Utilities\plan.2009-02-17-11.04.xml

To download the latest SAS 9.2 standard deployment plans that also contain a corresponding architectural diagram and pre-installation checklist, go to http://support.sas.com/installcenter/plans.

Content Repository Considerations

Before deploying SAS 9.2, consider where certain content repositories will reside:

 \Box SAS Table Server

If you are deploying the SAS Table Server, then the SAS configuration path should be a path local to the machine. The configuration path should not be on an NFS shared disk. If you want to put your configuration path on a shared disk, then you must make sure that you specify a local path for the table server content directory. Setting the table server content directory path is possible only on the SAS Deployment Wizard custom configuration prompting level. For more information, see "Interactive Prompting Levels" on page 69.

 \Box SAS Metadata Server

We recommend that your metadata repositories reside either on a local file system or a high-performance, high-availability network file system. For more information about metadata repositories, see "About SAS Metadata Repositories" in the SAS Intelligence Platform: System Administration Guide.

Installation Order Rules for Multiple Machine Deployments

Be aware that if you are deploying SAS on a multiple-machine, distributed system, you must install software on your computers in a particular order:

- □ Always install SAS software on the metadata server machine first.
- □ Install the SAS application servers (such as workspace or stored process servers) on machines other than the metadata server machine.
- □ Install the middle tier with SAS Foundation Services (that is, Remote Services).
- □ Install the middle tier with SAS Web Infrastructure Platform
- Install the middle tier with other Web applications (such as SAS BI Dashboard, SAS Web Report Studio, and so on).
- \Box Install software on machines that will host only clients last.

How the Deployment Wizard Names SAS Web Application Servers

The SAS Deployment Wizard creates multiple SAS web application servers as needed, based upon the products in your SAS order. By default, each SAS web application is assigned to a specific server for deployment. This distribution helps balance the load on each server, and defines a recommended number of servers based on the products in each configuration. Most of the time, the deployment wizard numbers these servers sequentially (for example, SASserver1, SASserver2, and SASserver3). However, depending on your particular SAS product order, the default application server names might not be named sequentially.

If you use the default names (for example, **SASserver***n*) in your configuration, then we recommend that you also maintain the default numbering scheme.

IPv6 Windows Machines that Communicate with SAS Foundation Servers

If the machine you are deploying SAS on matches these characteristics: uses IPv6 (Internet Protocol version 6)

Note: For more information, see "Designating Ports and Multicast Addresses" on page 19. \triangle

- \Box runs Windows
- communicates with the SAS Foundation Server tier

then you must perform your SAS 9.2 deployment in the following manner:

1 Run the SAS Deployment Wizard in install mode.

Begin following the directions for running the wizard. Early in the process, when the Select Deployment Type page appears, make sure that the Configure SAS Software check box is *not selected*. For more information, see "Install and Configure SAS Interactively" on page 87.

SAS Deployment Wizard	_ 🗆 ×
Select Deployment Type Select the type of deployment you want to perform.	
• Perform a Planned Deployment	
Perform a planned deployment of SAS software using a sample deployment specifically for your site. A planned deployment consists of installing and co deployment plan. You may choose to perform these steps independently b Install SAS Software Configure SAS Software	plan or a customized deployment plan created onfiguring the software on each machine in the y unselecting a step below.
C Install SAS Foundation and Related Software	
Express path for installing SAS Foundation and related software. A plan file	e is not used for this type of deployment.
C Install Additional Software	
Perform individual installs of SAS software by selecting from a list of availab when you want to add software to an existing deployment and do not need	le software. This option is recommended only d to perform configuration.
Help	< <u>₿</u> ack <u>N</u> ext > Cancel

2 After the installation phase has completed, copy the following JAR file from your SAS Software Depot to the machine's JRE ext directory:

*depot-install-dir***thirdparty****ipv6****sas.nioc.channels.jar** For example:

```
copy C:\SAS Software Depot\thirdparty\ipv6\sas.nioc.channels.jar
C:\Program Files\Java\jre1.5.0 15\lib\ext
```

3 Add the following JVM start-up options to your Web application server start-up script:

```
-Djava.net.preferIPv4Stack=false
```

-Djava.net.preferIPv6Addresses=true

By default, the script is named **SASServer1.bat** and resides in your Web application server configuration directory. For information on how to manually configure your Web application server for SAS Web applications, go to the Third-Party Software Downloads site at http://support.sas.com/resources/ thirdpartysupport/v92 and search for the product name of your Web application server.

4 Rerun the SAS Deployment Wizard in configure mode to complete your SAS 9.2 deployment.

Begin following the directions for running the wizard. Early in the process, when the Select Deployment Type page appears, make sure that the Install SAS Software check box is *not selected*. For more information, see "Install and Configure SAS Interactively" on page 87.

SAS Deployment Wizard
Select Deployment Type
Select the type of deployment you want to perform.
• Perform a Planned Deployment
Perform a planned deployment of SAS software using a sample deployment plan or a customized deployment plan created specifically for your site. A planned deployment consists of installing and configuring the software on each machine in the deployment plan. You may choose to perform these steps independently by unselecting a step below.
Install SAS Software
Configure SAS Software
C Install SAS Eoundation and Related Software
Express path for installing SAS Foundation and related software. A plan file is not used for this type of deployment.
C Install Additional Software
Perform individual installs of SAS software by selecting from a list of available software. This option is recommended only when you want to add software to an existing deployment and do not need to perform configuration.
Help Cancel

Interactive Prompting Levels

Shortly after you begin running the SAS Deployment Wizard to interactively install and initially configure SAS, you will be asked to choose between three wizard prompting levels:

```
Express
```

displays the minimum number of wizard pages needed to complete the SAS configuration.

```
Typical
```

displays the basic set of wizard pages needed to complete the SAS configuration.

Custom

displays all the wizard pages needed to complete the SAS configuration.

Note: If you are deploying the SAS Table Server, then the SAS configuration path should be a path local to the machine. The configuration path should not be on an NFS shared disk. If you want to put your configuration path on a shared disk, then you must make sure that you specify a local path for the table server content directory. You can set the content directory on the Table Server Invocation Options page. This option is available only on the custom configuration prompting level. \triangle

The following table lists the configuration options and the prompt level in which they display for the SAS Intelligence Platform only. Depending on your configuration, you might see differences for the prompt level in which a particular option displays. This is one example of a prompt level and configuration option mapping for a sample configuration.

Note: The configuration options you encounter depend on which SAS products are identified in your deployment plan, and, in multiple machine deployments, the machine you are currently deploying. \triangle

Configuration Option in the SAS Deployment Wizard	Prompt Level That Displays the Option		
	Express	Typical	Custom
Configuration prompting level [*]	X	X	X
Configuration directory and level [*]	Х	Х	Х
Migration [*]	Х	Х	Х
Type of deployment $\operatorname{accounts}^{*}$	Х	Х	Х
${\rm Installer\ account\ credentials}^{*}$	Х	Х	Х
Metadata server port and host name ¹	Х	Х	Х
Unrestricted administrator account credentials *	Х	Х	Х
Trusted user account $\operatorname{credentials}^*$	Х	Х	Х
Anonymous Web user account credentials *	Х	Х	Х
SAS spawned server account credentials $\overset{*}{}$	Х	Х	Х
E-mail server information [*]	Х	Х	Х
Web application server: managed server name and ports^*	Х	Х	Х
SAS Shared Services JDBC connection credentials *	Х	Х	Х
Web application server administrator (WebLogic and WebSphere only) *2	Х	Х	Х
WebSphere application server node name, node agent name, and profile name [*]	Х	Х	Х
Web application server dependencies	Х	Х	Х
SAS Web Application Themes dependencies	Х	Х	Х
SAS Web Report Studio scheduling user (Platform LSF only)	Х	Х	Х
SAS Web Report Studio dependencies	Х	Х	Х

Table 5.1 Configuration
 Options
 By
 Prompt
 Level

Configuration Option in the SAS Deployment Wizard	Prompt	Level That the Option	Displays
	Express	Typical	Custom
SAS BI Dashboard dependencies	X	X	X
SAS Information Delivery Portal JPS extension dependencies	Х	Х	Х
SAS Help Viewer metadata configuration dependencies	Х	Х	Х
SAS Web Infrastructure Platform dependencies	Х	Х	Х
SAS Information Delivery Portal dependencies	Х	Х	Х
SAS Shared Services dependencies	Х	Х	Х
SAS BI Portlets dependencies	Х	Х	Х
SAS Flex Application Themes dependencies	Х	Х	Х
SAS BID to WIP Cross Pollination dependencies	Х	Х	Х
Local machine name [*]		Х	Х
Windows options: create shortcuts option		Х	Х
Windows shortcuts scope		Х	Х
Integrated Windows authentication (IWA) *		Х	Х
Anonymous Web access [*]		Х	Х
First user display name and account credentials		Х	Х
Object spawner port		Х	Х
Object spawner port bank ports		Х	Х
SAS Application Server: server $context^*$		Х	Х
Workspace server port		Х	Х
${\it Metadata\ utility\ workspace\ server\ port}^*$		Х	Х
Pooled workspace server port [*]		Х	Х
Stored process server bridge port		Х	Х
Stored process server MultiBridge connection ports		Х	Х
OLAP server port		Х	Х
SAS/SHARE server port		Х	Х
SAS/CONNECT spawner port		Х	Х
Table server $port^*$		Х	Х
SAS DATA step batch server deployed jobs information		Х	Х
Metadata utility SAS DATA step batch server deployed jobs information $\ensuremath{^\circ}$		Х	Х
Operating System Services Scheduling Server port		X	X
Deployment Tester port and JUnit JAR file		X	X
Web application server automatic configuration *		Х	Х
SAS Remote Services application host name and port		X	X

Configuration Option in the SAS Deployment Wizard	Prompt Level That Displays the Option		
	Express	Typical	Custom
Event broker HTTP port and admin port		X	X
Web application server automatic deployment *		Х	Х
SAS Web Application Themes host name, protocol, and port		Х	Х
IP multicast address, UDP port, TTL, authentication token option $^{3^*}$		Х	Х
SAS Web Report Studio enable clustering support		Х	Х
Enable SAS Web Report Studio scheduling *		Х	Х
SAS Web Report Studio in-process scheduling ports		Х	Х
BI Web Services: new Web services deployment method		Х	Х
SAS Content Server repository directory *		Х	Х
SAS Information Delivery Portal samples		Х	Х
Database type for SAS Shared Services		Х	Х
SAS Shared Services database properties (not for SAS Table Server) [*]		Х	Х
SAS Shared Services JDBC driver jars directory *		Х	Х
WebLogic Web application server node manager host name and port		Х	Х
Web application server administration server name, port, and secured port (WebLogic and WebSphere only)		Х	Х
WebSphere application server deployment manager profile name, node name, and cell name		Х	Х
WebSphere application server deployment manager SOAP port and RMI port		Х	Х
Web application server enable administrative security		Х	Х
WebSphere application server node SOAP port and RMI port		Х	Х
SAS WebParts for Microsoft SharePoint automatic deployment		Х	Х
SAS Flex Application Themes host name, port, and protocol		Х	Х
SAS BI Portlets Portal server		Х	Х
Select products to configure ⁴			Х
Authentication domain*			Х
Windows options: run as managed scripts or services [*]			Х
Metadata server: server librefs			Х
Metadata server name and logical name *			Х
Metadata server log file name and invocation options			Х
Metadata server foundation repository			Х
Metadata server Windows service information			Х

Configuration Option in the SAS Deployment Wizard	Prompt	Level That the Option	Displays
	Express	Typical	Custom
SAS BI Web Services authentication method *			X
SAS Spawned Servers account: enable local security policy settings			Х
SAS First User account: enable local security policy settings			Х
SAS General Servers group			Х
SAS Table Server Admins group			Х
SAS BI Web Services Users group			Х
Common directories for logs, users, data, and temporary space [*]			Х
Metadata server encryption level and algorithm *			Х
Client-side connection profile credentials policy [*]			Х
Object spawner name and host name			Х
Object spawner object name in metadata			Х
Object spawner invocation options and log filename			Х
Object spawner Windows service information			Х
SAS Application Server librefs			Х
Workspace server name, logical name, and host name			Х
Workspace server invocation options and log filename			Х
Metadata utility workspace server name, logical name, and host name [*]			Х
Metadata utility workspace server invocation options and log filename			Х
Pooled workspace server name, logical name, and host name [*]			Х
Pooled workspace server invocation options and log filename			Х
Stored process server name, logical name, and host name			Х
Stored process server invocation options and log filename			Х
OLAP server name, logical name, schema name, and host name			Х
OLAP server invocation options and log filename			Х
OLAP server Windows service information			Х
SAS/SHARE server name and host name			Х
SAS/SHARE server: server component name			Х
SAS/SHARE server invocation options, server short name, and log filename			Х
SAS/SHARE server Windows service information			Х
SAS/CONNECT server name and logical server name			X

Configuration Option in the SAS Deployment Wizard	Prompt	Level That the Option	Displays
	Express	Typical	Custom
SAS/CONNECT server invocation options and log filename			X
SAS/CONNECT spawner name and host name			Х
SAS/CONNECT spawner server component name			Х
SAS/CONNECT spawner invocation options and log filename			Х
SAS/CONNECT spawner Windows service information			Х
Table server name and host name [*]			Х
Table server content directory, invocation options and log filename			Х
Table server Windows service information			Х
SAS DATA step batch server name, logical name, invocation options, and deployed jobs information			Х
Metadata utility SAS DATA step batch server name, logical name, invocation options, and deployed jobs information [*]			Х
Operating System Services name and host name			Х
Operating System Services Scheduling Server additional SAS invocation options, object server parameter, and log filename			Х
Deployment Tester host name			Х
Query cache library directory and libref [*]			Х
Output management library information [*]			Х
Web application server administration server protocol and additional JVM options			Х
WebSphere application server protocol for deployment manager - node agent protocol and ports			Х
Secure JMS resources (WebLogic and JBoss only)			Х
Web application server: proxy information *			Х
WebSphere application server node additional JVM $\operatorname{options}^*$			Х
Web application server: configure multiple managed servers *			Х
WebLogic Web application server domain path and home directory			Х
Web application server: managed server protocol and additional JVM options $^{\circ}$			Х
Web application server restrictive policy files (WebSphere and JBoss only)			X
SAS Remote Services Windows service information			X
SAS Remote Services JVM settings [*]			X
SAS Web Report Studio upgrade reports			Х

Configuration Option in the SAS Deployment Wizard	Prompt	Level That the Option	Displays
	Express	Typical	Custom
SAS Web Report Studio deployment instance name (WebLogic and WebSphere only)			Х
SAS Web Report Studio description and context root			Х
SAS BI Dashboard context root			Х
SAS BI Dashboard content directory			Х
SAS BI Web Services: completion code values, dynamic prompt validation, and execution time-out			Х
BI Web Services: new Web services base namespace, temp directory, and delete temp files			Х
SAS Information Delivery Portal banner title and menu display options			Х
SAS Information Delivery Portal unchallenged access^*			Х
SAS Information Delivery Portal and SAS Package Viewer context root			Х
SAS BI Portlets editing and viewing interfaces			Х
SAS BI Portlets and SAS JSR 168 Remote Portlets context roots			Х
SAS Flex Application Themes host name, port, and protocol			Х
SAS Web Parts for Microsoft SharePoint name, port, directory, and application pool			Х
SAS Web Parts for Microsoft SharePoint URLs, installation directory, and user ID^*			Х

* An asterisk (*) next to a configuration option indicates that more information is available later in this document. See the SAS Deployment Wizard online Help for information about all options.

- 1 Option available for the server tier on Typical and Custom prompt levels only.
- 2 Option displays during express for WebLogic dpeloyments only.
- 3 Option displays during express and typical prompting when the configuration directory and level pre-exists.
- 4 Option displays during express and typical prompting whenever the middle tier is deployed.

Installing SAS OnlineDoc for the Web

If you choose to install and deploy SAS OnlineDoc for the Web, you must be sure to select the option **Create the Enterprise Archive for SAS OnlineDoc for the Web** when you run the SAS Deployment Wizard. (This is not the default.)



In the page that follows, you must specify the Web application server that you are using.

SAS Deployment Wizard	
Specify Server Options for SAS OnlineDoc for the Web SAS OnlineDoc for the Web requires a Java Application Server. See the he deployment information.	alp for
Select the Java application server to assemble for:	
JBoss	
Specify the archive name for the Enterprise Archive for SAS OnlineDoc for the	Web:
sas.onlinedocweb	
Specify the context root for the SAS OnlineDoc for the Web application:	
SASOnlineDoc	
Help	< Back Next > Cancel

After the deployment wizard finishes, check the following logs in the SAS-Home/ Documentation/9.2 directory:

- □ onlinedocweb_install_YYYY-MM-DD-hh.mm.ss.log
- \Box onlinedocweb_update_YYYY-MM-DD-hh.mm.ss.log

Search the logs for the occurrence of "ERROR" (case-sensitive). Note that the logs might state "BUILD SUCCESSFUL" even when errors have occurred.

For more information, see "Deploying SAS OnlineDoc Manually for the Web" in the SAS Intelligence Platform: Web Application Administration Guide.

Deploy SAS BI Lineage When LSF Scheduler Is on a Separate Machine from the Workspace Server

The most common topology involving the Load Sharing Facility Scheduler (LSF Scheduler) is to locate it on the same machine as the SAS workspace server. However, an alternative topology could consist of the following:

- \square Machine 1 hosts the metadata and workspace servers.
- □ Machine 2 hosts the LSF Scheduler and BI Lineage Scheduling servers.

To achieve this configuration, you run the deployment wizard twice: first on machine 1 and then on machine 2.

To deploy the SAS BI Lineage Scheduling Server when the LSF Scheduler is installed on a separate machine from the SAS workspace server, follow these steps:

1 When running the SAS Deployment Wizard on machine 1, the metadata and workspace server machine, make sure that you deselect **SAS BI Lineage Scheduling Server** on the Select Product to Install page.

For information about how to run the deployment wizard, see "Install and Configure SAS Interactively" on page 87.

SAS Deployment Wizard	_ 🗆 ×
Select Products to Install Select the products you want to install on this machine.	DO
Machine: Server and Middle Tier	or not supported on
Product	Info
SAS Foundation	0
🔽 SAS Management Console	0
🗹 SAS BI Lineage Plug-in for SAS Management Console	0
🗹 SAS Deployment Tester Plug-in for SAS Management Console	0
🗹 SAS OLAP Server Monitor for SAS Management Console	0 _
🗹 SAS Web Infrastructure Client	0
🗹 SAS Data Integration Studio Server Data	0
SAS BI Lineage Scheduling Server	0
SAS BI Report Services	0
SAS BI Dashboard Configuration Data	0
SAS Foundation Services	0
SAS Web Infrastructure Platform	0
SAS Flex Application Themes	
Select All Clear All	
Help < Back Next >	Cancel

2 On the Select Configuration Prompting Level page, select **Custom** for the prompting level.

SAS Deployment Wizard	
Select Configuration Prompting Level Select the level of prompting for configuration information dialogs.	
Configuration is the final stage of deployment and is necessary to integrate a dialogs gather information needed to perform configuration on this machine.	all aspects of your deployment. The remaining
C Express	
Display the minimum set of required dialogs to complete configuration.	
C Typical	
Display the basic set of configuration dialogs, excluding custom settings.	
Custon Display all configuration dialogs and custom settings.	
Help	< Back Next > Cancel

- **3** On the Select Products to Configure page, deselect the following:
 - D Platform Process Manager

5A5 Deployment Wizard	
elect Products to Configure	
Select the products you want to configure on this machine.	
oduct Search:	Eind Next
Some products are not listed because they are either not available in	this order or are not supported on this platform.
g p	
7 SAS Metadata Server Coofiguration	
SAS Management Console	
Z SAS Object Snawner	
Operating System Services Scheduling Server	
Platform Process Manager	
SAS OLAP Server Configuration	
SAS Pooled Workspace Server	
SAS Stored Process Server	
SAS Table Server	
SAS Workspace Server	
SAS Add-in for MS Office Server Data	
SAS BI Report Services Workspace Configuration	
ASAS Management Console Server Data	
SAS BI Lineage Scheduling Server	
Select All Clear All	

4 On the SAS Web Report Studio: Scheduling page, deselect Enable Scheduling.

SAS Deployment Wizard		
SAS Web Report Studio: Scheduling Select whether to enable the scheduling feature of SAS Web Report Studi	o.	
SAS Web Report Studio supports a scheduling feature that allows you to scher	dule reports to run when you choose.	
Help	< <u>B</u> ack Next > Canc	el

5 Answer the remaining deployment wizard prompts.

The wizard will install and initially configure machine 1 based on the input that you have provided.

- 6 After the wizard completes running on machine 1, back up your metadata repository and your SAS configuration directory before you run the SAS Deployment Wizard on the next machine called for by your deployment plan.
 - □ Make a backup copy of your SAS 9.2 configuration directories by using your site-approved method. Your SAS configuration directories are all the child directories beneath the path that you specified earlier in this procedure on the Specify Configuration Information wizard page.
 - □ Back up your Web application server directories.
 - □ Back up your metadata repository and repository manager on the SAS Metadata Server machine. For more information, see "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.
- 7 Be sure to restart any servers that you stopped for purposes of creating a backup.
- 8 When you are finished completing any manual configuration tasks called for in Instructions.html, and you have made the necessary backups, log on to machine 2 (the BI Lineage Scheduling and LSF Scheduler servers machine) and launch the wizard a second time.

For information about how to run the deployment wizard, see "Install and Configure SAS Interactively" on page 87.

9 Use the same deployment plan and again select the Server and Middle Tier machine when prompted for products to install.

SAS Deployment Wizard			-	
Select Products to Install				
Select the products you want to install on this machine.				
				_
Machine: Server and Middle Tier				T
Some products are not listed for the selected machine because they are eil this platform. Refer to the previous dialog for a list of the excluded product	ther not available ts.	in this order or	[,] not supporte	d on
Product			Info	\Box
SAS Foundation			0	
SAS Management Console			0	
SAS BI Lineage Plug-in for SAS Management Console			0	
🔽 SAS Deployment Tester Plug-in for SAS Management Console			0	
SAS OLAP Server Monitor for SAS Management Console			0	
SAS Web Infrastructure Client			0	
🗹 SAS Data Integration Studio Server Data			0	
🔽 SAS BI Lineage Scheduling Server			0	
SAS BI Report Services			0	
🗹 SAS BI Dashboard Configuration Data			0	
SAS Foundation Services			0	
SAS Web Infrastructure Platform			0	
SAS Flex Application Themes			0	-
Select All Clear All		1		
Help	< Back	Next >	Cancel	

10 Select only the following products to install:

- □ SAS Management Console
- □ SAS BI Lineage Plug-in for SAS Management Console
- □ SAS BI Lineage Scheduling Server
- □ SAS Intelligence Platform Object Framework (not pictured).

SAS Deployment Wizard	_ 🗆 ×
Select Products to Install	
Select the products you want to install on this machine.	
Marbina - Server and Middle Tier	
Some products are not listed for the selected machine because they are either not ava this platform. Refer to the previous dialog for a list of the excluded products.	lable in this order or not supported on
Product	Info
SAS Foundation	0
✓ SAS Management Console	0
🔽 SAS BI Lineage Plug-in for SAS Management Console	0
SAS Deployment Tester Plug-in for SAS Management Console	0
SAS OLAP Server Monitor for SAS Management Console	0 _
🔲 SAS Web Infrastructure Client	0
🗌 SAS Data Integration Studio Server Data	0
SAS BI Lineage Scheduling Server	0
SAS BI Report Services	0
SAS BI Dashboard Configuration Data	0
SAS Foundation Services	0
🔲 SAS Web Infrastructure Platform	0
SAS Flex Application Themes	0
Help < Back	Next > Cancel

11 On the Select Configuration Prompting Level page, select **Custom** for the prompting level.

SAS Deployment Wizard
Select Configuration Prompting Level Select the level of prompting for configuration information dialogs.
Configuration is the final stage of deployment and is necessary to integrate all aspects of your deployment. The remaining dialogs gather information needed to perform configuration on this machine.
C Express
Display the minimum set of required dialogs to complete configuration.
C Typical
Display the basic set of configuration dialogs, excluding custom settings.
© Custom Display all configuration dialogs and custom settings.
Help Cancel

12 On the Select Products to Configure page, select only the following products:

- \square SAS Management Console
- \Box Platform Process Manager
- $\hfill\square$ SAS BI Lineage Scheduling Server

SAS Deployment Wizard	_ 🗆 >
Select Products to Configure	
Select the products you want to configure on this machine.	
······································	
roduct Search:	Eind Next
$\underline{ m N}$ Some products are not listed because they are either not available in this order or are not s	upported on this platform.
Product	
SAS Metadata Server Configuration	
SAS Management Console	
SAS Object Spawner	
Operating System Services Scheduling Server	
Platform Process Manager	
SAS OLAP Server Configuration	
SAS Pooled Workspace Server	
SAS Stored Process Server	
SAS Table Server	
SAS Workspace Server	
SAS Add-in for MS Office Server Data	
SAS BI Report Services Workspace Configuration	
SAS Management Console Server Data	
SAS BI Lineage Scheduling Server	<u> </u>
Select All	
Units and a Death	March Council

13 Answer the remaining deployment wizard prompts.

The wizard will install and initially configure machine 2 based on the input that you have provided.

- 14 If you are deploying a middle-tier machine and opted not to automatically deploy your SAS Web applications, then you must manually deploy them. For more information, go to the Third-Party Software Downloads site at http:// support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.
- 15 When you are finished installing and configuring SAS on each machine called for in your deployment plan, proceed to the section "Validate the SAS 9.2 Servers" on page 106.

Installing SAS Web Parts for Microsoft SharePoint

What Is SAS Web Parts for Microsoft SharePoint?

SAS Web Parts for Microsoft SharePoint enables you to display SAS BI Dashboard and SAS Analytics in SharePoint pages. SAS Web Parts for Microsoft SharePoint includes the following components:

- □ the SAS BI Dashboard Web Part, which displays dashboards and KPIs to enable users to monitor organizational performance
- □ the SAS Stored Process Web Part, which enables users to view the results of a stored process on the SharePoint site

SAS Web Parts for Microsoft SharePoint Architecture

SAS Web Parts for Microsoft SharePoint consists of the following components:

 \square SAS Web Parts

This component is deployed on the SharePoint server.

□ SAS Web Parts Service

This service runs in a separate Microsoft Internet Information Server (IIS) application from SharePoint, and can be installed on the same machine where SharePoint resides or on a separate machine. SAS Web Parts Service for Microsoft SharePoint provides communication between SAS Web Parts and your SAS servers. This Web service can be hosted on your SharePoint server or another Microsoft Windows machine that is running Microsoft Internet Information Server.

The SAS Web Parts Service must be able to connect to your SAS servers via SAS Integration Technologies. Therefore, a firewall cannot exist between the SAS Web Parts Service and the SAS servers. Because the SAS Web Parts connect to the service via SOAP over HTTPS, a firewall can exist between the SAS Web Parts Service and SharePoint. In the most common and simple deployments, this service runs on the SharePoint server.

Automatically Deploy SAS Web Parts for Microsoft SharePoint

This topic provides an overview for how you use the SAS Deployment Wizard to automatically install and configure SAS Web Parts for Microsoft SharePoint. For more information on automatically deploying SAS Web Parts, see "Install and Configure SAS Interactively" on page 87.

Note: If you want to avoid installing a Java Runtime Environment (JRE), a dependency for the deployment wizard, you can manually deploy SAS Web Parts on a machine that contains a JRE and move the SAS Web Parts deployment to another machine. For more information, see "Manually Deploy SAS Web Parts for Microsoft SharePoint and Move It" on page 85. \triangle

1 Install the SAS Web Parts and the SAS Web Parts Services.

When running the SAS Deployment Wizard, select the deployment plan for the **SharePoint** machine.

💁 SAS Deployment Wizard	_ 🗆 🗡
Select Products to Install Select the products you want to install on this machine.	
Machine: SharePoint (optional)	
Product	Info
SAS Integration Technologies Client	0
SAS Intelligence Platform Object Framework	0
☑ SAS Web Parts Services for Microsoft SharePoint	0
🔽 SAS Web Parts for Microsoft SharePoint	0
Heln Serk Next >	Cancel
	Cancor

If your SharePoint installation is not in the default location (C:\inetpub\wwwroot\wss\VirtualDirectories\80), you have to select the Custom option for the prompting level in the deployment wizard:

SAS Deployment Wizard		
Select Configuration Prompting Level Select the level of prompting for configuration information dialogs.		
Configuration is the final stage of deployment and is necessary to integrate all asp dialogs gather information needed to perform configuration on this machine.	pects of your deployment. The m	emaining
C Express		
Display the minimum set of required dialogs to complete configuration.		
O Typical		
Display the basic set of configuration dialogs, excluding custom settings.		
© Custom		
Display all configuration dialogs and custom settings.		
Help	< <u>B</u> ack <u>N</u> ext >	Cancel

You must also change the installation path in the SharePoint installation directory field:

SAS Deployment Wizard			_ 🗆 🗵
SAS Web Parts for Microsoft SharePoint: Details Provide details about your SharePoint installation and SAS connectivity			
Web URL:			
http://localhost			
Site URL:			
http://localhost			
SharePoint installation directory:			
C:\inetpub\wwwroot\wss\VirtualDirectories\80			Browse
SAS User ID (optional):			
Encrypt SAS Trusted User password (recommended)			
Help	< <u>B</u> ack	<u>N</u> ext >	Cancel

If you choose the option Automatically Deploy SAS Web Parts for Microsoft SharePoint in the SAS Deployment Wizard, SAS Web Parts is deployed and configured automatically.

SAS Deployment Wizard	
SAS Web Parts for Microsoft SharePoint: Automatic Deployment Specify whether or not the SAS Web Parts for Microsoft SharePoint will be automatically.	e deployed
To attempt automatic deployment, Microsoft SharePoint must be installed on the available if you choose not to automatically deploy.	his machine. Manual deployment instructions are
Help	< Back Next > Cancel

For more information on automatically deploying SAS Web Parts, see "Install and Configure SAS Interactively" on page 87.

2 Secure SAS Web Parts for Microsoft SharePoint.

For more information, see "Configure HTTPS Connections for SAS Web Parts for Microsoft SharePoint" on page 86.

3 Enable SAS BI Dashboard to access the SharePoint server

For more information, see the "Enabling SAS BI Dashboard to Access the SharePoint Server" in the SAS Intelligence Platform: Web Application Administration Guide.

Manually Deploy SAS Web Parts for Microsoft SharePoint and Move It

The SAS deployment and configuration tools rely on a Java Runtime Environment (JRE) that is not a dependency for SAS Web Parts. To avoid installing a JRE on your Microsoft SharePoint server, you can deploy SAS Web Parts on a machine which does contain a JRE and then move your deployment to your SharePoint server later.

To manually deploy SAS Web Parts for Microsoft and then move it to a different machine, follow these steps:

1 Run the SAS Deployment Wizard on a machine that contains the required JRE.

For more information, see "Install and Configure SAS Interactively" on page 87.

2 On the Automatic Deployment page, be sure to *deselect* the option Automatically Deploy SAS Web Parts for Microsoft SharePoint.

SAS Deployment Wizard	
SAS Web Parts for Microsoft SharePoint: Automatic Deployment Specify whether or not the SAS Web Parts for Microsoft SharePoint will be dep automatically.	ployed
To attempt automatic deployment, Microsoft SharePoint must be installed on this m available if you choose not to automatically deploy. Image: Automatically Deploy SAS Web Parts for Microsoft SharePoint]	nachine. Manual deployment instructions are
Help	< Back Next > Cancel

3 After the deployment wizard has finished executing, on the machine where you deployed SAS Web Parts, navigate to the **Applications** sub-folder under the SAS configuration folder.

For example: C:\SAS\Lev1\Applications.

4 Under the Applications, copy the sub-folder SAS Web Parts for Microsoft SharePoint to the Microsoft SharePoint server where you want to deploy the SAS Web Parts software.

An example target location on the SharePoint server is: C:\Program Files\SAS Web Parts for Microsoft SharePoint.

Note: Be sure to copy (not move) the sub-folder so that you can continue to apply updates or reconfigure your SAS Web Parts deployment in the future. \triangle

5 On the Microsoft SharePoint server, run the batch file WebPartsSetup.bat.

WebPartsSetup.bat resides in the SAS Web Parts for Microsoft SharePoint sub-folder that you copied in the previous step.

A Windows command prompt window displays that lists the progress and status of the SAS Web Parts installation and configuration.

6 When prompted, press any key to close the command prompt window.

The move of SAS Web Parts for Microsoft SharePoint to the new machine is now complete.

- 7 The next steps are as follows:
 - □ Secure SAS Web Parts for Microsoft SharePoint.

For more information, see "Configure HTTPS Connections for SAS Web Parts for Microsoft SharePoint" on page 86.

□ Enable SAS BI Dashboard to access the SharePoint server.

For more information, see the "Enabling SAS BI Dashboard to Access the SharePoint Server" in the SAS Intelligence Platform: Web Application Administration Guide.

Configure HTTPS Connections for SAS Web Parts for Microsoft SharePoint

The connection between SAS Web Parts and the SAS Web Parts Service requires Hypertext Transfer Protocol Secure (HTTPS) to encrypt the communication. HTTPS uses Secure Socket Layer (SSL) and public key cryptography, which is based on the implementation of a public and private key pair.

To enable HTTPS, an SSL server certificate must be attached to the SAS Web Parts Service. If your organization has a standard procedure for obtaining an SSL server certificate, follow those guidelines and attach that certificate to the service.

Another alternative is to use a self-signed SSL certificate for the SAS Web Parts Service. Because the secure communication occurs only between SAS Web Parts and SAS Web Parts Service, the self-signed certificate needs to be imported only into the Microsoft SharePoint machine's certificate store. Refer to your Microsoft Internet Information Server (IIS) documentation for instructions on how to create and install the self-signed certificate, and complete the following steps:

- 1 On the machine hosting the SAS Web Parts Service, use the IIS Manager to create a self-signed certificate and associate it with the SASWebPartsService Web site.
- 2 On the SharePoint Server host, import the self-signed certificate into Internet Explorer's Trusted Root Certification Authorities store.

For more information about how to create and install a self-signed certificate, see the following SAS Note:

http://support.sas.com/kb/39/912.html

Configure User Access for SAS Web Parts for Microsoft SharePoint

Users of SAS Web Parts for Microsoft SharePoint can access content in the SAS servers in one of two modes:

- □ Actual identity (default)
- \Box Shared identity

Actual identity controls user access to SAS Web Parts explicitly through a SAS metadata identity and the permissions associated with that identity. Users might have permissions in SharePoint to view a page, but they can be denied access to the Web

part's content if they are not granted permission to access the dashboard or stored process in SAS metadata. For information about creating metadata identities and assigning permissions, see "Users, Groups, and Roles" and "Getting Started With Permissions" in the SAS Intelligence Platform: Security Administration Guide.

Shared identity controls user access to SAS Web Parts through a single identity defined in SAS metadata that all users share. Authentication of the individual user is managed by SharePoint.

CAUTION:

When using shared identity, it is important in SharePoint to grant access to only those users who are allowed to view SAS content. \times

To enable shared identity, store the SAS metadata identity in the web.config file.

CAUTION:

In addition to storing a possible shared metadata identity, web.config also contains connection information to the SAS Web Parts service plus an encrypted form of the SAS Trusted User ID and password. As a best practice, we recommend that you limit access to web.config. The default location for config.web in IIS 6 is:

C:\Inetpub\wwwroot\wss\VirtualDirectories80\web.config. For more information, see your Microsoft Internet Information Server documentation. \triangle

Install and Configure SAS Interactively

Installing and configuring SAS interactively with the SAS Deployment Wizard consists of two main phases:

- □ Providing installation information such as the following:
 - \Box installation type (planned or unplanned)
 - □ deployment plan location (if planned)
 - \Box machine type (single machine, server machine, and so on)
 - $\hfill\square$ SAS components to be installed on the machine
 - $\hfill\square$ valid paths to any required pre-installed, third-party software
- □ Providing configuration information such as the following:
 - □ prompting level (express, typical, custom)
 - $\hfill\square$ SAS components to be configured on the machine
 - \Box configuration directory name
 - □ single sign-on preference (Windows only)
 - □ required user account credentials
 - \Box server port numbers

This topic describes some of the more important configuration pages that you will encounter during the configuration phase of a SAS 9.2 deployment. The type and number of configuration-related pages that you will see depend upon the prompt level that you choose, the SAS tier that you are currently deploying, and the contents of your SAS 9.2 custom order. For information about all SAS Deployment Wizard prompts, see the online Help for the wizard page in question.

To install and configure SAS interactively, complete these steps:

1 Verify that you have performed the earlier required steps outlined in "Overview of Installing and Configuring Your SAS Software" on page 65.

Note: A few pages into the SAS installation, the SAS Deployment Wizard prompts you for paths to the requested third-party software. You must have the

necessary third-party software installed on the current machine, or the SAS Deployment Wizard will *not* let you continue with the installation. In this situation, you will have to end the SAS Deployment Wizard session and install the required third-party software before you can continue. \triangle

- 2 If you use any garbage collection scripts, temporarily suspend these scripts during SAS Deployment Wizard execution. If any wizard temporary files are deleted during wizard execution, configuration failures can occur.
- 3 Review information about where to source certain SAS content repositories described in the topic, "Content Repository Considerations" on page 67.
- **4** Review information about SAS Deployment Wizard configuration prompting levels described in the topic, "Interactive Prompting Levels" on page 69.
- 5 If you are deploying SAS on multiple machines, make sure that you are following the process described in "Installation Order Rules for Multiple Machine Deployments" on page 67.
- 6 If you are deploying the SAS middle tier and intend on having the SAS Deployment Wizard automatically configure your Web application server, make sure that the server is installed, but not running.
- 7 If any machines on which your are deploying SAS 9.2 use IPv6, then a different deployment procedure is required. For more information, see "IPv6 Windows Machines that Communicate with SAS Foundation Servers" on page 68.
- 8 Log on to the machine with a user ID that meets the requirements for the appropriate operating system:
 - \square Windows:

Use an account that is available for the long term (for future SAS maintenance) and is a member of the Administrators group.

 \Box UNIX:

Use the same account on all machines on which you are deploying SAS. Do not use **root**.

 \Box z/OS:

Use the same account on all machines on which you are deploying SAS.

9 Start the SAS Deployment Wizard from the highest-level directory in your SAS Software Depot using the command appropriate for your operating system:

 Table 5.2
 Startup Commands for the SAS Deployment Wizard

Operating System	Command
Windows	setup.exe -record -deploy
UNIX	setup.sh -record -deploy
z/OS	setup.rexx -record -deploy
	To use a temporary directory other than /tmp , specify -templocation new-temp-dir.

Note: Using the **-record -deploy** options causes the wizard to create a response file that records the inputs that you supplied. This can be helpful when

you want to repeat the deployment on other machines or when troubleshooting a deployment issue. \vartriangle

By default, the deployment wizard writes the response file in the following location:

 \Box Windows:

C:\Documents and Settings*current-user*\sdwresponse.properties

~/sdwresponse.properties

You should see a welcome page similar to the following:

SAS Deployment Wizard	
<u>s</u> .sas	
	SAS [®] Deployment Wizard 9.2
THE POWER TO KNOW.	
Copyright © 2010, SAS Instit	ute Inc., Cary, NC, USA. All Rights Reserved

- 10 Select the language that you want the SAS Deployment Wizard to use when it displays text.
- 11 Select Install SAS Software.
- 12 If you have more than one SAS software order in your depot, the wizard prompts you to select the order that you want to deploy.
- 13 Select Perform a Planned Deployment, and make sure that Install SAS Software and Configure SAS Software are both checked.

5AS Deployment Wizard	
elect Deployment Type	
Select the type of deployment you want to perform.	1000
Perform a Planned Deployment	
Perform a planned deployment of SAS software using a sample dep specifically for your site. A planned deployment consists of installin deployment plan. You may choose to perform these steps indepen	loyment plan or a customized deployment plan created g and configuring the software on each machine in the dently by unselecting a step below.
✓ Install SAS Software	
☑ <u>C</u> onfigure SAS Software	
Install SAS <u>Foundation and Related Software</u>	
Express path for installing SAS Foundation and related software.	A plan file is not used for this type of deployment.
Install Additional Software	
Perform individual installs of SAS software by selecting from a list of when you want to add software to an existing deployment and do	f available software. This option is recommended only not need to perform configuration.

Note: If any machines on which your are deploying SAS 9.2 use IPv6, then a different deployment procedure is required. For more information, see "IPv6 Windows Machines that Communicate with SAS Foundation Servers" on page 68. \triangle

14 Specify the location (SAS Home) where you want to install SAS.

Note: The deployment wizard prompts you for SAS Home the first time that you run the wizard. On any subsequent sessions on this machine, the wizard uses the previously specified location for SAS Home. \triangle

15 Specify the type of deployment plan you are using:

 \Box customized deployment plan

Choose Specify the full path to a customized deployment plan, and then click Browse to navigate to the plan file (plan.xml).

 \Box standard deployment plan

Choose Select a standard deployment plan, and then choose the appropriate plan in the drop-down list.

For more information, see "About Deployment Plans" on page 66.

1_files	Bro <u>w</u> se
	•
	p_files

16 Select the machine on which you are installing software, and select the SAS products that you want to install, by doing the following:

a Select the machine on which you are installing software from the Machine drop-down list.

Note: If you are deploying SAS on multiple machines, make sure that you are following the process described in "Installation Order Rules for Multiple Machine Deployments" on page 67. \triangle

b By default, all products displayed will be installed. Deselect any products that you do *not* want to install.

SAS Deployment Wizard			_ 🗆
Select Products to Install			
Select the products you want to install on this machine.			
achine: SingleMachine			
Some products are not listed for the selected machine because they are eil this platform. Refer to the previous dialog for a list of the excluded product	ther not availab ts.	le in this order or	not supported a
Product			Info
SAS Foundation			0
SAS Management Console			0
SAS BI Lineage Plug-in for SAS Management Console			0
SAS Deployment Tester Plug-in for SAS Management Console			0
SAS OLAP Server Monitor for SAS Management Console			0 -
SAS Web Infrastructure Client			0
SAS Data Integration Studio Server Data			0
SAS BI Lineage Scheduling Server			0
SAS BI Report Services			0
SAS BI Dashboard Configuration Data			0
SAS Foundation Services			0
SAS Web Infrastructure Platform			0
SAS Flex Application Themes			0
Select All			
Help	< <u>B</u> ack	Next >	Cancel

17 Specify the location of the SAS installation data file that contains information about the software that you have licensed for the current machine.

CAUTION:

If you do not use the installation data file that supports the products you are planning to install and configure on this machine, you might experience errors later when you are trying to use the products. \triangle

- 18 Deselect any languages that you do not want SAS to support. By default, SAS attempts to support all languages that your machine's operating system is configured for.
- 19 The deployment wizard prompts you to do one of the following:

(z/OS only) No Java Runtime Environment	Select to have the deployment wizard install your software on z/OS without a Java Runtime Environment (JRE).
(UNIX and Windows only) Use the recommended Java Runtime Environment	(Recommended) select to have the deployment wizard install the required JRE on this machine.
	On UNIX, specify in the text field where you want the deployment wizard to extract the JRE.
Select an existing Java Runtime Environment	Select to specify the path to a JRE that you have already installed on this machine.
For more inform	nation see http://support sas com/resources/

For more information, see http://support.sas.com/resources/ thirdpartysupport/v92/jres.html.

20 Select this option if you want to install and deploy SAS OnlineDoc for the Web.

A Web application server is required for this product. For more information, see "Installing SAS OnlineDoc for the Web" on page 75.

21 On the Select Microsoft Office Applications page, choose the Microsoft Office applications for which you want the SAS Add-In for Microsoft Office activated.

When the Office application is launched, the activated SAS add-in automatically loads, and users see either a **SAS** tab on the Ribbon (Microsoft Office 2010 and 2007) or a **SAS** menu and toolbars (Microsoft Office 2003). To activate the SAS Add-In for Microsoft Office in Microsoft Excel, Word, PowerPoint, or Outlook after the installation, you can run SwitcherUtility.exe. For more information, see the Help for the SAS Add-In for Microsoft Office.

22 (z/OS only) Provide input for the following prompts:

Note: For more information, see the Configuration Guide for SAS 9.2 Foundation for z/OS, available on the SAS Install Center (http://support.sas.com/documentation/installcenter/). \triangle

FTP Batch Generation

Specify the fully qualified host name or IP address of the z/OS mainframe machine on which you are deploying SAS. Also supply a valid user ID and password with which the SAS Deployment Wizard will FTP deployment information to the mainframe machine.

Specify Jobcard Information

Specify the job account, programmer-name, message class, message level, time, and region values. For more information, consult your z/OS documentation.

Select Installation Action

Choose A - Install a new SAS system.

Specify New Installation Qualifier

Specify the path where you want to install SAS. You can also choose to require Storage Management Subsystem (SMS) parameters. For more information, consult your z/OS documentation.

Specify IBM's SMS Parameters

If you chose to require Storage Management Subsystem (SMS) parameters on the previous page, enter them here. For more information, consult your z/OS documentation.

Specify Parameters

These are all parameters that are used in various DD statements throughout the installation. For more information, consult your IBM JCL documentation.

Specify Entry Point

Specify the parameters for various ways that SAS can be run with different performance implications. Choose SAS (default ENTRY point) to run the unbundled configuration. Choose SASB to run the bundled configuration. Choose SASLPA to run the bundled configuration with some modules installed in the Link Pack Area (LPA).

Specify Parameters

Specify additional parameters for DD statements. VOLDISK designates the VOLSER that the installed data sets will go to. For more information, consult your IBM JCL documentation.

Specify Parameters

Specify parameters used for reblocking the SAS load modules to a library with an optimum block size.

23 (UNIX only) If your system uses Pluggable Authentication Modules (PAM), select Use PAM Authentication. In addition, you might also need to update your PAM

configuration files in order for SAS 9.2 to use PAM authentication. For more information, see the *Configuration Guide for SAS 9.2 Foundation for UNIX Environments*.

If you are uncertain that this system uses PAM for authentication, contact your system administrator.

Note: Do not select the PAM option if you know that your system uses /etc/ password or /etc/shadow authentication. \triangle

24 Review the list of third-party software that is required for the SAS software that you are installing on the current machine. (The list of third-party software depends on the SAS software that you are installing on the current machine.) In the pages that immediately follow, be prepared to provide paths to these third-party applications. (The number of dialog boxes varies depending on the SAS software you are deploying on the current machine.)

Note: You must provide valid paths to the requested third-party software, or the SAS Deployment Wizard will *not* let you continue with the installation. \triangle

25 Specify the amount of information to provide the SAS Deployment Wizard for configuring the SAS software you are installing on the current machine. Choose one of the three prompting levels:

Note: When deploying the SAS 9.2 middle-tier, by default, the SAS Deployment Wizard automatically configures your Web application server. To disable this feature, run the wizard using either the Typical or Custom prompting levels. \triangle

Express

display the minimum number of wizard pages needed to complete the SAS configuration.

Typical

display the basic set of wizard pages needed to complete the SAS configuration.

Custom

display all the wizard pages needed to complete the SAS configuration.

Refer to "Interactive Prompting Levels" on page 69 for more information about the SAS Deployment Wizard prompting levels.

26 Provide the remaining configuration information as the wizard prompts you for it.

Note: This topic describes some of the more important pages that you will encounter during the configuration phase of a SAS 9.2 deployment. The options for which the SAS Deployment Wizard prompts you depends on which SAS products are identified in your deployment plan and, in multiple machine deployments, which machine you are currently deploying. For information about all SAS Deployment Wizard prompts, see the online Help for the wizard dialog box in question. Δ

Specify Configuration Information

Select the path where the SAS Deployment Wizard will write SAS configuration files and logs and the level you want to deploy. For example, Lev1 = production.

In UNIX environments the SAS Installer generally overrides the default configuration directory with the site's preferred location (for example, /opt/sas/config). The installer must have Write permission on this path.

Note: The last digit of the default port number reflects the configuration level that you select in the SAS Deployment Wizard. For example, when you

select Lev1, the default port for the metadata server is 8561. If you choose another level, such as Lev2, the wizard changes the default port to 8562. \triangle

For more information, see "Overview of the Configuration Directory Structure" in the SAS Intelligence Platform: System Administration Guide.

Note: Although your SAS Home and SAS configuration directories can share the same parent directory, one directory should not reside inside another. Defining the configuration directory under the SAS Home directory, or vice versa, can lead to file permission issues arising from the need to manage installed files differently than site-specific configurations. \triangle

On z/OS, the mount point must exist. The SAS Deployment Wizard will create the necessary subdirectories.

If you are deploying the SAS Table Server, then SAS configuration path should be a path local to the machine. The configuration path should not be on an NFS shared disk. If you want to put your configuration path on a shared disk, then you must make sure that you specify a local path for the table server content directory. You can set the content directory on the Table Server Invocation Options page. This page is available only on the custom configuration prompting level.

Local Machine Name

Enter the complete name of the local host in Fully-qualified Local Host Name. The fully qualified local host name typically takes the form of the local host name plus the domain name server (for example, myserver.example.com). Enter a short host name in Short Local Host Name. The short local host name is the abbreviated, more common method of referring to the host, usually only a single word.

Migration Information

Ignore this page and click Next.

If you need to migrate SAS 9.1.3 content to SAS 9.2, see "Overview of Migrating Content to SAS 9.2" in the SAS Intelligence Platform: 9.1.3 to 9.2 Migration Guide.

□ Authentication Domain

Accept the default value (DefaultAuth), unless the deployment that you are migrating uses a different SAS authentication domain for servers on this machine.

For example, if the metadata server is on Windows and the workspace server is on UNIX, the workspace server might be assigned to a SAS authentication domain named UnixAuth. For more information, see "About Authentication Domains" in the SAS Management Console: Guide to Users and Permissions.

$\hfill\square$ Windows Options (run as managed scripts or services)

On Windows, choose how to run your SAS servers, either by using management scripts or running them as Windows services. If you choose the script option, then the user account that runs the object spawner must meet the following requirements on the object spawner machine:

- □ be the administrator or a member of the Windows Administrator's group
- \Box have the following Windows local user rights:
 - □ Adjust memory quotas for a process
 - Replace a process level token
- Integrated Windows Authentication

Select to use Integrated Windows authentication (IWA) for workspace servers running on Windows only. IWA supports a single sign-on feature in which a metadata server running on Windows accepts a user's previous authentication to his or her Windows desktop when the user attempts to access a workspace server.

Selecting this page when you are deploying a workspace server on Windows enables the workspace server to use IWA. You also encounter this page when deploying SAS Enterprise Guide and SAS Add-In for Microsoft Office. If you have not chosen IWA for the workspace server, then choosing IWA for these clients has no effect.

For more information, see "Integrated Windows Authentication" in the SAS Intelligence Platform: Security Administration Guide.

A metadata server running on Windows has IWA turned on by default. For more information, see "SSPI System Option" in the SAS Intelligence Platform: Application Server Administration Guide.

SAS Metadata Server

If you have any changes for the metadata server, enter them in this page.

The deployment wizard creates a separate server context (SASMeta) for the metadata server and the other servers required to perform metadata server utility functions, such as backup and promotion. A server context is a SAS IOM server concept that describes how SAS Application Servers manage client requests. A SAS Application Server has an awareness (or context) of how it is being used and makes decisions based on that awareness. The server context name is prepended to all server names defined in the server context. Therefore, we recommend that you not change the logical server or server prefix (SASMeta).

For more information, see "Overview of the SAS Metadata Server and Its Initial Configuration" in the SAS Intelligence Platform: System Administration Guide.

Deployment Accounts: Type of Accounts

Select whether to use internal accounts when appropriate. Internal user accounts are accounts known only to SAS and are created and authenticated internally in metadata rather than externally.

Note: On Windows, whenever the deployment wizard prompts you for an external account, always enter a domain-qualified user account (for example, myDomain\myAccount). \triangle

For more information, see "Internal User Accounts" on page 6.

External Account: Installer

Enter the user ID and password for the external account to be used to install and configure SAS. Depending on the operating system, this account should meet the following requirements:

 \Box Windows:

Use a domain-qualified account that is available in the long term (for future SAS maintenance) and is a member of the Administrators group.

 \Box UNIX:

Use the same account on all machines on which you are deploying SAS. Do not use **root**.

 \Box z/OS:

Use the same account on all machines on which you are deploying SAS.

For more information, see "Defining User Accounts" on page 6.

SAS Internal Account: Unrestricted Administrator

Enter a password for the internal account (sasadm@saspw) that the wizard will create to serve as an unrestricted administrator for the purpose of configuring the SAS metadata server.

For more information, see "Defining User Accounts" on page 6.

SAS Internal Account: Trusted User

Enter a password for an internal account (sastrust@saspw) that the wizard will create to enable SAS server and spawner components to communicate securely with each other.

For more information, see "Defining User Accounts" on page 6.

SAS BI Web Services: Authentication Method

Select the method by which users of SAS BI Web Services are authenticated:

- □ SAS Authentication is managed by the metadata server.
- □ Web Authentication is managed by the Web application server using container-based authentication or a third-party product. Selecting Web Authentication has these effects:
 - □ fully configures Web authentication for .NET BI Web Services.
 - □ partially configures Web authentication for Java BI Web Services.

For more information, see "Securing SAS BI Web Services for Java" in the SAS Intelligence Platform: Web Application Administration Guide.

□ has no effect on the BI Web applications (such as SAS Web Report Studio, SAS Web Information Portal, and so on).

You will have to configure Web authentication for these BI Web applications.

□ prevents you from being offered a chance to set up an anonymous Web user (as this is incompatible with Web authentication).

Anonymous Web Access

When using SAS authentication you can select this option to set up a SAS identity for anonymous access to certain Web services and Web applications that support this feature. Currently, SAS BI Web Services for Java and .NET and the SAS Stored Process Web Application are the only components that support this feature.

For more information, see "Using the SAS Anonymous Web User With SAS Authentication" in the SAS Intelligence Platform: Web Application Administration Guide.

$\hfill\square$ SAS Internal Account: Anonymous Web User

(Optional) Enter the user ID and password for the internal SAS account to be used to grant clients access to applicable SAS Web Infrastructure Platform applications such as SAS BI Web Services and the Stored Process Web Application. When SAS authentication is being used and the user has not preemptively specified credentials, the client will be given access to these Web applications under the anonymous user account.

For more information, see "Using the SAS Anonymous Web User With SAS Authentication" in the SAS Intelligence Platform: Web Application Administration Guide.

External account: SAS Spawned Servers Account

Enter the user ID and password for the external account to be used to start the pooled workspace server and the stored process server. On Windows, enter a domain-qualified user ID.

For more information, see "Defining User Accounts" on page 6.

Create Common Directories

Select to create common directories for server and spawner logs, user-specific files, data (SAS libraries for tables and cubes), and temporary work tables and files.

When you select this option, the deployment wizard creates the specified directory (Logs, Users, Data, and Temp) under the SAS configuration directory.

Server Encryption

Select the encryption level and algorithm that SAS clients and servers use to connect to the metadata server.

Choose **Credentials** to encrypt only login credentials. Choose **Everything** to encrypt all communication with the metadata server.

To specify an encryption algorithm other than SASPROPRIETARY, you must have a license for SAS/SECURE software. The other algorithms are: RC2, RC4, DES, TripleDES, and AES.

For more information, see "Encryption Model" in the SAS Intelligence Platform: Security Administration Guide.

Client-side Credentials Policy

Select this option to set the policy to allow users to save their user IDs and passwords in client-side connection profiles on the metadata server for desktop applications. This input sets the value for OMA_SASSEC_LOCAL_PW_SAVE in omaconfig.xml.

For more information, see "Reference Information for omaconfig.xml" in the SAS Intelligence Platform: System Administration Guide.

E-mail Server

Enter the port and host name for an SMTP e-mail server that the SAS Metadata Server uses to send e-mail alerts to an administrator if journaling issues arise. The SAS Deployment Wizard also uses this e-mail server as the default for the SAS Application Server to provide e-mail services to various SAS clients. For example, with SAS Data Integration Studio, you can use a Publish to Email transformation to alert users about various data changes. In order for the SAS BI Dashboard to send alerts by e-mail to dashboard users and administrators, the port and host name must be configured for the e-mail server.

For more information, see "Overview of Adding or Modifying E-Mail Settings for SAS Application Servers" in the SAS Intelligence Platform: Application Server Administration Guide.

SAS Application Server: Server Context

Enter the name of the server context for the SAS Application Server definition. A server context is a SAS IOM server concept that describes how SAS Application Servers manage client requests. A SAS Application Server has an awareness (or context) of how it is being used and makes decisions based on that awareness. The server context name is prepended to all server names defined in the server context.

For more information, see "Overview of SAS Application Servers" in the SAS Intelligence Platform: Application Server Administration Guide.

Metadata Utility Workspace Server

Enter the name of the logical workspace server and the workspace in metadata. You also need to enter the name of the machine on which the workspace server runs and the port on which the object spawner will listen for client requests to launch workspace servers. The machine name should match the name specified to the object spawner.

Unlike a regular workspace server, access to this server is limited to members of the SAS Administrators group, and its use is limited to metadata server administration tasks such as promotion and backup.

In SAS 9.2, two or more workspace servers can share the same port even if they are running at the same time.

For more information about ports, see "Designating Ports and Multicast Addresses" on page 19.

□ SAS Pooled Workspace Server

Enter the name of the logical pooled workspace server and the pooled workspace in metadata. You also need to enter the name of the machine on which the pooled workspace server runs and the port on which the object spawner will listen for client requests to launch pooled workspace servers. The machine name should match the name specified to the object spawner.

For more information, see "Overview of Workspace Servers and Stored Process Servers" in the SAS Intelligence Platform: System Administration Guide.

□ SAS Table Server

Enter the name of the logical table server in metadata. You also need to enter the name of the machine on which the table server runs and the TCP/IP port on which the table server will listen to.

Metadata Utility SAS DATA Step Batch Server

Enter the various values required to configure a SAS DATA step batch server. The directory fields identify where the deployed SAS program is stored and the name of the deployed SAS DATA step program job. Access to this server is limited to members of the SAS Administrators group, and its use is limited to metadata server backup.

For more information, see "Contents of the Metadata Server Subdirectory (SASMeta)" in the SAS Intelligence Platform: System Administration Guide.

Query Cache Library

Enter the physical location on the file system where the SAS library will exist for temporary files used when creating optimized tables for query look-up.

In **Query Cache Libref**, enter the SAS library reference which SAS will use to refer to the query optimizer SAS library. The name must be eight characters or shorter and should be unique from other librefs used within this repository. Librefs must start with a letter or underscore and contain only letters, numerals, or underscores. The typical installation libref name is wrstemp. The libref will be used in conjunction with the server context name to form the SAS library name for the optimizer library.

Select **Enable Query Cache** to allow the query optimizer to run. If this selection is not made, then the query optimizer will not attempt to optimize queries and will not create temporary data sets for improving performance during rendering. A typical installation will have this selection turned on. The temporary files created within the query cache library will be visible to anyone with Read permission on the Renderer Optimizer directory, so if you have security concerns with the authorization on this folder you might want to leave the optimizer off.

For more information, see "Using the Query Cache" in the SAS Intelligence Platform: Web Application Administration Guide.

Output Management Library

Enter the physical location on the file system where the SAS library will exist for burst set definition tables for reports which will be distributed by e-mail. A burst definition table will contain e-mail addresses, channels, and possibly by group information.

In **Output Management Library Libref**, enter the SAS library reference that SAS will use to refer to the output management SAS library. The name must be eight characters or shorter and should be unique from other librefs used within this Repository. Librefs must start with a letter or underscore and contain only letters, numerals, or underscores. The typical installation libref name is wrsdist. The libref will be used in conjunction with the server context name to form the SAS library name for the distribution library.

For more information, see "Verifying Permissions for the Distribution Library" in the SAS Intelligence Platform: Web Application Administration Guide.

Web Application Server: Automatic Configuration

Select this option for the deployment wizard to automatically build and configure the SAS Web applications as well as configuring a sample Web application server for use with SAS 9.2. (To use this wizard feature, be sure that your Web application server is not running before proceeding. For WebSphere, it's necessary to stop all deployment manager servers, all node agent servers, and all application servers before continuing with your SAS 9.2 deployment. The one exception is on z/OS, where the WebShere web application server should be running.) For more information, see "Choose Whether to Automatically Configure Your Web Application Server" on page 55.

Note: When installing SAS Enterprise BI server to use a WebSphere Base Server, make sure that you choose *not* to have the SAS Deployment Wizard automatically configure your Web application server. \triangle

If you choose not to automatically configure your Web application server, you will still be prompted for Web application server information, and deployment stages such as Configure Products, Deploy Web Applications, and Start Web Application Servers will execute to create instructions for manual deployment. When configuration is complete, follow these manual instructions on how to configure your server and deploy your Web applications. If you manually configure WebLogic, a reference domain will be created in your SAS configuration area, but no servers will be started. If you manually configure JBoss, sample start scripts will be created, but not launched.

For more information, go to http://support.sas.com/resources/ thirdpartysupport/v92 and search for the product name of your Web application server.

Web Application Server: Multiple Managed Servers

Select to have the deployment wizard automatically configure multiple managed servers for you using SAS best practices for choosing the server to deploy each application to.

In some situations it might be preferable to split the SAS Web applications across multiple managed servers. This is usually done for performance reasons.

If you chose to manually configure your application servers, you will be provided with recommended configuration settings in a generated instructions file (Instructions.html) when the SAS Deployment Wizard completes.

More advanced performance configuration considerations are documented in the SAS Intelligence Platform: Web Application Administration Guide which can be found at http://support.sas.com/92administration.

Web Application Server: Managed Server

Enter a logical name for your managed server. This name will be displayed in your application server administrative console and used in administrative scripting.

In **HTTP Port**, enter the unsecured port on which the managed server will listen.

In HTTPS Port, enter the SSL port to be assigned to the managed server.

In **SOAP Port**, (WebSphere only) enter the SOAP port that the WebSphere administrative services will use to communicate with this managed server, if SOAP was selected. This port can also be used by the wsadmin utility.

In **RMI** Port, enter a port using these considerations:

□ WebSphere

This maps to the RMI BOOTSTRAP port. Each server contains an administrative services component and a separate and unique port is required for each application server.

 \Box JBoss

This maps to the default JNDI port. Clients connecting to applications running on JBoss, such as the JBoss shutdown command, would use this port.

□ WebLogic

No RMI port is required for WebLogic.

In **Configured Protocol**, select the communication protocol for the administration server: HTTP or HTTPS. Automated configuration through the SAS Deployment Wizard only supports the HTTP protocol. If you perform a manual configuration, you can set up HTTPS.

In enter any additional Java options that you want the managed server JVM (Java Virtual Machine) to use. These JVM options are tagged onto the end of the managed server's command line. Options that are deployment wizard defaults can be overridden in this way.

For more information, go to http://support.sas.com/resources/ thirdpartysupport/v92 and search for the product name of your Web application server.

□ SAS Shared Services database properties (not displayed when SAS Table Server is selected)

Enter the host name, fully qualified host name, or IP address for the host where the database is installed. Specify the port that the database server is listening to and the name of the database that will contain the SAS Shared Services tables.

Choose Automatically create tables and load data to have the deployment wizard automatically create tables and load the selected pre-existing database with initial data.

In the case of MySQL, the Shared Services configuration process will also create a new MySQL database in addition to creating tables and loading data. The new database is named according to the value specified in the **Database Name** field.

Note: If you are using MySQL, do not specify a pre-existing MySQL database or the configuration will fail. For more information, see "Configuring an Alternative Database for SAS Shared Services" at http://support.sas.com/resources/thirdpartysupport/v92m3/appservers/SharedServicesAlternativeDatabase.pdf. \triangle
For more information, see "About SAS Shared Services" in the SAS Intelligence Platform: Web Application Administration Guide.

SAS Shared Services JDBC Properties

Enter the user account and its password for accessing the database used with your SAS Shared Services tables.

If you have selected to automatically configure the SAS Shared Services database, this user account must have the ability to create tables and insert records. If you are not automatically configuring the SAS Shared Services database, this user account must have the ability to insert, update and delete records. The default user account is the SAS Trusted User account (sastrust@saspw). For more information, see "About SAS Shared Services" in the SAS Intelligence Platform: Web Application Administration Guide.

In the **Directory containing JDBC driver jars** fields enter the appropriate JDBC driver jars and your selected RDBMS database and version. Inappropriate or additional jar files will cause configuration failures, so just copy the minimum required jars to the JDBC driver jars directory.

Web Application Server: Automatic Deployment

Select to automatically deploy SAS 9.2 Web applications to the Web application server. For more information, see "Choose Whether to Automatically Deploy the SAS Web Applications" on page 56.

Regardless of whether you choose to automatically deploy your SAS Web applications, when building Web applications, the wizard also automatically explodes Web application archive files (.EAR files).

If you choose not to automatically deploy SAS Web applications, the deployment wizard writes manual deployment instructions to Instructions.html during the Web application deployment stage, that you will need to complete after the wizard finishes executing. For more information, go to http://support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.

Note: The SAS Deployment Wizard does *not* automatically deploy SAS OnlineDoc for the Web, even when you choose the automatic deployment option. You must manually deploy SAS OnlineDoc for the Web. For more information, see "Deploying SAS OnlineDoc Manually" in the SAS Intelligence Platform: Web Application Administration Guide. \triangle

□ External Account: Web Application Server Administrator

You are prompted for this information if your site uses the WebSphere or WebLogic Web application server. Enter the user ID and password for the administrator account for either the WebSphere Application Server or the WebLogic Server. On Windows, be sure to enter a domain-qualified user ID.

- □ For WebSphere, the Web application server administrator user ID is the administrator account specified when WebSphere Admin Security was enabled.
- □ For WebLogic, the Web application server administrator user ID is used to configure the WebLogic default security realm. When the deployment wizard automatically configures your Web application server, the wizard uses these credentials to create the administrator account and the WebLogic domain.

If you choose to manually configure your Web application server, you will need to create this administrator account (using the credentials you define here) with the WebLogic administrative tools.

For more information about configuring Web application servers to support the SAS middle tier, go to http://support.sas.com/resources/ thirdpartysupport/v92 and search for "WebSphere" or "WebLogic".

Web Application Server: Proxy Information

If you are using SAS Information Delivery Portal RSS feeds, then you will have to provide proxy server information. Enter the fully qualified host name for the proxy server and its port that your site uses to access the Internet.

For **NonProxy Hosts**, enter the DNS names of all the machines that should not be accessed through the proxy server. Be sure to include other machines where application servers are configured as part of a common WebLogic Domain or are part of a WebSphere cell. Separate each machine name with a vertical line character (|). Use an asterisk (*) as a wildcard for an entire subnet. For example, *.subnet.com excludes all machines with a DNS name that ends with .subnet.com.

If your site does not allow Internet access on production systems, refer to configuration information available at this SAS Web site: http://support.sas.com/resources/thirdpartysupport/v92. (Search for your Web application server.)

WebSphere Application Server: Node

In **Profile Name**, enter a profile name, or accept the default (SAShostname01). The profile name is used for the directory that contains the node agent and the SAS Web application server.

The node agent name is required, but cannot be configured using the deployment wizard.

In **Node Name**, enter a node name or accept the default (SAS*hostname*Node). The node name is the WebSphere node that contains one or more of the Web application servers.

In **Additional JVM Options**, enter any additional Java options that you want the Web application servers to use.

IP Multicast

Accept these IP multicast settings or enter new ones.

A multicast group communications protocol is used to communicate among middle-tier SAS applications in a single SAS deployment (the set of applications connected to the same metadata server). The combination of multicast IP address and multicast UDP port should be different for each SAS deployment and also different from those used by other multicast applications at your site. The defaults are most appropriate for deployments in a firewall-isolated data center environment.

For more information, see "Designating Ports and Multicast Addresses" on page 19.

SAS Remote Services Application: JVM

Enter the desired initial heap size for the remote services application using the JVM option format.

In Max JVM Heap Size, enter the desired maximum heap size for the remote services application using the JVM option format.

In Additional JVM Options, enter any additional Java options that you want the Remote Services VM to use. For example, you might want to add -Dmulticast_udp_ip_ttl=1 to restrict multicast traffic to a single subnet based on your network topology.

For more information, go to http://support.sas.com/resources/ thirdpartysupport/v92 and search for "SAS 9.2 Web Applications: Tuning for Performance and Scalability".

$\hfill\square$ SAS Information Delivery Portal unchallenged access

When unchallenged access is enabled, users can access the portal and interact with selected content without providing a user ID and password.

Enter a user ID that SAS will use to grant unchallenged access to portal users. On Windows, make sure to qualify the user ID as appropriate (for example, myDomain\sasguest).

Deselect **Display Search Menu for Unchallenged Access** if you want to suppress the search link from displaying in the main portal banner.

Specify what should appear in the portal banner for unchallenged users:

□ logoff

Display the Log Off link.

🗆 logon

Display the Log On link (which users can click to display the SAS Logon Manager).

🗆 hide

Hide the Log Off and Log On links.

For more information, see "Enabling Unchallenged Portal Access" in SAS Intelligence Platform: Web Application Administration Guide.

SAS Web Report Studio: Scheduling

Choose whether to enable scheduling for SAS Web Report Studio. If Platform Suite for SAS is in your deployment plan, then you have a choice between using Platform Process Manager, provided by Platform Computing, Inc., or SAS In-Process Services.

For more information, see "Setting Up Scheduling Using Platform Suite for SAS" or "Setting Up Scheduling Using SAS In-Process Scheduling" in *Scheduling in SAS*.

SAS Content Server: Repository Directory

Enter the location on the disk for the actual contents of the content repository. For more information, see "Administering the SAS Content Server" in the SAS Intelligence Platform: System Administration Guide.

SAS Web Parts for Microsoft SharePoint: Details

We recommend that you accept the defaults.

The Web URL is the address of the Web application where the SAS Web Parts solution is deployed.

The Site URL is the site collection where the feature is activated. A Web application can have multiple site collections, and a site collection can contain multiple sites. In most instances the URLs are the same (a site collection at the root of the web application), but they can also be different.

For more information, contact your site's SharePoint administrator.

The SAS User ID is the metadata identity that you use to implement shared identity mode. For more information, see "Configure User Access for SAS Web Parts for Microsoft SharePoint" on page 86.

27 When you see the Deployment Summary page, the deployment wizard has finished collecting installation and configuration input. This is the last opportunity to go back and change any information you have provided in previous pages before the wizard begins writing to your system.

Make one of the following choices:

□ Click **Start** to begin installing SAS files and writing the configuration to the current machine.

- □ Click **Back** to navigate to earlier wizard pages to change installation and configuration information previously entered.
- □ Click **Cancel** to terminate the wizard session. Note that you will lose installation and configuration information previously entered.

SAS Deployment Wizard	
Deployment Summary Review the software selected for deployment. This is your last chance to go make changes before writing to your system.	go back and
Stage 1: System Requirements	
🤖 1. System Requirements Wizard	
Stage 2: Installation	
1. Java Platform Standard Edition Runtime Environment	
2. SAS Deployment Manager	
3. SAS/SECURE Java Component	
A DataFlux Integration Server	
a 5. dfPower Studio	
6. SAS Foundation	
7. SAS Management Console	
8. SAS Deployment Tester Plug-in for SAS Management Console	
9. SAS OLAP Server Monitor for SAS Management Console	
10. SAS Table Server Plug-ins for SAS Management Console	
11. SAS Web Infrastructure Client	
12. SAS Data Integration Studio Server Data	
13. SAS BI Report Services	
14. SAS Foundation Services	•
iew Tostall Alert Notes	_
	C Requires user interaction
Help	< Back Start Cancel

On UNIX, when you are installing the server tier, you will be prompted enter the root password. As the message in the installation program explains, certain SAS products and features use functionality that requires SAS to check user ID authentication and file access authorizations. This in turn necessitates that certain files within your SAS installation have setuid permissions and be owned by root.

On Windows, the deployment wizard launches the System Requirements Wizard which checks to make sure that your machine contains the minimum system requirements necessary to run SAS 9.2.

Sometimes, it is necessary to reboot your machine after the wizard has installed certain system components. When this occurs, the wizard prompts you to log back on to the machine, relaunches the SAS Deployment Wizard, and continues to the next configuration step in your SAS deployment process.

When you see a page similar to the following, the SAS Deployment Wizard is finished:



The deployment wizard has installed, configured, and started SAS processes on your machine.

28 Click **Review Manual Configuration Instructions** and complete any necessary manual configuration steps.

The SAS Deployment Wizard writes the Instructions.html file to the **Documents** directory under the SAS configuration path. For example:

 \Box UNIX and z/OS:

/opt/SAS/Lev1/Documents/Instructions.html

 \Box Windows:

C:\SAS\Config\Lev1\Documents\Instructions.html

- 29 Click Finish to close the deployment wizard.
- **30** For multi-machine deployments, back up your metadata repository and your SAS configuration directory before you run the SAS Deployment Wizard on the next machine called for by your deployment plan.
 - □ Make a backup copy of your SAS 9.2 configuration directories by using your site-approved method. Your SAS configuration directories are all the child directories beneath the path that you specified earlier in this procedure on the **Specify Configuration Information** wizard page.
 - □ Back up your Web application server directories.
 - Back up your metadata repository and repository manager on the SAS Metadata Server machine. For more information, see "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.
- 31 If you are deploying a middle-tier machine and opted not to automatically deploy your SAS Web applications, then you must manually deploy them. For more information, go to the Third-Party Software Downloads site at http:// support.sas.com/resources/thirdpartysupport/v92 and search for the product name of your Web application server.

- **32** When you are finished completing any manual configuration tasks, and you have made the necessary backups, repeat the steps listed in this topic on each machine defined in your deployment plan.
- 33 Be sure to restart any servers that you stopped for purposes of creating a backup.
- **34** When you are finished installing and configuring SAS on each machine called for in your deployment plan, proceed to the next section.

Validate the SAS 9.2 Servers

There are a few simple steps required to confirm that the various SAS servers you have deployed are running properly. The following table summarizes server validation information:

Table 5.3 Validation Summary for the SAS Server Tie

Server	Validation Method
Metadata server	Successful login using the SAS Management Console.
Metadata utilityThe metadata utility workspace server can be used only by those nSASMeta) workspaceof the SAS Administrators group who have an external account thserverknown to the server's host and is associated with their SAS identithe server is on Windows and uses credential-based host authentithe account must have the Log on as a batch job user right.	
	Right-click the validate command in SAS Management Console using external account credentials that meet the criteria described above. Default path:
	Server Manager ► SASMeta ► Logical Workspace Server.
Object spawner	If either the stored process server or one of the workspace servers validates (see below), then the object spawner is running.
OLAP server	Right-click the validate command in SAS Management Console. Default path:
	Server Manager \blacktriangleright SASApp \blacktriangleright Logical OLAP Server. ¹
Pooled workspace server	Right-click the validate command in SAS Management Console. Default path:
	Server Manager \blacktriangleright SASApp \blacktriangleright Logical Pooled Workspace Server. ¹
Stored process server	Right-click the validate command in SAS Management Console. Default path:
	Server Manager \blacktriangleright SASApp \blacktriangleright Logical Stored Process Server. ¹
Workspace server	Right-click the validate command in SAS Management Console using external account credentials. Default path:
	Server Manager ► SASApp ► Logical Workspace Server. ¹

Server	Validation Method
DATA step batch server	Successful launch of SAS when running the sasbatch script (Windows and UNIX).
	On z/OS, use the Schedule Manager's Deploy SAS DATA Step Program to browse the appserver_autoexec_usermods.sas file created in the AppServer context.
Grid server	Successful launch of the grid test program found on the SAS Scalability and Performance focus area: http://support.sas.com/rnd/ scalability/grid/gridfunc.html#testprog. For more information, see "Verifying SAS Job Execution" in <i>Grid Computing in SAS</i> .

1 Use the value you entered during the deployment for the server context name. The *default* is SASApp.

This procedure is meant to provide validation for an out-of-the-box, basic deployment. For more complex server configurations, please refer to the appropriate SAS documentation for the server in question.

To validate the SAS server tier that has been deployed using the SAS Deployment Wizard, follow these steps:

- 1 Log on to the machine hosting one or more SAS servers.
- 2 Start SAS Management Console, using the following command for the appropriate operating system:
 - \Box Windows:

Start menu ► Programs ► SAS ► SAS Management Console 9.2

 \Box UNIX:

Type the following command:

sas-installation-directory/sasmc

For example:

/opt/sas/SASManagementConsole/9.2/sasmc

 \Box z/OS:

Use a Windows or UNIX machine on which SAS Management Console is installed and connect to the z/OS machine(s) where the SAS 9.2 server tier is running.

- **3** Log on to the metadata server using a set of valid credentials, such as for the SAS Administrator.
- 4 In SAS Management Console, on the Plug-ins tab, expand the Server Manager node.
- 5 Expand the SAS Application Server node. (The default name is SASApp.)
- 6 Highlight the server you want to validate, such as the SASApp Logical OLAP Server.
- 7 Right-click the highlighted server, and select Validate.

You should see the following message:

Validation Successful!

- 8 Repeat steps 6 and 7 for the other SAS servers:
 - \square pooled workspace server
 - \Box stored process server
 - \square workspace server

- **9** When validating the workspace server, if you are prompted for credentials, we suggest that you enter the credentials for the SAS Spawned Servers account (sassrv). Alternatively, you can enter a user ID and password that meet all of these requirements:
 - $\hfill\square$ The account is known to the host of the workspace server.
 - (An ID that ends in @saspw does not meet this requirement.)
 - □ The account has the Windows right Log on as a batch job (if the server is on Windows).
 - □ The account has a corresponding metadata identity.
- **10** To validate the DATA step batch server on Windows and UNIX, SAS should successfully launch when you run the following command, appropriate for the server host operating system:
 - \Box Windows:
 - Start menu ► Run ► sas-configuration-directory\sasbatch.bat For example:

```
Start menu ► Run ►
C:\SAS\AllServers\Lev1\SASApp\BatchServer\sasbatch.bat
```

 \Box UNIX:

Type the following command:

sas-configuration-directory/SASApp/BatchServer/sasbatch.sh
For example:

```
/opt/sas/AllServers/Lev1/SASApp/BatchServer/sasbatch.sh
```

- 11 To validate the DATA step batch server on z/OS, use the Schedule Manager's Deploy SAS DATA Step Program to browse the appserver_autoexec_usermods.sas file created in the AppServer context. When the JCL pane comes up and contains JCL, then the deployment of the batch server is successful.
 - a From SAS Management Console, right-click the Schedule Manager plug-in (Plug-ins tab) and choose Deploy SAS DATA Step Program.
 - b Click Browse and navigate to the appserver_autoexec_usermods.sas file under a server context such as SASApp (for example, SAS-configuration-directory/Levn/SASApp).
 - c You should see JCL in the bottom list box.
- 12 To verify that your grid servers are operational, follow the steps located in, "Verifying SAS Job Execution" in *Grid Computing in SAS*.
- 13 Repeat these steps on each machine in your deployment plan on which you have deployed one or more SAS servers.

About SAS Deployment Tester

SAS 9.2 ships with a SAS Management Console plug-in that you can use to test your SAS deployment. For more information, see the SAS Management Console Help for the SAS Deployment Tester.

Automating the SAS Installation on Multiple Machines

Overview of Automating the SAS Installation on Multiple Machines

The SAS Deployment Wizard provides a record and playback feature that enables you to automate a SAS installation across multiple machines. This feature is designed for large-scale enterprise deployments where SAS 9.2 clients need to be deployed across many machines. Using the record and playback feature prevents users from having to manually provide input on every page every time the SAS Deployment Wizard is run on a machine. The SAS Deployment Wizard can be run in one of the three playback modes. Each requires you to launch the wizard from the command line with a particular option. After the wizard finishes, you review the log file to verify that the installation completed successfully. Users can choose among three levels of automation when playing back a SAS Deployment Wizard response file.

Note: This same record and playback mechanism also works for the SAS Deployment Manager to automate configuration actions across multiple machines in a SAS deployment. \triangle

CAUTION:

If you choose to use the deployment manager's record and playback mechanism to perform a task that involves passwords, passwords are written to the response file. For greater security, delete the response file (or remove the passwords from the response file) when you are finished. A response file is present only if you use the record and playback mechanism, instead of completing the task manually as documented in the preceding steps. \triangle

The following summarizes the SAS Deployment Wizard record and playback process:

1 Create a response file.

Run the SAS Deployment Wizard once in record mode to create a response file. SAS is not installed or configured; the only output is a response file.

See "Recording a SAS Deployment Wizard Response File" on page 109.

2 Play back the response file to install SAS.

Run the SAS Deployment Wizard to install and configure SAS using the values you previously recorded in the response file.

See "Playing Back a SAS Deployment Wizard Response File" on page 110.

3 Verify that the installation completed successfully.

Check the SAS Deployment Wizard log file for the presence of any errors. See "Verifying the Playback Install" on page 114.

Recording a SAS Deployment Wizard Response File

To use the SAS Deployment Wizard in playback mode, your first step is to create a response file. A *response file* is a text file that contains values for the SAS Deployment Wizard to use to install and configure SAS when running in one of the three playback modes. You create a response file by running the SAS Deployment Wizard in record mode. While in record mode, you interact with the SAS Deployment Wizard as if you are

installing and configuring SAS. However, the SAS Deployment Wizard does not install or configure any software while in record mode. The only output is the response file.

The SAS Deployment Wizard stores any passwords you choose to record in the response file using a fixed-key, 32–bit proprietary encryption algorithm.

The SAS Deployment Wizard resides at the root of the SAS Software Depot directory, or on the root of the SAS media that you are installing from. The following command runs the SAS Deployment Wizard in record mode:

 \Box Windows:

```
setup.exe -record
```

 \Box UNIX:

```
setup.sh -record
```

 \Box z/OS:

```
setup.rexx -record
```

To run the SAS Deployment Wizard, you must be a user who is known to the target machine and who will be available for the long term (to perform future SAS maintenance). On Windows, the installer user should be a member of the Administrators group; on UNIX, use the same account on all machines. For more information, see "Required External User Accounts for SAS" on page 7.

By default, the SAS Deployment Wizard names the response file sdwresponse.properties and writes the file to the current user's home directory. For example, the default path and filename on Windows is as follows:

C:\Documents and Settings\current-user\sdwresponse.properties

To specify a response file that does not use the default name, use the **-responsefile** option. For example, on Windows you might type a command similar to this:

setup.exe -record -responsefile "C:\Program

Files\SAS\response.properties"

If you want, you can force the wizard to deploy SAS during recording mode by using the **-deploy** option. For example, on Windows you might type a command similar to this:

```
setup.exe -record -deploy -responsefile "C:\Program
Files\SAS\response.properties"
```

For information about verifying your deployment, see "Verifying the Playback Install" on page 114.

Playing Back a SAS Deployment Wizard Response File

Overview of Playing Back a SAS Deployment Wizard Response File

There are three playback modes that give users varying levels of automation with the SAS Deployment Wizard:

Mode	Level of Automation	Description
Quiet	High	No visual feedback from the SAS Deployment Wizard.
		See "Installing SAS in Quiet Mode" on page 111.
Partial prompt	Medium	Users only see SAS Deployment Wizard pages for values not contained in the response file.
_		See "Installing SAS in Partial Prompt Mode" on page 112.
Full prompt	Low	Users see all SAS Deployment Wizard pages with response file values supplied. Users can confirm these values or change them.
		See "Installing SAS in Full Prompt Mode" on page 113.

Table 5.4 Playback Modes for the SAS Deployment With	zard
--	------

Installing SAS in Quiet Mode

The SAS Deployment Wizard gives you flexibility in how you automate the SAS installation. The highest level of automated installation is running the SAS Deployment Wizard in quiet mode. In quiet mode, there is no user interface in which you provide installation inputs. The SAS Deployment Wizard uses inputs that you have already provided in the form of a response file to determine how to install and to configure SAS.

The following command runs the SAS Deployment Wizard in quiet playback mode:

 \Box Windows:

```
setup.exe -quiet -wait
```

Note: On Windows, you might also want to specify restart options. For more information, see "Managing a Machine Reboot During Playback (Windows)" on page 112. \triangle

 \Box UNIX:

setup.sh -quiet

 \Box z/OS:

setup.rexx -quiet -wait

Note: For information about -wait, see "Monitoring the SAS Deployment Wizard During Playback" on page 114. \triangle

To run the SAS Deployment Wizard, you must be a user who is known to the target machine and who will be available for the long term (to perform future maintenance). On Windows, the installer user should be a member of the Administrators group; on UNIX, use the same account on all machines. For more information, see "Required External User Accounts for SAS" on page 7.

When running in quiet mode, the SAS Deployment Wizard's default action is to look for its response file by default in the current user's home directory. For example, the default path and filename on Windows is as follows:

C:\Documents and Settings\current-user\sdwresponse.properties

To specify a response file that does not use the default name, use the **-responsefile** *absolute-pathname* option. For example, on Windows you might type a command similar to this:

setup.exe -quiet -responsefile "C:\Program

Files\SAS\response.properties"

For Windows machines, in the event that the machine must be rebooted, use the restart options to avoid having to manually log back on to the machine. For example, you might type a command similar to this:

```
setup.exe -quiet -responsefile "C:\Program
Files\SAS\response.properties" -restartdomain mydomain -restartuserid
myuserid -restartpassword mypassword
```

See the following topics for more information:

- $\hfill\square$ "Managing a Machine Reboot During Playback (Windows)" on page 112
- □ "Verifying the Playback Install" on page 114
- □ "Monitoring the SAS Deployment Wizard During Playback" on page 114

Managing a Machine Reboot During Playback (Windows)

During a deployment on Windows, the SAS Deployment Wizard runs the System Requirements Wizard to check the machine to make sure that it meets the minimum system requirements for SAS 9.2. If certain Microsoft system components that are required by SAS 9.2 are missing, the System Requirements Wizard shuts down the SAS Deployment Wizard, installs the missing components, and reboots the machine.

If you are playing back a response file in quiet mode, you should use the following options in order to log back on to the machine automatically and continue the SAS Deployment Wizard session:

```
-restartdomain domain
```

specifies the authentication domain for the SAS installer user account.

```
-restartuserid SAS-installer-ID
```

specifies the user account that you are logged in under to run the SAS Deployment Wizard to deploy SAS 9.2.

```
-restartpassword password
```

specifies the password for the specified user account.

For example, you might type a command similar to this:

```
setup.exe -quiet -wait -responsefile "C:\Program
Files\SAS\response.properties" -restartdomain mydomain -restartuserid
myuserid -restartpassword mypassword
```

Note: The values entered by using the -restart* command line options are temporarily stored in your Windows registry using the Windows auto logon functionality. In rare circumstances, it is possible those values will remain in your Windows registry after their use, thus posing a potential security risk. For more information about this functionality, including any risks, please refer to Microsoft's documentation about security and automatic logons on their Web site. You should weigh the risks of convenience for automatic logon after restart against the security policies in place at your site. \triangle

Installing SAS in Partial Prompt Mode

The SAS Deployment Wizard gives you flexibility with how you automate the SAS installation. You can fully automate the SAS installation (quiet mode), or you can pick and choose certain parts of the installation to automate (partial prompt mode).

When you run the SAS Deployment Wizard in partial prompt mode, the user sees only those wizard pages for which there are no response file values. There might be situations where it is permissible to automate most of the installation inputs but necessary to prompt for certain sensitive pieces of information. For example, storing user account credentials—even in an encrypted form—might violate a site's corporate security policy. It would require the user to interact with the SAS Deployment Wizard for those pages where user account credentials are entered. The SAS Deployment Wizard resides at the root of the SAS Software Depot directory, or on the root of the SAS media that you are installing from. The following command runs the SAS Deployment Wizard in partial prompt playback mode:

 \Box Windows:

setup.exe -partialprompt

 \Box UNIX:

setup.sh -partialprompt

 \Box z/OS:

setup.rexx -partialprompt

To run the SAS Deployment Wizard, you must be a user who is known to the target machine and who will be available for the long term (to perform future maintenance). On Windows, the installer user should be a member of the Administrators group; on UNIX, use the same account on all machines. For more information, see "Required External User Accounts for SAS" on page 7.

When running in partial prompt mode, the SAS Deployment Wizard's default action is to look for its response file by default in the current user's home directory. For example, the default path and filename on Windows is as follows:

C:\Documents and Settings\current-user\sdwresponse.properties

To specify a response file that does not use the default name, use the **-responsefile** option. For example, on Windows you might type a command similar to this:

setup.exe -partialprompt -responsefile "C:\Program

Files\SAS\response.properties"

For more information, see "Verifying the Playback Install" on page 114.

Installing SAS in Full Prompt Mode

There are three levels of automation from which you can choose when running the SAS Deployment Wizard in playback mode: quiet, partial prompt, and full prompt. Full prompt mode is the least automated of the three modes. When running in full prompt mode, the SAS Deployment Wizard requires user confirmation for all of its pages. However, in full prompt mode, the user is prompted with *default* values that are stored in the response file.

The SAS Deployment Wizard resides at the root of the SAS Software Depot directory, or on the root of the SAS media you are installing from. The following command runs the SAS Deployment Wizard in full prompt playback mode:

Windows:

setup.exe -responsefile absolute-pathname

UNIX:

setup.sh -responsefile absolute-pathname

z/OS:

setup.rexx -responsefile absolute-pathname

To run the SAS Deployment Wizard, you must be a user who is known to the target machine and who will be available for the long term (to perform future maintenance). On Windows, the installer user should be a member of the Administrators group; on UNIX, use the same account on all machines. For more information, see "Required External User Accounts for SAS" on page 7.

When running in full prompt mode, the SAS Deployment Wizard expects you to specify a path and filename to a valid response file. For example, on Windows type the following command:

setup.exe -responsefile "C:\Program Files\SAS\response.properties" For more information, see "Verifying the Playback Install" on page 114.

Verifying the Playback Install

When running in quiet mode, the SAS Deployment Wizard logs the following message after a successful completion:

Deployment completed successfully

If the SAS Deployment Wizard encounters an incorrect or a missing input in the response file, it records a message in its log file and returns an error code of -1. The SAS Deployment Wizard log file resides in the following location:

 \Box Windows:

```
C:\Documents and Settings\current-user\Local Settings\Application Data\SAS\SAS Deployment Wizard\SDW.log
```

```
\Box UNIX and z/OS:
```

~/.SASAppData/SASDeploymentWizard/9.2/SDW.log

Use the -loglevel n option to control the amount of information written by the SAS Deployment Wizard to its log. A change in the logging level is in effect for the current SAS Deployment Wizard invocation only. If you do not specify a log level, then the wizard uses the default (zero). n can be one of the following three values:

0

(default) specifies the least amount of information written to the log. Zero is acceptable for most SAS Deployment Wizard sessions.

1

specifies a medium amount of information written to the log. This value is generally used when working with SAS Technical Support to troubleshoot deployment issues.

 $\mathbf{2}$

specifies the greatest amount of information written to the log and should not be specified except when instructed to by SAS Technical Support.

For example, on Windows, to increase the SAS Deployment Wizard logging level you might type a command similar to this:

```
setup.exe -partialprompt -responsefile "C:\Program
Files\SAS\response.properties" -loglevel 1
```

Monitoring the SAS Deployment Wizard During Playback

Running the SAS Deployment Wizard in quiet mode provides the sought-after effect of suppressing the wizard's user interface. One drawback with the quiet mode is not being able to see the interface, which enables you to monitor the install and to see whether any errors occur. To address this concern, you can use the Task Manager on Windows or periodically issue the **ps** command on UNIX and z/OS to track whether the SAS Deployment Wizard is running.

On Windows, specify the **-wait** option when invoking the SAS Deployment Wizard in quiet mode to cause setup.exe to display and remain in the Windows Task Manager process list.

For example:

```
setup.exe -quiet -wait -responsefile "C:\Program Files\SAS\
response.properties"
```

If you did not use -wait, monitor the process named java.exe.

Note: Use of network management software (such as SMS or Tivoli) might require you to use the **-wait** option when running the SAS Deployment Wizard in quiet mode

in order for such software to determine when the SAS Deployment Wizard finishes executing. Refer to your network management platform documentation for more information. \triangle

On UNIX and z/OS, as with most processes, you issue the **ps** command to monitor the SAS Deployment Wizard running in quiet mode. For more information, see "More About Monitoring the SAS Deployment Wizard on UNIX and z/OS" on page 115.

More About Monitoring the SAS Deployment Wizard on UNIX and z/OS

Remember that output from a **ps** command can be misleading because the process name returned is not always named **setup.sh**. The name might differ because the actual script that the SAS Deployment Wizard is running at any given time varies. However, the process ID remains the same.

For example, if you were to run the SAS Deployment Wizard and immediately issue a **ps** command (before the language dialog box would be displayed), you would see output similar to this:

31762 pts/2 S 0:00 /bin/sh /depot/setup.sh

Note that the shell, /bin/sh, runs the initial script, /depot/setup.sh. The shell is the parent process, and in this example has a process ID of 31762. When setup.sh is finished executing, it passes control to the script, deploywiz.sh. If you were to look at the process list while the SAS Deployment Wizard is running, you would see something similar to the following in a process list:

31762 pts/2 S 0:00 /bin/sh

/tmp/_setup31762/products/deploywiz_9220_prt_xx_sp0_1/deploywiz.sh -startuplocation /depot

-templocation /tmp/_setup31762

The shell /bin/sh is still running and retains the same process ID. However, this shell is running a different script now, deploywiz.sh.

CHAPTER 6

What to Do Next: Administration Tasks

Overview of Administration Tasks 117 First-Priority Setup Tasks 118 Summary of First-Priority Setup Tasks 118 Recommended Operating System Protections for Windows Machines 118 Default Operating System Protections for UNIX and z/OS Machines 120 Standard Setup Tasks 121 Optional Setup Tasks 122 Ongoing System Administration Tasks 124 Best Practices for Ensuring the Integrity of Your System 125 Allow Only the Metadata Server to Access Your Metadata Repositories 125 Use Best Practices for Working with SAS Folders 125

Overview of Administration Tasks

Before you perform the administration tasks that are outlined in this chapter, you should have successfully completed the following tasks:

- □ Use the SAS Deployment Wizard to install and configure your software on each machine in your environment.
- □ Complete the post-installation tasks that are described in your Instructions.html file, which is located in the **Documents** subdirectory of your configuration directory. These tasks include performing manual configuration steps (if applicable), validating your SAS servers, validating your Web applications, and backing up your system.

After the SAS Intelligence Platform has been installed, configured, and validated, you will have a functional system. You can now begin performing administration tasks that are necessary to fully implement the SAS Intelligence Platform in your environment. These include the following categories of tasks:

- □ first-priority setup tasks that are necessary to protect the integrity of your system. You should perform these tasks first, as soon as possible after you have completed your installation.
- □ standard setup tasks that enable the users in your organization to begin using SAS Intelligence Platform client applications to access and analyze your data.
- □ optional setup tasks that you might want to perform to address specific requirements in your environment.
- □ ongoing tasks to keep the SAS Intelligence Platform operational.

First-Priority Setup Tasks

Summary of First-Priority Setup Tasks

The following tasks are necessary to protect the integrity of your system. Complete these steps as soon as possible after installation, before you complete any of the other tasks that are outlined in this chapter.

Table 0.1 FILST-FILOTILY Setup Task	Table 6.1	First-Priority	Setup	Tasks
-------------------------------------	-----------	----------------	-------	-------

Task	Description
Secure the SAS configuration on each server machine.	For a secure deployment, the configuration directory on each server machine must be protected by operating system controls. These controls will prevent inappropriate access to repository data sets, server scripts, server logs, and configuration files.
	On Windows systems, all configuration directories, files, and scripts are owned by the user who performs the installation. You must update the permissions as shown in "Recommended Operating System Protections for Windows Machines" on page 118. These recommendations assume that your SAS servers and spawners run as services under the Local System account.
	On UNIX and z/OS systems, the SAS Deployment Wizard automatically applies the appropriate permissions. The default permissions are shown in "Default Operating System Protections for UNIX and z/OS Machines" on page 120.
Establish a formal, regularly scheduled	Establish a formal, regularly scheduled backup process that includes your metadata repositories as well as the associated physical files.
backup process.	SAS provides backup and restore utilities that enable you to perform correct backups and restores of your metadata repositories, the repository manager, the metadata journal file, and the metadata server configuration files while minimizing disruptions in service. It is important to also back up the physical data that is associated with the metadata so that related information will be synchronized if a restore becomes necessary.
	Before you back up your SAS Intelligence Platform, read "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.

Recommended Operating System Protections for Windows Machines

On Windows server machines, we recommend that you apply the following operating system protections to your configuration directory. All of these directories are located in SAS-configuration-directory \Levn.

Table 6.2 Recommended Operating System Protections on Windows

Directories	Users	Recommended Permissions
SAS-configuration-directory SAS-configuration-directory\ Ley n	SYSTEM and Administrators	Full Control
\Levn subdirectories: Documents, ReportBatch, SASApp, SASMeta, Utilities, Web	All other users	List Folder Contents, Read
\Levn subdirectories: ConnectSpawner, Logs, ObjectSpawner, SASApp\OLAPServer	SYSTEM and	Full Control
SASMeta\MetadataServer, SASTS, ShareServer	Auministrators	Remove all other users and groups
SASApp subdirectories :	SYSTEM,	Full Control
PooledWorkspaceServer, StoredProcessServer	Administrators, and SAS Spawned Servers (sassrv)	Remove all other users and groups
SASApp subdirectories: ConnectServer\Logs, Data\wrsdist, Data\wrstemp, PooledWorkspaceServer\Logs, PooledWorkspaceServer\sasuser, StoredProcessServer\Logs, StoredProcessServer\sasuser, and WorkspaceServer\Logs	SYSTEM, Administrators, and SAS Spawned Servers (sassrv)	Full Control
sague moto of flo	SVSTEM and	Road and Write
sasv9_meta.cig me	Administrators	Remove all other users and groups
SASMeta subdirectories: MetadataServer, MetadataServer\rposmgr, MetadataServer\MetadataRepositories \Foundation Backup destination (for example, SASMeta\MetadataServer\SASBackup)	The user who backs up the metadata server. You can add this user to the Administrators group to provide the required access.	Full Control

Note:

- □ These recommendations assume that your SAS servers and spawners run as services under the Local System account. If servers and spawners are run under a different account, then grant that account the permissions that are recommended for SYSTEM.
- □ You might have selected the custom installation option to place all of your log files in a single directory. If you selected this option, then you will need to grant the SAS Spawned Servers (sassrv) user Full Control of the central log destination (for example, SAS-configuration-directory\Levn\Logs).
- □ If users will be using SAS Enterprise Guide to create stored processes, then the SAS Spawned Servers (sassrv) account must have Write access to the directory in which stored processes will be stored.
- □ If you enable logging for a workspace server, then you will need to grant all users of the workspace server Full Control of the log directory. (See "Create a Log File

for Workspace Server Troubleshooting" in the SAS Intelligence Platform: System Administration Guide).

Δ

For information about backups, see "Using the Backup Wizard in SAS Management Console" and "Using the %OMABAKUP Macro to Perform Backups and Restores" in the SAS Intelligence Platform: System Administration Guide.

For details about the configuration directory structure, see "Overview of the Configuration Directory Structure" in the SAS Intelligence Platform: System Administration Guide.

Default Operating System Protections for UNIX and z/OS Machines

The following table shows the default operating system protections that are provided automatically for configuration directories on UNIX and z/OS machines. All of these directories are located in *SAS-configuration-directory*/Levn.

Directories	Users	Default Permissions
SAS-configuration-directory	SAS Installer	Read, Write, and Execute
SAS-configuration-directory / Levn	All other users	Read and Execute
/Levn subdirectories: Documents, ReportBatch, SASApp, SASMeta, Utilities, Web		
/Levn subdirectories: ConnectSpawner, Logs,	SAS Installer	Read, Write, and Execute
ObjectSpawner, SASApp/OLAPServer, SASMeta/MetadataServer, SASTS, ShareServer	All other users	No access
SASApp subdirectories :	SAS Installer	Read, Write, and Execute
PooledWorkspaceServer, StoredProcessServer	sas group	Read and Execute
SASApp subdirectories : ConnectServer/Logs,	SAS Installer	Read, Write, and Execute
Data/wrsdist, Data/wrstemp, PooledWorkspaceServer/Logs, PooledWorkspaceServer/sasuser, StoredProcessServer/Logs,	sas group	Read, Write, and Execute
StoredProcessServer/sasuser, and		
WorkspaceServer/Logs		
SASMeta/WorkspaceServer/Logs		
sasv9_meta.cfg file	SAS Installer	Read and Write
	All other users	no access

Note:

- □ Make sure that the SAS Spawned Servers account (sassrv) is a member of the sas group, which has the necessary permissions to server configuration files and log directories.
- □ You might have selected the custom installation option to place all of your log files in a single directory. If you selected this option, then you will need to grant either

the sas group or the SAS Spawned Servers (sassrv) user Read, Write, and Execute permission on the central log destination (for example, *SAS-configuration-directory/Levn/Logs*).

- □ If users will be using SAS Enterprise Guide to create stored processes, then the SAS Spawned Servers (sassrv) account must have Write access to the directory in which stored processes will be stored.
- □ If you enable logging for a workspace server, then you will need to grant all users of the workspace server Full Control of the log directory. (See "Create a Log File for Workspace Server Troubleshooting" in the SAS Intelligence Platform: System Administration Guide).
- □ The user who backs up the metadata server must have full access to SAS-configuration-directory/Levn/SASMeta/MetadataServer, to its subdirectories rposmgr and MetadataRepositories/Foundation, and to the backup destination (for example, SAS-configuration-directory/Levn/SASMeta/MetadataServer/SASBackup). The SAS Installer user has the required access.

CAUTION:

Do not run a backup or a restore as the Root user. Doing so will change ownership of the metadata server files. \times

□ For information about backups, see "Using the Backup Wizard in SAS Management Console" and "Using the %OMABAKUP Macro to Perform Backups and Restores" in the SAS Intelligence Platform: System Administration Guide.

For details about the configuration directory structure, see "Overview of the Configuration Directory Structure" in the SAS Intelligence Platform: System Administration Guide.

Δ

Standard Setup Tasks

The following administration tasks are essential to enable the users in your organization to begin using SAS Intelligence Platform client applications to access and analyze your data.

Task	Description
Add users and manage access.	 Standard security setup activities include the following: □ creating SAS administrators and regular SAS users □ managing access to metadata, data, and application functionality
	For details, see "Security Tasks" in the SAS Intelligence Platform: Security Administration Guide.
Establish connectivity to your data sources.	To enable the client applications in the SAS Intelligence Platform to access your data sources (including SAS data sets, third-party relational databases, and data from Enterprise Resource Planning systems), you must create metadata objects that represent your data. For example, to enable users to access data in a library of SAS data sets, you must define metadata objects that represent the SAS library and each of the tables in the library. For details, see "Connecting to Common Data Sources" in the SAS Intelligence Platform: Data Administration Guide.
Set up your metadata folder structure.	SAS Intelligence Platform clients use a hierarchy of SAS folders to store metadata for content such as libraries, tables, OLAP schemas, jobs, information maps, and reports. The initial structure provides private folders for individual users and provides a separate area for shared data. Within these folders, you should create a customized folder structure that meets your specific needs. For details, see "Working with SAS Folders" in the SAS Intelligence Platform: System Administration Guide. Note: Be sure to secure access to the folders as described in the SAS Intelligence Platform: Security Administration Guide. \triangle

Table 6.4	Standard	Setup	Tasks
-----------	----------	-------	-------

Optional Setup Tasks

It might be necessary for you to modify your initial configuration to meet specific requirements in your environment. Optional administration and configuration tasks include the following.

Task	Description		
Optimize the performance and reliability of the metadata server.	 The following are some steps that you might need to take to optimize the performance and reliability of the metadata server: Move the metadata server journal file to another file system (see "Move the Journal File to Another File System" in the SAS Intelligence Platform: System Administration Guide). Adjust the maximum number of threads used by the metadata server (see "Configuring the Number of Threads Used by the Metadata Server" in the SAS Intelligence Platform: System Administration Guide). 		
	For other performance-related tasks, see "Managing Metadata Server Performance" in the SAS Intelligence Platform: System Administration Guide.		
Modify the configuration of your processing servers.	 The following are some server configuration changes that you might want to make for performance optimization or other reasons: Define a cluster of load-balanced workspace servers in order to balance a load across workspace servers that you have installed on multiple hosts. This type of configuration is most useful when you have a large number of users (such as data integration specialists) using a workspace server for relatively long-running jobs. For details, see "Understanding Server Load Balancing" in the SAS Intelligence Platform: Application Server Administration Guide. Modify load balancing or algorithms for stored process servers and pooled workspace servers. For details, see "Modify Logical Pooled Workspace or Logical Stored Process Server Load-Balancing Properties" in the SAS Intelligence Platform: Application Server Administration Server Administration Guide. If your SAS server metadata contains characters other than those typically found in the English language, then you must start your SAS server with an ENCODING= or LOCALE= system option that accommodates those characters. For details, see "Encoding and Locale Information" in the SAS Intelligence Platform: Application Server Administration Guide. If you will be submitting large jobs (for example, JAVA GRAPH jobs) on z/OS servers, then you might need to specify a larger region size. For details, see "Managing Memory" in the SAS Companion for z/OS. 		
Optimize Web application performance.	For information about configuring middle-tier components for better efficiency and performance, see "Best Practices for Configuring Your Middle Tier" in the SAS Intelligence Platform: Web Application Administration Guide.		
Adjust server logging.	You can change your server configurations to obtain additional logging information for troubleshooting, performance management, or other purposes. For details, see "Administering Logging for SAS Servers" in the SAS Intelligence Platform: System Administration Guide and SAS Logging: Configuration and Programming Reference.		

Table 6.5	Optional Setup	Tasks
10010 0.0	optional octup	100100

Task	Description	
Enable job and report scheduling.	To enable SAS scheduling features, you can install and configure scheduling software, configure operating system scheduling, or configure in-process scheduling. For details, see <i>Scheduling in SAS</i> .	
Increase Java heap memory allocation for desktop applications.	To process large amounts of data, you might need to modify the Java heap memory allocation that is configured for SAS Management Console, SAS Data Integration Studio, SAS OLAP Cube Studio, and SAS Information Map Studio. For details, see "Managing the Java Heap Used By Desktop Applications" in the SAS Intelligence Platform: System Administration Guide.	
Set up change management for SAS Data Integration Studio users.	If you want to implement change management for SAS Data Integration Studio, then you must set up project repositories and at least one change-managed folder. For details, see "Administering SAS Data Integration Studio" in the SAS Intelligence Platform: Desktop Application Administration Guide.	
Collect ARM log information for SAS Data Integration Studio batch jobs.	If you want to collect ARM log information for SAS Data Integration Studio jobs that are run on a batch basis, then you must enable logging for the batch server that executes the jobs. For details, see "Collecting ARM Log Information for SAS Data Integration Studio Jobs" in the SAS Intelligence Platform: System Administration Guide.	

Ongoing System Administration Tasks

The following table lists important system administration tasks that you will need to perform on an ongoing basis to keep the SAS Intelligence Platform operational.

Task	Documentation Reference
Start, stop, pause, resume, and refresh the servers that are used in the system.	"Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide
Check the status of a server of or of a metadata repository.	"Checking the Status of Servers" in the SAS Intelligence Platform: System Administration Guide
Monitor the activity of servers.	"Monitoring the Activity of SAS Servers" in the SAS Intelligence Platform: System Administration Guide
Perform regular full backups of the metadata server.	"Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide
Use server logs and configure logging options.	"Administering Logging for SAS Servers" in the SAS Intelligence Platform: System Administration Guide and SAS Logging: Configuration and Programming Reference

 Table 6.6
 Ongoing System Administration Tasks

Task	Documentation Reference
Create a new metadata repository.	"Creating, Registering, Moving, Copying, Renaming, and Deleting SAS Metadata Repositories" in the SAS Intelligence Platform: System Administration Guide
Promote individual metadata objects or groups of objects.	"Using the Promotion Tools" in the SAS Intelligence Platform: System Administration Guide

Note: The preceding table includes only the tasks that are documented in this guide. Other important administration tasks are described in the following documents:

- □ SAS Intelligence Platform: Security Administration Guide. In this guide, you can use the "Checklist for a More Secure Deployment" to ensure that your environment remains secure on an ongoing basis.
- SAS Intelligence Platform: Data Administration Guide
- SAS Intelligence Platform: Application Server Administration Guide
- SAS Intelligence Platform: Desktop Application Administration Guide
- □ SAS Intelligence Platform: Web Application Administration Guide
- \Box Scheduling in SAS
- □ SAS/SHARE User's Guide
- □ SAS/CONNECT User's Guide
- SAS Table Server Administrator's Guide

To access these documents, go to http://support.sas.com/92administration. \triangle

Best Practices for Ensuring the Integrity of Your System

Allow Only the Metadata Server to Access Your Metadata Repositories

The MetadataRepositories and rpsomgr subdirectories, which are located in the SAS configuration directory, are critical to the operation of your system. These data sets contain metadata that defines your servers, users, access levels, enterprise data sources, and data structures. They also contain metadata for resources that are created and used by SAS applications, including information maps, OLAP cubes, report definitions, stored process definitions, and jobs.

To safeguard the integrity of your system:

- □ Never move, delete, modify, or directly read the data sets in the **MetadataRepositories** and **rpsomgr** directories. These data sets should be accessed only by metadata server processes.
- \square Do not place other files in these directories.
- Back up the contents of these directories regularly, as described in "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.

Use Best Practices for Working with SAS Folders

The folders that appear in the **Folders** tab of SAS Management console are used by client applications to store business intelligence content and system information.

Inappropriate renaming, deleting, or moving of these folders or their contents could cause client applications to malfunction.

When interacting with folders in SAS Management Console, be sure to follow the best practices that are provided in "Working with SAS Folders" in the SAS Intelligence *Platform: System Administration Guide*. If you need to move or copy the contents of these folders, use the procedures that are provided in "Using the Promotion Tools" in the SAS Intelligence Platform: System Administration Guide.



Troubleshooting Your Initial SAS 9.2 Deployment

Overview of Troubleshooting Your Initial SAS 9.2 Deployment 127
Review SAS Deployment Tool Documents, Reports, and Logs 128
Troubleshooting the SAS Server Tier 129
Troubleshooting SAS Web Applications 131

Overview of Troubleshooting Your Initial SAS 9.2 Deployment

The SAS Deployment Wizard performs two major functions. Using inputs that you have provided, the wizard installs SAS, and then initially configures SAS. There are many components to a SAS Intelligence Platform deployment, but if one component happens not to deploy properly, it does not mean that you have to repeat the entire deployment. In most cases you can continue with the rest of the SAS deployment, and later troubleshoot the component that failed to deploy.

If you encounter a configuration error while running the SAS Deployment Wizard, follow these steps:

- 1 Read the configuration alert box and, leaving the alert box displayed, take any steps that it suggests.
- 2 After you have performed the steps, go back to the configuration alert box and click **Retry**.
- 3 If the configuration alert box re-appears and you are unable to resolve the issue, try to finish the deployment by clicking **Yes**.
- **4** If the configuration continues to fail, after the wizard completes the entire SAS configuration, you can unconfigure the failed component and reconfigure it.

For more information, see "Removing a SAS Configuration" on page 169.





There can be situations when the configuration failed before the SAS Deployment Manager is properly configured. When this occurs, running the deployment manager is not an option. In these situations, you must do the following:

- \Box Stop the metadata server (if it is running).
- □ Restore the most recent backup of the metadata repository and repository manager that you created before deploying.
- □ Restore the most recent backup of the Web application server directories.
- □ If any servers that failed to configure were installed as services on Windows, manually remove their service definitions.

For more information, see your Microsoft Windows documentation.

□ Manually delete the configuration directories for the SAS components that failed to configure.

Review SAS Deployment Tool Documents, Reports, and Logs

During configuration of SAS 9.2 the SAS Deployment Wizard creates various documents, reports, and logs that can help you identify any remaining configuration tasks and errors. Use the following documents to perform any manual configuration steps and correct any configuration errors:

□ Instructions.html

contains a list of SAS manual steps that must be performed to complete your deployment. Instructions.html resides under the SAS configuration directory in the Levn/Documents subdirectory (for example: C:\SAS\Config92\Lev1\Documents).

DeploymentSummary.html

contains a list of the deployment tasks performed by the SAS Deployment Wizard and a brief status for each. The deployment summary is one source for a list of all the SAS products installed and configured in addition to information such as servers started, Web applications built, and Web applications deployed. **DeploymentSummary.html** resides under the SAS configuration directory in the **Lev***n***/Documents** subdirectory (for example: C:\SAS\Config\Lev1\Documents).

□ ConfigurationErrors.html

contains a list of configuration errors that require further attention. ConfigurationErrors.html resides under the SAS configuration directory in the Levn/Documents subdirectory (for example: C:\SAS\Config\Lev1\Documents).

 \Box UpdateInstructions.html

contains a list of SAS manual steps that must be performed to complete adding maintenance to your deployment. UpdateInstructions.html resides under the SAS configuration directory in the Levn/Documents subdirectory (for example: C:\SAS\Config92\Lev1\Documents).

 \Box Configuration logs (as needed)

provide a finer list of errors for each SAS component that the SAS Deployment Wizard migrates and configures. There is one log file for each SAS component. The configuration logs reside under the SAS configuration directory in the **Levn/Logs/ Configure** subdirectory (for example: C:\SAS\Config\Lev1\Logs\Configure).

□ SDW.log

logs SAS Deployment Wizard messages, which can be used for general troubleshooting. The deployment wizard log is written to the following path:

 \Box Windows:

```
\Documents and Settings\user\Local Settings\Application
Data\SAS\SASDeploymentWizard\9.2
```

 \Box Windows (Vista only):

```
\Users\user\AppData\Local\SAS\SASDeploymentWizard\9.2
```

 \Box UNIX:

home-directory/.SASAppData/SASDeploymentWizard/9.2

\Box SDM.log

logs SAS Deployment Manager messages, which can be used for general troubleshooting. The deployment manager log is written to the following path:

 \Box Windows:

\Documents and Settings\user\Local Settings\Application Data\SAS\SASDeploymentWizard\9.2

- \Box Windows (Vista only):
 - \Users\user\AppData\Local\SAS\SASDeploymentWizard\9.2
- \Box UNIX:

home-directory/.SASAppData/SASDeploymentWizard/9.2

Troubleshooting the SAS Server Tier

The following table lists some SAS server-tier errors and what to do to resolve them.

Table A1.1 Troubleshooting the SAS Server Tier

Error	Explanation	Resolution
When you attempt to run a SAS server for the first time, you receive an error message about the IOMServerAppender not finding a location for storing temporary utility files.	There is no temporary directory defined on the host machine's operating system.	Use the method appropriate for the server machine's operating system to define a temp directory. For more information, see "IOMServerAppender Usage and Best Practices" in SAS Logging: Configuration and Programming Reference.
Pooled workspace server fails to start during the configuration of SAS Shared Services.	One cause for this problem on Windows is that during installation, the SAS installer did not domain qualify the SAS Spawned Servers user account (sassrv). This account is entered as a login in the SAS General Servers group, so it is required to have a domain prefix as are all Windows logins. Without domain qualifying the login, connections by this account become PUBLIC connections. By default, PUBLIC users cannot access the repository, which prevents the pooled workspace server from launching successfully.	Using SAS Management Console, edit the login associated with the SAS General Servers group and add a domain to it (for example: myhost\sassrv). You can edit logins in the Plug-ins] tab of SAS Management Console (User Manager ► SAS General Servers ► Accounts ► Edit).
You cannot validate the logical workspace server from SAS Management Console using the Server Manager plug-in.	By default, the unrestricted user is a SAS internal account. The workspace server needs an operating system user account to be able to authenticate itself to the machine on which it runs.	Re-try the validation from SAS Management Console. You should be prompted for user account credentials. Enter credentials for a user account that the workspace server can authenticate and that has (on Windows) the Log in as a batch job user rights. One account that meets these requirements is the SAS Spawned Servers account (sassrv).

Error	Explanation	Resolution
After you have updated the user's credentials to allow access, you are denied access when trying to connect to or validate a server or spawner.	The credentials cache must be cleared before you try to connect or validate again.	To clear the credentials cache, in SAS Management Console, click File ► Clear Credentials Cache.
		If the object spawner denies access to a server because of the lack of ReadMetadata permissions, and the user is then granted the needed permission, you must reset the object spawner's authorization cache before the user tries to connect again. To do so, expand the Server Manager tree in SAS Management Console. Next, expand the object spawner, right-click the host node, and choose Connect in the pop-up menu. After you have connected, right-click the host node again, and choose Refresh Spawner in the pop-up menu.
Unable to start a pooled workspace server <i>and</i> unable to start a stored	Most likely, something is wrong with the object spawner.	Make sure that the object spawner is running. For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.
process server.	The metadata server might not be able to authenticate the object spawner.	If you cannot start the object spawner, make sure that the metadata server is running.
		Check the log for the object spawner and determine whether the spawner is able to find the server's definition. For more information, see "Using SAS Management Console to Monitor SAS Servers" in the SAS Intelligence Platform: System Administration Guide. Also check the event log on Windows or the syslog on UNIX or z/OS.
		You can correct the credentials used to authenticate the spawner in the SAS-configuration-directory/ ObjectSpawner/metadataConfig.xml file, or reconfigure the spawner using the SAS deployment tools. For more information, see "Overview of Managing Your SAS Deployment" on page 135.
		Make sure that no one has assigned user admin capabilities to the SAS Trusted User account (sastrust@saspw, by default).

Error	Explanation	Resolution
You cannot start your SAS server.	The file sas.servers might not be automatically generated. This does not imply any issue with your configuration and does not indicate something is wrong.	Generate the sas.servers file manually by running SAS-configuration-directory/data/SAS/BIServer/ Levn/generate_boot_scripts.sh. For more information, see "Using the sas.servers Script on UNIX or z/OS to Start or Stop All Servers "in the SAS Intelligence Platform: System Administration Guide.
You see an error message about the location of the JUnit JAR file not being specified for SAS Deployment Tester.	The SAS Deployment Tester tests other products that use JUnit for validation. Without JUnit, these products might operate properly, but you will not be able to validate them using the SAS Deployment Tester.	The JUnit JAR is available from the Third-Party Software Downloads site at http:// support.sas.com/resources/thirdpartysupport/ v92. Place the JUnit JAR in this location: Windows: C:\junit3.8.1\junit.jar UNIX and z/OS: /usr/local/junit3.8.1/junit.jar

Troubleshooting SAS Web Applications

The following table lists some SAS Web application errors and what to do to resolve them.

Error	Explanation	Resolution
SAS Web Report Studio or the SAS Information Delivery Portal displays a "Cannot find server" error.	Either your servlet container or Web application server is not running. There is problem with the	Make sure that your servlet container or Web application server is running. If it is not running, start it. This will probably solve the problem. If the server is already running, the problem could be with the URL that you are using to start the Web application.
	URL that you are using to start the application.	Use the correct URL: http://host-name:port-number/ application-name. Make sure that the host name is the fully qualified name of the host on which your servlet container or Web application server is running. Make sure that the port number identifies the port on which the server is listening. For the JBoss Application Server, this will normally be port 8080. Finally, make sure that the application name in the URL matches the actual name of the Web application (including case).
Each time your Web application requests a new page, there is a long delay.	When a Java Server Page (JSP) is requested for the first time, you can expect a significant delay. When all of your JSPs have been converted to compiled servlets, the problem will be resolved.	Tune your servlet container or Web application server. For example, if you are using the WebLogic Server, the server might be checking (on a per application basis) for updated JSPs and updated compiled servlets. You can suppress these checks by setting an application's JSPPageCheck and ServletReloadCheck properties to -1. See your server vendor's documentation for similar tips.
The SAS Information Delivery Portal displays a "Could not authenticate user" error.	The user is not registered in the metadata repository. On Windows, if the user that is trying to log on is registered in the metadata, but the user name is not domain qualified, the user will not be able to log on.	In SAS Management Console, add a login to the Person object that contains at least a user name. On Windows, make sure the user name has the form <i>host\user-ID</i> or <i>domain\user-ID</i> . For more information, see "About User Administration" in the SAS Intelligence Platform: System Administration Guide.
SAS stored processes run from the SAS Add-In for Microsoft Office, but don't run from the SAS Information Delivery Portal.	The SAS Services Application might not be running.	Start the following in this order: WebDAV Server, SAS Services Application, and your servlet container or Web application server. For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.
You are unable to start the SAS Services Application.	Another application might be using the same port as the SAS Services Application (by default, 5091).	Configure the SAS Services Application to listen on a different port.
You receive a server error when accessing the Help menu from a SAS Web application.	SAS Help Viewer Metadata Configuration is not configured.	Rerun the SAS Deployment Wizard to install and configure SAS Help Viewer Metadata Configuration. For more information, see "Install and Configure SAS Interactively" on page 87.

 Table A1.2
 Troubleshooting the SAS Web Applications

Error	Explanation	Resolution
An error page appears when you access the Help menu from a SAS application or the Help menu item for a SAS application does not display.	The online Help for the SAS application was not installed or the SAS Help Viewer Metadata Configuration Web application was not rebuilt after the online Help was installed.	Verify that the online Help was installed. If not, install it using the SAS Deployment Wizard. Once the Help is installed, rebuild the SAS Help Viewer Metadata Configuration Web application using the SAS Deployment Manager and redeploy the SAS Help Viewer Metadata Configuration EAR. For more information, see "Install and Configure SAS Interactively" on page 87 and "Rebuilding the SAS Web Applications" in the SAS Intelligence Platform: Web Application Administration Guide.
You are having problems running SAS OnlineDoc for the Web.	Most likely, an error occurred during installation and deployment.	You should reinstall SAS Help Viewer for the Web and SAS OnlineDoc for the Web in order to generate a new EAR. For more information, see "Installing SAS OnlineDoc for the Web" on page 75 and "Deploying SAS OnlineDoc Manually for the Web" in the SAS Intelligence Platform: Web Application Administration Guide.

Managing Your SAS Deployment

Overview of Managing Your SAS Deployment 135 Adding, Updating, and Upgrading SAS Software 136 What Is Adding, Updating, and Upgrading? 136 Summary of Adding, Updating, and Upgrading SAS Software 136 How the SAS Deployment Wizard Adds, Updates, and Upgrades Software 137 Remove Update Backup Files 139 Specify a Different JRE 140 Adding SAS Products 141 Overview of Adding SAS Products 141 About SAS Software Orders and SAS Software Depots 142 Add SAS Products that Do Not Require Configuration 142 Add SAS Products that Require Configuration 147 Configuring SAS Products 153 About Configuring SAS Products 153 Configure New SAS Products 153 Configure Updated or Upgraded SAS Products 160 Updating the SID File in Metadata for SAS Solutions 165 About Updating the SID File in Metadata for SAS Solutions 165 About Adding a SAS Solution to Your Deployment 165 About Renewing Your Software License for SAS Solutions 165 Update the SID File in Metadata for SAS Solutions 165 Determine Which SID File to Update in Metadata 169 Removing a SAS Configuration 169 Overview of Removing a SAS Configuration 169 Summary of Steps for Removing a SAS Configuration 171 Identify Dependent SAS Products 172 *Remove a Configuration* 175

Overview of Managing Your SAS Deployment

APPENDIX

The sections that follow discuss how to use the SAS 9.2 deployment tools to add, update, or configure a SAS product, remove a SAS product configuration, and renew your software license for certain SAS solutions.

For information about removing a SAS installation, see "Overview of Uninstalling the SAS Intelligence Platform" on page 177.

Adding, Updating, and Upgrading SAS Software

What Is Adding, Updating, and Upgrading?

This document uses the terms "adding," "updating," and "upgrading" in the following ways.

- □ "Adding" refers to installing and configuring a SAS product that is new to your system. Here are some common scenarios:
 - □ You ordered the SAS product but did not install it.
 - \Box You are deploying new products from a new SAS order.
- "Updating" refers to installing and configuring a SAS product with a maintenance release. Information related to updates resides mainly in *Planning for Maintenance Releases and Product Upgrades for SAS 9.2*. However, configuring updates is also covered in this guide (in "Configure Updated or Upgraded SAS Products" on page 160.)
- "Upgrading" refers to installing and configuring new versions of SAS products that are already deployed on your system (for example, upgrading to SAS Web Report Studio 4.3 from version 4.2). Upgrading should not be confused with migration or promotion.

For more information, see "Upgrading SAS Products" in the *Planning for* Maintenance Releases and Product Upgrades for SAS 9.2.

Summary of Adding, Updating, and Upgrading SAS Software

When you are adding, updating, or upgrading your SAS 9.2 deployment, the SAS Deployment Wizard is able to determine whether the order from which you are running the wizard contains SAS software with a newer, older, or identical release level than what is already deployed in the SAS installation directory (commonly referred to as SAS Home).

If the wizard determines that there is newer SAS software in the current order than what's already deployed, then the wizard automatically goes into *update mode*. Update mode forces you to install updates to your software before you can perform any other deployment task. For example, if you are adding new products or language support to an existing SAS deployment, you will install those in an additional SAS Deployment Wizard session, after the wizard (in update mode) has first updated the products on your machine to match the versions contained in your SAS order.

For more information, see the following:

- "How the SAS Deployment Wizard Adds, Updates, and Upgrades Software" on page 137.
- □ "Remove Update Backup Files" on page 139.
- □ "Specify a Different JRE" on page 140.
- □ "Adding SAS Products" on page 141.
- □ "Configuring SAS Products" on page 153.
- □ Planning for Maintenance Releases and Product Upgrades for SAS 9.2.
How the SAS Deployment Wizard Adds, Updates, and Upgrades Software

This topic describes in greater detail how the SAS Deployment Wizard adds, updates, and upgrades SAS software.

The wizard compares the release version of the SAS software in the current order to the SAS software that is deployed on the machine. Three possibilities exist:

- \Box The software in the order has a *newer* release level than the software deployed on the machine.
- □ The software in the order has an *older* release level than the software deployed on the machine.
- □ The software in the order has an *identical* release level as the software deployed on the machine.

Upgrades and updates consist of a new version or an incremental delta update (also referred to as maintenance) to an installed product. If the deployment wizard detects that one or more products in the order have a *newer* release level than any products deployed in the specified SAS Home on the machine, the wizard goes into update mode. (SAS Home is shorthand for the SAS installation directory (for example, **C:\Program Files\SAS**). The wizard displays an updates page of all the products deployed on the machine for which there are updates in the current order.

🛐 SAS Deployment Wizard		
Review Required Updates Review software that requires updating prior to deployin	ng new softw	ware.
The products listed in the summary below are already installed included in this order. Prior to deploying new software from compatability.	ed in your SA this order, tl	AS Home, but are at an earlier release level than what is these products must be upgraded to ensure
Products to Install:		
SAS Web Application Themes	Installed 9.2	J Updated 9.21
Products to Upgrade:	T	
SAS PI Dashbaard Help and Decumentation	Installed	4.2 M1
SAS Help Viewer for the Web	9.2	9.2 M1
SAS Information Delivery Portal Help and Documentation	4.2	4.2 M1
SAS Web OLAP Viewer for Java Help and Documentation	4.2	4.2 M1
SAS Web Report Studio Help and Documentation	4.2	4.2_M1
Print		
Help		< Back Next > Cancel

The deployment wizard updates page is broken into two sections that list new product versions and new product delta updates (or maintenance). In the example of the updates page shown earlier, SAS Web Application Themes represents a new product version (for example, 9.2 to 9.21). SAS BI Dashboard Help and Documentation represents a delta update (for example, 4.2 to 4.2_M1). If you choose to proceed with your deployment from this order, to the specified SAS Home, the wizard requires that you install these updates to bring your existing deployment to the release level from

which your new order was mastered. When you click **Next**, the wizard automatically upgrades the products to the release levels that are shown on the updates page.

When running in update mode, the wizard displays no deployment plan, SAS installation data file, or language pages down this path. The wizard simply installs the newest versions and delta updates of the product set already deployed in the specified SAS Home. If the update contains updated language support for a specific product (such as, SAS, SAS Enterprise Guide, and SAS Add-In for Microsoft Office), the wizard installs only the update for the languages previously installed. If you are adding new products or language support to an existing SAS deployment, you will install those in an additional SAS Deployment Wizard session, after the update is installed and any customization or validation is performed.

If the deployment wizard detects that one or more products in the software order has an *older* release level than any products deployed in the specified SAS Home on the machine, the wizard does *not* go into update mode. Instead, the wizard presents you with an alert box listing those products in your order that are older than the ones deployed on your machine.



SAS wants to make sure that you are always installing software from an order corresponding to a release level that is identical to or newer than the one used to originally deploy your SAS software. Your options are to use a different software order, designate a different SAS Home directory, or uninstall the products that are newer.

If the deployment wizard detects that all the products in the order have an *identical* release level to all products deployed in the specified SAS Home on the machine, the wizard does *not* go into update mode. Instead, the wizard presents pages that enable you to perform normal deployment tasks such as deploying products, installing additional software, and so on.

The following diagram summarizes how the SAS Deployment Wizard manages deploying products, installing additional software, and applying updates:



Figure A2.1 SAS Deployment Wizard Flowchart

Remove Update Backup Files

Whenever the SAS Deployment Wizard upgrades or updates software on a machine, it creates a backup copy of the software being updated. After you apply the updates, you can use the SAS Update File Cleanup Utility to remove the backup copies to reclaim disk space. To remove update backup files, follow these steps:

- 1 Log on as the SAS Installer user to the machine on which the SAS updates were applied.
- 2 From an operating system prompt, change to the SASHome/InstallMisc/MIT subdirectory.

For example, issue one of the following commands:

 \Box UNIX:

cd /opt/sas_92/InstallMisc/MIT

 \Box Windows:

cd \Program Files\SAS\InstallMisc\MIT

 \square z/OS:

cd /usr/lpp/SAS/SAS_92/InstallMisc/MIT

- **3** Type the following command appropriate for your operating system:
 - \Box UNIX and z/OS:

./cleanup.sh

 \Box Windows:

cleanup.bat

The SAS Update File Cleanup Utility window appears.

🛐 SAS Update File Cleanup Utility 📃 🗔 🗙		
This utility will reclaim disk space used for backups when applying updates, such as maintenance and hot fixes. If you choose to use this utility, you will not be able to recover any file that is removed. Use this utility with caution.		
SAS Home: C:\Program Files\SAS		
Results		
Scanning:		
Deleting:		
Files removed:		
Space reclaimed:		
Remove Backup Files Close		

4 Click Remove Backup Files.

The utility sweeps through the SAS Home directory structure and deletes backup files.

DHD Opdace	File Cleanup Utility
'his utility will rea f you choose to	laim disk space used for backups when applying updates, such as maintenance and hot fixes. use this utility, you will not be able to recover any file that is removed. Use this utility with caution
AS Home: C:\F	rogram Files\SA5
Results	
Scanning:	sas.graph.sganno.nls 902200.4.0.20090610190000 v920m2
~	
Deleting:	META-INF
Deleting: Files removed:	META-INF 49

When the deletion process is complete, the Complete alert box displays.

Complete	e X
٩	The dearing process has completed. For more information on which files were removed, please refer to C:\Program Files\SAS\InstalMsc\InstalLogs\Maintenance\Cleanup_43680.log.
	FOK.

5 Click ok.

The cleanup utility logs which files and directories that it removes in the following location: SASHome/InstallMisc/InstallLogs/Maintenance/Cleanup nnnnn.log.

Specify a Different JRE

During a first-time SAS 9.2 deployment, the SAS Deployment Wizard prompts you for the version of the Java Runtime Environment (JRE) that you want to use with the SAS Java applications. Your options are to have the deployment wizard install a JRE that SAS has certified to run with SAS 9.2, or to point to a JRE that you have already installed.

SAS Deployment Wizard		
Select Java Runtime Environment Select a Java Runtime Environment to use with SAS software.		
The SAS products being installed require a Java Runtime Environment.		
View Information About Supported Java Runtime Environment Ve	rsions	
Use the recommended Java Runtime Environment		
This option ensures that your SAS software is running with the version of t recommended by SAS.	the Java Runtime Environment th	at is
O Select an existing Java Runtime Environment		
The Java Runtime Environment specified below will be used for SAS softwa	re on this machine.	
C:\Program Files\Java\jre1.5.0_12		Browse
Help	< Back Next >	Cancel

In most situations where you are updating or adding a product to SAS 9.2, the deployment wizard does *not* prompt you for a JRE. However, you can override this behavior. To specify a different JRE with which to run SAS Java applications, follow these steps:

1 Log on to the machine on which you run SAS Java applications using the SAS Installer user.

For more information, see "Required External User Accounts for SAS" on page 7.

2 Run the deployment wizard using its command line invocation and add the option -forcejreprompt (for example, setup.exe -forcejreprompt).

For more information, see "Install and Configure SAS Interactively" on page 87.

- **3** During your deployment wizard session, you should see the Select Java Runtime Environment page that prompts you for a JRE path.
- 4 After the deployment wizard has finished executing, change to the SAS installation directory (SAS Home) (for example, C:\Program Files\SAS).
- **5** Open sassw.config in a text editor and update the JREHOME property with the path to the new JRE that you want to use.

For example: JREHOME=C:\Program Files\Java\jre6\bin\java.exe

Adding SAS Products

Overview of Adding SAS Products

The SAS Deployment Wizard enables you to change your SAS 9.2 deployment. Here are some of the most common scenarios:

1 configuring new products from your initial SAS 9.2 order.

For one reason or another, you ordered the software and did not install it. Or you installed the software, but chose not to configure it.

2 deploying additional products from a new SAS 9.2 order.

The additional products are not a part of your original SAS 9.2 order. So you made another order and now have to download and deploy the new order.

3 re-installing and reconfiguring (redeploying) a SAS product.

You want to move the SAS product to a new machine.

4 applying updates (maintenance) to a SAS product that requires also updating its configuration.

For some reason, you were unable to finish applying the updates and you need to rerun the SAS Deployment Manager to complete the updates to your configuration.

Most SAS products require that you install and configure them in a two-step process: You shut down the SAS server and middle tiers and run the SAS Deployment Wizard to install the new products. Then, you restart the SAS server and middle tiers and rerun the deployment wizard to configure the newly installed products.

A few products, such as SAS Drivers for ODBC, do not require the configuration step. You simply shut down the SAS server and middle tiers, install the new products, and then restart what you shut down.

About SAS Software Orders and SAS Software Depots

A SAS Software Depot is a file system that consists of a collection of SAS installation files that represents one or more orders. The depot is organized in a specific format that is meaningful to the SAS Deployment Wizard, which is the tool that is used to install and initially configure SAS. The depot contains the SAS Deployment Wizard executable, one or more deployment plans, SAS installation data files, order data, and product data.

A SAS Software Depot is designed to contain your initial SAS 9.2 software order and additional orders that you make in the future. When you download your additional order to your pre-existing software depot, you download only those products that you don't already have. If you are downloading an additional order and creating a new software depot, then your download time could be longer.

When you add a new SAS software order to your pre-existing SAS Software Depot, you run the SAS Download Manager and specify the location of the original depot. For more information, see "Create a Depot by Using the SAS Download Manager" on page 30.

If you decide that you want to create a new SAS Software Depot for your new software order, you also run the SAS Download Manager. However, first make sure that you have fulfilled the necessary requirements described in "Prerequisites for Creating a SAS Software Depot" on page 30.

Add SAS Products that Do Not Require Configuration

Some SAS products such as SAS Drivers for ODBC do not require the SAS Deployment Wizard to configure them. If the products that you are adding to your SAS deployment do not require configuration, follow these steps:

1 Verify that you have installed all the necessary third-party software outlined in "About Installing Third-Party Products" on page 54.

Note: During the SAS installation, the SAS Deployment Wizard prompts you for paths to the requested third-party software. You must have the necessary

third-party software installed on the current machine, or the SAS Deployment Wizard will *not* let you continue with the installation. In this situation, you will have to end the SAS Deployment Wizard session and install the required third-party software before you can continue. \triangle

2 Make sure that your SAS Software Depot is accessible to all the machines on which you are installing SAS. If this is not possible, then you will have to copy the entire depot to a location that the target machine can access.

For information about copying your depot to a location that is not on your network, see "Create a Disc Image of Your Order" on page 50.

3 If you are installing a SAS 9.2 product that is not a part of your original order, make sure that you have downloaded the additional order.

For more information, see "About SAS Software Orders and SAS Software Depots" on page 142.

4 Shut down your SAS server and middle-tier servers.

For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.

5 Log on to the machine as the SAS Installer user.

This is the user with which your SAS deployment was installed. For more information, see "Required External User Accounts for SAS" on page 7.

6 Start the SAS Deployment Wizard from the highest-level directory in your SAS Software Depot using the command appropriate for your operating system.

Note: If you want to use a different Java Runtime Environment, you must invoke the deployment wizard with a special startup option, **-forcejreprompt**. For more information, see "Specify a Different JRE" on page 140. \triangle

Operating System	Command
Windows	setup.exe -record -deploy
UNIX	setup.sh -record -deploy
z/OS	setup.rexx -record -deploy
	To use a temporary directory other than /tmp, specify
	-templocation new-temp-dir.

Table A2.1 Startup Commands for the SAS Deployment Wizard

For more information, see "Creating SAS Software Depots" on page 29. You should see a welcome page similar to the following:



- 7 Select the language that you want the SAS Deployment Wizard to use when it displays text.
- 8 Select Install SAS Software.
- **9** If you have more than one SAS software order in your depot, the wizard prompts you to select the order that you want to install.
- 10 If the wizard detects that there are SAS software products in your order that are more recent than what you have deployed on your machine, then the wizard automatically goes into update mode. For more information, see "Summary of Adding, Updating, and Upgrading SAS Software" on page 136.

If you need to install product updates, then follow these steps:

- a Install the updates using the SAS Deployment Wizard. For more information, see *Planning for Maintenance Releases and Product Upgrades for SAS 9.2.*
- **b** When you are finished performing any required manual configuration steps, rerun the SAS Deployment Wizard.
- 11 On the Select Deployment Type page, choose Install Additional Software.

SAS Deployment Wizard	
Select Deployment Type Select the type of deployment you want to perform.	
© Perform a Planned Deployment	
Perform a planned deployment of SAS software using a sample deploymer specifically for your site. A planned deployment consists of installing and deployment plan. You may choose to perform these steps independently Install SAS Software	nt plan or a customized deployment plan created configuring the software on each machine in the by unselecting a step below.
☑ Configure SAS Software	
O Install SAS Foundation and Related Software	
Express path for installing SAS Foundation and related software. A plan f	ile is not used for this type of deployment. Ible software. This option is recommended only ed to perform configuration.
Help	< Back Next > Cancel

12 (UNIX and z/OS only) Specify the location (SAS Home) where you want to install SAS.

13 In the Select Products to Install page, select the products that you want to install.

Remember, that the deployment wizard will not configure any of your selections. The wizard only installs the software.

SAS Deployment Wizard	_ [X
Select Products to Install Select the products you want to install on this machine.	0	
Product Search:	Find Next	
Product	Info	
SAS Deployment Tester - Server	0	
SAS Deployment Tester Plug-in for SAS Management Console	Ö	
SAS Drivers for JDBC	Ö	
SAS Drivers for ODBC	Ö	
SAS Enterprise Guide	Ö	
🔲 SAS ESRI Map Manager Plug-in for SAS Management Console	Ö	
SAS Foundation	0	
SAS Foundation Services	Ö	
SAS Help Viewer for the Web	Ō	
SAS Information Delivery Portal	Ö	_
SAS Information Delivery Portal Help and Documentation	Ö	
SAS Information Delivery Portal JPS Extension	0	
SAS Information Map Studio	Ö	
SAS Integration Technologies Client	Ö	
SAS Intelligence Platform Object Framework	Ö	
🗖 SAS Locale Setup Manager	Ö	
SAS Management Console	Ö	-
	-	
Help <a>K Next >	Cancel	

14 Specify the location of the SAS installation data file that contains information about the software that you have licensed for the current machine.

CAUTION:

If you do not use the installation data file that supports the products you are planning to install and configure on this machine, you might experience errors later when you are trying to use the products. \triangle

15 When you see the Deployment Summary page, the deployment wizard has finished collecting installation input. This is the last opportunity to go back and change any information you have provided in previous pages before the wizard begins writing to your system.

Make one of the following choices:

- □ Select **Start** to begin installing SAS files to the current machine.
- □ Select **Back** to navigate to earlier wizard pages to change installation information previously entered.
- □ Select **Cancel** to terminate the wizard session. Note that you will lose installation information previously entered.

SAS Deployment Wizard			_ 🗆 >
Deployment Summary Review the software selected for deployment. This is your last chance to g make changes before writing to your system.	o back and		00
Stage 1: Installation 1. SAS Drivers for ODBC			
View Install Alert Notes		La Requires	user interaction
Help	< Back	Start	Cancel

16 Provide the remaining information as the wizard prompts you for it. For more information, see "Install and Configure SAS Interactively" on page 87.

When you see a page similar to the following, the SAS Deployment Wizard is finished:

SAS Deployment Wizard	
Deployment Complete	
Stage 1: Installation 1. SAS Drivers for ODBC	
	Completed successfully Completed with errors
Help	< Back Next > Cancel

- 17 Click Next to go to the Additional Resources page.
- **18** Click **Finish** to close the deployment wizard.

19 Restart your SAS server and middle tiers.

For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.

Add SAS Products that Require Configuration

Most SAS products that you add to your deployment require that you install and configure them in a two-step process: you shut down the SAS server and middle tiers and run the SAS Deployment Wizard to install the new products. Then, you restart the SAS server and middle tiers and rerun the deployment wizard to configure the newly installed products. If the products that you are adding to your SAS deployment require configuration, follow these steps:

1 Verify that you have installed all the necessary third-party software outlined in "About Installing Third-Party Products" on page 54.

Note: During the SAS installation, the SAS Deployment Wizard prompts you for paths to the requested third-party software. You must have the necessary third-party software installed on the current machine, or the SAS Deployment Wizard will *not* let you continue with the installation. In this situation, you will have to end the SAS Deployment Wizard session and install the required third-party software before you can continue. Δ

2 Make sure that your SAS Software Depot is accessible to all the machines on which you are installing SAS. If this is not possible, then you will have to copy the entire depot to a location that the target machine can access.

For information about copying your depot to a location that is not on your network, see "Create a Disc Image of Your Order" on page 50.

3 If you are installing a SAS 9.2 product that is not a part of your original order, make sure that you have downloaded the additional order.

For more information, see "About SAS Software Orders and SAS Software Depots" on page 142.

4 Make sure that you use a deployment plan that contains any add-on products as well as all original products for each machine that you are configuring.

SAS 9.2 Products Being Added	Location of My Deployment Plan
Are part of my original SAS 9.2 order	In the plan_files directory in the original SAS Software Depot
Are on a machine where a SAS 9.2 server, middle tier, or data tier already resides	In the SAS configuration directory in the Utilities directory
Are part of my new SAS 9.2 order	In the plan_files directory in the SAS Software Depot

Table A2.2 Where is My Deployment Plan?

5 Shut down your SAS server and middle tier servers.

For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.

- **6** If you have a multiple-machine SAS deployment, it is important to run the SAS Deployment Wizard using your new deployment plan on every machine, following this order:
 - a Metadata server
 - **b** SAS servers
 - c SAS data servers
 - d SAS middle-tier servers

e SAS clients

If the SAS software requires updates, the the deployment wizard will go into update mode. When you have finished updating, rerun the wizard to install any additional SAS software that the new add-on product might require. Do this on each each machine following the sequence earlier specified.

7 Log on to the machine as the SAS Installer user.

This is the user with which your SAS deployment was installed. For more information, see "Required External User Accounts for SAS" on page 7.

8 Start the SAS Deployment Wizard from the highest-level directory in your SAS Software Depot using the command appropriate for your operating system:

Note: If you want to use a different Java Runtime Environment, you must invoke the deployment wizard with a special startup option, **-forcejreprompt**. For more information, see "Specify a Different JRE" on page 140. \triangle

Table A2.3 Startup Commands for the SAS Deployment Wizard

Operating System	Command
Windows	setup.exe -record -deploy
UNIX	setup.sh -record -deploy
z/OS	setup.rexx -record -deploy
	To use a temporary directory other than /tmp , specify
	-templocation new-temp-dir.

For more information, see "Creating SAS Software Depots" on page 29. You should see a welcome page similar to the following:

SAS Deployment Wizard	
<u>s</u> .sas	
	SAS [®] Deployment Wizard 9.2
THE POWER TO KNOW.	
Copyright © 2010, SAS Instit	ute Inc., Cary, NC, USA. All Rights Reserved

9 Select the language that you want the SAS Deployment Wizard to use when it displays text.

10 Select Install SAS Software.

11 If you have more than one SAS software order in your depot, the wizard prompts you to select the order that you want to install.

12 If the wizard detects that there are SAS software products in your order that are more recent than what you have deployed on your machine, then the wizard automatically goes into update mode.

For more information, see "Adding, Updating, and Upgrading SAS Software" on page 136.

If you need to install product updates, then follow these steps:

- a Install the updates using the SAS Deployment Wizard. For more information, see *Planning for Maintenance Releases and Product Upgrades for SAS 9.2.*
- **b** When you are finished performing any required manual configuration steps, rerun the SAS Deployment Wizard.
- 13 On the Select Deployment Type page, choose Perform a Planned Deployment and Install SAS Software.

Note: Make sure that Configure SAS Software is deselected. \triangle

SAS Deployment Wizard	
Select Deployment Type	00
Delett the type of deployment you want to perform.	0
• Perform a Planned Deployment	
Perform a planned deployment of SAS software using a sample deploymen specifically for your site. A planned deployment consists of installing and o deployment plan. You may choose to perform these steps independently	it plan or a customized deployment plan created configuring the software on each machine in the by unselecting a step below.
Install SAS Software	
Configure SAS Software	
C Install SAS Foundation and Related Software	
Express path for installing SAS Foundation and related software. A plan f	ile is not used for this type of deployment.
C Install Additional Software	
Perform individual installs of SAS software by selecting from a list of availa when you want to add software to an existing deployment and do not nee	ble software. This option is recommended only ed to perform configuration.
Help	< Back Next > Cancel
	Concernation

- 14 (UNIX and z/OS only) Specify the location (SAS Home) where you want to install SAS.
- 15 Specify the type of deployment plan you are using.
 - \Box customized deployment plan

Choose Specify the full path to a customized deployment plan, and then click Browse to navigate to the plan file.

 $\hfill\square$ standard deployment plan

Choose Select a standard deployment plan, and then choose the appropriate plan in the drop-down list.

SAS Deployment Wizard	_ 🗆 ×
Specify Deployment Plan Specify a customized or standard deployment plan.	00
© Specify the full path to a customized deployment plan	
{\image.unx.sas.com\sasvcd\shipevents\ship920_09w38\rmdtest.20090729\plan_files	Browse
© Select a standard deployment plan	
EBI EDI EG, three machines, JBoss	-
Details of the selected deployment plan:	
Note: Products in bold text are either not available in this order or are not supported on this platform.	
Server	
Software to Install	
1. DataFlux Integration Server	
2. SAS Foundation	
 5AS Management Console 5AS Deployment Tester Plug-in for SAS Management Console 	
5. SAS OLAP Server Monitor for SAS Management Console	
6. SAS Table Server Plug-ins for SAS Management Console	
8. SAS Data Integration Studio Server Data	-
· · ·	
Help < Back Next >	Cancel

- **16** Select the machine on which you are installing, and select the SAS products that you want to install, by doing the following:
 - a Select the machine on which you are installing software from the Machine drop-down list.

Note: If you are deploying SAS on multiple machines, make sure that you are following the process described in "Installation Order Rules for Multiple Machine Deployments" on page 67. \triangle

- **b** By default, all products displayed will be installed. Leave all products selected. If there are no product changes, then the deployment wizard will not re-install any pre-existing products.
- 17 If you are installing SAS on a Windows 64-bit operating system, you will see a wizard page that asks you which mode you want to install SAS Foundation in (32-bit or 64-bit mode). The advantage to installing SAS in 64-bit mode is that you can access memory beyond the four GB limit imposed by the 32-bit Windows operating system. For more information, consult the deployment wizard online Help.
- 18 Specify the location of the SAS installation data file that contains information about the software that you have licensed for the current machine.

CAUTION:

If you do not use the installation data file that supports the products you are planning to install and configure on this machine, you might experience errors later when you are trying to use the products. \triangle

19 (z/OS only) Provide input for the following prompts:

Note: For more information, see the Configuration Guide for SAS 9.2 Foundation for z/OS, available on the SAS Install Center (http://support.sas.com/documentation/installcenter/). \triangle

□ FTP Batch Generation

Specify the fully qualified host name or IP address of the z/OS mainframe machine on which you are deploying SAS. Also supply a valid user ID and

password with which the SAS Deployment Wizard will FTP deployment information to the mainframe machine.

Specify Jobcard Information

Specify the job account, programmer name, message class, message level, time, and region values. For more information, consult your z/OS documentation.

Select Installation Action

Choose A - Install a new SAS system.

Specify New Installation Qualifier

Specify the path where you want to install SAS. You can also choose to require Storage Management Subsystem (SMS) parameters. For more information, consult your z/OS documentation.

Specify IBM's SMS Parameters

If you chose to require Storage Management Subsystem (SMS) parameters on the previous page, enter them here. For more information, consult your z/OS documentation.

Specify Parameters

These are all parameters that are used in various DD statements throughout the installation. For more information, consult your IBM JCL documentation.

□ Specify Entry Point

Specify the parameters for various ways that SAS can be run with different performance implications. Choose **SAS** (default ENTRY point) to run the unbundled configuration. Choose **SASB** to run the bundled configuration. Choose **SASLPA** to run the bundled configuration with some modules installed in the Link Pack Area (LPA).

Specify Parameters

Specify additional parameters for DD statements. VOLDISK designates the VOLSER that the installed data sets will go to. For more information, consult your IBM JCL documentation.

Specify Parameters

Specify parameters used for reblocking the SAS load modules to a library with an optimum block size.

- **20** Deselect any languages that you do not want SAS to support. By default, SAS attempts to support all languages that your machine's operating system is configured for.
- **21** Review the list of required third-party software that is required for the SAS software that you are installing on the current machine. (The list of third-party software depends on the SAS software that you are installing on the current machine.)
- **22** In the pages that immediately follow, be prepared to provide paths to these third-party applications. (The number of pages varies depending on the SAS software you are deploying on the current machine.)

Note: You must provide valid paths to the requested third-party software, or the SAS Deployment Wizard will *not* let you continue with the installation. \triangle

23 The SAS Deployment Wizard has finished collecting installation input. This is the last opportunity to go back and change any information you have provided in previous pages before the wizard begins writing to your system.

Make one of the following choices:

□ Select **Start** to begin installing SAS files to the current machine.

- □ Select **Back** to navigate to earlier wizard pages to change installation information previously entered.
- □ Select **Cancel** to terminate the wizard session. Note that you will lose installation information previously entered.

§ SAS Deployment Wizard	- O ×
Deployment Summary Review the software selected for deployment. This is your last chance to g make changes before writing to your system.	go back and
Stage 1: Installation 1. SAS Deployment Manager 2. SAS Deployment Tester - Server 3. SAS Deployment Tester - Server (Update) 4. SAS Deployment Tester - Client 5. SAS Deployment Tester - Client (Update)	
View Install Alert Notes	Ce Requires user interaction
Help	< Back Start Cancel

When you see a page similar to the following, the SAS Deployment Wizard is finished:

SAS Deployment Wizard	_ 🗆 ×
Deployment Complete	
Stage 1: Installation I. SAS Deployment Manager I. SAS Deployment Tester - Server I. SAS Deployment Tester - Server (Update) I. SAS Deployment Tester - Client I. SAS Deployment Tester - Client I. SAS Deployment Tester - Client (Update) I. SAS Deployment Tester - Client (Update)	Completed successfully Completed with errors Requires user interaction
Help	<back next=""> Cancel</back>

24 Click Next to go to the Additional Resources page.

SAS Deployment Wizard	
Additional Resources Below are links to additional resources for your deployment.	
5AS Customer Support Center	
http://support.sas.com	
5A5 Install Center	
http://support.sas.com/documentation/installcenter/92/index.html	
5AS Technical Support	
ttp://support.sas.com/techsup	
5AS Software Downloads	
http://www.sas.com/apps/demosdownloads/setupintro.jsp	
5AS Training	
http://support.sas.com/training	
Print	
Help	< Pack Finish Cancel
4 Hell 1	K Daux Pinish Canter

- 25 Click Finish to close the deployment wizard.
- 26 To configure the SAS products that you just installed, proceed to "Configure New SAS Products" on page 153.

Configuring SAS Products

About Configuring SAS Products

You can configure SAS products that are new to your deployment, or configure SAS products that you are updating or upgrading:

- □ "Configure New SAS Products" on page 153
- □ "Configure Updated or Upgraded SAS Products" on page 160

Configure New SAS Products

Follow these steps to use the SAS Deployment Wizard to configure SAS products that you have already installed.

1 Make sure that the machine where you want to add the new SAS 9.2 software contains the necessary user accounts, groups, and ports.

For more information, see Chapter 2, "Setting Up Users, Groups, and Ports," on page 5.

2 Make a backup copy of your SAS 9.2 configuration directories by using your site-approved method. Your SAS configuration directories are all the child directories beneath the configuration path that was specified during the initial SAS 9.2 deployment on the Specify Configuration Information wizard page.

- **3** Back up your metadata repository and repository manager on the SAS Metadata Server machine. For more information, see "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.
- **4** If you are reconfiguring SAS Web Parts for Microsoft SharePoint that was deployed manually, read the following topic before proceeding: "Reconfigure a Manual Deployment of SAS Web Parts for Microsoft SharePoint "in the SAS Intelligence Platform: Web Application Administration Guide.
- **5** Make sure that your SAS server and middle tiers are running.

For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.

6 Make sure that you use a deployment plan that contains any add-on products as well as all original products for the machine that you are configuring.

SAS 9.2 Products Being Added	Location of My Deployment Plan
Are part of my original SAS 9.2 order	In the plan_files directory in the original SAS Software Depot
Are on a machine where a SAS 9.2 server, middle tier, or data tier already resides	In the SAS configuration directory in the Utilities directory
Are part of my new SAS 9.2 order	In the plan_files directory in the SAS Software Depot

Table A2.4 Where is My Deployment Plan?

- 7 Log on to the machine on which you want to add the new SAS 9.2 products as the SAS Installer user. This is the user with which your SAS deployment was installed. For more information, see "Required External User Accounts for SAS" on page 7.
- 8 Start the SAS Deployment Wizard from the highest-level directory in your SAS Software Depot using the command appropriate for your operating system.

Note: If you want to use a different Java Runtime Environment, you must invoke the deployment wizard with a special startup option, **-forcejreprompt**. For more information, see "Specify a Different JRE" on page 140. \triangle

Command	
setup.exe -record -deploy	
setup.sh -record -deploy	
setup.rexx -record -deploy	
To use a temporary directory other than /tmp , specify -templocation new-temp-dir.	
	Command setup.exe -record -deploy setup.sh -record -deploy setup.rexx -record -deploy To use a temporary directory other than /tmp, specify -templocation new-temp-dir.

 Table A2.5
 Startup Commands for the SAS Deployment Wizard

For more information, see "Creating SAS Software Depots" on page 29. You should see a welcome page similar to the following:



- **9** Select the language that you want the SAS Deployment Wizard to use when it displays text.
- 10 Select Install SAS Software.
- **11** If you have more than one SAS software order in your depot, the wizard prompts you to select the order that you want to configure.
- 12 If the wizard detects that there are SAS software products in your order that are more recent than what you have deployed on your machine, then the wizard automatically goes into update mode.

For more information, see "Adding, Updating, and Upgrading SAS Software" on page 136.

If you need to install product updates, then follow these steps:

- a Install the updates using the SAS Deployment Wizard. For more information, see *Planning for Maintenance Releases and Product Upgrades for SAS 9.2.*
- **b** When you are finished performing any required manual configuration steps, rerun the SAS Deployment Wizard.

13 Select Perform a Planned Deployment and Configure SAS Software.

Note: Make sure that Install SAS Software is deselected. \triangle

SAS Deployment Wizard	
Select Deployment Type Select the type of deployment you want to perform.	
© Perform a Planned Deployment	
Perform a planned deployment of SAS software using a sample deployment specifically for your site. A planned deployment consists of installing and c deployment plan. You may choose to perform these steps independently I	It plan or a customized deployment plan created configuring the software on each machine in the by unselecting a step below.
Install SAS Software	
Configure SAS Software	
C Install SAS Foundation and Related Software	
Express path for installing SAS Foundation and related software. A plan fi	le is not used for this type of deployment.
C Install Additional Software	
Perform individual installs of SAS software by selecting from a list of availal when you want to add software to an existing deployment and do not nee	ble software. This option is recommended only ed to perform configuration.
Help	< Back Next > Cancel

14 Specify the type of deployment plan you are using.

□ customized deployment plan

Choose Specify the full path to a customized deployment plan, and then click Browse to navigate to the plan file.

 \Box standard deployment plan

Choose Select a standard deployment plan, and then choose the appropriate plan in the drop-down list.

SAS Deployment Wizard	
Specify Deployment Plan Specify a customized or standard deployment plan.	
C Specify the full path to a customized deployment plan	
\\image.unx.sas.com\sasvcd\shipevents\ship920_09w38\rmdtest.20090729\plan_files	Browse
© Select a standard deployment plan	
EBI EDI EG, three machines, JBoss	
Details of the selected deployment plan:	
Note: Products in bold text are either not available in this order or are not supported on this platform. <u>Server</u>	-
Software to Install	
 DataFlux Integration Server SAS Foundation SAS Management Console SAS Deployment Tester Plug-in for SAS Management Console SAS OLAP Server Monitor for SAS Management Console SAS Table Server Plug-ins for SAS Management Console SAS Table Server Plug-ins for SAS Management Console SAS Web Infrastructure Client SAS Data Integration Studio Server Data 	*
Help <a>Back Next >	Cancel

15 If there are multiple machines in your SAS deployment, select the machine on which you are configuring.

The deployment wizard lists the SAS products in your order that should be installed on the machine.

16 Choose either the **Typical** or the **Custom** configuration prompting level. You want to be able to access the configuration page where you can set the SAS Metadata Server. The Express prompt level does not allow you to access this SAS server configuration setting.

Note: When reconfiguring SAS 9.2 products, make sure that you specify the metadata repository name if the one you are using has a name other than the default (Foundation). To access the deployment wizard page to specify a custom repository name, choose the Custom configuration prompting level. \triangle

Refer to "Interactive Prompting Levels" on page 69 for more information about the SAS Deployment Wizard prompting levels.

- **17** On the Specify Configuration Information page, specify the configuration directory and level for your current SAS deployment to which you are adding the new configuration.
- 18 If you are adding the products you are configuring to an existing SAS deployment, you are asked to confirm your selection.



19 In the Select Products to Configure page, choose only those products that you want to configure on the machine.

The SAS Deployment Wizard has queried the metadata about your current configuration and checked the appropriate products to be configured.

We recommend that you accept the product selections displayed on this page.

Note: Any time that you configure your deployment you must also configure your Web application server, even if your configuration does not involve your SAS middle tier. If you manually configured the Web application server when you deployed SAS 9.2, then configure it again manually. If the deployment wizard automatically configured your Web application server, then choose the automatic configuration option. \triangle

SAS Deployment Wizard	
Select Products to Configure Select the products you want to configure on this machine.	
Product Search:	Find Next
A Some products are not listed because they are either not available in this order or are not supported on this pla	atform.
Product	
1 SAS Stored Process Server	
SAS Table Server	
SAS Workspace Server	
SAS/CONNECT Server Configuration	
SAS/SHARE Server Configuration	
SAS Add-in for MS Office Server Data	
SAS BI Report Services Workspace Configuration	
🔲 SAS Data Integration Studio Server Data	
SAS Enterprise Guide Server Data	
SAS Management Console Server Data	
SAS BI Report Services	
SAS Deployment Tester - Server	
SAS Deployment Tester - Client	
SAS Client Connection Profile Configuration	-
Select All Clear All	
Help < Back Next >	Cancel

- **20** Provide the remaining configuration information as the wizard prompts you for it. (The actual number of configuration pages you must provide input for depends on the prompt level that you chose.) For more information, see "Install and Configure SAS Interactively" on page 87.
- **21** When you see the Deployment Summary page, the deployment wizard has finished collecting configuration input. This is the last opportunity to go back and change any information you have provided in previous pages before the wizard begins writing to your system.

Make one of the following choices:

- □ Select **Start** to begin writing the configuration to the current machine.
- □ Select **Back** to navigate to earlier wizard pages to change configuration information previously entered.
- □ Select **Cancel** to terminate the wizard session. Note that you will lose configuration information previously entered.

🛐 SAS Deployment Wizard	
Deployment Summary Review the software selected for deployment. This is your last chance to go make changes before writing to your system.	o back and
Stage 1: Installation 1. SAS Deployment Manager Stage 2: Initialize Configuration Directory 1. SAS Deployment Manager Stage 3: Configure Products 1. SAS Application Server Context 3. SAS Deployment Tester - Server Stage 4: Run Post-configuration Tasks 1. SAS Deployment Manager	
View Install Alert Notes Help	Ce Requires user interaction

When you see a page similar to the following, the SAS Deployment Wizard is finished:

SAS Deployment Wizard	
Deployment Complete	
Stage 1: Installation	
1. SAS Deployment Manager	
Stage 2: Initialize Configuration Directory	
 1. SAS Deployment Manager 	
Stage 3: Configure Products	
1. SAS Deployment Manager	
2. SAS Application Server Context	
3. SAS Deployment Tester - Server	
Stage 4: Run Post-configuration Tasks 1. SAS Deployment Manager	
	Constant automatical
	Completed soccessions
	Completed with errors
	C Requires user interaction
Help	< Back Next > Cancel

22 Click Next to go to the Additional Resources page.

SAS Deployment Wizard	-	. 🗆 🗙
Additional Resources Below are links to additional resources for your deployment.		
Review Manual Configuration Instructions Manual steps are required to complete your configuration. You can view these C:\SAS\EBIEDIEG\Lev1\Documents\Instructions.html.	se steps in	_
SAS Customer Support Center http://support.sas.com		
SAS Install Center http://support.sas.com/documentation/installcenter/92/index.html		
SAS Technical Support http://support.sas.com/techsup		
SAS Software Downloads http://www.sas.com/apps/demosdownloads/setupintro.jsp		
SAS Training http://support.sas.com/training		
Print		
Help	< Back Finish Cance	el 🔤

23 Click **Review Manual Configuration Instructions** and complete any necessary manual configuration steps.

The SAS Deployment Wizard writes the Instructions.html file to the Documents directory on the SAS configuration path. For example:

 \Box UNIX and z/OS:

/opt/SAS/Lev1/Documents/Instructions.html

 \square Windows:

C:\SAS\Config\Lev1\Documents\Instructions.html

Note: The wizard backs up your previous Instructions.html file to the **Backup** subdirectory under the **Documents** directory on the SAS configuration path (for example, C:\SAS\Config\Lev1\Documents\Backup\Instructions.html_YYYY-MM-DD-HH.MM.bak). \triangle

- 24 Click Finish to close the deployment wizard.
- **25** When you are configuring SAS Web applications, restart the SAS Services Application (Remote Services).

On Windows, you must restart the SAS Services Application (Remote Services) from a Windows command line, using the **RemoteServices.bat** -start command. For more information, see "Starting or Stopping the SAS Services Application" in the SAS Intelligence Platform: System Administration Guide.

- **26** For multi-machine deployments, back up your metadata repository and your SAS configuration directory before you run the SAS Deployment Wizard on the next machine called for by your deployment plan.
 - □ Make a backup copy of your SAS 9.2 configuration directories by using your site-approved method. Your SAS configuration directories are all the child directories beneath the path that you specified earlier in this procedure on the Specify Configuration Information wizard page.
 - Back up your metadata repository and repository manager on the SAS Metadata Server machine. For more information, see "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.

- **27** When you are finished completing any manual configuration tasks, and you have made the necessary backups, repeat these steps listed in this topic on each machine defined in your deployment plan.
- 28 When you are finished installing and configuring SAS on each machine called for in your deployment plan, proceed to the section, "Validate the SAS 9.2 Servers" on page 106.

Note: If you encounter error messages about your SAS license expiring, you might need to perform another procedure to correct this. For more information, see "About Adding a SAS Solution to Your Deployment" on page 165. \triangle

Configure Updated or Upgraded SAS Products

Follow these steps to use the SAS Deployment Manager to configure SAS products for which you have already installed updates or upgrades.

- 1 Make a backup copy of your SAS 9.2 configuration directories by using your site-approved method. Your SAS configuration directories are all the child directories beneath the configuration path that was specified during the initial SAS 9.2 deployment on the Specify Configuration Information wizard page.
- 2 Back up your metadata repository and repository manager on the SAS Metadata Server machine. For more information, see "Best Practices for Backing Up and Restoring Your System" in the SAS Intelligence Platform: System Administration Guide.
- 3 Make sure that your SAS server and middle tiers are running.

For more information, see "Operating Your Servers" in the SAS Intelligence Platform: System Administration Guide.

- 4 If you are reconfiguring SAS Web Parts for Microsoft SharePoint that was deployed manually, read the following topic before proceeding: "Reconfigure a Manual Deployment of SAS Web Parts for Microsoft SharePoint "in the SAS Intelligence Platform: Web Application Administration Guide.
- **5** Log on to the machine on which you want to update the SAS product configuration as the SAS Installer user. This is the user with which your SAS deployment was installed and updated. For more information, see "Required External User Accounts for SAS" on page 7.
- 6 On the host machine for the products whose configurations you are updating, navigate to SAS-installation-directory/SASDeploymentManager/9.2 and launch config.exe (Windows), config.sh (UNIX), or config.rexx (z/OS). On Windows, you can use the shortcut on the Start menu.
- 7 In the SAS Deployment Manager, select Update Existing Configuration.

SAS Deployment Manager	۱×
Select Configuration Task Select the configuration task you would like to perform.	
C Update Passwords	
Update passwords for selected users in an existing configuration.	
C Rebuild Web Applications	
Rebuild Web applications previously configured in an existing configuration.	
C Remove Existing Configuration	
Remove configuration content for an existing configuration. Installed products will not be removed.	
Remove user content for SAS Information Delivery Portal	
C Update SID File in Metadata	
Update the SID file in metadata to license certain SAS mid-tier products. SAS Foundation software is not affected by this option.	
C Update Host Name References	
Update host name references in an existing configuration.	
© Update Existing Configuration	
Update an existing configuration with maintenance or newer versions of existing products.	
Help Cancel	

8 In the next page, specify the configuration directory and the level (for example, Lev1) that you want to update.

Note: Any time that you configure your deployment you must also configure your Web application server, even if your configuration does not involve your SAS middle tier. If you manually configured the Web application server when you deployed SAS 9.2, then configure it again manually. If the deployment wizard automatically configured your Web application server, then choose the automatic configuration option. \triangle

SAS Deployment Manager	
Select Configuration Directory/Level Select the configuration directory and the level within the configuration dire manage.	ectory to
© Select Configuration Directory	
Configuration Directory	Configuration Level
C:\SAS\Config	Lev1
C:\SAS\EBIEDIEG	Lev1
C Enter Configuration Directory and Level	
	Browse
Configuration Level:	
Lev1 💌	
Help	< Back Next > Cancel

- 9 If you are running in a UNIX environment, restart the SAS Metadata Server:
 - **a** At a UNIX prompt, navigate to the directory where the SAS Metadata Server is configured.
 - **b** Type ./MetadataServer.sh start .
- **10** In the next page, enter the user ID and password for an unrestricted administrative user.

SAS Deployment Manager	_ 🗆 ×
Specify Connection Information Specify connection information to the SA5 Metadata Server.	00
Host Name:	
d18374.na.sas.com	
Port:	
8561	
User ID:	
sasadm@saspw	
Password:	
Help	< Back Next > Cancel

- 11 If you are configuring a SAS product that involves the WebSphere Web application server, you are prompted if you are using WebSphere Admin Security. Make your selection and click Next.
- 12 If you are using WebSphere Admin Security, then on the Web Application Server Administrator page, enter the user ID and password for the administrator and click Next.
- 13 When you see the Summary page, the deployment manager has finished collecting configuration input. This is the last opportunity to go back and change any information you have provided in previous pages before the manager begins writing to your system.

Make one of the following choices:

- □ Select **Start** to begin writing the configuration to the current machine.
- □ Select **Back** to navigate to earlier manager pages to change configuration information previously entered.
- □ Select **Cancel** to terminate the manager session. Note that you will lose configuration information previously entered.

SAS Deployment Manager	
Summary Review the selected product configurations. This is the last chance to go b make changes before writing to your system.	back and
Stage 1: Apply Update 1. SA5 Deployment Manager 2. SA5 Metadata Server Configuration 3. SA5 Table Server 4. JBoss Application Server 5. SA5 Web Infrastructure Platform 6. SA5 Shore Service	<u>*</u>
Stage 2: Build Web Applications 1. SAS Web Infrastructure Platform 2. SAS Web Application Themes 3. SAS Web Report Studio 4. SAS Information Delivery Portal 5. SAS Shared Services 6. SAS Web OLAP Viewer for Java 7. SAS BI Deshboard 8. SAS Help Viewer Metadata Configuration 9. SAS BI Portlets	
	C Requires user interaction
Help	< Back Start Cancel

During the configuration process, SAS automatically restarts your SAS servers, configures your Web application servers, and rebuilds and redeploys your SAS Web applications.

When you see a page similar to the following, the SAS Deployment Manager is finished:

<u>s</u> sa	5 Deployment Manager	
Dep	loyment Complete	
Sta	age 6: Deploy Web Applications 1. SAS Web Infrastructure Platform 2. SAS Web Application Themes 3. SAS Web Report Studio 4. SAS Information Delivery Portal	×
00000	5. SAS Shared Services 6. SAS Web OLAP Viewer for Java 7. SAS BI Dashboard 8. SAS Help Viewer Metadata Configuration 9. SAS BI Portlets	
Sta	age 7: Start Web Application Server 1. JBoss Application Server age 8: Run Post-update Tasks	
0	1. SAS Deployment Manager	Completed successfully Completed with warnings Completed with errors Requires user interaction
	Help	< Back Next > Cancel

14 Click Next to go to the Additional Resources page.

SAS Deployment Manager	_ 🗆 ×	
Additional Resources Below are links to additional resources for your deployment.	89	
Review Manual Configuration Instructions Manual steps are required to complete your configuration. You can view these : C:\SAS\EMiner\Lev1\Documents\UpdateInstructions.html. SAS Customer Support Center	steps in	
Acto://support.sas.com SAS Install Center http://support.sas.com/documentation/installcenter/92/index.html SAS Technical Support http://support.sas.com/techsup		
SAS Software Downloads http://www.sas.com/apps/demosdownloads/setupintro.jsp SAS Training http://support.sas.com/training		
Print		
Help	< Back Finish Cancel	

15 If your configuration:

 \Box encountered errors

The first link on the Additional Resources page goes to the ConfigurationErrors.html file. Click this link and follow the instructions to debug your configuration.

 \Box encountered no errors

The first link on the Additional Resources page goes to the UpdateInstructions.html file. Click this link and follow the instructions to complete any manual steps necessary to complete your configuration.

The SAS Deployment Manager writes its HTML pages to the Documents directory on the SAS configuration path. For example:

□ UNIX and z/OS:

/opt/SAS/Lev1/Documents/UpdateInstructions.html

 \Box Windows:

C:\SAS\Config\Lev1\Documents\UpdateInstructions.html

Note: The manager backs up your previous HTML files to the **Backup** subdirectory under the **Documents** directory on the SAS configuration path (for example,

16 Click Finish to close the deployment manager.

Detailed log messages are written to a file called product-name_updateConfigure_date-and-time.log, where product-name identifies the product that was configured. The deployment manager writes this file to SAS-configuration-directory\Levn\Logs\Configure.

Updating the SID File in Metadata for SAS Solutions

About Updating the SID File in Metadata for SAS Solutions

There are two situations when you might need to update the SAS installation data (SID) file in metadata for SAS solutions:

- □ when you add a SAS solution to your SAS 9.2 deployment
- $\hfill\square$ when you need to renew your software license for a SAS solution

About Adding a SAS Solution to Your Deployment

When you deploy a SAS solution on a middle-tier machine that does not also contain SAS Foundation, you must update the SID file in metadata using the SAS Deployment Manager from the machine on which the SETINIT for the solution is enabled. For more information, see "Update the SID File in Metadata for SAS Solutions" on page 165.

About Renewing Your Software License for SAS Solutions

SAS 9.2 ships with a 30-day initial license, or SETINIT. When your new SETINIT arrives, you must renew it on every machine that runs SAS 9.2 software using the typical method according to your operating system: SAS Renewal Tool (Windows), SAS Setup (UNIX), and RENEW job (z/OS). For more information, see the instructions appropriate for your operating system on the Install Center, located at http://support.sas.com/documentation/installcenter/92/index.html (search for "renewal").

Some SAS 9.2 solutions that depend on a SAS middle tier require you to perform an additional step. You will know when you have to update your middle-tier SETINIT when you receive error messages that your SAS license has expired. You must run the SAS Deployment Manager on the machine that the SETINIT is intended for. During the process, the deployment manager locates the new SETINIT and loads it into SAS metadata, effectively renewing your SAS solution software. (For more information about the other Deployment Manager features, see "Overview of SAS Deployment Manager and SAS Web Administration Console" in the SAS Intelligence Platform: System Administration Guide.)

Update the SID File in Metadata for SAS Solutions

After you add a SAS solution to your deployment, or renew your SAS software, some SAS 9.2 solutions that depend on a SAS middle tier require you to apply the new SETINIT in metadata. This procedure involves using the SAS Deployment Manager to update the SID file in your SAS metadata repository.

Note: You can automate running the deployment manager when you need to perform the same configuration action on many machines in your deployment. The deployment manager uses the same record and playback mechanism as the SAS Deployment Wizard to perform a non-interactive, silent configuration. For more information, see "Overview of Automating the SAS Installation on Multiple Machines" on page 109. \triangle

To apply your new software license for middle-tier SAS solutions, follow these steps:

- 1 Make sure that you have first done the following:
 - $\hfill\square$ obtained your new SETINIT from your SAS representative.

Your SETINIT is contained in a SAS installation data file (sometimes referred to as a SID) that is attached to your software order e-mail (SOE).

 \Box renewed your software license on each machine that runs SAS 9.2.

Follow the instructions appropriate for your operating system located at http://support.sas.com/documentation/installcenter/92/ index.html (search for "renewal").

 $\hfill\square$ added your newly licensed software to each machine in your deployment.

For more information, see "Adding SAS Products" on page 141.

- 2 If you received more than one SID file, you must make sure that you locate the correct one in order to perform the steps that follow. For more information, see "Determine Which SID File to Update in Metadata" on page 169.
- **3** Make sure that you have saved the new SID file on the machine that the SETINIT is intended for.

Note: On z/OS machines only, save the new SID file to the following path: *SASHome/SASFoundation/9.2/setinit.sas* For example:

```
/usr/lpp/SAS/SAS 92/SASFoundation/9.2/setinit.sas \triangle
```

- 4 Make sure that the metadata server is running.
- 5 Log on to the machine that the SETINIT is intended for as the SAS Installer user.

This is the user with which your SAS deployment was installed. For more information, see "Required External User Accounts for SAS" on page 7.

- 6 Navigate to SAS-installation-directory/SASDeploymentManager/9.2 and launch config.exe (Windows), config.sh (UNIX), or config.rexx (z/OS). On Windows, you can use the shortcut on the Start menu.
- 7 In the SAS Deployment Manager, select Update SID File in Metadata.

S	SAS Deployment Manager	_ 🗆 🗡
	Select Configuration Task Select the configuration task you would like to perform.	
	Update Passwords Update passwords for selected users in an existing configuration. Rebuild Web Applications Rebuild Web applications previously configured in an existing configuration. Remove Existing Configuration Remove configuration content for an existing configuration. Installed products will not be removed. Remove user content for SAS Information Delivery Portal	
	 Update <u>SID</u> File in Metadata Update the SID file in metadata to license certain SAS mid-tier products. SAS Foundation software is not affecte option. Update Host Name References Update host name references in an existing configuration. Update Existing Configuration Update an existing configuration with maintenance or newer versions of existing products. 	d by this
	Help	Cancel

8 On the next page, specify the configuration directory and the level (for example, Lev1) for your SAS Solution.

S	5AS Deployment Manager	
5	elect Configuration Directory/Level Select the configuration directory and the level within the configuration directory to manage.	
0	Select Configuration Directory	
	Configuration Directory Co	onfiguration Level
	C:\SAS\Config Let	v1
	Encer Configuration Directory and Level	
	Configuration Directory:	
		Browse
	Configuration Level:	
	Levi 💌	
	Help < <u>B</u> ack <u>N</u> ext >	Cancel

9 On the next page, enter the user ID and password for an unrestricted administrative user.

SAS Deployment Manager	
Specify Connection Information Specify connection information to the SAS Metadata Server.	
Hos <u>t</u> Name:	
pubhdc1.na.sas.com	
Port:	
8561	
User ID:	
sasadm@saspw	
Password:	
,	
Help	< Back Next > Cancel

10 On the next page, enter the absolute path to the new SID file on the machine.

SAS Deployment Manager		_ 🗆 ×
Specify SAS Installation Data File Specify the full path to your SAS installation data file.		
C:\Program Files\SAS\SASDeploymentManager\9.2\order_data\win_planning_ Details of the selected SAS installation data file:	_920_09w44\sid.txt Bro	<u>w</u> se
Product: SAS 9.2 Platform: Windows Order: win_planning_920_09w44_order Licensed SAS Foundation Software Expiration Date tletter.txt not available		
Help	< <u>B</u> ack <u>N</u> ext > Ca	ancel

11 Click Start.

When the deployment manager has successfully updated your SETINIT, you should see a page similar to the following:

🧕 SAS Deployment Manager	
Deployment Complete	
Stage 1: Load SID File into Metadata 1. SAS Deployment Manager	
	Completed successfully Completed with warnings Completed with errors En Requires user interaction
Help	< Back Finish Cancel

12 Click Finish.

The deployment manager has located the new SETINIT and loaded it into metadata. Your SAS solution software has been renewed.

- 13 Repeat steps 4 11 on any other machines that run a SAS Solution.
- 14 Restart your SAS Web application server.

For more information, see "Starting and Stopping Web Application Servers" in the SAS Intelligence Platform: System Administration Guide.

Note: If you have more than one SAS Web application server, restart the one on which the SASWebInfrastructurePlatformServices9.2 application is running. You can determine which Web application server runs the

SASWebInfrastructurePlatformServices 9.2 application by consulting your Web application administrative console. \bigtriangleup

Determine Which SID File to Update in Metadata

If you received more than one SID file, you must make sure that you locate the correct one with which to update your metadata. To determine which SID file to use, follow these steps:

 Locate the SAS order number that contains the SAS solution you are adding or whose license you are renewing.

If you do not know the order number, refer to your software order e-mail (SOE).

2 Locate the tech support site number that contains the SAS solution that you are adding or renewing.

A listing of the tech support site numbers and the SAS product to which they apply can be found in the soi.html file in your SAS Software Depot located under the install_doc/order-number subdirectory. For example: C:\SAS 9.2 Depot\install_doc\507863\soi.html.

3 SID files are named using this convention:

product order-number tech-support-site-number operating-system.txt

For example: SAS92_507873_70082502_SUN_Sparc.txt.

- 4 Open the SID file and verify that the SAS solution is declared in the file.
- **5** Record the name of the SID file. You will need to know which SID file to use when performing the steps in "Update the SID File in Metadata for SAS Solutions" on page 165.

Removing a SAS Configuration

Overview of Removing a SAS Configuration

The Remove Existing Configuration feature of the SAS Deployment Manager provides an automated way to remove one more products of a SAS Intelligence Platform configuration from your environment. With this feature, you can remove the configurations of all SAS products or just selected products from a machine. You can remove configuration information only, or you can also remove associated user-created content. (For more information about the other Deployment Manager features, see "Overview of SAS Deployment Manager and SAS Web Administration Console" in the SAS Intelligence Platform: System Administration Guide.)

Note: You can automate running the deployment manager when you need to perform the same configuration action on many machines in your deployment. The deployment manager uses the same record and playback mechanism as the SAS Deployment Wizard to perform a non-interactive, silent configuration. For more information, see "Overview of Automating the SAS Installation on Multiple Machines" on page 109. \triangle

S	s	AS Deployment Manager	
	Se	lect Configuration Task Select the configuration task you would like to perform.	
	c	Update Passwords	
		Update passwords for selected users in an existing configuration.	
	C	Rebuild Web Applications	
		Rebuild Web applications previously configured in an existing configuration.	
(C	Remove Existing Configuration	
		Remove configuration content for an existing configuration. Installed products will not be removed.	
		Remove user content for SAS Information Delivery Portal	
	C Update SID File in Metadata		
		Update the SID file in metadata to license certain SAS mid-tier products. SAS Foundation software is not affected by this option.	
	С	C Update Host Name References	
		Update host name references in an existing configuration.	
	С	Update Existing Configuration	
		Update an existing configuration with maintenance or newer versions of existing products.	
ľ			
		Help <a>Seck Next > Cancel	

Note: The SAS Deployment Manager does not uninstall or otherwise affect the SAS software that is located in the SAS installation directory. To uninstall SAS software, see "Overview of Uninstalling the SAS Intelligence Platform" on page 177. \triangle

The Remove Existing Configuration feature of the SAS Deployment Manager is useful for the following purposes:

- \Box to remove a product that you will no longer be using
- □ to move a product (for example, a SAS Application Server) from one machine to another. In this situation you would do the following:
 - **1** Use the SAS Deployment Manager to remove the product's configuration from the first machine.
 - 2 Use the SAS Deployment Wizard to install and configure the product on the second machine.
- □ to recover from errors in the initial configuration of a product or to implement different configuration options for a product. In these situations you would do the following:
 - 1 Use the SAS Deployment Manager to remove the product's configuration.
 - **2** Use the SAS Deployment Wizard to configure the product on the same machine, and select different configuration options than you selected previously.

When you remove a product's configuration, the SAS Deployment Manager performs the following tasks:

- □ stops the product (or the associated service) if it is running, as well as any dependent products (or associated services). For example:
 - □ If you are removing the configuration of a running OLAP server, then it stops the server. If the server is installed as a Windows service, then it stops the service.

□ If you are removing the configuration of a running metadata server, then it stops the server (or the associated Windows service). It also stops any running servers and services that depend on the metadata server, OLAP servers, stored process servers, table servers, workspace servers, pooled workspace servers, batch servers, SAS/SHARE servers, and SAS/CONNECT servers.

Note: The SAS Deployment Manager does not stop the object spawner. You must do this manually. \bigtriangleup

- If you are removing the configuration for SAS Foundation Services, then it stops the SAS Services Application (Remote Services) or the associated Windows service.
- □ deletes metadata objects that contain the product's configuration information. For example, if you remove a server configuration, then the server's metadata definition is removed and the server no longer appears in the Server Manager tree in SAS Management Console.
- □ on Windows systems, deletes shortcuts that are associated with the product. For example, if you remove a server configuration, then any shortcuts for starting, stopping, pausing, or resuming the server are deleted.
- □ on Windows systems, deletes the service (if applicable) that is associated with the product. For example, if you remove a server configuration, and if the server runs as a Windows service, then the service is removed.
- □ deletes configuration files and directories that are associated with the product. For example, if you remove the configuration for a SAS OLAP server, then the server's configuration directory, files, scripts, **sasusers** directory, and logs directory are deleted. The only exception is sasv9_usermods.cfg, which is retained if its contents have changed since the initial installation.
- deletes site-specific portal content if you are removing the configuration for the SAS Information Delivery Portal and if you select the option to **Remove user content for SAS Information Delivery Portal**. The content that is removed includes portal pages; portlets; changes to page navigation, page layout, and package sort order; and other similar customizations.
- determines whether other products in your deployment depend on the removed products. If dependent products exist, and if you have not selected those products for removal, then the SAS Deployment Manager prompts you to remove them. For example, the SAS BI Dashboard depends on the SAS Information Delivery Portal. If you remove the configuration for the SAS Information Delivery Portal, but you do not remove the configuration for the SAS BI Dashboard, then the SAS Deployment Manager prompts you to remove it. For more information about dependencies, see "Identify Dependent SAS Products" on page 172.
- □ creates an HTML page that lists the items that were removed and describes any additional manual tasks that you need to perform. The page is created in a temporary location. You should save it to a permanent location on your network or file system.
- writes detailed log messages to a file called product-name_unconfigure_date-and-time, where product-name identifies the product that was removed. The deployment manager writes this file to SAS-configuration-directory\Levn\Logs\Configure.

Summary of Steps for Removing a SAS Configuration

Here is a summary of the steps that you should take when removing a configuration:

1 Determine which products' configurations to remove.

- 2 Determine which products depend on the products that you are removing. You will need to remove the configuration for each of these products. For details, see "Identify Dependent SAS Products" on page 172.
- **3** For each product that you plan to remove, identify the machine where it is installed.

In a single-machine installation, you can remove the configurations of multiple products as well their dependent products in a single execution of the SAS Deployment Manager.

In a multiple-machine installations, you should remove middle-tier products first. Then remove products on the SAS server tier. If you are removing the metadata server, you should remove it last.

- 4 Create a complete backup of your system before removing a configuration. This backup should include a correct backup of the metadata server. (See "Best Practices for Backing Up and Restoring Your System" in SAS Intelligence *Platform: System Administration Guide.*) This step is important because it is not possible to undo the removal of a configuration.
- **5** If you are removing a server, you might want to stop the server (or its associated service), although this is not required. However, you must stop the object spawner if you are removing one of the servers that it runs.

Note: The only exception is the metadata server, which must be running. \triangle

- **6** If you are unconfiguring a SAS Web application, then depending on the operating system and the Web application server that you are using, do the following:
 - \Box JBoss:

Always stop the JBoss Web application server before unconfiguring any of the SAS Web applications.

- □ WebLogic:
 - □ On UNIX, keep the WebLogic Web application server running while unconfiguring the SAS Web application.
 - On Windows, always stop the WebLogic Web application server before unconfiguring any of the SAS Web applications. (Make sure that the WebLogic Node Manager is running.)
- \square WebSphere:

Ensure that the WebSphere Deployment Manager (dmgr) server and nodeagent server are running while unconfiguring the SAS Web application. All application servers (for example, SASServer1) should be stopped.

- 7 If you are unconfiguring a SAS middle tier on UNIX, first stop SAS Remote Services before running the SAS Deployment Manager.
- 8 When all of the preparatory steps are complete, follow the steps that are described in "Remove a Configuration" on page 175.

Identify Dependent SAS Products

If you remove the configuration of a product that another product depends on, then the dependent product will not be able to function. Therefore, when you remove a product's configuration, the SAS Deployment Manager requires that you also remove the configurations of any dependent products.

Product dependencies are shown in the following table. If you remove the configuration for a product in the left column, then you must also remove the configurations for all of the products that are in the right column opposite that product. For example:
- □ If you remove the SAS BI Dashboard configuration, then you do not need to remove any other products. No products depend on the SAS BI Dashboard.
- If you remove the SAS BI Report Services Workspace Configuration, then you must also remove the following dependent products: BI Report Services, SAS BI Dashboard, SAS Web Report Studio, and SAS Web Report Viewer.
- □ If you remove the SAS Metadata Server configuration, then you must remove all other products.

 Table A2.6
 Dependencies in the SAS Intelligence Platform

Product	Dependent Products*
BI Report Services	None
MySQL Database Server	SAS Shared Services (unless SAS Shared Services is using the SAS Table Server) SAS Solutions Services
Platform Process Manager	SAS Web Report Studio and SAS BI Dashboard (if report scheduling is enabled via Platform Process Manager)
SAS Application Server Context	All products except Platform Process Manager
SAS BI Dashboard	None
SAS BI Report Services Workspace Configuration	BI Report Services SAS BI Dashboard SAS Web Report Studio SAS Web Report Viewer
SAS Foundation Services	Web application server (JBoss, WebLogic, or WebSphere) SAS BI Dashboard SAS Help Viewer Metadata Configuration SAS Information Delivery Portal SAS Information Delivery Portal JPS Extension SAS Shared Services SAS Web Report Studio SAS Web Report Viewer SAS Web Infrastructure Platform
SAS Grid Manager Control Server Configuration	SAS Grid Manager Node Configuration
SAS Grid Manager Control Server Configuration (with other grid middleware)	SAS Grid Manager Node Configuration (with other grid middleware)
SAS Information Delivery Portal	SAS BI Dashboard SAS BI Portlets SAS Shared Services
SAS Metadata Server	All products

Product	Dependent Products*
SAS Object Spawner	BI Report Services
	Operating System Scheduling Services
	SAS BI Dashboard
	SAS BI Report Services Workspace
	Configuration
	SAS Pooled Workspace Server
	SAS Shared Services
	SAS Stored Process Server
	SAS Web Report Studio
	SAS Web Report Viewer
	SAS Workspace Server
SAS Pooled Workspace Server	SAS BI Dashboard
	SAS BI Report Services Workspace Configuration
	SAS Shared Services (if used by SAS Table Server)
SAS Shared Services	None
SAS Solutions Services	None
SAS Stored Process Server	None
SAS Table Server	SAS Shared Services (unless SAS Shared Services is using MySQL Database Server)
SAS Web Infrastructure Platform	SAS BI Dashboard
	SAS BI Portlets
	SAS Information Delivery Portal
	SAS Web Report Studio
	SAS Web Report Viewer
	SAS Themes
SAS Web Report Studio	SAS BI Dashboard
	SAS BI Portlets
SAS Workspace Server	SAS BI Dashboard
Web application server (JBoss, WebLogic, or	SAS BI Dashboard
WebSphere)	SAS BI Portlets
	SAS Help Viewer Metadata Configuration
	SAS Information Delivery Portal
	SAS Shared Services
	SAS Web Report Studio
	SAS Web Report Viewer
	SAS Web Infrastructure Platform
	SAS Themes

 $\ast\,$ These products depend on the product in column 1. Therefore, they must be removed if the product in column 1 is removed.

Note: On z/OS, using the SAS Deployment Manager to remove a Web Application Server Network Deployment configuration also removes the Web application server itself from the node. In the third maintenance release of SAS 9.2, the SAS Deployment Wizard does not support configuring a WebSphere Application Server on z/OS. Therefore, contact your WebSphere System Administrator to redefine the node's Web application servers after unconfiguration. \triangle

When you remove a product's configuration, the SAS Deployment Manager checks to see whether your deployment plan includes any products that depend on that product. If dependent products exist, and if you have not selected those products for removal, then the SAS Deployment Manager prompts you to remove them.

Remove a Configuration

In a single-machine installation, you can remove the configurations of multiple products as well their dependent products in a single execution of the SAS Deployment Manager.

<mark>§</mark> 5	AS Deployment Manager		
Select Configuration Task			
	Select the configuration task you would like to perform.		
_			
0	Update Passwords		
	Update passwords for selected users in an existing configuration.		
C Rebuild Web Applications			
	Rebuild Web applications previously configured in an existing configuration.		
0	Remove Existing Configuration		
۲	Remove configuration content for an existing configuration. Installed products will not be removed.		
	Remove user content for SAS Information Delivery Portal		
0	Update <u>S</u> ID File in Metadata		
	Update the SID file in metadata to license certain SAS mid-tier products. SAS Foundation software is not affected by this option.		
0	Update Host Name References		
	Update host name references in an existing configuration.		
0	Update Existing Configuration		
	Update an existing configuration with maintenance or newer versions of existing products.		
	Help Searce Cancel		

In a multiple-machine installations, you should remove middle-tier product configurations first. Then remove product configurations on the SAS server tier. If you are removing the metadata server configuration, then you should remove it last.

Note: When removing a configuration, the SAS Deployment Manager does not delete any configuration log files associated with the configuration. However, server log files are removed. \triangle

Follow these steps to run the SAS Deployment Manager to remove the configurations from each machine:

1 Make sure that you have completed the preparatory steps that are described in "Summary of Steps for Removing a SAS Configuration" on page 171.

- 2 On the host machine for the products whose configurations you are removing, navigate to SAS-installation-directory/SASDeploymentManager/9.2 and launch config.exe (Windows), config.sh (UNIX), or config.rexx (z/OS). On Windows, you can use the shortcut on the Start menu.
- 3 In the SAS Deployment Manager, select Remove Existing Configuration.

If you are removing the SAS Information Delivery Portal, then you can also select the option to remove user content that is associated with the portal. If you select this option, the SAS Deployment Manager removes portal pages; portlets; changes to page navigation, page layout, and package sort order; and other similar customizations.

CAUTION:

Use caution when choosing the option to remove user content for the SAS Information Delivery Portal. The content cannot be recovered unless you have a complete backup of your system. \triangle

- 4 In the next page, specify the configuration directory and the level (for example, Lev1) from which the configuration is to be removed.
- **5** In the next page, enter the user ID and password for an unrestricted administrative user.
- 6 On the next page, select the check boxes for the products that you want to remove. For each product that you select, be sure to also include the other products on the machine that depend on that product (see "Identify Dependent SAS Products" on page 172).
- 7 Detailed log messages are written to a file called product-name_unconfigure_date-and-time.log, where product-name identifies the product that was removed. The deployment manager writes this file to SAS-configuration-directory\Levn\Logs\Configure.
- 8 When the configuration removal is complete, the Additional Resources page is displayed. In this page, click on the following document name:

configuration-name-and-level ConfigurationRemoval.html

The document contains details about the products that were removed and additional manual steps that you might need to perform. The document is created in a temporary location. You should save it on your network or your file system so that you can refer to it later.

For details about what occurs when you remove a configuration, see "Overview of Removing a SAS Configuration" on page 169.

After removing the configuration, you might need to take one of the following additional steps, depending on the reason for the removal:

- □ run the SAS Deployment Wizard to create a new configuration. For details, see "Configuring SAS Products" on page 153.
- uninstall the associated software (if you will no longer be using the product on the current machine, or if you will be reinstalling the software on the current machine). For details, see "Overview of Uninstalling the SAS Intelligence Platform" on page 177.

Uninstalling the SAS Intelligence Platform

Overview of Uninstalling the SAS Intelligence Platform 177 Stopping SAS Servers That Are Running 178 Stop SAS Servers That Are Running on Windows 178 Stop SAS Servers That Are Running on UNIX 178 Uninstalling Your SAS Software 178 Overview of Uninstalling Your SAS Software 178 Uninstall SAS on Windows 178 Uninstall SAS on UNIX 179 Uninstalling Third-Party Software 179 Uninstalling the SAS JRE and the JDK 180 Deployed Web Applications 180 Overview of Uninstalling the SAS JRE and the JDK 180 Windows 180 UNIX 180

Overview of Uninstalling the SAS Intelligence Platform

Remove software from machines deploying SAS 9.2 in the following order:

1 client-tier machines

APPENDIX

- 2 middle-tier machines
- **3** server-tier machines
- 4 metadata server machine

To uninstall the SAS 9.2 Intelligence Platform, you need to perform the following steps—where applicable—on each machine in your deployment:

1 Unconfigure your SAS software.

See "Remove a Configuration" on page 175.

2 Stop SAS servers that are running.

See "Stopping SAS Servers That Are Running" on page 178.

3 Uninstall your SAS software.

See "Uninstalling Your SAS Software" on page 178.

4 Uninstall third-party software.

See "Uninstalling Third-Party Software" on page 179.

5 Uninstall the SAS JRE and the JDK.

See "Uninstalling the SAS JRE and the JDK" on page 180.

Stopping SAS Servers That Are Running

Stop SAS Servers That Are Running on Windows

Before uninstalling any software on a machine, you must stop any SAS servers that are running there. To stop SAS servers running on Windows, follow steps:

- □ Log on to the machine as the SAS Installer user (the user account used to install the SAS Software) or as the Administrator (or a user in the Administrators group).
- □ Run the Windows Services snap-in (Start ► Control Panel ► Administrative Tools ► Services).
- \Box Stop all of the SAS services that are running.

For more information, refer to your Microsoft Windows documentation.

Stop SAS Servers That Are Running on UNIX

Before uninstalling any software on a machine, you must stop any SAS servers that are running there. To stop SAS servers running on UNIX, follow steps:

- $\hfill\square$ Log on to the machine as the SAS user.
- □ From the **Lev***n* SAS configuration directory, run the following command:

sas.servers stop

For example:

```
/opt/SAS/Config/Lev1/sas.servers stop
```

Uninstalling Your SAS Software

Overview of Uninstalling Your SAS Software

You should now uninstall the SAS products. Do *not* uninstall the SAS JRE (Java Runtime Environment). The Java uninstallers need the JRE in order to execute.

Uninstall SAS on Windows

To uninstall SAS software from a Windows machine, perform these steps:

- 1 Remove the configurations for any SAS software you are uninstalling by following the instructions described in, "Remove a Configuration" on page 175.
- 2 Make sure that you are logged on as the SAS Installer user (the user account used to install the SAS Software) or as the Administrator (or a user in the Administrators group).
- 3 Open the Control Panel by selecting Start ► Settings ► Control Panel.
- 4 From the Control Panel, open the Add or Remove Programs window.
- 5 From the Add or Remove Programs window, remove SAS software components.

Note: Remove the SAS Versioned Jar Repository last. \triangle

6 Close the Add or Remove Programs window and the Control Panel.

- 7 Delete your SAS installation directory (SAS Home) (for example, C:\Program Files\SAS).
- 8 Delete your SAS configuration directory (for example, C:\SAS\Config\Lev1).
- 9 Delete the SAS directory under \Local Settings\Application Data for the SAS Installer user:

Uninstall SAS on UNIX

To uninstall SAS software on a UNIX machine, perform these steps:

- 1 Make sure that you have first unconfigured the SAS software on the machine by following the directions in "Removing a SAS Configuration" on page 169.
- 2 Make sure that you have permission to delete files from the SAS home directory (the directory in which your SAS software is installed).
- **3** Make sure that you have permission to delete files from your configuration directory.
- **4** Make sure that you are logged on as the SAS Installer user (the user account used to install the SAS Software).
- 5 Remove the SAS 9.2 installation directories by executing the **rm** -**rf** command on the top-level SAS 9.2 installation directory. Note that you must *not* **cd** to this directory before executing the command.

For example, if the top-level SAS 9.2 installation directory is /opt/SAS/SAS_92, then you would use the following command:

rm -rf /opt/SAS/SAS_9.2

Uninstalling Third-Party Software

The SAS Intelligence Platform often makes use of third-party products, such as a Web application server. You can determine whether third-party software was deployed on a particular machine by reviewing your deployment plan file (plan.xml). To uninstall these products, use the same procedures that you used to uninstall your SAS software. (See "Uninstalling Your SAS Software.")

The following table shows the main third-party products that are used with the SAS 9.2 Intelligence Platform.

Type of Product	Products
Web application servers and servlet	JBoss Application Server
containers	WebLogic Server
	\Box WebSphere Application Server
Scheduling servers	Platform Process Manager

Table A3.1

Uninstalling the SAS JRE and the JDK

Deployed Web Applications

Undeploy and delete WAR and EAR files that are deployed to your Web application server or servlet container.

Overview of Uninstalling the SAS JRE and the JDK

After you have uninstalled your SAS software and your third-party software, you can uninstall the Java Runtime Environment (JRE) that SAS uses. If the Java Development Kit (JDK) on the machine was being used only in support of SAS Web applications, you can also remove the JDK.

Windows

To uninstall the JRE and the JDK used by SAS from a Windows machine, perform these steps:

- 1 Open the Control Panel by selecting Start ► Settings ► Control Panel.
- 2 From the Control Panel, open the Add or Remove Programs window.
- 3 From the Add or Remove Programs window, remove the products.
- 4 Close the Add or Remove Programs window and the Control Panel.

UNIX

This procedure applies only if you had the SAS Foundation installed. In any event, proceed with caution.

Note: Make sure that the JRE and JDK are not being used for other software on the machine before you delete the products. \triangle

To uninstall the JRE and the JDK used by SAS from a UNIX machine, perform these steps:

- 1 Locate the directory where these products are installed, and make sure that you have permission to delete files in this directory.
- 2 Delete the product with uninstallers whenever you can. Otherwise, use the rm -rf command on the top-level installation folder.



Recommended Reading

Recommended Reading 181

Recommended Reading

Here is the recommended reading list for this title:

- Dependence of Planning for Maintenance Releases and Product Upgrades for SAS 9.2
- SAS Enterprise Miner: Single-User Installation Guide
- □ SAS Intelligence Platform: Overview
- $\hfill \ensuremath{\:\square}$ SAS Intelligence Platform: Data Administration Guide
- □ SAS Intelligence Platform: Security Administration Guide
- □ SAS Intelligence Platform: System Administration Guide
- □ SAS Intelligence Platform: Application Server Administration Guide
- □ SAS Intelligence Platform: Web Application Administration Guide
- SAS Intelligence Platform: Desktop Application Administration Guide

For a complete list of SAS publications, go to **support.sas.com/bookstore**. If you have questions about which titles you need, please contact a SAS Publishing Sales Representative at:

SAS Publishing Sales SAS Campus Drive Cary, NC 27513 Telephone: 1-800-727-3228 Fax: 1-919-531-9439 E-mail: sasbook@sas.com Web address: support.sas.com/bookstore

Customers outside the United States and Canada, please contact your local SAS office for assistance.

Glossary

attribute

a characteristic that is part of the standard metadata for an object. Examples of attributes include the object's name, creation date, and modification date.

authentication

the process of verifying the identity of a person or process within the guidelines of a specific authorization policy.

authentication domain

a SAS internal category that pairs logins with the servers for which they are valid. For example, an Oracle server and the SAS copies of Oracle credentials might all be classified as belonging to an OracleAuth authentication domain.

cluster

a group of machines that participate in load balancing. Each machine in the cluster runs an object spawner that handles client requests for connections.

component

a self-contained, reusable programming object that provides some type of service to other components in an object-oriented programming environment.

connection profile

a client-side definition of where a metadata server is located. The definition includes a computer name and a port number. In addition, the connection profile can also contain user connection information.

credentials

the user ID and password for an account that exists in some authentication provider.

daemon

a process that starts and waits either for a request to perform work or for an occurrence of a particular event. After the daemon receives the request or detects the occurrence, it performs the appropriate action. If nothing else is in its queue, the daemon then returns to its wait state.

data warehouse

a collection of data that is extracted from one or more sources for the purpose of query, reporting, and analysis. In contrast to a data mart, a data warehouse is better suited for storing large amounts of data that originates in other corporate applications or which is extracted from external data sources such as public databases.

database management system

a software application that enables you to create and manipulate data that is stored in the form of databases. Short form: DBMS.

database server

a server that provides relational database services to a client. Oracle, DB/2 and Teradata are examples of relational databases.

DBMS

See database management system.

deploy

to install an instance of operational SAS software and related components. The deployment process often includes configuration and testing as well. See also migrate.

deployment plan

information about what software should be installed and configured on each machine in a SAS deployment. A deployment plan is an XML file that is used as input to the SAS Deployment Wizard. There are two types of deployment plans: standard and custom. A standard deployment plan describes a common configuration. Standard plans are stored by default in the SAS Software Depot. A custom deployment plan is created by a SAS representative specifically for a site.

domain

a database of users that has been set up by an administrator by using a specific authentication provider such as LDAP or the host operating system. The domain name should be unique within your enterprise. For example, you should not have a Windows domain and a UNIX domain that are both named "SALES". See also authentication domain.

encryption

the act or process of converting data to a form that only the intended recipient can read or use.

Extensible Markup Language

a markup language that structures information by tagging it for content, meaning, or use. Structured information contains both content (for example, words or numbers) and an indication of what role the content plays. For example, content in a section heading has a different meaning from content in a database table. Short form: XML.

Integrated Windows authentication

a Microsoft technology that facilitates use of authentication protocols such as Kerberos. In the SAS implementation, all participating components must be in the same Windows domain or in domains that trust each other.

Internet Protocol Version 6

a protocol that specifies the format for network addresses for all computers that are connected to the Internet. This protocol, which is the successor of Internet Protocol Version 4, uses hexadecimal notation to represent 128-bit address spaces. The format can consist of up to eight groups of four hexadecimal characters, delimited by colons, as in FE80:0000:0000:0000:0202:B3FF:FE1E:8329. As an alternative, a group of consecutive zeros could be replaced with two colons, as in

FE80::0202:B3FF:FE1E:8329. Short form: IPv6 See also IP address and Internet Protocol Version 4.

IPv6

See Internet Protocol Version 6.

IWA

See Integrated Windows authentication.

JAR file

a Java Archive file. The JAR file format is used for aggregating many files into one file. JAR files have the file extension .jar.

Java

a set of technologies for creating software programs in both stand-alone environments and networked environments, and for running those programs safely. Java is a Sun Microsystems trademark.

Java Database Connectivity

a standard interface for accessing SQL databases. JDBC provides uniform access to a wide range of relational databases. It also provides a common base on which higher-level tools and interfaces can be built. Short form: JDBC.

Java Development Kit

a software development environment that is available from Sun Microsystems, Inc. The JDK includes a Java Runtime Environment (JRE), a compiler, a debugger, and other tools for developing Java applets and applications. Short form: JDK.

JDBC

See Java Database Connectivity.

JDK

See Java Development Kit.

job

a metadata object that specifies processes that create output.

load balancing

for IOM bridge connections, a program that runs in the object spawner and that uses an algorithm to distribute work across object server processes on the same or separate machines in a cluster.

localhost

a keyword that is used to specify the machine on which a program is executing. If a client specifies localhost as the server address, the client connects to a server that runs on the same machine.

login

a SAS copy of information about an external account. Each login includes a user ID and belongs to one SAS user or group. Most logins do not include a password.

metadata identity

a metadata object that represents an individual user or a group of users in a SAS metadata environment. Each individual and group that accesses secured resources on a SAS Metadata Server should have a unique metadata identity within that server.

metadata object

a set of attributes that describe a table, a server, a user, or another resource on a network. The specific attributes that a metadata object includes vary depending on which metadata model is being used.

middle tier

in a SAS business intelligence system, the architectural layer in which Web applications and related services execute. The middle tier receives user requests, applies business logic and business rules, interacts with processing servers and data servers, and returns information to users.

migrate

to populate a new deployment of SAS software with the content, data, or metadata (or a combination of these) from an existing deployment. Migrating might include upgrading to a new software release, converting data or metadata, or other changes to ensure compatibility.

object

in object-oriented programming, an instantiation or specific representation of a class.

object spawner

a program that instantiates object servers that are using an IOM bridge connection. The object spawner listens for incoming client requests for IOM services. When the spawner receives a request from a new client, it launches an instance of an IOM server to fulfill the request. Depending on which incoming TCP/IP port the request was made on, the spawner either invokes the administrator interface or processes a request for a UUID (Universal Unique Identifier).

OLAP

See online analytical processing.

online analytical processing

a software technology that enables users to dynamically analyze data that is stored in cubes. Short form: OLAP.

planned deployment

a method of installing and configuring a SAS business intelligence system. This method requires a deployment plan that contains information about the different hosts that are included in the system and the software and SAS servers that are to be deployed on each host. The deployment plan then serves as input to an installation and configuration tool called the SAS Deployment Wizard.

pre-installation checklist

a checklist that enumerates the tasks a customer must perform before installing the business intelligence platform. The primary task is to create a set of operating system user accounts on the metadata server host. See also metadata server.

resource

any object that is registered in a metadata repository. For example, a resource can be an application, a data store, a dimension in an OLAP cube, a metadata item, an access control template, or a password.

SAS Application Server

in the SAS Intelligence Platform, a logical entity that represents the SAS server tier. This logical entity contains specific servers (for example, a SAS Workspace Server and a SAS Stored Process Server) that execute SAS code. A SAS Application Server has relationships with other metadata objects. For example, a SAS library can be assigned to a SAS Application Server. When a client application needs to access that library, the client submits code to the SAS Application Server to which the library is assigned.

SAS authentication

a form of authentication in which the target SAS server is responsible for requesting or performing the authentication check. SAS servers usually meet this responsibility by asking another component (such as the server's host operating system, an LDAP provider, or the SAS Metadata Server) to perform the check. In a few cases (such as SAS internal authentication to the metadata server), the SAS server performs the check for itself. A configuration in which a SAS server trusts that another component has pre-authenticated users (for example, Web authentication) is not part of SAS authentication.

SAS configuration directory

the location where configuration information for a SAS deployment is stored. The configuration directory contains configuration files, logs, scripts, repository files, and other items for the SAS software that is installed on the machine.

SAS data set

a file whose contents are in one of the native SAS file formats. There are two types of SAS data sets: SAS data files and SAS data views. SAS data files contain data values in addition to descriptor information that is associated with the data. SAS data views contain only the descriptor information plus other information that is required for retrieving data values from other SAS data sets or from files that are stored in other software vendors' file formats.

SAS Deployment Manager

a cross-platform utility that manages SAS deployments. The SAS Deployment Manager supports functions such as updating passwords for your SAS deployment, rebuilding SAS Web applications, and removing configurations.

SAS Deployment Wizard

a cross-platform utility that installs and initially configures many SAS products. Using a SAS installation data file and, when appropriate, a deployment plan for its initial input, the wizard is designed to prompt the customer for all the remaining input at the start of the session so that the customer does not have to monitor an entire deployment.

SAS Foundation Services

a set of core infrastructure services that programmers can use in developing distributed applications that are integrated with the SAS platform. These services provide basic underlying functions that are common to many applications. These functions include making client connections to SAS application servers, dynamic service discovery, user authentication, profile management, session context management, metadata and content repository access, activity logging, event management, information publishing, and stored process execution. See also service.

SAS installation data file

a control file containing license information that is required in order to install SAS.

SAS installation directory

the location where your SAS software is installed. This location is the parent directory to the installation directories of all SAS products. The SAS installation directory is also referred to as SAS Home in the SAS Deployment Wizard.

SAS Management Console

a Java application that provides a single user interface for performing SAS administrative tasks.

SAS Metadata Server

a multi-user server that enables users to read metadata from or write metadata to one or more SAS Metadata Repositories. The SAS Metadata Server uses the Integrated Object Model (IOM), which is provided with SAS Integration Technologies, to communicate with clients and with other servers.

SAS OLAP Server

a SAS server that provides access to multidimensional data. The data is queried using the multidimensional expressions (MDX) language.

SAS Pooled Workspace Server

a SAS Workspace Server that is configured to use server-side pooling. In this configuration, the SAS object spawner maintains a collection of workspace server processes that are available for clients.

SAS Software Depot

a file system that consists of a collection of SAS installation files that represents one or more orders. The depot is organized in a specific format that is meaningful to the SAS Deployment Wizard, which is the tool that is used to install and initially configure SAS. The depot contains the SAS Deployment Wizard executable, one or more deployment plans, a SAS installation data file, order data, and product data.

SAS Stored Process Server

a SAS IOM server that is launched in order to fulfill client requests for SAS Stored Processes.

SAS Workspace Server

a SAS IOM server that is launched in order to fulfill client requests for IOM workspaces.

SAS/CONNECT server

a server that provides SAS/CONNECT services to a client. When SAS Data Integration Studio generates code for a job, it uses SAS/CONNECT software to submit code to remote computers. SAS Data Integration Studio can also use SAS/ CONNECT software for interactive access to remote libraries.

SAS/SHARE server

the result of an execution of the SERVER procedure, which is part of SAS/SHARE software. A server runs in a separate SAS session that services users' SAS sessions by controlling and executing input and output requests to one or more SAS libraries.

server context

a SAS IOM server concept that describes how SAS Application Servers manage client requests. A SAS Application Server has an awareness (or context) of how it is being used and makes decisions based on that awareness. For example, when a SAS Data Integration Studio client submits code to its SAS Application Server, the server determines what type of code is submitted and directs it to the correct physical server for processing (in this case, a SAS Workspace Server).

service

one or more application components that an authorized user or application can call at any time to provide results that conform to a published specification. For example, network services transmit data or provide conversion of data in a network, database services provide for the storage and retrieval of data in a database, and Web services interact with each other on the World Wide Web. See also SAS Foundation Services.

servlet

a Java program that runs on a Web server. Servlets can be considered a complementary technology to applets, which run in Web browsers. Unlike applet code, servlet code does not have to be downloaded to a Web browser. Instead, servlets send HTML or other appropriate content back to a browser or to another type of Web-based client application.

servlet container

an execution environment for Java servlets that contains a Java Virtual Machine. The servlet container also provides other services for servlets and for the Web applications that those servlets are part of. For example, the servlet container converts HTTP requests that are sent by clients to Java objects that servlets can work with, and it converts the output of servlets to HTTP responses. An example of a popular servlet container is the JBoss server.

single sign-on

an authentication model that enables users to access a variety of computing resources without being repeatedly prompted for their user IDs and passwords. For example, single sign-on can enable a user to access SAS servers that run on different platforms without interactively providing the user's ID and password for each platform. Single sign-on can also enable someone who is using one application to launch other applications based on the authentication that was performed when the user initially logged on.

spawner

See object spawner.

SSO

See single sign-on.

trusted user

a privileged service account that can act on behalf of other users on a connection to the metadata server.

unrestricted user

a special user of a metadata server who can access all metadata on the server (except for passwords, which an unrestricted user can overwrite but cannot read). An unrestricted user can also perform administrative tasks such as starting, stopping, pausing, and refreshing the metadata server. You are an unrestricted user if your user ID is listed in the adminUsers.txt file and is preceded by an asterisk.

update mode

an operating state of the SAS Deployment Wizard in which users are required to install software updates before they can perform any other deployment tasks. The SAS Deployment Wizard automatically goes into update mode when it determines that the current SAS order contains new versions or maintenance updates to the deployed products in a given SAS installation directory.

Web application

an application that is accessed via a Web browser over a network such as the Internet or an intranet. SAS Web applications are Java Enterprise Edition (JEE) applications that are delivered via Web application archive (WAR) files. The applications can depend on Java and non-Java Web technologies.

Web authentication

a configuration in which users of Web applications and Web services are verified at the Web perimeter and the metadata server trusts that verification.

Web browser

a software application that is used to present Web content. To accomplish this task, the browser submits URL (Uniform Resource Locator) requests to a Web server and handles any results that the request generates.

Web Distributed Authoring and Versioning

a set of extensions to the HTTP protocol that enables users to collaboratively edit and manage files on remote Web servers. Short form: WebDAV.

WebDAV

See Web Distributed Authoring and Versioning.

WebDAV server

an HTTP server that supports the collaborative authoring of documents that are located on the server. The server supports the locking of documents, so that multiple authors cannot make changes to a document at the same time. It also associates metadata with documents in order to facilitate searching. The SAS business intelligence applications use this type of server primarily as a report repository. Common WebDAV servers include the Apache HTTP Server (with its WebDAV modules enabled), Xythos Software's WebFile Server, and Microsoft Corporation's Internet Information Server (IIS).

workspace

in the IOM object hierarchy for a SAS Workspace Server, an object that represents a single session in SAS.

XML

See Extensible Markup Language.

Index

A

accessibility features 3 accounts *See* user accounts administration 117 setup tasks 118 system administration tasks 124

C

changing SAS order details 46 checklists pre-installation for groups 15, 16 pre-installation for port numbers 21 pre-installation for users 11, 12, 13 configuration automatic for Web application server 55 information for SAS Deployment Wizard 93 interactive 87 logs 129 modifying to optimize performance 122 removing information or content 169 configuration directories protections on Windows 118 configuration directory creating for z/OS 17 Configuration Errors.html file 129

D

deleting a SAS order 48 deployment plans 66 DeploymentSummary.html file 128 directory service accounts 10

E

external user accounts 7 rights required for 9

F

full prompt mode installation 113

G

grid computing Platform Suite for SAS and 58 groups defining 14 pre-installation checklist for 15, 16 sas group (UNIX) 15 SAS Server Users group 14 SASGRP group (z/OS) 15 setting up 5

I

installation 2
automating for multiple machines 108
from third-party software Web site 57
full prompt mode 113
interactive 87
partial prompt mode 112
products from Platform Suite for SAS 58
quiet mode 111
SAS OnlineDoc for the Web 75
third-party products 53
verifying 114
Instructions.html file 128
interactive prompting levels 69
internal user accounts 6
IPv6 (Internet Protocol version 6) 68

J

Java Development Kit installing from third-party software Web site 57 recording information about 59 Java Runtime Environment (JRE) in Russia 58 uninstalling 180 JBoss Application Server recording information about 59

L

local accounts 10 logs configuration 129 LSF Administrator account 9 LSF User account 9

М

managing a SAS deployment 135 removing a configuration 169 metadata repositories, accessing 125 multicast addresses 19 multiple machine deployments 67

Ν

network accounts 10

0

operating system protections for configuration directories on Windows 118 optimizing performance changes to initial configuration 122

Ρ

partial prompt mode installation 112 passwords policies for SAS system accounts 11 permissions 120 Platform Grid Management Service installing 58 Platform LSF (Load Sharing Facility) installing 58 Platform Process Manager installing 58 Platform Suite for SAS installing products from 58 recording information about 59 playing back SAS Deployment Wizard response files 110 full prompt mode 113 managing a machine reboot 112 monitoring the wizard 114 partial prompt mode 112 quiet mode 111 verifying the installation 114 ports designating 19 reserving for SAS servers and spawners 21 pre-installation checklists for groups 15, 16 for port numbers 21 for third-party products 59 for users 11, 12, 13

Q

quiet mode installation 111

R

reboot during response file playback 112 recording SAS Deployment Wizard response files 109 removing a configuration 169, 171 identifying dependent components 172 running the SAS Deployment Manager 175 required user accounts 5 reserving ports SAS servers and spawners 21 response files playing back 110 recording 109 rights external user accounts 9

S

SAS Administrator account 6 SAS Deployment Manager removing a configuration 169, 175 SAS Deployment Tester 108 SAS Deployment Wizard 66 configuration information 93 creating SAS Software Depots 40 documents and reports 128 installing and configuring SAS 87 interactive prompting levels 69 monitoring during playback 114 options 66, 70 response files 109 SAS Download Manager creating SAS Software Depots 30 SAS folders 125 sas group (UNIX) 15 SAS Installer account 8 SAS Intelligence Platform deploying 2 software offerings 1 uninstalling 177 SAS OnlineDoc for the Web, installing 75 SAS orders and SAS Software Depots 142 changing order details 46 creating a disc image 50 deleting an order 48 SAS server tier, troubleshooting 129 SAS Server Users group 14 SAS servers reserving ports for 21 stopping 178 validation 106 SAS software uninstalling 178 SAS Software Depots 25 and SAS orders 142 benefits 27 best practices for 29 creating with SAS Deployment Wizard 40 creating with SAS Download Manager 30 installing third-party products 56 prerequisites for creating 30 SAS Spawned Servers account 8 SAS system accounts 5 passwords 11 SAS Trusted User account 6 SASGRP group (z/OS) 15 scheduling Platform Suite for SAS and 58 security protections for configuration directories on Windows 118 setup tasks 118 permissions 120 spawners reserving ports for 21 stopping SAS servers 178 system administration 124

Т

temporary directory changing 87 third-party products installing 53 installing from third-party software Web site 57 installing products from Platform Suite for SAS 58 installing with SAS Software Depot 56 pre-installation checklists 59 recording information about 59 uninstalling 179 user accounts for 9 third-party software Web site 57 troubleshooting 127 SAS server tier 129 SAS Web applications 131

U

uninstalling the SAS Intelligence Platform 177 Java Development Kit 180 SAS JRE 180 SAS software 178 stopping servers 178 third-party software 179 UNIX sas group 15 user accounts 5 defining 6 directory service accounts 10 external 7 for third-party software 9 internal 6 local accounts 10 network accounts 10 password policies 11 pre-installation checklist for 11, 12, 13 SAS system accounts 5 setting up required accounts 5

V

validating SAS servers 106

W

Web application server automatic configuration 55 installing from third-party software Web site 57 Web applications automatic deployment 56 troubleshooting 131 WebLogic Server recording information about 59 WebSphere Application Server recording information about 59 Windows SAS Server Users group 14

Ζ

z/OS creating a configuration directory 17 SASGRP group 15

Your Turn

We welcome your feedback.

- □ If you have comments about this book, please send them to **yourturn@sas.com**. Include the full title and page numbers (if applicable).
- □ If you have comments about the software, please send them to **suggest@sas.com**.

SAS® Publishing Delivers!



SAS Publishing provides you with a wide range of resources to help you develop your SAS software expertise. Visit us online at **support.sas.com/bookstore**.

SAS[®] PRESS

SAS Press titles deliver expert advice from SAS[®] users worldwide. Written by experienced SAS professionals, SAS Press books deliver real-world insights on a broad range of topics for all skill levels.

support.sas.com/saspress

SAS® DOCUMENTATION

We produce a full range of primary documentation:

- Online help built into the software
- Tutorials integrated into the product
- Reference documentation delivered in HTML and PDF formats-free on the Web
- Hard-copy books

support.sas.com/documentation

SAS® PUBLISHING NEWS

Subscribe to SAS Publishing News to receive up-to-date information via e-mail about all new SAS titles, product news, special offers and promotions, and Web site features.

support.sas.com/spn

SOCIAL MEDIA: JOIN THE CONVERSATION!

Connect with SAS Publishing through social media. Visit our Web site for links to our pages on Facebook, Twitter, and LinkedIn. Learn about our blogs, author podcasts, and RSS feeds, too.

support.sas.com/socialmedia

