SAS® High-Performance Analytics Server 12.1
User's Guide

SAS® Documentation

The correct bibliographic citation for this manual is as follows: SAS Institute Inc. 2012. *SAS® High-Performance Analytics Server 12.1: User's Guide*. Cary, NC: SAS Institute Inc.

SAS® High-Performance Analytics Server 12.1: User's Guide

Copyright © 2012, SAS Institute Inc., Cary, NC, USA

All rights reserved. Produced in the United States of America.

For a hard-copy book: No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc.

For a Web download or e-book: Your use of this publication shall be governed by the terms established by the vendor at the time you acquire this publication.

The scanning, uploading, and distribution of this book via the Internet or any other means without the permission of the publisher is illegal and punishable by law. Please purchase only authorized electronic editions and do not participate in or encourage electronic piracy of copyrighted materials. Your support of others' rights is appreciated.

U.S. Government Restricted Rights Notice: Use, duplication, or disclosure of this software and related documentation by the U.S. government is subject to the Agreement with SAS Institute and the restrictions set forth in FAR 52.227-19, Commercial Computer Software-Restricted Rights (June 1987).

SAS Institute Inc., SAS Campus Drive, Cary, North Carolina 27513.

Electronic book 1, August 2012

SAS® Publishing provides a complete selection of books and electronic products to help customers use SAS software to its fullest potential. For more information about our e-books, e-learning products, CDs, and hard-copy books, visit the SAS Publishing Web site at **support.sas.com/publishing** or call 1-800-727-3228.

SAS® and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Other brand and product names are registered trademarks or trademarks of their respective companies.

Contents

Chapter 1. What's New in the HPA Server 12.1 . . . 1
Chapter 2. Introduction . . . 7
Chapter 3. Shared Concepts and Topics . . . 15
Chapter 4. Installation and System Administration . . . 61
Chapter 5. SAS High-Performance Analytics Features in SAS/OR . . . 79
Chapter 6. The HP4SCORE Procedure . . . 93
Chapter 7. The HPBIN Procedure . . . 101
Chapter 8. The HPCORR Procedure . . . 123
Chapter 9. The HPCOUNTREG Procedure . . . 139
Chapter 10. The HPDECIDE Procedure . . . 173
Chapter 11. The HPDMDB Procedure . . . 189
Chapter 12. The HPDS2 Procedure . . . 199
Chapter 13. The HPFOREST Procedure . . . 213
Chapter 14. The HPIMPUTE Procedure . . . 265
Chapter 15. The HPLMIXED Procedure . . . 277
Chapter 16. The HPLOGISTIC Procedure . . . 319
Chapter 17. The HPLSO Procedure . . . 375
Chapter 18. The HPNEURAL Procedure . . . 417
Chapter 19. The HPNLIN Procedure . . . 437
Chapter 20. The HPQLIM Procedure . . . 471
Chapter 21. The HPREDUCE Procedure . . . 507
Chapter 22. The HPREG Procedure . . . 535
Chapter 23. The HPSAMPLE Procedure . . . 581
Chapter 24. The HPSEVERITY Procedure . . . 593
Chapter 25. The HPSUMMARY Procedure . . . 717
Chapter 26. The HPTMINE Procedure (Experimental) . . . 747
Chapter 27. The HPTMSCORE Procedure (Experimental) . . . 785

Subject Index **795**

Syntax Index **807**

Credits and Acknowledgments

Credits

Documentation

Editing	Anne Baxter, Ed Huddleston
Documentation Support	Tim Arnold, Melanie Gratton

Software

The SAS High-Performance Analytics Server was implemented by the following members of the development staff. Program development includes design, programming, debugging, support, and documentation. In the following list, the names of the developers who currently provide primary support are listed first; other developers and previous developers are also listed.

HP4SCORE	Ashok Savasere, Padraic Neville
HPBIN	Taiping He
HPCORR	Charles Shorb
HPCOUNTREG	Richard Potter
HPDECIDE	Scott Pope
HPDMDB	Scott Pope
HPDS2	Mark Freskos, Tom P. Weber, Oliver Schabenberger
HPFOREST	Ashok Savasere, Padraic Neville
HPIMPUTE	Tao Wang
HPLMIXED	Tianlin Wang, Biruk Gebramariam
HPLOGISTIC	Robert E. Derr, Oliver Schabenberger
HPLSO	Joshua Griffin, Steven Gardner
HPNEURAL	Larry Lewis
HPNLIN	Marc Kessler, Oliver Schabenberger
HPQLIM	Richard Potter
HPREDUCE	Alan (Zheng) Zhao
HPREG	Robert Cohen
HPSAMPLE	Ye Liu
HPSEVERITY	Mahesh Joshi
HPSUMMARY	Gordon Keener
HPTMINE	Alan (Zheng) Zhao, Russell Albright, David Bultman, Joshua Griffin

HPTMSCORE	Alan (Zheng) Zhao, Russell Albright, David Bultman, Joshua Griffin
High-performance computing foundation	Steve E. Krueger
High-performance analytics foundation	Robert Cohen, Georges H. Guirguis, Trevor Kearney, Richard Knight, Gang Meng, Oliver Schabenberger, Charles Shorb, Tom P. Weber
High-perfomance SAS/OR enhancements	Tao Huang, Matthew Galati, Ben-Hao Wang, Jack Rouse
Numerical routines	Georges H. Guirguis

The following people contribute to the SAS High-Performance Analytics Server with their leadership and support: Chris Bailey, Tanya Balan, David Pope, Oliver Schabenberger, Renee Sciortino.

Testing

Shu An, Leslie Anderson, Shahrzad Azizzadeh, Jack Berry, Keith Carter, Tim Carter, Ming Chun-Chang, Melissa Corn, John Crouch, Enzo D'Andreti, Bruce Elsheimer, Alex Fang, Girija Gavankar, Greg Goodwin, Sanggohn Han, Lisa Hemmerle, Dright Ho, Gerardo Hurtado, Seungho Huh, Nilesh Jakhotiya, Angela Jones, Rui Kang, Jagruti Kanjia, Paul Kovach, Cheryl LeSaint, Yu Liang, Yu-Min Lin, Jim McKenzie, Jim Metcalf, Huiping Miao, Kelly Miller, Phil Mohr, Muralee Muraleetharan, Bengt Pederson, Jeff Prevatt, Laura Rock, Kim Stott, Carol Thompson, Weihua Shi, Benita Taylor, Vinu Vainateya, Kaihong Xu, Lois Zhu.

Internationalization Testing

Alex Chai, Mi-Na Chu, Jacky Dong, Feng Gao, Masayuki Iizuka, David Li, Lan Luan, Haiyong Rong, Bin Sun, Frank Wang, Lina Xu, Catherine Yang.

Technical Support

Phil Gibbs

Acknowledgments

Many people make significant and continuing contributions to the development of SAS software products.

The final responsibility for the SAS System lies with SAS alone. We hope that you will always let us know your opinions about the SAS System and its documentation. It is through your participation that SAS software is continuously improved.

Please visit us at http://www.sas.com/software/high-performance-computing/.

Chapter 1
What's New in the HPA Server 12.1

Contents

Overview **1**
Running Alongside the Hadoop Distributed File Sysytem **2**
New Procedures **2**
HP4SCORE Procedure 2
HPBIN Procedure 2
HPCORR Procedure 2
HPDECIDE Procedure 2
HPIMPUTE Procedure 2
HPLSO Procedure 3
HPQLIM Procedure 3
HPTMINE Procedure (Experimental) 3
HPTMSCORE Procedure (Experimental) 3
Enhancements **4**
HPFOREST Procedure 4
HPLOGISTIC Procedure 4
HPNEURAL Procedure 4
HPREG Procedure 4
HPSEVERITY Procedure 5
High-Performance Features in SAS/OR **5**
Distributed Computing for the Multistart Method in the OPTMODEL Procedure (Experimental) 5
The Decomposition Algorithm in the OPTMODEL, OPTLP, and OPTMILP Procedures 6
Distributed Computing for Parameter Tuning in the OPTMILP Procedure (Experimental) 6

Overview

The SAS High-Performance Analytics Server 12.1 includes several new procedures and many enhancements. Additionally, all High-Performance Analytics procedures can now run alongide the Hadoop Distributed File System (HDFS).

Running Alongside the Hadoop Distributed File Sysytem

If you use the new SAS Data in HDFS Engine to distribute data from a SAS client to machines in a cluster where the SAS High-Performance Deployment of Hadoop is installed, then you can run SAS High-Performance Analytics procedures in distributed mode with those data. For more information about using the SAS Data in HDFS Engine, see the chapter "Using the SAS Data in HDFS Engine" in the *SAS LASR Analytic Server: Administration Guide*.

New Procedures

HP4SCORE Procedure

The HP4SCORE procedure scores forest models that have been created by the HPFOREST procedure either on the client or on the SAS appliance.

HPBIN Procedure

The HPBIN procedure conducts high-performance binning for interval variables. In this release, it provides bucket binning, Winsorized binning, and pseudo–quantile binning. PROC HPBIN produces basic statistic tables, which include the mean table, Winsor and trim statistics, pseudo–quantile estimation, and so on. The CODE statement supports score code generation.

HPCORR Procedure

The HPCORR procedure computes Pearson product-moment correlation coefficients and the probabilities that are associated with these statistics.

HPDECIDE Procedure

The HPDECIDE procedure creates optimal decisions that are based on a decision matrix that you specify, on prior probabilities, and on output from a modeling procedure (which can be predicted values for an interval target variable). The HPDECIDE procedure can also adjust the posterior probabilities for changes in the prior probabilities.

HPIMPUTE Procedure

The HPIMPUTE procedure performs missing value imputation of numeric variables. It can replace missing values with the mean, the pseudo-median, a random value, or a user-specified value.

HPLSO Procedure

The HPLSO procedure uses a parallel derivative-free hybrid approach to perform local-search optimization of nonlinear functions that are defined over both continuous and integer variables. Functions that are optimized can be nonsmooth, discontinuous, and computationally taxing to evaluate; no assumptions are made about the nature of the function. The HPLSO procedure uses several different optimization solvers, executing them in coordinated fashion and in parallel. Function evaluation is also distributed among available computational nodes, and the results are shared among the parallel optimization processes. Input data for the HPLSO procedure can also be stored in distributed form.

HPQLIM Procedure

The HPQLIM procedure fits linear, censored, and truncated regression models with heteroscedasticity and stochastic frontier production and cost models.

HPTMINE Procedure (Experimental)

The experimental HPTMINE procedure is a high-performance procedure for analyzing large-scale textual data. PROC HPTMINE provides the SAS High-Performance Analytics platform an essential capability for text mining and supports a wide range of fundamental text analysis features, including tokenizing, stemming, part-of-speech tagging, noun-group extraction, default or customized stop and start lists, entity parsing, multiword tokens, synonym lists, term weighting, term-by-document matrix creation, action-by-term filtering and singular value decomposition (SVD). PROC HPTMINE can also generate results that can be used to facilitate scoring by the HPTMSCORE procedure. You can use the HPTMINE procedure to read data in distributed form and perform text analysis in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode.

HPTMSCORE Procedure (Experimental)

The experimental HPTMSCORE procedure is a high-performance procedure for scoring large-scale textual data. PROC HPTMSCORE scores a set of documents by using the outputs generated by the HPTMINE procedure, including the configuration table, the term table, and the singular value decomposition (SVD) projection matrix. After scoring, PROC HPTMSCORE can generate a term-by-document matrix and a table that includes SVD projections for the input documents. The HPTMSCORE procedure can read data in distributed form and perform text analysis in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode.

Enhancements

HPFOREST Procedure

The HPFOREST procedure now accepts inputs with missing values and can use them when creating a splitting rule. The HPFOREST procedure now also computes variable importance based on loss or impurity reduction. Values of a variable in the FREQ statement are no longer truncated to an integer. The trained model can be saved in a binary format on the client so that it can be used for subsequent scoring. PROC HPFOREST also supports scoring the training data set and saving the scored results on the SAS appliance.

HPLOGISTIC Procedure

For all model selection methods, you can now choose effects to be in every model by using the INCLUDE= option in the MODEL statement. The START= option in the MODEL statement enables you to begin the forward and stepwise model selection processes at a specific model. The new CODE statement supports score code generation.

HPNEURAL Procedure

The following features are now production:

- logistic architecture (no hidden neurons)
- logistic initialization with skip architectures
- PARTITION statement for selecting validation observations
- stand-alone scoring mode, which uses a previously trained model
- CODE statement for generating SAS scoring code
- MISSING=MAP option for assigning a valid classification level to missing values during training
- progress notes written to the SAS log every minute during training
- significantly lower memory usage for classification variables with a large number of levels

HPREG Procedure

The HPREG procedure now supports BY processing when it runs in client mode or when it runs in distributed mode and the input data is a SAS data set. The new CODE statement supports score code generation.

HPSEVERITY Procedure

The following enhancements have been added to the HPSEVERITY procedure:

- Three new statistics-of-fit have been added: Kolmogorov-Smirnov (KS), Anderson-Darling (AD), and Cramér-von Mises (CvM). These are computed by comparing the parametric cumulative distribution function (CDF) with the local estimates of empirical distribution function (EDF).
- (Experimental) You can now estimate parameters by minimizing your own objective function, which you can specify by using SAS programming statements. You can use various keyword functions in your SAS program; the keyword functions are internally expanded by PROC HPSEVERITY with distribution-specific or problem-specific versions.
- The new DFMIXTURE= option in the SCALEMODEL statement enables you to control how the CDF estimates are computed in presence of regressors. The CDF estimates are used to compute the new EDF-based statistics-of-fit.
- The DIST statement now supports two more keywords in addition to the _PREDEFINED_ keyword: the _USER_ keyword includes all your custom distributions, and the _ALL_ keyword specifies the union of all predefined and custom distributions.

  The DIST statement also has two new options, LISTONLY and VALIDATEONLY, which enable you to list and validate the specified distributions, respectively.

High-Performance Features in SAS/OR

SAS/OR 12.1 adds a number of capabilities that make special use of the distributed computing environment that is provided by the SAS High-Performance Analytics Server. These capabilities include the new HPLSO procedure (see the section "HPLSO Procedure" on page 3) and added experimental distributed computing features for existing procedures.

Distributed Computing for the Multistart Method in the OPTMODEL Procedure (Experimental)

In PROC OPTMODEL, distributed computing accelerates the multistart method for nonlinear optimization. This method starts optimization at several different initial points, which are determined by an algorithm. This method is useful for problems that are likely to have multiple locally optimal points; starting optimization from multiple locations makes it more likely that one of the resulting locally optimal solutions returned is also globally optimal. Problems that are likely to exhibit multiple local optima include those that feature nonconvex nonlinear functions in either or both the objective and the constraints. Distributed optimization enables optimization starting from what might be a large number of initial points to occur in parallel on multiple nodes, thus dramatically shortening the real time needed for optimization. The distributed computing implementation of the multistart method for nonlinear optimization is experimental in SAS/OR 12.1.

The Decomposition Algorithm in the OPTMODEL, OPTLP, and OPTMILP Procedures

The most fundamental change for both linear and mixed-integer optimization in SAS/OR 12.1 is the addition of the decomposition (DECOMP) algorithm, which is used in PROC OPTMODEL, PROC OPTLP, and PROC OPTMILP. This algorithm is useful for problems in which distinct sets of constraints involve distinct subsets of decision variables, possibly with a small set of constraints that involve all or most of the decision variables. The DECOMP algorithm operates by decomposing the overall problem into a set of component problems that can be solved in parallel on separate computational threads. The algorithm repeatedly solves these component problems and then cycles back to the overall problem to update key information that is used the next time the component problems are solved. This process continues iteratively and in the end produces a solution to the complete problem, with the linking constraints present. Distributed computing speeds this process by enabling a large number of component problems to be solved in parallel on separate computational nodes. The distributed computing implementation of this feature is experimental in SAS/OR 12.1.

Distributed Computing for Parameter Tuning in the OPTMILP Procedure (Experimental)

In SAS/OR 12.1, PROC OPTMILP introduces parameter tuning for mixed-integer optimization, which helps to determine the best options settings for one or more problems. You can choose between tuning a large or small predetermined set of parameters and tuning a set that you specify. Parameter tuning starts with an initial set of parameter values and uses those settings to solve the problem. The problem is solved repeatedly with different parameter values, with a local search algorithm guiding the choices for parameter values. When the tuning process terminates, the best parameter values are output to a specified data set. Distributed computing enables these various optimizations to proceed in parallel, shortening the overall time needed for parameter tuning. The distributed computing implementation of this feature is experimental in SAS/OR 12.1.

Chapter 2
Introduction

Contents

Overview of the SAS High-Performance Analytics Server **7**
About This Book **8**
Chapter Organization 8
Typographical Conventions 9
Options Used in Examples 9
Where to Turn for More Information **9**
SAS Technical Support Services 10
Related SAS Software **10**
SAS/IML Software 10
SAS/IML Studio 10
Base SAS Software 11
SAS/ETS Software 12
SAS/GRAPH Software 12
SAS/OR Software 12
SAS/QC Software 13
SAS/STAT Software 13
SAS Enterprise Miner Software 13

Overview of the SAS High-Performance Analytics Server

The SAS High-Performance Analytics Server provides tools for analytic tasks in a high-performance environment that is characterized by massively parallel processing (MPP) and symmetric multiprocessing (SMP) on a distributed database system. You can use the SAS High-Performance Analytics Server to perform analyses that range from descriptive statistics and summarization to correlation analysis, generalized linear modeling, variable selection, neural networks, and maximum likelihood in nonlinear models.

The SAS High-Performance Analytics Server uses a computing appliance that houses either a massively parallel database system or a Hadoop Distributed File System (HDFS) to manage data in distributed form and to perform the computations in parallel. A computing appliance is a dedicated hardware and software environment that provides computing resources in a client-server model. You are connected indirectly to the appliance through the network connection between the client machine and the computing appliance. Software instructions on the client machine are translated into and deferred to software execution on the appliance.

The SAS High-Performance Analytics appliance provides a massively parallel computing environment supported by Message Passing Interface (MPI) combined with either a massively parallel distributed database

management system (Teradata or EMC Greenplum) or a Hadoop Distributed File Sytem on a x64-Linux platform.

You can also operate SAS High-Performance Analytics procedures in a local SMP mode, where software execution does not engage the appliance and multithreaded analytics are executed on the client machine that runs the SAS session.

SAS High-Performance Analytics procedures do not require access to distributed data, but in many situations performance can be improved dramatically when data are read or written in distributed form.

The software is constantly being updated to reflect new methodology and advances in high-performance analytics.

About This Book

Since High-Performance Analytics software is a part of the SAS System, this book assumes that you are familiar with Base SAS software and with the books *SAS Language Reference: Concepts* and the *Base SAS Procedures Guide*. It also assumes that you are familiar with basic SAS System concepts such as creating SAS data sets with the DATA step and manipulating SAS data sets with Base SAS procedures (for example, the PRINT and SORT procedures).

Chapter Organization

This book is organized as follows.

Chapter 2, this chapter, provides an overview of SAS High-Performance Analytics and summarizes related information, products, and services.

Chapter 3, "Shared Concepts and Topics," provides information about topics that are common to all High-Performance Analytics procedures, such as how these procedures differ from other procedures in processing input and output data sets and how to navigate the distributed computing environment. The chapter also covers syntax that is common among many High-Performance Analytics procedures, such as the CLASS, ID, FREQ, SELECTION, VAR, PERFORMANCE, and WEIGHT statements. Any differences in a procedure's implementation of the common syntax elements is noted in the specific procedure chapter.

Subsequent chapters describe the procedures that make up the SAS High-Performance Analytics Server. These chapters appear in alphabetical order by procedure name. Each chapter is organized as follows:

- The "Overview" section provides a brief description of the analysis provided by the procedure.
- The "Getting Started" section provides a quick introduction to the procedure through a simple example.
- The "Syntax" section describes the SAS statements and options that control the procedure.
- The "Details" section discusses methodology and miscellaneous details, such as ODS tables.
- The "Examples" section contains examples that use the procedure.
- The "References" section contains references for the methodology and for examples of the procedure.

Typographical Conventions

This book uses several type styles for presenting information. The following list explains the meaning of the typographical conventions used in this book:

roman	is the standard type style used for most text.
UPPERCASE ROMAN	is used for SAS statements, options, and other SAS language elements when they appear in the text. However, you can enter these elements in your own SAS programs in lowercase, uppercase, or a mixture of the two.
UPPERCASE BOLD	is used in the "Syntax" sections' initial lists of SAS statements and options.
oblique	is used for user-supplied values for options in the syntax definitions and in text.
VariableName	is used for the names of variables and data sets when they appear in the text.
bold	is used to refer to matrices and vectors.
italic	is used for terms that are defined in the text, for emphasis, and for references to publications.
`monospace`	is used for example code. In most cases, this book uses lowercase type for SAS code.

Options Used in Examples

Output of Examples

Most of the output shown in this book is produced with the following SAS System options:

```
options linesize=80 pagesize=500 nonumber nodate;
```

The HTMLBLUE style is used to create the HTML output and graphs that appear in the online documentation. A style template controls stylistic elements such as colors, fonts, and presentation attributes. The style template is specified in the ODS HTML statement as follows:

```
ods html style=HTMLBlue;
```

If you run the examples, you might get slightly different output. This is a function of the SAS System options used and the precision used by your computer for floating-point calculations.

Where to Turn for More Information

This section describes other sources of information about the SAS High-Performance Analytics Server.

SAS Technical Support Services

As with all SAS products, the SAS Technical Support staff is available to respond to problems and answer technical questions regarding the use of the SAS High-Performance Analytics Server. Go to `http://support.sas.com/techsup` for more information.

Related SAS Software

Many features not found in the SAS High-Performance Analytics Server are available in other parts of the SAS System. If you do not find something you need in the SAS High-Performance Analytics Server, try looking for the feature in the following SAS software products.

SAS/IML Software

SAS/IML software gives you access to a powerful and flexible programming language (interactive matrix language) in a dynamic, interactive environment. The fundamental object of the language is a data matrix. You can use SAS/IML software interactively (at the statement level) to see results immediately, or you can store statements in a module and execute them later. The programming is dynamic because necessary activities such as memory allocation and dimensioning of matrices are done automatically. SAS/IML enables you to program your methods in the SAS System. For more information, see the *SAS/IML User's Guide*.

SAS/IML Studio

SAS/IML Studio is a tool for data exploration and analysis; it provides a highly flexible programming environment in which you can run the SAS High-Performance Analytics Server or SAS/IML analyses and display the results with dynamically linked graphics and data tables. You can also move seamlessly between interactive analysis and programmatically driven analysis. SAS/IML Studio is intended for data analysts who write SAS programs to solve statistical problems but need more versatility for data exploration and model building.

The programming language in SAS/IML Studio, which is called *IMLPlus*, is an enhanced version of the SAS/IML programming language. IMLPlus extends SAS/IML by providing features such as the ability to create and manipulate dynamically linked graphs and the ability to call SAS procedures.

SAS/IML Studio also includes an interface to the R language. The IMLPlus language provides functions that transfer data between SAS data sets and R data frames, and between SAS/IML matrices and R matrices.

SAS/IML Studio runs on a PC in the Microsoft Windows operating environment. For more information about SAS/IML Studio, see the *SAS/IML Studio User's Guide* and *SAS/IML Studio for SAS/STAT Users*.

Base SAS Software

The features provided by the SAS High-Performance Analytics Server are in addition to the features provided by Base SAS software. Many data management and reporting capabilities that you need are part of Base SAS software. Refer to *SAS Language Reference: Concepts* and the *Base SAS Procedures Guide* for documentation of Base SAS software.

Base SAS software provides the following:

ODS Graphics

- The statistical graphics (SG) family of procedures provides a simple syntax for creating stand-alone statistical graphics. These procedures include SGPLOT, SGSCATTER, and SGPANEL, which provide a simple and convenient syntax for producing many types of displays. They are particularly convenient for exploring and presenting data. See the *SAS/GRAPH: Statistical Graphics Procedures Guide* for more information.
- The GTL (graph template language) and the SGRENDER procedure provide a powerful syntax for creating customized graphs. See the *SAS/GRAPH: Graph Template Language User's Guide* and the *SAS/GRAPH: Graph Template Language Reference* for more information. You can also use the GTL to modify the SAS templates that are provided for use with SAS/STAT procedures.
- The ODS Graphics Editor enables you to make immediate changes to ODS Graphics by using a point-and-click interface. See the *SAS/GRAPH: ODS Graphics Editor User's Guide* for more information.

SAS DATA Step

The DATA step is your primary tool for reading and processing data in the SAS System. The DATA step provides a powerful general purpose programming language that enables you to perform all kinds of data processing tasks. The DATA step is documented in *SAS Language Reference: Concepts*.

Base SAS Procedures

Base SAS software includes many useful SAS procedures. Base SAS procedures are documented in the *Base SAS Procedures Guide*. The following is a list of Base SAS procedures you might find useful:

CORR	computes correlations.
RANK	computes rankings or order statistics.
STANDARD	standardizes variables to a fixed mean and variance.
MEANS	computes descriptive statistics and summarizes or collapses data over cross sections.
TABULATE	prints descriptive statistics in tabular format.
UNIVARIATE	computes descriptive statistics.

SAS/ETS Software

SAS/ETS software provides SAS procedures for econometrics and time series analysis. It includes capabilities for forecasting, systems modeling and simulation, seasonal adjustment, and financial analysis and reporting. In addition, SAS/ETS software includes an interactive time series forecasting system. For more information, see the *SAS/ETS User's Guide*.

SAS/GRAPH Software

SAS/GRAPH software includes procedures that create two- and three-dimensional plots and charts. For more information, see *SAS/GRAPH: Reference*.

SAS/OR Software

SAS/OR software provides operations research capabilities that include optimization, discrete-event simulation, and project and resource scheduling. Most SAS/OR features are provided via procedures. In addition, SAS Simulation Studio is a Windows-based Java application for discrete-event simulation. SAS/OR capabilities include:

- building and solving optimization models (including linear, mixed integer, quadratic, and general nonlinear optimization) with a powerful algebraic modeling language and solver suite
- building, running, and analyzing the results of discrete-event simulation models in a graphical modeling environment
- creating project and resource schedules
- creating Gantt chart and network diagram views of projects and their schedules
- monitoring the progress of projects via macros for computing and graphically displaying earned value management metrics
- using finite-domain constraint programming to find feasible solutions to constraint satisfaction problems (both general and scheduling-oriented)

SAS High-Performance Analytics Server users might be particularly interested in the diverse SAS/OR mathematical optimization capabilities, which encompass a broad range of problem types and solution algorithms and include partially and fully customized solution methods. Furthermore, several SAS/OR procedures have been enhanced to include a number of capabilities that make special use of the distributed computing environment that is provided by the SAS High-Performance Analytics Server (see Chapter 5, "SAS High-Performance Analytics Features in SAS/OR.") For more information, see *SAS/OR User's Guide: Mathematical Programming*, *SAS/OR User's Guide: Constraint Programming*, *SAS/OR User's Guide: Local Search Optimization*, *SAS/OR User's Guide: Project Management*, and *SAS Simulation Studio: User's Guide*.

SAS/QC Software

SAS/QC software provides a variety of procedures for statistical quality control and quality improvement, including procedures for the following:

- Shewhart control charts
- cumulative sum control charts
- moving average control charts
- process capability analysis
- Ishikawa diagrams
- Pareto charts
- experimental design

For more information, see the *SAS/QC User's Guide*.

SAS/QC software also includes the ADX interface for experimental design. For more information, see *Getting Started with the SAS ADX Interface for Design of Experiments*.

SAS/STAT Software

SAS/STAT software provides comprehensive statistical tools for a wide range of statistical analyses, including analysis of variance, categorical data analysis, cluster analysis, multiple imputation, multivariate analysis, nonparametric analysis, power and sample size computations, psychometric analysis, regression, survey data analysis, and survival analysis. Other examples include linear and nonlinear mixed models, generalized linear models, correspondence analysis, and robust regression. For more information, see the *SAS/STAT User's Guide*.

The syntax of many SAS High-Performance Analytics procedures closely follows their counterparts in SAS/STAT software. The algorithms in High-Performance Analytics procedures are based to some extent on the statistical algorithms in SAS/STAT procedures. However, the algorithms in High-Performance Analytics procedures are highly threaded for concurrent execution and have been adapted for a distributed computing environment. Differences in numerical operations and choices for defaults that are motivated by large-data problems can cause numerical differences between High-Performance Analytics procedures and SAS/STAT procedures.

SAS Enterprise Miner Software

SAS Enterprise Miner software provides a comprehensive set of tools for building predictive and descriptive data mining models for deployment to production scoring environments. The bundle includes both a unique set of SAS procedures and an interactive client interface. The procedures cover a broad range of prediction, classification, decision analysis, clustering, and market basket models. The client interface provides

a complete set of interactive tools to help users build repeatable processes and reports. The client bundle can be deployed on the desktop or via a network and integrates with the SAS BI Infrastructure. The entire model-scoring process is saved as score code that can be deployed to a wide range of production scoring systems. For more information, see the SAS Enterprise Miner Reference Help.

Chapter 3
Shared Concepts and Topics

Contents

SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures **16**
SMP and MPP Modes 16
Environment Variables 17
Switching Modes 18
Alongside-the-Database Execution 22
Alongside-HDFS Execution 24
Output Data Sets 26
Working with Formats 27
Syntax **28**
CLASS Statement 28
FREQ Statement 32
ID Statement 32
SELECTION Statement 32
PERFORMANCE Statement 38
VAR Statement 41
WEIGHT Statement 41
Levelization of Classification Variables **41**
Specification and Parameterization of Model Effects **44**
Effect Operators 45
Bar and At Sign Operators 45
Colon, Dash, and Double Dash Operators 46
GLM Parameterization of Classification Variables and Effects 47
Intercept 48
Regression Effects 48
Main Effects 48
Interaction Effects 48
Nested Effects 49
Continuous-Nesting-Class Effects 50
Continuous-by-Class Effects 50
General Effects 50
Reference Parameterization 51
Model Selection **52**
Methods 52
Full Model Fitted 52
Forward Selection 52

Backward Elimination 55
Stepwise Selection 56
Forward-Swap Selection 58
Least Angle Regression 58
Lasso Selection 59
Adaptive Lasso Selection 60
References **60**

This chapter discusses topics that are common to all SAS High-Performance Analytics procedures. It contains sections about general procedure features and behavior and sections about common syntax elements. Any deviation by a High-Performance Analytics procedure from the common syntax, which is documented in the section "Syntax" on page 28, is documented in the specific chapter for the procedure later in this book.

SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures

High-Performance Analytics procedures behave in many ways like other procedures in the SAS System. However, their ability to use a computing appliance, their focus on high performance, and their ability to perform computations in parallel lead to some important differences in features and behavior.

How a specific procedure differs from a procedure with similar functionality in other SAS products (for example, how the HPREG procedure differs from the REG procedure in SAS/STAT) is discussed in the individual procedure chapters. This section focuses on High-Performance Analytics procedures in general.

SMP and MPP Modes

Symmetric multiprocessing (SMP) is a computing model in which multiple processors or multiple cores are controlled by a single operating system and can access shared resources, such as disks and memory. In this book, SMP mode refers to an application running multiple concurrent threads on a multicore machine in order to take advantage of parallel execution on multiple processing units. Even more simply, SMP mode for High-Performance Analytics applications means multithreading on the client machine.

All High-Performance Analytics procedures are capable of running in SMP mode, and this is the default mode when a procedure executes on the client machine. The number of concurrent threads is determined by the procedure based on the number of CPUs (cores) on the machine. High-Performance Analytics procedures use different methods to map core count to the number of concurrent threads, depending on the analytic task. Using one thread per core is not uncommon for the procedures that implement data-parallel algorithms.

Massively parallel processing (MPP) is a computing model in which several nodes in a distributed computing environment participate in the calculations. In this book, the MPP mode of a High-Performance Analytics procedure refers to the procedure performing the analytics on the database management system (DBMS) appliance or on machines in a cluster where the SAS High-Performance Deployment of Hadoop is installed and running. MPP mode has three variations:

- The input data for the analytic task are not stored on the appliance or cluster but are distributed to the distributed computing environment by the High-Performance Analytics framework during execution of the procedure. This is termed the client-data (or local-data) model of MPP execution.
- The data are stored in the distributed database and are read in parallel from the DBMS; this is termed the alongside-the-database model of MPP execution.
- The data are stored in the Hadoop Distributed File System (HDFS) and are read in parallel from the HDFS; this is termed the alongside-HDFS model of MPP execution.

Environment Variables

You control the execution mode with environment variables or options in the PERFORMANCE statement in High-Performance Analytics procedures or both.

The important environment variables are the following:

- *grid host*: identifies the domain name system (DNS) or IP address of the appliance node to which the High-Performance Analytics software connects to run in MPP mode.
- *installation location*: identifies the directory in which the SAS High-Performance software is installed on the appliance.
- *data server*: identifies the database server on Teradata appliances as defined in the HOSTS file on the client. This data server is the same entry that you typically specify in the SERVER= entry of a LIBNAME statement for Teradata. For more information about specifying LIBNAME statements for Teradata and other relational databases, see the *SAS/ACCESS Interface* documentation for the specific database.

You can set an environment variable directly from the SAS program by using the OPTION SET= command. For example, the following statements define the three variables for a Teradata appliance:

```
option set=GRIDHOST      ="hpa.sas.com";
option set=GRIDINSTALLLOC="/opt/TKGrid";
option set=GRIDDATASERVER="myserver";
```

Alternatively, you can set the parameters in the PERFORMANCE statement in High-Performance Analytics procedures. For example:

```
performance host      ="hpa.sas.com"
            install   ="/opt/TKGrid"
            dataserver="myserver";
```

A specification in the PERFORMANCE statement overrides a specification of an environment variable without resetting its value. An environment variable that is set in the SAS session with an OPTION SET= command remains in effect until it is modified or until the SAS session terminates.

Specifying a data server is necessary only on Teradata systems. Its specification depends on the entries in the (client) HOSTS file. The HOSTS file specifies the server (suffixed by "cop" and a number), and an IP address. For example:

```
myservercop1  33.44.55.66
```

The key variable that determines whether a High-Performance Analytics procedure executes in SMP or MPP mode is the *grid host*. The installation location and data server are needed to ensure that a connection to the grid host can be made, given that a host is specified. This book assumes that the installation location and data server (if necessary) have been set by your system administrator.

The following sets of SAS statements are functionally equivalent:

```
proc hpreduce;
   var x:;
   performance host="hpa.sas.com";
run;

option set=GRIDHOST="hpa.sas.com";
proc hpreduce;
   var x:;
run;
```

Switching Modes

You can switch between SMP and MPP mode in High-Performance Analytics procedures according to the following rules:

- If no grid host is specified, the analysis is carried out in SMP mode on the client machine that runs the SAS session.
- If a grid host is specified, the default behavior depends on whether the execution is alongside-the-database or alongside-HDFS. If the data are local to the client (that is, not stored in the distributed database or HDFS on the appliance), you need to specify with the NODES= option in the PERFORMANCE statement the number of nodes on the appliance or cluster you want to engage in the analysis. If the procedure executes alongside the database or alongside HDFS, you do not need to specify the NODES= option.

The following example works through SMP and client-data MPP configurations with a data set of 100,000 observations simulated from a logistic regression model. The data are generated in the SAS session with this DATA step:

```
data simulate1;
   array _a{8} _temporary_ (0,0,0,1,0,1,1,1);
   array _b{8} _temporary_ (0,0,1,0,1,0,1,1);
   array _c{8} _temporary_ (0,1,0,0,1,1,0,1);
   do obsno=1 to 100000;
      x  = rantbl(1,0.28,0.18,0.14,0.14,0.03,0.09,0.08,0.06);
      a  = _a{x};
      b  = _b{x};
      c  = _c{x};
      x1 = int(ranuni(1)*400);
      x2 = 52 + ranuni(1)*38;
      x3 = ranuni(1)*12;
      lp = 6. -0.015*(1-a) + 0.7*(1-b) + 0.6*(1-c) + 0.02*x1 -0.05*x2 - 0.1*x3;
      y  = ranbin(1,1,(1/(1+exp(lp))));
      output;
   end;
   drop x lp;
run;


proc hplogistic data=simulate1;
   class a b c;
   model y = a b c x1 x2 x3;
run;
```

Figure 3.1 shows the results from the analysis.

Figure 3.1 Results from Logistic Regression in SMP Mode

```
                          The HPLOGISTIC Procedure

                          Performance Information

                       Execution Mode       On client
                       Number of Threads    4


                             Model Information

              Data Source                 WORK.SIMULATE1
              Response Variable           y
              Class Parameterization      GLM
              Distribution                Binary
              Link Function               Logit
              Optimization Technique      Newton-Raphson with Ridging
```

Figure 3.1 *continued*

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	5.7011	0.2539	Infty	22.45	<.0001
a 0	-0.01020	0.06627	Infty	-0.15	0.8777
a 1	0	.	.	.	.
b 0	0.7124	0.06558	Infty	10.86	<.0001
b 1	0	.	.	.	.
c 0	0.8036	0.06456	Infty	12.45	<.0001
c 1	0	.	.	.	.
x1	0.01975	0.000614	Infty	32.15	<.0001
x2	-0.04728	0.003098	Infty	-15.26	<.0001
x3	-0.1017	0.009470	Infty	-10.74	<.0001

The entries in the "Performance Information" table shows that the HPLOGISTIC procedure executes in client (SMP) mode using eight threads which are chosen according to the number of CPUs on the client machine. You can force a certain number of threads on any machine involved in the computations with the NTHREADS option in the PERFORMANCE statement.

The following statements use 10 nodes (in MPP mode) to analyze the data on the appliance; results appear in Figure 3.2.

```
proc hplogistic data=simulate1;
   class a b c;
   model y = a b c x1 x2 x3;
   performance host="hpa.sas.com" nodes=10;
run;
```

Figure 3.2 Results from Logistic Regression in MPP Mode

The HPLOGISTIC Procedure

Performance Information

Host Node	hpa.sas.com
Execution Mode	Distributed
Number of Compute Nodes	10
Number of Threads per Node	24

Model Information

Data Source	WORK.SIMULATE1
Response Variable	y
Class Parameterization	GLM
Distribution	Binary
Link Function	Logit
Optimization Technique	Newton-Raphson with Ridging

Figure 3.2 *continued*

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	5.7011	0.2539	Infty	22.45	<.0001
a 0	-0.01020	0.06627	Infty	-0.15	0.8777
a 1	0	.	.	.	.
b 0	0.7124	0.06558	Infty	10.86	<.0001
b 1	0	.	.	.	.
c 0	0.8036	0.06456	Infty	12.45	<.0001
c 1	0	.	.	.	.
x1	0.01975	0.000614	Infty	32.15	<.0001
x2	-0.04728	0.003098	Infty	-15.26	<.0001
x3	-0.1017	0.009470	Infty	-10.74	<.0001

The specification of a host causes the "Performance Information" table to display the name of the host node of the appliance. The "Performance Information" table also indicates that the calculations were performed in a distributed environment (MPP on the appliance). Twenty-four threads on each of 10 nodes were used to perform the calculations—for a total of 240 threads.

Another indication of distributed (MPP) execution on the appliance is the following message, which is issued in the SAS Log by all High-Performance Analytics procedures.

```
NOTE: The HPLOGISTIC procedure is executing in the distributed
      computing environment with 10 worker nodes.
```

You can override the presence of a grid host and force the computations into SMP mode by specifying the NODES=0 option in the PERFORMANCE statement:

```
proc hplogistic data=simulate1;
   class a b c;
   model y = a b c x1 x2 x3;
   performance host="hpa.sas.com" nodes=0;
run;
```

Figure 3.3 shows the results.

Figure 3.3 SMP Mode Despite Host Specification

The HPLOGISTIC Procedure

Performance Information

Host Node	hpa.sas.com
Execution Mode	On client
Number of Threads	4

In the analysis shown previously in Figure 3.2, the data set Work.simulate1 is local to the client, and the HPLOGISTIC procedure distributed the data to 10 nodes on the appliance. The High-Performance Analytics framework does not keep these data on the appliance; when the procedure terminates, the in-memory representation of the input data on the appliance is freed.

When the input data set is large, sending client-side data to the appliance is not advisable; data transfer can easily dominate the execution time. In practice, transfer speeds are typically lower than the theoretical limits of the network connection or disk I/O rates. At a transfer rate of 40 megabytes per second, sending a 10-gigabyte data set to the appliance requires more than four minutes. If analytic execution time is in the range of seconds, the "performance" of the process is dominated by data movement.

The alongside-the-database execution model, unique to High-Performance Analytics procedures, enables you to read and write data in distributed form from the database that is installed on the appliance.

Alongside-the-Database Execution

High-Performance Analytics procedures interface with the distributed database management system (DBMS) on the appliance in a unique way. If the input data are stored in the DBMS and the grid host is the appliance that houses the data, High-Performance Analytics procedures create a distributed computing environment in which an analytic process is co-located with the nodes of the DBMS. Data then passes from the DBMS to the analytic process on each node. Instead of data movement across the network and possibly back to the client machine, data passes locally between the processes on each node of the appliance.

Since the analytic processes on the appliance are separate from the database processes, the technique is referred to as the alongside-the-database model in contrast to in-database execution where the analytic code executes in the database process.

In general, with a large amount of input data, you can achieve the best performance characteristics with High-Performance Analytics procedures if execution is alongside the database.

Before you can run alongside the database, you must distribute the data to the appliance. The following statements use the HPDS2 procedure to distribute the data set Work.simulate1 into database mydb on the appliance hpa.sas.com. In this particular example, the appliance houses a Greenplum database.

```
option set=GRIDHOST="hpa.sas.com";
libname applianc greenplm
        server  ="hpa.sas.com"
        user    =XXXXXX
        password=YYYYY
        database=mydb;


proc datasets lib=applianc nolist; delete simulate1;
proc hpds2 data=simulate1
           out =applianc.simulate1(distributed_by='distributed randomly');
  performance commit=10000;
  data DS2GTF.out;
     method run();
        set DS2GTF.in;
     end;
  enddata;
run;
```

If the output table applianc.simulate1 exists, the DATASETS procedure removes the table from the Greenplum database because a DBMS typically does not support replacement operations on tables.

Note that the LIBNAME for the output table points to the appliance. The data set option informs the HPDS2 procedure to distribute the records randomly among the data segments of the appliance. The statements that follow the PERFORMANCE statement are the DS2 program that copies the input data to the output data without further transformations.

The following HPLOGISTIC statements perform the analysis on the appliance in the alongside-the-database mode. These statements are almost identical to the first HPLOGISTIC example in the previous section, which executed in SMP (client) mode.

```
proc hplogistic data=applianc.simulate1;
   class a b c;
   model y = a b c x1 x2 x3;
run;
```

The subtle differences are as follows:

- A grid host has been specified by the OPTION SET command in the previous statements.
- A LIBNAME is used that the High-Performance Analytics procedure identifies as the data source housed on the appliance.

Figure 3.4 shows the results from this analysis. The "Performance Information" table now shows that the execution was not only in distributed (MPP) mode, but also alongside the Greenplum database. The numeric results agree with the previous analyses shown in Figure 3.1 and Figure 3.2.

Figure 3.4 Alongside Greenplum Execution

```
                    The HPLOGISTIC Procedure

                    Performance Information

Host Node                      hpa.sas.com
Execution Mode                 Distributed, alongside Greenplum
Number of Compute Nodes        32
Number of Threads per Node     24


                       Model Information

    Data Source                SIMULATE1
    Response Variable          y
    Class Parameterization     GLM
    Distribution               Binary
    Link Function              Logit
    Optimization Technique     Newton-Raphson with Ridging
```

Figure 3.4 *continued*

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	5.6878	0.2540	Infty	22.39	<.0001
a 0	-0.01364	0.06638	Infty	-0.21	0.8372
a 1	0	.	.	.	.
b 0	0.7102	0.06568	Infty	10.81	<.0001
b 1	0	.	.	.	.
c 0	0.8024	0.06465	Infty	12.41	<.0001
c 1	0	.	.	.	.
x1	0.01977	0.000616	Infty	32.11	<.0001
x2	-0.04710	0.003101	Infty	-15.19	<.0001
x3	-0.1012	0.009480	Infty	-10.68	<.0001

If you specify a NODES= option in the PERFORMANCE statement in the alongside-the-database mode, the HPLOGISTIC procedure ignores the NODES= specification. If the data are read alongside the database, the number of compute nodes is determined by the layout of the database and cannot be modified. The particular appliance used in the example consists of 32 nodes (see the "Performance Information" table).

Alongside-HDFS Execution

Running High-Performance Analytics procedures alongside HDFS shares many features with running alongside the database. If the grid host is a cluster that houses data that have been distributed by using the SAS Data in HDFS Engine, then High-Performance Analytics procedures can analyze those data in the alongside-HDFS mode. The procedures use the distributed computing environment in which an analytic process is co-located with the nodes of the cluster. Data then pass from HDFS to the analytic process on each node of the cluster.

Before you can run alongside HDFS, you must distribute data to the cluster. You do this by using the SAS Data in HDFS Engine. The following statements use this engine to distribute to HDFS the simulate1 data set that was used in the previous two sections:

```
option set=GRIDHOST="hpa.sas.com";

libname hdoop sashdat
        path="/hps";

 data hdoop.simulate1 (replace = yes) ;
     set simulate1;
 run;
```

In this example the GRIDHOST is a cluster where the SAS Data in HDFS Engine is installed. If a data set named simulate1 already exists in the /hps directory in HDFS, it will be overwritten because the REPLACE=YES data set option is specified. For more information about using this LIBNAME statement, see the section "LIBNAME Statement for the SAS Data in HDFS Engine" in the *SAS LASR Analytic Server: Administration Guide*.

The following HPLOGISTIC procedure statements perform the analysis in the alongside-HDFS mode. These statements are almost identical to the PROC HPLOGISTIC example in the previous two sections, which executed in SMP (client) mode and alongside-the-database mode, respectively.

```
proc hplogistic data=hdoop.simulate1;
   class a b c;
   model y = a b c x1 x2 x3;

run;
```

Figure 3.5 shows the "Performance Information" table. You see that not only is the execution in distributed (MPP) mode, but it is also alongside HDFS. The numeric results shown in Figure 3.6 agree with the previous analyses shown in Figure 3.1, Figure 3.2, and Figure 3.4.

Figure 3.5 Alongside-HDFS Execution

Performance Information

Host Node	hpa.sas.com
Execution Mode	Distributed, alongside HDFS
Number of Compute Nodes	207
Number of Threads per Node	8

Figure 3.6 Alongside-HDFS Execution

Model Information

Data Source	HDOOP.SIMULATE1
Response Variable	y
Class Parameterization	GLM
Distribution	Binary
Link Function	Logit
Optimization Technique	Newton-Raphson with Ridging

Figure 3.6 *continued*

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	5.7011	0.2539	Infty	22.45	<.0001
a 0	-0.01020	0.06627	Infty	-0.15	0.8777
a 1	0	.	.	.	.
b 0	0.7124	0.06558	Infty	10.86	<.0001
b 1	0	.	.	.	.
c 0	0.8036	0.06456	Infty	12.45	<.0001
c 1	0	.	.	.	.
x1	0.01975	0.000614	Infty	32.15	<.0001
x2	-0.04728	0.003098	Infty	-15.26	<.0001
x3	-0.1017	0.009470	Infty	-10.74	<.0001

Output Data Sets

In the alongside-the-database mode, the data are read in distributed form, minimizing data movement for best performance. Similarly, when you write output data sets and a High-Performance Analytics procedure executes in MPP mode, the data can be written in parallel into the database.

For example, in the following statements, the HPLOGISTIC procedure executes in distributed mode using eight nodes on the appliance to perform the logistic regression on work.simulate1:

```
proc hplogistic data=simulate1;
   class a b c;
   model y = a b c x1 x2 x3;
   id a;
   output out=applianc.simulate1_out pred=p;
   performance host="hpa.sas.com" nodes=8;
run;
```

The output data set applianc.simulate1_out is written in parallel into the database. Although the data are fed on eight nodes, the database might distribute the data on more nodes.

When a High-Performance Analytics procedure executes in SMP mode, all output objects are created on the client. If the LIBNAME of the output data sets points to the appliance, the data are transferred to the database on the appliance. This can lead to considerable performance degradation compared to execution in MPP mode.

Many procedures in SAS software add the variables from the input data set when an observationwise output data set is created. The assumption of High-Performance Analytics procedures is that the input data sets can be large and contain many variables. For performance reasons, the output data set contains the following:

- variables that are explicitly created by the statement
- variables listed in the ID statement
- distribution keys or hash keys that are transferred from the input data set

Including this information enables you to add to the output data set information necessary for subsequent SQL joins without copying the entire input data set to the output data set.

Working with Formats

You can use SAS formats and user-defined formats with High-Performance Analytics procedures as you can with other procedures in the SAS System. However, because the analytic work is carried out in a distributed environment and might depend on the formatted values of variables, some special handling can improve the efficiency of work with formats.

High-Performance Analytics procedures examine the variables used in an analysis for association with user-defined formats. Any user-defined formats that are found by a procedure are transmitted automatically to the appliance. If you are running multiple High-Performance Analytics procedures in a SAS session and the analysis variables depend on user-defined formats, you can preprocess the formats. This step involves generating an XML stream (a file) of the formats and passing the stream to the High-Performance Analytics procedures.

Suppose that the following formats are defined in your SAS program:

```
proc format;
     value YesNo        1='Yes'        0='No';
     value checkThis    1='ThisisOne'  2='ThisisTwo';
     value $cityChar    1='Portage'    2='Kinston';
run;
```

The next group of SAS statements create the XML stream for the formats in the file *Myfmt.xml*, associate that file with the file reference myxml, and pass the file reference with the FMTLIBXML= option in the PROC HPLOGISTIC statement.

```
filename myxml 'Myfmt.xml';
libname  myxml XML92 xmltype=sasfmt tagset=tagsets.XMLsuv;
proc format cntlout=myxml.allfmts;
run;


proc hplogistic data=six fmtlibxml=myxml;
   class wheeze cit age;
   format wheeze best4. cit $cityChar.;
   model wheeze = cit age;
run;
```

Generation and destruction of the stream can be wrapped in convenience macros:

```
%macro Make_XMLStream(name=tempxml);
    filename &name 'fmt.xml';
    libname  &name XML92 xmltype=sasfmt tagset=tagsets.XMLsuv;
    proc format cntlout=&name..allfmts;
    run;
%mend;

%macro Delete_XMLStream(fref);
    %let rc=%sysfunc(fdelete(&fref));
%mend;
```

If you do not pass an XML stream to a High-Performance Analytics procedure that supports the FMTLIBXML= option, the procedure generates an XML stream as needed when it is invoked.

Syntax

CLASS Statement

CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < / *global-options* > **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. These variables enter the analysis not through their values, but through levels to which the unique values are mapped. See the section "Levelization of Classification Variables" on page 41 for details about these mappings.

If a CLASS statement is specified, it must precede the MODEL statement in High-Performance Analytics procedures that support a MODEL statement.

If the procedure permits a classification variable as a response (dependent variable, target), the response does not need to be specified in the CLASS statement.

Options can be specified either as individual variable *options* or as *global-options*. You can specify *options* for each variable by enclosing the options in parentheses after the variable name. You can also specify *global-options* for the CLASS statement by placing them after a slash (/). *Global-options* are applied to all the variables specified in the CLASS statement. If you specify more than one CLASS statement, the *global-options* specified in any one CLASS statement apply to all CLASS statements. However, individual CLASS variable *options* override the *global-options*.

You can specify the following values for either an *option* or a *global-option*:

DESCENDING

DESC

reverses the sorting order of the classification variable. If both the DESCENDING and ORDER= options are specified, High-Performance Analytics procedures order the categories according to the ORDER= option and then reverse that order.

ORDER=DATA | FORMATTED | INTERNAL

ORDER=FREQ | FREQDATA | FREQFORMATTED | FREQINTERNAL

specifies the sorting order for the levels of classification variables. This ordering determines which parameters in the model correspond to each level in the data. By default, ORDER=FORMATTED. For ORDER=FORMATTED and ORDER=INTERNAL, the sort order is machine-dependent. When ORDER=FORMATTED is in effect for numeric variables for which you have supplied no explicit format, the levels are ordered by their internal values.

The following table shows how High-Performance Analytics procedures interpret values of the ORDER= option.

Value of ORDER=	Levels Sorted By
DATA	Order of appearance in the input data set
FORMATTED	External formatted values, except for numeric variables with no explicit format, which are sorted by their unformatted (internal) values
FREQ	Descending frequency count (levels with more observations come earlier in the order)
FREQDATA	Order of descending frequency count, and within counts by order of appearance in the input data set when counts are tied
FREQFORMATTED	Order of descending frequency count, and within counts by formatted value when counts are tied
FREQINTERNAL	Order of descending frequency count, and within counts by unformatted (internal) value when counts are tied
INTERNAL	Unformatted value

For more information about sorting order, see the chapter on the SORT procedure in the *Base SAS Procedures Guide* and the discussion of BY-group processing in *SAS Language Reference: Concepts*.

REF=*'level'* | *keyword*

REFERENCE=*'level'* | *keyword*

specifies the reference level for PARAM=REFERENCE. For an individual (but not a global) variable REF= *option*, you can specify the *level* of the variable to use as the reference level. Specify the formatted value of the variable if a format is assigned. For a REF= *option* or *global-option*, you can use one of the following *keywords*. The default is REF=LAST.

FIRST designates the first ordered level as reference.

LAST designates the last ordered level as reference.

If you choose a reference level for any CLASS variable, all variables are parameterized in the reference parameterization for computational efficiency. In other words, High-Performance Analytics procedures apply a single parameterization method to all classification variables.

Suppose that the variable temp has three levels with values `'hot'`, `'warm'`, and `'cold'`, and that the variable gender has two levels with values `'M'` and `'F'`. The following statements fit a logistic regression model:

```
proc hplogistic;
   class gender(ref='F') temp;
   model y = gender gender*temp;
run;
```

Both CLASS variables are in reference parameterization in this model. The reference levels are `'F'` for the variable gender and `'warm'` for the variable temp, since the statements are equivalent to the following statements:

```
proc hplogistic;
   class gender(ref='F') temp(ref=last);
   model y = gender gender*temp;
run;
```

SPLIT

requests that the columns of the design matrix that correspond to any effect that contains a split classification variable can be selected to enter or leave a model independently of the other design columns of that effect. This option is specific to the HPREG procedure

Suppose that the variable temp has three levels with values `'hot'`, `'warm'`, and `'cold'`, that the variable gender has two levels with values `'M'` and `'F'`, and that the variables are used in a PROC HPREG run as follows:

```
proc hpreg;
   class temp gender / split;
   model y = gender gender*temp;
run;
```

The two effects in the MODEL statement are split into eight independent effects. The effect "gender" is split into two effects labeled "gender_M" and "gender_F". The effect "gender*temp" is split into six effects labeled "gender_M*temp_hot", "gender_F*temp_hot", "gender_M*temp_warm", "gender_F*temp_warm", "gender_M*temp_cold", and "gender_F*temp_cold". The previous PROC HPREG step is equivalent to the following:

```
proc hpreg;
   model y = gender_M gender_F
             gender_M*temp_hot  gender_F*temp_hot
             gender_M*temp_warm gender_F*temp_warm
             gender_M*temp_cold gender_F*temp_cold;
run;
```

The split option can be used on individual classification variables. For example, consider the following PROC HPREG step:

```
proc hpreg;
   class temp(split) gender;
   model y = gender gender*temp;
run;
```

In this case the effect "gender" is not split and the effect "gender*temp" is split into three effects labeled "gender*temp_hot", "gender*temp_warm", and "gender*temp_cold". Furthermore each of these three split effects now has two parameters that correspond to the two levels of "gender." The PROC HPREG step is equivalent to the following:

```
proc hpreg;
   class gender;
   model y = gender gender*temp_hot gender*temp_warm gender*temp_cold;
run;
```

The following values can be specified as a *global-option*:

MISSING
treats missing values (".", ".A", . . . , ".Z" for numeric variables and blanks for character variables) as valid values for the CLASS variable.

If you do not specify the MISSING option, observations with missing values for CLASS variables are removed from the analysis, even if the CLASS variables are not used in the model formulation.

PARAM=*keyword*
specifies the parameterization method for the classification variable or variables. You can specify the following *keywords*:

GLM a less-than-full-rank reference cell coding. This parameterization is used in, for example, the GLM, MIXED, and GLIMMIX procedures in SAS/STAT.

REFERENCE a reference cell encoding. You can choose the reference value with a specific variable option in the CLASS statement, or designate the first or last ordered value with a *global-option*. The default is REF=LAST.

The GLM parameterization is the default. See the section "Specification and Parameterization of Model Effects" on page 44 for more information about how parameterization of classification variables affects the construction and interpretation of model effects.

TRUNCATE<=*n***>**
specifies the truncation width of formatted values of CLASS variables when the optional *n* is specified.

If *n* is not specified, the TRUNCATE option requests that classification levels should be determined using no more than the first 16 characters of the formatted values of CLASS variables.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. High-Performance Analytics procedures that support the FREQ statement treat each observation as if it appeared f times, where f is the value of the FREQ variable for the observation. If the frequency value is not an integer, it is truncated to an integer. If the frequency value is less than 1 or missing, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

ID Statement

ID *variables* **;**

The ID statement lists one or more variables from the input data set that are transferred to output data sets created by High-Performance Analytics procedures, provided that the output data set contains one (or more) records per input observation. For example, when an OUTPUT statement is used to produce observation-wise scores or prediction statistics, ID variables are added to the output data set.

By default, High-Performance Analytics procedures do not include all variables from the input data set in output data sets. In the following statements, a logistic regression model is fit and then scored. The input and output data are stored in the Greenplum database. The output data set contains three columns (p, account, trans_date) where p is computed during the scoring process and the account and transaction date are transferred from the input data set (High-Performance Analytics procedures also transfer any distribution keys from the input to the output data).

```
libname GPLib greenplm server=gpdca user=XXX password=YYY
              database=ZZZ;
proc hplogistic data=gplib.myData;
   class a b;
   model y = a b x1-x20;
   output out=gplib.scores pred=p;
   id account trans_date;
run;
```

SELECTION Statement

SELECTION < *options* > **;**

High-Performance Analytics procedures that support model selection use the SELECTION statement to control details about the model selection process. This statement is supported in different degrees by the HPREDUCE, HPREG, and HPLOGISTIC procedures. The HPREG procedure supports the most complete set of options.

You can specify the following *options* in the SELECTION statement:

METHOD=NONE | *method*< *method-options* >

specifies the method used to select the model, optionally followed by parentheses enclosing options that are applicable to the specified method. The default selection method (when the METHOD= option is not specified) is METHOD=STEPWISE.

The following *methods* are available and are explained in detail in the section "Methods" on page 52.

NONE specifies no model selection.

FORWARD specifies forward selection. This method starts with no effects in the model and adds effects.

BACKWARD specifies backward elimination. This method starts with all effects in the model and deletes effects.

STEPWISE specifies stepwise regression. This method is similar to the FORWARD method except that effects already in the model do not necessarily stay there.

FORWARDSWAP specifies forward-swap selection, which is an extension of the forward selection method. Before any addition step, all pairwise swaps of one effect in the model and one effect out of the current model that improve the selection criterion are made. When the selection criterion is R square, this method is the same as the MAXR method in the REG procedure in SAS/STAT software. This method is supported in High-Performance Analytics only by the HPREG procedure.

LAR specifies least angle regression. Like forward selection, this method starts by adding effects to an empty model. The parameter estimates at any step are "shrunk" when compared to the corresponding least squares estimates. If the model contains classification variables, then these classification variables are split. See the SPLIT option in the CLASS statement for details. This method is supported in High-Performance Analytics only by the HPREG procedure.

LASSO adds and deletes parameters based on a version of ordinary least squares where the sum of the absolute regression coefficients is constrained. If the model contains classification variables, then these classification variables are split. See the SPLIT option in the CLASS statement for details. This method is supported in High-Performance Analytics only by the HPREG procedure.

Table 3.1 lists the applicable *method-options* for each of these methods.

Table 3.1 Applicable *method-options* by *method*

method-option	FORWARD	BACKWARD	STEPWISE	FORWARDSWAP	LAR	LASSO
ADAPTIVE					x	x
CHOOSE =	x	x	x		x	x
COMPETITIVE			x			
CRITERION =	x	x	x	x		
FAST		x				
LSCOEFFS					x	x
MAXEFFECTS =	x		x	x	x	x
MAXSTEPS =	x	x	x	x	x	x
MINEFFECTS =		x	x			
SELECT =	x	x	x	x		
SLENTRY =	x		x		x	x
SLSTAY =		x	x			x
STOP =	x	x	x	x	x	x

The syntax of the *method-options* that you can specify in parentheses after the SELECTION= option *method* follows. As described in Table 3.1, not all selection *method-options* are applicable to every SELECTION= *method*.

ADAPTIVE < (GAMMA=*nonnegative number***) >**

requests that adaptive weights be applied to each of the coefficients when METHOD=LASSO. Ordinary least squares estimates of the model parameters are used to form the adaptive weights. You use the GAMMA= option to specify the power transformation that is applied to the parameters in forming the adaptive weights. The default value is GAMMA=1.

CHOOSE=*criterion*

chooses from the list of models (at each step of the selection process) the model that yields the best value of the specified criterion. If the optimal value of the specified criterion occurs for models at more than one step, then the model with the smallest number of parameters is chosen. If you do not specify the CHOOSE= option, then the selected model is the model at the final step in the selection process. The criteria that are supported depend on the type of model that is being fit. For the supported criteria, see the chapters for the relevant High-Performance Analytics procedures.

COMPETITIVE

is applicable only as a *method-option* when METHOD=STEPWISE and the SELECT criterion is not SL. If you specify the COMPETITIVE option, then the SELECT= criterion is evaluated for all models where an effect currently in the model is dropped or an effect not yet in the model is added. The effect whose removal or addition to the model yields the maximum improvement to the SELECT= criterion is dropped or added.

CRITERION=*criterion*

is an alias for the SELECT option.

FAST
implements the computational algorithm of Lawless and Singhal (1978) to compute a first-order approximation to the remaining slope estimates for each subsequent elimination of a variable from the model. When applied in backward selection, the option essentially leads to approximating the selection process as the selection process of a linear regression model in which the crossproducts matrix equals the Hessian matrix in the full model under consideration. The FAST option is available only when METHOD=BACKWARD in the HPLOGISTIC procedure. It is computationally efficient in logistic regression models because the model is not fit after removal of each effect.

LSCOEFFS
requests a hybrid version of the LAR and LASSO methods, where the sequence of models is determined by the LAR or LASSO algorithm but the coefficients of the parameters for the model at any step are determined by using ordinary least squares.

MAXEFFECTS=*n*
specifies the maximum number of effects in any model considered during the selection process. This option is ignored with METHOD=BACKWARD. If at some step of the selection process the model contains the specified maximum number of effects, then no candidates for addition are considered.

MAXSTEPS=*n*
specifies the maximum number of selection steps that are performed. The default value of *n* is the number of effects in the MODEL statement when METHOD=FORWARD, METHOD=BACKWARD, or METHOD=LAR. It is three times the number of effects when METHOD=STEPWISE or METHOD=LASSO.

MINEFFECTS=*n*
specifies the minimum number of effects in any model considered during backward selection. This option is ignored unless METHOD=BACKWARD is specified. The backward selection process terminates if at some step of the selection process the model contains the specified minimum number of effects.

SELECT=SL | *criterion*
specifies the criterion that the procedure uses to determine the order in which effects enter or leave at each step of the selection method. The criteria that are supported depend on type of model that is being fit. See the chapter for the relevant High-Performance Analytics procedure for the supported criteria.

The SELECT option is not valid with the LAR and LASSO methods. You can use SELECT=SL to request the traditional approach, where effects enter and leave the model based on the significance level. With other SELECT= criteria, the effect that is selected to enter or leave at any step of the selection process is the effect whose addition to or removal from the current model yields the maximum improvement in the specified criterion.

SLENTRY=*value*

SLE=*value*
specifies the significance level for entry, used when the STOP=SL or SELECT=SL option is in effect. The default is 0.05.

SLSTAY=*value*

SLS=*value*

specifies the significance level for staying in the model, used when the STOP=SL or SELECT=SL option is in effect. The default is 0.05.

STOP=SL | NONE | *criterion*

specifies a criterion that is used to stop the selection process. The criteria that are supported depend on the type of model that is being fit. See the chapter for the relevant High-Performance Analytics procedure for the supported criteria.

If you do not specify the STOP= option but do specify the SELECT= option, then the criterion specified in the SELECT= option is also used as the STOP= criterion.

If you specify STOP=NONE, then the selection process stops if no suitable add or drop candidates can be found or if a size-based limit is achieved. For example, if you specify STOP=NONE MAXEFFECTS=5, then the selection process stops at the first step that produces a model with five effects.

With STOP=SL, selection stops at the step where the significance level of the candidate for entry is greater than the SLENTRY= value for addition steps when METHOD=FORWARD or METHOD=STEPWISE and where the significance level of the candidate for removal is greater than the SLSTAY= value when METHOD=BACKWARD or METHOD=STEPWISE.

If you specify a criterion other than SL with the STOP= option, then the selection process stops if the selection process produces a local extremum of this criterion, or if a size-based limit is achieved. For example, if you specify STOP=AIC MAXSTEPS=5, then the selection process stops before step 5 if the sequence of models has a local minimum of the AIC criterion before step 5. The determination of whether a local minimum is achieved is made on the basis of a stop horizon. The default stop horizon is 3, but you can change this by using the STOPHORIZON= option. If the stop horizon is n and the STOP= criterion at any step is better than the stop criterion at the next n steps, then the selection process terminates.

DETAILS=NONE | SUMMARY | ALL

DETAILS=STEPS< CANDIDATES(ALL | *n***) >**

specifies the level of detail about the selection process that is produced. The default is DETAILS=SUMMARY.

The DETAILS=ALL and DETAILS=STEPS options produce the following output:

- tables that provide information about the model selected at each step of the selection process.
- entry and removal statistics for inclusion or exclusion candidates at each step. By default, only the top 10 candidates at each step are shown. If you specify STEPS(CANDIDATES(*n*)), then the best *n* candidates are shown. If you specify STEPS(CANDIDATES(ALL)), then all candidates are shown.
- a selection summary table that shows by step the effect that is added to or removed from the model in addition to the values of the SELECT, STOP, and CHOOSE criteria for the resulting model.
- a stop reason table that describes why the selection process stopped.
- a selection reason table that describes why the selected model was chosen.

- a selected effects table that lists the effects that are in the selected model.

The DETAILS=SUMMARY option produces only the selection summary, stop reason, selection reason, and selected effects tables.

HIERARCHY=NONE | SINGLE | SINGLECLASS
specifies whether and how the model hierarchy requirement is applied. This option also controls whether a single effect or multiple effects are allowed to enter or leave the model in one step. You can specify that only classification effects, or both classification and continuous effects, be subject to the hierarchy requirement. The HIERARCHY= option is ignored unless you also specify one of the following options: METHOD=FORWARD, METHOD=BACKWARD, or METHOD=STEPWISE.

Model hierarchy refers to the requirement that, for any term to be in the model, all model effects contained in the term must be present in the model. For example, in order for the interaction A*B to enter the model, the main effects A and B must be in the model. Likewise, neither effect A nor effect B can leave the model while the interaction A*B is in the model.

The keywords you can specify in the HIERARCHY= option are as follows:

NONE specifies that model hierarchy not be maintained. Any single effect can enter or leave the model at any given step of the selection process.

SINGLE specifies that only one effect enter or leave the model at one time, subject to the model hierarchy requirement. For example, suppose that the model contains the main effects A and B and the interaction A*B. In the first step of the selection process, either A or B can enter the model. In the second step, the other main effect can enter the model. The interaction effect can enter the model only when both main effects have already entered. Also, before A or B can be removed from the model, the A*B interaction must first be removed. All effects (CLASS and interval) are subject to the hierarchy requirement.

SINGLECLASS is the same as HIERARCHY=SINGLE except that only CLASS effects are subject to the hierarchy requirement.

The default value is HIERARCHY=NONE.

SELECTION=NONE | BACKWARD | FORWARD | FORWARDSWAP | STEPWISE | LAR | LASSO
is an alias for the METHOD= option.

STOPHORIZON=*n*
specifies the number of consecutive steps at which the STOP= criterion must worsen for a local extremum to be detected. The default value is STOPHORIZON=3. The stop horizon value is ignored if you also specify STOP=NONE or STOP=SL. For example, suppose that STOP=AIC and the sequence of AIC values at steps 1 to 6 of a selection are 10, 7, 4, 6, 5, 2. If STOPHORIZON=2, then the AIC criterion is deemed to have a local minimum at step 3 because the AIC value at the next two steps are greater than the value of 4 that occurs at step 3. However, if STOPHORIZON=3, then the value of step 3 is not deemed to be a local minimum because the AIC value at step 6 is lower than the AIC value at step 3.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a High-Performance Analytics procedure.

With the PERFORMANCE statement, you can also control whether a High-Performance Analytics procedure executes in SMP or MPP mode.

You can specify the following *performance-options* in the PERFORMANCE statement:

COMMIT=*n*

requests that the High-Performance Analytics procedure write periodic updates to the SAS Log when observations are sent from the client to the appliance for distributed processing.

High-Performance Analytics procedures do not have to use input data that are stored in the appliance. You can perform distributed computations regardless of the origin or format of the input data, provided the data are in a format that can be read by the SAS System (for example, because a SAS/ACCESS engine is available).

In the following example, the HPREG procedure performs LASSO variable selection with an input data set stored on the client:

```
proc hpreg data=work.one;
   model y = x1-x500;
   selection method=lasso;
   performance nodes=10 host='mydca' commit=10000;
run;
```

In order to perform the work as requested using 10 nodes on the appliance, the data set Work.One needs to be distributed to the appliance.

High-Performance Analytics procedures send the data in blocks to the appliance. Whenever the number of observations sent exceeds an integer multiple of the COMMIT= size, a SAS Log message is produced. The message indicates the actual number of observations distributed, and not an integer multiple of the COMMIT= size.

CPUCOUNT=ACTUAL | *num*

specifies how many processors the procedure assumes are available on each host in the computing environment. *num* can be any integer from 1 to 256.

CPUCOUNT=ACTUAL sets CPUCOUNT to the number of physical processors available. This number can be less than the physical number of CPUs if the SAS process has been restricted by system administration tools. Setting CPUCOUNT= to a number greater than the actual number of available CPUs might result in reduced performance. This option overrides the CPUCOUNT= SAS system option.

If a High-Performance Analytics procedure executes in SMP mode, this option refers to the client machine of the SAS session. In MPP mode, this option applies to the nodes on the appliance.

DATASERVER=*"name"*
specifies the name of the server on Teradata systems as defined through the *hosts* file and as used in the LIBNAME statement for Teradata. For example, if the *hosts* file defines

```
myservercop1  33.44.55.66
```

as the server for Teradata, then a LIBNAME specification would be as follows:

```
libname TDLib teradata server=myserver user= password= database= ;
```

A PERFORMANCE statement to induce running alongside the Teradata server would specify the following:

```
performance dataserver="myserver";
```

If the DATASERVER= option is specified, it overrides the GRIDDATASERVER environment variable.

DETAILS
requests a table that shows a timing breakdown of the procedure steps.

TIMEOUT=*s*
specifies the timeout in seconds for a High-Performance Analytics procedure to wait for a connection to the appliance and establish a connection back to the client. The default is *s*=120 seconds. If jobs are submitted to the appliance through workload management tools that might suspend access to the appliance for a longer period, you might want to increase the timeout value.

HOST=*"name"*
GRIDHOST=*"name"*
specifies the name of the appliance host in single or double quotes. If the HOST= option is specified, it overrides the value of the GRIDHOST environment variable.

INSTALL=*"name"*
INSTALLLOC=*"name"*
specifies the directory in which the High-Performance Analytics shared libraries are installed on the appliance. Specifying the INSTALL= option overrides the GRIDINSTALLLOC environment variable.

NODES=ALL | *n*
NNODES=ALL | *n*
specifies the number of nodes in the distributed computing environment, provided that the data are not processed alongside the database.

If you specify NODES=0, you indicate that you want to process the data in SMP mode on the client machine. If the input data are not alongside the database, this is the default. The High-Performance Analytics procedures then perform the analysis multithreaded on the client. For example, the following sets of statements are equivalent:

```
proc hplogistic data=one;
   model y = x;
run;
```

```
proc hplogistic data=one;
   model y = x;
   performance nodes=0;
run;
```

If the data are not read alongside the database, the NODES= option specifies the number of nodes on the appliance involved in the analysis. For example, the following statements perform the analysis in MPP mode using 10 units of work on the appliance identified with the HOST= option:

```
proc hplogistic data=one;
   model y = x;
   performance nodes=10 host="hpa.sas.com";
run;
```

If the number of nodes can be modified by the application, you can specify a NODES=*n* option where *n* exceeds the number of physical nodes on the appliance. The High-Performance Analytics software then *oversubscribes* the nodes and associates nodes with multiple units of work. For example, on a system with 16 appliance nodes, the following statements oversubscribe the system by a factor of 3:

```
proc hplogistic data=one;
   model y = x;
   performance nodes=48 host="hpa.sas.com";
run;
```

Generally, it is not advisable to oversubscribe the system because the analytic code is optimized for a certain level of multithreading on the nodes that depends on the CPU count. You can specify NODES=ALL if you want to use all available nodes on the appliance without oversubscribing the system.

If the data are read alongside the distributed database on the appliance, specifying a nonzero value for the NODES= option has no effect. The number of units of work in the distributed computing environment is then determined by the distribution of the data and cannot be altered. For example, if you are running alongside an appliance with 24 nodes, the NODES= option in the following statements is ignored:

```
libname GPLib greenplm server=gpdca user=XXX password=YYY
              database=ZZZ;
proc hplogistic data=gplib.one;
   model y = x;
   performance nodes=10 host="hpa.sas.com";
run;
```

NTHREADS=*n*

specifies the number of threads for analytic computations and overrides the SAS system option THREADS | NOTHREADS. If you do not specify the NTHREADS= option, the number of threads are determined based on the number of CPUs on the host on which the analytic computations execute. The algorithm by which a CPU count is converted to a thread count is specific to the High-Performance Analytics procedure. Most procedures create one thread per CPU for the analytic computations. You may use NTHREADS=CPUCOUNT to explicitly specify one thread per CPU.

By default, High-Performance Analytics procedures execute in multiple concurrent threads unless turned off by the NOTHREADS system option or you force single-threaded execution with NTHREADS=1. The largest number that can be specified for *n* is 256. Individual High-Performance Analytics procedures can impose more stringent limits if called for by algorithmic considerations.

You can affect the determination of the CPU count with the CPUCOUNT= option in the PERFORMANCE statement.

NOTE: The SAS system options THREADS | NOTHREADS apply to the client machine on which the SAS High-Performance Analytics procedures execute. They do not apply to the compute nodes in a distributed environment.

VAR Statement

VAR *variable-list* **;**

Some High-Performance Analytics procedures (in particular procedures that do not support a MODEL statement) use a VAR statement to identify numerical variables for the analysis.

WEIGHT Statement

WEIGHT *variable* **;**

The *variable* in the WEIGHT statement is used as a weight to perform a weighted analysis of the data. Observations with nonpositive or missing weights are not included in the analysis. If a WEIGHT statement is not included, all observations used in the analysis are assigned a weight of 1.

Levelization of Classification Variables

A classification variable is a variable that enters the statistical analysis or model not through its values but through its levels. The process of associating values of a variable with levels is termed *levelization*.

During the process of levelization, observations that share the same value are assigned to the same level. The manner in which values are grouped can be affected by the inclusion of formats. The sort order of the levels can be determined with the ORDER= option in the procedure statement. With High-Performance Analytics procedures, you can also control the sorting order separately for each variable in the CLASS statement.

Consider the data on nine observations in Table 3.2. The variable A is integer-valued, and the variable X is a continuous variable with a missing value for the fourth observation. The fourth and fifth columns of Table 3.2 apply two different formats to the variable X.

Table 3.2 Example Data for Levelization

Obs	A	x	FORMAT x 3.0	FORMAT x 3.1
1	2	1.09	1	1.1
2	2	1.13	1	1.1
3	2	1.27	1	1.3
4	3	.	.	.
5	3	2.26	2	2.3
6	3	2.48	2	2.5
7	4	3.34	3	3.3
8	4	3.34	3	3.3
9	4	3.14	3	3.1

By default, levelization of the variables groups the observations by the formatted value of the variable, except for numerical variables for which no explicit format is provided. Numerical variables for which no explicit format is provided are sorted by their internal value. The levelization of the four columns in Table 3.2 leads to the level assignment in Table 3.3.

Table 3.3 Values and Levels

	A		X		FORMAT x 3.0		FORMAT x 3.1	
Obs	Value	Level	Value	Level	Value	Level	Value	Level
1	2	1	1.09	1	1	1	1.1	1
2	2	1	1.13	2	1	1	1.1	1
3	2	1	1.27	3	1	1	1.3	2
4	3	2	.	.	.	.	.	.
5	3	2	2.26	4	2	2	2.3	3
6	3	2	2.48	5	2	2	2.5	4
7	4	3	3.34	7	3	3	3.3	6
8	4	3	3.34	7	3	3	3.3	6
9	4	3	3.14	6	3	3	3.1	5

The sorting order for the levels of CLASS variables can be affected with the ORDER= option in the CLASS statement.

When ORDER=FORMATTED (which is the default) is in effect for numeric variables for which you have supplied no explicit format, the levels are ordered by their internal values. To order numeric class levels with no explicit format by their BEST12. formatted values, you can specify the BEST12. format explicitly for the CLASS variables.

Table 3.4 shows how values of the ORDER= option are interpreted.

Table 3.4 Interpretation of Values of ORDER= Option

Value of ORDER=	Levels Sorted By
DATA	Order of appearance in the input data set
FORMATTED	External formatted value, except for numeric variables with no explicit format, which are sorted by their unformatted (internal) value
FREQ	Descending frequency count (levels with the most observations come first in the order)
INTERNAL	Unformatted value
FREQDATA	Order of descending frequency count, and within counts by order of appearance in the input data set when counts are tied
FREQFORMATTED	Order of descending frequency count, and within counts by formatted value when counts are tied
FREQINTERNAL	Order of descending frequency count, and within counts by unformatted (internal) value when counts are tied

For FORMATTED, FREQFORMATTED, FREQINTERNAL, and INTERNAL values, the sort order is machine-dependent. For more information about sort order, see the chapter on the SORT procedure in the *Base SAS Procedures Guide* and the discussion of BY-group processing in *SAS Language Reference: Concepts*.

When the MISSING option is specified in the CLASS statement, the missing values ('.' for a numeric variable and blanks for a character variable) are included in the levelization and are assigned a level. Table 3.5 displays the results of levelizing the values in Table 3.2 when the MISSING option is in effect.

Table 3.5 Values and Levels with the MISSING Option

	A		X		FORMAT x 3.0		FORMAT x 3.1	
Obs	Value	Level	Value	Level	Value	Level	Value	Level
1	2	1	1.09	2	1	2	1.1	2
2	2	1	1.13	3	1	2	1.1	2
3	2	1	1.27	4	1	2	1.3	3
4	3	2	.	1	.	1	.	1
5	3	2	2.26	5	2	3	2.3	4
6	3	2	2.48	6	2	3	2.5	5
7	4	3	3.34	8	3	4	3.3	7
8	4	3	3.34	8	3	4	3.3	7
9	4	3	3.14	7	3	4	3.1	6

When the MISSING option is not specified, it is important to understand the implications of missing values for your statistical analysis. When a High-Performance Analytics procedure levelizes the CLASS variables, an observation for which any CLASS variable has a missing value is excluded from the analysis. This is true regardless of whether the variable is used to form the statistical model. Consider, for example, the case

in which some observations contain missing values for variable A but the records for these observations are otherwise complete with respect to all other variables in the statistical models. The analysis results from the following statements do not include any observations for which variable A contains missing values, even though A is not specified in the MODEL statement:

```
class A B;
model y = B x B*x;
```

High-Performance Analytics procedures print a "Number of Observations" table that shows the number of observations read from the data set and the number of observations used in the analysis. Pay careful attention to this table—especially when your data set contains missing values—to ensure that no observations are unintentionally excluded from the analysis.

Specification and Parameterization of Model Effects

High-Performance Analytics procedures that have a MODEL statement support the formation of effects. An *effect* is an element in a linear model structure that is formed from one or more variables. At some point the statistical representations of these models involve linear structures such as

$$\mathbf{X}\boldsymbol{\beta}$$

or

$$\mathbf{X}\boldsymbol{\beta} + \mathbf{Z}\boldsymbol{\gamma}$$

The model matrices $\mathbf{X}$ and $\mathbf{Z}$ are formed according to effect construction rules.

Procedures that also have a CLASS statement support the rich set of effects discussed in this section. In order to correctly interpret the results from a statistical analysis, you need to understand how construction (*parameterization*) rules apply to regression-type models, whether these are linear models in the HPREG procedure or generalized linear models in the HPLOGISTIC procedure.

Effects are specified with a special notation that uses variable names and operators. There are two kinds of variables: classification (or CLASS) variables and continuous variables. *Classification variables* can be either numeric or character and are specified in a CLASS statement. See the section "Levelization of Classification Variables" on page 41 for details. An independent variable that is not declared in the CLASS statement is assumed to be *continuous*. For example, the heights and weights of subjects are continuous variables.

Two primary operators (crossing and nesting) are used for combining the variables, and several additional operators are used to simplify effect specification. Operators are discussed in the section "Effect Operators" on page 45.

High-Performance Analytics procedures with a CLASS statement support a general linear model (GLM) parameterization and a reference parameterization for the classification variables. The GLM parameterization is the default for all High-Performance Analytics procedures. See the sections "GLM Parameterization of Classification Variables and Effects" on page 47 and "Reference Parameterization" on page 51 for details.

Effect Operators

Table 3.6 summarizes the operators that are available for selecting and constructing effects. These operators are discussed in the following sections.

Table 3.6 Available Effect Operators

Operator	Example	Description
Interaction	A*B	Crosses the levels of the effects
Nesting	A(B)	Nests A levels within B levels
Bar operator	A | B | C	Specifies all interactions
At sign operator	A | B | C@2	Reduces interactions in bar effects
Dash operator	A1-A10	Specifies sequentially numbered variables
Colon operator	A:	Specifies variables with common prefix
Double dash operator	A- -C	Specifies sequential variables in data set order

Bar and At Sign Operators

You can shorten the specification of a large factorial model by using the bar operator. For example, two ways of writing the model for a full three-way factorial model follow:

```
model Y = A B C   A*B A*C B*C   A*B*C;
model Y = A|B|C;
```

When the bar (|) is used, the right and left sides become effects, and the cross of them becomes an effect. Multiple bars are permitted. The expressions are expanded from left to right, using rules 2–4 given in Searle (1971, p. 390).

- Multiple bars are evaluated from left to right. For instance, A | B | C is evaluated as follows:

$$\begin{aligned} \text{A | B | C} &\rightarrow \{\text{ A | B }\}\text{ | C} \\ &\rightarrow \{\text{ A B A*B }\}\text{ | C} \\ &\rightarrow \text{A B A*B C A*C B*C A*B*C} \end{aligned}$$

- Crossed and nested groups of variables are combined. For example, A(B) | C(D) generates A*C(B D), among other terms.
- Duplicate variables are removed. For example, A(C) | B(C) generates A*B(C C), among other terms, and the extra C is removed.
- Effects are discarded if a variable occurs on both the crossed and nested parts of an effect. For instance, A(B) | B(D E) generates A*B(B D E), but this effect is eliminated immediately.

You can also specify the maximum number of variables involved in any effect that results from bar evaluation by specifying that maximum number, preceded by an at sign (@), at the end of the bar effect. For example, the following specification selects only those effects that contain two or fewer variables:

```
model Y = A|B|C@2;
```

The preceding example is equivalent to specifying the following MODEL statement:

```
model Y = A B C   A*B A*C B*C;
```

More examples of using the bar and at operators follow:

A | C(B)	is equivalent to	A C(B) A*C(B)
A(B) | C(B)	is equivalent to	A(B) C(B) A*C(B)
A(B) | B(D E)	is equivalent to	A(B) B(D E)
A | B(A) | C	is equivalent to	A B(A) C A*C B*C(A)
A | B(A) | C@2	is equivalent to	A B(A) C A*C
A | B | C | D@2	is equivalent to	A B A*B C A*C B*C D A*D B*D C*D
A*B(C*D)	is equivalent to	A*B(C D)

Colon, Dash, and Double Dash Operators

You can simplify the specification of a large model when some of your variables have a common prefix by using the colon (:) operator and the dash (-) operator. The dash operator enables you to list variables that are numbered sequentially, and the colon operator selects all variables with a given prefix. For example, if your data set contains the variables X1 through X9, the following MODEL statements are equivalent:

```
model Y = X1 X2 X3 X4 X5 X6 X7 X8 X9;
model Y = X1-X9;
model Y = X:;
```

If your data set contains only the three covariates X1, X2, and X9, then the colon operator selects all three variables:

```
model Y = X:;
```

However, the following specification returns an error because X3 through X8 are not in the data set:

```
model Y = X1-X9;
```

The double dash (--) operator enables you to select variables that are stored sequentially in the SAS data set, whether or not they have a common prefix. You can use the CONTENTS procedure (see the *Base SAS Procedures Guide*) to determine your variable ordering. For example, if you replace the dash in the preceding MODEL statement with a double dash, as follows, then all three variables are selected:

```
model Y = X1--X9;
```

If your data set contains the variables A, B, and C, then you can use the double dash operator to select these variables by specifying the following:

```
model Y = A--C;
```

GLM Parameterization of Classification Variables and Effects

Table 3.7 shows the types of effects that are available in High-Performance Analytics procedures; they are discussed in more detail in the following sections. Let A, B, and C represent classification variables, and let X and Z represent continuous variables.

Table 3.7 Available Types of Effects

Effect	Example	Description
Intercept	Default	Intercept (unless NOINT)
Regression	X Z	Continuous variables
Polynomial	X*Z	Interaction of continuous variables
Main	A B	CLASS variables
Interaction	A*B	Crossing of CLASS variables
Nested	A(B)	Main effect A nested within CLASS effect B
Continuous-by-class	X*A	Crossing of continuous and CLASS variables
Continuous-nesting-class	X(A)	Continuous variable X1 nested within CLASS variable A
General	X*Z*A(B)	Combinations of different types of effects

Table 3.8 shows some examples of MODEL statements that use various kinds of effects.

Table 3.8 Model Statement Effect Examples

Specification	Type of Model
`model Y=X;`	Simple regression
`model Y=X Z;`	Multiple regression
`model Y=X X*X;`	Polynomial regression
`model Y=A;`	One-way analysis of variance (ANOVA)
`model Y=A B C;`	Main-effects ANOVA
`model Y=A B A*B;`	Factorial ANOVA with interaction
`model y=A B(A) C(B A);`	Nested ANOVA
`model Y=A X;`	Analysis of covariance (ANCOVA)
`model Y=A X(A);`	Separate-slopes regression
`model Y=A X X*A;`	Homogeneity-of-slopes regression

Intercept

By default, High-Performance Analytics linear models automatically include a column of 1s in **X** which corresponds to an intercept parameter. In many procedures you can use the NOINT option in the MODEL statement to suppress this intercept. For example, the NOINT option is useful when the MODEL statement contains a classification effect and you want the parameter estimates to be in terms of the mean response for each level of that effect.

Regression Effects

Numeric variables or polynomial terms that involve them can be included in the model as regression effects (covariates). The actual values of such terms are included as columns of the relevant model matrices. You can use the bar operator with a regression effect to generate polynomial effects. For example, X | X | X expands to X X*X X*X*X, which is a cubic model.

Main Effects

If a classification variable has m levels, the GLM parameterization generates m columns for its main effect in the model matrix. Each column is an indicator variable for a given level. The order of the columns is the sort order of the values of their levels and can be controlled with the ORDER= option in the CLASS statement.

Table 3.9 is an example where β_0 denotes the intercept and A and B are classification variables with two and three levels, respectively.

Table 3.9 Example of Main Effects

Data		**I**	A		B		
A	B	β_0	A1	A2	B1	B2	B3
1	1	1	1	0	1	0	0
1	2	1	1	0	0	1	0
1	3	1	1	0	0	0	1
2	1	1	0	1	1	0	0
2	2	1	0	1	0	1	0
2	3	1	0	1	0	0	1

Typically, there are more columns for these effects than there are degrees of freedom to estimate them. In other words, the GLM parameterization of main effects is *singular*.

Interaction Effects

Often a model includes interaction (crossed) effects to account for how the effect of a variable changes with the values of other variables. With an interaction, the terms are first reordered to correspond to the order of the variables in the CLASS statement. Thus, B*A becomes A*B if A precedes B in the CLASS statement. Then, the GLM parameterization generates columns for all combinations of levels that occur in the data. The order of the columns is such that the rightmost variables in the interaction change faster than the leftmost variables (Table 3.10).

In the HPLMIXED procedure, which supports both fixed- and random-effects models, empty columns (that is, columns that would contain all 0s) are not generated for fixed effects, but they are generated for random effects.

Table 3.10 Example of Interaction Effects

Data		I	A		B			A*B					
A	B	β_0	A1	A2	B1	B2	B3	A1B1	A1B2	A1B3	A2B1	A2B2	A2B3
1	1	1	1	0	1	0	0	1	0	0	0	0	0
1	2	1	1	0	0	1	0	0	1	0	0	0	0
1	3	1	1	0	0	0	1	0	0	1	0	0	0
2	1	1	0	1	1	0	0	0	0	0	1	0	0
2	2	1	0	1	0	1	0	0	0	0	0	1	0
2	3	1	0	1	0	0	1	0	0	0	0	0	1

In the preceding matrix, main-effects columns are not linearly independent of crossed-effects columns; in fact, the column space for the crossed effects contains the space of the main effect.

When your model contains many interaction effects, you might be able to code them more parsimoniously by using the bar operator (|). The bar operator generates all possible interaction effects. For example, A | B | C expands to A B A*B C A*C B*C A*B*C. To eliminate higher-order interaction effects, use the at sign (@) in conjunction with the bar operator. For instance, A | B | C | D@2 expands to A B A*B C A*C B*C D A*D B*D C*D.

Nested Effects

Nested effects are generated in the same manner as crossed effects. Hence, the design columns generated by the following two statements are the same (but the ordering of the columns is different):

```
model Y=A B(A);

model Y=A A*B;
```

The nesting operator in High-Performance Analytics software is more of a notational convenience than an operation that is distinct from crossing. Nested effects are typically characterized by the property that the nested variables do not appear as main effects. The order of the variables within nesting parentheses is made to correspond to the order of these variables in the CLASS statement. The order of the columns is such that variables outside the parentheses index faster than those inside the parentheses, and the rightmost nested variables index faster than the leftmost variables (Table 3.11).

Table 3.11 Example of Nested Effects

Data		I	A		B(A)					
A	B	β_0	A1	A2	B1A1	B2A1	B3A1	B1A2	B2A2	B3A2
1	1	1	1	0	1	0	0	0	0	0
1	2	1	1	0	0	1	0	0	0	0
1	3	1	1	0	0	0	1	0	0	0
2	1	1	0	1	0	0	0	1	0	0
2	2	1	0	1	0	0	0	0	1	0
2	3	1	0	1	0	0	0	0	0	1

Continuous-Nesting-Class Effects

When a continuous variable nests or crosses with a classification variable, the design columns are constructed by multiplying the continuous values into the design columns for the classification effect (Table 3.12).

Table 3.12 Example of Continuous-Nesting-Class Effects

Data		**I**	A		X(A)	
X	A	β_0	A1	A2	X(A1)	X(A2)
21	1	1	1	0	21	0
24	1	1	1	0	24	0
22	1	1	1	0	22	0
28	2	1	0	1	0	28
19	2	1	0	1	0	19
23	2	1	0	1	0	23

This model estimates a separate intercept and a separate slope for X within each level of A.

Continuous-by-Class Effects

Continuous-by-class effects generate the same design columns as continuous-nesting-class effects. Table 3.13 shows the construction of the X*A effect. The two columns for this effect are the same as the columns for the X(A) effect in Table 3.12.

Table 3.13 Example of Continuous-by-Class Effects

Data		**I**	**X**	A		X*A	
X	A	β_0	X	A1	A2	X*A1	X*A2
21	1	1	21	1	0	21	0
24	1	1	24	1	0	24	0
22	1	1	22	1	0	22	0
28	2	1	28	0	1	0	28
19	2	1	19	0	1	0	19
23	2	1	23	0	1	0	23

You can use continuous-by-class effects together with pure continuous effects to test for homogeneity of slopes.

General Effects

An example that combines all the effects is X1*X2*A*B*C(D E). The continuous list comes first, followed by the crossed list, followed by the nested list in parentheses. You should be aware of the sequencing of parameters when you use statements that depend on the ordering of parameters. Such statements include CONTRAST and ESTIMATE statements, which are used in a number of procedures to estimate and test functions of the parameters.

Effects might be renamed by the procedure to correspond to ordering rules. For example, B*A(E D) might be renamed A*B(D E) to satisfy the following:

- Classification variables that occur outside parentheses (crossed effects) are sorted in the order in which they appear in the CLASS statement.
- Variables within parentheses (nested effects) are sorted in the order in which they appear in the CLASS statement.

The sequencing of the parameters generated by an effect can be described by which variables have their levels indexed faster:

- Variables in the crossed list index faster than variables in the nested list.
- Within a crossed or nested list, variables to the right index faster than variables to the left.

For example, suppose a model includes four effects—A, B, C, and D—each having two levels, 1 and 2. If the CLASS statement is

```
class A B C D;
```

then the order of the parameters for the effect B*A(C D), which is renamed A*B(C D), is

$$\begin{array}{llll} A_1B_1C_1D_1 \rightarrow & A_1B_2C_1D_1 \rightarrow & A_2B_1C_1D_1 \rightarrow & A_2B_2C_1D_1 \rightarrow \\ A_1B_1C_1D_2 \rightarrow & A_1B_2C_1D_2 \rightarrow & A_2B_1C_1D_2 \rightarrow & A_2B_2C_1D_2 \rightarrow \\ A_1B_1C_2D_1 \rightarrow & A_1B_2C_2D_1 \rightarrow & A_2B_1C_2D_1 \rightarrow & A_2B_2C_2D_1 \rightarrow \\ A_1B_1C_2D_2 \rightarrow & A_1B_2C_2D_2 \rightarrow & A_2B_1C_2D_2 \rightarrow & A_2B_2C_2D_2 \end{array}$$

Note that first the crossed effects B and A are sorted in the order in which they appear in the CLASS statement so that A precedes B in the parameter list. Then, for each combination of the nested effects in turn, combinations of A and B appear. The B effect changes fastest because it is rightmost in the cross list. Then A changes next fastest, and D changes next fastest. The C effect changes most slowly because it is leftmost in the nested list.

Reference Parameterization

Classification variables can be represented in the reference parameterization in High-Performance Analytics procedures. Only one parameterization applies to the variables in the CLASS statement.

To understand the reference representation, consider the classification variable A with four values, 1, 2, 5, and 7. The reference parameterization generates three columns (one less than the number of variable levels). The columns indicate group membership of the nonreference levels. For the reference level, the three dummy variables have a value of 0. If the reference level is 7 (REF='7'), the design columns for variable A are as shown in Table 3.14.

Table 3.14 Reference Coding

	Design Matrix		
A	**A1**	**A2**	**A5**
1	1	0	0
2	0	1	0
5	0	0	1
7	0	0	0

Parameter estimates of CLASS main effects that use the reference coding scheme estimate the difference in the effect of each nonreference level compared to the effect of the reference level.

Model Selection

Methods

The model selection methods implemented in the High-Performance Analytics procedures are specified with the METHOD= option in the SELECTION statement. The following methods are available, although specific procedures might support only a subset of these methods. Furthermore, the examples in this section refer to fit criteria that might not be supported by a specific procedure.

Full Model Fitted

When METHOD=NONE, the complete model specified in the MODEL statement is used to fit the model, and no effect selection is done.

Forward Selection

METHOD=FORWARD specifies the forward selection technique, which begins with just the intercept and then sequentially adds the effect that most improves the fit. The process terminates when no significant improvement can be obtained by adding any effect.

In the traditional implementation of forward selection, the statistic used to determine whether to add an effect is the significance level of a hypothesis test that reflects an effect's contribution to the model if it is included. At each step, the effect that is most significant is added. The process stops when the significance level for adding any effect is greater than some specified entry significance level.

An alternative approach to address the critical problem of when to stop the selection process is to assess the quality of the models produced by the forward selection method and choose the model from this sequence that "best" balances goodness of fit against model complexity. There are several criteria that you can use for this purpose. These criteria fall into two groups—information criteria and criteria based on out-of-sample prediction performance.

You use the CHOOSE= option of forward selection to specify the criterion for selecting one model from the sequence of models produced. If you do not specify a CHOOSE= criterion, then the model at the final step is the selected model.

For example, if you specify the following statement, then forward selection terminates at the step where no effect can be added at the 0.2 significance level:

```
selection method=forward(select=SL choose=AIC SLE=0.2);
```

However, the selected model is the first one with the minimal value of Akaike's information criterion. Note that in some cases this minimal value might occur at a step much earlier that the final step, while in other cases the AIC might start increasing only if more steps are done—that is, a larger value is used for the significance level for entry. If you are interested in minimizing AIC, then too many steps are done in the former case and too few in the latter case. To address this issue, the High-Performance Analytics procedures enable you to specify a stopping criterion with the STOP= option. With a stopping criterion specified, forward selection continues until a local extremum of the stopping criterion in the sequence of models generated is reached. To be deemed a local extremum, a criterion value at a given step must be better than its value at the next n steps, where n is known as the "stop horizon." By default, the stop horizon is three steps but you can change this by using the STOPHORIZON= option.

For example, if you specify the following statement, then forward selection terminates at the step where the effect to be added at the next step would produce a model with an AIC statistic larger than the AIC statistic of the current model:

```
selection method=forward(select=SL stop=AIC) stophorizon=1;
```

In most cases, provided that the entry significance level is large enough that the local extremum of the named criterion occurs before the final step, specifying either of the following statements selects the same model, but more steps are done in the first case:

```
selection method=forward(select=SL choose=CRITERION);

selection method=forward(select=SL stop=CRITERION);
```

In some cases there might be a better local extremum that cannot be reached if you specify the STOP= option but can be found if you use the CHOOSE= option. Also, you can use the CHOOSE= option in preference to the STOP= option if you want to examine how the named criterion behaves as you move beyond the step where the first local minimum of this criterion occurs.

You can specify both the CHOOSE= and STOP= options. You can also use these options together with options that specify size-based limits on the selected model. You might want to consider models generated by forward selection that have at most some fixed number of effects but select from within this set based on a criterion you specify. For example, specifying the following statements requests that forward selection continue until there are 20 effects in the final model and chooses among the sequence of models the one that has the largest value of the adjusted R-square statistic:

```
selection method=forward(stop=none maxeffects=20 choose=ADJRSQ);
```

You can also combine these options to select a model where one of two conditions is met. For example, the following statement chooses whatever occurs first between a local minimum of the sum of squares on validation data and a local minimum of the corrected Akaike's information criterion (AICC):

```
selection method=forward(stop=AICC choose=VALIDATE);
```

It is important to keep in mind that forward selection bases the decision about what effect to add at any step by considering models that differ by one effect from the current model. This search paradigm cannot guarantee reaching a "best" subset model. Furthermore, the add decision is greedy in the sense that the effect deemed most significant is the effect that is added. However, if your goal is to find a model that is best in terms of some selection criterion other than the significance level of the entering effect, then even this one step choice might not be optimal. For example, the effect you would add to get a model with the smallest value of the Mallows' $C(p)$ statistic at the next step is not necessarily the same effect that is most significant based on a hypothesis test. The High-Performance Analytics procedures enable you to specify the criterion to optimize at each step by using the SELECT= option. For example, the following statement requests that at each step the effect that is added be the one that gives a model with the smallest value of the Mallows' $C(p)$ statistic:

```
selection method=forward(select=CP);
```

In the case where all effects are variables (that is, effects with one degree of freedom and no hierarchy), using ADJRSQ, AIC, AICC, BIC, CP, RSQUARE, or SBC as the selection criterion for forward selection produces the same sequence of additions. However, if the degrees of freedom contributed by different effects are not constant or if an out-of-sample prediction-based criterion is used, then different sequences of additions might be obtained.

You can use the SELECT= option together with the CHOOSE= and STOP= options. If you specify only the SELECT= criterion, then this criterion is also used as the stopping criterion. In the previous example where only the selection criterion is specified, not only do effects enter based on the Mallows' $C(p)$ statistic, but the selection terminates when the $C(p)$ statistic has a local minimum.

You can find discussion and references to studies about criteria for variable selection in Burnham and Anderson (2002), along with some cautions and recommendations.

Examples of Forward Selection Specifications

The following statement adds effects that at each step give the lowest value of the SBC statistic and stops at the step where adding any effect would increase the SBC statistic:

```
selection method=forward stophorizon=1;
```

The following statement adds effects based on significance level and stops when all candidate effects for entry at a step have a significance level greater than the default entry significance level of 0.05:

```
selection=forward(select=SL);
```

The following statement adds effects based on significance level and stops at a step where adding any effect increases the error sum of squares computed on the validation data:

```
selection=forward(select=SL stop=validation) stophorizon=1;
```

The following statement adds effects that at each step give the lowest value of the AIC statistic and stops at the first step whose AIC value is smaller than the AIC value at the next three steps:

```
selection=forward(select=AIC);
```

The following statement adds effects that at each step give the largest value of the adjusted R-square statistic and stops at the step where the significance level corresponding to the addition of this effect is greater than 0.2:

```
selection=forward(select=ADJRSQ stop=SL SLE=0.2);
```

Backward Elimination

METHOD=BACWARD specifies the backward elimination technique, which starts from the full model, which includes all independent effects. Then effects are deleted one by one until a stopping condition is satisfied. At each step, the effect that shows the smallest contribution to the model is deleted.

In the traditional implementation of backward selection, the statistic used to determine whether to drop an effect is significance level. At any step, the least significant predictor is dropped and the process continues until all effects that remain in the model are significant at a specified stay significance level (SLS).

Just as with forward selection, you can change the criterion used to assess effect contributions with the SELECT= option. You can also specify a stopping criterion with the STOP= option and use a CHOOSE= option to provide a criterion for selecting among the sequence of models produced. See the discussion in the section "Forward Selection" on page 52 for additional details.

Examples of Backward Selection Specifications

The following statement removes effects that at each step produce the largest value of the Schwarz Bayesian information criterion (SBC) statistic and stops at the step where removing any effect increases the SBC statistic:

```
selection method=backward stophorizon=1;
```

The following statement removes effects based on significance level and stops when all candidate effects for removal at a step are significant at the default stay significance level of 0.05:

```
selection method=backward(select=SL);
```

The following statement removes effects based on significance level and stops when all effects in the model are significant at the 0.1 level. Finally, from the sequence of models generated, the chosen model is the one that gives the smallest average square error when scored on the validation data:

```
selection method=backward(select=SL choose=validate SLS=0.1);
```

The following statement applies in logistic regression models the fast backward technique of Lawless and Singhal (1978), a first-order approximation that has greater numerical efficiency than full backward selection:

```
selection method=backward(fast);
```

The fast technique fits an initial full logistic model and a reduced model after the candidate effects have been dropped. On the other hand, full backward selection fits a logistic regression model each time an effect is removed from the model.

Stepwise Selection

METHOD=STEPWISE specifies the stepwise method, which is a modification of the forward selection technique that differs in that effects already in the model do not necessarily stay there.

In the traditional implementation of stepwise selection method, the same entry and removal significance levels for the forward selection and backward elimination methods are used to assess contributions of effects as they are added to or removed from a model. If at a step of the stepwise method any effect in the model is not significant at the SLSTAY= level, then the least significant of these effects is removed from the model and the algorithm proceeds to the next step. This ensures that no effect can be added to a model while some effect currently in the model is not deemed significant. Only after all necessary deletions have been accomplished can another effect be added to the model. In this case the effect whose addition is the most significant is added to the model and the algorithm proceeds to the next step. The stepwise process ends when none of the effects outside the model is significant at the SLENTRY= level and every effect in the model is significant at the SLSTAY= level. In some cases, neither of these two conditions for stopping is met and the sequence of models cycles. In this case, the stepwise method terminates at the end of the cycle.

Just as with forward selection and backward elimination, you can use the SELECT= option to change the criterion used to assess effect contributions. You can also specify a stopping criterion with the STOP= option and use a CHOOSE= option to provide a criterion for selecting among the sequence of models produced. See the discussion in the section "Forward Selection" on page 52 for additional details.

For selection criteria other than significance level, the High-Performance Analytics procedures optionally support a further modification in the stepwise method. In the standard stepwise method, no effect can enter the model if removing any effect currently in the model would yield an improved value of the selection criterion. In the modification, you can use the COMPETITIVE option to specify that addition and deletion of effects should be treated competitively. The selection criterion is evaluated for all models obtained by deleting an effect from the current model or by adding an effect to this model. The action that most improves the selection criterion is the action taken.

Examples of Stepwise Selection Specifications

The following statement requests stepwise selection based on the SBC criterion:

```
selection method=stepwise;
```

First, if removing any effect yields a model with a lower SBC statistic than the current model, then the effect that produces the smallest SBC statistic is removed. When removing any effect increases the SBC statistic, then provided that adding some effect lowers the SBC statistic, the effect that produces the model with the lowest SBC is added.

The following statement requests the traditional stepwise method:

```
selection=stepwise(select=SL)
```

First, if the removal of any effect in the model is not significant at the default stay level of 0.05, then the least significant effect is removed and the algorithm proceeds to the next step. Otherwise the effect whose addition is the most significant is added, provided that it is significant at the default entry level of 0.05.

The following statement requests the traditional stepwise method, where effects enter and leave based on significance levels, but with the following extra check: if any effect to be added or removed yields a model whose SBC statistic is greater than the SBC statistic of the current model, then the stepwise method terminates at the current model.

```
selection method=stepwise(select=SL stop=SBC) stophorizon=1;
```

In this case, the entry and stay significance levels still play a role as they determine whether an effect is deleted from or added to the model. This extra check might result in the selection terminating before a local minimum of the SBC criterion is found.

The following statement selects effects to enter or drop as in the previous example except that the significance level for entry is now 0.1 and the significance level to stay is 0.08. From the sequence of models produced, the selected model is chosen to yield the minimum AIC statistic:

```
selection method=stepwise(select=SL SLE=0.1 SLS=0.08 choose=AIC);
```

The following statement requests stepwise selection based on the AICC criterion with additions and deletions treated competitively:

```
selection method=stepwise(select=AICC competitive);
```

Each step evaluates the AICC statistics that correspond to the removal of any effect in the current model or the addition of any effect to the current model and chooses the addition or removal that produced the minimum value, provided that this minimum is lower than the AICC statistic of the current model.

The following statement requests stepwise selection based on the SBC criterion with additions and deletions treated competitively and where stopping is based on the average square error over the validation data:

```
selection=stepwise(select=SBC competitive stop=VALIDATE);
```

At any step, SBC statistics that correspond to the removal of any effect from the current model or the addition of any effect to the current model are evaluated. The addition or removal that produces the minimum SBC value is made. The average square error on the validation data for the model with this addition or removal is evaluated. The selection stops when the average square error so produced increases for three consecutive steps.

Forward-Swap Selection

METHOD=FORWARDSWAP specifies the forward-swap selection method, which is an extension of the forward selection method. The forward-swap selection method incorporates steps that improve a model by replacing an effect in the model with an effect that is not in the model. When the model selection criterion is R square, this method is the same as the maximum R-square improvement (MAXR) method that is implemented in the REG procedure in SAS/STAT software. You cannot use the effect significance level as the selection criterion for the forward-swap method.

The forward-swap selection method begins by finding the one-effect model that produces the best value of the selection criterion. Then another effect (the one that yields the greatest improvement in the selection criterion) is added. Once the two-effect model is obtained, each of the effects in the model is compared to each effect not in the model. For each comparison, the forward-swap method determines whether removing one effect and replacing it with the other effect improves the selection criterion. After comparing all possible swaps, the forward-swap method makes the swap that produces the greatest improvement in the selection criterion. Comparisons begin again, and the process continues until the forward-swap method finds that no other swap could improve the selection criterion. Thus, the two-variable model achieved is considered the "best" two-variable model that the technique can find. Another variable is then added to the model, and the comparing-and-swapping process is repeated to find the "best" three-variable model, and so forth.

The difference between the stepwise selection method and the forward-swap selection method is that all swaps are evaluated before any addition is made in the forward-swap method. In the stepwise selection method, the "worst" effect might be removed without considering what adding the "best" remaining effects might accomplish. Because the forward-swap method needs to examine all possible pairwise effect swaps at each step of the selection process, the forward-swap method is much more computionally expensive than the stepwise selection method; it might not be appropriate for models that contain a large number of effects.

Least Angle Regression

METHOD=LAR specifies least angle regression (LAR), which is supported in the HPREG procedure. LAR was introduced by Efron et al. (2004). Not only does this algorithm provide a selection method in its own right, but with one additional modification it can be used to efficiently produce LASSO solutions. Just like the forward selection method, the LAR algorithm produces a sequence of regression models in which one parameter is added at each step, terminating at the full least squares solution when all parameters have entered the model.

The algorithm starts by centering the covariates and response and scaling the covariates so that they all have the same corrected sum of squares. Initially all coefficients are zero, as is the predicted response. The predictor that is most correlated with the current residual is determined, and a step is taken in the direction of this predictor. The length of this step determines the coefficient of this predictor and is chosen so that some other predictor and the current predicted response have the same correlation with the current residual. At this point, the predicted response moves in the direction that is equiangular between these two predictors. Moving in this direction ensures that these two predictors continue to have a common correlation with the current residual. The predicted response moves in this direction until a third predictor has the same correlation with the current residual as the two predictors already in the model. A new direction is determined that is equiangular among these three predictors, and the predicted response moves in this direction until a fourth predictor, which has the same correlation with the current residual, joins the set. This process continues until all predictors are in the model.

As with other selection methods, the issue of when to stop the selection process is crucial. You can specify a criterion for choosing among the models at each step with the CHOOSE= option. You can also specify a

stopping criterion with the STOP= option. These formulas use the approximation that at step k of the LAR algorithm, the model has k degrees of freedom. See Efron et al. (2004) for a detailed discussion of this so-called simple approximation.

A modification of LAR selection suggested in Efron et al. (2004) uses the LAR algorithm to select the set of covariates in the model at any step, but it uses ordinary least squares regression with just these covariates to obtain the regression coefficients. You can request this hybrid method by specifying the LSCOEFFS suboption of METHOD=LAR.

Lasso Selection

Method=LASSO specifies the least absolute shrinkage and selection operator (LASSO) method, which is supported in the HPREG procedure. LASSO arises from a constrained form of ordinary least squares regression where the sum of the absolute values of the regression coefficients is constrained to be smaller than a specified parameter. More precisely let $X = (x_1, x_2, \ldots, x_m)$ denote the matrix of covariates and let y denote the response, where the x_is have been centered and scaled to have unit standard deviation and mean zero and y has mean zero. Then for a given parameter t, the LASSO regression coefficients $\beta = (\beta_1, \beta_2, \ldots, \beta_m)$ are the solution to the following constrained optimization problem:

$$\text{minimize} ||y - X\beta||^2 \qquad \text{subject to} \quad \sum_{j=1}^{m} |\beta_j| \leq t$$

Provided that the LASSO parameter t is small enough, some of the regression coefficients are exactly zero. Hence, you can view the LASSO as selecting a subset of the regression coefficients for each LASSO parameter. By increasing the LASSO parameter in discrete steps, you obtain a sequence of regression coefficients in which the nonzero coefficients at each step correspond to selected parameters.

Early implementations (Tibshirani 1996) of LASSO selection used quadratic programming techniques to solve the constrained least squares problem for each LASSO parameter of interest. Later Osborne, Presnell, and Turlach (2000) developed a "homotopy method" that generates the LASSO solutions for all values of t. Efron et al. (2004) derived a variant of their algorithm for least angle regression that can be used to obtain a sequence of LASSO solutions from which all other LASSO solutions can be obtained by linear interpolation. This algorithm for METHOD=LASSO is used in PROC HPREG. It can be viewed as a stepwise procedure with a single addition to or deletion from the set of nonzero regression coefficients at any step.

As with the other selection methods supported by the High-Performance Analytic procedures, you can specify a criterion to choose among the models at each step of the LASSO algorithm with the CHOOSE= option. You can also specify a stopping criterion with the STOP= option. See the discussion in the section "Forward Selection" on page 52 for additional details. The model degrees of freedom PROC GLMSELECT uses at any step of the LASSO are simply the number of nonzero regression coefficients in the model at that step. Efron et al. (2004) cite empirical evidence for doing this but do not give any mathematical justification for this choice.

A modification of LASSO selection suggested in Efron et al. (2004) uses the LASSO algorithm to select the set of covariates in the model at any step, but it uses ordinary least squares regression with just these covariates to obtain the regression coefficients. You can request this hybrid method by specifying the LSCOEFFS suboption of SELECTION=LASSO.

Adaptive Lasso Selection

Adaptive lasso selection is a modification of lasso selection; in adaptive lasso selection, weights are applied to each of the parameters in forming the lasso constraint (Zou, 2006). More precisely, suppose that the response y has mean zero and the regressors x are scaled to have mean zero and common standard deviation. Furthermore, suppose that you can find a suitable estimator $\hat{\beta}$ of the parameters in the true model and you define a weight vector by $w = 1/|\hat{\beta}|^{\gamma}$, where $\gamma \geq 0$. Then the adaptive lasso regression coefficients $\beta = (\beta_1, \beta_2, \ldots, \beta_m)$ are the solution to the following constrained optimization problem:

$$\text{minimize} ||y - X\beta||^2 \qquad \text{subject to} \quad \sum_{j=1}^{m} |w_j \beta_j| \leq t$$

PROC HPREG uses the solution to the unconstrained least squares problem as the estimator $\hat{\beta}$. This is appropriate unless collinearity is a concern. If the regressors are collinear or nearly collinear, then Zou (2006) suggests using a ridge regression estimate to form the adaptive weights.

References

Burnham, K. P., and Anderson, D. R. (2002), *Model Selection and Multimodel Inference,* Second Edition, New York: Springer-Verlag.

Efron, B., Hastie, T., Johnstone, I., and Tibshirani, R. (2004), "Least Angle Regression (with Discussion)," *Annals of Statistics*, 32, 407–499.

Lawless, J. F. and Singhal, K. (1978), "Efficient Screening of Nonnormal Regression Models," *Biometrics*, 34, 318–327.

Osborne, M., Presnell, B., and Turlach, B. (2000), "A New Approach to Variable Selection in Least Squares Problems," *IMA Journal of Numerical Analysis*, 20, 389–404.

Searle, S. R. (1971), *Linear Models,* New York: John Wiley & Sons.

Tibshirani, R. (1996), "Regression Shrinkage and Selection via the Lasso," *Journal of the Royal Statistical Society Series B*, 58, 267–288.

Zou, H. (2006), "The Adaptive Lasso and Its Oracle Properties," *Journal of the American Statistical Association*, 101, 1418–1429.

Chapter 4
Installation and System Administration

Contents

Overview of SAS High-Performance Analytics Server Installation **62**
Configure the Client **62**
Configure SAS/ACCESS Interface to Greenplum 62
Configure SAS/ACCESS Interface to Greenplum in a Windows Environment 62
Configure SAS/ACCESS Interface to Greenplum on Supported UNIX and Linux Platforms 63
Register SAS/ACCESS Interface to Greenplum 64
Configure SAS/ACCESS Interface to Teradata 65
Configure FastExport 65
MultiLoad 65
Teradata Parallel Transporter 66
Install SAS High-Performance Analytics Server on the Appliance **67**
Create a File with All Machine Names 67
Install SAS High-Performance Deployment of Hadoop 68
Identication of User ID That Runs Hadoop 68
Install SAS High-Performance Deployment of Hadoop 68
Format the Hadoop NameNode 71
Updating SAS High-Performance Deployment of Hadoop 72
Install the SAS Executables 73
Prepare the Greenplum Database 74
SAS Protocol and Related Functions 74
Database Roles 75
Prepare the Teradata Database 76
Install User-Defined Functions 76
Grant Privileges for Database Accounts 76
Set Up User Accounts **76**
Set Up SSH Keys **77**
Set Up SSH Keys on the Appliance 77
Set Up SSH Keys on the Client 78
Running with an Alternate User Name and Identity 78

Overview of SAS High-Performance Analytics Server Installation

The SAS High-Performance Analytics Server software has client-side and server-side components. The High-Performance Analytics client is the machine on which the SAS session executes and is where you run High-Performance Analytics procedures. The server is the High-Performance Analytics appliance to which the client connects. The server is frequently referred to as the *grid host*, *head node*, or the *host node* throughout this document. This chapter provides instructions for the installation and configuration of both the client-side and server-side components of SAS High-Performance Analytics software.

Configure the Client

After you install SAS on the client, you need to perform the following steps to configure SAS High-Performance Analytics Server, which are described in subsequent sections:

- Configure SAS/ACCESS Interface to Greenplum or SAS/ACCESS Interface to Teradata. See the section "Configure SAS/ACCESS Interface to Greenplum" on page 62 and the section "Configure SAS/ACCESS Interface to Teradata" on page 65.
- Set up a secure shell (SSH) key to support a secure connection to the appliance. See the section "Set Up SSH Keys" on page 77.

Configure SAS/ACCESS Interface to Greenplum

Configure SAS/ACCESS Interface to Greenplum in a Windows Environment

SAS/ACCESS Interface to Greenplum uses the DataDirect Technologies Greenplum wire protocol Open Database Connectivity (ODBC) driver component, which should be downloaded from SAS. For information about downloading this component, see the section "SAS/ACCESS Interface to Greenplum" in the *System Requirements for SAS 9.3 Foundation for Microsoft Windows*.

After you have downloaded the ODBC driver, use the following steps to unzip it and store it in the appropriate location:

1. Use Windows Explorer to navigate to the *!SASROOT\access\sasmisc* directory where the *<platform>gplm60.zip* is located, where *<platform>* is specific to your Windows version.
2. Unzip the *<platform>gplm60.zip* file.
3. Follow the instructions in the *Readme.txt* file, which is contained in the zip file.

Configure SAS/ACCESS Interface to Greenplum on Supported UNIX and Linux Platforms

1. Set the ODBCHOME environment variable to your ODBC home directory.

   The location for the ODBC driver is the ODBCHOME directory; it is used to set up the paths both to the shared libraries and also to the *odbc.ini* file. During the initial installation of SAS/ACCESS Interface to Greenplum, the SAS Deployment Wizard enables you to specify the location for the required ODBC driver. If you want to update that location after the initial installation, you can do so by using the SAS Deployment Manager. For information about updating the location, see the section "Configure SAS/ACCESS Interface to Greenplum" of the *SAS Deployment Wizard and SAS Deployment Manager 9.3: User's Guide*, located at http://support.sas.com/deploywizug93.html.

2. Edit the *odbc.ini* system information file, which contains a list of possible data sources that you can connect to your Greenplum servers. You must configure at least one data source in order to use SAS/ACCESS Interface to Greenplum. Edit the *odbc.ini* file with a text editor to configure the data sources. The general format of the *odbc.ini* file is as follows, where **greenplum** is the name of the configured data source name that is specified in the DSN= option when you assign a libref to the SAS/ACCESS Interface to Greenplum engine:

```
[ODBC Data Sources]
greenplum=SAS ACCESS to Greenplum

[ODBC]
InstallDir=<my install dir>
Trace=0
TraceDll=<my install dir>/lib/odbctrac.so
TraceFile=odbctrace.out

[greenplum]
Driver=<my install dir>/lib/S0gplm<file version>.so
Description=SAS ACCESS to Greenplum
AlternateServers=
ApplicationUsingThreads=1
ConnectionReset=0
ConnectionRetryCount=0
ConnectionRetryDelay=3
Database=<db>
EnableDescribeParam=1
ExtendedColumnMetadata=0
FailoverGranularity=0
FailoverMode=0
FailoverPreconnect=0
FetchRefCursor=1
FetchTSWTZasTimestamp=0
FetchTWFSasTime=0
HostName=<Greenplum host>
InitializationString=
LoadBalanceTimeout=0
LoadBalancing=0
LoginTimeout=15
LogonID=
MaxPoolSize=100
```

```
MinPoolSize=0
Password=
Pooling=0
PortNumber=<Greenplum server port>
QueryTimeout=0
ReportCodepageConversionErrors=0
TransactionErrorBehavior=1
XMLDescribeType=-10
```

a) It is recommended that you leave the field shown as **<file version>** as it is. This field describes the specific version of the DataDirect Greenplum driver that is installed with SAS/ACCESS Interface to Greenplum; it contains a two-digit version that describes the version of the actual driver library. You do not need to update this version specification in your *odbc.ini* file.

b) Replace all occurrences of **<my install dir>** in *odbc.ini* with the names of the path and directory where you installed the Greenplum ODBC driver. This is the same directory that is specified by the ODBCHOME environment variable that you set in step 1.

c) Replace **<Greenplum host>** with the IP address or named server of your Greenplum server.

d) Replace **<Greenplum server port>** with the port number that your Greenplum server is listening on (typically 5432).

e) Replace **<db>** with the name of your Greenplum database.

3. Set the ODBCINI environment variable to the location and name of your *odbc.ini* as follows:

```
ODBCINI=$ODBCHOME/odbc.ini
export ODBCINI
```

4. Include the full path to the shared libraries as shown in the following example so that the ODBC drivers can be loaded dynamically at run time. The DataDirect Greenplum ODBC drivers are ODBC API-compliant shared libraries, which are referred to in UNIX as shared objects.

```
$ LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$ODBCHOME/lib
$ export LD_LIBRARY_PATH
```

It might be convenient to set these environment variables in the *bin/sasenv_local* file of your SAS installation to enable ODBC for all SAS users.

Register SAS/ACCESS Interface to Greenplum

If the GREENPLM name is not known in LIBNAME statements, run the following SAS procedure to register SAS/ACCESS Interface to Greenplum with the SAS system catalog:

```
proc nickname cat=sashelp.core engine;
   add nickname=greenplm
       module  =sasiogpl
       desc    ="SAS/ACCESS to Greenplum"
       prefered eng;
quit;
```

Configure SAS/ACCESS Interface to Teradata

Before you use SAS/ACCESS Interface to Teradata, verify connectivity by logging into your Teradata account with the Teradata BTEQ utility. If BTEQ is unavailable, establish connectivity as documented in the *SAS/ACCESS to Teradata* white paper, available at http://support.sas.com/resources/papers/teradata.pdf.

If BTEQ fails to connect to the Teradata server, you might need an entry in the *hosts* file on your PC to provide the network address of the Teradata server. Typically, this means adding a **dbccop1** entry to your *hosts* file. For more information about the entry, see the *Teradata Client for Windows Installation Guide*.

Configure FastExport

For optimal reads of large tables, SAS/ACCESS can use the Teradata FastExport Utility, which must be present on the system where you install SAS. The FastExport Utility is not required; SAS/ACCESS reads large tables quite efficiently without it. For more information, see the DBSLICEPARM option in the chapter "SAS/ACCESS Interface to Teradata" in *SAS/ACCESS 9.3 for Relational Databases: Reference*. See also the *SAS/ACCESS to Teradata* white paper, available on the SAS Web site at http://support.sas.com/resources/papers/teradata.pdf.

Contact Teradata if you want to obtain the Teradata FastExport Utility.

Configure FastExport for Windows

Modify the PATH system variable by appending the following directory paths to the end of PATH:

- the directory where *fexp.exe* (the FastExport Utility) is located (often this is *C:\Program Files\Teradata\Client\13.10\bin*)
- the directory where *sasaxsm.dll* is located (*sasaxsm.dll* is usually located in your SAS product tree, in the *!sasroot\access\sasexe directory*)

Configure FastExport for Supported UNIX and Linux Platforms

Modify your library path environment variable to include the directory that contains the shared object *sasaxsm.so*. This shared object is delivered in the *$SASROOT/sasexe directory*. You can copy this module where you want, but ensure that the directory you copy it into is specified in the LD_LIBRARY_PATH environment variable.

Make sure that the Teradata FastExport utility, *fexp*, has its directory included in the PATH environment variable. This utility is usually installed in the */usr/bin* directory.

MultiLoad

SAS/ACCESS can load large volumes of data to non-empty tables by using the Teradata MultiLoad utility if it is present on the system where you install SAS.

The MultiLoad utility is not required; SAS/ACCESS provides other options for loading tables. For more information, see the MULTISTMT option in the chapter "SAS/ACCESS Interface to Teradata" in *SAS ACCESS 9.3 for Relational Databases: Reference.*

Contact Teradata if you want to obtain the Teradata MultiLoad utility.

Configure MultiLoad for Windows

Modify the PATH system variable by appending the following directory paths to the end of PATH:

- the directory where *mload.exe* (the MultiLoad Utility) is located (often this is *C:\Program Files\Teradata\Client\13.10\bin*)
- the directory where *sasmlam.dll* and *sasmlne.dll* are located (*sasmlam.dll* and *sasmlne.dll* are usually located in your SAS product tree, in the *!sasroot\access\sasexe* directory)

Configure MultiLoad for Supported UNIX and Linux Platforms

Modify the LD_LIBRARY_PATH environment variable to include the directory that contains the shared objects *sasmlam.so* and *sasmlne.so*. These shared objects are delivered in the *$SASROOT/sasexe directory*. You can copy these modules where you want, but ensure that the directory you copy them into is specified in the LD_LIBRARY_PATH environment variable.

Make sure that the Teradata MultiLoad utility, *mload*, has its directory included in the PATH environment variable. This utility is usually installed in the */usr/bin* directory.

Teradata Parallel Transporter

SAS/ACCESS supports the Teradata Parallel Transporter API for loading data by using Multiload, FastLoad, and multistatement inserts. The API also supports reading data by using FastExport. The Teradata Parallel Transporter API is not required; SAS/ACCESS provides other options for loading and reading data.

If you plan to use the Teradata Parallel Transporter API, the API must be installed on the system where SAS is installed. Additional requirements depend on the operating system as follows.

Configure Teradata Parallel Transporter for Windows

Modify the system variable TKPATHIA32. If the variable does not exist already, you must add it. To modify the variable, append the directory where *sasiotpt.dll* is located (*sasiotpt.dll* is usually located in your SAS product tree, in the *!sasroot\access\sasexe directory*).

You must also update your PATH environment variable to include the following location: *C:\Program Files\Teradata\Client\13.10\Teradata ParallelTransporter\bin\vc7*. For more information, go to `http://support.sas.com/kb/42/351.html`.

Configure Teradata Parallel Transporter for Supported UNIX and Linux Platforms

The PATH system variable must include the location of the Teradata PT API libraries (specifically the location of *libtelapi.**). The LD_LIBRARY_PATH and NLSPATH environment variables also need to include that path as follows:

```
LD_LIBRARY_PATH=TPT-API-LIBRARY-LOCATION:$LD_LIBRARY_PATH
NLSPATH=TPT-API-MESSAGE-CATALOG-LOCATION
```

Install SAS High-Performance Analytics Server on the Appliance

Configuring the appliance for SAS High-Performance Analytics Sever involves the following steps, whose details are described in subsequent subsections:

1. Ensure that the hostname (both short names and long names) of every node can be resolved by all nodes in the environment.
2. Create a file with a list of all the machine names in the appliance. See the section "Create a File with All Machine Names" on page 67.
3. (Optional) Install SAS High-Performance Deployment of Hadoop. See the section "Install SAS High-Performance Deployment of Hadoop" on page 68.
4. Install the SAS executables via the self-extracting shell script. See the section "Install the SAS Executables" on page 73.
5. Set up user accounts and SSH keys for the users who will access SAS High-Performance Analytics Server on the appliance. See the section "Set Up User Accounts" on page 76 and the section "Set Up SSH Keys" on page 77.
6. Prepare the database management system for interaction with SAS High-Performance Analytics Server. See the section "Prepare the Greenplum Database" on page 74 or the section "Prepare the Teradata Database" on page 76.

Create a File with All Machine Names

Before the SAS High-Performance Analytics Server components can be installed on the appliance nodes, you must create a file on the appliance that contains a lists of host names that resolve to IP addresses for the Message Passing Interface (MPI) communication on the appliance. The head node is listed first.

A typical host file on Greenplum appliances contains the following host names:

```
mdw
sdw1
sdw2
sdw3
sdw4
...
```

A typical host file on Teradata appliances contains the following host names:

```
dbccop0
dbccop1
dbccop2
dbccop3
...
```

Install SAS High-Performance Deployment of Hadoop

SAS High-Performance Analytics provides the option of using Hadoop for data storage. The instructions in the following sections you guide through the installation of the supported version of Hadoop.

The SAS High-Performance Deployment of Hadoop requires a Java Runtime Environment (JRE) or Java Development Kit (JDK) on every machine in the cluster. The path to the Java executable must be the same on all of the machines in the cluster. Make a note of the path and perform the steps in the section "Install SAS High-Performance Deployment of Hadoop" on page 68.

For information about the supported Java version, see `http://wiki.apache.org/hadoop/HadoopJavaVersions`. The SAS High-Performance Deployment of Hadoop uses the Apache Hadoop 0.21.0 version.

Identication of User ID That Runs Hadoop

An operating system user ID is required to run the Hadoop applications on the machines in the cluster. This user ID must exist on all the machines in the cluster and must be configured for passwordless SSH.

Install SAS High-Performance Deployment of Hadoop

The software that is needed for the SAS High-Performance Deployment of Hadoop is available from within the SAS Software Depot that was created by the site depot administrator: *standalone_installs\SAS_High_Performance_Deployment_for_Hadoop\1_5\Linux_for_x64\sashadoop.tar.gz*

On the machine you want to use as the Hadoop NameNode (blade 0), follow these steps:

1. Log on as **root** to the machine you want to use as the Hadoop NameNode (blade 0).
2. Copy the *sashadoop.tar.gz* file to a temporary location and extract it:

   ```
   cp sashadoop.tar.gz /tmp
   cd /tmp
   tar xzf sashadoop.tar.gz
   ```

   A directory that is named *sashadoop* is created.
3. Change directory to the *sashadoop* directory and run the **hadoopInstall** command:

   ```
   cd sashadoop
   ./hadoopInstall
   ```

4. Respond to the following prompts from the configuration program:

   a) **Do you wish to use an existing Hadoop installation? (y/N)**

   Press Enter to perform a new installation.

b) **Enter path to install Hadoop. The directory 'hadoop-0.21.0' will be created in the path specified.**

Enter an existing directory such as */hadoop*.

c) **Enter replication factor. Default 2**

Press Enter to accept the default, or enter a preferred number (0–10) of replications for blocks. For example, if a value of 0 is entered, each block of data is replicated once. This prompt, corresponds to the *dfs.replication* property for HDFS.

d) **Enter port number for fs.defaultFS. Default 54310**

Press Enter to accept the default port number.

e) **Enter port number for mapred.job.tracker. Default 54311**

Press Enter to accept the default port number.

f) **Enter port number for dfs.namenode.https-address. Default 50470**

Press Enter to accept the default port number.

g) **Enter port number for dfs.datanode.https.address. Default 50475**

Press Enter to accept the default port number.

h) **Enter port number for dfs.datanode.address. Default 50010**

Press Enter to accept the default port number.

i) **Enter port number for dfs.datanode.ipc.address. Default 50020**

Press Enter to accept the default port number.

j) **Enter port number for dfs.namenode.http-address. Default 50070**

Press Enter to accept the default port number.

k) **Enter port number for dfs.datanode.http.address. Default 50075**

Press Enter to accept the default port number.

l) **Enter port number for dfs.secondary.http.address. Default 50090**

Press Enter to accept the default port number.

m) **Enter port number for dfs.namenode.backup.address. Default 50100**

Press Enter to accept the default port number.

n) **Enter port number for dfs.namenode.backup.http-address. Default 50105**

Press Enter to accept the default port number.

o) **Enter port number for mapred.job.tracker.http.address. Default 50030**

Press Enter to accept the default port number.

p) **Enter port number for mapred.task.tracker.http.address. Default 50060**

Press Enter to accept the default port number.

q) **Enter port number for com.sas.lasr.hadoop.service.namenode.port. Default 5452**

Press Enter to accept the default port number.

r) **Enter port number for com.sas.lasr.hadoop.service.datanode.port. Default 5453**

Press Enter to accept the default port number.

s) **Enter user that will be running the HDFS server process.**

Enter the user name to run the Hadoop services. This user will have administrative privileges on the Hadoop services. It is recommended that you run the services under the **root** account. This account should also set the HADOOP_HOME environment variable.

t) **Enter path for JAVA_HOME directory. (Default: /usr/lib/jvm/jre)**

Press Enter to accept the default JRE, or enter the path to the JRE or JDK.

NOTE: The configuration program does not verify that a JRE is installed at */usr/lib/jvm/jre*, which is the default path for some Linux vendors.

u) **Enter path for Hadoop data directory. This should be on a large drive. Default is '/hadoop/hadoop-data'.**

Press Enter to accept the default value, or enter the path that you prefer to use.

v) **Enter path for Hadoop system directory. Default is '/hadoop/hadoop-system'.**

Press Enter to accept the default value, or enter the path that you prefer to use.

w) **Enter path for Hadoop local directory. Default is '/hadoop/hadoop-local'.**

Press Enter to accept the default value, or enter the path that you prefer to use.

x) **Enter path for Hadoop name directory. Default is '/hadoop/hadoop-name'.**

Press Enter to accept the default value, or enter the path that you prefer to use.

y) **Enter full path to machine list. The NameNode 'host' should be listed first.**

Enter **/etc/gridhosts**.

5. The installation program installs SAS High-Performance Deployment of Hadoop on the local host, configures several files, and then provides a prompt:

```
The installer can now copy '/hadoop/hadoop-0.21.0' to all the slave
machines using scp, skipping the first entry. Perform copy?  (YES/no)
```

Enter Yes to install SAS High-Performance Deployment of Hadoop on the other machines in the cluster.

Format the Hadoop NameNode

If this is an initial installation of SAS High-Performance Deployment of Hadoop (rather than an update to a newer version), then follow these steps:

1. Log on as **root** to the machine you want to use as the Hadoop NameNode (blade 0).
2. Invoke **hadoop** with the -format option.

   ```
   /hadoop/hadoop-0.21.0/bin/hadoop namenode -format
   ```

3. ```
   Re-format filesystem in /hadoop/hadoop-name ? (Y or N)
   ```

   Enter Y. The response is case-sensitive.

   Output similar to the following line indicates that the format is successful:

   ```
   12/02/18 21:19:18 INFO common.Storage: Storage directory /hadoop/hadoop-name
   has been successfully formatted.
   ```

4. While still using the **hadoop** user account, start the SAS High-Performance Deployment of Hadoop software:

   a) ```
      /hadoop/hadoop-0.21.0/bin/start-dfs.sh
      ```

      A series of messages are printed to report the creation of log files and processes.

   b) ```
      /hadoop/hadoop-0.21.0/bin/start-mapred.sh
      ```

      A series of messages are printed to report the creation of log files and processes.

5. Create a directory in HDFS that permits read and write access for all users:

   ```
   /hadoop/hadoop-0.21.0/bin/hadoop fs -mkdir /user
   /hadoop/hadoop-0.21.0/bin/hadoop fs -chmod 777 /user
   ```

   You can confirm that Hadoop is running successfully by opening a browser to a link of the form http://<namenode>:50070/dfshealth.jsp, where <namenode> is the name of the machine where Hadoop is installed. Review the information in the cluster summary section of the page. Confirm that the number of live nodes equals the number of DataNodes and that the number of dead nodes is zero.

   NOTE: It can take a few seconds for each node to start. If you do not see every node, then refresh the connection in the Web interface.
   ```

Updating SAS High-Performance Deployment of Hadoop

SAS High-Performance Deployment of Hadoop can be updated with the **hadoopInstall** command. An update is very similar to the installation process. The similarities include the process for copying the *sashadoop.tar.gz* file to a temporary location and extracting the archive with the **tar** command.

As a convenience, you can start the **hadoopInstall** command while the existing installation is running. In this case, after you indicate that you want to use an existing installation, the installer attempts to determine the value of the **hadoop.home.dir** property and the user ID that is used to run the process.

CAUTION: If you begin the update with Hadoop running, you are prompted to stop Hadoop after the installer determines the home directory and user ID. At that point, use the **stop-all.sh** or **stop-dfs.sh** and **stop-mapred.sh** commands to stop Hadoop and then return to the installer and continue.

On the machine that is used as the Hadoop NameNode (blade 0), follow these steps:

1. Log on as **root**.
2. Copy the *sashadoop.tar.gz* file to a temporary location and extract it with the **tar** command.
3. Change directory to the *sashadoop* directory that is created and run the **hadoopInstall** command.

   ```
   Do you wish to use an existing Hadoop installation? (y/N)
   ```

   Enter Y to update the installation.
4. If SAS High-Performance Deployment of Hadoop is running, the installer attempts to determine the value of the **hadoop.home.dir** property and the user ID that runs the server:

   ```
   Active Hadoop server running as user: 'userid' from: '/hadoop/hadoop'
    Update this install (Y/n)?
   ```

   Enter Y to update the detected installation.
5. If SAS High-Performance Deployment of Hadoop is not running, or you want to update an installation that is not detected, you must respond to the following prompts:

   a) `Enter path to existing Hadoop installation.`

      Enter the path, such as **/hadoop/hadoop**. Do not include bin in your response.

   b) `Enter user that will be running the HDFS server process.`

      Enter the user name.
6. At the following prompt, use the **stop-all.sh** or **stop-dfs.sh** and **stop-mapred.sh** commands and then press Enter:

   ```
   Stop Hadoop server at: '/hadoop/hadoop', and Hit Return
   ```

7. The installation program then updates the machine that is used for the NameNode with the JAR files provided by SAS, the **setperm** command, and the *setperm.users* file.

8. The installation program then updates the JAR files provided by SAS, the **setperm** command, and *setperm.users* file on each of the machines that is listed in the conf/slaves file.

9. The installation program does not update any configuration files (*conf/core-site.xml*, *conf/hdfs-site.xml*, or *conf/mapred-site.xml*). However, the program prints a list of the properties for the *conf/hdfs-site.xml* file that you need to check against the real file.

Install the SAS Executables

You install the server-side components of SAS High-Performance Analytics Server via a self-extracting shell script, which can be found in the following directory of the install depot image that is created by your site administrator: *standalone_installs\SAS_High-Performance_Node_Installation\1_5\Linux_for_x64*

To install server-side components of SAS High-Performance Analytics Server via a self-extracting shell script:

1. Copy the file *TKHPAGrid_Linux_x86_64.sh* to the */tmp* directory of the head node of the appliance.

2. Log on to the head node of the appliance, and change directories to the desired install location (for example, */opt*).

3. Run the shell script in this directory. The shell script creates the *TKGrid* subdirectory and places all files in *TKGrid* subdirectory.

4. Respond to the following prompts from the configuration program:

   a) **`Shared install or replicate to each node? (Y=SHARED/n=replicated)`**

   If you are installing to a local drive on each node, indicate that this is a replicated installation. If you are installing to a drive that is shared across all the nodes (for example, network file system [NFS]), choose the shared installation.

   b) **`MPICH2 1.3.2 is included in this install. Would you like to use it? (Y/n)`**

   Select 'Yes' unless you want to use a different version of the Message Passing Interface (MPI).

   c) **`Enter additional options to mpirun.`**

   Usually, there are no additional options that you need to add to each **`mpirun`** command. If you do not want to add options, simply press RETURN.

   d) **`Enter path to use for Utility files. (default is /tmp).`**

   SAS High-Performance Analytics Server applications might write scratch files. By default, these files are created in the */tmp* directory. You can redirect the files to a different location by entering the path at the prompt.

   e) **`Enter path to Hadoop. (default is Hadoop not installed).`**

   If a SAS High-Performance Analytics Server application needs to access data that are stored in Hadoop, enter the path to the Hadoop directory; otherwise, accept the default ('Hadoop not installed').

f) **`Force Root Rank to run on headnode? (y/N)`**

If the appliance resides behind a firewall and only the head node can connect back to the client machines, select 'Yes'; otherwise, accept the default ('No').

g) **`Enter full path to machine list...`**

Enter the name of the file you created in the section "Create a File with All Machine Names" on page 67, (for example, */etc/gridhosts*).

h) **`Enter maximum runtime for grid jobs (in seconds). Default 7200 (2 hours).`**

If a SAS High-Performance Analytics Server application executes for more than the maximum allowable run time, it is automatically terminated. You can adjust that run-time limit here.

i) **`Enter value for UMASK. (default is unset).`**

Enter 022 as the UMASK value. This value masks out write permission for the group and others.

j) If you selected a replicated installation at the first prompt, you are now prompted to choose the technique for distributing the contents to the appliance nodes:

```
The install can now copy this directory to all the machines
listed in '<filename>' using scp, skipping the first entry.
Perform copy?  (YES/no)
```

Select 'Yes' if you want the installation program to perform the replication. Select 'No' if you plan to distribute the contents of the installation directory by some other technique.

Prepare the Greenplum Database

SAS Protocol and Related Functions

The SAS High-Performance Analytics Server interface to the Greenplum database is supported by several functions that are associated with a dedicated SAS protocol. To enable the functionality, the database administrator (a superuser such as the *gpadmin* role) should perform the following steps (in these steps, the server-side components are installed in the */opt/TKGrid* directory):

1 Install the formatter functions:

```
CREATE OR REPLACE FUNCTION formatter_export(record)
       RETURNS bytea
       AS '/opt/TKGrid/lib/gpformatter.so', 'formatter_export'
       LANGUAGE C STABLE;

CREATE OR REPLACE FUNCTION formatter_import()
       RETURNS record
       AS '/opt/TKGrid/lib/gpformatter.so', 'formatter_import'
       LANGUAGE C STABLE;
```

2 Create the protocol functions and the SAS protocol:

```
CREATE OR REPLACE FUNCTION gpdb_to_sas() RETURNS integer
       AS '/opt/TKGrid/lib/sas_gpext.so', 'sasprot_export'
       LANGUAGE C STABLE;

CREATE OR REPLACE FUNCTION sas_to_gpdb() RETURNS integer
       AS '/opt/TKGrid/lib/sas_gpext.so', 'sasprot_import'
       LANGUAGE C STABLE;

CREATE TRUSTED PROTOCOL sas(readfunc='sas_to_gpdb', writefunc='gpdb_to_sas');
```

The functions must be created in a schema that is either in your schema search path or in the global *pg_catalog* catalog.

Each database role that executes SAS High-Performance Analytics Server procedures against the Greenplum database needs to be granted execution rights for the SAS protocol, as described in the next section.

3 Repeat these steps for each database that is accessed through SAS High-Performance Analytics Server procedures. You can define the functions on a database template from which new databases are derived.

Database Roles

1 If multiple users access the SAS High-Performance Analytics Server environment on the Greenplum database, it is recommended that you set up a group role and associate the database roles for individual users with the group. The Greenplum database administrator can then associate access to the environment at the group level. For example:

```
CREATE GROUP sas_cust_group NOLOGIN;
ALTER ROLE sas_cust_group CREATEEXTTABLE;
```

2 For each user, create a database role and associate it with the group:

```
CREATE ROLE megan  LOGIN IN ROLE sas_cust_group PASSWORD 'megan';
CREATE ROLE calvin LOGIN IN ROLE sas_cust_group PASSWORD 'calvin';
```

3 If a resource queue exists, associate the roles with the queue:

```
CREATE RESOURCE QUEUE sas_cust_queue WITH
               (MIN_COST=10000.0   ,
               ACTIVE_STATEMENTS=20,
               PRIORITY=HIGH       ,
               MEMORY_LIMIT='4GB'  );

ALTER ROLE megan  RESOURCE QUEUE sas_cust_queue;
ALTER ROLE calvin RESOURCE QUEUE sas_cust_queue;
```

4 Grant the database roles execution rights on the SAS High-Performance Analytics Server protocol:

```
GRANT ALL ON PROTOCOL sas TO megan;
GRANT ALL ON PROTOCOL sas TO calvin;
```

Prepare the Teradata Database

Install User-Defined Functions

Install Teradata user-defined functions (UDFs) by using the scripts that are provided by the installation script (in the following commands, the server-side components are installed in the */opt/TKGrid* directory).

1. On the host node, enter the following command:

   ```
   sh /opt/TKGrid/bin/add_udfs.sh
   ```

2. You are prompted for a database account name with sufficient privileges to add user-defined functions.

To uninstall the UDFs from Teradata, enter the following command:

```
sh /opt/TKGrid/bin/rem_udfs.sh
```

Grant Privileges for Database Accounts

The database users who run SAS High-Performance Analytics Server procedures on Teradata need to have the following privileges:

- execute on SAS_SYSFNLIB
- select on SAS_SYSFNLIB
- execute function on SAS_SYSFNLIB

Set Up User Accounts

In addition to the database accounts that are discussed in previous sections, each user must have an operating system account on each node of the appliance, each user must have an operating system account on each node of the appliance. Each user account should have the same user identifier (uid) and group identifier (gid) across all the nodes.

Set Up SSH Keys

SAS High-Performance Analytics Server uses SSH as the communcation protocol between the appliance and client machine to provide passwordless login. The following sections describe how to set up SSH keys on the appliance and on the client.

Set Up SSH Keys on the Appliance

1 After the operating system account has been created, generate an SSH key for the user by entering this command as the new user:

```
ssh-keygen -t rsa
```

Press ENTER for all prompts and leave the passphrase blank. The operation of SAS High-Performance Analytics Server requires passwordless SSH between the host node and the other nodes on the appliance.

2 Add the public key to the list of authorized keys by appending *~/.ssh/id_rsa.pub* to the list of authorized keys in *~/.ssh/authorized_keys2* with a command such as this:

```
cat ~/.ssh/id_rsa.pub >> ~/.ssh/authorized_keys2
```

3 Set the proper file permissions on the *.ssh* directory and its contents. The *.ssh* directory and files contained in it should have read/write privileges for the user only (**chmod 600** for the *id_rsa* file and **chmod 700** for the *.ssh* directory).

4 Copy the *.ssh* directory to the user's home directory on all the nodes in the appliance.

5 Verify that the SSH keys are correct by using the **ssh** command to access all available nodes. The SSH connection should be successful without entering the user's password.

6 Verify each user account has been set up properly by entering the following command (where *#nodes* denotes the number of nodes in the system) to run an MPI job from the host node of the appliance:

```
export LD_LIBRARY_PATH=<install_location>/mpich2-install/lib
<install_location>/mpich2-install/bin/mpirun -f <install_location>/grid.hosts \
                                    -n \#nodes hostname
```

```
export LD_LIBRARY_PATH=/opt/TKGrid/mpich2-install/lib
/opt/TKGrid/mpich2-install/bin/mpirun -f /opt/TKGrid/grid.hosts \
                     -n \24 hostname
```

7 Provide the private key that is stored in *~/.ssh/id_rsa* to the user. The client can then complete installation of the key in the client home directory as discussed in the section "Set Up SSH Keys on the Client" on page 78. The user's user name on the client is also used as the user name on the appliance.

Set Up SSH Keys on the Client

The system administrator of the SAS High-Performance Analytics Server appliance provides you with an SSH key. This key is necessary for connecting to the appliance and needs to be stored on the client machine in the following location:

UNIX or Linux client	SAS reads the private key from *~/.ssh/id_rsa*.
Windows client	SAS searches for the key in *%HOMEDRIVE%\%HOMEPATH%\.ssh\id_rsa* and then in *%USERPROFILE%\.ssh\id_rsa*. For example, in a Windows 7 environment, keys are located in *c:\Users\<userid>\.ssh*.

Running with an Alternate User Name and Identity

The user name and the user's key file can by specified directly by setting the TKSSH_USER environment variable to an alternate user name and by setting the TKSSH_IDENTITY environment variable to the full path and filename of an alternate identity file.

Environment variables can be set on the client machine prior to running the SAS System, or they can be set in the SAS program with the OPTION SET= programming statement. For example, the following statements set an alternate user name and identity in the SAS program:

```
options set=TKSSH_USER="altuser";
options set=TKSSH_IDENTITY="/home/altuser/.ssh/alt_rsa";
```

Chapter 5
SAS High-Performance Analytics Features in SAS/OR

Contents

Overview **79**
DECOMP= Option (Experimental) **80**
Overview 80
Example 5.1: ATM Cash Management 80
MULTISTART Option (Experimental) **86**
Overview 86
Example 5.2: Solving Nonlinear Programming Problems with Several Local Minima 86
TUNER Statement (Experimental) **89**
Overview 89
Example 5.3: Tuning the Full Tuning Option Set in a Grid Environment 89
References **92**

Overview

The SAS High-Performance Analytics Server provides enhancements for several SAS/OR features. The PERFORMANCE statement enables you to control whether the OPTMODEL, OPTLP, OPTMILP, and OPTQP procedures execute in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. For more information about the PERFORMANCE statement, see Chapter 3, "Shared Concepts and Topics" (*SAS/OR User's Guide: Mathematical Programming*).

Table 5.1 lists SAS/OR features that exploit MPP mode.

Table 5.1 High-Performance Analytics Features in SAS/OR (Experimental)

Statement or Option	Procedure
DECOMP= option	OPTMODEL (LP and MILP solvers), OPTLP, OPTMILP
MULTISTART option	OPTMODEL (NLP solver)
TUNER statement	OPTMILP

This chapter provides a brief overview of each feature and an example that demonstrates the syntax for running SAS/OR procedures in MPP mode. For more information about running in MPP mode, see Chapter 3, "Shared Concepts and Topics."

NOTE: The features described in this chapter require SAS/OR software.

DECOMP= Option (Experimental)

Overview

The SAS/OR decomposition algorithm provides an alternative method for solving linear programs (LPs) and mixed integer linear programs (MILPs) by exploiting the ability to efficiently solve a relaxation of the original problem. The decomposition algorithm is available as an option in the OPTMODEL, OPTLP, and OPTMILP procedures and is based on the methodology described in Galati (2009). For more information about the decomposition algorithm, see Chapter 12, "The Decomposition Algorithm" (*SAS/OR User's Guide: Mathematical Programming*).

The DECOMP= option supports only the DETERMINISTIC value of the PARALLELMODE= option in the PERFORMANCE statement. For more information about the PARALLELMODE= option, see Chapter 3, "Shared Concepts and Topics" (*SAS/OR User's Guide: Mathematical Programming*).

Example 5.1: ATM Cash Management

This example illustrates the use of the DECOMP= option in a grid environment. The example describes an optimization model used in the management of cash flow for a bank's automated teller machine (ATM) network. The goal of the model is to determine a replenishment schedule for allocating cash inventory at bank branches to service a preassigned subset of ATMs. For more information about the problem and the model formulation, see Chapter 12, "The Decomposition Algorithm" (*SAS/OR User's Guide: Mathematical Programming*).

The following statements create the data sets for the problem:

```
data budget_data;
   input d $ budget;
   datalines;
DATE0      70079
DATE1      66418
DATE10     52656
DATE11     50439
DATE12     58688
DATE13     45002
DATE14     52369
...
;

data cashout_data;
    input a $ cashOutLimit;
    datalines;
ATM0            31
ATM1            24
ATM2            41
ATM3            43
ATM4            29
ATM5            24
```

```
ATM6            52
ATM7            44
ATM8            35
ATM9            48
ATM10           31
ATM11           47
ATM12           26
ATM13           34
ATM14           29
ATM15           32
ATM16           33
ATM17           32
ATM18           43
ATM19           28
;

data polyfit_data;
    input a $ d $ cx cy cz cu c withdrawal;
    datalines;
ATM0     DATE0       2822     1984    -1984    1045    1373        780
ATM0     DATE1       1337     2530    -2530    1510     174       2351
ATM0     DATE2       2685      -67       67     145    2820       2288
ATM0     DATE3       -595    -3135     3135     581    3319       1357
...
ATM19    DATE96      -734     3392    -3392     162    1648        914
ATM19    DATE97     -1062      969     -969     444    1746       2264
ATM19    DATE98      7676     2308    -2308      59    1388        972
ATM19    DATE99      3062     1308    -1308    1080     654        698
;
```

The following PROC OPTMODEL statements read in the data and define the necessary sets and parameters:

```
proc optmodel;
   set<str> DATES;
   set<str> ATMS;

   /* cash budget per date */
   num budget{DATES};
   /* maximum amount of cash-outs allowed at each atm */
   num cashOutLimit{ATMS};
   /* historical withdrawal amount per atm each date */
   num withdrawal{ATMS, DATES};

   /* polynomial fit coefficients for predicted cash flow needed */
   num c {ATMS, DATES};
   num cx{ATMS, DATES};
   num cy{ATMS, DATES};
   num cz{ATMS, DATES};
   num cu{ATMS, DATES};

   /* number of points used in approximation of continuous range */
   num nSteps = 10;
   set STEPS = {0..nSteps};
```

```
read data budget_data into DATES=[d] budget;
read data cashout_data into ATMS=[a] cashOutLimit;
read data polyfit_data into [a d] cx cy cz cu c withdrawal;
```

The following statements declare the variables:

```
var x{ATMS,STEPS}                 binary;
var v{ATMS,DATES}                 binary;
var z{ATMS,STEPS}                 >= 0 <= 1;
var y{ATMS}                       >= 0 <= 1;
var u{ATMS}                       >= 0;
var fPlus{ATMS,DATES}             >= 0;
var fMinus{a in ATMS, d in DATES} >= 0 <= withdrawal[a,d];
```

The following statements declare the objective and constraints:

```
min CashFlowDiff =
   sum{a in ATMS, d in DATES} (fPlus[a,d] + fMinus[a,d]);

con BudgetCon{d in DATES}:
   sum{a in ATMS} (fPlus[a,d] - fMinus[a,d] + withdrawal[a,d])
       <= budget[d];

con CashFlowDefCon{a in ATMS, d in DATES}:
   cx[a,d] * sum{t in STEPS} (t/nSteps) * x[a,t] +
   cy[a,d] * y[a]                                +
   cz[a,d] * sum{t in STEPS} (t/nSteps) * z[a,t] +
   cu[a,d] * u[a]                                +
   c[a,d] - withdrawal[a,d] = fPlus[a,d] - fMinus[a,d];

con PickOneStepCon{a in ATMS}:
   sum{t in STEPS} x[a,t] = 1;

con CashOutLinkCon{a in ATMS, d in DATES}:
   fMinus[a,d] <= withdrawal[a,d] * v[a,d];

con CashOutLimitCon{a in ATMS}:
   sum{d in DATES} v[a,d] <= cashOutLimit[a];

con Linear1Con{a in ATMS, t in STEPS}:
   z[a,t] <= x[a,t];

con Linear2Con{a in ATMS}:
   sum{t in STEPS} z[a,t] = y[a];
```

The following statements define the block decomposition by ATM:

```
/* create numeric block index */
num blockIndex {ATMS};
num index init 0;
for{a in ATMS} do;
   blockIndex[a] = index;
   index = index + 1;
end;

/* define blocks for each ATM */
for{a in ATMS} do;
   PickOneStepCon[a].block  = blockIndex[a];
   CashOutLimitCon[a].block = blockIndex[a];
   Linear2Con[a].block      = blockIndex[a];
   for{d in DATES} do;
      CashFlowDefCon[a,d].block = blockIndex[a];
      CashOutLinkCon[a,d].block = blockIndex[a];
   end;
   for{t in STEPS} do;
      Linear1Con[a,t].block = blockIndex[a];
   end;
end;
```

Finally, the following statements use the DECOMP= option to solve the problem. The PERFORMANCE statement specifies the number of threads and nodes to be used.

```
/* set the number of threads and get performance details */
performance details nthreads=12 nodes=4;

/* solve with the decomposition algorithm */
solve with milp / relobjgap=1e-5 decomp=();
quit;
```

The "Solution Summary," "Performance Information," and "Procedure Task Timing" tables are displayed in Figure 5.1.1.

Output 5.1.1 Performance Information, Solution Summary, and Task Timing Table

```
                    The OPTMODEL Procedure

                   Performance Information

Host Node                        << your grid host >>
Execution Mode                            Distributed
Number of Compute Nodes                             4
Number of Threads per Node                         12
```

Output 5.1.1 *continued*

Solution Summary

Solver	MILP
Algorithm	Decomposition
Objective Function	CashFlowDiff
Solution Status	Optimal
Objective Value	2463559.2425
Iterations	68
Best Bound	2463559.2425
Nodes	55
Relative Gap	0
Absolute Gap	0
Primal Infeasibility	2.6361704E-9
Bound Infeasibility	3.4861E-13
Integer Infeasibility	1E-5

Procedure Task Timing

Task	Time (sec.)	% Time
Problem Generation	0.09	0.03%
Solver Initialization	0.06	0.02%
Code Generation	0.00	0.00%
Solver	367.99	99.95%
Solver Postprocessing	0.02	0.00%

The iteration log, which contains the problem statistics, the progress of the solution, and the optimal objective value, is shown in Figure 5.1.2.

Output 5.1.2 Log

```
NOTE: There were 100 observations read from the data set WORK.BUDGET_DATA.
NOTE: There were 20 observations read from the data set WORK.CASHOUT_DATA.
NOTE: There were 2000 observations read from the data set WORK.POLYFIT_DATA.
NOTE: Problem generation will use 2 threads.
NOTE: The problem has 6480 variables (0 free, 0 fixed).
NOTE: The problem has 2220 binary and 0 integer variables.
NOTE: The problem has 4380 linear constraints (2340 LE, 2040 EQ, 0 GE, 0 range).
NOTE: The problem has 58878 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The MILP presolver value AUTOMATIC is applied.
NOTE: The MILP presolver removed 535 variables and 367 constraints.
NOTE: The MILP presolver removed 1249 constraint coefficients.
NOTE: The MILP presolver modified 0 constraint coefficients.
NOTE: The presolved problem has 5945 variables, 4013 constraints, and 57629
      constraint coefficients.
NOTE: The MILP solver is called.
NOTE: The Decomposition algorithm is used.
NOTE: The High-Performance Analytics Server version of the Decomposition
      algorithm is experimental.
NOTE: The Decomposition algorithm is executing in the distributed computing
      environment with 4 worker nodes.
NOTE: The DECOMP method value USER is applied.
NOTE: The decomposition subproblems consist of 20 disjoint blocks.
NOTE: The decomposition subproblems cover 5945 (100.00%) variables and 3913
      (97.51%) constraints.
NOTE: The deterministic parallel mode is enabled.
NOTE: The Decomposition algorithm is using up to 12 threads.
Iter         Best       Master         Best       LP       IP   CPU  Real
           Bound    Objective      Integer      Gap      Gap  Time  Time
NOTE: Starting phase 1.
   1       0.0000       1.1767            . 1.18e+00        .     0    15
   2       0.0000       0.0000            . 0.00e+00        .     0    15
NOTE: Starting phase 2.
   .    2.4432e+06   2.6320e+06   2.7000e+06    7.73%   10.51%     0    15
   4    2.4556e+06   2.4839e+06   2.7000e+06    1.15%    9.95%     0    24
   5    2.4630e+06   2.4642e+06   2.7000e+06    0.05%    9.62%     0    29
   6    2.4631e+06   2.4631e+06   2.7000e+06    0.00%    9.62%     0    33
NOTE: The Decomposition algorithm stopped on the continuous RELOBJGAP option.
   .    2.4631e+06   2.4631e+06   2.4640e+06    0.00%    0.04%     0    33
NOTE: Starting branch and bound.
   Node  Active   Sols         Best         Best      Gap      CPU     Real
                             Integer        Bound             Time     Time
      0       1      2   2.4640e+06   2.4631e+06    0.04%       0       33
     10       8      2   2.4640e+06   2.4635e+06    0.02%       0       97
     19       5      4   2.4637e+06   2.4635e+06    0.00%       0      165
     20       4      4   2.4637e+06   2.4636e+06    0.00%       0      172
     30       2      4   2.4637e+06   2.4636e+06    0.00%       0      232
     40       4      4   2.4637e+06   2.4636e+06    0.00%       0      289
     50       4      4   2.4637e+06   2.4636e+06    0.00%       0      339
     54       0      5   2.4636e+06   2.4636e+06    0.00%       0      365
NOTE: The Decomposition algorithm used 12 threads.
NOTE: The Decomposition algorithm time is 365.27 seconds.
NOTE: Optimal.
NOTE: Objective = 2463559.24.
```

MULTISTART Option (Experimental)

Overview

For optimization problems that contain many local optima, the NLP solver for the OPTMODEL procedure can be run in multistart mode by specifying the MULTISTART option. For more information about this option, see Chapter 7, "The Nonlinear Programming Solver" (*SAS/OR User's Guide: Mathematical Programming*).

If the multistart mode is specified, the NLP solver samples the feasible region and generates a number of starting points. Then the local solver can be called from each of those starting points and could converge to possibly different local optima. The local minimum with the best objective value is reported back to the user as the optimal solution.

The MULTISTART option supports only the DETERMINISTIC value of the PARALLELMODE= option in the PERFORMANCE statement. For more information about the PARALLELMODE= option, see Chapter 3, "Shared Concepts and Topics" (*SAS/OR User's Guide: Mathematical Programming*).

Example 5.2: Solving Nonlinear Programming Problems with Several Local Minima

This example is taken from Hock and Schittkowski (1981); for more information about the problem and the OPTMODEL statements, see Chapter 7, "The Nonlinear Programming Solver" (*SAS/OR User's Guide: Mathematical Programming*).

The following nonlinear programming problem has several local minima:

$$
\begin{array}{ll}
\text{minimize} & f(x) = (x_1 - 1)^2 + (x_1 - x_2)^2 + (x_2 - x_3)^3 + (x_3 - x_4)^4 + (x_4 - x_5)^4 \\
\text{subject to} & x_1 + x_2^2 + x_3^3 = 2 + 3\sqrt{2} \\
& x_2 + x_4 - x_3^2 = -2 + 2\sqrt{2} \\
& x_1 x_5 = 2 \\
& -5 \le x_i \le 5, i = 1, \ldots, 5
\end{array}
$$

The following statements call the NLP solver to search the feasible region for different local minima. The PERFORMANCE statement requests that the multistart algorithm use multiple threads and multiple nodes. The SEED= option is specified for reproducibility, but you can run the multistart algorithm without specifying this option. The PRINT statement prints the initial point that is specified in the VAR declaration (x.init), the starting point that led to the best local solution (x.msinit), and finally the best local solution (x) that is found by the NLP solver in multistart mode.

```
proc optmodel;
   var x{i in 1..5} >= -5 <= 5 init -2;

   min f=(x[1] - 1)^2 + (x[1] - x[2])^2 + (x[2] - x[3])^3 +
         (x[3] - x[4])^4 + (x[4] - x[5])^4;
```

```
   con g1: x[1] + x[2]^2 + x[3]^3 =  2 + 3*sqrt(2);
   con g2: x[2] + x[4]   - x[3]^2 = -2 + 2*sqrt(2);
   con g3: x[1]*x[5] = 2;

   performance nthreads=4 nodes=4;
   solve with nlp/multistart seed=42 msmaxstarts=10;
   print x.init x.msinit x;
quit;
```

The SAS log shows the progress of the algorithm. See Output 5.2.1.

Output 5.2.1 Progress of the Algorithm as Shown in the Log

```
NOTE: Problem generation will use 2 threads.
NOTE: The problem has 5 variables (0 free, 0 fixed).
NOTE: The problem has 0 linear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The problem has 3 nonlinear constraints (0 LE, 3 EQ, 0 GE, 0 range).
NOTE: The OPTMODEL presolver removed 0 variables, 0 linear constraints, and 0
      nonlinear constraints.
NOTE: Using analytic derivatives for objective.
NOTE: Using analytic derivatives for nonlinear constraints.
NOTE: The NLP solver is called.
NOTE: The Interior Point algorithm is used.
NOTE: The MULTISTART option is enabled.
NOTE: The High-Performance Analytics Server version of the Multistart algorithm
      is experimental.
NOTE: The deterministic parallel mode is enabled.
NOTE: The Multistart algorithm is executing in the distributed computing
      environment with 4 worker nodes.
NOTE: The Multistart algorithm is using up to 4 threads.
NOTE: Random number seed 42 is used.
                    Best       Local  Optimality    Infeasi-  Local  Local
      Start    Objective   Objective       Error      bility  Iters  Status
          1   0.02931077  0.02931077  7.21986E-7  7.21986E-7     24  Optimal
          2   0.02931077  0.02931084  9.71955E-7  1.01574E-7    106  Optimal
          3   0.02931077  27.8719052  6.77215E-7  1.22974E-8    195  Optimal
          4   0.02931067  0.02931067  6.61678E-7  6.28814E-7     25  Optimal
          5   0.02931067  27.8719052  9.32311E-7  3.99823E-8    119  Optimal
          6   0.02931067  0.02931083  9.43333E-7  2.05071E-9    180  Optimal
          7   0.02931067  27.8719056  9.98916E-7  4.02764E-8    174  Optimal
          8   0.02931067  27.8719052  3.85945E-7  5.01823E-9    107  Optimal
          9   0.02931067  607.035495   1.7036E-7  3.67285E-8     14  Optimal
         10   0.02931067  27.8719052  6.04449E-7  4.8022E-11    720  Optimal
NOTE: The Multistart algorithm generated 1600 sample points.
NOTE: 10 distinct local optima were found.
NOTE: The best objective value found by local solver = 27.871905225.
```

Output 5.2.2 shows the summaries and solution. Note that the best solution was found by starting the local solver from a starting point (x.msinit) that is different from the point that is specified in the VAR declaration (x.init).

Output 5.2.2 Summaries and the Optimal Solution

The OPTMODEL Procedure

Problem Summary

Objective Sense	Minimization
Objective Function	f
Objective Type	Nonlinear
Number of Variables	5
Bounded Above	0
Bounded Below	0
Bounded Below and Above	5
Free	0
Fixed	0
Number of Constraints	3
Linear LE (<=)	0
Linear EQ (=)	0
Linear GE (>=)	0
Linear Range	0
Nonlinear LE (<=)	0
Nonlinear EQ (=)	3
Nonlinear GE (>=)	0
Nonlinear Range	0

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	4
Number of Threads per Node	4

Solution Summary

Solver	Multistart NLP
Algorithm	Interior Point
Objective Function	f
Solution Status	Best Feasible
Objective Value	27.871900787
Number of Starts	10
Number of Sample Points	1600
Number of Distinct Optima	9
Random Seed Used	42
Optimality Error	0.0262811381
Infeasibility	5.3054973E-7

Output 5.2.2 *continued*

[1]	x.INIT	x.MSINIT	x
1	-2	0	-1.2730
2	-2	0	2.4103
3	-2	0	1.1949
4	-2	0	-0.1542
5	-2	0	-1.5711

TUNER Statement (Experimental)

Overview

The OPTMILP procedure provides numerous solver techniques and algorithms, which include branch-and-bound, cutting planes, and heuristics. PROC OPTMILP also provides control options that you can adjust to improve the performance of these techniques. Although the default values of the control options have been tuned to work well for most instances, non-default settings can significantly improve performance for certain classes of problems. The TUNER statement enables you to explore alternative (and potentially better) option configurations for your optimization problems. For more information about the TUNER statement, see Chapter 13, "The OPTMILP Option Tuner" (*SAS/OR User's Guide: Mathematical Programming*).

The TUNER statement supports only the NONDETERMINISTIC value of the PARALLELMODE= option in the PERFORMANCE statement. For more information about the PARALLELMODE= option, see Chapter 3, "Shared Concepts and Topics" (*SAS/OR User's Guide: Mathematical Programming*).

Example 5.3: Tuning the Full Tuning Option Set in a Grid Environment

This example illustrates the use of the TUNER statement in PROC OPTMILP in a grid environment.

The standard set of MILP benchmark cases is called MIPLIB (Bixby et al. 1998, Achterberg, Koch, and Martin 2003) and can be found at `http://miplib.zib.de/`. Suppose that you want to solve the problems air04 and air05 from this set, you have stored the SAS data sets *air04.dat* and *air05.dat* (both in MPS format) in library a, and you want to tune the full set of tuning options on these two problems.

The following DATA steps generate the data set probs, which contains the list of problems to be solved. Because you are tuning the full set of options, it is not necessary to create an OPTIONVALUES= data set.

```
data probs;
   input name $1-8;
   datalines;
a.air04
a.air05
;
```

The following statements call the OPTMILP procedure and enable the option tuner. Specifying OPTIONMODE=FULL causes the tuner to tune the full set of available tuning options. The PERFORMANCE statement specifies the number of threads and nodes to be used by the option tuner.

```
proc optmilp maxtime=300;
   tuner problems=probs optionmode=full maxtime=1200
         goal=sum loglevel=1 tunerout=tout;
   performance nthreads=2 nodes=4;
run;
```

The "Tuner Results" table displays the option configurations that yield the smallest and largest average run time per problem. This table is shown in Output 5.3.1. Because the tuner results are nondeterministic, your results might vary from the values shown.

Output 5.3.1 Tuner Results: Grid Environment

The OPTMILP Procedure

Tuner Results

	Config 0	Config 1	Config 2	Config 3	Config 4	Config 5
PRESOLVER	-1	1	-1	-1	-1	-1
PROBE	-1	2	2	2	2	2
SCALE	-1	0	0	0	0	0
CONFLICTSEARCH	-1	2	2	2	2	2
NODESEL	-1	2	2	2	2	2
VARSEL	-1	2	2	2	2	2
STRONGITER	-1	2.1475E9	2.1475E9	2.1475E9	2.1475E9	2.1475E9
HEURISTICS	-1	0	0	0	0	1
ALLCUTS	-1	2	2	2	2	2
CUTSTRATEGY	-1	2	2	2	2	2
CUTSFACTOR	3	5	5	5	5	5
CUTCLIQUE	-1	2	2	2	2	2
CUTFLOWCOVER	-1	2	2	2	2	2
CUTFLOWPATH	-1	0	0	0	0	0
CUTGOMORY	-1	-1	0	-1	-1	-1
CUTGUB	0	2	2	2	2	2
CUTIMPLIED	0	1	1	1	1	1
CUTKNAPSACK	0	0	0	0	0	0
CUTLAP	0	1	1	1	1	1
CUTMILIFTED	-1	-1	-1	1	-1	-1
CUTMIR	0	1	1	1	1	1
CUTZEROHALF	-1	2	2	2	0	2
Run Time (Mean)	69.39	49.31	59.11	59.42	59.68	59.68
Run Time (Sum)	142.12	98.64	118.56	119.2	119.63	119.84
Num of Failed	0	0	0	0	0	0

Output 5.3.1 *continued*

The OPTMILP Procedure

Tuner Results

	Config 6	Config 7	Config 8	Config 9	Config 10
PRESOLVER	-1	0	-1	3	2
PROBE	2	1	1	2	2
SCALE	0	-1	0	-1	-1
CONFLICTSEARCH	2	0	-1	2	1
NODESEL	2	0	0	0	1
VARSEL	3	1	1	1	1
STRONGITER	2.1475E9	100	10000	-1	1000
HEURISTICS	0	1	3	0	3
ALLCUTS	2	-1	-1	-1	2
CUTSTRATEGY	2	0	0	-1	-1
CUTSFACTOR	5	5	10	0.25	1
CUTCLIQUE	2	-1	0	2	0
CUTFLOWCOVER	2	-1	-1	0	1
CUTFLOWPATH	0	1	1	1	0
CUTGOMORY	-1	2	2	2	2
CUTGUB	2	1	1	0	2
CUTIMPLIED	1	0	2	2	1
CUTKNAPSACK	0	0	1	2	0
CUTLAP	1	1	1	1	1
CUTMILIFTED	-1	0	-1	2	1
CUTMIR	1	2	0	1	1
CUTZEROHALF	2	0	2	0	-1
Run Time (Mean)	123.19	300.01	300.38	301.04	301.2
Run Time (Sum)	267.34	600.03	600.77	602.09	602.41
Num of Failed	0	0	0	0	0

References

Achterberg, T., Koch, T., and Martin, A. (2003), "MIPLIB 2003," on the MIPLIB Web page: http://miplib.zib.de/.

Bixby, R. E., Ceria, S., McZeal, C. M., and Savelsbergh, M. W. P. (1998), "An Updated Mixed Integer Programming Library: MIPLIB 3.0," *Optima*, 58, 12–15.

Galati, M. (2009), *Decomposition in Integer Linear Programming*, Ph.D. thesis, Lehigh University.

Hock, W. and Schittkowski, K. (1981), *Lecture Notes in Economics and Mathematical Systems: Test Examples for Nonlinear Programming Codes*, Berlin: Springer-Verlag.

Chapter 6
The HP4SCORE Procedure

Contents

Overview: HP4SCORE Procedure **93**
PROC HP4SCORE Features 94
PROC HP4SCORE Contrasted with Other SAS Procedures 94
Getting Started: HP4SCORE Procedure **94**
Syntax: HP4SCORE Procedure **96**
PROC HP4SCORE Statement 96
ID Statement 96
PERFORMANCE Statement 97
SCORE Statement 97
Details: HP4SCORE Procedure **97**
Displayed Output 97
Output Data Set 98
Examples: HP4SCORE Procedure **98**
Example 6.1: Running PROC HP4SCORE on the Client 98
Example 6.2: Running PROC HP4SCORE with Client Data on the SAS Appliance . 99
Example 6.3: Running PROC HP4SCORE with Data on the SAS Appliance 100

Overview: HP4SCORE Procedure

The HP4SCORE procedure is a high-performance procedure that scores a data set with a forest predictive model that was previously trained by the HPFOREST procedure. See Chapter 13, "The HPFOREST Procedure."

The forest predictive model is an ensemble of hundreds of decision trees that are used to predict a target. The target can have either an interval or a nominal measurement level. Each decision tree consists of a sequence of rules that are applied to the observation to arrive at the prediction. The final prediction is either an average of the individual predictions for a target that has an interval measurement level or is derived from the average of the individual posterior probabilities for a target that has a nominal measurement level.

The HP4SCORE procedure can score the data in distributed form in parallel when executed in the symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about how to configure the execution mode of SAS High-Performance Analytics procedures.

PROC HP4SCORE Features

The HP4SCORE procedure is designed to be used subsequent to the training performed by the HPFOREST procedure. PROC HP4SCORE requires the binary model file that is created by the HPFOREST procedure and that encapsulates the full forest model. PROC HP4SCORE then applies the model for scoring a specified data set. For successful scoring, the variables in the data set that is specified in the input to PROC HP4SCORE must have the same attributes as the data set on which the model was trained (that is, the data set that was specified as input to PROC HPFOREST). If the attributes do not match, the HP4SCORE procedure stops with an error.

PROC HP4SCORE Contrasted with Other SAS Procedures

No other SAS procedure scores a forest model. SAS high-performance procedures create DATA step programs that incorporate the scoring logic in the model. The decision tree procedures in SAS Enterprise Miner (the ARBOR, DMSPLIT, and SPLIT procedures) also output the score code directly. Because the forest model is an ensemble of hundreds of decision trees and each decision tree can contain hundreds or thousands of decision rules for scoring, the DATA step program can become extremely large. In addition to slow scoring performance, a very large DATA step program also poses additional challenges. PROC HP4SCORE overcomes these difficulties by reading the binary model file and scoring the observations directly.

The HP4SCORE procedure can run on a grid of computers as can other SAS High-Performance Analytics procedures. It exploits the parallelism available on the grid such that each CPU core runs a separate scoring task. For general contrasts between SAS High-Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16.

Getting Started: HP4SCORE Procedure

This example shows the usage of the HP4SCORE procedure in conjunction with the HPFOREST procedure. The HPFOREST procedure first trains a model on the training data and saves the model as a binary file. The HP4SCORE procedure then uses the trained model to score a different data set.

The hypothetical data set contains the ratings by three different volunteers on six different proportions of fruits. The following DATA step creates the SAS data set PunchTrain with the proportions of watermelon, pineapple, orange, and the numerical ratings for each combination of fruit mix and the volunteer:

```
data PunchTrain;
   input watermelon pineapple orange rating;
   datalines;
   1.0 0.0 0.0 4.3
   1.0 0.0 0.0 4.7
   1.0 0.0 0.0 4.8
   0.0 1.0 0.0 6.2
   0.0 1.0 0.0 6.5
   0.0 1.0 0.0 6.3
```

```
      0.5 0.5 0.0 6.3
      0.5 0.5 0.0 6.1
      0.5 0.5 0.0 5.8
      0.0 0.0 1.0 7.0
      0.0 0.0 1.0 6.9
      0.0 0.0 1.0 7.4
      0.5 0.0 0.5 6.1
      0.5 0.0 0.5 6.5
      0.5 0.0 0.5 5.9
      0.0 0.5 0.5 6.2
      0.0 0.5 0.5 6.1
      0.0 0.5 0.5 6.2
      ;
    run;
```

The following statements train the forest model on the data set with the rating as the target and different fruit mix proportions as the independent variables. The SAVE statement saves the model to a binary file *punchModel.sav* in the current directory. For the full details of the HPFOREST procedure options, see Chapter 13, "The HPFOREST Procedure."

```
proc hpforest data=PunchTrain maxtrees=10;
   input watermelon pineapple orange;
   target rating;
   save file="punchModel.sav";
run;
```

The following DATA step creates the SAS data set PunchScore, which contains only the proportions of watermelon, pineapple, orange fruit:

```
  data PunchScore;
     input watermelon pineapple orange;
     datalines;
     0.6 0.4 0.0
     0.9 0.1 0.0
     0.8 0.0 0.2
     0.5 0.3 0.2
     0.3 0.1 0.6
     ;
   run;
```

The following statements invoke HP4SCORE to score this data set:

```
proc hp4score data=PunchScore;
   score file="punchModel.sav" out=scoreout;
run;

proc print data=scoreout;
run;
```

The SAS data set scoreout contains the ratings for each input observation as predicted by the model. Output 6.1 shows the scoring results.

Figure 6.1 Scored Data set

Obs	P_rating	_WARN_
1	5.61429	
2	5.50286	
3	5.50286	
4	5.61429	
5	5.83429	

Syntax: HP4SCORE Procedure

The following statements are available in the HP4SCORE procedure:

PROC HP4SCORE *data-options* **;**
ID *variables* **;**
SCORE *score-options* **;**
PERFORMANCE *performance-options* **;**

The PROC HP4SCORE statement and SCORE statements are required.

PROC HP4SCORE Statement

PROC HP4SCORE DATA=< *libref.*>*SAS-data-set* **;**

The PROC HP4SCORE statement invokes the procedure.

DATA=< *libref.*>*SAS-data-set*
names the SAS data set to be used for scoring by PROC HP4SCORE. This argument is required.

If the data are already distributed, PROC HP4SCORE reads the data alongside the distributed database. The different nodes then independently read the data rows, score them and write them back. See the section "SMP and MPP Modes" on page 16 for information about the various execution modes and the section "Alongside-the-Database Execution" on page 22 for information about the alongside-the-database model.

ID Statement

ID *variables* **;**

The ID statement lists one or more *variables* from the input data set that are transferred to the output data set. The ID statement accepts numeric and character variables. For more information about the ID statement, see the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics." in the SAS High-Performance Analytics User Guide. The ID statement is optional.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HP4SCORE procedure.

You can also use the PERFORMANCE statement to control whether the HP4SCORE procedure executes in symmetric multiprocessing or massively parallel mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SCORE Statement

SCORE *score-options* **;**

The SCORE statement specifies the name of the model file and the output data set name. You can specify the following *score-options*:

FILE=*model-file-name*
specifies either the file reference or the full path and member name of the valid model file that was created by PROC HPFOREST.

OUT=< *libref.***>***SAS-data-set*
names the output SAS data set to contain the scored results.

Details: HP4SCORE Procedure

When PROC HPFOREST saves the model, it saves only the variables that were used in the model. These might be all the input variables or a subset of those variables. The data set to be scored must contain the variables that are in the model. These variables must have same attributes as the training data. They include variable names (differences in character case are ignored), the data type, and the length. If a variable that has a nominal measurement level has a level that was not present in the training data set, that level is treated as a missing value. The HP4SCORE procedure does not ignore observations with missing values while scoring. The full model is applied on all the observations, and the prediction is computed.

Displayed Output

The HP4SCORE procedure displays the the following information tables:

- The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution, the procedure execution mode, the numbers of computing nodes, and the number of threads used in the execution.

- The “Number of Observations” table displays total number of observations that are read from the data set and the total number of observations scored.
- The “Procedure Task Timing” table reports the total elapsed time.

Output Data Set

The HP4SCORE procedure writes the scored results as a separate output data set, which contains one observation for each input observation. Only the ID variables specified in the ID statement are copied from the input data set to the output data set. The prediction variables depend on the measurement type of the target variable in the model. For a target that has an interval measurement level, a single prediction variable is generated. For each level of the target that has a nominal measurement level, a posterior probability variable is generated in addition to the final predicted level. The names of the variables are constructed using the rules that are explained in the SAS Enterprise Miner product documentation.

If the input data set is read in alongside-the-database mode from the SAS appliance, the output data set is written back in parallel. In this case, the output records are distributed across the processing nodes such that the input row and the corresponding output row are colocated.

Examples: HP4SCORE Procedure

All examples use the same training data set and the model file, which is created by PROC HPFOREST in the following statements:

```
filename outmodel "C:\Temp\HPForestModel";
proc HPFOREST data=sampsio.hmeq;
  input CLAGE CLNO LOAN MORTDUE VALUE YOJ DEBTINC/level=interval;
  input BAD DELINQ DEROG NINQ REASON/level=nominal;
  target JOB/level=nominal;
  save file=outmodel;
quit;
```

Example 6.1: Running PROC HP4SCORE on the Client

When the input data set resides on the client and no PERFORMANCE statement is specified, as in this example, the client performs all computations:

```
filename outmodel "C:\Temp\HPForestModel";
proc hp4score data=sampsio.hmeq;
   score file=outmodel out=scoreout2;
run;

proc print data=scoreout2(obs=10);
run;
```

Output 6.1.1 shows the performance information.

Output 6.1.1 Performance Information

Performance Information	
Execution Mode	On client
Number of Threads	2

Output 6.1.2 shows the first 10 rows from the output data set.

Output 6.1.2 Sample Output Dataset

Obs	P_JOBMGR	P_JOBOFFICE	P_JOBOTHER	P_JOBPROFEXE	P_JOBSALES	P_JOBSELF	I_JOB	_WARN
1	0.13556	0.09691	0.62320	0.09956	0.008110	0.036663	OTHER	
2	0.13870	0.14024	0.51601	0.14507	0.020314	0.039667	OTHER	
3	0.12168	0.13966	0.58658	0.10160	0.009183	0.041306	OTHER	
4	0.15152	0.06748	0.62082	0.11853	0.003805	0.037842	OTHER	U
5	0.12314	0.26041	0.31289	0.24781	0.004851	0.050903	OTHER	
6	0.09581	0.10532	0.70354	0.07118	0.004112	0.020035	OTHER	
7	0.15158	0.12388	0.57065	0.08740	0.021844	0.044641	OTHER	
8	0.10845	0.10360	0.68056	0.08255	0.005095	0.019745	OTHER	
9	0.12251	0.13444	0.54375	0.15251	0.007440	0.039353	OTHER	
10	0.10804	0.13842	0.57147	0.10252	0.033633	0.045920	OTHER	

Example 6.2: Running PROC HP4SCORE with Client Data on the SAS Appliance

This example uses the same data set and model file as Example 6.1.

When the input data set resides on the client and a PERFORMANCE statement with a NODES= option is specified, as in the following statements, PROC HP4SCORE copies the data set to the SAS appliance and performs the scoring:

```
/* Uses the model generated in the previous example */
option set=GRIDHOST      = "&GRIDHOST";
option set=GRIDINSTALLLOC= "&GRIDINSTALLLOC";
filename outmodel "C:\Temp\HPForestModel";
proc hp4score data=sampsio.hmeq;
  score file=outmodel out=scoreout2;
  performance nodes=10 nthreads=8;
run;
```

Output 6.2.1 shows the performance information.

Output 6.2.1 Performance Information

```
                    Performance Information

Host Node                      << your grid host >>
Execution Mode                 Distributed
Number of Compute Nodes        10
Number of Threads per Node     8
```

Example 6.3: Running PROC HP4SCORE with Data on the SAS Appliance

When the input data set resides on the SAS appliance, the SAS appliance performs all computations, writes out results on the SAS appliance, and reports the results and performance back to the client. In the following statements, the input data reside in the MyLib library (which is a distributed data source), and the output data set is a distributed data set in the MyLib library. You can use the DATASETS procedure to delete the output table if it already exists on the SAS appliance.

```
/* Uses the model generated in the previous example */
option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC= "&GRIDINSTALLLOC";
libname MyLib &LIBTYPE
       server  = "&GRIDDATASERVER"
       user    = &USER
       password= &PASSWORD
       database= &DATABASE;
proc datasets lib=Mylib nolist; delete scoreout2;
run;
filename outmodel "C:\Temp\HPForestModel";
proc hp4score data=Mylib.hmeq;
   score file=outmodel out=scoreout2;
   performance details;
run;
```

Output 6.3.1 shows the performance information.

Output 6.3.1 Performance Information

```
                    Performance Information

Host Node                      << your grid host >>
Execution Mode                 Distributed, alongside Greenplum
Number of Compute Nodes        16
Number of Threads per Node     24
```

Chapter 7
The HPBIN Procedure

Contents

Overview: HPBIN Procedure **101**
PROC HPBIN Features 102
Getting Started: HPBIN Procedure **102**
Bucket Binning 102
Winsorized Binning 103
Pseudo–Quantile Binning 103
Syntax: HPBIN Procedure **105**
PROC HPBIN Statement 105
CODE Statement 107
FREQ Statement 107
ID Statement 107
PERFORMANCE Statement 108
VAR Statement 108
Details: HPBIN Procedure **108**
Computation and Formulas 108
Data Output 110
ODS Tables 110
Examples **112**
Example 7.1: Bucket Binning in SMP Mode 112
Example 7.2: Pseudo–Quantile Binning on the Grid 115
Example 7.3: Winsorized Binning 120
Example 7.4: Bucket Binning on the Teradata Appliance 121

Overview: HPBIN Procedure

Binning is a common step in the data preparation stage of the model building process. You can use binning to classify missing variables, reduce the impact of outliers, and generate multiple effects. The generated effects are useful and contain certain nonlinear information about the original interval variables.

The HPBIN procedure conducts high-performance binning using either bucket binning, Winsorized binning, or pseudo–quantile binning. Like other high-performance procedures, the HPBIN procedure can read and write data in distributed form, and it can perform computation in parallel in either symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode.

PROC HPBIN Features

The HPBIN procedure has the following features:

- can perform analysis on a massively parallel SAS high-performance appliance
- reads input data in parallel and writes output data in parallel when the data source is in a database on the appliance
- is highly multithreaded during all phases of analytic execution
- provides a bucket (equal-length) binning method
- provides a Winsorized binning method and Winsorized statistics
- provides a pseudo–quantile binning method, which is similar to quantile binning
- provides a mapping table for the selected binning method
- provides a basic statistical table that contains the minimum, maximum, mean, pseudo-median, and so on
- provides a histogram table that shows the output mapping statistics
- provides an estimation of a pseudo–quantile table

Getting Started: HPBIN Procedure

Bucket Binning

If you are familiar with SAS Enterprise Miner, you might recall a special variable named *aov16*, which is used heavily during the data preparation and variable selection stages. This variable is a classification variable with maximum level 16 that is derived from an interval variable. If you discretize the levels of the interval variables, you can obtain much better results. Bucket binning creates equal-length bins and assigns the data to one of these bins. You can choose the number of bins during the binning; the default number of bins (the binning level) is 16.

Winsorized Binning

Winsorized binning is similar to bucket binning except that both tails are cut off to obtain a smooth binning result. This technique is often used to remove outliers during the data preparation stage.

Pseudo–Quantile Binning

Quantile binning requires data to be sorted in a particular way, and the sorting process usually consumes a significant amount of CPU time and memory size. When the input data set is larger than the available memory, the sorting algorithm becomes more complicated. In distributed computing, data communications overhead also increases the sorting challenge.

To address these issues, the HPBIN procedure offers a novel approach to quantile binning, called pseudo–quantile binning. The pseudo–quantile binning method is very efficient, and the results mimic those of the quantile binning method. For example, consider the following statements:

```
data bindata;
    do i=1 to 1000;
     x=rannorm(1);
     output;
    end;
run;

proc rank data=bindata out=rankout group=8;
    var x;
    ranks rank_x;
run;

proc univariate data=rankout plot;
    var rank_x;
    histogram;
run;
```

These statements create a data set that contains 1,000 observations, each generated from a random normal distribution. The histogram for this data set is shown in Figure 7.1.

Figure 7.1 Histogram for Rank X



The pseudo–quantile binning method in the HPBIN procedure can achieve a similar result with far less computation time. In this case, the time complexity is $C * O(n)$, where C is a constant and n is the number of observations. When the algorithm runs on the grid, the total amount of computation time is much less. For example, if a cluster has 32 nodes and each node has 24 shared-memory CPUs, then the time complexity is $(C * O(n))/(32 * 24)$.

The following statements bin the data by using the PSEUDO_QUANTILE option in the PROC HPBIN statement and generate the histogram for the binning output data. (See Figure 7.2.) This histogram is similar to the one in Figure 7.1.

```
proc hpbin data=bindata output=binout numbin=8 pseudo_quantile;
    var x;
run;

proc univariate data=binout plot;
    var bin_x;
    histogram;
run;
```

Figure 7.2 Histogram For Binning X



Syntax: HPBIN Procedure

The following statements are available in the HPBIN procedure:

PROC HPBIN DATA=*sas-data-set* < *options* > **;**
VAR *variables-list* **;**
ID *variables-list* **;**
FREQ *variable* **;**
CODE *FILE=filename* **;**
PERFORMANCE < *performance-options* > **;**

The following sections describe the PROC HPBIN statement and then describe the other statements in alphabetical order.

PROC HPBIN Statement

PROC HPBIN < *options* > **;**

The PROC HPBIN statement invokes the procedure. Table 7.1 summarizes important *options* in the PROC HPBIN statement by function.

Table 7.1 PROC HPBIN Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
OUTPUT=	Specifies the output data set
NOPRINT	Overwrites the ODS output
Binning Level Options	
NUMBIN=	Specifies the expected number of bins
Output Options	
REPLACE	Specifies the replacement of the original variables
Binning Method Options	
BUCKET	Specifies the bucket method
WINSOR	Specifies the Winsor method and Winsor rate
WINSORRATE=	
PSEUDO_QUANTILE	Specifies the pseudo–quantile method
Statistics Options	
COMPUTESTATS	Computes the basic statistics of the variables
COMPUTEQUANTILE	Compute a quantile estimation of the variables

BUCKET | WINSOR WINSORRATE=*number*| **PSEUDO_QUANTILE**

specifies which binning method to use. If you specify BUCKET, then PROC HPBIN uses equal-length binning. If you specify WINSOR, PROC HPBIN uses Winsorized binning and you must specify the WINSORRATE option with a value from 0.0 to 0.5 exclusive for *number*. If you specify PSEUDO_QUANTILE, then PROC HPBIN generates a result which approximates the quantile binning. You can specify only one option. The default is BUCKET.

COMPUTEQUANTILE

specifies the quantile result to be computed. If you specify COMPUTEQUANTILE, PROC HPBIN generates the estimated quantile table, which contains the following percentages: 0%, 1%, 5%, 10%, 25%, 50%, 75%, 90%, 95%, 99%, and 100%.

COMPUTESTATS

specifies the statistic result to be computed. If you specify COMPUTESTATS, basic statistical information is computed and ODS output can be provided. The output table contains the minimum, maximum, mean, std (standard deviation), pseudo-median, and so on.

DATA=*SAS-data-set*

specifies the input SAS data set or database table to be used by PROC HPBIN.

If the procedure executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. In this case, PROC HPBIN reads the data alongside the distributed database.

For SMP mode, the input is a SAS data set.

NOPRINT
suppresses the generation of ODS outputs.

NUMBIN=*integer*
specifies the number of binning levels. The value of *integer* can be any integer between 2 and 1,000, inclusive. The default number of binning levels is 16, which is used in SAS Enterprise Miner.

The resulting number of binning levels might be less than *integer* if the sample size is small or if the data are not normalized. In this case, PROC HPBIN provides a warning message.

OUTPUT=*SAS-data-set*
creates an output SAS data set in SMP mode or database table that is saved alongside the distributed database in MPP mode.

By default, the output data set or table contains both the original table and additional binning variables.

REPLACE
replaces the variables that appear in the original table by the binning variables. If an ID statement is specified, the REPLACE option is ignored, and the output contains only the IDs and the binning variables.

CODE Statement

CODE FILE=*filename* **;**

The CODE statement is optional in PROC HPBIN. If you use a CODE statement, score code is generated and stored in a file that can be used for scoring purposes. Only one CODE statement is processed. If you specify multiple CODE statements, only the first one is used.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. The HPBIN procedure treats each observation as if it appeared *f* times, where *f* is the value of the *variable* for the observation. If *f* is not an integer, it is truncated to an integer. If *f* is less than 1 or missing, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

ID Statement

ID *id1 id2 . . . idn* **;**

The ID statement is optional in PROC HPBIN. If you specify an ID statement, the output contains only the IDs and the binning output variables, and the original variables from the input table are not included in the

output table. The ID statement is useful when you have a large amount of data in the database appliance. For example, in a Teradata database, each table has a primary index. The table partition is based on the primary index, which affects data access directly when parallel reading or writing is applied. If you specify an ID statement, PROC HPBIN generates the output table, which contains fewer columns. This means that the output table can be much smaller; in other words, the performance is better.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, communicates variable information about the distributed computing environment, and requests detailed performance results from the HPBIN procedure. With the PERFORMANCE statement, you can control whether the HPBIN procedure executes in symmetric multiprocessing mode or massively parallel mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

VAR Statement

VAR *var1 var2 . . . varn* **;**

The interval variables in the VAR statement are input as the binning variables. Unlike other procedures, PROC HPBIN requires the VAR statement. If the VAR statement is omitted, the procedure stops. The selected variables must be intervals. If classification variables are provided, the procedure stops with an error message.

Duplicate variables are not supported in PROC HPBIN. If the VAR statement contains a duplicate variable, the procedure stops with an error message.

Input variables are not allowed in the ID statement or as frequency variables.

Details: HPBIN Procedure

Computation and Formulas

For variable *x*, assume the data set is $\{x_i\}$, where $i = 1, 2, ..., n$. Let $min(x) = \min_{i \in \{1..n\}} \{x_i\}$, and let $max(x) = \max_{i \in \{1..n\}} \{x_i\}$. The range of the variable is $range(x) = max(x) - min(x)$.

The computation for the bucket, pseudo–quantile, and Winsor binning methods is as follows:

- For bucket binning, the length of the bucket is

$$L = \frac{max(x) - min(x)}{n}$$

and the split points are

$$s_k = min(x) + L * k$$

where $k = 1, 2, ..., numbin - 1$.

When the data are evenly distributed on the SAS appliance, the time complexity for bucket binning is $\mathcal{O}(n)/(nodes * cpus)$ where n is the number of observations, $nodes$ is the number of computer nodes on the appliance, and $cpus$ is the number of CPUs on each node.

- For pseudo–quantile binning and Winsorized binning, the sorting algorithm is more complex. For variable x, a simple bucket sorting method is used to obtain the basic information. Let $N = 10,000$ be the number of buckets, ranging from $min(x)$ to $max(x)$. For each bucket B_i, $i = 1, 2, ..., N$, PROC HPBIN keeps following information:
  - c_i: count of x in B_i
  - min_i: minimum value of x in B_i
  - max_i: maximum value of x in B_i
  - sum_i: sum of x in B_i
  - $sum2_i$: sum of x^2 in B_i

  To calculate the quantile table, let $P = \{0.00, 0.01, 0.05, 0.10, 0.25, 0.50, 0.75, 0.90, 0.95, 0.99, 1.00\}$. For each $p_k \in P$, $k = 1, 2, ..., 11$, find the smallest I_k, such that $\sum_{i=1}^{I_k} c_i >= p_k * n$. Therefore, the quantile value Q_k is obtained,

$$Q_k = \begin{cases} min_{I_k} & \text{if } \sum_{i=1}^{I_k} c_i > p_k * n \\ max_{I_k} & \text{if } \sum_{i=1}^{I_k} c_i = p_k * n \end{cases}$$

  where $k = 1, 2, ..., 11$.

  For pseudo–quantile binning, the split points are calculated. Let the base count $bc = ceil(\frac{n}{numbin})$. Find those integers $\{I_k | k = 1, 2, ...\}$ such that $\sum_{i=1}^{I_k} c_i >= \sum_{i=1}^{I_{k-1}} c_i + bc$ or $\sum_{i=1}^{I_k} c_i >= \frac{n}{numbin} * k$, where k is the kth split. The split value is

$$s_k = min(x) + \frac{max(x) - min(x)}{N} * I_k$$

  where $k = 1, 2, ...,$ and $k < numbin$.

  The time complexity for pseudo–quantile binning is $C\mathcal{O}(n)/(nodes * cpus)$, where C is a constant that depends on the number of sorting bucket N, n is the number of observations, $nodes$ is the number of computer nodes on the appliance, and $cpus$ is the number of CPUs on each node.

- For Winsorized binning, the Winsor statistics are computed first. After the Winsor minimum and Winsor maximum have been found, the split points are calculated the same way as in bucket binning.

  Let the Winsor tail count $wc = ceil(WinsorRate * n)$ and find the smallest I, such that $\sum_{i=1}^{I} c_i >= wc$. Then the left Winsor tail count is $lwc = \sum_{i=1}^{I} c_i$. Find the next I_l, such that $\sum_{i=1}^{I_l} c_i > lwc$. Therefore the Winsor minimum value is $WinsorMin = min_{I_l}$. Similarly, find the largest I, such that $\sum_{i=I}^{N} c_i >= wc$. The right Winsor tail count is $rwc = \sum_{i=I}^{N} c_i$. Find the next

I_r, such that $\sum_{i=I_r}^{N} c_i > rwc$. Then the Winsor maximum value is $WinsorMax = max_{I_r}$. The Winsor mean is calculated with the formula

$$WinsorMean = \frac{lwc * WinsorMin + \sum_{i=I_l}^{I_r} sum_i + rwc * WinsorMax}{n}$$

and the trimmed mean is calculated with the formula

$$trimmedMean = \frac{\sum_{i=I_l}^{I_r} sum_i}{n - lwc - rwc}$$

Data Output

The strength of HPBIN procedure is its ability to write an output table back to the database. If the input data are from the appliances and the process is alongside the database, PROC HPBIN writes the output table back to each appliance in parallel. For SMP mode, the output table is a SAS data set. In this case, you can still take advantage of multithreading, which does parallel computation on a single node.

If you do not specify the OUTPUT option in PROC HPBIN statement, the write-back process is skipped. This is useful when only the basic statistical tables are computed.

By default, the output table consists of both new binned variables and the original table. If you specify the REPLACE option, PROC HPBIN replaces the original variables with binned variables. If you specify an ID statement, the output table contains only the IDs and the binning variables. In this case, the output speed is even faster.

NOTE: If an input variable value is missing, then the binning output level value is 0.

ODS Tables

Each table that the HPBIN procedure creates has a name associated with it. You must use this name to refer to the table in ODS statements. These table names are listed in Table 7.2.

Table 7.2 ODS Tables Produced by PROC HPBIN

Table Name	Description	Statement Option
HISTOGRAMTABLE	Frequency of the data mapping result	BUCKET | WINSOR | PSEUDO_QUANTILE
HPBININFO	Basic binning information and parameters	none
MAPPINGTABLE	Level mapping table	BUCKET | WINSOR | PSEUDO_QUANTILE
MEANTABLE	Basic statistics for the given variables	COMPUTESTATS
PERFORMANCEINFO	Information about high-performance computing environment	none

Table 7.2 *continued*

Table Name	Description	Statement Option
QUANTILETABLE	Estimated quantile table	COMPUTEQUANTILE
WINSORTABLE	Winsor statistical information	WINSOR, WINSORRATE
TRIMTABLE	Trimmed statistical information	WINSOR, WINSORRATE

The following list provides more information about these tables:

HISTOGRAMTABLE This table contains the variable name, binned variable name, binning level, frequency, and mapping range.

HPBININFO The "HPBIN Information" table displays some procedure parameters and data information, which includes the binning method, user-specified bins, number of variables, and total number of observations.

MAPPINGTABLE By default, PROC HPBIN generates a "HPBIN Mapping" table in its ODS output. This table provides the level mapping for the input variables. The level starts at 1 and increases to the value that you specify in the NUMBIN= option in the PROC HPBIN statement. In the mapping table, a missing value for the lower bound indicates negative infinity, and a missing value for the upper bound indicates positive infinity.

The final bin level can be less than the NUMBIN value if the input data are small or the binning variable is discrete. In this case, a warning message is printed in the log.

In addition to the level mapping table, PROC HPBIN also produces the "HPBIN Histogram" table. This table contains the true frequencies of the mapping result for each mapping range.

MEANTABLE PROC HPBIN generates the "Variable Statistic" table if you specify the COMPUTESTATS option. This table contains variable (the variable name), nobs (the number of observations), n (the number of nonmissing observations), nmiss (the number of missing observations), mean, pmedian (the pseudo median), std (the standard deviation), min, and max.

PERFORMANCEINFO By default, the HPBIN procedure produces the "Performance Information" table, which displays information about the grid host for distributed execution and indicates whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The table also displays the numbers of computing nodes and threads.

QUANTILETABLE PROC HPBIN generates the "Estimated Quantile Statistic" table if you specify the COMPUTEQUANTILE option. This table contains the following quantiles 0%, 1%, 5%, 10%, 15%, 25%, 50%, 75%, 90%, 95%, 99%, and 100% for each variable.

WINSORTABLE PROC HPBIN generates the "Winsor Statistics" table if you specify the WINSOR option. The Winsor table contains Winsor Min, Winsor Max, Winsor Mean, STD Error Mean, Left Winsor Tail, Left Winsor Tail Percentage, Right Winsor Tail, Right Winsor Tail Percentage, and DF.

TRIMTABLE PRODC HPBIN also generates the "Trim Statistics" table if you specify the WINSOR option. This table contains Trimmed Min, Trimmed Max, Trimmed Mean, Trimmed STD Error Mean, Trimmed Left Tail, Trimmed Left Tail Percentage, Trimmed Right Tail, Trimmed Right Tail Percentage, and DF.

Examples

Example 7.1: Bucket Binning in SMP Mode

This example shows how you can use PROC HPBIN in the SMP mode.

The following DATA step creates the SAS data set as the input for the example:

```
data ex12;
    length id 8;
    do id=1 to 1000;
        x1 = ranuni(101);
        x2 = 10*ranuni(201);
        x3 = 100*ranuni(301);
        output;
    end;
run;
```

The following statements show the basic usage:

```
proc HPBIN data=ex12 output=out numbin=10 bucket;
    var x1-x3;
run;
```

PROC HPBIN generates several ODS tables, which are shown in Output 7.1.1 through Output 7.1.3.

Output 7.1.1 PROC HPBIN Information Display

HPBIN Information

Description	Value
Method	Bucket Binning
Number of Bins	10
Number of Variables	3
Observations	1000

Output 7.1.2 PROC HPBIN Mapping Table

HPBIN Mapping Table

NAME	BIN_NAME	LB	UB	EM_BIN_LABEL	BIN
x1	BIN_x1	.	0.099925	x1 < 0.099925	1
x1	BIN_x1	0.099925	0.199399	0.099925 <= x1 < 0.199399	2
x1	BIN_x1	0.199399	0.298872	0.199399 <= x1 < 0.298872	3
x1	BIN_x1	0.298872	0.398345	0.298872 <= x1 < 0.398345	4
x1	BIN_x1	0.398345	0.497818	0.398345 <= x1 < 0.497818	5
x1	BIN_x1	0.497818	0.597291	0.497818 <= x1 < 0.597291	6
x1	BIN_x1	0.597291	0.696764	0.597291 <= x1 < 0.696764	7
x1	BIN_x1	0.696764	0.796237	0.696764 <= x1 < 0.796237	8
x1	BIN_x1	0.796237	0.895711	0.796237 <= x1 < 0.895711	9
x1	BIN_x1	0.895711	.	0.895711 <= x1	10
x2	BIN_x2	.	1.021539	x2 < 1.021539	1
x2	BIN_x2	1.021539	2.015407	1.021539 <= x2 < 2.015407	2
x2	BIN_x2	2.015407	3.009275	2.015407 <= x2 < 3.009275	3
x2	BIN_x2	3.009275	4.003143	3.009275 <= x2 < 4.003143	4
x2	BIN_x2	4.003143	4.997011	4.003143 <= x2 < 4.997011	5
x2	BIN_x2	4.997011	5.990878	4.997011 <= x2 < 5.990878	6
x2	BIN_x2	5.990878	6.984746	5.990878 <= x2 < 6.984746	7
x2	BIN_x2	6.984746	7.978614	6.984746 <= x2 < 7.978614	8
x2	BIN_x2	7.978614	8.972482	7.978614 <= x2 < 8.972482	9
x2	BIN_x2	8.972482	.	8.972482 <= x2	10
x3	BIN_x3	.	10.173597	x3 < 10.173597	1
x3	BIN_x3	10.173597	20.142996	10.173597 <= x3 < 20.142996	2
x3	BIN_x3	20.142996	30.112396	20.142996 <= x3 < 30.112396	3
x3	BIN_x3	30.112396	40.081796	30.112396 <= x3 < 40.081796	4
x3	BIN_x3	40.081796	50.051196	40.081796 <= x3 < 50.051196	5
x3	BIN_x3	50.051196	60.020596	50.051196 <= x3 < 60.020596	6
x3	BIN_x3	60.020596	69.989995	60.020596 <= x3 < 69.989995	7
x3	BIN_x3	69.989995	79.959395	69.989995 <= x3 < 79.959395	8
x3	BIN_x3	79.959395	89.928795	79.959395 <= x3 < 89.928795	9
x3	BIN_x3	89.928795	.	89.928795 <= x3	10

Output 7.1.3 PROC HPBIN Histogram

HPBIN Histogram

NAME	BIN_NAME	BIN	FREQUENCY	RANGE
x1	BIN_x1	0	0	MISSING
x1	BIN_x1	1	108	x1 < 0.099925
x1	BIN_x1	2	94	0.099925 <= x1 < 0.199399
x1	BIN_x1	3	90	0.199399 <= x1 < 0.298872
x1	BIN_x1	4	95	0.298872 <= x1 < 0.398345
x1	BIN_x1	5	90	0.398345 <= x1 < 0.497818
x1	BIN_x1	6	115	0.497818 <= x1 < 0.597291
x1	BIN_x1	7	116	0.597291 <= x1 < 0.696764
x1	BIN_x1	8	105	0.696764 <= x1 < 0.796237
x1	BIN_x1	9	106	0.796237 <= x1 < 0.895711
x1	BIN_x1	10	81	0.895711 <= x1
x2	BIN_x2	0	0	MISSING
x2	BIN_x2	1	99	x2 < 1.021539
x2	BIN_x2	2	110	1.021539 <= x2 < 2.015407
x2	BIN_x2	3	99	2.015407 <= x2 < 3.009275
x2	BIN_x2	4	85	3.009275 <= x2 < 4.003143
x2	BIN_x2	5	109	4.003143 <= x2 < 4.997011
x2	BIN_x2	6	98	4.997011 <= x2 < 5.990878
x2	BIN_x2	7	100	5.990878 <= x2 < 6.984746
x2	BIN_x2	8	94	6.984746 <= x2 < 7.978614
x2	BIN_x2	9	112	7.978614 <= x2 < 8.972482
x2	BIN_x2	10	94	8.972482 <= x2
x3	BIN_x3	0	0	MISSING
x3	BIN_x3	1	97	x3 < 10.173597
x3	BIN_x3	2	97	10.173597 <= x3 < 20.142996
x3	BIN_x3	3	106	20.142996 <= x3 < 30.112396
x3	BIN_x3	4	94	30.112396 <= x3 < 40.081796
x3	BIN_x3	5	102	40.081796 <= x3 < 50.051196
x3	BIN_x3	6	99	50.051196 <= x3 < 60.020596
x3	BIN_x3	7	107	60.020596 <= x3 < 69.989995
x3	BIN_x3	8	92	69.989995 <= x3 < 79.959395
x3	BIN_x3	9	91	79.959395 <= x3 < 89.928795
x3	BIN_x3	10	115	89.928795 <= x3

In this example, PROC HPBIN also generates the output table. The first 10 observations of the table are shown in Output 7.1.4.

Output 7.1.4 First 10 Observations in the Output Table

			Binning			
id	x1	x2	x3	bin_x1	bin_x2	bin_x3
1	0.68122	9.78960	38.2255	7	10	4
2	0.19926	0.81860	89.7012	2	1	9
3	0.84090	7.00864	2.9197	9	8	1
4	0.72322	7.51176	91.0923	8	8	10
5	0.19283	7.85642	65.9410	2	8	7
6	0.01659	5.33791	68.2893	1	6	7
7	0.65325	8.77259	51.1892	7	9	6
8	0.68915	4.13965	0.9787	7	5	1
9	0.05472	3.43685	8.6936	1	4	1
10	0.62683	8.40734	7.8350	7	9	1

Example 7.2: Pseudo–Quantile Binning on the Grid

This example shows pseudo–quantile binning executed in the grid environment. The following DATA step generates 1,000,000 observations:

```
data ex12;
    length id 8;
    do id=1 to 1000000;
        x1 = ranuni(101);
        x2 = 10*ranuni(201);
        output;
    end;
run;
```

To run this program in the grid environment, you need to specify two macros for the options GRIDHOST and GRIDINSTALLLOC:

```
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";

ods output hpbininfo=bininfo;
ods output performanceinfo=perfTable;
ods output mappingTable=mapTable;
ods output histogramTable=histogramTable;
ods output meanTable=meanTable;
ods output quantiletable=quantiletable;
ods listing close;
proc hpbin data=ex12 output=out numbin=10 pseudo_quantile
          computestats computequantile;
    var x1-x2;
    performance nodes=100 nthreads=8 details;
run;
ods listing;
```

The "Performance Information" table in Output 7.2.1 shows the grid setting.

Output 7.2.1 PROC HPBIN Performance Information

Performance Information

Descr	Value
Host Node	<HOST NODE>
Execution Mode	Distributed
Number of Compute Nodes	100
Number of Threads per Node	8

The "HPBIN Information" table in Output 7.2.2 shows the binning method, number of bins, and so on.

Output 7.2.2 PROC HPBIN Binning Information

HPBIN Information

Descr	Value
Method	Pseudo-Quantile Binning
Number of Bins	10
Number of Variables	2
Observations	1000000

The "HPBIN Level Mapping" table in Output 7.2.3 shows the level mapping of the input variables.

Output 7.2.3 PROC HPBIN Level Mapping

HPBIN Level Mapping

NAME	BIN_NAME	LB	UB	EM_BIN_LABEL	BIN
x1	bin_x1	.	0.099802	x1 < 0.099802	1
x1	bin_x1	0.099802	0.199402	0.099802 <= x1 < 0.199402	2
x1	bin_x1	0.199402	0.299001	0.199402 <= x1 < 0.299001	3
x1	bin_x1	0.299001	0.398901	0.299001 <= x1 < 0.398901	4
x1	bin_x1	0.398901	0.499901	0.398901 <= x1 < 0.499901	5
x1	bin_x1	0.499901	0.599801	0.499901 <= x1 < 0.599801	6
x1	bin_x1	0.599801	0.699700	0.599801 <= x1 < 0.699700	7
x1	bin_x1	0.699700	0.800300	0.699700 <= x1 < 0.800300	8
x1	bin_x1	0.800300	0.900300	0.800300 <= x1 < 0.900300	9
x1	bin_x1	0.900300	.	0.900300 <= x1	10
x2	bin_x2	.	0.997027	x2 < 0.997027	1
x2	bin_x2	0.997027	1.992023	0.997027 <= x2 < 1.992023	2
x2	bin_x2	1.992023	2.986018	1.992023 <= x2 < 2.986018	3
x2	bin_x2	2.986018	3.989014	2.986018 <= x2 < 3.989014	4
x2	bin_x2	3.989014	4.990009	3.989014 <= x2 < 4.990009	5
x2	bin_x2	4.990009	5.990005	4.990009 <= x2 < 5.990005	6
x2	bin_x2	5.990005	6.991000	5.990005 <= x2 < 6.991000	7
x2	bin_x2	6.991000	7.993996	6.991000 <= x2 < 7.993996	8
x2	bin_x2	7.993996	8.995992	7.993996 <= x2 < 8.995992	9
x2	bin_x2	8.995992	.	8.995992 <= x2	10

The "HPBIN Histogram" table in Output 7.2.4 provides the frequency information from the result table.

Output 7.2.4 PROC HPBIN Histogram Table

HPBIN Histogram

NAME	BIN_NAME	BIN	FREQUENCY	RANGE
x1	bin_x1	0	0	MISSING
x1	bin_x1	1	100091	x1 < 0.099802
x1	bin_x1	2	99941	0.099802 <= x1 < 0.199402
x1	bin_x1	3	100016	0.199402 <= x1 < 0.299001
x1	bin_x1	4	99982	0.299001 <= x1 < 0.398901
x1	bin_x1	5	99977	0.398901 <= x1 < 0.499901
x1	bin_x1	6	100004	0.499901 <= x1 < 0.599801
x1	bin_x1	7	100033	0.599801 <= x1 < 0.699700
x1	bin_x1	8	100018	0.699700 <= x1 < 0.800300
x1	bin_x1	9	100002	0.800300 <= x1 < 0.900300
x1	bin_x1	10	99936	0.900300 <= x1
x2	bin_x2	0	0	MISSING
x2	bin_x2	1	100018	x2 < 0.997027
x2	bin_x2	2	100011	0.997027 <= x2 < 1.992023
x2	bin_x2	3	99984	1.992023 <= x2 < 2.986018
x2	bin_x2	4	100043	2.986018 <= x2 < 3.989014
x2	bin_x2	5	100021	3.989014 <= x2 < 4.990009
x2	bin_x2	6	100007	4.990009 <= x2 < 5.990005
x2	bin_x2	7	99997	5.990005 <= x2 < 6.991000
x2	bin_x2	8	99967	6.991000 <= x2 < 7.993996
x2	bin_x2	9	99965	7.993996 <= x2 < 8.995992
x2	bin_x2	10	99987	8.995992 <= x2

The "Variable Statistic" table in Output 7.2.5 displays the basic statistical information, including nobs, n, nmiss, mean, pseudo-median, and so on.

Output 7.2.5 PROC HPBIN Variable Statistic Table

Variable Statistic

variable	nobs	n	nmiss	mean	pmedian	std	min	max
x1	1000000	1000000	0	0.499650	0.499801	0.288916	0.000002	0.999999
x2	1000000	1000000	0	4.992828	4.989022	2.887087	0.000031	9.999987

The "Estimated Quantile Statistic" table in Output 7.2.6 shows the quantile estimation of the given variables. The ODS table is generated only when the option COMPUTESTATS is specified in the PROC HPBIN statement.

Output 7.2.6 PROC HPBIN Quantile Estimation

Estimated Quantile Statistic

Variable	Quantile		Estimate
x1	100%	Max	0.999999
x1	99%		0.990100
x1	95%		0.950000
x1	90%		0.900200
x1	75%	Q3	0.749800
x1	50%	Median	0.499801
x1	25%	Q1	0.249004
x1	10%		0.099707
x1	5%		0.049803
x1	1%		0.009904
x1	0%	Min	0.000002
x2	100%	Max	9.999987
x2	99%		9.901007
x2	95%		9.497990
x2	90%		8.994992
x2	75%	Q3	7.492020
x2	50%	Median	4.989022
x2	25%	Q1	2.489032
x2	10%		0.996043
x2	5%		0.499041
x2	1%		0.099043
x2	0%	Min	0.000031

Example 7.3: Winsorized Binning

For Winsorized binning, PROC HPBIN provides both the bucket binning and the basic Winsor statistical information for the input data. The following statements include both the WINSOR and WINSORRATE=0.05 options and generate both WINSORTABLE and TRIMTABLE ODS tables.

```
data ex12;
    length id 8;
    do id=1 to 10000;
        x1 = ranuni(101);
        x2 = 10*ranuni(201);
        x3 = 100*ranuni(301);
        output;
    end;
run;

ods output WINSORTABLE=winsorTable;
ods output TRIMTABLE=trimTable;
ods listing close;
proc hpbin data=ex12 NUMBIN=10 WINSOR WINSORRATE=0.05;
    var x1-x2;
run;
ods listing;
```

The preceding statements generate Output 7.3.1 and Output 7.3.2.

Output 7.3.1 PROC HPBIN Winsor Statistics

Winsor Statistics

Variable	WinsorMin	WinsorMax	WinsorMean	Winsor STDErr	WinsorLeft Tail
x1	0.047580	0.949006	0.501757	0.003164	500
x2	0.495634	9.524295	5.030255	0.031850	500

Winsor LTPercent	WinsorRight Tail	Winsor RTPercent	DF
5.00	501	5.01	8998
5.00	501	5.01	8998

Output 7.3.2 PROC HPBIN Trim Statistics

Trim Statistics

Variable	trimMin	trimMax	trimMean	trimSTDErr	trimLeftTail
x1	0.047580	0.949006	0.502093	0.003164	500
x2	0.495634	9.524295	5.032010	0.031850	500

trim LTPercent	trimRight Tail	trim RTPercent	DF
5.00	501	5.01	8998
5.00	501	5.01	8998

Example 7.4: Bucket Binning on the Teradata Appliance

This example shows the output when the ID statement in PROC HPBIN is used. Assume that the data are stored in the Teradata database and alongside-the-database MPP mode is used.

You can generate the database table *TDLib.ex12demo* by using the following statements. ID is the primary index of the database table. Several SAS macros are needed to successfully execute the code.

```
libname TDLib teradata
         server   = &GRIDDATASERVER
         user     = &DATABASEUSER
         password = &DATABASEPASSWORD
         database = hps;
run;

data ex12;
    length id 8;
    do id = 1 to 10000;
        x1 = ranuni(101);
        x2 = 10*ranuni(201);
        x3 = 100*ranuni(301);
        output;
    end;
run;

data TDLib.ex12demo;
    set ex12;
run;

option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC = "&GRIDINSTALLLOC";
option set=GRIDDATASERVER = "&GRIDDATASERVER";

proc hpbin data=TDLib.ex12demo output=TDLib.ex12out numbin=5 BUCKET;
    var x1-x3;
```

```
    id id;
    performance details;
run;

proc print data=TDLib.ex12out(obs=10);
title "HPBin output table";
run;
```

The database and SAS appliance information is shown in Output 7.4.1.

Output 7.4.1 PROC HPBIN Performance Information

Performance Information

Host Node	<HOST NODE>
Data Server	<DATABASE SERVER>
Execution Mode	Distributed, alongside Teradata
Number of Compute Nodes	24
Number of Threads per Node	24

Ten random observations of the output table are printed, including the ID and binned variables.

Output 7.4.2 PROC HPBIN Output

Binning

id	bin_x1	bin_x2	bin_x3
176	2	1	5
1242	4	5	5
6659	2	4	4
7511	4	5	2
7017	4	5	2
325	5	2	3
1922	5	3	5
3244	4	2	1
2962	3	3	5
1036	5	1	4

Chapter 8
The HPCORR Procedure

Contents

Overview: HPCORR Procedure **123**
PROC HPCORR Features 124
Getting Started: HPCORR Procedure **124**
Syntax: HPCORR Procedure **126**
PROC HPCORR Statement 127
FREQ Statement 129
PERFORMANCE Statement 129
VAR Statement 129
WEIGHT Statement 130
Details: HPCORR Procedure **130**
Pearson Product-Moment Correlation 130
Multithreading 131
Output Tables 132
Output Data Sets 132
ODS Table Names 133
Examples: HPCORR Procedure **134**
Example 8.1: Computing the Pearson Measure of Association in Client Mode 134
Example 8.2: Computing the Pearson Measure of Association in Distributed Mode . . 135
References **137**

Overview: HPCORR Procedure

The HPCORR procedure computes Pearson correlation coefficients and the probabilities associated with these statistics. The Pearson product-moment correlation is a parametric measure of a linear relationship between two variables.

A related type of correlation, polychoric correlation, measures the correlation between two unobserved variables that have a bivariate normal distribution. Information about these variables is obtained through two corresponding observed ordinal variables that are derived from the unobserved variables by classifying their values into finite sets of discrete, ordered values. Polychoric correlation is not available in the HPCORR procedure, but it is available in the FREQ procedure.

When only one set of analysis variables is specified, the default correlation analysis includes descriptive statistics for each analysis variable and pairwise Pearson correlation statistics for these variables.

When two sets of analysis variables are specified, the default correlation analysis includes descriptive statistics for each analysis variable and pairwise Pearson correlation statistics between the two sets of variables.

When the relationship between two variables is nonlinear or when outliers are present, the correlation coefficient might incorrectly estimate the strength of the relationship.

You can save the correlation statistics in a SAS data set for use with other statistical and reporting procedures.

PROC HPCORR Features

The HPCORR procedure is a high-performance procedure that offers the following functionality:

- It can perform analysis on a massively parallel SAS high-performance appliance.
- It reads input data in parallel and writes output data in parallel when the data source is the appliance database.
- It is highly multithreaded during all phases of analytic execution.

Getting Started: HPCORR Procedure

This example creates a simple data set and then uses PROC HPCORR to produce simple Pearson correlations by executing on the client machine.

The following statements create the data set Fitness, which has been altered to contain some missing values:

```
*----------------- Data on Physical Fitness -----------------*
| These measurements were made on men involved in a physical |
| fitness course at N.C. State University.                   |
| The variables are Age (years), Weight (kg),                |
| Runtime (time to run 1.5 miles in minutes), and            |
| Oxygen (oxygen intake, ml per kg body weight per minute)   |
| Certain values were changed to missing for the analysis.   |
*------------------------------------------------------------*;
data Fitness;
   input Age Weight Oxygen RunTime @@;
   datalines;
44 89.47 44.609 11.37    40 75.07 45.313 10.07
44 85.84 54.297  8.65    42 68.15 59.571  8.17
38 89.02 49.874   .      47 77.45 44.811 11.63
40 75.98 45.681 11.95    43 81.19 49.091 10.85
44 81.42 39.442 13.08    38 81.87 60.055  8.63
44 73.03 50.541 10.13    45 87.66 37.388 14.03
45 66.45 44.754 11.12    47 79.15 47.273 10.60
54 83.12 51.855 10.33    49 81.42 49.156  8.95
51 69.63 40.836 10.95    51 77.91 46.672 10.00
48 91.63 46.774 10.25    49 73.37   .    10.08
```

```
57 73.37 39.407 12.63    54 79.38 46.080 11.17
52 76.32 45.441  9.63    50 70.87 54.625  8.92
51 67.25 45.118 11.08    54 91.63 39.203 12.88
51 73.71 45.790 10.47    57 59.08 50.545  9.93
49 76.32   .       .     48 61.24 47.920 11.50
52 82.78 47.467 10.50
;
```

The following statements invoke the HPCORR procedure and request a correlation analysis:

```
proc hpcorr data=Fitness;
run;
```

The "Performance Information" table in Figure 8.1 shows that the procedure executes in client mode—that is, the data reside and the computation executes on the machine where the SAS session executes. This run of the HPCORR procedure was performed on a multicore machine; one computational thread was spawned for each core.

The "Simple Statistics" table in Figure 8.1 displays univariate statistics for the analysis variables.

Figure 8.1 Performance Information and Univariate Statistics

The HPCORR Procedure

Performance Information

Execution Mode	On client
Number of Threads	2

4 Variables: Age Weight Oxygen RunTime

Simple Statistics

Variable	N	Mean	Std Dev	Sum	Minimum	Maximum
Age	31	47.67742	5.21144	1478	38.00000	57.00000
Weight	31	77.44452	8.32857	2401	59.08000	91.63000
Oxygen	29	47.22721	5.47718	1370	37.38800	60.05500
RunTime	29	10.67414	1.39194	309.55000	8.17000	14.03000

By default, all numeric variables not listed in other statements are used in the analysis. Observations that have nonmissing values for each variable are used to derive the univariate statistics for that variable.

The "Pearson Correlation Coefficients" table in Figure 8.2 displays the Pearson correlation, the p-value under the null hypothesis of zero correlation, and the number of nonmissing observations for each pair of variables.

Figure 8.2 Pearson Correlation Coefficients

Pearson Correlation Coefficients
Prob > |r| under H0: Rho=0
Number of Observations

	Age	Weight	Oxygen	RunTime
Age	1.00000	−0.23354	−0.31474	0.14478
		0.2061	0.0963	0.4536
	31	31	29	29
Weight	−0.23354	1.00000	−0.15358	0.20072
	0.2061		0.4264	0.2965
	31	31	29	29
Oxygen	−0.31474	−0.15358	1.00000	−0.86843
	0.0963	0.4264		<.0001
	29	29	29	28
RunTime	0.14478	0.20072	−0.86843	1.00000
	0.4536	0.2965	<.0001	
	29	29	28	29

By default, Pearson correlation statistics are computed from observations that have nonmissing values for each pair of analysis variables. Figure 8.2 displays a correlation of −0.86843 between Runtime and Oxygen, which is significant with a p-value less than 0.0001. That is, an inverse linear relationship exists between these two variables. As Runtime (time in minutes to run 1.5 miles) increases, Oxygen (oxygen intake in milliliters per kilogram body weight per minute) decreases.

Syntax: HPCORR Procedure

The following statements are available in PROC HPCORR:

PROC HPCORR < *options* > **;**
FREQ *variable* **;**
PERFORMANCE *performance-options* **;**
VAR *variables* **;**
WEIGHT *variable* **;**

The FREQ statement specifies the variable that represents the frequency of occurrence for other values in the observation. The VAR statement lists the numeric variables to be analyzed and their order in the correlation matrix. If you omit the VAR statement, all numeric variables not listed in other statements are used. The WEIGHT statement identifies the variable whose values weight each observation to compute Pearson product-moment correlation.

The PROC HPCORR statement is the only required statement for the HPCORR procedure.

The rest of this section provides detailed syntax information for each of these statements, beginning with the PROC HPCORR statement. The remaining statements are presented in alphabetical order.

PROC HPCORR Statement

PROC HPCORR < *options* > **;**

Table 8.1 summarizes the *options* available in the PROC HPCORR statement.

Table 8.1 Summary of PROC HPCORR Options

Option	Description
Data Sets	
DATA=	Specifies the input data set
OUTP=	Specifies the output data set with Pearson correlation statistics
Statistical Analysis	
EXCLNPWGT	Excludes from the analysis observations that have nonpositive weight values
NOMISS	Excludes from the analysis observations that have missing analysis values
Pearson Correlation Statistics	
COV	Computes covariances
CSSCP	Computes corrected sums of squares and crossproducts
SSCP	Computes sums of squares and crossproducts
Printed Output	
BEST=	Displays the specified number of ordered correlation coefficients
NOCORR	Suppresses Pearson correlations
NOPRINT	Suppresses all printed output
NOPROB	Suppresses *p*-values
NOSIMPLE	Suppresses descriptive statistics
RANK	Displays ordered correlation coefficients

You can specify the following *options* in the PROC HPCORR statement:

BEST=*n*

prints the *n* highest correlation coefficients for each variable. The value of *n* must be greater than or equal to 1. Correlations are ordered from highest to lowest in absolute value. If you do not specify this option, PROC HPCORR prints correlations in a rectangular table, using the variable names as row and column labels.

COV

displays the variance/covariance matrix. When you specify this option, the Pearson correlations are also displayed. If you specify the OUTP= option, the output data set also contains the covariance matrix with the corresponding _TYPE_ variable value `'COV'`.

CSSCP

displays a table of the corrected sums of squares and crossproducts. When you specify this option, the Pearson correlations are also displayed. If you specify the OUTP= option, the output data set also contains a CSSCP matrix with the corresponding _TYPE_ variable value `'CSSCP'`.

DATA=*SAS-data-set*
names the SAS data set to be analyzed by PROC HPCORR. If you do not specify this option, PROC HPCORR uses the most recently created SAS data set.

EXCLNPWGT
EXCLNPWGTS
excludes from the analysis observations that have nonpositive weight values. If you do not specify this option, PROC HPCORR treats observations with negative weights like those with zero weights and counts them in the total number of observations.

NOCORR
suppresses the display of the Pearson correlations. If you specify the OUTP= option, the data set _TYPE_ remains `'CORR'`. To change the data set type to COV, CSSCP, or SSCP, use the (TYPE=) data set option.

NOMISS
excludes from the analysis observations that have missing values. If you do not specify this option, PROC HPCORR computes correlation statistics by using all of the nonmissing pairs of variables. Using this option is computationally more efficient.

NOPRINT
suppresses all displayed output. Use this option if you only want to create an output data set.

NOPROB
suppresses the display of the probabilities that are associated with each correlation coefficient.

NOSIMPLE
suppresses the printing of simple descriptive statistics for each variable. However, if you request an output data set, the output data set still contains simple descriptive statistics for the variables.

OUTP=*output-data-set*
OUT=*output-data-set*
creates an output data set that contains Pearson correlation statistics. This data set also includes means, standard deviations, and the number of observations. The value of the _TYPE_ variable is `'CORR'`.

RANK
displays the ordered correlation coefficients for each variable. Correlations are ordered from highest to lowest in absolute value.

SSCP
displays a table of the sums of squares and crossproducts. When you specify this option, the Pearson correlations are also displayed. If you specify the OUTP= option, the output data set contains a SSCP matrix and the corresponding _TYPE_ variable value is `'SSCP'`.

VARDEF=DF | N | WDF | WEIGHT | WGT
specifies the variance divisor in the calculation of variances and covariances. The default is VARDEF=DF.

Table 8.2 shows the available values and associated divisors for the VARDEF= option, where n is the number of nonmissing observations and w_j is the weight associated with the jth nonmissing observation.

Table 8.2 Possible Values for the VARDEF= Option

Value	Description	Divisor
DF	Degrees of freedom	$n - 1$
N	Number of observations	n
WDF	Sum of weights minus one	$\sum_j^n w_j - 1$
WEIGHT | WGT	Sum of weights	$\sum_j^n w_j$

FREQ Statement

FREQ *variable* **;**

The FREQ statement specifies a numeric *variable* whose value represents the frequency of the observation. If you use the FREQ statement, PROC HPCORR assumes that each observation represents n observations, where n is the value of the FREQ *variable*. If n is not an integer, SAS truncates it. If n is less than 1 or is missing, the observation is excluded from the analysis. The sum of the frequency variables represents the total number of observations.

The effects of the FREQ and WEIGHT statements are similar except when the degrees of freedom are calculated.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement you can also control whether a SAS High-Performance Analytics procedure executes in SMP or MPP mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics.".

VAR Statement

VAR *variables* **;**

The VAR statement lists variables for which correlation coefficients are to be computed. If the VAR statement is not specified, PROC HPCORR computes correlations for all numeric variables that are not listed in other statements.

WEIGHT Statement

WEIGHT *variable* **;**

The WEIGHT statement lists weights to use in the calculation of Pearson weighted product-moment correlation.

Observations that have missing weights are excluded from the analysis. By default, for observations that have nonpositive weights, weights are set to 0 and the observations are included in the analysis. You can use the EXCLNPWGT option to exclude observations with negative or zero weights from the analysis.

Details: HPCORR Procedure

Pearson Product-Moment Correlation

The Pearson product-moment correlation is a parametric measure of association for two variables. It measures both the strength and the direction of a linear relationship. If one variable X is an exact linear function of another variable Y, a positive relationship exists if the correlation is 1, and a negative relationship exists if the correlation is -1. If there is no linear predictability between the two variables, the correlation is 0. If the two variables are normal with a correlation 0, the two variables are independent. Correlation does not imply causality because, in some cases, an underlying causal relationship might not exist.

The formula for the population Pearson product-moment correlation, denoted ρ_{xy}, is

$$\rho_{xy} = \frac{\mathrm{Cov}(x,y)}{\sqrt{\mathrm{V}(x)\mathrm{V}(y)}} = \frac{\mathrm{E}(\,(x-\mathrm{E}(x))(y-\mathrm{E}(y))\,)}{\sqrt{\mathrm{E}(x-\mathrm{E}(x))^2\,\mathrm{E}(y-\mathrm{E}(y))^2}}$$

The sample correlation, such as a Pearson product-moment correlation or weighted product-moment correlation, estimates the population correlation. The formula for the sample Pearson product-moment correlation is as follows, where $\bar{x}$ is the sample mean of x and $\bar{y}$ is the sample mean of y:

$$r_{xy} = \frac{\sum_i (\,(x_i-\bar{x})(y_i-\bar{y})\,)}{\sqrt{\sum_i (x_i-\bar{x})^2 \sum_i (y_i-\bar{y})^2}}$$

The formula for a weighted Pearson product-moment correlation is as follows, where w_i is the weight, $\bar{x}_w$ is the weighted mean of x, and $\bar{y}_w$ is the weighted mean of y:

$$r_{xy} = \frac{\sum_i w_i (x_i-\bar{x}_w)(y_i-\bar{y}_w)}{\sqrt{\sum_i w_i (x_i-\bar{x}_w)^2 \sum_i w_i (y_i-\bar{y}_w)^2}}$$

Probability Values

Probability values for the Pearson correlation are computed by treating the following equation as if it came from a t distribution with $(n-2)$ degrees of freedom, where r is the sample correlation:

$$t = (n-2)^{1/2}\left(\frac{r^2}{1-r^2}\right)^{1/2}$$

The partial variance-covariance matrix is calculated with the variance divisor (specified in the VARDEF= option). PROC HPCORR then uses the standard Pearson correlation formula on the partial variance-covariance matrix to calculate the Pearson partial correlation matrix.

When a correlation matrix is positive definite, the resulting partial correlation between variables x and y after adjusting for a single variable z is identical to that obtained from the following first-order partial correlation formula, where r_{xy}, r_{xz}, and r_{yz} are the appropriate correlations:

$$r_{xy.z} = \frac{r_{xy} - r_{xz}r_{yz}}{\sqrt{(1 - r_{xz}^2)(1 - r_{yz}^2)}}$$

The formula for higher-order partial correlations is a straightforward extension of the preceding first-order formula. For example, when the correlation matrix is positive definite, the partial correlation between x and y that controls for both z_1 and z_2 is identical to the following second-order partial correlation formula, where $r_{xy.z_1}$, $r_{xz_2.z_1}$, and $r_{yz_2.z_1}$ are first-order partial correlations among variables x, y, and z_2 given z_1:

$$r_{xy.z_1z_2} = \frac{r_{xy.z_1} - r_{xz_2.z_1}r_{yz_2.z_1}}{\sqrt{(1 - r_{xz_2.z_1}^2)(1 - r_{yz_2.z_1}^2)}}$$

Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPCORR procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statements, the HPCORR procedure schedules threads as if it executed on a system with four CPUs, regardless of the actual CPU count:

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This specification overrides the NOTHREADS system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement, which overrides the CPUCOUNT system option and instructs the HPCORR procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output. The HPCORR procedure allocates one thread per CPU.

The HPCORR procedure implements a data-parallel model. For example, if the input data set has 1,000 observations and you are running with four threads, then 250 observations are associated with each thread. All operations that require access to the data are then multithreaded.

Output Tables

By default, PROC HPCORR prints a report that includes descriptive statistics and correlation statistics for each variable. The descriptive statistics include the number of observations that have nonmissing values, the mean, the standard deviation, the minimum, and the maximum.

If a nonparametric measure of association is requested, the descriptive statistics include the median. Otherwise, the sample sum is included. If a Pearson partial correlation is requested, the descriptive statistics also include the partial variance and partial standard deviation.

If variable labels are available, PROC HPCORR labels the variables. If you specify the CSSCP, SSCP, or COV option, the appropriate sums of squares and crossproducts and covariance matrix appear at the top of the correlation report. If the data set contains missing values, PROC HPCORR prints additional statistics for each pair of variables. These statistics, calculated from the observations that have nonmissing row and column variable values, might include the following:

- SSCP('W','V'), uncorrected sums of squares and crossproducts
- USS('W'), uncorrected sums of squares for the row variable
- USS('V'), uncorrected sums of squares for the column variable
- CSSCP('W','V'), corrected sums of squares and crossproducts
- CSS('W'), corrected sums of squares for the row variable
- CSS('V'), corrected sums of squares for the column variable
- COV('W','V'), covariance
- VAR('W'), variance for the row variable
- VAR('V'), variance for the column variable
- DF('W','V'), divisor for calculating covariance and variances

For each pair of variables, PROC HPCORR prints the correlation coefficients, the number of observations that are used to calculate the coefficient, and the p-value.

Output Data Sets

PROC HPCORR creates an output data set that contains statistics for Pearson correlation. By default, the output data set is a special data set type (TYPE=CORR) that is recognized by many SAS/STAT procedures, including the REG and FACTOR procedures. When you specify the NOCORR option and the COV, CSSCP, or SSCP option, use the (TYPE=) data set option to change the data set type to COV, CSSCP, or SSCP.

The output data set includes the following variables:

- BY variables, which identify the BY group when a BY statement is used
- _TYPE_ variable, which identifies the type of observation
- _NAME_ variable, which identifies the variable that corresponds to a given row of the correlation matrix
- INTERCEPT variable, which identifies variable sums when the SSCP option is specified
- VAR variables, which identify the variables listed in the VAR statement

You can use a combination of the _TYPE_ and _NAME_ variables to identify the contents of an observation. The _NAME_ variable indicates which row of the correlation matrix the observation corresponds to. The values of the _TYPE_ variable are as follows:

- SSCP, uncorrected sums of squares and crossproducts
- CSSCP, corrected sums of squares and crossproducts
- COV, covariances
- MEAN, mean of each variable
- STD, standard deviation of each variable
- N, number of nonmissing observations for each variable
- SUMWGT, sum of the weights for each variable when using a WEIGHT statement
- HPCORR, correlation statistics for each variable

If you specify the SSCP option, the OUTP= data set includes an additional observation that contains intercept values.

ODS Table Names

PROC HPCORR assigns a name to each table it creates. These names are listed in Table 8.3. You must use these names to refer to tables when you use the Output Delivery System (ODS). For more information about ODS, see Chapter 20, "Using the Output Delivery System" (*SAS/STAT User's Guide*).

Table 8.3 ODS Tables Produced by PROC HPCORR

ODS Table Name	Description	Option
Cov	Covariances	COV
Csscp	Corrected sums of squares and crossproducts	CSSCP
PearsonCorr	Pearson correlations	
SimpleStats	Simple descriptive statistics	
Sscp	Sums of squares and crossproducts	SSCP
VarInformation	Variable information	
PerformanceInfo	Information about high-performance computing environment	

Examples: HPCORR Procedure

Example 8.1: Computing the Pearson Measure of Association in Client Mode

The Fitness data set created in the section "Getting Started: HPCORR Procedure" on page 124 contains measurements from a study of physical fitness of 31 participants. The following statements request the Pearson measure of association for the variables Weight, Oxygen, and Runtime:

```
title 'Measures of Association for a Physical Fitness Study';
proc hpcorr data=Fitness pearson;
   var Weight Oxygen RunTime;
run;
```

The "Simple Statistics" table in Output 8.1.1 displays univariate descriptive statistics for the analysis variables. By default, observations that have nonmissing values for each variable are used to derive the univariate statistics for that variable.

Output 8.1.1 Simple Statistics

Measures of Association for a Physical Fitness Study

The HPCORR Procedure

Performance Information

Execution Mode	On client
Number of Threads	2

3 Variables: Weight Oxygen RunTime

Simple Statistics

Variable	N	Mean	Std Dev	Sum	Minimum	Maximum
Weight	31	77.44452	8.32857	2401	59.08000	91.63000
Oxygen	29	47.22721	5.47718	1370	37.38800	60.05500
RunTime	29	10.67414	1.39194	309.55000	8.17000	14.03000

The "Pearson Correlation Coefficients" table in Output 8.1.2 displays the Pearson correlation statistics for pairs of analysis variables. The Pearson correlation is a parametric measure of association for two continuous random variables. When the data have missing values, the number of observations used to calculate the correlation can vary.

Output 8.1.2 Pearson Correlation Coefficients

Pearson Correlation Coefficients Prob > |r| under H0: Rho=0 Number of Observations			
	Weight	Oxygen	RunTime
Weight	1.00000	−0.15358	0.20072
		0.4264	0.2965
	31	29	29
Oxygen	−0.15358	1.00000	−0.86843
	0.4264		<.0001
	29	29	28
RunTime	0.20072	−0.86843	1.00000
	0.2965	<.0001	
	29	28	29

The table shows that the Pearson correlation between Runtime and Oxygen is −0.86843, which is significant with a p-value less than 0.0001. This indicates a strong negative linear relationship between these two variables. As Runtime increases, Oxygen decreases linearly.

Example 8.2: Computing the Pearson Measure of Association in Distributed Mode

The real power of HPCORR is when the computation is solved with multiple threads or in a distributed environment.

You can switch to running in MPP mode simply by specifying valid values for the NODES=, INSTALL=, and HOST= options in the PERFORMANCE statement.

An alternative to specifying the INSTALL= and HOST= options in the PERFORMANCE statement is to set appropriate values for the GRIDHOST and GRIDINSTALLLOC environment variables by using OPTIONS SET commands. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about setting these options or environment variables.

The following statements provide an example. To run these statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to macro variables with appropriate values.

The macro variable BRECLIB is the name of a libref to a billion-record database.

```
title 'HPCORR processing 1-Billion record database';
proc hpcorr data=&BRECLIB;
   var x1-x5;
   performance host=&GRIDHOST install=&GRIDINSTALLLOC;
run;
```

The execution mode in the "Performance Information" table shown in Output 8.2.1 indicates that the calculations were performed in a distributed environment that uses 16 nodes; the data are predistributed using a Greenplum parallel database.

Output 8.2.1 Performance Information in MPP

HPCORR processing 1-Billion record database

Performance Information

Host Node	<< your grid host >>
Install Location	<< your grid install location >>
Execution Mode	Distributed, alongside Greenplum
Number of Compute Nodes	16

Another indication of distributed (MPP) execution is the following message issued by all High-Performance Analytics procedures in the SAS log:

```
NOTE: The HPCORR procedure is executing in the distributed
      computing environment with 16 worker nodes.
```

Because the sample database uses random data, the results are not meaningful. The power of High-Performance Analytics is that this test can be completed in a matter of minutes instead of hours.

References

Anderson, T. W. (1984), *An Introduction to Multivariate Statistical Analysis,* Second Edition, New York: John Wiley & Sons.

Blum, J. R., Kiefer, J., and Rosenblatt, M. (1961), "Distribution Free Tests of Independence Based on the Sample Distribution Function," *Annals of Mathematical Statistics*, 32, 485–498.

Conover, W. J. (1998), *Practical Nonparametric Statistics*, Third Edition, New York: John Wiley & Sons.

Cox, N. R. (1974), "Estimation of the Correlation between a Continuous and a Discrete Variable," *Biometrics*, 30, 171–178.

Cronbach, L. J. (1951), "Coefficient Alpha and the Internal Structure of Tests," *Psychometrika*, 16, 297–334.

Drasgow, F. (1986), "Polychoric and Polyserial Correlations" in *Encyclopedia of Statistical Sciences*, vol. 7, ed. S. Kotz and N. L. Johnson, New York: John Wiley & Sons, 68–74.

Fisher, R. A. (1915), "Frequency Distribution of the Values of the Correlation Coefficient in Samples from an Indefinitely Large Population," *Biometrika*, 10, 507–521.

Fisher, R. A. (1921), "On the "Probable Error" of a Coefficient of Correlation Deduced from a Small Sample," *Metron*, 1, 3–32.

Fisher, R. A. (1936), "The Use of Multiple Measurements in Taxonomic Problems," *Annals of Eugenics*, 7, 179–188.

Fisher, R. A. (1970), *Statistical Methods for Research Workers,* Fourteenth Edition, Davien, CT: Hafner Publishing Company.

Hoeffding, W. (1948), "A Non-Parametric Test of Independence," *Annals of Mathematical Statistics*, 19, 546–557.

Hollander, M. and Wolfe, D. (1999), *Nonparametric Statistical Methods*, Second Edition, New York: John Wiley & Sons.

Keeping, E. S. (1962), *Introduction to Statistical Inference,* New York: D. Van Nostrand.

Knight, W. E. (1966), "A Computer Method for Calculating Kendall's Tau with Ungrouped Data," *Journal of the American Statistical Association*, 61, 436–439.

Moore, D. S. (2000), *Statistics: Concepts and Controversies*, Fifth Edition, New York: W. H. Freeman.

Mudholkar, G. S. (1983), "Fisher's z-Transformation," *Encyclopedia of Statistical Sciences*, 3, 130–135.

Noether, G. E. (1967), *Elements of Nonparametric Statistics*, New York: John Wiley & Sons.

Novick, M. R. (1967), "Coefficient Alpha and the Reliability of Composite Measurements," *Psychometrika*, 32, 1–13.

Nunnally, J. C. and Bernstein, I. H. (1994), *Psychometric Theory*, Third Edition, New York: McGraw-Hill.

Olsson, U., Drasgow, F., and Dorans, N. J. (1982), "The Polyserial Correlation Coefficient," *Biometrika*, 47, 337–347.

Ott, R. L. and Longnecker, M. T. (2000), *An Introduction to Statistical Methods and Data Analysis*, Fifth Edition, Belmont, CA: Wadsworth.

Spector, P. E. (1992), *Summated Rating Scale Construction: An Introduction*, Newbury Park, CA: Sage.

Yu, C. H. (2001) "An Introduction to Computing and Interpreting Cronbach Coefficient Alpha in SAS," Proceedings of the Twenty-Sixth Annual SAS Users Group International Conference, Cary, NC: SAS Institute, Inc., paper 246.

Chapter 9
The HPCOUNTREG Procedure

Contents

Overview: HPCOUNTREG Procedure **140**
PROC HPCOUNTREG Features 140
Getting Started: HPCOUNTREG Procedure **140**
Syntax: HPCOUNTREG Procedure **143**
Functional Summary 144
PROC HPCOUNTREG Statement 145
BOUNDS Statement 147
FREQ Statement 147
INIT Statement 148
MODEL Statement 148
OUTPUT Statement 149
PERFORMANCE Statement 150
RESTRICT Statement 151
WEIGHT Statement 151
ZEROMODEL Statement 151
Details: HPCOUNTREG Procedure **152**
Missing Values 152
Poisson Regression 153
Negative Binomial Regression 154
Zero-Inflated Count Regression Overview 156
Zero-Inflated Poisson Regression 157
Zero-Inflated Negative Binomial Regression 159
Computational Resources 162
Nonlinear Optimization Options 162
Covariance Matrix Types 162
Displayed Output 163
OUTPUT OUT= Data Set 164
OUTEST= Data Set 165
ODS Table Names 165
Examples: The HPCOUNTREG Procedure **166**
Example 9.1: High-Performance Zero-Inflated Poisson Model 166
References **171**

Overview: HPCOUNTREG Procedure

The HPCOUNTREG procedure is a high-performance version of the COUNTREG procedure in SAS/ETS software. Similar to the COUNTREG procedure, the HPCOUNTREG procedure fits regression models in which the dependent variable takes on nonnegative integer or count values. Unlike the COUNTREG procedure which can be run only on an individual workstation, the HPCOUNTREG procedure takes advantage of a computing environment that enables it to distribute the optimization task among one or more nodes. In addition, each node can use one or more threads to carry out the optimization on its subset of the data. When several nodes are employed with each node using several threads to carry out its part of the work, the result is a highly parallel computation that provides a dramatic gain in performance.

With the HPCOUNTREG procedure you can read and write data in distributed form and perform analyses in massively parallel processing (MPP) and symmetric multiprocessing (SMP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about how to affect the execution mode of SAS High-Performance Analytics procedures.

The HPCOUNTREG procedure is specifically designed to operate in the high-performance distributed environment. By default, PROC HPCOUNTREG performs computations in multiple threads.

PROC HPCOUNTREG Features

The HPCOUNTREG procedure estimates the parameters of a count regression model by maximum likelihood techniques. The following list summarizes some basic features of the HPCOUNTREG procedure:

- can perform analysis on a massively parallel high-performance appliance
- reads input data in parallel and writes output data in parallel when the data source is the appliance database
- is highly multithreaded during all phases of analytic execution
- performs maximum likelihood estimation
- supports multiple link functions

Currently the HPCOUNTREG procedure does not support BY-group processing or the CLASS statement.

Getting Started: HPCOUNTREG Procedure

Except for its ability to operate in the high-performance distributed environment, the HPCOUNTREG procedure is similar in use to other regression model procedures in the SAS System. For example, the following statements are used to estimate a Poisson regression model:

```
proc hpcountreg data=one ;
   model y = x / dist=poisson ;
run;
```

The response variable y is numeric and has nonnegative integer values.

This section illustrates two simple examples that use PROC HPCOUNTREG. The data are taken from Long (1997). This study examines how factors such as gender (fem), marital status (mar), number of young children (kid5), prestige of the graduate program (phd), and number of articles published by a scientist's mentor (ment) affect the number of articles (art) published by the scientist.

The first 10 observations are shown in Figure 9.1.

Figure 9.1 Article Count Data

Obs	art	fem	mar	kid5	phd	ment
1	3	0	1	2	1.38000	8.0000
2	0	0	0	0	4.29000	7.0000
3	4	0	0	0	3.85000	47.0000
4	1	0	1	1	3.59000	19.0000
5	1	0	1	0	1.81000	0.0000
6	1	0	1	1	3.59000	6.0000
7	0	0	1	1	2.12000	10.0000
8	0	0	1	0	4.29000	2.0000
9	3	0	1	2	2.58000	2.0000
10	3	0	1	1	1.80000	4.0000

The following SAS statements estimate the Poisson regression model. The model is executed in the distributed computing environment with two threads and four nodes.

```
/*-- Poisson Regression --*/
proc hpcountreg data=long97data;
   model art = fem mar kid5 phd ment / dist=poisson method=quanew;
   performance nthreads=2 nodes=4 details;
run;
```

The "Model Fit Summary" table shown in Figure 9.2, lists several details about the model. By default, the HPCOUNTREG procedure uses the Newton-Raphson optimization technique. The maximum log-likelihood value is shown, in addition to two information measures—Akaike's information criterion (AIC) and Schwarz's Bayesian information criterion (SBC)—which can be used to compare competing Poisson models. Smaller values of these criteria indicate better models.

Figure 9.2 Estimation Summary Table for a Poisson Regression

The HPCOUNTREG Procedure

Model Fit Summary

Dependent Variable	art
Number of Observations	915
Data Set	WORK.LONG97DATA
Model	Poisson
Log Likelihood	-1651
Maximum Absolute Gradient	0.0002080
Number of Iterations	13
Optimization Method	Quasi-Newton
AIC	3314
SBC	3343

Figure 9.3 shows the parameter estimates of the model and their standard errors. All covariates are significant predictors of the number of articles, except for the prestige of the program (phd), which has a p-value of 0.6271.

Figure 9.3 Parameter Estimates of Poisson Regression

Parameter Estimates

Effect	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	0.3046	0.1030	2.96	0.0031
fem	1	-0.2246	0.05461	-4.11	<.0001
mar	1	0.1552	0.06137	2.53	0.0114
kid5	1	-0.1849	0.04013	-4.61	<.0001
phd	1	0.01282	0.02640	0.49	0.6271
ment	1	0.02554	0.002006	12.73	<.0001

To allow for variance greater than the mean, you can fit the negative binomial model instead of the Poisson by specifying the DIST=NEGBIN option, as shown in the following statements. While the Poisson model requires that the conditional mean and conditional variance be equal, the negative binomial model allows for overdispersion, in which the conditional variance can exceed the conditional mean.

```
/*-- Negative Binomial Regression --*/
proc hpcountreg data=long97data;
   model art = fem mar kid5 phd ment / dist=negbin(p=2) method=quanew;
   performance nthreads=2 nodes=4 details;
run;
```

Figure 9.4 shows the fit summary and Figure 9.5 shows the parameter estimates.

Figure 9.4 Estimation Summary Table for a Negative Binomial Regression

The HPCOUNTREG Procedure

Model Fit Summary

Dependent Variable	art
Number of Observations	915
Data Set	WORK.LONG97DATA
Model	NegBin
Log Likelihood	-1561
Maximum Absolute Gradient	0.0000666
Number of Iterations	16
Optimization Method	Quasi-Newton
AIC	3136
SBC	3170

Figure 9.5 Parameter Estimates of Negative Binomial Regression

Parameter Estimates

Effect	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	0.2561	0.1386	1.85	0.0645
fem	1	-0.2164	0.07267	-2.98	0.0029
mar	1	0.1505	0.08211	1.83	0.0668
kid5	1	-0.1764	0.05306	-3.32	0.0009
phd	1	0.01527	0.03604	0.42	0.6718
ment	1	0.02908	0.003470	8.38	<.0001
_Alpha	1	0.4416	0.05297	8.34	<.0001

The parameter estimate for _Alpha of 0.4416 is an estimate of the dispersion parameter in the negative binomial distribution. A t test for the hypothesis $H_0 : \alpha = 0$ is provided. It is highly significant, indicating overdispersion ($p < 0.0001$).

The null hypothesis $H_0 : \alpha = 0$ can be also tested against the alternative $\alpha > 0$ by using the likelihood ratio test, as described by Cameron and Trivedi (1998, pp. 45, 77–78). The likelihood ratio test statistic is equal to $-2(\mathcal{L}_P - \mathcal{L}_{NB}) = -2(-1651 + 1561) = 180$, which is highly significant, providing strong evidence of overdispersion.

Syntax: HPCOUNTREG Procedure

The following statements are available in the HPCOUNTREG procedure. Items within angle brackets (< >) or square brackets ([ ]) are optional.

```
PROC HPCOUNTREG <options> ;
    BOUNDS bound1 [ , bound2 . . . ] ;
    FREQ freq-variable ;
    INIT initialization1 < , initialization2 . . . > ;
    MODEL dependent-variable = regressors </ options> ;
    OUTPUT <output-options> ;
    PERFORMANCE performance-options ;
    RESTRICT restriction1 [, restriction2 . . . ] ;
    WEIGHT variable </ option> ;
    ZEROMODEL dependent-variable ~ zero-inflated-regressors </ options> ;
```

There can be only one MODEL statement. The ZEROMODEL statement, if used, must appear after the MODEL statement. If a FREQ or WEIGHT statement is specified more than once, the variable specified in the first instance is used.

Functional Summary

Table 9.1 summarizes the statements and options used with the HPCOUNTREG procedure.

Table 9.1 HPCOUNTREG Functional Summary

Description	Statement	Option
Data Set Options		
Specifies the input data set	HPCOUNTREG	DATA=
Writes parameter estimates to an output data set	HPCOUNTREG	OUTEST=
Writes estimates of $\mathbf{x}_i'\boldsymbol{\beta}$ and $\mathbf{z}_i'\boldsymbol{\gamma}$ to an output data set	OUTPUT	OUT=
Specifies an optional frequency variable	FREQ	
Specifies an optional weight variable	WEIGHT	
Printing Control Options		
Prints the correlation matrix of the estimates	MODEL	CORRB
Prints the covariance matrix of the estimates	MODEL	COVB
Prints a summary iteration listing	MODEL	ITPRINT
Suppresses the normal printed output	HPCOUNTREG	NOPRINT
Requests all printing options	MODEL	PRINTALL
Options to Control the Optimization Process		
Specifies maximum number of iterations allowed	MODEL	MAXITER=
Selects the iterative minimization method to use	HPCOUNTREG	METHOD=
Specifies maximum number of iterations allowed	HPCOUNTREG	MAXITER=
Specifies maximum number of function calls	HPCOUNTREG	MAXFUNC=
Specifies the upper limit of CPU time in seconds	HPCOUNTREG	MAXTIME=
Specifies absolute function convergence criterion	HPCOUNTREG	ABSCONV=
Specifies absolute function convergence criterion	HPCOUNTREG	ABSFCONV=
Specifies absolute gradient convergence criterion	HPCOUNTREG	ABSGCONV=

Description	Statement	Option
Specifies relative function convergence criterion	HPCOUNTREG	FCONV=
Specifies relative gradient convergence criterion	HPCOUNTREG	GCONV=
Specifies absolute parameter convergence criterion	HPCOUNTREG	ABSXCONV=
Specifies matrix singularity criterion	HPCOUNTREG	SINGULAR=
Sets boundary restrictions on parameters	BOUNDS	
Sets initial values for parameters	INIT	
Sets linear restrictions on parameters	RESTRICT	
Model Estimation Options		
Specifies the type of model	MODEL	DIST=
Specifies the type of model	HPCOUNTREG	DIST=
Specifies the type of covariance matrix	MODEL	COVEST=
Suppresses the intercept parameter	MODEL	NOINT
Specifies the offset variable	MODEL	OFFSET=
Specifies the zero-inflated offset variable	ZEROMODEL	OFFSET=
Specifies the zero-inflated link function	ZEROMODEL	LINK=
Output Control Options		
Includes covariances in the OUTEST= data set	HPCOUNTREG	COVOUT
Outputs probability of the actual value	OUTPUT	PROB=
Outputs expected value of response variable	OUTPUT	PRED=
Outputs estimates of XBeta $= \mathbf{x}_i'\boldsymbol{\beta}$	OUTPUT	XBETA=
Outputs estimates of ZGamma $= \mathbf{z}_i'\boldsymbol{\gamma}$	OUTPUT	ZGAMMA=
Outputs probability of a zero value as a result of the zero-generating process	OUTPUT	PROBZERO=
Performance Options		
Requests a table that shows a timing breakdown	PERFORMANCE	DETAILS
Specifies the number of threads to use	PERFORMANCE	NTHREADS=
Specifies the number of nodes to use on the SAS appliance	PERFORMANCE	NODES=

PROC HPCOUNTREG Statement

PROC HPCOUNTREG <*options*> **;**

The following *options* can be used in the PROC HPCOUNTREG statement:

Input Data Set Option

DATA=*SAS-data-set*
specifies the input SAS data set. If the DATA= option is not specified, PROC HPCOUNTREG uses the most recently created SAS data set.

Output Data Set Options

OUTEST=*SAS-data-set*
writes the parameter estimates to the specified output data set.

COVOUT
writes the covariance matrix for the parameter estimates to the OUTEST= data set. This option is valid only if the OUTEST= option is specified.

Printing Options

You can specify the following options in either the PROC HPCOUNTREG statement or in the MODEL statement:

CORRB
prints the correlation matrix of the parameter estimates.

COVB
prints the covariance matrix of the parameter estimates.

ITPRINT
prints the objective function and parameter estimates at each iteration. The objective function is the negative log-likelihood function.

NOPRINT
suppresses all printed output.

PRINTALL
requests all printing options.

Estimation Control Options

COVEST=*value*
specifies the type of covariance matrix for the parameter estimates.

The default is COVEST=HESSIAN. You can specify the following *values*:

OP	specifies the covariance from the outer product matrix.
HESSIAN	specifies the covariance from the Hessian matrix.
QML	specifies the covariance from the outer product and Hessian matrices.

Options to Control the Optimization Process

PROC HPCOUNTREG uses the nonlinear optimization (NLO) subsystem to perform nonlinear optimization tasks. All the NLO options are available. For details, see Chapter 6, "Nonlinear Optimization Methods" (*SAS/ETS User's Guide*). In addition, the following *option* is supported in the PROC HPCOUNTREG statement:

METHOD=*value*

specifies the iterative minimization method to use. The default is METHOD=NRA. You can specify the following *values*:

CG	specifies the conjugate-gradient method.
DD	specifies the double dogleg method.
NONE	specifies that no optimization be performed beyond using the ordinary least squares method to compute the parameter estimates.
NRA	specifies the Newton-Raphson method (the default).
NRR	specifies the Newton-Raphson Ridge method.
QN	specifies the quasi-Newton method.
TR	specifies the trust region method.

BOUNDS Statement

BOUNDS *bound1* [*, bound2 . . .*] **;**

The BOUNDS statement imposes simple boundary constraints on the parameter estimates. You can specify any number of BOUNDS statements.

Each *bound* is composed of parameter names, constants, and inequality operators as follows:

item operator item [*operator item* [*operator item . . .*]]

Each *item* is a constant, a parameter name, or a list of parameter names. Each *operator* is <, >, <=, or >=. Parameter names are as shown in the Effect column of the "Parameter Estimates" table.

You can use both the BOUNDS statement and the RESTRICT statement to impose boundary constraints. However, the BOUNDS statement provides a simpler syntax for specifying these kinds of constraints. See also the section "RESTRICT Statement" on page 151.

The following BOUNDS statement illustrates the use of parameter lists to specify boundary constraints. It constrains the estimates of the parameter for `z` to be negative, the parameters for `x1` through `x10` to be between 0 and 1, and the parameter for `x1` in the zero-inflation model to be less than 1.

```
bounds z < 0,
       0 < x1-x10 < 1,
       Inf_x1 < 1;
```

FREQ Statement

FREQ *freq-variable* **;**

The FREQ statement identifies a variable (*freq-variable*) that contains the frequency of occurrence of each observation. PROC HPCOUNTREG treats each observation as if it appears n times, where n is the value

of *freq-variable* for the observation. If the value for the observation is not an integer, it is truncated to an integer. If the value is less than 1 or missing, the observation is not used in the model fitting. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

INIT Statement

INIT *initialization1* < *, initialization2 . . .* > **;**

The INIT statement sets initial values for parameters in the optimization.

Each *initialization* is written as a parameter or parameter list, followed by an optional equal sign (=), followed by a number:

parameter <=> *number*

Parameter names are as shown in the Effect column of the "Parameter Estimates" table.

MODEL Statement

MODEL *dependent-variable* **=** *regressors* </ *options*> **;**

The MODEL statement specifies the dependent variable and independent regressor variables for the regression model. The dependent count variable should take on only nonnegative integer values in the input data set. PROC HPCOUNTREG rounds any positive noninteger count value to the nearest integer. PROC HPCOUNTREG discards any observation that has a negative count.

Only one MODEL statement can be specified. The following *options* can be used in the MODEL statement after a slash (/).

DIST=*value*
specifies a type of model to be analyzed. You can specify the following *values*:

POISSON | P specifies the Poisson regression model.

NEGBIN(P=1) specifies the negative binomial regression model with a linear variance function.

NEGBIN(P=2) | NEGBIN specifies the negative binomial regression model with a quadratic variance function.

ZIPOISSON | ZIP specifies zero-inflated Poisson regression.

ZINEGBIN | ZINB specifies zero-inflated negative binomial regression.

NOINT
suppresses the intercept parameter.

OFFSET=*offset-variable*
specifies a variable in the input data set to be used as an offset variable. The offset variable is used to allow the observational units to vary across observations. For example, when the number of shipping accidents could be measured across different time periods or the number of students who participate in an activity could be reported across different class sizes, the observational units need to be adjusted

to a common denominator by using the offset variable. The offset variable appears as a covariate in the model with its parameter restricted to 1. The offset variable cannot be the response variable, the zero-inflation offset variable (if any), or any of the explanatory variables. The "Model Fit Summary" table gives the name of the data set variable used as the offset variable; it is labeled as "Offset."

Printing Options

You can specify the following options in either the PROC HPCOUNTREG statement or in the MODEL statement:

CORRB
prints the correlation matrix of the parameter estimates.

COVB
prints the covariance matrix of the parameter estimates.

ITPRINT
prints the objective function and parameter estimates at each iteration. The objective function is the negative log-likelihood function.

NOPRINT
suppresses all printed output.

PRINTALL
requests all printing options.

OUTPUT Statement

OUTPUT < *output-options* > **;**

The OUTPUT statement creates a new SAS data set that includes variables created by the *output-options*. These variables include the estimates of $\mathbf{x}_i'\boldsymbol{\beta}$, the expected value of the response variable, and the probability of the response variable taking on the current value. Furthermore, if a zero-inflated model was fit, you can request that the output data set contain the estimates of $\mathbf{z}_i'\boldsymbol{\gamma}$ and the probability that the response is zero as a result of the zero-generating process. These statistics can be computed for all observations in which the regressors are not missing, even if the response is missing. By adding observations with missing response values to the input data set, you can compute these statistics for new observations or for settings of the regressors that are not present in the data without affecting the model fit.

You can specify only one OUTPUT statement. You can specify the following *output-options*:

OUT=*SAS-data-set*
names the output data set.

OUTVAR(*SAS-variable-names***)**
adds SAS variables to the output data set.

PRED=*name*
names the variable to contain the predicted value of the response variable.

PROB=*name*
names the variable to contain the probability of the response variable taking the actual value, $\Pr(Y = y_i)$.

PROBCOUNT(*value1* **<** *value2* **... >)**
outputs the probability of the response variable taking particular values. Each value should be a nonnegative integer. Nonintegers are rounded to the nearest integer. For *value*, you can also specify a list of the form X TO Y BY Z. For example, PROBCOUNT(0 1 2 TO 10 BY 2 15) requests predicted probabilities for counts 0, 1, 2, 4, 5, 6, 8, 10, and 15. This option is not available for the fixed- and random-effects panel models.

PROBZERO=*name*
names the variable to contain the value of φ_i, which is the probability of the response variable taking on the value of 0 as a result of the zero-generating process. This variable is written to the output file only if the model is zero-inflated.

XBETA=*name*
names the variable to contain estimates of $\mathbf{x}_i'\boldsymbol{\beta}$.

ZGAMMA=*name*
names the variable to contain estimates of $\mathbf{z}_i'\boldsymbol{\gamma}$.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement specifies options to control the multithreaded and distributed computing environment and requests detailed results about the performance characteristics of the HPCOUNTREG procedure. With the PERFORMANCE statement you can also control whether the HPCOUNTREG procedure executes in SMP or MPP mode. The most commonly used *performance-options* in the PERFORMANCE statement include the following:

DETAILS
requests a table that shows a timing breakdown of the procedure steps.

NODES=*n*
specifies the number of nodes in the distributed computing environment, provided that the data are not processed alongside the database.

NTHREADS=*n*
specifies the number of threads for analytic computations and overrides the SAS system option THREADS | NOTHREADS. If you do not specify the NTHREADS= option, PROC HPCOUNTREG creates one thread per CPU for the analytic computations.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in more detail in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

RESTRICT Statement

RESTRICT *restriction1* [, *restriction2 . . .*] **;**

The RESTRICT statement imposes linear restrictions on the parameter estimates. You can specify any number of RESTRICT statements.

Each *restriction* is written as an expression, followed by an equality operator (=) or an inequality operator (<, >, <=, >=), followed by a second expression, as follows:

expression operator expression

The *operator* can be =, <, >, <=, or >=.

Restriction expressions can be composed of parameter names, constants, and the following operators: times ($*$), plus ($+$), and minus ($-$). Parameter names are as shown in the Effect column of the "Parameter Estimates" table. The restriction expressions must be a linear function of the variables.

Lagrange multipliers are reported in the "Parameter Estimates" table for all the active linear constraints. They are identified with the names Restrict1, Restrict2, and so on. The probabilities of these Lagrange multipliers are computed using a beta distribution (LaMotte 1994). Nonactive (nonbinding) restrictions have no effect on the estimation results and are not noted in the output.

The following RESTRICT statement constrains the negative binomial dispersion parameter α to 1, which restricts the conditional variance to be $\mu + \mu^2$:

```
restrict _Alpha = 1;
```

WEIGHT Statement

WEIGHT *variable* < / *option* > **;**

The WEIGHT statement specifies a variable to supply weighting values to use for each observation in estimating parameters. The log likelihood for each observation is multiplied by the corresponding weight variable value.

If the weight of an observation is nonpositive, that observation is not used in the estimation.

The following *option* can be added to the WEIGHT statement after a slash (/).

NONORMALIZE
does not normalize the weights. (By default, the weights are normalized so that they add up to the actual sample size. Weights w_i are normalized by multiplying them by $\frac{n}{\sum_{i=1}^{n} w_i}$, where n is the sample size.) If the weights are required to be used as they are, then specify the NONORMALIZE option.

ZEROMODEL Statement

ZEROMODEL *dependent-variable* ~ *zero-inflated-regressors* < / *options* > **;**

The ZEROMODEL statement is required if either ZIP or ZINB is specified in the DIST= option in the MODEL statement. If ZIP or ZINB is specified, then the ZEROMODEL statement must follow the MODEL statement. The dependent variable in the ZEROMODEL statement must be the same as the dependent variable in the MODEL statement.

The zero-inflated (ZI) regressors appear in the equation that determines the probability (φ_i) of a zero count. Each of these q variables has a parameter to be estimated in the regression. For example, let $\mathbf{z}_i'$ be the ith observation's $1 \times (q + 1)$ vector of values of the q ZI explanatory variables (w_0 is set to 1 for the intercept term). Then φ_i is a function of $\mathbf{z}_i'\boldsymbol{\gamma}$, where $\boldsymbol{\gamma}$ is the $(q + 1) \times 1$ vector of parameters to be estimated. (The zero-inflated intercept is γ_0; the coefficients for the q zero-inflated covariates are $\gamma_1, \ldots, \gamma_q$.) If q is equal to 0 (no ZI explanatory variables are provided), then only the intercept term γ_0 is estimated. The "Parameter Estimates" table in the displayed output shows the estimates for the ZI intercept and ZI explanatory variables; they are labeled with the prefix "Inf_". For example, the ZI intercept is labeled "Inf_intercept". If you specify Age (a variable in your data set) as a ZI explanatory variable, then the "Parameter Estimates" table labels the corresponding parameter estimate "Inf_Age".

You can specify the following *options* in the ZEROMODEL statement following a slash (/):

LINK=*value*

specifies the distribution function used to compute probability of zeros. The supported distribution functions are as follows:

LOGISTIC	specifies logistic distribution.
NORMAL	specifies standard normal distribution.

If this option is omitted, then the default ZI link function is logistic.

OFFSET=*zero-inflated-offset-variable*

specifies a variable in the input data set to be used as a zero-inflated (ZI) offset variable. The ZI offset variable *zero-inflated-offset-variable* is included as a term, with coefficient restricted to 1, in the equation that determines the probability (φ_i) of a zero count and represents an adjustment to a common observational unit. The ZI offset variable cannot be the response variable, the offset variable (if any), or any of the explanatory variables. The name of the data set variable used as the ZI offset variable is displayed in the "Model Fit Summary" table, where it is labeled as "Inf_offset".

Details: HPCOUNTREG Procedure

Missing Values

Any observation in the input data set with a missing value for one or more of the regressors is ignored by PROC HPCOUNTREG and not used in the model fit. PROC HPCOUNTREG rounds any positive noninteger count values to the nearest integer. PROC HPCOUNTREG ignores any observations with a negative count.

If the input data set contains any observations that have missing response values but nonmissing regressors, PROC HPCOUNTREG can compute several statistics and store them in an output data set by using the

OUTPUT statement. For example, you can request that the output data set contain the estimates of $\mathbf{x}_i'\boldsymbol{\beta}$, the expected value of the response variable, and the probability of the response variable taking on the current value. Furthermore, if a zero-inflated model was fit, you can request that the output data set contain the estimates of $\mathbf{z}_i'\boldsymbol{\gamma}$, and the probability that the response is 0 as a result of the zero-generating process. Note that the presence of such observations (with missing response values) does not affect the model fit.

Poisson Regression

The most widely used model for count data analysis is Poisson regression. Poisson regression assumes that y_i, given the vector of covariates $\mathbf{x}_i$, is independently Poisson distributed with

$$P(Y_i = y_i|\mathbf{x}_i) = \frac{e^{-\mu_i}\mu_i^{y_i}}{y_i!}, \quad y_i = 0, 1, 2, \ldots$$

and the mean parameter—that is, the mean number of events per period—is given by

$$\mu_i = \exp(\mathbf{x}_i'\boldsymbol{\beta})$$

where $\boldsymbol{\beta}$ is a $(k + 1) \times 1$ parameter vector. (The intercept is β_0; the coefficients for the k regressors are $\beta_1, \ldots, \beta_k$.) Taking the exponential of $\mathbf{x}_i'\boldsymbol{\beta}$ ensures that the mean parameter μ_i is nonnegative. It can be shown that the conditional mean is given by

$$E(y_i|\mathbf{x}_i) = \mu_i = \exp(\mathbf{x}_i'\boldsymbol{\beta})$$

The name *log-linear model* is also used for the Poisson regression model since the logarithm of the conditional mean is linear in the parameters:

$$\ln[E(y_i|\mathbf{x}_i)] = \ln(\mu_i) = \mathbf{x}_i'\boldsymbol{\beta}$$

Note that the conditional variance of the count random variable is equal to the conditional mean in the Poisson regression model:

$$V(y_i|\mathbf{x}_i) = E(y_i|\mathbf{x}_i) = \mu_i$$

The equality of the conditional mean and variance of y_i is known as *equidispersion*.

The marginal effect of a regressor is given by

$$\frac{\partial E(y_i|\mathbf{x}_i)}{\partial x_{ji}} = \exp(\mathbf{x}_i'\boldsymbol{\beta})\boldsymbol{\beta}_j = E(y_i|\mathbf{x}_i)\beta_j$$

Thus, a one-unit change in the jth regressor leads to a proportional change in the conditional mean $E(y_i|\mathbf{x}_i)$ of β_j.

The standard estimator for the Poisson model is the maximum likelihood estimator (MLE). Since the observations are independent, the log-likelihood function is written as

$$\mathcal{L} = \sum_{i=1}^{N}(-\mu_i + y_i \ln \mu_i - \ln y_i!) = \sum_{i=1}^{N}(-e^{\mathbf{x}_i'\boldsymbol{\beta}} + y_i\mathbf{x}_i'\boldsymbol{\beta} - \ln y_i!)$$

The gradient and the Hessian are as follows, respectively:

$$\frac{\partial \mathcal{L}}{\partial \boldsymbol{\beta}} = \sum_{i=1}^{N}(y_i - \mu_i)\mathbf{x}_i = \sum_{i=1}^{N}(y_i - e^{\mathbf{x}_i'\boldsymbol{\beta}})\mathbf{x}_i$$

$$\frac{\partial^2 \mathcal{L}}{\partial \boldsymbol{\beta}\partial \boldsymbol{\beta}'} = -\sum_{i=1}^{N}\mu_i \mathbf{x}_i \mathbf{x}_i{}' = -\sum_{i=1}^{N} e^{\mathbf{x}_i'\boldsymbol{\beta}}\mathbf{x}_i\mathbf{x}_i'$$

The Poisson model has been criticized for its restrictive property that the conditional variance equals the conditional mean. Real-life data are often characterized by *overdispersion*—that is, the variance exceeds the mean. Allowing for overdispersion can improve model predictions since the Poisson restriction of equal mean and variance results in the underprediction of zeros when overdispersion exists. The most commonly used model that accounts for overdispersion is the negative binomial model.

Negative Binomial Regression

The Poisson regression model can be generalized by introducing an unobserved heterogeneity term for observation i. Thus, the individuals are assumed to differ randomly in a manner that is not fully accounted for by the observed covariates. This is formulated as

$$E(y_i|\mathbf{x}_i, \tau_i) = \mu_i \tau_i = e^{\mathbf{x}_i'\boldsymbol{\beta}+\epsilon_i}$$

where the unobserved heterogeneity term $\tau_i = e^{\epsilon_i}$ is independent of the vector of regressors $\mathbf{x}_i$. Then the distribution of y_i conditional on $\mathbf{x}_i$ and τ_i is Poisson with conditional mean and conditional variance $\mu_i\tau_i$:

$$f(y_i|\mathbf{x}_i, \tau_i) = \frac{\exp(-\mu_i\tau_i)(\mu_i\tau_i)^{y_i}}{y_i!}$$

Let $g(\tau_i)$ be the probability density function of τ_i. Then, the distribution $f(y_i|\mathbf{x}_i)$ (no longer conditional on τ_i) is obtained by integrating $f(y_i|\mathbf{x}_i, \tau_i)$ with respect to τ_i:

$$f(y_i|\mathbf{x}_i) = \int_0^{\infty} f(y_i|\mathbf{x}_i, \tau_i)g(\tau_i)d\tau_i$$

An analytical solution to this integral exists when τ_i is assumed to follow a gamma distribution. This solution is the negative binomial distribution. When the model contains a constant term, it is necessary to assume that $E(e^{\epsilon_i}) = E(\tau_i) = 1$, in order to identify the mean of the distribution. Thus, it is assumed that τ_i follows a gamma(θ, θ) distribution with $E(\tau_i) = 1$ and $V(\tau_i) = 1/\theta$,

$$g(\tau_i) = \frac{\theta^{\theta}}{\Gamma(\theta)}\tau_i^{\theta-1}\exp(-\theta\tau_i)$$

where $\Gamma(x) = \int_0^\infty z^{x-1} \exp(-z) dz$ is the gamma function and θ is a positive parameter. Then, the density of y_i given $\mathbf{x}_i$ is derived as

$$\begin{aligned} f(y_i|\mathbf{x}_i) &= \int_0^\infty f(y_i|\mathbf{x}_i, \tau_i) g(\tau_i) d\tau_i \\ &= \frac{\theta^\theta \mu_i^{y_i}}{y_i! \Gamma(\theta)} \int_0^\infty e^{-(\mu_i+\theta)\tau_i} \tau_i^{\theta+y_i-1} d\tau_i \\ &= \frac{\theta^\theta \mu_i^{y_i} \Gamma(y_i+\theta)}{y_i! \Gamma(\theta)(\theta+\mu_i)^{\theta+y_i}} \\ &= \frac{\Gamma(y_i+\theta)}{y_i! \Gamma(\theta)} \left(\frac{\theta}{\theta+\mu_i}\right)^\theta \left(\frac{\mu_i}{\theta+\mu_i}\right)^{y_i} \end{aligned}$$

Making the substitution $\alpha = \frac{1}{\theta}$ ($\alpha > 0$), the negative binomial distribution can then be rewritten as

$$f(y_i|\mathbf{x}_i) = \frac{\Gamma(y_i+\alpha^{-1})}{y_i! \Gamma(\alpha^{-1})} \left(\frac{\alpha^{-1}}{\alpha^{-1}+\mu_i}\right)^{\alpha^{-1}} \left(\frac{\mu_i}{\alpha^{-1}+\mu_i}\right)^{y_i}, \quad y_i = 0, 1, 2, \ldots$$

Thus, the negative binomial distribution is derived as a gamma mixture of Poisson random variables. It has conditional mean

$$E(y_i|\mathbf{x}_i) = \mu_i = e^{\mathbf{x}_i'\boldsymbol{\beta}}$$

and conditional variance

$$V(y_i|\mathbf{x}_i) = \mu_i[1 + \frac{1}{\theta}\mu_i] = \mu_i[1 + \alpha\mu_i] > E(y_i|\mathbf{x}_i)$$

The conditional variance of the negative binomial distribution exceeds the conditional mean. Overdispersion results from neglected unobserved heterogeneity. The negative binomial model with variance function $V(y_i|\mathbf{x}_i) = \mu_i + \alpha\mu_i^2$, which is quadratic in the mean, is referred to as the NEGBIN2 model (Cameron and Trivedi 1986). To estimate this model, specify DIST=NEGBIN(P=2) in the MODEL statement. The Poisson distribution is a special case of the negative binomial distribution where $\alpha = 0$. A test of the Poisson distribution can be carried out by testing the hypothesis that $\alpha = \frac{1}{\theta_i} = 0$. A Wald test of this hypothesis is provided (it is the reported t statistic for the estimated α in the negative binomial model).

The log-likelihood function of the negative binomial regression model (NEGBIN2) is given by

$$\begin{aligned} \mathcal{L} &= \sum_{i=1}^N \left\{ \sum_{j=0}^{y_i-1} \ln(j+\alpha^{-1}) - \ln(y_i!) \right. \\ &\quad \left. -(y_i+\alpha^{-1}) \ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) + y_i \ln(\alpha) + y_i \mathbf{x}_i'\boldsymbol{\beta} \right\} \end{aligned}$$

where use of the following fact is made if y is an integer:

$$\Gamma(y+a)/\Gamma(a) = \prod_{j=0}^{y-1} (j+a)$$

The gradient is

$$\frac{\partial \mathcal{L}}{\partial \boldsymbol{\beta}} = \sum_{i=1}^{N} \frac{y_i - \mu_i}{1 + \alpha\mu_i}\mathbf{x}_i$$

and

$$\frac{\partial \mathcal{L}}{\partial \alpha} = \sum_{i=1}^{N} \left\{ -\alpha^{-2} \sum_{j=0}^{y_i-1} \frac{1}{(j + \alpha^{-1})} + \alpha^{-2}\ln(1 + \alpha\mu_i) + \frac{y_i - \mu_i}{\alpha(1 + \alpha\mu_i)} \right\}$$

Cameron and Trivedi (1986) consider a general class of negative binomial models with mean μ_i and variance function $\mu_i + \alpha\mu_i^p$. The NEGBIN2 model, with $p = 2$, is the standard formulation of the negative binomial model. Models with other values of p, $-\infty < p < \infty$, have the same density $f(y_i|\mathbf{x}_i)$ except that α^{-1} is replaced everywhere by $\alpha^{-1}\mu^{2-p}$. The negative binomial model NEGBIN1, which sets $p = 1$, has variance function $V(y_i|\mathbf{x}_i) = \mu_i + \alpha\mu_i$, which is linear in the mean. To estimate this model, specify DIST=NEGBIN(P=1) in the MODEL statement.

The log-likelihood function of the NEGBIN1 regression model is given by

$$\begin{aligned}\mathcal{L} \;=\; & \sum_{i=1}^{N} \left\{ \sum_{j=0}^{y_i-1} \ln\left(j + \alpha^{-1}\exp(\mathbf{x}_i'\boldsymbol{\beta})\right) \right. \\ & \left. -\ln(y_i!) - \left(y_i + \alpha^{-1}\exp(\mathbf{x}_i'\boldsymbol{\beta})\right)\ln(1 + \alpha) + y_i\ln(\alpha) \right\}\end{aligned}$$

The gradient is

$$\frac{\partial \mathcal{L}}{\partial \boldsymbol{\beta}} = \sum_{i=1}^{N} \left\{ \left(\sum_{j=0}^{y_i-1} \frac{\mu_i}{(j\alpha + \mu_i)} \right)\mathbf{x}_i - \alpha^{-1}\ln(1 + \alpha)\mu_i\mathbf{x}_i \right\}$$

and

$$\frac{\partial \mathcal{L}}{\partial \alpha} = \sum_{i=1}^{N} \left\{ -\left(\sum_{j=0}^{y_i-1} \frac{\alpha^{-1}\mu_i}{(j\alpha + \mu_i)} \right) - \alpha^{-2}\mu_i\ln(1 + \alpha) - \frac{(y_i + \alpha^{-1}\mu_i)}{1 + \alpha} + \frac{y_i}{\alpha} \right\}$$

Zero-Inflated Count Regression Overview

The main motivation for zero-inflated count models is that real-life data frequently display overdispersion and excess zeros. Zero-inflated count models provide a way of both modeling the excess zeros and allowing for overdispersion. In particular, there are two possible data generation processes for each observation. The result of a Bernoulli trial is used to determine which of the two processes is used. For observation i, Process 1 is chosen with probability φ_i and Process 2 with probability $1 - \varphi_i$. Process 1 generates only zero counts. Process 2 generates counts from either a Poisson or a negative binomial model. In general,

$$y_i \sim \begin{cases} 0 & \text{with probability} \quad \varphi_i \\ g(y_i) & \text{with probability} \quad 1 - \varphi_i \end{cases}$$

Therefore, the probability of $\{Y_i = y_i\}$ can be described as

$$\begin{aligned} P(y_i = 0|\mathbf{x}_i) &= \varphi_i + (1-\varphi_i)g(0) \\ P(y_i|\mathbf{x}_i) &= (1-\varphi_i)g(y_i), \quad y_i > 0 \end{aligned}$$

where $g(y_i)$ follows either the Poisson or the negative binomial distribution.

When the probability φ_i depends on the characteristics of observation i, φ_i is written as a function of $\mathbf{z}_i'\boldsymbol{\gamma}$, where $\mathbf{z}_i'$ is the $1 \times (q+1)$ vector of zero-inflated covariates and $\boldsymbol{\gamma}$ is the $(q+1) \times 1$ vector of zero-inflated coefficients to be estimated. (The zero-inflated intercept is γ_0; the coefficients for the q zero-inflated covariates are $\gamma_1, \ldots, \gamma_q$.) The function F that relates the product $\mathbf{z}_i'\boldsymbol{\gamma}$ (which is a scalar) to the probability φ_i is called the zero-inflated link function,

$$\varphi_i = F_i = F(\mathbf{z}_i'\boldsymbol{\gamma})$$

In the HPCOUNTREG procedure, the zero-inflated covariates are indicated in the ZEROMODEL statement. Furthermore, the zero-inflated link function F can be specified as either the logistic function,

$$F(\mathbf{z}_i'\boldsymbol{\gamma}) = \Lambda(\mathbf{z}_i'\boldsymbol{\gamma}) = \frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{1+\exp(\mathbf{z}_i'\boldsymbol{\gamma})}$$

or the standard normal cumulative distribution function (also called the probit function),

$$F(\mathbf{z}_i'\boldsymbol{\gamma}) = \Phi(\mathbf{z}_i'\boldsymbol{\gamma}) = \int_0^{\mathbf{z}_i'\boldsymbol{\gamma}} \frac{1}{\sqrt{2\pi}} \exp(-u^2/2)du$$

The zero-inflated link function is indicated by using the LINK= option in the ZEROMODEL statement. The default ZI link function is the logistic function.

Zero-Inflated Poisson Regression

In the zero-inflated Poisson (ZIP) regression model, the data generation process referred to earlier as Process 2 is

$$g(y_i) = \frac{\exp(-\mu_i)\mu_i^{y_i}}{y_i!}$$

where $\mu_i = e^{\mathbf{x}_i'\boldsymbol{\beta}}$. Thus the ZIP model is defined as

$$\begin{aligned} P(y_i = 0|\mathbf{x}_i, \mathbf{z}_i) &= F_i + (1-F_i)\exp(-\mu_i) \\ P(y_i|\mathbf{x}_i, \mathbf{z}_i) &= (1-F_i)\frac{\exp(-\mu_i)\mu_i^{y_i}}{y_i!}, \quad y_i > 0 \end{aligned}$$

The conditional expectation and conditional variance of y_i are given by

$$E(y_i|\mathbf{x}_i, \mathbf{z}_i) = \mu_i(1-F_i)$$

$$V(y_i|\mathbf{x}_i, \mathbf{z}_i) = E(y_i|\mathbf{x}_i, \mathbf{z}_i)(1+\mu_i F_i)$$

Note that the ZIP model (in addition to the ZINB model) exhibits overdispersion since $V(y_i|\mathbf{x}_i, \mathbf{z}_i) > E(y_i|\mathbf{x}_i, \mathbf{z}_i)$.

In general, the log-likelihood function of the ZIP model is

$$\mathcal{L} = \sum_{i=1}^{N} \ln\left[P(y_i|\mathbf{x}_i, \mathbf{z}_i)\right]$$

Once a specific link function (either logistic or standard normal) for the probability φ_i is chosen, it is possible to write the exact expressions for the log-likelihood function and the gradient.

ZIP Model with Logistic Link Function

First, consider the ZIP model in which the probability φ_i is expressed with a logistic link function, namely

$$\varphi_i = \frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{1 + \exp(\mathbf{z}_i'\boldsymbol{\gamma})}$$

The log-likelihood function is

$$\begin{aligned}\mathcal{L} &= \sum_{\{i:y_i=0\}} \ln\left[\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + \exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))\right] \\ &\quad + \sum_{\{i:y_i>0\}} \left[y_i\mathbf{x}_i'\boldsymbol{\beta} - \exp(\mathbf{x}_i'\boldsymbol{\beta}) - \sum_{k=2}^{y_i}\ln(k)\right] \\ &\quad - \sum_{i=1}^{N} \ln\left[1 + \exp(\mathbf{z}_i'\boldsymbol{\gamma})\right]\end{aligned}$$

The gradient for this model is given by

$$\frac{\partial\mathcal{L}}{\partial\boldsymbol{\gamma}} = \sum_{\{i:y_i=0\}} \left[\frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + \exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\right]\mathbf{z}_i - \sum_{i=1}^{N}\left[\frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{1 + \exp(\mathbf{z}_i'\boldsymbol{\gamma})}\right]\mathbf{z}_i$$

$$\frac{\partial\mathcal{L}}{\partial\boldsymbol{\beta}} = \sum_{\{i:y_i=0\}} \left[\frac{-\exp(\mathbf{x}_i'\boldsymbol{\beta})\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}{\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + \exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\right]\mathbf{x}_i + \sum_{\{i:y_i>0\}}\left[y_i - \exp(\mathbf{x}_i'\boldsymbol{\beta})\right]\mathbf{x}_i$$

ZIP Model with Standard Normal Link Function

Next, consider the ZIP model in which the probability φ_i is expressed with a standard normal link function: $\varphi_i = \Phi(\mathbf{z}_i'\boldsymbol{\gamma})$. The log-likelihood function is

$$\begin{aligned}\mathcal{L} &= \sum_{\{i:y_i=0\}} \ln\left\{\Phi(\mathbf{z}_i'\boldsymbol{\gamma}) + \left[1 - \Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))\right\} \\ &\quad + \sum_{\{i:y_i>0\}} \left\{\ln\left[\left(1 - \Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right)\right] - \exp(\mathbf{x}_i'\boldsymbol{\beta}) + y_i\mathbf{x}_i'\boldsymbol{\beta} - \sum_{k=2}^{y_i}\ln(k)\right\}\end{aligned}$$

The gradient for this model is given by

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \boldsymbol{\gamma}} &= \sum_{\{i:y_i=0\}} \frac{\varphi(\mathbf{z}_i'\boldsymbol{\gamma})\left[1-\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))\right]}{\Phi(\mathbf{z}_i'\boldsymbol{\gamma})+\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\mathbf{z}_i \\ &- \sum_{\{i:y_i>0\}} \frac{\varphi(\mathbf{z}_i'\boldsymbol{\gamma})}{\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]}\mathbf{z}_i\end{aligned}$$

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \boldsymbol{\beta}} &= \sum_{\{i:y_i=0\}} \frac{-\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\exp(\mathbf{x}_i'\boldsymbol{\beta})\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}{\Phi(\mathbf{z}_i'\boldsymbol{\gamma})+\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\exp(-\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\mathbf{x}_i \\ &+ \sum_{\{i:y_i>0\}} \left[y_i-\exp(\mathbf{x}_i'\boldsymbol{\beta})\right]\mathbf{x}_i\end{aligned}$$

Zero-Inflated Negative Binomial Regression

The zero-inflated negative binomial (ZINB) model in PROC HPCOUNTREG is based on the negative binomial model with quadratic variance function (when DIST=NEGBIN in the MODEL or PROC HPCOUNTREG statement). The ZINB model is obtained by specifying a negative binomial distribution for the data generation process referred to earlier as Process 2:

$$g(y_i) = \frac{\Gamma(y_i+\alpha^{-1})}{y_i!\Gamma(\alpha^{-1})}\left(\frac{\alpha^{-1}}{\alpha^{-1}+\mu_i}\right)^{\alpha^{-1}}\left(\frac{\mu_i}{\alpha^{-1}+\mu_i}\right)^{y_i}$$

Thus the ZINB model is defined to be

$$\begin{aligned}P(y_i=0|\mathbf{x}_i,\mathbf{z}_i) &= F_i+(1-F_i)\left(1+\alpha\mu_i\right)^{-\alpha^{-1}} \\ P(y_i|\mathbf{x}_i,\mathbf{z}_i) &= (1-F_i)\frac{\Gamma(y_i+\alpha^{-1})}{y_i!\Gamma(\alpha^{-1})}\left(\frac{\alpha^{-1}}{\alpha^{-1}+\mu_i}\right)^{\alpha^{-1}} \\ &\times \left(\frac{\mu_i}{\alpha^{-1}+\mu_i}\right)^{y_i}, \quad y_i>0\end{aligned}$$

In this case, the conditional expectation and conditional variance of y_i are

$$E(y_i|\mathbf{x}_i,\mathbf{z}_i) = \mu_i(1-F_i)$$

$$V(y_i|\mathbf{x}_i,\mathbf{z}_i) = E(y_i|\mathbf{x}_i,\mathbf{z}_i)\left[1+\mu_i(F_i+\alpha)\right]$$

As with the ZIP model, the ZINB model exhibits overdispersion because the conditional variance exceeds the conditional mean.

ZINB Model with Logistic Link Function

In this model, the probability φ_i is given by the logistic function, namely

$$\varphi_i = \frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{1+\exp(\mathbf{z}_i'\boldsymbol{\gamma})}$$

The log-likelihood function is

$$\begin{aligned}
\mathcal{L} &= \sum_{\{i:y_i=0\}} \ln\left[\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + (1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}\right] \\
&+ \sum_{\{i:y_i>0\}} \sum_{j=0}^{y_i-1} \ln(j+\alpha^{-1}) \\
&+ \sum_{\{i:y_i>0\}} \left\{-\ln(y_i!) - (y_i+\alpha^{-1})\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) + y_i\ln(\alpha) + y_i\mathbf{x}_i'\boldsymbol{\beta}\right\} \\
&- \sum_{i=1}^{N} \ln\left[1+\exp(\mathbf{z}_i'\boldsymbol{\gamma})\right]
\end{aligned}$$

The gradient for this model is given by

$$\begin{aligned}
\frac{\partial\mathcal{L}}{\partial\boldsymbol{\gamma}} &= \sum_{\{i:y_i=0\}} \left[\frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + (1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}}\right]\mathbf{z}_i \\
&- \sum_{i=1}^{N} \left[\frac{\exp(\mathbf{z}_i'\boldsymbol{\gamma})}{1+\exp(\mathbf{z}_i'\boldsymbol{\gamma})}\right]\mathbf{z}_i
\end{aligned}$$

$$\begin{aligned}
\frac{\partial\mathcal{L}}{\partial\boldsymbol{\beta}} &= \sum_{\{i:y_i=0\}} \left[\frac{-\exp(\mathbf{x}_i'\boldsymbol{\beta})(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}-1}}{\exp(\mathbf{z}_i'\boldsymbol{\gamma}) + (1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}}\right]\mathbf{x}_i \\
&+ \sum_{\{i:y_i>0\}} \left[\frac{y_i - \exp(\mathbf{x}_i'\boldsymbol{\beta})}{1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})}\right]\mathbf{x}_i
\end{aligned}$$

$$\frac{\partial\mathcal{L}}{\partial\alpha} = \sum_{\{i:y_i=0\}} \frac{\alpha^{-2}\left[(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) - \alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})\right]}{\exp(\mathbf{z}_i'\boldsymbol{\gamma})(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{(1+\alpha)/\alpha} + (1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))}$$

$$+ \sum_{\{i:y_i>0\}} \left\{-\alpha^{-2}\sum_{j=0}^{y_i-1}\frac{1}{(j+\alpha^{-1})} + \alpha^{-2}\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) + \frac{y_i-\exp(\mathbf{x}_i'\boldsymbol{\beta})}{\alpha(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\right\}$$

ZINB Model with Standard Normal Link Function

For this model, the probability φ_i is specified with the standard normal distribution function (probit function): $\varphi_i = \Phi(\mathbf{z}_i'\boldsymbol{\gamma})$. The log-likelihood function is

$$\begin{aligned}
\mathcal{L} &= \sum_{\{i:y_i=0\}} \ln\left\{\Phi(\mathbf{z}_i'\boldsymbol{\gamma}) + \left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right](1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}\right\} \\
&+ \sum_{\{i:y_i>0\}} \ln\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right] \\
&+ \sum_{\{i:y_i>0\}} \sum_{j=0}^{y_i-1} \left\{\ln(j+\alpha^{-1})\right\} \\
&- \sum_{\{i:y_i>0\}} \ln(y_i!) \\
&- \sum_{\{i:y_i>0\}} (y_i+\alpha^{-1})\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) \\
&+ \sum_{\{i:y_i>0\}} y_i\ln(\alpha) \\
&+ \sum_{\{i:y_i>0\}} y_i\mathbf{x}_i'\boldsymbol{\beta}
\end{aligned}$$

The gradient for this model is given by

$$\frac{\partial\mathcal{L}}{\partial\boldsymbol{\gamma}} = \sum_{\{i:y_i=0\}} \left[\frac{\varphi(\mathbf{z}_i'\boldsymbol{\gamma})\left[1-(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}\right]}{\Phi(\mathbf{z}_i'\boldsymbol{\gamma}) + \left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right](1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}}\right]\mathbf{z}_i$$

$$- \sum_{\{i:y_i>0\}} \left[\frac{\varphi(\mathbf{z}_i'\boldsymbol{\gamma})}{1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})}\right]\mathbf{z}_i$$

$$\frac{\partial\mathcal{L}}{\partial\boldsymbol{\beta}} = \sum_{\{i:y_i=0\}} \frac{-\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\exp(\mathbf{x}_i'\boldsymbol{\beta})(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-(1+\alpha)/\alpha}}{\Phi(\mathbf{z}_i'\boldsymbol{\gamma}) + \left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right](1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{-\alpha^{-1}}}\mathbf{x}_i$$

$$+ \sum_{\{i:y_i>0\}} \left[\frac{y_i-\exp(\mathbf{x}_i'\boldsymbol{\beta})}{1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})}\right]\mathbf{x}_i$$

$$\frac{\partial\mathcal{L}}{\partial\alpha} = \sum_{\{i:y_i=0\}} \frac{\left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right]\alpha^{-2}\left[(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) - \alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})\right]}{\Phi(\mathbf{z}_i'\boldsymbol{\gamma})(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))^{(1+\alpha)/\alpha} + \left[1-\Phi(\mathbf{z}_i'\boldsymbol{\gamma})\right](1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))}$$

$$+ \sum_{\{i:y_i>0\}} \left\{-\alpha^{-2}\sum_{j=0}^{y_i-1}\frac{1}{(j+\alpha^{-1})} + \alpha^{-2}\ln(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta})) + \frac{y_i-\exp(\mathbf{x}_i'\boldsymbol{\beta})}{\alpha(1+\alpha\exp(\mathbf{x}_i'\boldsymbol{\beta}))}\right\}$$

Computational Resources

The time and memory required by PROC HPCOUNTREG are proportional to the number of parameters in the model and the number of observations in the data set being analyzed. Less time and memory are required for smaller models and fewer observations. When PROC HPCOUNTREG is run in the high-performance distributed environment, the amount of time required is also affected by the number of nodes and the number of threads per node as specified in the PERFORMANCE statement.

The method chosen to calculate the variance-covariance matrix and the optimization method also affect the time and memory resources. All optimization methods available through the METHOD= option have similar memory use requirements. The processing time might differ for each method depending on the number of iterations and functional calls needed. The data set is read into memory to save processing time. If not enough memory is available to hold the data, the HPCOUNTREG procedure stores the data in a utility file on disk and rereads the data as needed from this file. When this occurs, the execution time of the procedure increases substantially. The gradient and the variance-covariance matrix must be held in memory. If the model has p parameters including the intercept, then at least $8 * (p + p * (p + 1)/2)$ bytes are needed. The processing time is also a function of the number of iterations needed to converge to a solution for the model parameters. The number of iterations needed cannot be known in advance. You can use the MAXITER= option to limit the number of iterations that PROC HPCOUNTREG executes. You can alter the convergence criteria by using nonlinear optimization options available in the PROC HPCOUNTREG statement. For a list of all the nonlinear optimization options, see Chapter 6, "Nonlinear Optimization Methods" (*SAS/ETS User's Guide*).

Nonlinear Optimization Options

PROC HPCOUNTREG uses the nonlinear optimization (NLO) subsystem to perform nonlinear optimization tasks. In the PROC HPCOUNTREG statement, you can specify nonlinear optimization options that are then passed to the NLO subsystem. For a list of all the nonlinear optimization options, see Chapter 6, "Nonlinear Optimization Methods" (*SAS/ETS User's Guide*).

Covariance Matrix Types

The COVEST= option in the PROC HPCOUNTREG statement enables you to specify the estimation method for the covariance matrix. COVEST=HESSIAN estimates the covariance matrix based on the inverse of the Hessian matrix; COVEST=OP uses the outer product of gradients; and COVEST=QML produces the covariance matrix based on both the Hessian and outer product matrices. Although all three methods produce asymptotically equivalent results, they differ in computational intensity and produce results that might differ in finite samples. The COVEST=OP option provides the covariance matrix that is typically the easiest to compute. In some cases, the OP approximation is considered more efficient than the Hessian or QML approximations because it contains fewer random elements. The QML approximation is computationally the most complex because both the outer product of gradients and the Hessian matrix are required. In most cases, OP or Hessian approximations are preferred to QML. The need to use QML approximation arises in some cases when the model is misspecified and the information matrix equality does not hold. The default is COVEST=HESSIAN.

Displayed Output

PROC HPCOUNTREG produces the following displayed output.

Iteration History for Parameter Estimates

If you specify the ITPRINT or PRINTALL options in the PROC HPCOUNTREG statement, PROC HPCOUNTREG displays a table that contains the following for each iteration. Some information is specific to the model fitting procedure chosen, as indicated.

- iteration number
- number of restarts since the fitting began
- number of function calls
- number of active constraints at the current solution
- value of the objective function (–1 times the log-likelihood value) at the current solution
- change in the objective function from the previous iteration
- value of the maximum absolute gradient element
- step size (for Newton-Raphson and quasi-Newton methods)
- slope of the current search direction (for Newton-Raphson and quasi-Newton methods)
- lambda (for trust region method)
- radius value at current iteration (for trust region method)

Model Fit Summary

The "Model Fit Summary" table contains the following information:

- dependent (count) variable name
- number of observations used
- number of missing values in data set, if any
- data set name
- type of model that was fit
- offset variable name, if any
- zero-inflated link function, if any
- zero-inflated offset variable name, if any

- log-likelihood value at solution
- maximum absolute gradient at solution
- number of iterations
- AIC value at solution (smaller value indicates better fit)
- SBC value at solution (smaller value indicates better fit)

A line in the "Model Fit Summary" table indicates whether the algorithm successfully converged.

Parameter Estimates

The "Parameter Estimates" table in the displayed output gives the estimates for the ZI intercept and ZI explanatory variables; they are labeled with the prefix "Inf_". For example, the ZI intercept is labeled "Inf_intercept". If you specify "Age" (a variable in your data set) as a ZI explanatory variable, then the "Parameter Estimates" table labels the corresponding parameter estimate "Inf_Age". If you do not list any ZI explanatory variables (for the ZI option VAR=), then only the intercept term is estimated.

"_Alpha" is the negative binomial dispersion parameter. The t statistic given for "_Alpha" is a test of overdispersion.

Last Evaluation of the Gradient

If you specify the ITPRINT option in the PROC HPCOUNTREG or MODEL statement, the HPCOUNTREG procedure displays the last evaluation of the gradient vector.

Covariance of Parameter Estimates

If you specify the COVB option in the PROC HPCOUNTREG or MODEL statement, the HPCOUNTREG procedure displays the estimated covariance matrix, which is defined as the inverse of the information matrix at the final iteration.

Correlation of Parameter Estimates

If you specify the CORRB option in the PROC HPCOUNTREG or MODEL statement, the HPCOUNTREG procedure displays the estimated correlation matrix, which is based on the Hessian matrix used at the final iteration.

OUTPUT OUT= Data Set

The OUTPUT statement creates a new SAS data set that contains various estimates that you specify. You can request that the output data set contain the estimates of $\mathbf{x}_i'\boldsymbol{\beta}$, the expected value of the response variable, and the probability of the response variable taking on the current value. Furthermore, if a zero-inflated model is fit, you can request that the output data set contain the estimates of $\mathbf{z}_i'\boldsymbol{\gamma}$ and the probability that the response is 0 as a result of the zero-generating process. These statistics can be computed for all observations in which the regressors are not missing, even if the response is missing. By adding observations with missing response values to the input data set, you can compute these statistics for new observations or for settings

of the regressors that are not present in the data without affecting the model fit. Due to potential space limitations on the client workstation, the data set created by the OUTPUT statement does not contain the variables in the input data set.

OUTEST= Data Set

The OUTEST= data set is made up of at least two rows: the first row (with _TYPE_='PARM') contains each of the parameter estimates in the model, and the second row (with _TYPE_='STD') contains the standard errors for the parameter estimates in the model.

If you use the COVOUT option in the PROC HPCOUNTREG statement, the OUTEST= data set also contains the covariance matrix for the parameter estimates. The covariance matrix appears in the observations with _TYPE_='COV', and the _NAME_ variable labels the rows with the parameter names.

ODS Table Names

PROC HPCOUNTREG assigns a name to each table it creates. You can use these names to denote the table when you use the Output Delivery System (ODS) to select tables and create output data sets. These names are listed in Table 9.2.

Table 9.2 ODS Tables Produced in PROC HPCOUNTREG

ODS Table Name	Description	Option
ODS Tables Created by the MODEL Statement		
FitSummary	Summary of nonlinear estimation	Default
ConvergenceStatus	Convergence status	Default
ParameterEstimates	Parameter estimates	Default
CovB	Covariance of parameter estimates	COVB
CorrB	Correlation of parameter estimates	CORRB
InputOptions	Input options	ITPRINT
IterStart	Optimization start	ITPRINT
IterHist	Iteration history	ITPRINT
IterStop	Optimization results	ITPRINT
ParameterEstimatesResults	Parameter estimates	ITPRINT
ParameterEstimatesStart	Parameter estimates	ITPRINT
ProblemDescription	Problem description	ITPRINT

Examples: The HPCOUNTREG Procedure

Example 9.1: High-Performance Zero-Inflated Poisson Model

This example shows the use of the HPCOUNTREG procedure with an emphasis on large data set processing and the performance improvements that are achieved by executing in the high-performance distributed environment.

The following DATA step generates one million replicates from the zero-inflated Poisson (ZIP) model. The model contains seven variables and three variables that correspond to the zero-inflated process.

```
data simulate;
   call streaminit(12345);
   array vars x1-x7;
   array zero_vars z1-z3;

   array parms{7}  (.3 .4 .2 .4 -.3 -.5 -.3);
   array zero_parms{3} (-.6 .3 .2);

   intercept=2;
   z_intercept=-1;
   theta=0.5;

   do i=1 to 1000000;
      sum_xb=0;
      sum_gz=0;
      do j=1 to 7;
         vars[j]=rand('NORMAL',0,1);
         sum_xb=sum_xb+parms[j]*vars[j];
      end;
      mu=exp(intercept+sum_xb);
      y_p=rand('POISSON', mu);

      do j=1 to 3;
         zero_vars[j]=rand('NORMAL',0,1);
         sum_gz = sum_gz+zero_parms[j]*zero_vars[j];
      end;
      z_gamma = z_intercept+sum_gz;
      pzero = cdf('LOGISTIC',z_gamma);
      cut=rand('UNIFORM');
      if cut<pzero then y_p=0;
      output;
   end;
keep y_p x1-x7 z1-z3;
run;
```

The following statements estimate a zero-inflated Poisson model. The model is executed in the distributed computing environment with two threads and only one node. These settings are used to obtain a hypothetical environment that might resemble running the HPCOUNTREG procedure on a desktop workstation with a dual core CPU. To run these statements successfully, you need to set the macro variables GRIDHOST

and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to the macro variables in the example with the appropriate values.

```
   option set=GRIDHOST="&GRIDHOST";
   option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";

proc hpcountreg data=simulate dist=zip;
   performance nthreads=2 nodes=1 details;
   model y_p=x1-x7;
   zeromodel y_p ~ z1-z3;
run;
```

Output 9.1.1 shows the results for the zero-inflated Poisson model. The "Performance Information" table shows that the model was estimated on the grid defined in a macro variable named GRIDHOST in a distributed environment on only one node and that two threads were employed. The "Model Fit Summary" table shows detailed information about the model and indicates that all one million observations were used to fit the model. All parameter estimates in the "Parameter Estimates" table are highly significant and correspond to their theoretical values set during the data generating process. The optimization of the model with one million observations took 81.94 seconds.

Output 9.1.1 Zero-Inflated Poisson Model with One Node and Two Threads

The HPCOUNTREG Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	1
Number of Threads per Node	2

Model Fit Summary

Dependent Variable	y_p
Number of Observations	1000000
Data Set	WORK.SIMULATE
Model	ZIP
ZI Link Function	Logistic
Log Likelihood	-2215238
Maximum Absolute Gradient	2.04436E-8
Number of Iterations	7
Optimization Method	Newton-Raphson
AIC	4430500
SBC	4430642

Convergence criterion (FCONV=2.220446E-16) satisfied.

Output 9.1.1 *continued*

Parameter Estimates

Effect	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	2.0005	0.000492	4069.80	<.0001
x1	1	0.2995	0.000352	850.17	<.0001
x2	1	0.3998	0.000353	1132.23	<.0001
x3	1	0.2008	0.000352	570.27	<.0001
x4	1	0.3994	0.000353	1132.85	<.0001
x5	1	-0.2995	0.000353	-848.95	<.0001
x6	1	-0.5000	0.000353	-1414.9	<.0001
x7	1	-0.3002	0.000352	-852.14	<.0001
Inf_Intercept	1	-0.9993	0.002521	-396.45	<.0001
Inf_z1	1	-0.6024	0.002585	-233.02	<.0001
Inf_z2	1	0.2976	0.002454	121.25	<.0001
Inf_z3	1	0.1974	0.002430	81.20	<.0001

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	0.67	0.81%
Communication to client	0.03	0.04%
Optimization	81.94	98.8%
Post-optimization	0.30	0.37%

In the following statements, the PERFORMANCE statement is modified to use a grid with 10 nodes, with each node capable of spawning eight threads:

```
proc hpcountreg data=simulate dist=zip;
   performance nthreads=8 nodes=10 details;
   model y_p=x1-x7;
   zeromodel y_p ~ z1-z3;
run;
```

Since the two models being estimated are identical, it is reasonable to expect that Output 9.1.1 and Output 9.1.2 would show the same results. However, you can see a significant difference in performance. The second model which was run on a grid using 10 nodes with eight threads each, took only 3.28 seconds instead of 81.94 seconds to optimize.

In certain circumstances, you might observe slight numerical differences in the results, depending on the number of nodes and threads involved. This is a consequence of the fact that the order in which partial results are accumulated can make a difference in the final result, owing to the limits of numerical precision and the propagation of error in numerical computations.

Output 9.1.2 Zero-Inflated Poisson Model on 10 Nodes with Eight Threads Each

The HPCOUNTREG Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	10
Number of Threads per Node	8

Model Fit Summary

Dependent Variable	y_p
Number of Observations	1000000
Data Set	WORK.SIMULATE
Model	ZIP
ZI Link Function	Logistic
Log Likelihood	-2215238
Maximum Absolute Gradient	2.06085E-8
Number of Iterations	7
Optimization Method	Newton-Raphson
AIC	4430500
SBC	4430642

Convergence criterion (FCONV=2.220446E-16) satisfied.

Parameter Estimates

Effect	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	2.0005	0.000492	4069.80	<.0001
x1	1	0.2995	0.000352	850.17	<.0001
x2	1	0.3998	0.000353	1132.23	<.0001
x3	1	0.2008	0.000352	570.27	<.0001
x4	1	0.3994	0.000353	1132.85	<.0001
x5	1	-0.2995	0.000353	-848.95	<.0001
x6	1	-0.5000	0.000353	-1414.9	<.0001
x7	1	-0.3002	0.000352	-852.14	<.0001
Inf_Intercept	1	-0.9993	0.002521	-396.45	<.0001
Inf_z1	1	-0.6024	0.002585	-233.02	<.0001
Inf_z2	1	0.2976	0.002454	121.25	<.0001
Inf_z3	1	0.1974	0.002430	81.20	<.0001

Output 9.1.2 *continued*

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	0.05	1.46%
Communication to client	0.03	0.82%
Optimization	3.28	88.1%
Post-optimization	0.36	9.58%

As this example suggests, increasing the number of nodes and the number of threads per node improves performance significantly. When you use the parallelism afforded by a high-performance distributed environment, you can see an even more dramatic reduction in the time required for the optimization as the number of observations in the data set increases. When the data set is extremely large, the computations might not even be possible in some cases with the typical memory resources and computational constraints of a desktop computer. Under such circumstances the high-performance distributed environment becomes a necessity.

References

Cameron, A. C. and Trivedi, P. K. (1986), "Econometric Models Based on Count Data: Comparisons and Applications of Some Estimators and Some Tests," *Journal of Applied Econometrics*, 1, 29–53.

Cameron, A. C. and Trivedi, P. K. (1998), *Regression Analysis of Count Data*, Cambridge: Cambridge University Press.

LaMotte, L. R. (1994), "A Note on the Role of Independence in t Statistics Constructed from Linear Statistics in Regression Models," *The American Statistician*, 48, 238–240.

Long, J. S. (1997), *Regression Models for Categorical and Limited Dependent Variables*, Thousand Oaks, CA: Sage Publications.

Chapter 10
The HPDECIDE Procedure

Contents

Overview: HPDECIDE Procedure **173**
Getting Started: HPDECIDE Procedure **174**
Syntax: HPDECIDE Procedure **176**
PROC HPDECIDE Statement 177
CODE Statement 178
DECISION Statement 178
FREQ Statement 179
ID Statement 179
PERFORMANCE Statement 180
POSTERIORS Statement 180
PREDICTED Statement 180
TARGET Statement 181
Details: HPDECIDE Procedure **181**
Decision Matrix 181
Variables 181
Displayed Output 182
ODS Table Name 182
Examples: HPDECIDE Procedure **182**
Example 10.1: Using a Revenue Matrix and Cost Variables to Make Decisions 182
Example 10.2: Running with Client Data on the SAS Appliance 185

Overview: HPDECIDE Procedure

The HPDECIDE procedure creates optimal decisions that are based on a decision matrix that you specify, on prior probabilities, and on output from a modeling procedure. This output can be either posterior probabilities for a categorical target variable or predicted values for an interval target variable. The HPDECIDE procedure can also adjust the posterior probabilities for changes in the prior probabilities.

Some modeling procedures assume that the prior probabilities for categorical variable level membership either are all equal or are proportional to the relative frequency of the corresponding response level in the data set. PROC HPDECIDE enables you to specify other prior probabilities. Thus, you can conduct a sensitivity analysis without running the modeling procedure again.

The HPDECIDE procedure can exploit computer grids by running in parallel independently on different grid nodes, while multithreading is supported at each node. See the section "SMP and MPP Modes" on

page 16 in Chapter 3, "Shared Concepts and Topics," for more information about the execution of SAS High-Performance Analytics procedures on a grid of computers.

Getting Started: HPDECIDE Procedure

The HPDECIDE procedure can adjust posterior probabilities from a modeling procedure to make decisions. This fictitious example shows how to use the HPDECIDE procedure to adjust posterior probabilities from the DISCRIM procedure, and how to use a revenue matrix and cost constants to make decisions.

In a population of men who consult urologists for prostate problems, 70% have benign enlargement of the prostate, 25% have an infection, and 5% have cancer. A sample of 100 men is taken, and two new diagnostic measures, X and Y, are made on each patient. The training set also includes the diagnosis made by reliable, conventional methods. For each patient, three treatments are available: antibiotics, surgery, or no treatment. Antibiotics are effective against infection, but they might have moderately bad side effects. Antibiotics have no effect on benign enlargement or cancer. Surgery is effective for all diseases but has potentially severe side effects such as impotence.

The first step is to create the sample of 100 men. To simulate the measurements of diagnostics X and Y, this example uses the SAS random number generator. Because you specify the initial seed to the random number generator, all your results will be identical to those presented in this example.

The following statements create the Prostate data set. The first 70 observations represent benign tumors, the next 25 represent infections, and the final 5 represent cancer.

```
data Prostate;
    length dx $14;
    dx='Benign';
    mx=30; sx=10;
    my=30; sy=10;
    n=70;
    link generate;
    dx='Infection';
    mx=70; sx=20;
    my=35; sy=15;
    n=25;
    link generate;
    dx='Cancer';
    mx=50; sx=10;
    my=50; sy=15;
    n=5;
    link generate;
    stop;
generate:
    do i=1 to n;
    x=rannor(12345)*sx+mx;
    y=rannor(0) *sy+my;
    output;
    end;
run;
```

The following statements run the DISCRIM procedure, which assumes that all prior probabilities are equal (1/3 for this example). In this example, the DISCRIM procedure misidentifies some of the benign tumors as cancer or an infection. Also, it misidentifies some of the infections as benign tumors.

```
proc discrim data=prostate out=outdis short;
    class dx;
    var x y;
run;
```

Because PROC DISCRIM misidentifies some of the data, you want to create a data set that contains prior probabilities and revenue information. The revenue information indicates the benefit of each treatment. The cost of each treatment, such as bad side effects, will be specified later in a DECISION statement. The following DATA step creates the revenue matrix:

```
data rx(type=revenue);
    input dx $14. eqprior prior nothing antibiot surgery;
    datalines;
    Benign        0.3333 70 0 0 5
    Infection     0.3333 25 0 10 10
    Cancer        0.3333 5 0 0 100
;
```

The variable eqprior defines an equal prior probability for each diagnosis, and the variable prior uses information that is known from the sample data set. The other variables define the revenue of each treatment option. The revenue (benefit) of doing nothing in either case is 0, and the benefit of taking antibiotics is relevant only if the patient has an infection. Surgery can remove a benign tumor; but it has very little benefit because it is not necessary. Surgery completely removes an infection, so it has the same value as antibiotics. Finally, surgery can remove a cancerous tumor, which is an immense benefit to the patient.

You can now use the HPDECIDE procedure to assign a treatment to each patient. In the DECISION statement, you specify the costs of treatment. The cost of doing nothing is 0, the cost of antibiotics is 5, and the cost of surgery is 20.

```
proc hpdecide data=outdis out=decOut outstat=decSum;
    target dx;
    posteriors benign infection cancer;
    decision decdata=rx
    oldpriorvar=eqprior priorvar=prior
        decvars=nothing antibiot surgery
        cost= 0 5 20;
run;

proc print data=decSum;
run;
```

Output 10.1 shows the fit statistics information.

Figure 10.1 Fit Statistics

Obs	_PROF_	_APROF_
1	470	4.7

The data set decOut indicates that only one benign tumor was misidentified, but the number of infections that were misidentified as benign is similar to the results from the DISCRIM procedure. All of the cancerous tumors were identified and assigned the treatment of surgery, as was the lone misidentified benign tumor. The total profit for all patients, identified in the data set decSum is 470.

Due to the personal nature of medical decisions, the costs associated with each treatment can vary considerably from patient to patient. Some patients regard the side effects of surgery as more severe than other patients. Likewise, the costs of antibiotics might vary due to the patients' insurance plans. The following statements assume a higher cost for surgery and leave the other costs constant:

```
proc hpdecide data=outdis out=decOut2 outstat=decSum2;
    target dx;
    posteriors benign infection cancer;
    decision decdata=rx
    oldpriorvar=eqprior priorvar=prior
        decvars=nothing antibiot surgery
        cost= 0 5 50;
run;

proc print data=decSum2;
run;
```

Output 10.2 shows the fit statistics information with higher cost of surgery.

Figure 10.2 Fit Statistics with Higher Cost of Surgery

Obs	_PROF_	_APROF_
1	285	2.85

Notice that the misclassified benign tumor is now correctly classified. However, one of the cancer cases is identified as benign, which is a costly mistake. Notice in decOut that the total profit has been reduced from 470 to 285.

Syntax: HPDECIDE Procedure

The following statements are available in the HPDECIDE procedure:

PROC HPDECIDE < *options* > ;
ID *variables* ;
FREQ *variable* ;
PERFORMANCE *performance-options* ;
POSTERIORS *variables* ;
PREDICTED *variables* ;
TARGET *variable* ;
DECISION DECDATA=< *libref.* >*SAS-data-set* < *options* > ;
CODE < *options* > ;

PROC HPDECIDE Statement

PROC HPDECIDE < *options* > **;**

The PROC HPDECIDE statement invokes the procedure and identifies the input and output data sets. You also need the following statements:

- DECISION statement
- either a POSTERIORS or a PREDICTED statement
- TARGET statement

You can specify the following *options* in the PROC HPDECIDE statement:

DATA=< *libref.***>***SAS-data-set*

specifies the input data set that contains the output from a modeling procedure. The default is the most recently created data set. If the data are already distributed, PROC HPDECIDE reads the data alongside the distributed database. See the section "SMP and MPP Modes" on page 16 for the various execution modes and the section "Alongside-the-Database Execution" on page 22 for the alongside-the-database model.

OUT=< *libref.***>***SAS-data-set*

specifies the output data set, which always contains any variables from the input data set that is specified in the ID statement, the chosen decision (with a prefix of D_), and the expected consequence of the chosen decision (with a prefix of either EL_ or EP_).

If the target value is in the input data set, then the output data set also contains the following variables: the consequence of the chosen decision (which is computed from the target value and has a prefix of either CL_ or CP_) and the consequence of the best possible decision when the target value is known (this variable has a prefix of either BL_ or BP_).

If the profit matrix is revenue, then the output data set also contains the following variables: the investment cost (with a prefix of IC_) and the return on investment (with a prefix of ROI_).

Additionally, if the PRIORVAR= and OLDPRIORVAR= variables are specified, then this data set contains the recalculated posterior probabilities. The default name for this data set is data_n, where n is the smallest integer that is not already used to name a data set.

OUTFIT=< *libref.***>***SAS-data-set*

specifies an output data set to contain fit statistics. These statistics include the total and average profit or loss. You cannot specify this option when ROLE=SCORE. By default, this data set is not created.

ROLE=TRAIN | VALID | VALIDATION | TEST | SCORE

specifies the role of the input data set. This option affects the variables that are created in the DATA= data set. The default value is TEST. You can specify the following values:

TRAIN	specifies that the role of the input data set is training.
VALIDATION	specifies that the role of the input data set is validation.
TEST	specifies that the role of the input data set is testing.
SCORE	specifies that the role of the input data set is scoring.

CODE Statement

CODE < *options* > **;**

The CODE statement generates SAS DATA step code that can be used to score data sets. If neither the FILE= option nor the METABASE= option is specified, then the SAS code is written to the SAS log. You can specify both the FILE= option and the METABASE= option to write code to both locations. The target variable must appear both in the data set specified in the DATA= option in the PROC HPDECIDE statement and in the data set specified in the DECDATA= option in the DECISION statement.

FILE=*file-name*
names the file into which score code is saved.

METABASE=*catalog-spec*
specifies a catalog entry to contain the SAS score code. For example, you can specify METABASE=*myLibrary.myCatalog.catalog-entry*.

RESIDUAL
computes the variables that depend on the target variable in the score code.

DECISION Statement

DECISION DECDATA=< *libref.* >*SAS-data-set* < *options* > **;**

Required Argument

DECDATA=< *libref.* **>***SAS-data-set***<** *(type)* **>**
names the input data set that contains the decision matrix or the prior probabilities, or both. This argument is required.

The named data set must contain the target variable, which is specified in the TARGET statement. It might also contain decision variables that are specified in the DECVARS= option and prior probability variables that are specified with the PRIORVAR= option, the OLDPRIORVAR= option, or both.

For a categorical target variable, there should be one observation for each class. Each entry d_{ij} in the decision matrix indicates the consequence of selecting target value *i* for variable *j*. If any class appears twice or more in this data set, an error message is printed and the PROC HPDECIDE terminates. Any class value in the input data set that is not found in this data set is treated as a missing class value. The classes in this data set must correspond exactly to the variables in the POSTERIORS statement.

For an interval target variable, each row defines a knot in a piecewise linear spline function. The consequence of making a decision is computed by interpolation in the corresponding column of the decision matrix. If the predicted target value is outside the range of knots in the decision matrix, the consequence is computed by linear extrapolation. If the target values are monotonically increasing or decreasing, any interior target value is allowed to appear twice in data set. This enables you to specify discontinuities in the data. No target value is allowed to appear more than twice. If the target values are not monotonic, then they are sorted by PROC HPDECIDE and are not allowed to appear more than once.

The data set option *type* is specified in parentheses after the data set name when the data set is created or used. The possible values of *type* are LOSS, PROFIT, and REVENUE; the default is PROFIT.

Optional Arguments

You can specify the following *options*:

DECVARS=*variables*
specifies the numeric decision variables in the DECDATA= data set that contain the target-specific consequences for each decision. The decision variables cannot contain any missing values.

COST=*list-of-costs*
specifies the numeric constants that give the cost of a decision, the numeric variables in the input data set that contain case-specific costs, or any combination of constants and variables.

The number of cost constants and variables and the number of decision variables in the DECVARS= option must be the same. You cannot use abbreviated variable lists. For any observation in which a cost variable is missing, the results for that observation are considered missing. By default, all costs are assumed to be 0. You can specify this option only when *type* is REVENUE.

PRIORVAR=*variable*
specifies the number variable in the DECDATA= data set that contains the prior probabilities that are used to make decisions. Prior probabilities are also used to adjust the total and average profit or loss. Prior probabilities cannot be missing or negative, and there must be at least one positive prior probability. The prior probabilities are not required to sum 1. But if they do not sum to 1, then they are scaled by some constant so that they do sum to 1. If you do not specify this option, then no adjustment for prior probabilities is applied to the posterior probabilities.

OLDPRIORVAR=*variable*
specifies the numeric variable in the DECDATA= data set that contains the prior probabilities that were used the first time the model was fit. If you specify this option, then you must also specify the PRIORVAR= option.

FREQ Statement

FREQ *variable* **;**

The FREQ statement specifies a single numeric variable whose value represents the frequency of each observation. If you use the FREQ statement, the HPDECIDE procedure treats the data set as if each observation appeared *n* times, where *n* is the value of the FREQ variable. The FREQ variable has no effect on decisions of the adjustment for prior probabilities. It affects only the summary statistics in the OUTFIT= data set. If a value of the FREQ variable is not an integer, then the fractional part is not truncated. If a value of the FREQ variable is less than or equal to 0, then the observation does not contribute to the summary statistics. However, all the variables in the OUT= data set are processed as if the FREQ variable were positive.

ID Statement

ID *variables* **;**

The ID statement lists one or more variables from the input data set that are transferred to the output data set, provided that the output data set produces one (or more) records per input observation. By default, the HPDECIDE procedure does not include any variables from the input data set in the output data sets.

For documentation about the common ID statement in SAS High-Performance Analytics procedures, see the section "ID Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPDECIDE procedure.

With the PERFORMANCE statement, you can also control whether the HPDECIDE procedure executes in symmetric multiprocessing or massively parallel mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

POSTERIORS Statement

POSTERIORS *variable-list* **;**

The POSTERIORS statement specifies a list of the numeric variables in the input data set that contain the estimated posterior probabilities that correspond to the categories of the target variable. If one of the following conditions is met, then an observation is set to missing and the variable _WARN_ contains the flag *P*:

- The posterior probability is missing, negative, or greater than 1.
- There is a nonzero posterior that corresponds to a zero posterior.
- There is not at least one valid positive posterior probability.

The order of the variables in the *variable-list* must correspond exactly to the order of the classes in the data set that is specified in the DECDATA= option in the DECISION statement.

PREDICTED Statement

PREDICTED *variable* **;**

The PREDICTED statement specifies the numeric variable in the input data set that contains the predicted values of an interval target variable. You can specify only an interval target variable in the PREDICTED statement. You cannot use both the POSTERIORS statement and the PREDICTED statement.

TARGET Statement

TARGET *variable* **;**

The TARGET statement specifies which variable is the target variable in the data set that is specified in the DECDATA= option in the DECISION statement. The TARGET statement is required.

The HPDECIDE procedure searches for a target variable with the same name in the input data set. If none is found, then the HPDECIDE procedure assumes that actual target values are unknown. For a categorical variable, the target variables in the data sets that are specified in the DATA= option in the PROC HPDECIDE statement and in the DECDATA= option in the DECISION statement do not need to be the same type because only the formatted values are used for comparisons. For an interval target, both variables must be numeric. If scoring code is generated by the CODE statement, the code formats the target variable with the format and length from the DATA= data set.

Details: HPDECIDE Procedure

Decision Matrix

The decision matrix contains columns (decision variables) that correspond to each decision and rows (observations) that correspond to target values. The values of the decision variables represent target-specific consequences, which might be profit, loss, or revenue. These consequences are the same for all cases being scored.

For each decision, there might also be either a cost variable or a numeric constant. The values of these variables represent case-specific consequences, which are always costs. These consequences do not depend on the target values of the cases being scored. Costs are used for computing return on investment as

$$\frac{revenue - cost}{cost}$$

Variables

Cost variables might be specified only if the decision data set contains revenue, not profit or loss. Therefore, if revenues and costs are specified, profits are computed as revenue minus cost. If revenues are specified without costs, the costs are assumed to be 0. The interpretation of consequences as profits, losses, revenues, and costs is needed only to compute return on investment. You can specify values in the decision data set that are target-specific consequences but that might have some practical interpretation other than profit, loss, or revenue. Likewise, you can specify values for the cost variables that are case-specific consequences but that might have some practical interpretation other than costs. If the revenue/cost interpretation is not applicable, the values computed for return on investment might not be meaningful.

The HPDECIDE procedure chooses the optimal decision for each observation. If the *type* of decision data set (as specified in the DECISION statement) is PROFIT or REVENUE, PROC HPDECIDE chooses the

decision that produces the maximum expected or estimated profit. If *type* is LOSS, PROC HPDECIDE chooses the decision that produces the minimum expected or estimated loss.

If the actual value of the target variable is known, the HPDECIDE procedure calculates the following:

- the consequence of the chosen decision for the actual target value for each case
- the best possible consequence for each case
- summary statistics that give the total and average profit or loss

Displayed Output

By default, the HPDECIDE procedure displays performance information in the "Performance Information" table. It displays information about the grid host for distributed execution, whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

ODS Table Name

Table 10.1 lists the name of the data table created by the HPDECIDE procedure. Use this name in ODS statements.

Table 10.1 ODS Table Produced by PROC HPDECIDE

Table Name	Description	Required Statement / Option
PerformanceInfo	Performance information	Default output

Examples: HPDECIDE Procedure

Example 10.1: Using a Revenue Matrix and Cost Variables to Make Decisions

This fictitious example demonstrates how to use PROC HPDECIDE to adjust posterior probabilities and how to use a revenue matrix and cost variables make decisions. In the following DATA steps, the categorical target variable tar has two levels in the data set data1: a and b.

```
data data1(drop=i);
    do i=1 to 5;
    tar="b";
    if i<3 then tar="a";
    p_a=abs(ranuni(81923));
```

```
    p_b=abs(1-p_a);
    c1=ranpoi(38192,5);
    c2=ranpoi(28131,7);
    output;
    end;
run;

data decdata1(type=revenue);
    input dv1-dv2 op np tar $;
    cards;
    5 3 .5 .2 a
    6 3 .5 .8 b
;

proc print data=data1;
run;

proc print data=decdata1;
run;
```

Output 10.1.1 shows the data1 data set.

Output 10.1.1 data1 Data Set

Obs	tar	p_a	p_b	c1	c2
1	a	0.68861	0.31139	5	9
2	a	0.71523	0.28477	5	4
3	b	0.48280	0.51720	7	5
4	b	0.33161	0.66839	1	3
5	b	0.62213	0.37787	9	5

Output 10.1.2 shows the decdata1 data set.

Output 10.1.2 decdata1 Data Set

Obs	dv1	dv2	op	np	tar
1	5	3	0.5	0.2	a
2	6	3	0.5	0.8	b

The estimated posterior probabilities that correspond to the categories of the target variable are denoted by p_a and p_b. The two cost variables, c1 and c2, represent the target-specific consequences for decision variables dv1 and dv2, respectively. The variable op contains the "old" prior probabilities that were used the first time the model was fictitiously fit. The variable np contains the "new" prior probabilities that are used to make decisions.

The following statements take the data set data1 and the data set decdata1, and output the data set out1 and the data set outstat1. The target variable is tar. Since the input data set resides on the client and no PERFORMANCE statement is specified, the client performs all computations.

```
proc hpdecide data=data1 out=out1 outstat=outstat1;
    decision decdata=decdata1 decvars=dv1-dv2
    oldpriorvar=op priorvar=np cost=c1 c2;
    posteriors p_a p_b;
    target tar;
run;

proc print data=out1;
var p_a p_b I_tar F_tar dv1 dv2 D_DECDATA1 EP_DECDATA1 CP_DECDATA1;
run;

proc print data=outstat1;
run;
```

Output 10.1.3 shows the out1 data set, which displays the decision for each observation. The adjusted posterior probabilities are also shown in the out1 data set.

Output 10.1.3 out1 Data Set

Obs	p_a	p_b	I_tar	F_tar	dv1	dv2	D_DECDATA1	EP_DECDATA1	CP_DECDATA1
1	0.35602	0.64398	B	A	0.64398	-6	dv1	0.64398	0
2	0.38571	0.61429	B	A	0.61429	-1	dv1	0.61429	0
3	0.18922	0.81078	B	B	-1.18922	-2	dv1	-1.18922	-1
4	0.11035	0.88965	B	B	4.88965	0	dv1	4.88965	5
5	0.29158	0.70842	B	B	-3.29158	-2	dv2	-2.00000	-2

Output 10.1.4 shows the outstat1 data set, which shows that the total profit is 2.6666666667 and the average profit is 0.5333333333, based on the decisions from the out1 data set.

Output 10.1.4 outstat1 Data Set

Obs	_PROF_	_APROF_
1	2.66667	0.53333

Output 10.1.5 shows the performance information.

Output 10.1.5 Performance Information

Performance Information

Execution Mode	On client

Example 10.2: Running with Client Data on the SAS Appliance

This example demonstrates how to use PROC HPDECIDE to make decisions when the decision data set's type is LOSS and the target is continuous. When the input data set resides on the client and a PERFORMANCE statement with a NODES= option is specified, as in the following statements, PROC HPDECIDE copies the data set to the SAS appliance, where the computation is performed.

```
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";

data data2;
    input tar   p;
    cards;
    0     1
    1     1
    2     2
    3     0
;

data decdata2(type=loss);
    input dv1 dv2 dv3  tar ;
    cards;
    0 0 3 0
    1 0 2 1
    0 2 1 2
    0 3 0 3
;

proc print data=data2;
run;

proc print data=decdata2;
run;
```

Output 10.2.1 shows the data2 data set.

Output 10.2.1 data2 Data Set

Obs	tar	p
1	0	1
2	1	1
3	2	2
4	3	0

Output 10.2.2 shows the decdata2 data set.

Output 10.2.2 decdata2 Data Set

Obs	dv1	dv2	dv3	tar
1	0	0	3	0
2	1	0	2	1
3	0	2	1	2
4	0	3	0	3

The following statements take as input the data2 and decdata2 data sets (which reside on the client) and output the out2 and outstat2 data sets. The decision variables are dv1, dv2, and dv3, and the target variable is tar. Because five grid nodes are specified in the PERFORMANCE statement, the input data sets are distributed from the client to the five grid nodes, which perform the computations and then write the output data sets back to the client.

```
proc hpdecide data=data2 out=out2 outstat=outstat2;
    decision decdata=decdata2 decvars=dv1-dv3;
    predicted p;
    target tar;
    performance details nodes=5;
run;

proc print data=out2;
run;

proc print data=outstat2;
run;
```

Output 10.2.3 shows the out2 data set, which displays the decision for each observation. For each observation, the continuous target variable was interpolated.

Output 10.2.3 out2 Data Set

Obs	p	dv1	dv2	dv3	D_DECDATA2	EL_DECDATA2	CL_DECDATA2	BL_DECDATA2	_WARN_
1	1	1	0	2	dv2	0	0	0	
2	1	1	0	2	dv2	0	0	0	
3	2	0	2	1	dv1	0	0	0	
4	0	0	0	3	dv1	0	0	0	

Output 10.2.4 shows the outstat2 data set, which shows that the total loss is 0 and that the average loss is 0, based on the decisions from the out2 data set.

Output 10.2.4 outstat2 Data Set

Obs	_LOSS_	_ALOSS_
1	0	0

Output 10.2.5 shows the performance information.

Output 10.2.5 Performance Information

Performance Information

Host Node	**<< your grid host >>**
Execution Mode	**Distributed**
Number of Compute Nodes	**5**

Chapter 11
The HPDMDB Procedure

Contents

Overview: HPDMDB Procedure **189**
Getting Started: HPDMDB Procedure **189**
Syntax: HPDMDB Procedure **192**
PROC HPDMDB Statement 192
CLASS Statement 193
FREQ Statement 194
PERFORMANCE Statement 194
VAR Statement 195
WEIGHT Statement 195
Details: HPDMDB Procedure **196**
Examples: HPDMDB Procedure **196**
Example 11.1: Running PROC HPDMDB on the Client 196
Example 11.2: Running with Client Data on the SAS Appliance 197
Example 11.3: Running with Data on the SAS Appliance 198

Overview: HPDMDB Procedure

The HPDMDB procedure is a high-performance version of the DMDB procedure, which creates summaries of the input data source. PROC HPDMDB creates two output data sets: the VAROUT data set, which contains a summary of the numeric variables, and the CLASSOUT data set, which contains a summary of the classification variables.

PROC HPDMDB is high-performance in that it takes advantage of distributed and multicore computing environments when the input data are stored on the SAS Appliance.

You can use PROC HPDMDB to create a data mining database (DMDB) that is compatible with the DMDB from PROC DMDB, although this feature of PROC HPDMDB might not be supported in future versions.

Getting Started: HPDMDB Procedure

The HPDMDB procedure summarizes data. The following example uses the Sampsio.Hmeq data set, which includes information about 5,960 fictitious mortgages. Each case represents an applicant for a home equity loan, and all applicants have an existing mortgage. The binary target variable BAD indicates whether an

applicant eventually defaulted or was ever seriously delinquent. There are 10 numeric input variables and three classification input variables.

```
proc hpdmdb data=Sampsio.Hmeq
    classout=cout varout=vout;

    var loan derog mortdue value yoj delinq
        clage ninq clno debtinc;
    class bad(desc) reason(ascending) job;
run;

proc print data=cout;run;
proc print data=vout;run;
```

The data set cout (shown in Figure 11.1) contains the class summary table with levels sorted according to the sort option in the CLASS statement of PROC HPDMDB. You can see that the levels for BAD are in descending order and the levels for REASON are in ascending order. The levels for JOB are in the default ascending order.

Figure 11.1 Summaries of Classification Variables in Sampsio.Hmeq Data Set

Performance Information

Execution Mode	On client
Number of Threads	2

Obs	NAME	LEVEL	CODE	FREQUENCY	TYPE	CRAW	NRAW	FREQPERCENT	NMISSPERCENT
1	BAD	1	1	1189	N		1	19.9497	19.9497
2	BAD	0	0	4771	N		0	80.0503	80.0503
3	REASON		0	252	C		.	4.2282	.
4	REASON	DEBTCON	1	3928	C	DebtCon	.	65.9060	68.8157
5	REASON	HOMEIMP	2	1780	C	HomeImp	.	29.8658	31.1843
6	JOB		0	279	C		.	4.6812	.
7	JOB	MGR	1	767	C	Mgr	.	12.8691	13.5011
8	JOB	OFFICE	2	948	C	Office	.	15.9060	16.6872
9	JOB	OTHER	3	2388	C	Other	.	40.0671	42.0349
10	JOB	PROFEXE	4	1276	C	ProfExe	.	21.4094	22.4608
11	JOB	SALES	5	109	C	Sales	.	1.8289	1.9187
12	JOB	SELF	6	193	C	Self	.	3.2383	3.3973

Figure 11.1 *continued*

Obs	NAME	NMISS	N	MIN	MAX	MEAN	STD
1	LOAN	0	5960	1100.00	89900.00	18607.97	11207.48
2	DEROG	708	5252	0.00	10.00	0.25	0.85
3	MORTDUE	518	5442	2063.00	399550.00	73760.82	44457.61
4	VALUE	112	5848	8000.00	855909.00	101776.05	57385.78
5	YOJ	515	5445	0.00	41.00	8.92	7.57
6	DELINQ	580	5380	0.00	15.00	0.45	1.13
7	CLAGE	308	5652	0.00	1168.23	179.77	85.81
8	NINQ	510	5450	0.00	17.00	1.19	1.73
9	CLNO	222	5738	0.00	71.00	21.30	10.14
10	DEBTINC	1267	4693	0.52	203.31	33.78	8.60

Obs	SKEWNESS	KURTOSIS	SUM	USS	CSS
1	2.02378	6.9326	110903500.00	2.8121848E12	748495791434.56
2	5.32087	36.8728	1337.00	4099.00	3758.64
3	1.81448	6.4819	401406367.20	4.0362084E13	10754022449877
4	3.05334	24.3628	595186333.04	7.9830628E13	19254914800672
5	0.98846	0.3721	48581.75	745755.59	312296.19
6	4.02315	23.5654	2418.00	7922.00	6835.25
7	1.34341	7.5995	1016038.99	224259958.52	41610414.32
8	2.62198	9.7865	6464.00	23950.00	16283.34
9	0.77505	1.1577	122197.00	3192071.00	589751.93
10	2.85235	50.5040	158529.14	5702262.28	347161.26

Numeric summaries are in the data set **vout**, shown in Figure 11.2.

Figure 11.2 Summaries of Numeric Variables in Sampsio.Hmeq Data Set

Performance Information

Execution Mode	On client
Number of Threads	2

Obs	NAME	LEVEL	CODE	FREQUENCY	TYPE	CRAW	NRAW	FREQPERCENT	NMISSPERCENT
1	BAD	1	1	1189	N		1	19.9497	19.9497
2	BAD	0	0	4771	N		0	80.0503	80.0503
3	REASON		0	252	C		.	4.2282	.
4	REASON	DEBTCON	1	3928	C	DebtCon	.	65.9060	68.8157
5	REASON	HOMEIMP	2	1780	C	HomeImp	.	29.8658	31.1843
6	JOB		0	279	C		.	4.6812	.
7	JOB	MGR	1	767	C	Mgr	.	12.8691	13.5011
8	JOB	OFFICE	2	948	C	Office	.	15.9060	16.6872
9	JOB	OTHER	3	2388	C	Other	.	40.0671	42.0349
10	JOB	PROFEXE	4	1276	C	ProfExe	.	21.4094	22.4608
11	JOB	SALES	5	109	C	Sales	.	1.8289	1.9187
12	JOB	SELF	6	193	C	Self	.	3.2383	3.3973

Figure 11.2 *continued*

Obs	NAME	NMISS	N	MIN	MAX	MEAN	STD
1	LOAN	0	5960	1100.00	89900.00	18607.97	11207.48
2	DEROG	708	5252	0.00	10.00	0.25	0.85
3	MORTDUE	518	5442	2063.00	399550.00	73760.82	44457.61
4	VALUE	112	5848	8000.00	855909.00	101776.05	57385.78
5	YOJ	515	5445	0.00	41.00	8.92	7.57
6	DELINQ	580	5380	0.00	15.00	0.45	1.13
7	CLAGE	308	5652	0.00	1168.23	179.77	85.81
8	NINQ	510	5450	0.00	17.00	1.19	1.73
9	CLNO	222	5738	0.00	71.00	21.30	10.14
10	DEBTINC	1267	4693	0.52	203.31	33.78	8.60

Obs	SKEWNESS	KURTOSIS	SUM	USS	CSS
1	2.02378	6.9326	110903500.00	2.8121848E12	748495791434.56
2	5.32087	36.8728	1337.00	4099.00	3758.64
3	1.81448	6.4819	401406367.20	4.0362084E13	10754022449877
4	3.05334	24.3628	595186333.04	7.9830628E13	19254914800672
5	0.98846	0.3721	48581.75	745755.59	312296.19
6	4.02315	23.5654	2418.00	7922.00	6835.25
7	1.34341	7.5995	1016038.99	224259958.52	41610414.32
8	2.62198	9.7865	6464.00	23950.00	16283.34
9	0.77505	1.1577	122197.00	3192071.00	589751.93
10	2.85235	50.5040	158529.14	5702262.28	347161.26

Syntax: HPDMDB Procedure

The following statements are available in the HPDMDB procedure:

PROC HPDMDB DATA= < *libref.*>*SAS-data-set* < *options*> **;**
CLASS *variable* (< *order-option*>) *variable* (< *order-option*>) . . . **;**
FREQ *variable* **;**
PERFORMANCE *performance-options* **;**
VAR *variables* **;**
WEIGHT *variable* **;**

PROC HPDMDB Statement

PROC HPDMDB DATA= < *libref.*>*SAS-data-set* < *options*> **;**

The PROC HPDMDB statement invokes the procedure.

Required Arguments

DATA=< *libref.***>***SAS-data-set*

names the SAS data set that contains the information that you want added to the data mining database. If the data set resides on the SAS Appliance, then the SAS Appliance is used during summarization.

Optional Arguments

DMDBCAT=< *libref.***>***SAS-catalog*

names the metadata catalog to be created by PROC HPDMDB.

CLASSOUT=< *libref.***>***SAS-data-set*

names the data set to contain the summaries of classification variables that are specified in the CLASS statement.

VAROUT=< *libref.***>***SAS-data-set*

names the data set to contain the summaries of analysis variables that are specified in the VAR statement.

VARDEF=*divisor*

specifies the divisor to use in the calculation of the variance and standard deviation. Table 11.1 shows the possible values for VARDEF.

Table 11.1 Values for VARDEF=

Value	Divisor
N	Number of observations (n)
DF (default)	Degrees of freedom ($n - 1$)

PRINT

prints the class-level information to all open ODS destinations.

SPECIALMISSING

enables special missing values to be treated as separate levels.

MAXLEVEL=*max*

specifies the maximum number of levels to be reported for each class variable. If more than *max* levels of a class variable exist, PROC HPDMDB reports the frequency of unreported observations in a level named *_OTHER_*.

CLASS Statement

CLASS *variable (< order-option >) < variable (< order-option >) > . . .* **;**

The CLASS statement specifies the variables whose values define subgroup combinations for the analysis.

The CLASS and VAR statements are mutually exclusive.

Required Argument

variable

specifies a classification variable to be used in the analysis. For each level of a CLASS variable, the CLASSOUT data set contains information about each of the following: the level value, its frequency, and the type of the variable (numeric or character).

Optional Argument

order-option

specifies the order to use when considering the levels of CLASS variables to be sorted. The value of *order-option* can be one of the following:

ASCENDING | ASC

arranges class levels in lowest-to-highest order of unformatted values.

DESCENDING | DESC

arranges class levels in highest-to-lowest order of unformatted values.

ASCFORMATTED | ASCFMT

arranges class levels in ascending order by their formatted values.

DESFORMATTED | DESFMT

arranges class levels in descending order by their formatted values.

DSORDER | DATA

arranges class levels according to the order of their appearance in the input data set.

NOTE: The DSORDER sort option is not supported for input data sets that are stored on the SAS Appliance.

FREQ Statement

FREQ *variable* **;**

The FREQ statement specifies a numeric *variable* that contains the frequency of each observation.

Required Argument

variable

specifies a numeric variable whose value represents the frequency of the observation. For observations where *variable* is 0 or missing, the observation is omitted in the CLASSOUT data set and is not included in statistical calculations.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement you can also control whether a SAS High-Performance Analytics procedure executes in symmetric multiprocessor (SMP) or massively parallel processor (MPP) mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

VAR Statement

VAR *variables* **;**

The VAR statement specifies one or more numeric *variables* to analyze. The CLASS and VAR statements are mutually exclusive.

Required Argument

variables

specifies one or more numeric *variables* to be used in the analysis. The *variables* must be numeric. For each *variable*, the VAROUT data set and the metadata contain the following statistics:

Table 11.2 Statistics Recorded for VAR Variables

Statistic	Meaning
N	Number of observations
NMISS	Number of observations that contain a missing value
MIN	Minimum observed value
MAX	Maximum observed value
MEAN	Mean of observed values
STD	Standard deviation
SKEWNESS	Measure of asymmetry
KURTOSIS	Measure of the "heaviness of the tails"
SUM	Sum of all nonmissing observations
CSS	Corrected sum of squares
USS	Sum of squares

(See Appendix 1, "SAS Elementary Statistics Procedures" in *Base SAS Procedures Guide*, for formulas and other details.)

WEIGHT Statement

WEIGHT *variable* **;**

The WEIGHT statement specifies a numeric *variable* that contains a weight for each observation. The *variable* is used in the computation of means, standard deviation, skewness, and kurtosis.

Required Argument

variable

represents how the observation should be weighted in statistical calculations. For observations where *variable* is 0 or missing, the observation is still included in the CLASSOUT data set but the value is not used in statistical calculations.

Details: HPDMDB Procedure

The statistics recorded for numeric variables are detailed in the section "VAR Statement" on page 195.

For classification variables, a *level* is a distinct observed value after formatting, removal of beginning and ending white space, and capitalization. For example, the values **`MyLevel`** and **`MYLEVEL`** are treated as a single level in the data set. Classification variables can be numeric, and the same levelization rules apply. For example, **`3.000002`** and **`3.0000001`** are treated as the same level if they are formatted using **`BEST3`**.

Frequencies should be integers. If a noninteger frequency is specified, it is rounded to the nearest integer for calculations. Weights do not need to be integers. Negative frequencies and weights are treated as 0.

Examples: HPDMDB Procedure

Example 11.1: Running PROC HPDMDB on the Client

This example demonstrates how to run the HPDMDB procedure on the following data set on the client:

```
data ex;
input x1 x2 x3 x4 y$ w f y2;
cards;
1  2 1 1  m .90 1 0
1  2 1 2  m .91 2 1
1  2 1 3  x .89 1 4
1  2 1 4  x .90 2 4
1  3 1 1  m .91 1 1
1  3 1 2  m .89 2 1
2  3 1 3  x .90 1 5
2  3 1 4  x .89 2 5
3  1 2 1  z .90 1 2
3  1 2 2  z .89 2 2
3  1 2 3  y .90 1 7
3  1 2 4  y .89 2 7
3  4 2 1  z .90 1 3
3  4 2 2  z .89 2 3
4  4 2 3  y .90 1 6
4  4 2 4  y .89 2 6
;
run;
```

When the input data set resides on the client and no PERFORMANCE statement is specified, as in the following example, the client performs all computations:

```
proc hpdmdb data=ex print classout=cout varout=vout;
    class x1-x3;
    weight w;
    var x4 y2;
    freq f;
run;
```

Output 11.1.1 shows the summaries of the numeric variables in the data set ex.

Output 11.1.1 Summaries of Numeric Variables in ex Data Set

Obs	NAME	NMISS	N	MIN	MAX	MEAN	STD
1	x4	0	24	1	4	2.66326	1.06938
2	y2	0	24	0	7	3.57721	2.10658

Obs	SKEWNESS	KURTOSIS	SUM	USS	CSS
1	-0.05848	-1.19599	57.26	178.80	26.302
2	0.12214	-1.04243	76.91	377.19	102.067

Output 11.1.2 shows the summaries of the classification variables in the data set ex.

Output 11.1.2 Summaries of Classification Variables in ex Data Set

Obs	NAME	LEVEL	CODE	FREQUENCY	TYPE	CRAW	NRAW	FREQPERCENT	NMISSPERCENT
1	x1	1	0	9	N		1	37.5	37.5
2	x1	2	1	3	N		2	12.5	12.5
3	x1	3	2	9	N		3	37.5	37.5
4	x1	4	3	3	N		4	12.5	12.5
5	x2	1	0	6	N		1	25.0	25.0
6	x2	2	1	6	N		2	25.0	25.0
7	x2	3	2	6	N		3	25.0	25.0
8	x2	4	3	6	N		4	25.0	25.0
9	x3	1	0	12	N		1	50.0	50.0
10	x3	2	1	12	N		2	50.0	50.0

Example 11.2: Running with Client Data on the SAS Appliance

This example uses the same data set as is used in Example 11.1.

When the input data set resides on the client and a PERFORMANCE statement with a NODES= option is specified, as in the following example, PROC HPDMDB copies the data set to the SAS Appliance, which does the computations. To run these statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the macro variable references

in the example with the appropriate values.

```
option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC = "&GRIDINSTALLLOC";
/*Perform the computation on the SAS Appliance using 5 nodes*/
proc hpdmdb data=ex print classout=cout varout=vout;
    class x1-x3;
    weight w;
    var x4 y2;
    freq f;
    performance nodes=5 details;
run;
```

The results are the same as those shown in Output 11.1.1 and Output 11.1.2.

Example 11.3: Running with Data on the SAS Appliance

This example uses the same data set as is used in Example 11.1.

When the input data set resides on the SAS Appliance, the SAS Appliance performs all computations and reports the results back to the client. In the following example, the input data resides in the MyLib library, which is a distributed data source. To run these statements successfully, you need to set the macro variables to resolve to appropriate values, or you can replace the macro variable references with the appropriate values.

```
option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC = "&GRIDINSTALLLOC";

libname MyLib &LIBTYPE
        server  ="&GRIDDATASERVER"
        user    =&USER
        password=&PASSWORD
        database=&DATABASE;

/*MyLib is a libname for a distributed data source
  In this case, the computation is automatically done
  on the SAS Appliance.*/
proc hpdmdb data=MyLib.ex print classout=cout varout=vout;
    class x1-x3;
    weight w;
    var x4 y2;
    freq f;
    performance details;
run;
```

The results are the same as those shown in Output 11.1.1 and Output 11.1.2.

Chapter 12
The HPDS2 Procedure

Contents

Overview: HPDS2 Procedure **199**
PROC HPDS2 Features 200
Client and Grid Execution Modes 200
Getting Started: HPDS2 Procedure **201**
Syntax: HPDS2 Procedure **203**
PROC HPDS2 Statement 204
DATA Statement 204
ENDDATA Statement 204
PERFORMANCE Statement 204
QUIT Statement 205
RUN Statement 205
RUN CANCEL Statement 205
Details: HPDS2 Procedure **205**
Parallel Execution of DS2 Code 205
Limitations and Issues 206
Packages 206
PERFORMANCE Statement Options 206
Data Input/Output 206
Data Types and Declarations 207
Error Messages 207
Examples: HPDS2 Procedure **207**
Example 12.1: Compute Mandelbrot Set 207
Example 12.2: Aggregate Result Data Set 210

Overview: HPDS2 Procedure

The HPDS2 procedure enables you to submit DS2 language statements from a Base SAS session to a SAS High-Performance Analytics grid for parallel execution. PROC HPDS2 verifies the syntactic correctness of the DS2 source on the client machine before submitting it to the grid for execution. The output data created by the DS2 DATA statement can be output in either of the following ways: it can be written in parallel back to the grid data store or it can be returned to the client machine and directed to any data store that is supported by SAS.

Because the DS2 code is executed in parallel on separate grid nodes with single data partitions, there is separate output from each node that is the result of processing only the local data partition. As a result,

it might be necessary to use a second-stage program to aggregate the results from each node. The second stage can be executed on the SAS client by using the DS2 procedure, where the SET statement reads all rows created by the preceding parallel stage.

The syntax of DS2 is similar to that of the DATA step, but it does not include several key statements such as INPUT and MERGE. In addition, using DS2 in the High-Performance Analytics environment limits the PROC DS2 SET statement to a single input stream. The use of BY processing within the SET statement is also not supported. Therefore, many of the traditional DATA step data preparation features are not available in the HPDS2 procedure. PROC HPDS2 is most useful when significant amounts of computationally intensive, row-independent logic must be applied to the data. The DSTRANS procedure, which is documented in the *SAS DS2 Language Reference*, converts a DATA step to DS2 and in the process identifies DATA step syntax that is not compatible with PROC HPDS2.

For more information about the DS2 language, see the *SAS DS2 Language Reference* which is available at `http://support.sas.com/documentation/solutions/ds2/DS2Ref.pdf`.

PROC HPDS2 Features

The HPDS2 procedure provides a vehicle for the parallel execution of DS2 code in a distributed computing environment. The following list summarizes the basic features of the HPDS2 procedure:

- provides the ability to execute DS2 code in parallel
- enables DS2 code to be executed on a local client machine or on the High-Performance Analytics grid
- enables control of the level of parallelism per execution node and the number of nodes to engage
- performs a syntax check of the DS2 code on the local client machine before sending it to the grid for execution
- manages data migration to the location of execution and movement back to the client machine as needed

Client and Grid Execution Modes

The HPDS2 procedure controls the execution of DS2 language statements in two dimensions. You can control both the number of parallel threads per execution node and also the number of compute nodes to engage. The threading provided by PROC HPDS2 operates outside the syntax of the language in contrast to the THREADS PACKAGE DS2 syntax which provides single-node scalability as part of the DS2 syntax.

Alternatively, the HPDS2 procedure can be executed on the High-Performance Analytics grid. In grid mode, one or more copies of the DS2 program are executed in parallel on each grid node.

The grid mode of execution has two variations:

- In the client-data (local-data) model of grid execution, the input data are not stored on the appliance but are distibuted to the distributed computing environment by the High-Performance Analytics framework during execution of the HPDS2 procedure.

- In the alongside-the-database model of grid execution, the data source is the database on the appliance. The data are stored in the distributed database, and the DS2 program running on each node is able to read and write the data in parallel during execution of the procedure. Instead of data being moved across the network and possibly back to the client machine, data are passed locally between the processes on each node of the appliance. In general, especially with large data sets, the best HPDS2 performance can be achieved if execution is alongside the database.

By default, the number of copies of the DS2 program that are executed in parallel on a given host (that is, client machine or grid node) is determined by the HPDS2 procedure based on the number of CPUs (cores) available on the host machine. The default is to execute one instance of the DS2 program in a dedicated thread per CPU. This can be changed by means of the NTHREADS= option in the PERFORMANCE statement. For example, if NTHREADS=*n* is specified, then the HPDS2 procedure runs *n* copies of the DS2 program in parallel on each grid node.

The HPDS2 procedure can run in either symmetric multiprocessing (SMP) mode or in massively parallel processing (MPP) mode. For information about the available modes of execution of SAS High-Performance Analytics procedures and how to switch between them, see the section "SMP and MPP Modes" on page 10 of Chapter 2, "Shared Concepts and Topics."

Getting Started: HPDS2 Procedure

This example illustrates a simple HPDS2 procedure. In this case, the DS2 source statements are executed alongside the database in MPP mode. The DS2 code that is submitted to the grid is contained within the DATA and ENDDATA statements. The following DATA step creates a data set that consists of fictitious daily temperatures collected from a number of U.S. airports during a period of one week:

```
data daily_temps;
   input city $ mon tue wed thu fri;
datalines;
lax 88 92 94 97 86
sfo 65 60 75 72 74
nyc 99 95 94 95 90
phl 92 89 91 93 94
atl 95 99 92 98 94
den 85 87 89 72 73
pit 68 70 72 73 77
rdu 98 95 99 95 96
dtt 88 90 90 87 92
anc 51 56 60 64 62
sea 72 78 77 80 79
msy 98 97 99 98 99
mia 95 92 98 94 96
ord 87 85 84 80 79
dfw 95 96 97 95 97
hou 98 99 98 97 92
las 104 105 102 99 101
pdx 78 82 76 74 80
san 80 81 78 82 80
phx 95 98 95 97 100
```

```
cle 75 72 76 80 78
ont 78 80 78 81 72
tpa 94 94 92 90 92
bos 80 78 77 75 79
clt 83 80 79 80 81
;
run;
```

The HPDS2 procedure reads this data set and calculates a daily average temperature in Fahrenheit and Celsius for each airport and then provides a synopsis of the weekly temperature average.

In the following statements, the driver DS2GTF.out in the DATA statement names the input data set, and the SET DS2GTF.in statement names the output data set:

```
libname applianc &ENGINE
        server = "&GRIDDATASERVER"
        user   = &USER
        password = &PASSWORD
        database = &DATABASE;

proc hpds2 data=daily_temps
           out=applianc.avg_temps;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC";
   data DS2GTF.out;
      dcl double avgf avgc;
      dcl char(5) synopsis;
      method run();
         set DS2GTF.in;
         avgf = mean(mon, tue, wed, thu, fri);
         avgc = round((avgf - 32.0) * 5.0/9.0, .1);
         if avgf >= 95.0 then synopsis = 'Hot';
         else if avgf > 80.0 then synopsis = 'Warm';
         else if avgf > 60.0 then synopsis = 'Mild';
         else synopsis = 'Cold';
      end;
   enddata;
run;
```

The following PRINT procedure displays the table of average temperatures that are produced by the HPDS2 procedure:

```
proc print data=applianc.avg_temps;
   title1 'Average Temperatures';
   var city synopsis avgf avgc;
run;
```

Figure 12.1 displays the output of the PRINT procedure.

Figure 12.1 Average Temperatures

Average Temperatures

Obs	city	synopsis	avgf	avgc
1	lax	Warm	91.4	33.0
2	sfo	Mild	69.2	20.7
3	nyc	Warm	94.6	34.8
4	phl	Warm	91.8	33.2
5	atl	Hot	95.6	35.3
6	den	Warm	81.2	27.3
7	pit	Mild	72.0	22.2
8	rdu	Hot	96.6	35.9
9	dtt	Warm	89.4	31.9
10	anc	Cold	58.6	14.8
11	sea	Mild	77.2	25.1
12	msy	Hot	98.2	36.8
13	mia	Hot	95.0	35.0
14	ord	Warm	83.0	28.3
15	dfw	Hot	96.0	35.6
16	hou	Hot	96.8	36.0
17	las	Hot	102.2	39.0
18	pdx	Mild	78.0	25.6
19	san	Warm	80.2	26.8
20	phx	Hot	97.0	36.1
21	cle	Mild	76.2	24.6
22	ont	Mild	77.8	25.4
23	tpa	Warm	92.4	33.6
24	bos	Mild	77.8	25.4
25	clt	Warm	80.6	27.0

Syntax: HPDS2 Procedure

The following statements are available in the HPDS2 procedure:

```
PROC HPDS2 < options > ;
   PERFORMANCE performance-options ;
   DATA DS2GTF.out ;
        DS2 statements
        METHOD RUN()
        SET DS2GTF.in
        END
   ENDDATA ;
   RUN ;
   RUN CANCEL ;
   QUIT ;
```

PROC HPDS2 Statement

PROC HPDS2 < *options* > **;**

The PROC HPDS2 statement invokes the procedure.

You can specify the following options in the PROC HPDS2 statement:

DATA=*SAS-data-set*

IN=*data-set*
names the SAS data set or database table to be used by PROC HPDS2. The default is the most recently created data set.

OUTPUT=*data-set*

OUT=*data-set*
names the SAS data set or database table created by PROC HPDS2.

DATA Statement

DATA DS2GTF.out ;

The DATA statement indicates the beginning of the DS2 code block. The code block terminates with the ENDDATA statement.

A reference to the DS2 Grid Table Function driver (DS2GTF.out) must be included as part of the DATA statement. If an input data set is specified in the PROC HPDS2 statement, then a **`run()`** method should be included in the DS2 code block. The first statement after the METHOD RUN() statement must be the SET DS2GTF.in statement for this case. DS2GTF.out and DS2GTF.in refer to the input and output data sets, respectively.

ENDDATA Statement

ENDDATA ;

The ENDDATA statement terminates the DS2 code block. The statements between the DATA and ENDDATA statement are submitted to the grid for execution. The DS2 run, init, and term methods are specified between the DATA and ENDDATA statements.

PERFORMANCE Statement

PERFORMANCE *performance-options* **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a High-Performance Analytics procedure.

With the PERFORMANCE statement, you can also control whether a High-Performance Analytics procedure executes in SMP or MPP mode.

It is important to remember the distinction between the NODES= and NTHREADS= options. The NODES= option specifies the number of separate grid nodes that participate in the DS2 execution, while the NTHREADS= option determines how many independent copies of the DS2 program are run in parallel on each node. If the data are located on the grid, then all nodes must be engaged; therefore, the NODES= option might be overridden. Setting NODES=0 causes the DS2 code to execute on the client side only. Setting the NTHREADS= option to a value that is greater than the CPU count on each grid node is not likely to improve overall throughput.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

QUIT Statement

QUIT ;

The QUIT statement stops the procedure. PROC HPDS2 statements that have not been submitted with a RUN statement are terminated.

RUN Statement

RUN ;

The RUN statement submits the preceding PROC HPDS2 statements for execution.

The procedure requires the RUN statement to submit the statements. That is, SAS reads the program statements that are associated with one task until it reaches a RUN statement.

RUN CANCEL Statement

RUN CANCEL ;

The RUN CANCEL statement cancels the preceding PROC HPDS2 statements. RUN CANCEL is useful if you enter a typographical error.

Details: HPDS2 Procedure

Parallel Execution of DS2 Code

An important characteristic of multithreaded or distributed applications is that they might produce nondeterministic or unpredictable results. The exact behavior of a DS2 program running in parallel on the grid is

influenced by a number of factors, including the pattern of data distribution that is used, the execution mode that is chosen, the number of compute nodes and threads that are used, and so on. The HPDS2 procedure does not examine whether the DS2 code that is submitted produces meaningful and reproducible results. It simply executes the DS2 code that is provided on each of the units of work, whether these are multiple threads on a single machine or multiple threads on separate grid nodes. Each instance of the DS2 program operates on a subset of the data. The results produced by each unit of work are then gathered, without further aggregation, into the output data set.

Because the DS2 code instances are executed in parallel, consideration must be given to the DS2 language elements that are included in the DS2 code block of an HPDS2 procedure. Not all DS2 language elements can be meaningfully used in multithreaded or distributed applications. For example, lagging or retaining of variables can imply ordering of observations. A deterministic order of observations does not exist in distributed applications, and enforcing data order might have a negative impact on performance.

Optimal performance is achieved when the input data are stored in the distributed database and the grid host is the appliance that houses the data. With the data distributed in this manner, the different instances of the DS2 code running on the grid nodes can read the input data and write the output data in parallel from the local database management system (DBMS).

Limitations and Issues

The current release of the HPDS2 procedure does not support all of the features of the DS2 language. The following subsections summarizes the known limitations and issues for PROC HPDS2.

Packages

DS2 packages are collections of variables and methods that can be used in DS2 programs and threads. The HPDS2 procedure does not support DS2 packages at this time. Use of the PACKAGE and ENDPACKAGE constructs within an HPDS2 procedure results in an error. Similarly, existing packages cannot be referenced within an HPDS2 procedure.

PERFORMANCE Statement Options

The maximum allowed value for the CPUCOUNT= option in the PERFORMANCE statement is 256. However, setting CPUCOUNT= to very high values, including values that substantially exceed the actual number of available CPUs, can result in unpredictable errors, including DS2 program instances that unexpectedly produce no observations in the output data set.

Setting the NTHREADS= option in the PERFORMANCE statement to very high values can cause out-of-memory errors. For example, out-of-memory errors have been seen with NTHREADS=100.

Data Input/Output

If an input data set is specified, then a SET DS2GTF.in statement must be included in the METHOD RUN() statement. If either the SET DS2GTF.in or the SET DS2GTF.out driver reference is missing, then the SAS session stops responding.

The use of BY groups within the SET statement of an HPDS2 procedure is not supported at this time.

The use of nested SQL within the SET statement of an HPDS2 procedure is not supported at this time.

When used within an HPDS2 procedure, the PUT statement does not currently write any data to the client log.

The OVERWRITE= option is not supported in PROC HPDS2.

Data Types and Declarations

The HPDS2 procedure does not support the following data types: REAL, TINYINT, NCHAR, TIMESTAMP, DATE, and TIME. If any of these data types are declared within an HPDS2 procedure, then an error is displayed.

Informats and user-defined formats are not currently supported in PROC HPDS2.

Delimited identifiers (for example, dcl double "a%& b") are not currently supported in PROC HPDS2.

No warning or error messages are output when assignments involving out-of-bounds arrays are used within an HPDS2 procedure.

Error Messages

Incorrect source line numbers are reported when there is an error in an HPDS2 procedure. In addition, the ordering of error messages displayed is reversed for PROC HPDS2 from the order of error messages that is output for DS2.

Examples: HPDS2 Procedure

Example 12.1: Compute Mandelbrot Set

This example computes and plots a Mandelbrot set. The DS2 source statements that compute the set of coordinates that comprise the Mandelbrot set are submitted to the grid and executed alongside the database in MPP mode. Note that Mandelbrot set computation is perfectly scalable in that each point can be computed independently of every other point.

This example uses a DS2 procedure to create a data set that consists of one row for each Mandelbrot coordinate to be computed. The HPDS2 procedure reads this data set and computes the coordinates. The Mandelbrot set is then graphed via the GCONTOUR procedure.

```
libname applianc &ENGINE
        server = "&GRIDDATASERVER"
        user   = &USER
        password = &PASSWORD
        database = &DATABASE;

/* Set up the table that contains one row for each coordinate to compute */
proc ds2;
   data inp(overwrite=yes);
      dcl double p q r;
      dcl integer maxiterate;
      method init();
```

```
         dcl int n m;
         dcl int i j k;
         dcl double pmin pmax qmin qmax;
         n = 1024;
         m = 1024;
         pmin = -1.5; pmax = -0.5;
         qmin = -0.5; qmax =  0.5;
         r = 100.0;
         maxiterate = 50;
         do k = 1 to n*m;
            i = k/m;
            j = mod(k,m);
            p = i*(pmax-pmin)/(n-1)+pmin;
            q = j*(qmax-qmin)/(m-1)+qmin;
            output;
         end;
      end;
   enddata;
run;
quit;

/* Compute the coordinates */
proc hpds2 data=inp out=applianc.mandelbrot;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC";
   data DS2GTF.out;
      dcl int mesh;
      dcl double x y rr nx ny;
      keep p q mesh;
      method run();
         set DS2GTF.in;
         x = p;
         y = q;
         rr = r**2;
         mesh = 0;
         do while (mesh < maxiterate and (x**2+y**2 < rr));
            nx = x**2 - y**2 + p;
            ny = 2.0*x*y + q;
            x = nx;
            y = ny;
            mesh = mesh+1;
         end;
      end;
   enddata;
run;

/* Plot the results */
goptions colors= (
CX003366 CX336699 CX6699CC CX99CCFF CX006633 CX339966 CX66CC99 CX99FFCC
CX336600 CX669933 CX99CC66 CXCCFF99 CX663300 CX996633 CXCC9966 CXFFCC99
CX660033 CX993366 CXCC6699 CXFF99CC CX003366 CX663399 CX9966CC CXCC99FF
CX003366 CX663399 CX9966CC CXCC99FF CX003366 CX663399 CX9966CC CXCC99FF
CX003366 CX663399 CX9966CC CXCC99FF CX003366 CX663399 CX9966CC CXCC99FF
black
)
```

```
;

proc gcontour data=applianc.mandelbrot;
   Title 'Mandelbrot Set';
   plot q*p=mesh /
   nolegend
   pattern
   join
   levels = 5 to 45
  ;
run;
```

Output 12.1.1 shows the graphic representation of the Mandelbrot set computed by the HPDS2 procedure.

Output 12.1.1 Computed Mandelbrot Set



Example 12.2: Aggregate Result Data Set

This example illustrates how the intermediate result data that are generated from the DS2 code running in parallel on separate grid nodes can be aggregated into a final result data set. In this case, the aggregation is done by a second-stage PROC DS2 program that executes on the SAS client.

This example uses a DATA step program running on the SAS client to generate a sample data set that consists of dimensional information for each of 200 objects (closed cylinders). These data are used by the HPDS2 procedure to calculate the volume and surface area of each object. The second-stage DS2 procedure aggregates these results, summing the total volume and surface area for all objects and computing the average volume and surface area. Notice in this example that the DS2 code running in parallel on the grid is used to perform the row-independent and computationally intensive portion of the processing, while the work done by the second-stage DS2 procedure is limited to the final result aggregation and summary.

```
libname applianc &ENGINE
        server = "&GRIDDATASERVER"
        user   = &USER
        password = &PASSWORD
        database = &DATABASE;

data obj_dims;
   do id=1 to 200;
      radius = ranuni(1) * 10;
      height = ranuni(1) * 20;
      output;
   end;
run;

%let pi=3.14159;
proc hpds2 data=obj_dims
           out=applianc.obj_comps;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC";
   data DS2GTF.out;
      method run();
         set DS2GTF.in;
         volume = &pi * radius**2 * height;
         area = (2 * &pi * radius**2) + (2 * &pi * radius * height);
      end;
   enddata;
run;

proc print data=applianc.obj_comps (obs=20);
   title1 'Volumes and Areas';
run;

data obj_comps;
   set applianc.obj_comps;
run;
```

```
proc ds2;
   data obj_totals (keep = (ncount vsum asum vmean amean));
      dcl double ncount vsum asum vmean amean;
      method init();
         ncount = 0;
         vsum = 0;
         asum = 0;
      end;
      method run();
         set {select volume, area from obj_comps};
         ncount + 1;
         vsum + volume;
         asum + area;
      end;
      method term();
         if ncount ne 0 then do;
            vmean = vsum/ncount;
            amean = asum/ncount;
         end;
         output;
      end;
   enddata;
run;
quit;

proc print data=obj_totals;
   title1 'Total Volume and Area';
run;
```

Output 12.2.1 shows a subset of the volumes and areas computed by the HPDS2 procedure.

Output 12.2.1 Computed Volumes and Areas

Volumes and Areas

Obs	id	radius	height	volume	area
1	1	1.84963	19.4018	208.53	246.97
2	2	3.99824	5.1880	260.55	230.77
3	3	9.21603	19.3855	5172.67	1656.20
4	4	5.42979	10.6338	984.93	548.03
5	5	0.49794	1.3313	1.04	5.72
6	6	8.19319	10.4774	2209.58	961.15
7	7	8.53394	1.3437	307.43	529.64
8	8	9.57024	5.9439	1710.27	932.89
9	9	2.72612	13.7986	322.16	283.05
10	10	9.76765	4.5302	1357.82	877.48
11	11	6.88237	8.2553	1228.45	654.60
12	12	5.58554	5.7445	563.03	397.63
13	13	4.75789	16.8997	1201.87	647.45
14	14	6.34524	11.8073	1493.47	723.71
15	15	5.82582	7.5403	803.99	489.26
16	16	7.28362	10.1321	1688.66	797.02
17	17	9.31214	18.5824	5062.32	1632.10
18	18	5.89660	5.9445	649.33	438.70
19	19	3.91042	9.4486	453.90	328.23
20	20	6.79526	3.3618	487.67	433.66

Output 12.2.2 shows the aggregated results produced by the second-stage DS2 program.

Output 12.2.2 Computed Total Volume and Area

Total Volume and Area

Obs	NCOUNT	VSUM	ASUM	VMEAN	AMEAN
1	200	209883.99	104680.26	1049.42	523.401

Chapter 13
The HPFOREST Procedure

Contents

Overview: HPFOREST Procedure **214**
PROC HPFOREST Features 214
PROC HPFOREST Contrasted with Other SAS Procedures 215
Getting Started: HPFOREST Procedure **215**
Syntax: HPFOREST Procedure **220**
PROC HPFOREST Statement 221
FREQ Statement 224
INPUT Statement 224
PERFORMANCE Statement 224
SAVE Statement 225
SCORE Statement 225
TARGET Statement 225
Details: HPFOREST Procedure **226**
Bagging the Data 226
Training a Decision Tree 226
Controlling for Variable Selection Bias 227
Selecting a Splitting Variable 230
Searching for a Splitting Rule 232
Rules 232
Criteria 232
Algorithm 233
Predicting an Observation 233
Computing the Average Square Error and Misclassification Rate 234
Adjusting Statistics When Sampling Target Classes Unevenly 234
Formulas for Adjusting the Predictions and Fit Statistics 235
Why the Adjustments Matter 236
Technical Derivations of Adjustment Formulas 240
Handling Missing Values 241
Strategies 241
Specifics 242
Handling Values That Are Absent from Training Data 243
Measuring Variable Importance 243
Loss Reduction 244
Breiman's Method 245
Bias and Correlation 246
Preferences 247

Displaying the Output 248
ODS Table Names 248
Examples: HPFOREST Procedure **248**
Example 13.1: Out-Of-Bag Estimate of Misclassification Rate 249
Example 13.2: Number of Variables to Try When Splitting a Node 251
Example 13.3: Fraction of Training Data to Train a Tree 254
Example 13.4: Loss Reduction Variable Importance 255
Example 13.5: Missing Values and Imputed Values 257
References **262**

Overview: HPFOREST Procedure

The HPFOREST procedure is a high-performance procedure that creates a predictive model called a *forest* that consists of several decision trees. A *predictive model* defines a relationship between input variables and a target variable. The purpose of a predictive model is to predict a target value from inputs. The HPFOREST procedure *trains* the model; that is it creates the model using *training data* in which the target values are known. The model can then be applied to observations in which the target is unknown. If the predictions fit the new data well, the model is said to *generalize* well. Good generalization is the primary goal for predictive tasks. A predictive model might fit the training data well but generalize poorly.

A *decision tree* is a type of predictive model that has been developed independently in the statistics and artificial intelligence communities. The HPFOREST procedure creates a tree recursively. An input variable is chosen and used to create a rule to split the data into two segments. The process is then repeated in each segment, and then again in each new segment, and so on until some constraint is met. In the terminology of the tree metaphor, the segments are *nodes*, the original data set is the *root* node, and the final unpartitioned segments are *leaves* or *terminal nodes*. A node is an *internal node* if it is not a leaf. The data in a leaf determine the estimates of the value of the target variable. These estimates are subsequently applied to predict the target of a new observation assigned to the leaf.

The HPFOREST procedure creates decision trees that differ from each other in two ways. First, the training data for a tree is a sample, without replacement, from the original training data of the forest. Second, the input variables considered for splitting a node are randomly selected from all available inputs. Among these variables, the HPFOREST procedure considers only a single variable when forming a splitting rule. The chosen variable is the one that is most associated with the target.

Training a forest can require training hundreds of decision trees. The HPFOREST procedure can exploit computer grids by training trees in parallel independently on different grid nodes. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about the execution of SAS High-Performance Analytics procedures on a grid of computers.

PROC HPFOREST Features

The HPFOREST procedure creates an ensemble of hundreds of decision trees to predict a single target of either interval or nominal measurement level. An input variable can have an interval, ordinal, or nomi-

nal measurement level. The procedure can run on a grid of computers like other SAS High-Performance Analytics procedures.

The HPFOREST procedure deletes from the training data any observation that has a missing target value or a FREQ variable whose value is less than or equal to 0.

PROC HPFOREST Contrasted with Other SAS Procedures

No other SAS procedure creates a forest of decision trees for predictive modeling. SAS® Enterprise Miner™ has had three procedures (the ARBOR, DMSPLIT, and SPLIT procedures) during its history that create a single decision tree for predictive modeling. These three procedures search for a split on every variable in every node. The HPFOREST procedure searches for a split on only one variable in a node: the variable with the largest association with the target among candidates randomly selected in that node. Consequently, the HPFOREST procedure creates different trees than the other three procedures.

The syntax for the HPFOREST procedure follows the syntax of the ARBORETUM procedure in SAS Enterprise Miner, except for the PERFORMANCE statement: The HPFOREST procedure uses the same syntax for the PERFORMANCE statement used in other SAS High-Performance Analytics procedures, which is different from the syntax in the ARBORETUM procedure. The values of a variable in a FREQ statement in PROC HPFOREST are adjusted to the nearest integer, as is done in other SAS High-Performance Analytics procedures, and not as is done in the ARBORETUM procedure.

PROC ARBORETUM and PROC HPFOREST use a missing input value as a legitimate value by default. The procedures handle missing values differently in other respects.

The ARBORETUM procedure distinguishes between split-based and observation-based variable importance measures. The HPFOREST procedure calls these *loss reduction* and *Breiman's method* of variable importance, respectively.

The HPFOREST procedure can run on a grid of computers as can other SAS High-Performance Analytics procedures. For general contrasts between SAS High-Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16.

Getting Started: HPFOREST Procedure

This example uses diabetes data to illustrate PROC HPFOREST. Diabetes is a major American disease. The American Diabetes Association estimates that over 8% of Americans have diabetes, and diabetes costs Americans over $175 billion a year. The National Institute of Diabetes and Digestive and Kidney Diseases (NIDDK) has been studying diabetes and obesity in the Pima Indians in Arizona for over 30 years. Smith et al. (1988) prepared some of the NIDDK data for forecasting the onset of diabetes mellitus, and then donated the data for community use. Since then the data has been applied to dozens of experimental algorithms for predicting the onset of diabetes.

The Pima Indians diabetes data are available from the UCI Machine Learning Repository (Asuncion and Newman 2007) `http://archive.ics.uci.edu/ml/datasets/Pima+Indians+Diabetes`. The following SAS statements create a SAS data set from the data downloaded into a file called *c:\diabetes_data.txt*:

```
data diabetes;
   infile 'c:\diabetes_data.txt'  delimiter=',';
   input NumPregnancies
         plasmaGlucose
         diastolicBloodPr
         tricepsSkinfold
         hrSerumInsulin
         BodyMassIndex
         DiabetesPedigreeFn
         Age
         diabetes $
 ;
run;
```

The variable diabetes has values 0 and 1, 1 indicating the presence of diabetes. The other variables are raw measures on interval scales, except for DiabetesPedigreeFn which is an interval variable created by Smith et al. (1988) to capture the family history of diabetes. PROC HPFOREST uses an interval scale for numeric variables and a nominal scale for categorical variables unless the scale is specified. The following statements run PROC HPFOREST and saves the model in a binary file.

```
proc hpforest data=diabetes ;
   input NumPregnancies
         plasmaGlucose
         diastolicBloodPr
         tricepsSkinfold
         hrSerumInsulin
         BodyMassIndex
         DiabetesPedigreeFn
         Age ;
   target diabetes;
   save file="model";
run;
```

Output 13.1 shows that the program ran locally and that two threads were available. The listing also shows the values of the training parameters and the number of observations (768). No parameters are specified in the PROC HPFOREST statement; therefore, all the values are default. The maximum number of decision trees to create is 50. The VARS_TO_TRY= option equals 3, indicating that 3 of the 8 input variables are randomly selected to be considered for a splitting rule.

Figure 13.1 HPFOREST Getting Started Example Output

Performance Information

Execution Mode	On client
Number of Threads	2

Model Information

Parameter	Value	
Category Bins	30	(Default)
Leaf Size	5	(Default)
Maximum Depth	50	(Default)
Maximum Trees	50	(Default)
Minimum Category Size	5	(Default)
Variables to Try	3	(Default)
Alpha	0.2	(Default)
Exhaustive	5000	(Default)
Leaf Fraction	0.001	(Default)
Train Fraction	0.6	(Default)
Split Criterion	2	Gini
Missing Value Handling	1	Valid value

Number of Observations

Type	N
Number of Observations Read	768
Number of Observations Used	768

Figure 13.2 shows the Baseline Fit Statistics. PROC HPFOREST first computes baseline statistics without using a model. The listing shows a baseline misclassification rate of 0.349 because that is the proportion of observations with diabetes equal to 1.

Figure 13.2 HPFOREST Getting Started Example Output

Baseline Fit Statistics

Statistic	Value
Average Square Error	0.227
Misclassification Rate	0.349

Figure 13.3 shows the Fit Statistics. When not run on a grid, PROC HPFOREST computes fit statistics for a sequence of forests with an increasing number of trees. Typically the fit statistics improve (decrease) with the number of trees until reaching a rough bottom. Forest models provide an alternative estimate of average square error and misclassification rate, called the *out-of-bag* (OOB) estimate. It is a convenient substitute for an estimate based on test data, a less biased estimate of how the model will perform on future data. For more information, see the section "Bagging the Data" on page 226. The listing shows that the out-of-bag error estimate is worse (larger) than the estimate that evaluates all observations on all trees. This is usual. The out-of-bag misclassification rate for the model is 0.230, which is much less than the baseline rate of rate of 0.349. We can conclude that the model is good. In fact, 0.230 is the best misclassification rate (or close to it) in the literature for these data.

Figure 13.3 HPFOREST Getting Started Example Output

Fit Statistics

NTrees	NLeaves	Average Square Error (Full Data)	Average Square Error (OOB)	Misclassification Rate (Full Data)	Misclassification Rate (OOB)
1	7	0.183	0.217	0.284	0.341
2	17	0.165	0.210	0.250	0.311
3	34	0.154	0.202	0.219	0.306
4	60	0.145	0.196	0.215	0.287
5	77	0.141	0.190	0.198	0.275
6	97	0.137	0.184	0.197	0.274
7	113	0.137	0.181	0.190	0.262
8	125	0.135	0.175	0.188	0.257
9	133	0.136	0.171	0.198	0.249
10	157	0.133	0.169	0.191	0.244
11	176	0.133	0.169	0.194	0.240
12	182	0.134	0.168	0.201	0.242
13	201	0.132	0.167	0.194	0.244
14	220	0.131	0.166	0.193	0.238
15	243	0.130	0.165	0.190	0.240
16	254	0.131	0.164	0.193	0.238
17	274	0.130	0.164	0.193	0.244
18	286	0.131	0.163	0.190	0.244
19	301	0.131	0.164	0.199	0.245
20	323	0.131	0.164	0.194	0.248
21	338	0.130	0.163	0.194	0.248
22	353	0.130	0.162	0.189	0.244
23	372	0.130	0.162	0.193	0.244
24	388	0.130	0.162	0.188	0.245
25	400	0.130	0.161	0.184	0.243
26	412	0.131	0.162	0.188	0.247
27	422	0.131	0.162	0.193	0.250
28	440	0.131	0.162	0.193	0.249
29	460	0.130	0.162	0.191	0.242
30	478	0.130	0.162	0.185	0.242
31	495	0.130	0.162	0.188	0.240
32	504	0.130	0.161	0.185	0.238
33	527	0.130	0.162	0.189	0.236
34	538	0.130	0.161	0.189	0.238
35	562	0.129	0.161	0.186	0.236
36	574	0.130	0.161	0.188	0.237
37	583	0.130	0.161	0.190	0.236
38	592	0.130	0.160	0.189	0.234
39	606	0.130	0.160	0.188	0.230
40	623	0.129	0.160	0.189	0.237
41	637	0.130	0.160	0.186	0.237
42	651	0.130	0.160	0.189	0.236
43	664	0.130	0.161	0.190	0.237
44	676	0.131	0.161	0.188	0.238
45	686	0.131	0.161	0.191	0.236
46	711	0.130	0.161	0.188	0.236
47	732	0.130	0.161	0.189	0.230
48	753	0.130	0.160	0.189	0.229
49	769	0.130	0.160	0.189	0.230
50	782	0.130	0.160	0.188	0.230

Estimates of variable importance appear after the fit statistics. The NRules column in Figure 13.4 shows the number of splitting rules that use a variable. Section "Measuring Variable Importance" on page 243 explains the measures of importance. Each measure is computed twice: once on training data and once on out-of-bag data. As with fit statistics, the out-of-bag estimates are less biased. The GiniOOB column is negative for four variables. The splitting rules involving these variables are, on average, spurious. The worst is DiabetesPedigreeFn, suggesting that family history of diabetes is a misleading predictor, at least when measured with DiabetesPedigreeFn. The MarinOOB statistic gives DiabetesPedigreeFn more importance. The main conclusion from fitting the forest model to these data is that plasmaGlucose is the most important predictor of future onset of diabetes. Three other variables also contribute to the prediction.

Figure 13.4 HPFOREST Getting Started Example Output

Loss Reduction Variable Importance

Variable	NRules	Gini Reduction	Gini OOB	Margin	Margin OOB
plasmaGlucose	177	0.088300	0.03702	0.176600	0.095065
BodyMassIndex	118	0.028475	0.00506	0.056951	0.023278
NumPregnancies	106	0.016755	0.00377	0.033510	0.014685
Age	95	0.016540	0.00342	0.033080	0.014938
hrSerumInsulin	44	0.004026	−0.00098	0.008051	0.001538
tricepsSkinfold	44	0.003349	−0.00103	0.006698	0.001355
diastolicBloodPr	49	0.004052	−0.00261	0.008105	0.000316
DiabetesPedigreeFn	99	0.014013	−0.00404	0.028026	0.005053

Procedure Task Timing

Task	Time (sec.)	
Reading Data	1.73	84.7%
Training Forest	0.31	15.3%
Saving Model	0.00	0.00%

Syntax: HPFOREST Procedure

The following statements are available in the HPFOREST procedure:

PROC HPFOREST < *option(s)* > ;
  FREQ *variable* ;
  INPUT *variable(s)* < *option(s)* > ;
  PERFORMANCE *performance-options* ;
  SAVE < *options* > ;
  SCORE < *options* > ;
  TARGET *variable* < *option(s)* > ;

The PROC HPFOREST statement, INPUT, and TARGET statements are required. The INPUT statement can appear multiple times.

PROC HPFOREST Statement

PROC HPFOREST < *options* > **;**

The PROC HPFOREST statement invokes the procedure. You can specify one or more of the following optional arguments.

DATA=< *libref.*>*SAS-data-set*

names the SAS data set to be used by PROC HPFOREST for training the model. The default is the most recently created data set.

If the data are already distributed, the procedure reads the data alongside the distributed database. See the section "SMP and MPP Modes" on page 16 for the various execution modes and the section "Alongside-the-Database Execution" on page 22 for the alongside-the-database model. Data from all the computer grid nodes are combined into a structure that is optimized for model training and redistributed to the nodes. The different nodes then proceed independently with identical data to create decision trees.

ALPHA=*number*

specifies a threshold *p*-value for the significance level of a test of association of a candidate variable with the target. If no association meets this threshold, the node is not split. The default value is 0.2.

CATBINS=*k*

specifies the maximum number of categories of a nominal candidate variable to use in the association test. *k* refers only to the categories that are present in the training data in the node and that satisfy the MINCATSIZE= option. The categories are counted independently in each node. If more than *k* categories are present, then the least frequent categories are removed from the association test. Many infrequent categories can dilute a strong predictive ability of common categories. The search for a splitting rule uses all categories that satisfy the MINCATSIZE= options. The value of *k* must be a positive integer. The default value is 30.

EXHAUSTIVE=*number*

specifies the maximum number of splits to examine in a complete enumeration of all possible splits when the input variable is nominal and the target has more than two nominal categories. The exhaustive method of searching for a split examines all possible splits. If the number of possible splits is greater than *number*, then a heuristic search is done instead of an exhaustive search. The default value of *number* is 5,000.

LEAFFRACTION=*f*

specifies the smallest number of training observations that a new branch can have, expressed as the fraction of the number *N* of available observations in the DATA= data set. *N* might be less than the total number of observations in the data set because observations with a missing target value or non positive value of the variable specified in the FREQ statement are excluded from *N*. If you specify a number in the LEAFSIZE= option that implies a larger number than that specified in the LEAFFRACTION= option, *f* is ignored. The value *f* must be larger than 0 and less than 1. The default value is 0.001.

LEAFSIZE=*n*

specifies the smallest number of training observations a new branch can have. If you specify a value for the LEAFFRACTION= option that implies a larger value than *n*, the LEAFSIZE= option is ignored. The default value is 5.

MAXDEPTH=*d*

specifies the maximum depth of a node in any tree that PROC HPFOREST creates. The depth of a node equals the number of splitting rules needed to define the node. The root node has depth 0. The children of the root have depth 1, and on. The smallest acceptable value of *d* is 1. The default value of *d* is 50.

MAXTREES=*n*

specifies the number of trees in the forest. *n* is a positive integer. The number of trees in the resulting forest can be less than *n* when the HPFOREST procedure fails to split the training data for a tree. Up to two times *n* trees are attempted. If the procedure fails to split the training data for more than *n* trees, then less than *n* trees are created. The ALPHA=, LEAFSIZE=, and MINCATSIZE= options constrain the split search to form trees that are more likely to predict well using new data. Setting all of these options to 1 generally frees the search algorithm to find a split and train a tree, although the tree might not help the forest predict well. The default value of *n* is 50.

MINCATSIZE=*n*

specifies the minimum number of observations that a given nominal input category must have in order to use the category in a split search. Categorical values that appear in fewer than *n* observations are handled as if they were missing. The categories that occur in fewer than *n* observations are merged into the pseudo category for missing values for the purpose of finding a split. The policy for assigning such observations to a branch is the same as the policy for assigning missing values to a branch. The default value of *n* is 5.

MINUSEINSEARCH=*n*

specifies a threshold for utilizing missing values in the split search when MISSING=USEINSEARCH is specified as the missing value policy. If the number of observations in which the splitting variable has missing values in a node is greater than or equal to *n*, then PROC HPFOREST initiates the USEINSEARCH policy for missing values. See the section "Handling Missing Values" on page 241 for a more complete explanation. The default value of *n* is 1.

MISSING=USEINSEARCH | DISTRIBUTE

specifies how the training procedure handles an observation with missing values. If MISSING=USEINSEARCH and the number of training observations in the node is more than *n*, where *n* is the value of the MINUSEINSEARCH= option, then the missing value is used as a separate, legitimate value in the test of association and the split search. If MISSING=DISTRIBUTE, observations with a missing value of the candidate variable are omitted from the test of association and split search in that node. A splitting rule distributes such an observation to all branches. See the section "Handling Missing Values" on page 241 for a more complete explanation. By default, MISSING=USEINSEARCH.

NODESIZE=*n* | ALL

specifies the number of training observations to use for association tests and split searches. NODESIZE=ALL requests to use all the observations. The acceptable range is from two to two billion on most machines. The default value of *n* is 10,000.

The procedure counts the number of training observations in a node without adjusting the number with the values of the variable specified in the FREQ statement. If the count is larger than *n*, then the split search for that node is based on a random sample of size *n*. For categorical targets, the sample uses as many observations with less frequent target values as possible. The calculations for the association measures and split worth adjust the category counts to the category proportions in the node before sampling.

SEED=*n*

specifies the seed for generating random numbers. The HPFOREST procedure uses random numbers to select training observations for each tree and to select candidate variables in each node to split on. *n* is a nonnegative integer. Set *n* to 0 to use the internal default. The default value of the seed is 8,976,153.

SPLITSIZE=*n*

specifies the requisite number of training observations a node must have for the HPFOREST procedure to consider splitting it. By default, *n* is twice the value of the LEAFSIZE= option (or *n* is the value implied by LEAFFRACTION= option if the procedure ignores the LEAFSIZE= option). The procedure counts the number of observations in a node without adjusting the number with the values of the variable specified in the FREQ statement when it interprets the value specified in the LEAFFRACTION=, LEAFSIZE=, MINCATSIZE=, and SPLITSIZE= options.

TRAINFRACTION=*f*

specifies the fraction of training observations to train a tree with. Using less than all the available data often improves the generalization error. A different training sample is taken for each tree. *f* can be any number greater than 0 and at most 1. The default value of *f* is 0.6. PROC HPFOREST uses at least four observations in the training data regardless of how small *f* is (assuming four observations exist). If *f* is too small to accommodate the LEAFSIZE=, LEAFFRACTION=, and SPLITSIZE options then no tree is made. The TRAINN= option accepts an absolute number instead of a fraction to specify the same quantity. Specifying both the TRAINN= and TRAINFRACTION= options is an error.

TRAINN=*n*

specifies how many observations to use to train each tree. The observations are counted without regard to the variable specified in the FREQ statement. Using less than all the available data often improves the generalization error. A different training sample is taken for each tree. *n* can be any positive integer. If *n* is greater than the number of observations in the data set specified in the DATA= option, then all the available data are used. *n* must be at least 3 and large enough to accommodate the values of the LEAFSIZE=, LEAFFRACTION=, and SPLITSIZE options. The default value is 0.6 times the number of available observations in DATA= data set. The TRAINFRACTION= option accepts a fraction instead of an absolute number to specify the same quantity as the TRAINN= option. Specifying both the TRAINN= and TRAINFRACTION= is an error.

VARS_TO_TRY=*m* **| ALL**

specifies the number of input variables to consider splitting on in a node. *m* ranges from 1 to the number of input variables, *v*. The default value of *m* is $\sqrt{v}$. Specify VARS_TO_TRY=ALL to use all the inputs as candidates in a node.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. PROC HPFOREST accepts any positive value of a frequency variable without converting the value to an integer. If the frequency value is missing or less than or equal to 0, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

INPUT Statement

INPUT *variable(s)* < *option(s)* > **;**

The INPUT statement names input variables with common options. The INPUT statement can be repeated. You can specify the following *options*:

LEVEL=*level*

specifies the level of measurement of the variables. Accepted values of *level* are: BINARY, NOMINAL, ORDINAL, and INTERVAL.

ORDER=*order*

specifies the sorting order of the values of an ordinal input variable. Table 13.1 provides recognized values of *order*.

Table 13.1 ORDER= Option Values

Value of ORDER=	Variable Values Sorted By
ASCENDING	Ascending order of unformatted values (default)
ASCFORMATTED	Ascending order of formatted values
DESCENDING	Descending order of unformatted values
DESFORMATTED	Descending order of formatted values
DSORDER	Order of appearance in the input data set

NOTE: The DSORDER sort option is not supported for input data sets stored on the SAS appliance.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPFOREST procedure.

With the PERFORMANCE statement, you can also control whether the HPFOREST procedure executes in symmetric multiprocessing or massively parallel mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SAVE Statement

SAVE < *options* > **;**

The SAVE statement outputs the forest model information into a binary file. You can specify the following *options*:

FILE=*file-name*
names the file into which tree information is saved. The file name can be either a SAS file reference or the full path and member name of the binary file.

You can score new data sets against the forest model by specifying the name of this binary file in the FILE= option in the SCORE statement in the HP4SCORE procedure. For more information, see Chapter 6, "The HP4SCORE Procedure."

SCORE Statement

SCORE < *options* > **;**

The SCORE statement scores the training data set by using the forest model that was trained by PROC HPFOREST and outputs a data set that contains the scored results. The output data set contains the ID variables that are specified in the ID statement, predictions, residuals, and decisions. The prediction variables depend on the measurement type of the target variable in the model. For a target that has an interval measurement level, a single prediction variable is generated. For each level of the target that has a nominal measurement level, a posterior probability variable is generated in addition to the final predicted level. The names of the variables are constructed using the rules that are explained in the SAS Enterprise Miner product documentation.

OUT=< *libref.***>***SAS-data-set*
names the output data set to contain the scored data.

TARGET Statement

TARGET *variable* < **LEVEL=***level* > **;**

The TARGET statement names the variable whose values PROC HPFOREST tries to predict. You can specify the following optional argument:

LEVEL=*level*
specifies the level of measurement. Accepted values of *level* are: BINARY, NOMINAL, and INTERVAL. Note that *level* cannot be ORDINAL.

Details: HPFOREST Procedure

Bagging the Data

A decision tree in a forest trains on new training data that are derived from the original training data presented to the HPFOREST procedure. Training different trees with different training data reduces the correlation of the predictions of the trees, which in turn should improve the predictions of the forest.

The HPFOREST procedure samples the original data *without* replacement to create the training data for an individual tree. Most forest algorithms sample *with* replacement. The convention of sampling with replacement originated with Leo Breiman's *bagging* algorithm (Breiman 1996, 2001). The word *bagging* stems from "bootstrap aggregating," where "bootstrap" refers to a procedure that uses sampling with replacement. Breiman refers to the observations that are excluded from the sample as *out-of-bag* (OOB) observations. Therefore, observations in the training sample are called the *bagged* observations, and the training data for a specific decision tree are called the *bagged data*. Subsequently, Freedman and Popescu (2003) argued that sampling *without* replacement can provide more variability between the trees, especially with larger training sets.

The TRAINN= and TRAINFRACTION= options in the PROC HPFOREST statement specify the number of observations to sample without replacement into a bagged data set.

Estimating the goodness-of-fit of the model by using the training data is usually too optimistic; the fit of the model to new data is usually worse than the fit to the training data. Estimating the goodness-of-fit by using the out-of-bag data is usually too pessimistic at first. With enough trees, the out-of-bag estimates are an unbiased estimate of the generalization fit.

Training a Decision Tree

The HPFOREST procedure trains a decision tree by forming a binary split of the bagged data, then forming a binary split of each of the segments, and so on recursively until some constraint is met.

Creating a binary split involves a few subtasks:

1. selecting candidate inputs
2. reducing the number of nominal input categories
3. computing the association of each input with the target
4. searching for the best split that uses the most highly associated input

PROC HPFOREST selects candidate inputs independently in every node. The purpose of preselecting candidate inputs is to increase the differences between the trees, thereby decreasing the correlation and theoretically increasing the quality of the forest predictions. The selection is random, and each input has the same chance. The VARS_TO_TRY= option specifies the number of candidates to select. The quality of the forest often depends on the number of candidates. Unfortunately, a good value for the VARS_TO_TRY= option is generally not known in advance. Data with more irrelevant variables generally warrant a larger value.

The reason for searching only one input variable for a splitting rule instead of searching all inputs and choosing the best split is to improve prediction on new data. An input that offers more splitting possibilities provides the search routine more chances to find a spurious split. Loh and Shih (1997) demonstrate the bias towards spurious splits that result. They also demonstrate that preselecting the input variable and then searching only on that one input reduces the bias. The HPFOREST procedure preselects the input with the largest p-value of an asymptotic permutation distribution of an association statistic. Hothorn, Hornik, and Zeileis (2006) originated the idea and describe the statistic.

The HPFOREST procedure sometimes reduces the number of categories of a nominal input. Nominal inputs with fewer categories in the node than the number specified in the CATBINS= option are not modified. For nominal inputs with more categories, PROC HPFOREST ignores observations with the least frequent category values. Limiting the number of categories in a nominal input can strengthen the association of that input with the target by eliminating categories that have less predictive potential. PROC HPFOREST reduces the categories independently in every node.

The split search seeks to maximize the reduction in the Gini index for a nominal target and the reduction in variance of an interval target.

Controlling for Variable Selection Bias

Split-search algorithms generally inflate the worth of variables that offer many split possibilities beyond the predictive ability of the variable. Nominal variables are especially troublesome because they offer $2^{(k-1)}$ possible binary splits of the data, where k is the number of categories. A nominal variable that has many categories and no predictive power can produce a split of greater apparent worth simply by chance than a predictive variable that offers fewer split choices.

The problem motivated Gordon Kass to invent CHAID (Kass 1980), an algorithm that penalizes variables that produce more split candidates. The problem is mentioned in Breiman et al. 1984, p. 42, as one of the weaknesses of their algorithm. The problem is worse in Ross Quinlan's C5.0 algorithm (1993) because that algorithm creates many branches for a categorical input and only two for an interval input. Each branch provides an estimate of the target. Allowing some variables more estimates of a target than others gives those variables an unfair competitive advantage.

The HPFOREST procedure avoids the problem by not using the worth of a split to select the variable to split on. Instead, the inputs compete on a test of association with the target. The test adjusts for the different number of input categories. Only the winning variable is eligible for a splitting rule. Loh and Shih (1997) first proposed this in their QUEST algorithm. PROC HPFOREST uses the version in Hothorn, Hornik, and Zeileis (2006).

This section compares the different methods of selecting the variable to split the data. The data contain a purely random input X_j with j nominal categories and a second input Z_k with k categories that is predictive of the target. The plots show the proportions of samples in which a method selects X_j instead of

the predictive input, Z_k. The larger the proportion, the greater the bias of the method towards variables that offer more splitting possibilities than predictive power.

The data contain 500 observations. The target Y has values 0 and 1 with equal probabilities. Nominal input Z_k has equally probable integer values from 0 through $k-1$. The probability that $Y = 1$ given Z_k is greater than or equal to $k/2$ is 0.6 (and therefore $P(Y = 1|Z_k < k/2) = 0.4$). With enough data, a splitting algorithm that uses Z_k assigns values that are less than $k/2$ to one branch, and the rest to the other branch. X_j is equally distributed without reference to Y. With enough data, the best split on X_j has negligible worth. A variable selection method chooses between two variables. After repeating this for 1,000 samples, the proportion of times X_j is selected is recorded and plotted for several combinations of j and k.

Figure 13.5 shows the proportion of samples for which X_j is selected instead of Z_k when the split-search algorithm uses the reduction in Gini impurity as the splitting criterion. As shown in the figure, Gini reduction selects X_j more often as the number of categories j increases. When j is similar to k, Gini reduction selects X_j between 15% and 30% of the time. For $j-k = 10$, X_j is selected about 75% of the time. Gini reduction selects the wrong variable more often than not for these values of j and k.

Figure 13.5 Proportion of Samples for Which Gini Reduction Selects X_j



Figure 13.6 shows the proportion of samples for which X_j is selected using the CHAID split-search algorithm. The figure shows that CHAID selects X_j less often as the number of categories j increases. CHAID penalizes variables with many categories, and the penalty is larger than necessary. For $j - k = 10$, the proportion of times CHAID selects X_j decreases from about 70% ($j = 12$) to less than 10% ($j = 38$). CHAID selects the wrong variable more often than not for j much less than k.

Figure 13.6 Proportion of Samples for Which CHAID Selects X_j



Figure 13.7 shows the proportion of samples for which PROC HPFOREST selects X_j by using a test of association. As shown in the figure, given Z_k, PROC HPFOREST selects X_j the same proportion of times regardless of the number of categories j. When the number of categories k of Z_k increases, PROC HPFOREST selects X_j more often. However, the proportion never reaches 40%. PROC HPFOREST never selects the wrong variable more often than not for any values of j and k examined.

Figure 13.7 Proportion of Samples for Which an Association Test Selects X_j



The material in this section is part of a fuller discussion in de Ville, B. and Neville of variable selection bias.

Selecting a Splitting Variable

PROC HPFOREST considers only one input variable when it searches for a splitting rule in a node; it selects the variable with the highest association with the target. The measure of association is adapted from Hothorn, Hornik, and Zeileis (2006) and presented here.

Let Y and X denote the target variable and input variable, respectively. Let Y_i and X_i denote their values in observation i. The formulas for the association depend on whether Y and X are categorical. If Y is categorical, let J denote the number of values, and let Y_{ij} equal 1 if Y_i equals j and 0 otherwise. Similarly, if X is categorical, let K denote the number of values, and let X_{ik} equal 1 if X_i equals k and 0 otherwise. Let T denote the statistic defined in Table 13.2.

Table 13.2 Definition of T for Different Types of Variables

Type of Variable Y	X	Dimension of T	Definition
Interval	Interval	1	$T = \sum Y_i X_i$
J classes	Interval	J	$T_j = \sum Y_{ij} X_i$
Interval	K categories	K	$T_k = \sum Y_i X_{ik}$
J classes	K categories	$J \times K$	$T_{jk} = \sum Y_{ij} X_{ik}$

The test statistic is

$$C_{\text{quad}} = (T - \hat{\mu})^t \hat{\Sigma}^{-1} (T - \hat{\mu})$$

where

$\hat{\mu}$ = estimate of the expected value of T
$\hat{\Sigma}$ = estimate of the covariance of T
$\hat{\Sigma}^{-1}$ = generalized inverse of $\hat{\Sigma}$

PROC HPFOREST selects the variable with the smallest p-value, the integral from C_{quad} to infinity of the density of a chi-square distribution with degrees of freedom equal to the rank of $\hat{\Sigma}$.

Table 13.3 contains formulas for $\hat{\mu}$.

Table 13.3 Definition of $\hat{\mu}$ for Different Types of Variables

Type of Variable Y	X	Dimension of $\hat{\mu}$	Definition
Interval	Interval	1	$\hat{\mu} = (\sum Y_i)(\sum X_i)/N$
J classes	Interval	J	$\hat{\mu}_j = (\sum Y_{ij})(\sum X_i)/N$
Interval	K categories	K	$\hat{\mu}_k = (\sum Y_i)(\sum X_{ik})/N$
J classes	K categories	$J \times K$	$\hat{\mu}_{jk} = (\sum Y_{ij})(\sum X_{ik})/N$

To make the formulas more concise, let $J = 1$ and $Y_{ij} = Y_i$ when Y has an interval measurement level. Now J and Y_{ij} are defined for all types of Y. Similarly, let $K = 1$ and $X_{ik} = X_i$ when X has an interval measurement level. The multiple definitions of T in Table 13.2 now reduce to the single formula,

$$T_{jk} = \sum_{i=1}^{N} Y_{ij} X_{ik}$$

and the concise definition of $\hat{\mu}$ becomes

$$\hat{\mu}_{jk} = (\sum_{i=1}^{N} Y_{ij})(\sum_{i=1}^{N} X_{ik})/N$$

The dimension of $\hat{\Sigma}$ equals $(J \times K)^2$, the dimension of T squared. If X has a large number of categories, then K is large, and storing and inverting $\hat{\Sigma}$ can impede performance.

The formula for $\hat{\Sigma}$ is built as follows from the expectation and covariance of Y and a factor that depends on X:

$$
\begin{aligned}
\mathrm{E}(Y)_j &= \sum_{i=1}^{N} Y_{ij}/N \\
\mathrm{Cov}(Y)_{hj} &= \sum_{i=1}^{N} (Y_{ih} - \mathrm{E}(Y)_h)(Y_{ij} - \mathrm{E}(Y)_j)/N \\
\Xi_{kl} &= 1(k = l)(\sum_{i=1}^{N} X_{ik} X_{ik}) - (\sum_{i=1}^{N} X_{ik})(\sum_{i=1}^{N} X_{il}) \\
\hat{\Sigma}_{hjkl} &= \mathrm{Cov}(Y)_{hj} \Xi_{kl} N/(N-1)
\end{aligned}
$$

where $1(k = l)$ equals 1 when $k = l$ and 0 otherwise.

Searching for a Splitting Rule

Rules

A PROC HPFOREST splitting rule uses the value of a single input variable to assign an observation to one of two branches. If the split-search algorithm uses missing values, then the rule includes an assignment of missing values to a branch.

A rule might assign all observations with a nonmissing value of the splitting variable to one branch, and all observations with a missing value to the other. In this case, the missing values go the second branch.

If the split-search algorithm does not use missing values, then the rule assigns an observation with a missing value to both branches and adds to each copy a fractional weight that is proportional to the number of training observations in each branch. This is the policy when the splitting variable contains no missing variables in the node during training, even if the MISSING=USEINSEARCH option is specified.

Criteria

The HPFOREST procedure searches for rules that maximize the measure of worth that is associated with the splitting criterion. Formally, the worth of a split s is the reduction in node impurity,

$$\Delta i(s, \omega) = i(\omega) - \sum_{b=1}^{B} p(\omega_b|\omega) i(\omega_b)$$

where $i(\omega)$ is the impurity of the node ω, and $p(\omega_b|\omega)$ is the proportion of training observations in branch b. Generally, $p(\omega)$ is a nonnegative number that equals 0 if all observations in ω have the same target value, and $p(\omega)$ is large if the target values in ω are very different.

The impurity function for the Gini index is

$$i(\omega) = 1 - \sum_{j=1}^{J} p_j^2$$

where p_j is the probability of target value j. The impurity function for variance reduction is

$$i(\omega) = \frac{1}{N(\omega)} \sum_{i=1}^{N(\omega)} (Y_i - \bar{Y})^2$$

where $N(\omega)$ is the number of observations in node ω, Y_i is the target value of observation i, and $\bar{Y}$ is the average of Y_i in ω.

Algorithm

PROC HPFOREST searches for a splitting rule as follows:

1. It sorts the values in one of the following ways:
   - For an interval or ordinal input, it sorts by nonmissing values of the input.
   - For a nominal input with interval target, it sorts the categories by the average target value in the category.
   - For a nominal input with binary target, it sorts the categories by the proportion of one of the target values in the categories.
2. It walks from the lowest to the highest values, and it evaluates the split at every permissible position. A permissible position is one that does not separate two observations with the same target value and that satisfies any constraints, such as the LEAFSIZE= option.

If the algorithm allows missing input values, then the algorithm evaluates two splits at every permissible position of an interval or ordinal input: one that assigns the missing values to the left branch, and another that assigns missing values to the right branch.

For a nominal input, sorting reduces the number of candidate splits to $m - 1$ from $2^{(m-1)}$, where m is the number of nominal categories. Fisher (1958) proved it works and that the best split is among the $m - 1$ examined. Breiman et al. (1984) applied their theorem to decision trees.

No similar reduction is known for a nominal input with a nominal target (with more than two categories). However, PROC HPFOREST uses the following simple extension which usually works: For each nominal target category y, it sorts the input categories by the proportion of y and finds the best permissible split among the $m-1$ sorted positions. A total of km splits are considered, where k denotes the number of target values. PROC HPFOREST uses this approach unless the value of the EXHAUSTIVE= option is greater than or equal to $2^{(m-1)}$, in which case PROC HPFOREST examines all permissible splits.

Before PROC HPFOREST applies the algorithm, it might combine small nominal input categories to satisfy the CATBINS= and MINCATSIZE= options. The algorithm uses the combined category only if MISSING=USEINSEARCH and the number of missing observations in the node is greater than or equal to the value of the MINUSEINSEARCH= option.

Predicting an Observation

To predict an observation, the HPFOREST procedure first assigns the observation to a single leaf in each decision tree in the forest, then uses that leaf to make a prediction based on the tree that contains the leaf, and finally simply averages the predictions over the trees. For an interval target, the prediction in a leaf equals the average of the target values among the bagged training observations in that leaf. For a nominal target, the *posterior probability* of a target category equals the proportion of that category among the bagged training observations in that leaf. The predicted nominal target category is the category with the largest posterior probability. In case of a tie, the first category that occurs in the training data is the prediction.

The HPFOREST procedure also computes out-of-bag predictions. The *out-of-bag prediction* of an observation uses only trees for which the observation is out of bag (that is, not selected as part of the training data for that tree).

A model is worthless if its predictions are no better than predictions without a model. For an interval target, the *no-model* prediction of an observation is the average of the target among training observations. For a nominal target, the no-model posterior probabilities are the class proportions in the training data. The no-model predictions are the same for every observation.

Computing the Average Square Error and Misclassification Rate

The HPFOREST procedure computes the average square error and the misclassification rate to assess the model's goodness of fit. The average square error applies to all types of targets. The misclassification rate applies only to nominal targets.

The average square error for an interval, the average square error for a nominal target, and the misclassification rate for a nominal target are defined respectively as

$$\mathrm{ASE}_{\mathrm{int}} = \sum_{i=1}^{N} \frac{(y_i - \hat{y}_i)^2}{N}$$

$$\mathrm{ASE}_{\mathrm{cat}} = \sum_{i=1}^{N} \sum_{j=1}^{J} \frac{(\delta_{ij} - \hat{p}_{ij})^2}{JN}$$

$$\mathrm{MISC} = \sum_{i=1}^{N} \frac{1(y_i \neq \hat{y}_i)}{N}$$

where $\hat{y}_i$ is the target prediction of observation i, δ_{ij} equals 1 or 0 if the nominal target value j does or does not occur in observation i, respectively, $\hat{p}_{ij}$ is the predicted probability of nominal target value j for observation i, N is the number of observations, and J is the number of nominal target values (classes).

The definitions are valid whether $\hat{y}_i$ is the usual model prediction, the out-of-bag prediction, or the no-model prediction. The three predictions result in three different estimates of $\mathrm{ASE}_{\mathrm{int}}$. The model has some predictive ability if the out-of-bag estimate of fit is smaller than the no-model estimate. The $\mathrm{ASE}_{\mathrm{int}}$ that is based on the usual model predictions of the original training data is usually optimistic, smaller than what its value will be on future data.

Adjusting Statistics When Sampling Target Classes Unevenly

When the proportions of target classes in the training data differ from the proportions in the population to which the model is applied, predictions and fit statistics need to be adjusted for the population of interest. Consider fraud detection as an example. A random sample of 100,000 transactions might have too few fraudulent observations for training a good model. One solution is to preferentially include fraudulent cases in the sample. Adding extra observations of a rare target class into the training data is called *oversampling*. Another solution is to randomly sample enough transactions (several million perhaps) to obtain enough fraudulent cases. In this situation, the number of non-fraudulent cases might be more than are necessary for

training and might be a burden for data processing. Removing observations of a common target class from the training data is called *undersampling*.

Typically, the greater the class proportion in the training data, the greater the class posterior probability from a model. When the class proportions in the training data differ from those in the population of interest, the model inflates the predictions of the classes that are overrepresented in the training data. The following sections explain how to adjust the predictions and the fit statistics that estimate how well the model will perform when applied, illustrate why the adjustments matter, and present a technical derivation of the adjustment formulas.

Formulas for Adjusting the Predictions and Fit Statistics

The formulas for adjusting the probabilities and statistics assume that the distribution of the inputs for a target class is the same in the training data as in the population of interest. The class proportions can differ, but the distribution of input values within a class must be the same.

The formula for converting probabilities from the training sample to the population of interest is

$$\widehat{p_{\pi j}} = \frac{p_{\tau j}\gamma_j}{\sum_k p_{\tau k}\gamma_k}$$

where

$\widehat{p_{\pi j}}$ = estimate of $p_{\pi j}$ that is computed with the training data
$p_{\pi j}$ = adjusted probability of class j for the population of interest
$p_{\tau j}$ = unadjusted probability of class j for the training data
$\gamma_j = \pi_j / \tau_j$
π_j = proportion of class j in the population of interest
τ_j = proportion of class j in the training data

The circumflex above a population statistic such as $p_{\pi j}$ indicates that the statistic is estimated from training data. A population statistic without a circumflex indicates that the statistic is computed from population data.

Let *S* denote a statistic that can be expressed as the average of a loss metric, Loss(*y, p(y)*), between the actual target value and the predicted probabilities. Average square error and misclassification rate are examples.

The probability *p(y)* might be adjusted or unadjusted, and the average might be taken over the training data or the population of interest. An optional argument to *S* indicates whether the probabilities are adjusted, and an optional suffix indicates the sample for evaluating the statistic. Thus,

$$\begin{aligned}
S_\tau(p_\tau) &= \sum_{i=1}^{N_\tau} \frac{\text{Loss}(y_i, p_{\tau i})}{N_\tau} \\
S_\tau(p_\pi) &= \sum_{i=1}^{N_\tau} \frac{\text{Loss}(y_i, p_{\pi i})}{N_\tau} \\
S_\pi(p_\tau) &= \sum_{i=1}^{N_\pi} \frac{\text{Loss}(y_i, p_{\tau i})}{N_\pi} \\
S_\pi(p_\pi) &= \sum_{i=1}^{N_\pi} \frac{\text{Loss}(y_i, p_{\pi i})}{N_\pi}
\end{aligned}$$

To compute the estimate of a population statistic $S_\pi(p_\pi)$, multiply the terms for target class j by the proportion of class j observations in the population as

$$\widehat{S_\pi} = \sum_j S_{\tau j}(\widehat{p_\pi})\pi_j$$

where

$$\begin{aligned} S_{\tau j}(\widehat{p_\pi}) &= \sum_{i \ni y_i = j} \frac{\text{Loss}(y_i, \widehat{p_{\pi ij}})}{N_{\tau j}} \\ N_{\tau j} &= \text{number of class } j \text{ observations in the training data} \end{aligned}$$

The class j formulas for the average square error and misclassification rate are

$$\begin{aligned} \text{ASE}_{\tau j} &= \sum_{i \ni y_i = j} \sum_{k=1}^{J} \frac{(\delta_{jk} - \hat{p}_{\pi ik})^2}{J N_{\tau j}} \\ \text{MISC}_{\tau j} &= \sum_{i \ni y_i = j} \frac{1(j \neq \hat{y}_i)}{N_{\tau j}} \end{aligned}$$

where

$$\begin{aligned} \delta_{jk} &= 1 \text{ if } j = k \text{ and 0 otherwise} \\ \hat{y}_i &= \text{the class } k \text{ with the largest value of } \widehat{p_{\pi ik}} \end{aligned}$$

Why the Adjustments Matter

This section illustrates the need to adjust probabilities and statistics. The data consist of a binary target and two independent input variables from a normal distribution with standard deviation of 0.25. The mean value of an input is 0.25 for target class 0, and is 0.75 for class 1.

The test data set has 20,000 class 0 observations and 80,000 class 1 observations. All runs use the same test data. The training and validation data sets have 5,000 observations. The percentage of class 0 observations varies from 5 to 95. For each percentage, 20 training and validation data sets are generated. A decision tree is fit to each of the 20 training data sets and applied to the test data.

Figure 13.8 shows the misclassification rate of each tree, which is evaluated on the test data. A smooth curve passes near the average misclassification rate at each percentage of class 0 observations. (Technically, the curve is a cubic spline with λ equal to 0.05.) The rate is computed twice: once with the probabilities adjusted for the class proportions in the test data, and once without adjusting. A separate curve is drawn for each. The two rates are the same when the proportion of class 0 observations in the training data is 20 percent, which is the same as in the test data. The misclassification rates increase (get worse) as the class proportions in the training data differ more from the proportions in the test data. If you could choose the proportions of the target classes in the training data, this example suggests that the best choice would be to choose the same proportions as in the population of interest. However, if one target value is rare, oversampling would still be necessary to ensure that the training data have enough rare observations for the algorithm to work with.

In this example, adjusting probabilities is better because the rates that are computed after adjusting probabilities are generally smaller (better) than those computed without adjusting. The difference is larger when the class proportions in the training data differ more from those in the test data.

Figure 13.8 Test Set Misclassification Rates Using Adjusted and Unadjusted Predictions



Figure 13.9 shows the average square error (ASE) for each tree, which is evaluated on the test data. A smooth curve passes near the average ASE for each percentage of class 0 observations. When the proportion of class 0 observations in the training data is 0.5 or less, adjusting the probabilities makes no difference to the ASE. For larger proportions of class 0, adjusting the probabilities results in a slightly larger (worse) ASE in this example.

Figure 13.9 Test Set Average Square Error Using Adjusted and Unadjusted Predictions



Figure 13.10 shows the misclassification rate that is computed using validation data and adjusted probabilities. The rate is estimated in two ways: one estimate adjusts only the probabilities, and the other adjusts both the statistics and the probabilities. The two are defined respectively as

$$\text{MISC}_{\text{unadjusted}} = \sum_{j}^{J} \sum_{i \ni y_i = j} \frac{1(j \neq \hat{y}_i)}{N_{\tau j}} \frac{N_{\tau j}}{N_{\tau}}$$

$$\text{MISC}_{\text{adjusted}} = \sum_{j}^{J} \sum_{i \ni y_i = j} \frac{1(j \neq \hat{y}_i)}{N_{\tau j}} \pi_j$$

Only the last factor in each term is different. In Figure 13.10, the curve for $\text{MISC}_{\text{adjusted}}$ is indistinguishable from the curve for the test set misclassification rate. $\text{MISC}_{\text{adjusted}}$ predicts the test set rate perfectly in this example. On the other hand, the curve for $\text{MISC}_{\text{unadjusted}}$ is completely different and unreliable. Adjusting the misclassification rate is necessary in this example to get a good estimate of the rate in the test set.

Figure 13.10 Estimates of Test Set Misclassification Using Adjusted and Unadjusted Statistics



Figure 13.11 is the corresponding plot for ASE. The solid gray curve passes near the average ASE that is computed on the test data. The dashed blue curve that approximately follows the gray curve is the adjusted statistic that is computed on the validation data. The dashed green hill-shaped curve is the unadjusted statistic that is computed on the validation data. The evidence for adjusting the statistics for ASE is less compelling in this example than for the misclassification rate. For class 0 proportions between 45 and 65%, the unadjusted estimates of ASE are closer to the test set ASE than the adjusted estimates. For other class 0 proportions, the adjusted estimates are closer.

Figure 13.11 Estimates of Test Set ASE Using Adjusted and Unadjusted Statistics



Technical Derivations of Adjustment Formulas

The formulas for adjusting the probabilities and statistics rely on statistical theory that assumes that the training data and the population of interest are both samples drawn from two infinite, ideal populations. For each target value, the distributions of the inputs are assumed to be the same in the two ideal populations: $P(X_\tau|Y_\tau = j) = P(X_\pi|Y_\pi = j)$, where X_τ and Y_τ designate the inputs and target random variables in the population of the training sample and X_π and Y_π designate the inputs and target variables in the population of interest.

The formulas also assume that the model predictions converge to the population probabilities $P(y = j|x)$ as the training sample becomes large. The formula for adjusting the probabilities follows from Bayes' theorem, where α is a constant that is independent of the target class:

$$\begin{aligned} P(Y_\pi = j|X_\pi) &= P(X_\pi|Y_\pi = j)\frac{P(Y_\pi=j)}{P(X_\pi)} \\ &= P(X_\tau|Y_\tau = j)\frac{P(Y_\pi=j)}{P(X_\pi)} \\ &= P(Y_\tau = j|X_\tau)\frac{P(X_\tau)}{P(Y_\tau=j)}\frac{P(Y_\pi=j)}{P(X_\pi)} \\ &= P(Y_\tau = j|X_\tau)\frac{P(Y_\pi=j)}{P(Y=j)}\frac{P(X_\tau)}{P(X_\pi)} \\ &= P(Y_\tau = j|X_\tau)\frac{P(Y_\pi=j)}{P(Y_\tau=j)}\alpha \end{aligned}$$

The sum of the class probabilities equals 1:

$$\sum_j P(Y_\pi = j|X_\pi) = 1$$

Therefore,

$$\alpha = \frac{1}{\sum_j P(Y_\tau = j|X_\tau)P(Y_\pi = j)/P(Y_\tau = j)}$$

The formula works well when the model predictions are close to the population probabilities, $P(y = j|x)$. Similarly, the formula for adjusting a statistic S works well when S is close to its expected value. $S_\pi(p_\pi)$ equals the average of a loss function over a sample from the population of interest, and $S_\tau(p_\pi)$ equals the average of a loss function over the training population. The central limit theorem asserts that $S_\pi(p_\pi)$ converges to its expected value, $E_\pi(\text{Loss}(Y, p_\pi))$, as the sample size increases. Similarly, $S_\tau(p_\pi) \rightarrow E_\tau(\text{Loss}(Y, p_\pi))$. The same is true when the average is restricted to observations with the same target value, $S_{\tau j}(p_\pi) \rightarrow E_{\tau j}(\text{Loss}(Y, p_\pi))$. The formula that uses S_τ to estimate S_π assumes the averages are close to their expected values.

$$\begin{aligned} E_\pi(\text{Loss}(Y_\pi, p_\pi)) &= \iint \text{Loss}(Y_\pi, p_\pi)p(X_\pi, Y_\pi)\,dX_\pi\,dY_\pi \\ &= \textstyle\sum_j \int \text{Loss}(Y_\pi, p_\pi)p(X_\pi|Y_\pi = j)dX_\pi P(Y_\pi = j) \\ &= \textstyle\sum_j \int \text{Loss}(Y_\tau, p_\pi)p(X_\tau|Y_\tau = j)dX_\tau P(Y_\pi = j) \\ &= \textstyle\sum_j E_{\tau j}(\text{Loss}(Y_\tau, p_\pi))P(Y_\pi = j) \end{aligned}$$

King and Zeng (2001, Appendix B) discuss the adjustments of probabilities in more detail. Discussions of the adjustments of the statistics are hard to find.

Handling Missing Values

Strategies

Tree-based models use observations with missing input values. The HPFOREST procedure offers two strategies for handling missing values. The simplest strategy is to regard a missing value as a special nonmissing value. For a nominal input, a missing value simply constitutes a new categorical value. For an input whose values are ordered, each missing value constitutes a special value that is assigned a place in the ordering that yields the best split. The place is generally different in different nodes of the tree.

This strategy is beneficial when missing values are predictive of certain target values. For example, people with large incomes might be more reluctant to disclose their income than people with ordinary incomes. If income were predictive of a target, then missing income would be predictive of the target and the missing

values would be regarded as a special large income value. The strategy seems harmless when the distribution of missing values is uncorrelated with the target because no choice of branch for the missing values would help predict the target.

A linear regression could use the same strategy by adding binary indicator variables to designate whether a value is missing. Alternatively, and much more commonly, a linear regression could simply remove observations in which any input is missing. Let p denote the probability that a variable value is missing, and let v denote the number of input variables. The probability that an observation has one or more missing values is $(1 - p)^v$ (assuming missingness is independent and identically distributed among the inputs). If $p = 0.1$ and $v = 10$, then 65% of the observations would have missing values and be removed from linear regression.

The alternative strategy for decision trees is to exclude from the search algorithm observations that have a missing value in the single input variable that defines the splitting rule. If $p = 0.1$ and $v = 10$, then only 10% instead of 65% of the observations are excluded. Although this compares favorably with common linear regression, using observations with missing values might still be better. PROC HPFOREST is designed to run faster by using observations with missing values than by not using them.

When missing values are excluded from the split search, a new policy is needed for assigning an observation with missing values to a branch. Assigning all the observations with missing values to a single branch is likely to reduce the purity of the branch, thereby degrading the split. Instead, the HPFOREST procedure assigns the observation to both branches by replacing the single observation with two copies and assigning each copy a fractional frequency that is proportional to the size of the branches. The prediction for an observation is the weighted average of predictions of the derived fractional observations. The prediction that uses the two child nodes is the same as the prediction that would be obtained from not splitting the node. (This can be proved as follows: The prediction based on the two child nodes is the weighted average of the predictions of the two child nodes. The prediction in a node is the average of some variable. The weighted average of the averages in the child nodes is the average in the parent, which is the prediction based on the parent.)

Specifics

If the value of a target variable is missing, the observation is excluded from training and from evaluating the model. If the value of an input variable is missing, PROC HPFOREST uses the missing value as a legitimate value by default or if MISSING=USEINSEARCH and the number of observations in which the splitting variable has missing values is at least as large as the value of the MINUSEINSEACH= option.

Specifying MISSING=DISTRIBUTE forces every splitting rule to distribute an observation to the branches when the value of the splitting variable is missing. Specifying MISSING=USEINSEARCH also produces rules that distribute observations if the splitting variable has no missing values in the training data or when the value specified in the MINUSEINSEACH= option prevents using missing values in the search.

Observations that are distributed into multiple branches might slow down training noticeably. Values of distributed observations in a leaf are stored in a linked list and passed to the association and split-search routines individually. Values of observations that are not distributed (that is, observations that reside entirely within one leaf) are passed together in a single vector. Processing a single vector of values is much faster than plodding through a linked list and calling an accumulation routine separately for each value.

The discussion in this section applies to each candidate variable and each node separately. For example, the test of association that uses input variable X might use all observations, and the test that uses input variable

Z might ignore some observations because of missing values. The test that uses X might use all observations in one node but not all observations in another node.

Handling Values That Are Absent from Training Data

A splitting rule that uses a categorical variable might not recognize all possible values of the variable. Some categories might not exist in the training data. Others might be so infrequent in the training sample in the node that the procedure excludes them. The MINCATSIZE= option specifies the minimum number of occurrences required for a categorical value to participate in the search for a splitting rule. Splitting rules handle unseen categorical values the same way they handle missing values.

Measuring Variable Importance

The importance of a variable is the contribution it makes to the success of the model. For a predictive model, success means good prediction. Often the prediction relies mainly on a few variables. A good measure of importance reveals those variables. The better the prediction, the closer the model represents reality, and the more plausible it is that the important variables represent the true cause of prediction. Some people prefer a simple model so they can understand it. However, a simple model usually relinquishes details of reality. Sometimes it is better to first find a good model and ask what variables are important than to first ask what model is good for variable importance and train that model.

M. J. van der Laan (2006) asks whether a predictive model is appropriate at all. He believes that if variable importance is your goal, then you should predict importance directly instead of fitting a model. If your goal is to select suspicious genes for further study in a lab or to find variables in an industrial process that might influence the quality of the product, then his argument is persuasive. However, the purpose of many predictive models is to make predictions. In these cases, gaining insight to causes can be useful.

Variable importance is also useful for selecting variables for a subsequent model. The comparative importance between the selected variables does not matter. Researchers often seek speed and simplicity from the first model and seek accuracy from the subsequent model. Despite this tendency, a forest is often more useful than a simpler regression as a first model when interactions are wanted because variables contribute to the forest model through interactions.

Several authors have demonstrated that using a forest to select variables, then using only those variables in a subsequent forest, and then repeating the process produces a final forest with better prediction than the original.

Leo Breiman's seminal publication (2001) gives one measure of importance, which is called *Breiman's method* here. Breiman and Cutler (2003) introduce another method, which they call *Gini increase* but which is called *loss reduction* here for reasons discussed in the following section. Several modifications to Breiman's method have been proposed. *Strobl's method* (2008) assigns less importance to correlated variables than Breiman's method, which in turn assigns less than loss reduction. Strobl's method is also the most complex and takes the longest time to compute. Breiman's method is again in the middle. Running time is the main reason Breiman introduced loss reduction.

Loss Reduction

Loss reduction is also called Gini increase, Gini importance, or impurity reduction. It was introduced in Breiman et al. (1984) for decision trees, later modified for gradient boosting machines (Friedman 2001), and later used in forests (Breiman and Cutler 2003).

The importance of variable v is proportional to the sum of the reduction in node impurity, summed over nodes that v splits. Breiman et al. (1984) and Breiman and Cutler (2003) introduce the impurity measure with the Gini splitting criterion, hence the name Gini importance. However, Gini impurity is defined only for a categorical target. For an interval target, the most common node impurity measure is the sum of square errors. Friedman (2001) uses a square root at the end of the calculation to revert back to the scale of the target. This can fail when you use validation data because the impurity reduction can be negative. Therefore, the HPFOREST procedure computes both the reduction in absolute error and the reduction in square error.

PROC HPFOREST uses the word *loss* instead of *impurity* to associate the measure of importance with the reduction in loss from using the model. A loss function is a statistic that measures how well a model fits data. Average square error is a common loss function. Given a loss function, the next equation defines an associated measure of variable importance. The sum over variables of the associated variable importance equals the total loss when a model is not used minus the loss when a model is used. In other words, the loss reduction variable importance assigns shares to the variables of the total reduction in the loss that the model achieves.

The loss reduction variable importance for input v in tree T is computed as

$$I_{\text{loss}}(v;T) \propto \sum_{\omega \in T} 1(v \text{ splits } \omega)\Delta\text{Loss}(\omega)$$

where the sum is over internal nodes ω in T and where $1(v \text{ splits } \omega)$ is 1 if v is the splitting variable in ω and 0 otherwise. $\Delta\text{Loss}(\omega)$ is the reduction in loss from splitting ω. A loss function maps a response value and a prediction to a number that represents how bad the prediction is. Square error loss is most common,

$$\Delta\text{Loss}(\omega) = \text{SSE}(\omega) - \sum_{b \in B(\omega)} \text{SSE}(\omega_b)$$

$$\text{SSE}(\omega) = \begin{cases} \sum_{i=1}^{N(\omega)} (Y_i - \hat{Y}(\omega))^2 & \text{for interval target } Y \\ \sum_{i=1}^{N(\omega)} \sum_{j=1}^{J} (\delta_{ij} - \hat{p}_j(\omega))^2 & \text{for target with } J \text{ categories} \end{cases}$$

where

$B(\omega)$ = set of branches from ω
ω_b = child node of ω in branch b
$N(\omega)$ = number of observations in ω
$\hat{Y}(\omega)$ = average Y in training data in ω
δ_{ij} = 1 if $Y_i = j$, 0 otherwise
$\hat{p}_j(\omega)$ = average δ_{ij} in training data in ω

For an interval target, PROC HPFOREST also computes absolute error loss,

$$\Delta\text{Loss}(\omega) = \text{SAE}(\omega) - \sum_{b \in B(\omega)} \text{SAE}(\omega_b)$$

where

$$\text{SAE}(\omega) = \sum_{i=1}^{N(\omega)} |Y_i - \hat{Y}(\omega)|$$

For a categorical target, the formula for $\text{SSE}(\omega)$ reduces to

$$\text{SSE}(\omega) = \begin{cases} N(1 - \sum_{j=1}^{J} \hat{p}_j^2) & \text{for training data} \\ N(1 - \sum_{j=1}^{J} (2p_j - \hat{p}_j)\hat{p}_j) & \text{for validation data} \end{cases}$$

where p_j is the proportion of the validation data with target value j, and N, p_j, and $\hat{p}_j$ are evaluated in node ω. $\text{SSE}(\omega)$ for training data equals the Gini impurity index. Loss reduction variable importance is commonly called Gini importance for this reason.

Another measure of importance for a categorical target is based on the margin, the probability of the true class minus the maximum probability of the other classes. A good model increases the margin. Therefore, loss reduction variable importance uses the negative of margin.

$$\Delta\text{Loss}(\omega) = \text{SNM}(\omega) - \sum_{b \in B(\omega)} \text{SNM}(\omega_b)$$

where

$$\text{SNM}(\omega) = -\sum_{j=1}^{J} N_j(\hat{p}_j - \max_{k \neq j} \hat{p}_k)$$

and N_j is the number of class j observations in ω in the data set being used to evaluate the variable importance.

When the target is binary, variable importance based on the margin equals twice that of the variable importance based on the Gini index.

Breiman's Method

Breiman's method is also called a permutation-based or randomization method. Breiman's method calculates importance as

$$I_{\text{Breiman}}(v; T) \propto \sum_{i=1}^{n} \text{Loss}(y_i, \hat{y}_i(\pi(v))) - \sum_{i=1}^{n} \text{Loss}(y_i, \hat{y}_i)$$

where $\hat{y}_i$ is the prediction for observation i and $\hat{y}_i(\pi(v))$ is the prediction for observation i after randomizing the values of input v. In Breiman's writings, the sum uses only out-of-bag observations, and randomizing is done by permuting the out-of-bag values of v. Originally Breiman (2001) uses misclassification as the loss function. Breiman and Cutler (2003) retract that, saying misclassification loss is too volatile with many variables. Instead they recommend the margin for a nominal target: the probability of the true class minus the maximum probability among the other classes. Breiman (2001) bases the loss on the entire forest, not a single tree. Today authors generally compute the importance for each tree and then average these (Berk 2008; Grömping 2009).

Bias and Correlation

The loss reduction method uses only the variables that PROC HPFOREST selects for splitting rules. Selecting the wrong variable among candidates that compete for a rule reduces the importance of the correct variable in the final tally. Variable selection bias produces bias in variable importance as a consequence. PROC HPFOREST uses a variable selection method that is widely agreed to be free from bias for practical purposes (Strobl et al. 2008).

Even so, only one of possibly several deserving variables is selected in a node for splitting. Only one gets credit for loss reduction in a node. Ideally, a forest handles this by letting the variables compete many times in many trees with slightly different data and in nodes in which some variables are randomly excluded. The process should result in a fair distribution of the use of the variables, without correlated inputs masking each other, and a fair representation in the final variable importance.

What variable importance measures actually do with correlated variables is subtle. Suppose X and Z are correlated, and $Y = X$. Should Z be assigned any importance? One answer is no: Z is not even in the formula that generates Y. The other answer is yes: observing Z provides information about Y, and therefore Z is helpful in explaining the variation of Y. An input W has *conditional* importance if it is needed for prediction even after values of the other variables are given. Z has no conditional importance. An input W has *marginal* importance if it is predictive of Y by itself. Z has marginal importance.

The degree to which correlations determine the final importance values depends both on the algorithm for importance and on the algorithmic parameters for the model. In the current example, if VARS_TO_TRY=2, then X and Z compete in every node, PROC HPFOREST selects X to split almost all the nodes, and all importance measures assign Z negligible importance. If VARS_TO_TRY=1, then PROC HPFOREST must use Z to split some nodes, and it assigns some importance to Z. In general, loss reduction assigns more importance to correlated variables than Breiman's method, and Breiman's method assigns more importance than a conditional permutation method discussed in Strobl et al. (2008).

To illustrate, you can generate 500 bivariate correlated normal observations, run PROC HPFOREST with VARS_TO_TRY=1, and plot the proportion of total importance that is assigned to Z. Figure 13.12 shows the result from generating 25 samples at each of several correlation values that range from 0 to 1. The figure has a point for each of three measures of importance that are evaluated on each sample. Unless the correlation equals 1, Breiman's method and Strobl's method assign little importance to Z. (Strobl's method extends Breiman's method by first segregating the observations by quantiles of X, then permuting Z within the quantile limits, and then scoring the result to compute the importance of Z.) All methods pick X as the most important variable unless they are perfectly correlated.

Figure 13.12 Z's Proportion of Total Importance



Archer and Kimes (2008) present a simulation that compares the variable importance methods. To emulate genomic data, correlated variables appear in groups, and at most one variable in a correlated group is in the regression equation that generates the target. Both forest methods are about as good as using a method of variable importance from regression. This is consistent with Figure 13.12, which deems X the most important variable by every method and every correlation value except a correlation of 1.

Preferences

Loss reduction applies to tree-based models. Breiman's method can apply to any predictive model by using hold-out data instead of out-of-bag data. However, it is generally not used in practice. One reason is the long running time needed to score every observation for every variable that is evaluated. A more important reason is the lack of a convincing example where Breiman's method succeeds and others fail. The comparison in the previous section applies only to forests because only in forests can the VARS_TO_TRY= option be set. No comparison of importance measures is published with the VARS_TO_TRY= option equal to all the variables.

Some authors insist on using Breiman's method. Berk (2008) says that importance must be measured outside of the procedure that is used to measure it. Otherwise, it is not a practical measure. It simply restates a part

of the model itself without reference to the practical reason for creating the model. Nicodemus and Malley (2009) present plots that clearly show loss reduction as hopelessly biased, while Breiman's method gives the correct results on the same data. Actually, they are not the same data. All these authors use training data with loss reduction and hold-out data with Breiman's method. Berk even says loss reduction is a fit measure, and as such should be used with the training data. This is misguided. Using hold-out data to evaluate a predictive model is generally recommended. Computing loss reduction with both training and validation data can reveal which inputs are fooling the training algorithm, and corrective action can be taken.

Displaying the Output

The HPFOREST procedure displays the parameters used to train the model, fit statistics of the trained model, and the time it took to train. If PROC HPFOREST is not run on a grid of computers, the evolution of fit statistics as the number of trees increases is displayed.

ODS Table Names

Table 13.4 lists the names of the data tables created by the HPFOREST procedure. Use these names in ODS statements.

Table 13.4 ODS Tables Produced by PROC HPFOREST

Table Name	Description	Required Statement / Option
PerformanceInfo	Performance information	Default output
NObs	Number of observations	Default output
Baseline	Fit statistics without a model	Default output
FitStatistics	Fit statistics from the model	Default output
VariableImportance	Loss reduction variable importance	Default output
ModelInfo	Model information	Default output
Timing	Absolute and relative times for tasks performed by the procedure	Default output

Examples: HPFOREST Procedure

The following examples illustrate the basic concepts of forests. The first three examples use the spambase data available from the UCI Machine Learning Repository (Asuncion and Newman 2007) `http://archive.ics.uci.edu/ml/datasets/Spambase`.

Example 13.1: Out-Of-Bag Estimate of Misclassification Rate

Using the original training data to evaluate a forest model is poor practice because the forest predicts the training data much better than it predicts similar data withheld from training. Using the out-of-bag data is better practice because, with enough trees, the fit of a forest to the out-of-bag data converges to what the fit would be on similar data withheld from training. With only a few trees, the fit to the out-of-bag data is worse than what the fit would be on withheld data. Consequently, the training and out-of-bag data provide lower and upper bounds to what the error rate will be when the forest is applied to new data.

This example illustrates the difference between the misclassification rates estimated from the training and out-of-bag data. The HPFOREST procedure is run on the spambase data. The target, SPAM, has two values: 0 indicates a legitimate e-mail, 1 indicates spam. The number of trees is set large enough for the out-of-bag misclassification error rates to converge (MAXTREES=200 or 500).

The following SAS statements create a SAS data set from the data downloaded into a file called *c:\spambase_data.txt*:

```
   data spambase;
      infile 'c:\spambase_data.txt' delimiter = ',';
      input wf_make       wf_adress     wf_all        wf_3d      wf_our
            wf_over       wf_remove     wf_internet   wf_order   wf_mail
            wf_receive    wf_will       wf_people     wf_report  wf_addresses
            wf_free       wf_business   wf_email      wf_you     wf_credit
            wf_your       wf_font       wf_000        wf_money   wf_hp
            wf_hpl        wf_george     wf_650        wf_lab     wf_labs
            wf_telnet     wf_857        wf_data       wf_415     wf_85
            wf_technology wf_1999       wf_parts      wf_pm      wf_direct
            wf_cs         wf_meeting    wf_original   wf_project wf_re
            wf_edu        wf_table      wf_conference
            cf_semicolon  cf_parenthese cf_bracket    cf_exclamation
            cf_dollar     cf_pound
            average       longest       total
            spam;
   run;

proc hpforest data=spambase maxtrees=200;
   input w: c: average longest total/level=interval;
   target spam/level=binary;
   ods output FitStatistics=fitstats(rename=(Ntrees=Trees));
run;

data fitstats;
   set fitstats;
   label Trees = 'Number of Trees';
   label MiscAll = 'Full Data';
   label Miscoob = 'OOB';
run;
proc sgplot data=fitstats;
   title "OOB vs Training";
   series x=Trees y=MiscAll;
   series x=Trees y=MiscOob/lineattrs=(pattern=shortdash thickness=2);
   yaxis label='Misclassification Rate';
```

```
run;
title;
```

Output 13.1.1 Plot of OOB versus Training Misclassification Rate



Figure 13.1.1 shows the misclassification rate is worse (larger) based on the out-of-bag (OOB) data, and more trees are needed for the out-of-bag rates to level off. Both characteristics are typical of a forest.

Example 13.2: Number of Variables to Try When Splitting a Node

This example illustrates the effect of changing the number of variables to randomly select as candidate splitting variables in a node. In each node in each tree, *m* variables are randomly selected to be candidates to split on. Use the VARS_TO_TRY= option to specify *m*. Specifying *m* less than the number of available inputs is one way to reduce the correlation between the trees in the forest. Broadly speaking, the predictions of a forest improve when the trees are less correlated. On the other hand, the predictions of the forest improve when the predictions of the trees improve (without changing the correlations). When the number of useful inputs are much less than the total number of inputs, smaller values of *m* produce weaker trees because fewer nodes consider useful inputs for defining a splitting rule. Try several values of *m* to find a good one for the data.

The following SAS statements create a SAS data set from the data downloaded into a file called *c:\spambase_data.txt*:

```
data spambase;
   infile 'c:\spambase_data.txt' delimiter = ',';
   input wf_make       wf_adress     wf_all        wf_3d      wf_our
         wf_over       wf_remove     wf_internet   wf_order   wf_mail
         wf_receive    wf_will       wf_people     wf_report  wf_addresses
         wf_free       wf_business   wf_email      wf_you     wf_credit
         wf_your       wf_font       wf_000        wf_money   wf_hp
         wf_hpl        wf_george     wf_650        wf_lab     wf_labs
         wf_telnet     wf_857        wf_data       wf_415     wf_85
         wf_technology wf_1999       wf_parts      wf_pm      wf_direct
         wf_cs         wf_meeting    wf_original   wf_project wf_re
         wf_edu        wf_table      wf_conference
         cf_semicolon  cf_parenthese cf_bracket    cf_exclamation
         cf_dollar     cf_pound
         average       longest       total
         spam;
run;
```

```
%macro hpforest(Vars=);
proc hpforest data=spambase maxtrees=200
   vars_to_try=&Vars.;
   input w: c: average longest total/level=interval;
   target spam/level=binary;
   ods output
   FitStatistics = fitstats_vars&Vars.(rename=(Miscoob=VarsToTry&Vars.));
run;
%mend;

%hpforest(vars=all);
%hpforest(vars=40);
%hpforest(vars=26);
%hpforest(vars=7);
%hpforest(vars=2);

data fitstats;
   merge
   fitstats_varsall
   fitstats_vars40
   fitstats_vars26
   fitstats_vars7
   fitstats_vars2;
   rename Ntrees=Trees;
   label VarsToTryAll = "Vars=All";
   label VarsToTry40 = "Vars=40";
   label VarsToTry26 = "Vars=26";
   label VarsToTry7 = "Vars=7";
   label VarsToTry2 = "Vars=2";
run;

proc sgplot data=fitstats;
   title "Misclassification Rate for Various VarsToTry Values";
   series x=Trees y = VarsToTryAll/lineattrs=(Color=black);
   series x=Trees y=VarsToTry40/lineattrs=(Pattern=ShortDash Thickness=2);
   series x=Trees y=VarsToTry26/lineattrs=(Pattern=ShortDash Thickness=2);
   series x=Trees y=VarsToTry7/lineattrs=(Pattern=MediumDashDotDot Thickness=2);
   series x=Trees y=VarsToTry2/lineattrs=(Pattern=LongDash Thickness=2);
   yaxis label='OOB Misclassification Rate';
run;
title;
```

Output 13.2.1 Effect of the VARS_TO_TRY= Option on the Misclassification Rate



Specifying a value of 40 or 26 for the VARS_TO_TRY= option results in a slightly more accurate forest than would occur without random selection of variables (VARS_TO_TRY=ALL). Specifying VARS_TO_TRY=2 is much worse than specifying VARS_TO_TRY=ALL. A good value for VARS_TO_TRY= depends on the data. In this example, the HPFOREST procedure uses a default value of $\sqrt{58} = 7$.

Example 13.3: Fraction of Training Data to Train a Tree

This example illustrates the effect of changing the fraction of original training observations used to train an individual tree. Use the TRAINFRACTION= option to specify f. Specifying f less than 1 is one way to reduce the correlation between the trees in the forest.

The following SAS statements create a SAS data set from the data downloaded into a file called *c:\spambase_data.txt*:

```
data spambase;
   infile 'c:\spambase_data.txt' delimiter = ',';
   input wf_make       wf_adress     wf_all        wf_3d      wf_our
         wf_over       wf_remove     wf_internet   wf_order   wf_mail
         wf_receive    wf_will       wf_people     wf_report  wf_addresses
         wf_free       wf_business   wf_email      wf_you     wf_credit
         wf_your       wf_font       wf_000        wf_money   wf_hp
         wf_hpl        wf_george     wf_650        wf_lab     wf_labs
         wf_telnet     wf_857        wf_data       wf_415     wf_85
         wf_technology wf_1999       wf_parts      wf_pm      wf_direct
         wf_cs         wf_meeting    wf_original   wf_project wf_re
         wf_edu        wf_table      wf_conference
         cf_semicolon  cf_parenthese cf_bracket    cf_exclamation
         cf_dollar     cf_pound
         average       longest       total
         spam;
run;


%macro hpforest(f=, output_suffix=);
proc hpforest data=spambase maxtrees=500 vars_to_try=26
   trainfraction=&f;
   input w: c: average longest total/level=interval;
   target spam/level=binary;
   ods output
   FitStatistics = fitstats_f&output_suffix.(rename=(Miscoob=fraction&output_suffix.));
run;
%mend;

%hpforest(f=0.8, output_suffix=08);
%hpforest(f=0.6, output_suffix=06);
%hpforest(f=0.4, output_suffix=04);

data fitstats;
   merge
   fitstats_f08
   fitstats_f06
   fitstats_f04;
   rename Ntrees=Trees;
   label fraction08 = "Fraction=0.8";
   label fraction06 = "Fraction=0.6";
   label fraction04 = "Fraction=0.4";
run;
```

```
proc sgplot data=fitstats;
   title "Misclassification Rate for Various Fractions of Training Data";
   series x=Trees y=fraction08/lineattrs=(Pattern=ShortDash Thickness=2);
   series x=Trees y=fraction06/lineattrs=(Pattern=MediumDashDotDot Thickness=2);
   series x=Trees y=fraction04/lineattrs=(Pattern=LongDash Thickness=2);
   yaxis label='OOB Misclassification Rate';
run;
title;
```

Output 13.3.1 Effect of the TRAINFRACTION Option on the Misclassification Rate



Using the default number of trees (MAXTREES=50) in this example, the default value of TRAINFRACTION=0.6 results in the best OOB misclassification rate. Using more trees, TRAINFRACTION=0.8 is best.

Example 13.4: Loss Reduction Variable Importance

This example compares the loss reduction variable importance measure on uncorrelated and correlated variables. The data have eight inputs that are generated from a standard normal distribution. The first four inputs

are independent; the last four have a correlation of 0.9. The target Y is computed as

$$Y = X1 + X2 + 2X3 + X5 + X6 + 2X7$$

The following SAS statements create a SAS data set and run PROC HPFOREST:

```
data output;
   call streaminit(54321);
   do i=1 to 10000;
      x1 = rand('normal', 0, 1);
      x2 = rand('normal', 0, 1);
      x3 = rand('normal', 0, 1);
      x4 = rand('normal', 0, 1);
      output;
   end;
run;

data cov;
   input x5-x8;
   datalines;
   1 0.9 0.9 0.9
   0.9 1 0.9 0.9
   0.9 0.9 1 0.9
   0.9 0.9 0.9 1
run;

proc simnormal data=cov(type=cov)
   out = osim(drop=Rnum)
   numreal = 10000
   seed = 54321;
   var x5-x8;
run;

data output;
   merge output osim;
   y = x1 + x2 + 2*x3 + x5 + x6 + 2*x7;
run;

proc hpforest data=output vars_to_try=all;
   input x:/level=interval;
   target y/level=interval;
   ods select VariableImportance;
run;
```

Output 13.4.1 shows the PROC HPFOREST variable importance table. The NRules column contains the number of splitting rules that use each variable. The next four columns are loss reduction measures of variable importance. The mean square error and the absolute error are computed with the training data. The OOB columns contain the same measures computed with out-of-bag data. In this example, the relative importance of any pair of variables is similar in every measure.

Output 13.4.1 Loss Reduction Variable Importance

Loss Reduction Variable Importance

Variable	NRules	MSE	MSE OOB	Absolute Error Reduction	OOB Absolute Error Reduction
x7	3092	14.06756	9.15219	1.594952	1.017569
x3	4397	3.72293	2.36836	0.667098	0.397890
x2	4943	0.77243	0.44134	0.217217	0.106669
x1	4925	0.77099	0.42248	0.217621	0.104431
x5	2772	0.66905	0.38739	0.156935	0.080153
x6	2781	0.46631	0.24469	0.122941	0.055567
x8	362	0.01391	0.00347	0.005423	0.000940
x4	67	0.00118	-0.00092	0.000595	-0.000238

PROC HPFOREST reports X7 as the most important variable. Although X7 and X3 have the same coefficient, X7 steals importance from correlated variables X5 and X6. PROC HPFOREST assigns less importance to X5 and X6 than to the uncorrelated variables X1 and X2 as a result, even though all four variables have the same coefficient in the formula for Y.

X8 is not in the formula for Y but gets some importance because it is correlated with variables that are in the formula; therefore, X8 is correlated to some extent with Y. Splits that use X8 have some validity because of this correlation. X4 is not in the formula and is not correlated with any variables that are in the formula. The splits that use X4 are all spurious. The out-of-bag measures of importance are negative because, on balance, the spurious splits assign out-of-bag observations to the branch with the worse prediction.

Specifying VARS_TO_TRY=ALL in this example requests that PROC HPFOREST compare all inputs when it selects a variable to split a node on. The larger the number, the more dominant the importance of X7 is in this example. If VARS_TO_TRY=3 or less, variables X5, X6, and X7 would each get approximately the same importance, which would be slightly higher than the importance given to X3. Changing the VARS_TO_TRY= option has little effect on the importance of X1, X2, and X3.

Example 13.5: Missing Values and Imputed Values

This example uses the Home Equity data from the SAS sample library to illustrate the difference between using missing values and using imputed values. A nonrandom pattern of missingness in the data can help predict the target. PROC HPFOREST cannot use this pattern when missing values are replaced by imputed values in the training data. The following statements illustrate this by running PROC HPFOREST twice: once on the original data, and once on the data after missing nominal values have been replaced by the mode of the variable and missing interval values have been replaced by the mean of the variable.

The Sampsio.Hmeq data set contains fictitious mortgage data in which each case represents an applicant for a home equity loan. All applicants have an existing mortgage. The binary target BAD equals 1 for an applicant who eventually defaulted or was ever seriously delinquent. Nine interval inputs are available for modeling. JOB and REASON are the only nominal inputs. The modes for JOB and REASON are OTHER and DEBTCON, respectively.

```
proc hpimpute data=sampsio.hmeq out=imout;
   input mortdue value yoj clage ninq clno debtinc derog delinq;
   impute mortdue value yoj clage ninq clno debtinc derog delinq/method=mean;
run;

data job_reason;
   set sampsio.hmeq;
   if job='' then job="Other";
   if reason='' then reason="DebtCon";
run;

data imout;
   merge imout job_reason;
run;

proc hpforest data=imout vars_to_try=all;
   input im:/level=interval;
   input reason job/level=nominal;
   target bad/level=binary;
   ods output
      VariableImportance=imvi
      FitStatistics=imfit(rename=(Ntrees=Trees Miscall=ImMiscall Miscoob=ImMiscoob));
run;

proc hpforest data=sampsio.hmeq vars_to_try=all;
   input mortdue value yoj clage ninq clno debtinc derog delinq/level=interval;
   input reason job/level=nominal;
   target bad/level=binary;
   ods output
      Baseline=bs
      VariableImportance=vi
      FitStatistics=fit(rename=(Ntrees=Trees));
run;

proc sql noprint;
 select value into :MiscBaseline trimmed from bs where Statistic='Misclassification Rate';
quit;

data fitstats;
   merge imfit fit;
   MiscBaseline = &MiscBaseline;
   label Trees = 'Number of Trees';
   label MiscAll = 'Full Data';
   label Miscoob = 'OOB';
   label ImMiscAll = 'Full Data - Impute';
   label ImMiscoob = 'OOB - Impute';
   label Miscbaseline = 'Baseline';
run;

proc sgplot data=fitstats;
   title "Misclassification Rate With and Without Imputed Values";
   series x=trees y=Miscbaseline/lineattrs=(Pattern=Solid Color=black);
   series x=Trees y=MiscAll/lineattrs=(Pattern=Solid Thickness=2);
```

```
   series x=Trees y=Miscoob/lineattrs=(Pattern=ShortDash Thickness=2);
   series x=Trees y=ImMiscAll/lineattrs=(Pattern=ShortDash Thickness=2);
   series x=Trees y=ImMiscoob/lineattrs=(Pattern=MediumDashDotDot Thickness=2);
   yaxis label='Misclassification Rate';
run;

data vi;
  set vi;
  keep Variable NRules Gini GiniOOB Rank;
  Rank = _n_;
run;

proc sort data=vi;
  by Variable;
run;

data imvi;
  set imvi;
  keep Variable RankImputed NRules Gini GiniOOB;
  if substr(Variable,1,3)='IM_' then Variable=substr(Variable, 4);
  RankImputed=_n_;
  label RankImputed="Rank (Imput)";
  rename NRules=RulesImputed;
  label NRules="Rules (Imputed)";
  rename Gini=GiniImputed;
  label Gini="Gini (Imputed)";
  rename GiniOOB=GiniOOBImputed;
  label GiniOOB="OOB Gini Reduction (Impute)";
run;

proc sort data=imvi;
  by Variable;
run;

data vi;
  merge vi imvi;
  by Variable;
  rename NRules=Rules;
run;

proc sort data=vi;
  by rank;
run;

data t1(keep=Variable Rules RulesImputed RankImputed)
    t2(keep=Variable Gini GiniImputed GiniOOB GiniOOBImputed);
   set vi;
run;

proc print data=t1; run;

proc print data=t2; run;

data debtinc_miss;
```

```
  set sampsio.hmeq;
  if debtinc =. then debtinc_is_missing='MISSING    ';
  else debtinc_is_missing='NOT MISSING';
run;

proc freq data=debtinc_miss;
  tables debtinc_is_missing*bad/nocol;
run;
```

Figure 13.5.1 shows the misclassification rate and the out-of-bag misclassification rate with and without imputed missing values. Without any model, the misclassification rate equals 0.1995. The out-of-bag rate from the model trained with imputed values is not much better. The out-of-bag rate with the original data is much better, close to half the baseline rate.

Output 13.5.1 The Effect of Imputing Missing Values



Output 13.5.2 shows the number of times each model uses each variable. The Rules column shows the number of times using the original data; the RankImputed column shows the number of times using the imputed data. The numbers in the Rules column vary much more than those in the RuleImputed column, which suggests that variables with missing values have more distinctive information than variables with imputed values.

The order of the variables is the order of importance from the model that uses the original data. The RankImpute column shows the order of importance from the model that uses imputed values. DEBTINC is the most important variable when the original data are used, and among the last in importance when imputed values are used. Imputing changes the characteristics of these data dramatically.

Output 13.5.2 Variable Importance Ranking

Misclassification Rate With and Without Imputed Values

Obs	Variable	Rules	Rules Imputed	Rank Imputed
1	DEBTINC	862	526	8
2	DELINQ	748	414	1
3	DEROG	440	427	4
4	CLAGE	1130	534	11
5	VALUE	4140	519	5
6	NINQ	1034	518	9
7	CLNO	573	608	6
8	REASON	223	310	3
9	JOB	498	534	2
10	MORTDUE	716	398	7
11	YOJ	980	610	10

Output 13.5.3 shows the in-bag and out-of-bag Gini measures of importance for each variable. PROC HPFOREST uses only the training data in a tree to compute the in-bag measure, and it uses only the out-of-bag data in a tree for the out-of-bag measure. The out-of-bag measure is a better estimate of the contribution the variable makes to predicting new observations. A negative value indicates that the variable makes the prediction worse on average. The GiniOOB column shows that DEBTINC is six times more important than the next variable. However, when missing values are imputed, GinioOOB is slightly negative for DEBTINC, indicating that DEBTINC makes prediction slightly worse.

Output 13.5.3 Variable Importance Ranking

Misclassification Rate With and Without Imputed Values

Obs	Variable	Gini	GiniOOB	Gini Imputed	Gini OOBImputed
1	DEBTINC	0.114505	0.07181	0.005911	−0.00159
2	DELINQ	0.022592	0.01198	0.011046	0.00406
3	DEROG	0.010230	0.00471	0.004509	−0.00020
4	CLAGE	0.015952	0.00167	0.007823	−0.00237
5	VALUE	0.017810	0.00134	0.008441	−0.00101
6	NINQ	0.005895	−0.00061	0.004520	−0.00199
7	CLNO	0.005783	−0.00067	0.008768	−0.00120
8	REASON	0.001477	−0.00068	0.002987	−0.00010
9	JOB	0.003181	−0.00086	0.006935	0.00081
10	MORTDUE	0.003799	−0.00175	0.005901	−0.00151
11	YOJ	0.007206	−0.00197	0.006911	−0.00225

Output 13.5.4 shows the count of observations for which DEBTINC is or is not missing for each value of the target BAD. DEBTINC is missing in 21% of the observations. If DEBTINC is missing, then the proportion of observations with BAD equal to 1 (which indicates an applicant who becomes delinquent) is 62%. If DEBTINC is not missing, then the proportion is only 8.6%. Missing values in DEBTINC are highly predictive of BAD in this example. Imputing the missing values destroys the predictive power.

Output 13.5.4 Contingency Table of BAD by DEBTINC_IS_MISSING

Frequency Percent Row Pct	Table of debtinc_is_missing by BAD BAD		
debtinc_is_missing	0	1	Total
MISSING	481 8.07 37.96	786 13.19 62.04	1267 21.26
NOT MISSING	4290 71.98 91.41	403 6.76 8.59	4693 78.74
Total	4771 80.05	1189 19.95	5960 100.00

References

Archer, K. J. and Kimes, R. V. (2008), "Empirical Characterization of Random Forest Variable Importance Measures," *Computational Statistics and Data Analysis*, 52, 2249–2260.

Asuncion, A. and Newman, D. J. (2007), "UCI Machine Learning Repository," http://archive.ics.uci.edu/ml/.

Berk, R. A. (2008), *Statistical Learning from a Regression Perspective*, New York: Springer.

Breiman, L. (1996), "Bagging Predictors," *Machine Learning*, 24(2), 123–140.

Breiman, L. (2001), "Random Forests," *Machine Learning*, 45(1), 5–32.

Breiman, L. and Cutler, A. (2003), "Manual–Setting Up, Using, and Understanding Random Forests V4.0," .
URL http://oz.berkeley.edu/users/breiman/Using_random_forests_v4.0.pdf

Breiman, L., Friedman, J., Olshen, R. A., and Stone, C. J. (1984), *Classification and Regression Trees*, Wadsworth.

de Ville, B. and Neville, P. G. (2013), *Decision Trees for Business Intelligence and Data Mining: Using SAS Enterprise Miner*, Cary, NC: SAS Institute Inc.

Fisher, W. D. (1958), "On Grouping for Maximum Homogeneity," *Journal of the American Statistical Association*, 53, 789–798.

Freedman, J. H. and Popescu, B. E. (2003), *Importance Sampled Learning Ensembles*, Technical report, Department of Statistics, Stanford University.

Friedman, J. H. (2001), "Greedy Function Approximation: A Gradient Boosting Machine," *Annals of Statistics*, 29(5), 1189–1232.

Grömping, U. (2009), "Variable Importance Assessment in Regression: Linear Regression versus Random Forest," *The American Statistician*, 63(4), 308–319.

Hothorn, T., Hornik, K., and Zeileis, A. (2006), "Unbiased Recursive Partitioning: A Conditional Inference Framework," *Journal of Computational and Graphical Statistics*, 15, 651–674.

Kass, G. V. (1980), "An Exploratory Technique for Investigating Large Quantities of Categorical Data," *Applied Statistics*, 29, 119–127.

King, G. and Zeng, L. (2001), "Logistic Regression in Rare Events Data," *Political Analysis*, 9, 137–163.

Loh, W. and Shih, Y. (1997), "Split Selection Methods for Classification Trees," *Statistica Sinica*, 7(4), 815–840.

Nicodemus, K. K. and Malley, J. D. (2009), "Predictor Correlation Impacts Machine Learning Algorithms: Implications for Genomic Studies," *Bioinformatics*, 25(15), 1884–1890.

Quinlan, R. J. (1993), *C4.5: Programs for Machine Learning*, San Francisco: Morgan Kaufmann.

Smith, J. W., Everhart, J. E., Dickson, W. C., Knowler, W. C., and Johannes, R. S. (1988), "Using the ADAP Learning Algorithm to Forecast the Onset of Diabetes Mellitus," in *Proceedings of the Symposium on Computer Applications and Medical Care*, 261–265, Los Alamitos, CA: IEEE Computer Society Press.

Strobl, C., Boulesteix, A.-L., Kneib, T., Augustin, T., and Zeileis, A. (2008), "Conditional Variable Importance for Random Forests," *Bioinformatics*, 9(307).

van der Laan, M. J. (2006), "Statistical Inference for Variable Importance," *International Journal of Biostatistics*, 2(1).

Chapter 14
The HPIMPUTE Procedure

Contents

Overview: HPIMPUTE Procedure **265**
PROC HPIMPUTE Features 266
Client and Grid Execution Modes 266
Getting Started: HPIMPUTE Procedure **266**
Syntax: HPIMPUTE Procedure **268**
PROC HPIMPUTE Statement 268
CODE Statement 268
FREQ Statement 269
ID Statement 269
IMPUTE Statement 269
INPUT Statement 270
PERFORMANCE Statement 270
Details: HPIMPUTE Procedure **271**
Obtaining the Statistics for Imputation 271
Displayed Output 271
ODS Table Names 271
Examples: HPIMPUTE Procedure **272**
Example 14.1: Running PROC HPIMPUTE on the Client 272
Example 14.2: Running with Client Data on the SAS Appliance 273
Example 14.3: Running with Data on the SAS Appliance 274

Overview: HPIMPUTE Procedure

The HPIMPUTE procedure executes high-performance numeric variable imputation. Imputation is a common step in the data preparation stage. The HPIMPUTE procedure takes only numeric variables.

The HPIMPUTE procedure can replace numeric missing values with a specified value. It can also replace numeric missing values with the mean, the pseudo-median, or some random value between the minimum value and the maximum value of the nonmissing values.

When the mean, the pseudo-median, or a random value is being calculated, the HPIMPUTE procedure ignores any observation that has a FREQ variable whose value is less than or equal to 0.

PROC HPIMPUTE Features

PROC HPIMPUTE provides a vehicle for the parallel execution of imputation in a distributed computing environment. The following list summarizes the basic features of PROC HPIMPUTE:

- provides the ability to execute imputation in parallel
- enables you to control the level of parallelism per execution node and the number of nodes to engage
- is highly multithreaded
- manages data migration to the location of execution and movement back to the client machine as needed

Client and Grid Execution Modes

The HPIMPUTE procedure can exploit computer grids by imputing independently on different grid nodes in parallel, while multithreading is supported at each node. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for more information about the execution of SAS High-Performance Analytics procedures on a grid of computers.

PROC HPIMPUTE controls the execution of imputation in two dimensions. You can control both the number of parallel threads per execution node and also the number of computing nodes to engage.

Alternatively, PROC HPIMPUTE can be executed on the High-Performance Analytics grid. In grid mode, one or more copies of the imputation code are executed in parallel on each grid node.

The grid mode of execution has two variations:

- In the client-data (local-data) model of grid execution, the input data are not stored on the appliance but are distributed to the distributed computing environment during execution of the HPIMPUTE procedure.
- In the alongside-the-database model of grid execution, the data source is the database on the appliance. The data are stored in the distributed database, and the imputation code running on each node can read and write the data in parallel during execution of the procedure. Instead of data being moved across the network and possibly back to the client machine, data are passed locally between the processes on each node of the appliance. In general and especially with large data sets, the best PROC HPIMPUTE performance can be achieved if execution is alongside the database.

Getting Started: HPIMPUTE Procedure

The HPIMPUTE procedure can use four methods to impute numeric missing values. This example uses all four imputation methods available in the IMPUTE statement to manipulate a data set. The following SAS DATA step creates the SAS data set ex1, which has six variables: the first four variables all have some missing values, the fifth variable is the frequency variable, and the last variable is an index variable.

```
data ex1;
input a  b  c  d  freq id;
cards;
       2    3   1  1   2   1
       2    2   2  2   3   2
       .    0   3  .   0   3
       2    3   .  .   .   4
       2    .   .  .   -5  5
       .    6   .  .   3   6
       .    4   .  .   4   7
       2    5   .  .   3   8
       .    6   9  9   1   9
       2    3   10 10  3   10
run;
```

The following statements include four IMPUTE statements, each of which specifies a different imputation method. The INPUT statement specifies the input variables. PROC HPIMPUTE assumes that the variables have an interval level of measurement because the variables are numeric.

```
proc hpimpute data=ex1 out=out1;
    id id;
    input a b c d;
    impute a / value=0.1;
    impute b / method=pmedian;
    impute c / method=random;
    impute d / method=mean;
    freq freq;
run;
```

Output 14.1 shows the imputation results. The Variable Name column shows the original variable names from the input data set. The Imputation Indicator Variable column is 0 if that observation was not imputed and 1 if it was. The Imputed Variable Name column shows the names of imputed variables in the output data set. The Type of Imputation column shows the types of imputation methods: Given Value, Pseudo Median, Random (between the minimum value and the maximum value of the nonmissing values), and Mean. For random imputation, the last column shows the imputation seed. For other imputation methods, the last column shows the imputation value that is used to replace missing values.

Figure 14.1 HPIMPUTE Getting Started Example Output

Imputation Results

Variable Name	Imputation Indicator Variable Name	Imputed Variable Name	Num of Missing	Type of Imputation	Imputation Value (Seed)
a	M_a	IM_a	4	Given value	0.1000
b	M_b	IM_b	1	Pseudo Median	4.0000
c	M_c	IM_c	5	Random	5.0000
d	M_d	IM_d	6	Mean	5.2222

Syntax: HPIMPUTE Procedure

The following statements are available in the HPIMPUTE procedure:

PROC HPIMPUTE < *options* > **;**
INPUT *variables* < *options* > **;**
IMPUTE *variables* < *options* > **;**
PERFORMANCE *performance-options* **;**
ID *variables* **;**
FREQ *variable* **;**
CODE < *options* > **;**

The PROC HPIMPUTE statement, INPUT statement, and IMPUTE statement are required. The INPUT statement and IMPUTE statement can appear multiple times.

PROC HPIMPUTE Statement

PROC HPIMPUTE < *options* > **;**

The PROC HPIMPUTE statement invokes the procedure. You can specify one or more of the following *options*.

DATA=< *libref.* **>***SAS-data-set*
names the SAS data set for which PROC HPIMPUTE is to impute values. The default is the most recently created data set. If the data are already distributed, PROC HPIMPUTE reads the data alongside the distributed database. See the section "SMP and MPP Modes" on page 16 for more information about the various execution modes and the section "Alongside-the-Database Execution" on page 22 for more information about the alongside-the-database model. WHERE processing is supported.

DMDBCAT=< *libref.* **>***SAS-catalog*
names the SAS catalog to be used by PROC HPIMPUTE for looking up the variable metadata. If you specify this option and the imputation value is available in the named SAS catalog, PROC HPIMPUTE imputes with the value in the SAS catalog. Otherwise, PROC HPIMPUTE first computes the imputation value and then imputes with that value.

OUT=< *libref.* **>***SAS-data-set*
names the SAS data set to which PROC HPIMPUTE writes the data with ID variables (if applicable), imputation indicator variables (0 for not imputed or 1 for imputed), and imputed variables.

CODE Statement

CODE < *options* > **;**

The CODE statement generates SAS DATA step code that mimics the computations done by the IMPUTE statement. You can specify the following *options*:

FILE=*filename*
specifies the filename of the file to which the SAS score code is written.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. SAS High-Performance Analytics procedures that support the FREQ statement treat each observation as if it appeared f times, where f is the value of the FREQ variable for the observation. If the frequency value is not an integer, it is truncated to an integer. If the frequency value is less than 1 or missing, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

ID Statement

ID *variables* **;**

The optional ID statement lists one or more *variables* from the input data set that are transferred to the output data set. The ID statement accepts numeric and character variables. For example, when you specify the OUT= option in the PROC HPIMPUTE statement, the ID variables, followed by indicator variables and imputed variables, are added to the output data set. For more information about the common ID statement in SAS High-Performance Analytics procedures, see the section "ID Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

By default, the HPIMPUTE procedure does not include any variables from the input data set in the output data sets.

The variables in an ID statement must not appear in any INPUT statement; if they appear, an error is reported.

IMPUTE Statement

IMPUTE *variables* < *options* > **;**

The IMPUTE statement names the variables whose values PROC HPIMPUTE imputes. You can specify multiple IMPUTE statements. The IMPUTE statement takes only numeric variables; character variables are reported as an error. The variables in an IMPUTE statement must appear in an INPUT statement; if they do not appear in an INPUT statement, an error is reported.

You can specify the following *options*:

METHOD=MEAN | RANDOM | PMEDIAN
specifies the method of imputation. You can specify the following values:

MEAN replaces missing values with the algebraic mean of the variable. If there is no nonmissing value, the mean is 0.

RANDOM replaces missing values with a random value drawn between the minimum and maximum of the variable. If there is no nonmissing value, the random value is 0.

PMEDIAN replaces missing values with the pseudo-median of the variable. If there is no nonmissing value, the mean is 0.

VALUE=*value*
replaces missing values with the specified *value*.

INPUT Statement

INPUT *variables* < *options* > **;**

The INPUT statement names one of more input variables with common options. You can specify multiple INPUT statements. You can specify the following *options* in each INPUT statement:

LEVEL=BINARY | NOMINAL | ORDINAL | INTERVAL
specifies the level of measurement of the variables. Accepted values are BINARY, NOMINAL, ORDINAL, and INTERVAL.

NOTE: If you specify BINARY, NOMINAL, or ORDINAL, the variable is ignored by the IMPUTE statement.

ORDER=*order*
specifies the sorting order of the values of an ordinal input variable. Table 14.1 provides the recognized values of *order*.

Table 14.1 ORDER= Option Values

Value of ORDER=	Variable Values Sorted By
ASCENDING	Ascending order of unformatted values
ASCFORMATTED	Ascending order of formatted values
DESCENDING	Descending order of unformatted values
DESFORMATTED	Descending order of formatted values
DSORDER	Order of appearance in the input data set

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPIMPUTE procedure.

With the PERFORMANCE statement, you can also control whether the HPIMPUTE procedure executes in symmetric multiprocessing or massively parallel mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

Details: HPIMPUTE Procedure

Obtaining the Statistics for Imputation

If you specify the DMDBCAT= option in the PROC HPIMPUTE statement and the imputation value is available in the SAS catalog named by that option, PROC HPIMPUTE imputes with the value in that catalog. Otherwise, PROC HPIMPUTE first computes the imputation value and then imputes with that value.

Some statistics, such as mean, minimum, and maximum, are computed precisely. The pseudo-median, which is calculated if you specify METHOD=PMEDIAN in the IMPUTE statement, is an estimation of the median. The computation of the median requires sorting the entire data. However, in a grid computing environment, each grid node has only a part of the entire data. Sorting the entire data in such an environment requires a lot of internode communications, which degrades the performance dramatically. To address this challenge, a binning-based method is used to estimate the pseudo-median. Experiments show that the pseudo-median is a good estimation of the median and that the performance is satisfactory.

Displayed Output

The HPIMPUTE procedure displays imputation results and performance information.

The "imputation results" include six columns. The first column shows the original variable names from the input data set. The second column displays a 0 if that observation was not imputed and a 1 if it was. The third column shows the names of imputed variables in the output data set. The fourth column shows the types of imputation methods: Given Value, Mean, Pseudo Median, Random (between the minimum value and the maximum value of the nonmissing values). The last column shows the imputation seed for which random imputation generated the imputation value, or the imputation value for other imputation methods that replaces missing values.

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution and indicates whether PROC HPIMPUTE executes in client mode, distributed mode, or alongside-the-database mode. The numbers of computing nodes and threads are also displayed, depending on the environment.

ODS Table Names

Table 14.2 lists the names of the data tables that are created by the HPIMPUTE procedure. Use these names in ODS statements.

Table 14.2 ODS Tables Produced by PROC HPIMPUTE

Table Name	Description	Required Statement / Option
PerformanceInfo	Performance information	Default output
ImputeResults	Imputation results	Default output

Examples: HPIMPUTE Procedure

Example 14.1: Running PROC HPIMPUTE on the Client

This example demonstrates how to use PROC HPIMPUTE to perform imputation on the Sampsio.Hmeq data set, which resides on the client.

When the input data set resides on the client and no PERFORMANCE statement is specified, as in the following statements, the client performs all computations:

```
/*sampsio is a libname for a data source on the client.*/
proc hpimpute data=sampsio.hmeq out=out1;
    input mortdue value clage debtinc;
    impute mortdue / value  = 70000;
    impute value   / method = mean;
    impute clage   / method = random;
    impute debtinc / method = pmedian;
run;
```

Output 14.1.1 shows the imputation results.

Output 14.1.1 Imputation Results

Imputation Results

Variable Name	Imputation Indicator Variable Name	Imputed Variable Name	Num of Missing	Type of Imputation	Imputation Value (Seed)
MORTDUE	M_MORTDUE	IM_MORTDUE	518	Given value	70000
VALUE	M_VALUE	IM_VALUE	112	Mean	101776
CLAGE	M_CLAGE	IM_CLAGE	308	Random	5.0000
DEBTINC	M_DEBTINC	IM_DEBTINC	1267	Pseudo Median	34.8170

Output 14.1.2 shows the performance information.

Output 14.1.2 Performance Information

Performance Information

Execution Mode	On client
Number of Threads	2

Example 14.2: Running with Client Data on the SAS Appliance

This example uses the same data set as is used in Example 14.1.

When the input data set resides on the client and a PERFORMANCE statement with a NODES= option is specified, as in the following statements, PROC HPIMPUTE copies the data set to the SAS appliance, where the imputation is performed:

```
/*Perform the computation on the SAS appliance using 2 nodes*/
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";
proc hpimpute data=sampsio.hmeq out=out2;
    input mortdue value clage debtinc;
    impute mortdue / value  = 70000;
    impute value   / method = mean;
    impute clage   / method = random;
    impute debtinc / method = pmedian;
    performance nodes=10 nthreads=8;
run;
```

Output 14.2.1 shows the imputation results.

Output 14.2.1 Imputation Results

Imputation Results

Variable Name	Imputation Indicator Variable Name	Imputed Variable Name	Num of Missing	Type of Imputation	Imputation Value (Seed)
MORTDUE	M_MORTDUE	IM_MORTDUE	518	Given value	70000
VALUE	M_VALUE	IM_VALUE	112	Mean	101776
CLAGE	M_CLAGE	IM_CLAGE	308	Random	5.0000
DEBTINC	M_DEBTINC	IM_DEBTINC	1267	Pseudo Median	34.8170

Output 14.2.2 shows the performance information.

Output 14.2.2 Performance Information

Performance Information	
Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	10
Number of Threads per Node	8

Example 14.3: Running with Data on the SAS Appliance

This example uses the same data set as is used in Example 14.1.

When the input data set resides on the SAS appliance, the SAS appliance performs all computations and imputations, writes out results on the SAS appliance, and reports the results and performance back to the client. In the following statements, the input data resides in the MyLib library (which is a distributed data source), and the output data set is a distributed data set in the MyLib library. You can use the DATASETS procedure to delete the output table if it already exists on the SAS appliance.

```
/*MyLib is a libname for a distributed data source
  In this case, the computation is automatically done
  on the SAS appliance.*/
option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC = "&GRIDINSTALLLOC";
libname MyLib &LIBTYPE
        server  ="&GRIDDATASERVER"
        user    =&USER
        password=&PASSWORD
        database=&DATABASE;

proc datasets lib=Mylib nolist; delete out3;
run;
proc hpimpute data=MyLib.hmeq out=MyLib.out3;
    input mortdue value clage debtinc;
    impute mortdue / value  = 70000;
    impute value   / method = mean;
    impute clage   / method = random;
    impute debtinc / method = pmedian;
run;
```

Output 14.3.1 shows the imputation results.

Output 14.3.1 Imputation Results

Imputation Results

Variable Name	Imputation Indicator Variable Name	Imputed Variable Name	Num of Missing	Type of Imputation	Imputation Value (Seed)
MORTDUE	M_MORTDUE	IM_MORTDUE	518	Given value	70000
VALUE	M_VALUE	IM_VALUE	112	Mean	101776
CLAGE	M_CLAGE	IM_CLAGE	308	Random	5.0000
DEBTINC	M_DEBTINC	IM_DEBTINC	1267	Pseudo Median	34.8170

Output 14.3.2 shows the performance information.

Output 14.3.2 Performance Information

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed, alongside Greenplum
Number of Compute Nodes	32
Number of Threads per Node	24

Chapter 15
The HPLMIXED Procedure

Contents

Overview: HPLMIXED Procedure **278**
PROC HPLMIXED Features 279
Notation for the Mixed Model 279
PROC HPLMIXED Contrasted with Other SAS Procedures 281
Getting Started: HPLMIXED Procedure **281**
Mixed Model Analysis of Covariance with Many Groups 281
Syntax: HPLMIXED Procedure **284**
PROC HPLMIXED Statement 285
CLASS Statement 290
MODEL Statement 290
PARMS Statement 291
PERFORMANCE Statement 293
RANDOM Statement 293
REPEATED Statement 299
Details: HPLMIXED Procedure **300**
Linear Mixed Models Theory 300
Matrix Notation 301
Formulation of the Mixed Model 301
Estimating Covariance Parameters in the Mixed Model 306
Estimating Fixed and Random Effects in the Mixed Model 307
Statistical Properties 308
Computational Method 309
Distributed Computing 309
Multithreading 309
Displayed Output 310
Performance Information 310
Model Information 310
Class Level Information 310
Dimensions 310
Number of Observations 311
Optimization Information 311
Iteration History 311
Convergence Status 312
Covariance Parameter Estimates 312
Fit Statistics 312
Timing Information 313

ODS Table Names 313
Examples: HPLMIXED Procedure **313**
Example 15.1: Computing BLUPs for a Large Number of Subjects 313
References **316**

Overview: HPLMIXED Procedure

The HPLMIXED procedure fits a variety of mixed linear models to data and enables you to use these fitted models to make statistical inferences about the data. A *mixed linear model* is a generalization of the standard linear model used in the GLM procedure in SAS/STAT software; the generalization is that the data are permitted to exhibit correlation and nonconstant variability. Therefore, the mixed linear model provides you with the flexibility of modeling not only the means of your data (as in the standard linear model) but also their variances and covariances.

The primary assumptions underlying the analyses performed by PROC HPLMIXED are as follows:

- The data are normally distributed (Gaussian).
- The means (expected values) of the data are linear in terms of a certain set of parameters.
- The variances and covariances of the data are in terms of a different set of parameters, and they exhibit a structure that matches one of those available in PROC HPLMIXED.

Since Gaussian data can be modeled entirely in terms of their means and variances/covariances, the two sets of parameters in a mixed linear model actually specify the complete probability distribution of the data. The parameters of the mean model are referred to as *fixed-effects parameters*, and the parameters of the variance-covariance model are referred to as *covariance parameters*.

The fixed-effects parameters are associated with known explanatory variables, as in the standard linear model. These variables can be either qualitative (as in the traditional analysis of variance) or quantitative (as in standard linear regression). However, the covariance parameters are what distinguishes the mixed linear model from the standard linear model.

The need for covariance parameters arises quite frequently in applications; the following scenarios are the most typical:

- The experimental units on which the data are measured can be grouped into clusters, and the data from a common cluster are correlated. This scenario can be generalized to include one set of clusters nested within another. For example, if students are the experimental unit, they can be clustered into classes, which in turn can be clustered into schools. Each level of this hierarchy can introduce an additional source of variability and correlation.
- Repeated measurements are taken on the same experimental unit, and these repeated measurements are correlated or exhibit variability that changes. This scenario occurs in longitudinal studies, where repeated measurements are taken over time. Alternatively, the repeated measures could be spatial or multivariate in nature.

PROC HPLMIXED provides a variety of covariance structures to handle these two scenarios. The most common covariance structures arise from the use of *random-effects parameters*, which are additional unknown random variables that are assumed to affect the variability of the data. The variances of the random-effects parameters, commonly known as *variance components*, become the covariance parameters for this particular structure. Traditional mixed linear models contain both fixed- and random-effects parameters; in fact, it is the combination of these two types of effects that led to the name *mixed model*. PROC HPLMIXED fits not only these traditional variance component models but also numerous other covariance structures.

PROC HPLMIXED fits the structure you select to the data by using the method of *restricted maximum likelihood (REML)*, also known as *residual maximum likelihood*. It is here that the Gaussian assumption for the data is exploited.

PROC HPLMIXED Features

PROC HPLMIXED provides easy accessibility to numerous mixed linear models that are useful in many common statistical analyses.

Here are some basic features of PROC HPLMIXED:

- covariance structures, including variance components, compound symmetry, unstructured, AR(1), Toeplitz, and factor analytic
- MODEL, RANDOM, and REPEATED statements for model specification as in the MIXED procedure
- appropriate standard errors, *t* tests, and *F* tests for all specified estimable linear combinations of fixed and random effects
- a subject effect that enables blocking
- REML and ML (maximum likelihood) estimation methods implemented with a variety of optimization algorithms
- capacity to handle unbalanced data
- special dense and sparse algorithms that take advantage of distributed and multicore computing environments

PROC HPLMIXED uses the Output Delivery System (ODS), a SAS subsystem that provides capabilities for displaying and controlling the output from SAS procedures. ODS enables you to convert any output from PROC HPLMIXED into a SAS data set. See the section "ODS Table Names" on page 313.

Notation for the Mixed Model

This section introduces the mathematical notation used throughout this chapter to describe the mixed linear model and assumes familiarity with basic matrix algebra (for an overview, see Searle 1982). A more detailed description of the mixed model is contained in the section "Linear Mixed Models Theory" on page 300.

A statistical model is a mathematical description of how data are generated. The standard linear model, as used by the GLM procedure, is one of the most common statistical models:

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \boldsymbol{\epsilon}$$

In this expression, $\mathbf{y}$ represents a vector of observed data, $\boldsymbol{\beta}$ is an unknown vector of fixed-effects parameters with a known design matrix $\mathbf{X}$, and $\boldsymbol{\epsilon}$ is an unknown random error vector that models the statistical noise around $\mathbf{X}\boldsymbol{\beta}$. The focus of the standard linear model is to model the mean of $\mathbf{y}$ by using the fixed-effects parameters $\boldsymbol{\beta}$. The residual errors $\boldsymbol{\epsilon}$ are assumed to be independent and identically distributed Gaussian random variables with mean 0 and variance σ^2.

The mixed model generalizes the standard linear model as follows:

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \mathbf{Z}\boldsymbol{\gamma} + \boldsymbol{\epsilon}$$

Here, $\boldsymbol{\gamma}$ is an unknown vector of random-effects parameters with a known design matrix $\mathbf{Z}$, and $\boldsymbol{\epsilon}$ is an unknown random error vector whose elements are no longer required to be independent and homogeneous.

To further develop this notion of variance modeling, assume that $\boldsymbol{\gamma}$ and $\boldsymbol{\epsilon}$ are Gaussian random variables that are uncorrelated, have expectations $\mathbf{0}$, and have variances $\mathbf{G}$ and $\mathbf{R}$, respectively. The variance of $\mathbf{y}$ is thus

$$\mathbf{V} = \mathbf{Z}\mathbf{G}\mathbf{Z}' + \mathbf{R}$$

Note that when $\mathbf{R} = \sigma^2\mathbf{I}$ and $\mathbf{Z} = \mathbf{0}$, the mixed model reduces to the standard linear model.

You can model the variance of the data $\mathbf{y}$ by specifying the structure of $\mathbf{Z}$, $\mathbf{G}$, and $\mathbf{R}$. The model matrix $\mathbf{Z}$ is set up in the same fashion as $\mathbf{X}$, the model matrix for the fixed-effects parameters. For $\mathbf{G}$ and $\mathbf{R}$, you must select some covariance structure. Possible covariance structures include the following:

- variance components
- compound symmetry (common covariance plus diagonal)
- unstructured (general covariance)
- autoregressive
- spatial
- general linear
- factor analytic

By appropriately defining the model matrices $\mathbf{X}$ and $\mathbf{Z}$ in addition to the covariance structure matrices $\mathbf{G}$ and $\mathbf{R}$, you can perform numerous mixed model analyses.

PROC HPLMIXED Contrasted with Other SAS Procedures

The RANDOM and REPEATED statements of the HPLMIXED procedure follow the convention of the same statements in the MIXED procedure in SAS/STAT software. For information about how these statements differ from RANDOM and REPEATED statements in the MIXED procedure, see the documentation for the MIXED procedure in the *SAS/STAT User's Guide*.

The GLIMMIX procedure in SAS/STAT software fits generalized linear mixed models. Linear mixed models—where the data are normally distributed, given the random effects—are in the class of generalized linear mixed models. Therefore, PROC GLIMMIX accommodates nonnormal data with random effects.

Generalized linear mixed models have intrinsically nonlinear features because a nonlinear mapping (the link function) connects the conditional mean of the data (given the random effects) to the explanatory variables. The NLMIXED procedure also accommodates nonlinear structures in the conditional mean, but places no restrictions on the nature of the nonlinearity.

The HPMIXED procedure in SAS/STAT software is also termed a "high-performance" procedure, but it does not follow the general pattern of High-Performance Analytics procedures. The HPMIXED procedure does not take advantage of distributed or multicore computing environments; it derives high-performance from applying sparse techniques to solving the mixed model equations. The HPMIXED procedure fits a small subset of the statistical models you can fit with the MIXED or HPLMIXED procedures and is particularly suited for problems in which the $[\mathbf{XZ}]'[\mathbf{XZ}]$ crossproducts matrix is sparse.

The HPLMIXED procedure employs algorithms that are specialized for distributed and multicore computing environments. The HPLMIXED procedure does not support BY processing.

Getting Started: HPLMIXED Procedure

Mixed Model Analysis of Covariance with Many Groups

Suppose you are an educational researcher who studies how student scores on math tests change over time. Students are tested four times, and you want to estimate the overall rise or fall, accounting for correlation between test response behaviors of students in the same neighborhood and school. One way to model this correlation is by using a random-effects analysis of covariance, where the scores for students from the same neighborhood and school are all assumed to share the same quadratic mean test response function, the parameters of this response function being random. The following statements simulate a data set with this structure:

```
data SchoolSample;
   do SchoolID = 1 to 300;
      do nID = 1 to 25;
         Neighborhood = (SchoolID-1)*5 + nId;
         bInt   = 5*ranuni(1);
         bTime  = 5*ranuni(1);
         bTime2 =   ranuni(1);
         do sID = 1 to 2;
            do Time = 1 to 4;
```

```
               Math = bInt + bTime*Time + bTime2*Time*Time + rannor(2);
               output;
               end;
            end;
         end;
      end;
run;
```

In this data, there are 300 schools and about 1,500 neighborhoods; neighborhoods are associated with more than one school and vice versa. The following statements use PROC HPLMIXED to fit a mixed analysis of covariance model to this data:

```
proc hplmixed data=SchoolSample;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC" nodes=20;
   class Neighborhood SchoolID;
   model Math = Time Time*Time / solution;
   random   int Time Time*Time / sub=Neighborhood(SchoolID) type=un;
run;
```

This model fits a quadratic mean response model with an unstructured covariance matrix to model the covariance between the random parameters of the response model. With 7,500 neighborhood/school combinations, this model can be computationally daunting to fit, but PROC HPLMIXED finishes quickly and displays the results shown in Figure 15.1.

Figure 15.1 Mixed Model Analysis of Covariance

```
                        The HPLMIXED Procedure

                       Performance Information

            Host Node                     rdgrd0001.unx.sas.com
            Execution Mode                Distributed
            Number of Compute Nodes       20
            Number of Threads per Node    8


                         Model Information

         Data Set                     WORK.SCHOOLSAMPLE
         Dependent Variable           Math
         Covariance Structure         Unstructured
         Subject Effect               Neighborho(SchoolID)
         Estimation Method            Restricted Maximum Likelihood
         Residual Variance Method     Profile
         Fixed Effects SE Method      Model-Based
         Degrees of Freedom Method    Residual


                       Class Level Information

   Class           Levels    Values

   Neighborhood      1520    1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18
                             19 20 ...
   SchoolID           300    1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18
                             19 20 ...
```

Figure 15.1 *continued*

Dimensions

Covariance Parameters	7
Columns in X	3
Columns in Z Per Subject	3
Subjects	7500
Max Obs Per Subject	8

Number of Observations Read	60000
Number of Observations Used	60000
Number of Observations Not Used	0
Number of Observations Swapped	52500
Number of Subjects Needing Swap	7500

Optimization Information

Optimization Technique	Newton-Raphson with Ridging
Parameters in Optimization	6
Lower Boundaries	3
Upper Boundaries	0
Starting Values From	Data

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	2	225641.67142	.	2.135E-8

Convergence criterion (ABSGCONV=0.00001) satisfied.

Covariance Parameter Estimates

Cov Parm	Subject	Estimate
UN(1,1)	Neighborho(SchoolID)	2.0902
UN(2,1)	Neighborho(SchoolID)	0.000349
UN(2,2)	Neighborho(SchoolID)	2.0517
UN(3,1)	Neighborho(SchoolID)	0.01448
UN(3,2)	Neighborho(SchoolID)	0.01599
UN(3,3)	Neighborho(SchoolID)	0.08047
Residual		1.0083

Fit Statistics

-2 Res Log Likelihood	225642
AIC (smaller is better)	225656
AICC (smaller is better)	225656
BIC (smaller is better)	225704

Figure 15.1 *continued*

Solution for Fixed Effects

Effect	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	2.5070	0.02828	6E4	88.66	<.0001
Time	2.5124	0.02659	6E4	94.48	<.0001
Time*Time	0.5010	0.005247	6E4	95.48	<.0001

Syntax: HPLMIXED Procedure

The following statements are available in PROC HPLMIXED.

PROC HPLMIXED < *options* > **;**
  CLASS *variables* **;**
  MODEL *dependent* **=** < *fixed-effects* > < / *options* > **;**
  RANDOM *random-effects* < / *options* > **;**
  REPEATED *repeated-effect* < / *options* > **;**
  PARMS < **(***value-list***)** *. . .* > < / *options* > **;**
  PERFORMANCE < *options* > **;**

Items within angle brackets (< >) are optional. The RANDOM statement can appear multiple times. Other statements can appear only once.

The PROC HPLMIXED and MODEL statements are required, and the MODEL statement must appear after the CLASS statement if a CLASS statement is included. The RANDOM statement must follow the MODEL statement.

Table 15.1 summarizes the basic functions and important options of the PROC HPLMIXED statements. The syntax of each statement in Table 15.1 is described in the following sections in alphabetical order after the description of the PROC HPLMIXED statement.

Table 15.1 Summary of PROC HPLMIXED Statements

Statement	Description	Important Options
PROC HPLMIXED	Invokes the procedure	DATA= specifies the input data set; METHOD= specifies the estimation method.
CLASS	Declares qualitative variables that create indicator variables in **X** and **Z** matrices.	None
MODEL	Specifies dependent variable and fixed effects, setting up **X**	S requests a solution for fixed-effects parameters.

Table 15.1 *continued*

Statement	Description	Important Options
RANDOM	Specifies random effects, setting up **Z** and **G**	SUBJECT= creates block-diagonality; TYPE= specifies the covariance structure; S requests a solution for the random effects.
REPEATED	Sets up **R**	SUBJECT= creates block-diagonality; TYPE= specifies the covariance structure.
PARMS	Specifies a grid of initial values for the covariance parameters	HOLD= and NOITER hold the covariance parameters or their ratios constant; PARMSDATA= reads the initial values from a SAS data set.
PERFORMANCE	Invokes the distributed computing connection	NODES= specifies the number of nodes to use.

PROC HPLMIXED Statement

PROC HPLMIXED < *options* > **;**

The PROC HPLMIXED statement invokes the procedure. Table 15.2 summarizes important options in the PROC HPLMIXED statement by function. These and other options in the PROC HPLMIXED statement are then described fully in alphabetical order.

Table 15.2 PROC HPLMIXED Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
METHOD=	Specifies the estimation method
NAMELEN=	Limits the length of effect names
BLUP	Computes the best linear unbiased prediction
Options Related to Output	
NOCLPRINT	Suppresses the "Class Level Information" table completely or in parts
MAXCLPRINT=	Specifies the maximum levels of CLASS variables to print
Optimization Options	
ABSCONV=	Tunes an absolute function convergence criterion
ABSFCONV=	Tunes an absolute function difference convergence criterion
ABSGCONV=	Tunes the absolute gradient convergence criterion
FCONV=	Tunes the relative function convergence criterion
GCONV=	Tunes the relative gradient convergence criterion

Table 15.2 *continued*

Option	Description
MAXITER=	Chooses the maximum number of iterations in any optimization
MAXFUNC=	Specifies the maximum number of function evaluations in any optimization
MAXTIME=	Specifies the upper limit on seconds of CPU time for any optimization
MINITER=	Specifies the minimum number of iterations in any optimization
TECHNIQUE=	Selects the optimization technique
XCONV=	Tunes the relative parameter convergence criterion

You can specify the following *options* in the PROC HPLMIXED statement.

ABSCONV=*r*

specifies an absolute function convergence criterion. For minimization, termination requires $f(\boldsymbol{\psi}^{(k)}) \leq r$, where $\boldsymbol{\psi}$ is the vector of parameters in the optimization and $f(\cdot)$ is the objective function. The default value of r is the negative square root of the largest double-precision value, which serves only as a protection against overflows.

ABSFCONV=*r*

specifies an absolute function difference convergence criterion. For all techniques except Nelder–Mead simplex (NMSIMP), termination requires a small change of the function value in successive iterations:

$$|f(\boldsymbol{\psi}^{(k-1)}) - f(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}^{(k)}$ is defined as the vertex with the lowest function value and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The default value is $r = 0$.

ABSGCONV=*r*

specifies an absolute gradient convergence criterion. Termination requires the maximum absolute gradient element to be small:

$$\max_j |g_j(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization and $g_j(\cdot)$ is the gradient of the objective function with respect to the j parameter. This criterion is not used by the NMSIMP technique. The default value is r=1E–5.

BLUP< *(suboptions)* >

requests that best linear unbiased predictions (BLUPs) for the random effects be displayed. To use this option, you must also use the PARMS statement to specify fixed values for the covariance parameters.

The BLUP solution might be sensitive to the order of observations, and hence to how the data are distributed on the grid. If there are multiple measures of a repeated effect, then the BLUP solution is not unique. If the order of these multiple measures on the grid differs for different runs, then different BLUP solutions will result.

You can specify the following *suboptions*:

ITPRINT=*number* specifies that the iteration history be displayed after every *number* of iterations. The default value is 10, which means the procedure displays the iteration history for every 10 iterations.

MAXITER=*number* specifies the maximum number of iterations allowed. The default value is the number of parameters in the BLUP option plus 2.

TOL=*number* specifies the tolerance value. The default value is the square root of machine precision.

DATA=*SAS-data-set*

names the SAS data set to be used as the input data set. The default is the most recently created data set.

FCONV=*r*

specifies a relative function convergence criterion. For all techniques except NMSIMP, termination requires a small relative change of the function value in successive iterations,

$$\frac{|f(\boldsymbol{\psi}^{(k)}) - f(\boldsymbol{\psi}^{(k-1)})|}{|f(\boldsymbol{\psi}^{(k-1)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}^{(k)}$ is defined as the vertex with the lowest function value and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex.

The default is $r = 10^{-\mathrm{FDIGITS}}$, where FDIGITS is $-\log_{10}(\epsilon)$ and ϵ is the machine precision.

GCONV=*r*

specifies a relative gradient convergence criterion. For all techniques except CONGRA and NMSIMP, termination requires that the normalized predicted function reduction be small,

$$\frac{\mathbf{g}(\boldsymbol{\psi}^{(k)})'[\mathbf{H}^{(k)}]^{-1}\mathbf{g}(\boldsymbol{\psi}^{(k)})}{|f(\boldsymbol{\psi}^{(k)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, $f(\cdot)$ is the objective function, and $\mathbf{g}(\cdot)$ is the gradient. For the CONGRA technique (where a reliable Hessian estimate $\mathbf{H}$ is not available), the following criterion is used:

$$\frac{\| \mathbf{g}(\boldsymbol{\psi}^{(k)}) \|_2^2 \quad \| \mathbf{s}(\boldsymbol{\psi}^{(k)}) \|_2}{\| \mathbf{g}(\boldsymbol{\psi}^{(k)}) - \mathbf{g}(\boldsymbol{\psi}^{(k-1)}) \|_2 \, |f(\boldsymbol{\psi}^{(k)})|} \leq r$$

This criterion is not used by the NMSIMP technique. The default value is *r*=1E–8.

MAXCLPRINT=*number*

specifies the maximum levels of CLASS variables to print in the ODS table "ClassLevels." The default value is 20. MAXCLPRINT=0 enables you to print all levels of each CLASS variable. However, the option NOCLPRINT takes precedence over MAXCLPRINT.

MAXFUNC=*n*
specifies the maximum number *n* of function calls in the optimization process. The default values are as follows, depending on the optimization technique:

- TRUREG, NRRIDG, NEWRAP: 125
- QUANEW, DBLDOG: 500
- CONGRA: 1,000
- NMSIMP: 3,000

The optimization can terminate only after completing a full iteration. Therefore, the number of function calls that are actually performed can exceed *n*. You can choose the optimization technique with the TECHNIQUE= option.

MAXITER=*n*
specifies the maximum number *n* of iterations in the optimization process. The default values are as follows, depending on the optimization technique:

- TRUREG, NRRIDG, NEWRAP: 50
- QUANEW, DBLDOG: 200
- CONGRA: 400
- NMSIMP: 1,000

These default values also apply when *n* is specified as a missing value. You can choose the optimization technique with the TECHNIQUE= option.

MAXTIME=*r*
specifies an upper limit of *r* seconds of CPU time for the optimization process. The default value is the largest floating-point double representation of your computer. The time specified by the MAXTIME= option is checked only once at the end of each iteration. Therefore, the actual running time can be longer than *r*.

METHOD=REML

METHOD=ML
specifies the estimation method for the covariance parameters. METHOD=REML performs residual (restricted) maximum likelihood; it is the default method. METHOD=ML performs maximum likelihood.

MINITER=*n*
specifies the minimum number of iterations. The default value is 0. If you request more iterations than are actually needed for convergence to a stationary point, the optimization algorithms can behave strangely. For example, the effect of rounding errors can prevent the algorithm from continuing for the required number of iterations.

NAMELEN=*number*
specifies the length to which long effect names are shortened. The minimum value is 20, which is also the default.

NOCLPRINT< =*number* >**
suppresses the display of the "Class Level Information" table if you do not specify *number*. If you specify *number*, the values of the classification variables are displayed for only those variables whose number of levels is less than *number*. Specifying a *number* helps to reduce the size of the "Class Level Information" table if some classification variables have a large number of levels.

NOPRINT
suppresses the generation of ODS output.

SINGCHOL=*number*
tunes the singularity criterion in Cholesky decompositions. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

SINGSWEEP=*number*
tunes the singularity criterion for sweep operations. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

SINGULAR=*number*
tunes the general singularity criterion applied by the HPLMIXED procedure in sweeps and inversions. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

TECHNIQUE=*keyword*
specifies the optimization technique for obtaining maximum likelihood estimates. You can specify any of the following *keywords*:

CONGRA	performs a conjugate-gradient optimization.
DBLDOG	performs a version of double-dogleg optimization.
NEWRAP	performs a Newton-Raphson optimization combining a line-search algorithm with ridging.
NMSIMP	performs a Nelder-Mead simplex optimization.
NONE	performs no optimization.
NRRIDG	performs a Newton-Raphson optimization with ridging.
QUANEW	performs a dual quasi-Newton optimization.
TRUREG	performs a trust-region optimization.

The default value is TECHNIQUE=NRRIDG.

XCONV=*r*
specifies the relative parameter convergence criterion:

- For all techniques except NMSIMP, termination requires a small relative parameter change in subsequent iterations:

$$\frac{\max_j |\psi_j^{(k)} - \psi_j^{(k-1)}|}{\max(|\psi_j^{(k)}|, |\psi_j^{(k-1)}|)} \leq r$$

- For the NMSIMP technique, the same formula is used, but $\psi_j^{(k)}$ is defined as the vertex with the lowest function value and $\psi_j^{(k-1)}$ is defined as the vertex with the highest function value in the simplex.

The default value is r = 1E–8 for the NMSIMP technique and r = 0 otherwise.

CLASS Statement

CLASS *variables* **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. These variables enter the analysis not through their values, but through levels to which the unique values are mapped. See the section "Levelization of Classification Variables" on page 41 of Chapter 3, "Shared Concepts and Topics" for details about these mappings.

If a CLASS statement is specified, it must precede the MODEL statement in High-Performance Analytics procedures that support a MODEL statement.

Levels of classification variables are ordered by their external formatted values, except for numeric variables with no explicit format, which are ordered by their unformatted (internal) values.

MODEL Statement

MODEL *dependent* **=** < *fixed-effects* >< / *options* > **;**

The MODEL statement names a single dependent variable and the fixed effects, which determine the **X** matrix of the mixed model. (For details, see the section "Specification and Parameterization of Model Effects" on page 44 of Chapter 3, "Shared Concepts and Topics".) The MODEL statement is required.

An intercept is included in the fixed-effects model by default. If no fixed effects are specified, only this intercept term is fit. The intercept can be removed by using the NOINT option.

Table 15.3 summarizes options in the MODEL statement. These are subsequently discussed in detail in alphabetical order.

Table 15.3 Summary of Important MODEL Statement Options

Option	Description
Model Building	
NOINT	Excludes the fixed-effect intercept from model
Statistical Computations	
ALPHA=α	Determines the confidence level $(1-\alpha)$ for fixed effects
DDFM=	Specifies the method for computing denominator degrees of freedom
Statistical Output	
CL	Displays confidence limits for fixed-effects parameter estimates
SOLUTION	Displays fixed-effects parameter estimates

You can specify the following *options* in the MODEL statement after a slash (/).

ALPHA=*number*
sets the confidence level to be 1−*number* for each confidence interval of the fixed-effects parameters. The value of *number* must be between 0 and 1; the default is 0.05.

CL
requests that *t*-type confidence limits be constructed for each of the fixed-effects parameter estimates. The confidence level is 0.95 by default; this can be changed with the ALPHA= option.

DDFM=NONE | RESIDUAL
specifies the method for computing the denominator degrees of freedom for the tests of fixed effects.

The DDFM=RESIDUAL option performs all tests by using the residual degrees of freedom, $n - \mathrm{rank}(\mathbf{X})$, where n is the number of observations used. It is the default degrees-of-freedom method.

DDFM=NONE specifies that no denominator degrees of freedom be applied. PROC HPLMIXED then essentially assumes that infinite degrees of freedom are available in the calculation of p-values. The p-values for t tests are then identical to p-values that are derived from the standard normal distribution. In the case of F tests, the p-values equal those of chi-square tests determined as follows: if F_{obs} is the observed value of the F test with l numerator degrees of freedom, then

$$p = \Pr\{F_{l,\infty} > F_{obs}\} = \Pr\{\chi^2_l > lF_{obs}\}$$

NOINT
requests that no intercept be included in the model. (An intercept is included by default.)

SOLUTION

S
requests that a solution for the fixed-effects parameters be produced. Using notation from the section "Linear Mixed Models Theory" on page 300, the fixed-effects parameter estimates are $\widehat{\boldsymbol{\beta}}$ and their approximate standard errors are the square roots of the diagonal elements of $(\mathbf{X}'\widehat{\mathbf{V}}^{-1}\mathbf{X})^{-}$.

Along with the estimates and their approximate standard errors, a *t* statistic is computed as the estimate divided by its standard error. The Pr > |t| column contains the two-tailed p-value that corresponds to the *t* statistic and associated degrees of freedom. You can use the CL option to request confidence intervals for all of the parameters; they are constructed around the estimate by using a radius that is the product of the standard error times a percentage point from the *t* distribution.

PARMS Statement

PARMS < *(value-list)...* > < / *options* > **;**

The PARMS statement specifies initial values for the covariance parameters, or it requests a grid search over several values of these parameters. You must specify the values in the order in which they appear in the "Covariance Parameter Estimates" table.

The *value-list* specification can take any of several forms:

m	a single value
$m_1, m_2, \ldots, m_n$	several values
m to n	a sequence in which m equals the starting value, n equals the ending value, and the increment equals 1
m to n by i	a sequence in which m equals the starting value, n equals the ending value, and the increment equals i
m_1, m_2 to m_3	mixed values and sequences

You can use the PARMS statement to input known parameters.

If you specify more than one set of initial values, PROC HPLMIXED performs a grid search of the likelihood surface and uses the best point on the grid for subsequent analysis. Specifying a large number of grid points can result in long computing times.

The results from the PARMS statement are the values of the parameters on the specified grid (denoted by CovP1 through CovP*n*), the residual variance (possibly estimated) for models with a residual variance parameter, and various functions of the likelihood.

You can specify the following *options* in the PARMS statement after a slash (/).

HOLD=*all*

EQCONS=*all*

specifies that all parameter values be held to equal the specified values.

For example, the following statement constrains all covariance parameters to equal 5, 3, 2, and 3:

```
parms (5) (3) (2) (3) / hold=all;
```

LOWERB=*value-list*

enables you to specify lower boundary constraints on the covariance parameters. The *value-list* specification is a list of numbers or missing values (.) separated by commas. You must list the numbers in the order that PROC HPLMIXED uses for the covariance parameters, and each number corresponds to the lower boundary constraint. A missing value instructs PROC HPLMIXED to use its default constraint. If you do not specify numbers for all of the covariance parameters, PROC HPLMIXED assumes the remaining ones are missing.

This option is useful when you want to constrain the **G** matrix to be positive definite in order to avoid the more computationally intensive algorithms that would be required when **G** becomes singular. The corresponding statements for a random coefficients model are as follows:

```
proc hplmixed;
   class person;
   model y = time;
   random int time / type=fa0(2) sub=person;
   parms / lowerb=1e-4,.,1e-4;
run;
```

The TYPE=FA0(2) structure specifies a Cholesky root parameterization for the 2×2 unstructured blocks in **G**. This parameterization ensures that the **G** matrix is nonnegative definite, and the PARMS statement then ensures that it is positive definite by constraining the two diagonal terms to be greater than or equal to 1E–4.

NOITER
requests that no optimization iterations be performed and that PROC HPLMIXED use the best value from the grid search to perform inferences. By default, iterations begin at the best value from the PARMS grid search.

PARMSDATA=*SAS-data-set*

PDATA=*SAS-data-set*
reads in covariance parameter values from a SAS data set. The data set should contain the Est or Covp1 through Covp*n* variables.

UPPERB=*value-list*
enables you to specify upper boundary constraints on the covariance parameters. The *value-list* specification is a list of numbers or missing values (.) separated by commas. You must list the numbers in the order that PROC HPLMIXED uses for the covariance parameters, and each number corresponds to the upper boundary constraint. A missing value instructs PROC HPLMIXED to use its default constraint. If you do not specify numbers for all of the covariance parameters, PROC HPLMIXED assumes that the remaining ones are missing.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement you can also control whether a SAS High-Performance Analytics procedure executes in SMP or MPP mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

RANDOM Statement

RANDOM *random-effects* < / *options* > **;**

The RANDOM statement defines the random effects that constitute the $\boldsymbol{\gamma}$ vector in the mixed model. You can use this statement to specify traditional variance component models and to specify random coefficients. The random effects can be classification or continuous, and multiple RANDOM statements are possible.

Using notation from the section "Linear Mixed Models Theory" on page 300, the purpose of the RANDOM statement is to define the $\mathbf{Z}$ matrix of the mixed model, the random effects in the $\boldsymbol{\gamma}$ vector, and the structure of $\mathbf{G}$. The $\mathbf{Z}$ matrix is constructed exactly as the $\mathbf{X}$ matrix for the fixed effects is constructed, and the $\mathbf{G}$ matrix is constructed to correspond with the effects that constitute $\mathbf{Z}$. The structure of $\mathbf{G}$ is defined by using the TYPE= option.

You can specify INTERCEPT (or INT) as a random effect to indicate the intercept. PROC HPLMIXED does not include the intercept in the RANDOM statement by default as it does in the MODEL statement.

Table 15.4 summarizes important options in the RANDOM statement. All options are subsequently discussed in alphabetical order.

Table 15.4 Summary of Important RANDOM Statement Options

Option	Description
Construction of Covariance Structure	
SUBJECT=	Identifies the subjects in the model
TYPE=	Specifies the covariance structure
Statistical Output	
ALPHA=α	Determines the confidence level $(1-\alpha)$
CL	Requests confidence limits for predictors of random effects
SOLUTION	Displays solutions $\widehat{\boldsymbol{\gamma}}$ of the random effects

You can specify the following *options* in the RANDOM statement after a slash (/).

ALPHA=*number*

sets the confidence level to be $1-$*number* for each confidence interval of the random-effects estimates. The value of *number* must be between 0 and 1; the default is 0.05.

CL

requests that *t*-type confidence limits be constructed for each of the random-effect estimates. The confidence level is 0.95 by default; this can be changed with the ALPHA= option.

SOLUTION

S

requests that the solution for the random-effects parameters be produced. Using notation from the section "Linear Mixed Models Theory" on page 300, these estimates are the empirical best linear unbiased predictors (EBLUPs), $\widehat{\boldsymbol{\gamma}} = \widehat{\mathbf{G}}\mathbf{Z}'\widehat{\mathbf{V}}^{-1}(\mathbf{y}-\mathbf{X}\widehat{\boldsymbol{\beta}})$. They can be useful for comparing the random effects from different experimental units and can also be treated as residuals in performing diagnostics for your mixed model.

The numbers displayed in the SE Pred column of the "Solution for Random Effects" table are not the standard errors of the $\widehat{\boldsymbol{\gamma}}$ displayed in the Estimate column; rather, they are the standard errors of predictions $\widehat{\boldsymbol{\gamma}}_i - \boldsymbol{\gamma}_i$, where $\widehat{\boldsymbol{\gamma}}_i$ is the ith EBLUP and $\boldsymbol{\gamma}_i$ is the ith random-effect parameter.

SUBJECT=*effect*

SUB=*effect*

identifies the subjects in your mixed model. Complete independence is assumed across subjects; thus, for the RANDOM statement, the SUBJECT= option produces a block-diagonal structure in $\mathbf{G}$ with identical blocks. In fact, specifying a subject effect is equivalent to nesting all other effects in the RANDOM statement within the subject effect.

When you specify the SUBJECT= option and a classification random effect, computations are usually much quicker if the levels of the random effect are duplicated within each level of the SUBJECT= effect.

TYPE=*covariance-structure*

specifies the covariance structure of **G**. Valid values for *covariance-structure* and their descriptions are listed in Table 15.5. Although a variety of structures are available, most applications call for either TYPE=VC or TYPE=UN. The TYPE=VC (variance components) option is the default structure, and it models a different variance component for each random effect.

The TYPE=UN (unstructured) option is useful for correlated random coefficient models. For example, the following statement specifies a random intercept-slope model that has different variances for the intercept and slope and a covariance between them:

```
random intercept age / type=un subject=person;
```

You can also use TYPE=FA0(2) here to request a **G** estimate that is constrained to be nonnegative definite.

If you are constructing your own columns of **Z** with continuous variables, you can use the TYPE=TOEP(1) structure to group them together to have a common variance component. If you want to have different covariance structures in different parts of **G**, you must use multiple RANDOM statements with different TYPE= options.

Table 15.5 Covariance Structures

Structure	Description	Parms	(i, j) element
ANTE(1)	Antedependence	$2t-1$	$\sigma_i\sigma_j\prod_{k=i}^{j-1}\rho_k$
AR(1)	Autoregressive(1)	2	$\sigma^2\rho^{\lvert i-j\rvert}$
ARH(1)	Heterogeneous AR(1)	$t+1$	$\sigma_i\sigma_j\rho^{\lvert i-j\rvert}$
ARMA(1,1)	Autoregressive moving average(1,1)	3	$\sigma^2[\gamma\rho^{\lvert i-j\rvert-1}1(i\neq j)+1(i=j)]$
CS	Compound symmetry	2	$\sigma_1+\sigma^2 1(i=j)$
CSH	Heterogeneous compound symmetry	$t+1$	$\sigma_i\sigma_j[\rho 1(i\neq j)+1(i=j)]$
FA(q)	Factor analytic	$\frac{q}{2}(2t-q+1)+t$	$\Sigma_{k=1}^{\min(i,j,q)}\lambda_{ik}\lambda_{jk}+\sigma_i^2 1(i=j)$
FA0(q)	No diagonal FA	$\frac{q}{2}(2t-q+1)$	$\Sigma_{k=1}^{\min(i,j,q)}\lambda_{ik}\lambda_{jk}$
FA1(q)	Equal diagonal FA	$\frac{q}{2}(2t-q+1)+1$	$\Sigma_{k=1}^{\min(i,j,q)}\lambda_{ik}\lambda_{jk}+\sigma^2 1(i=j)$
HF	Huynh-Feldt	$t+1$	$(\sigma_i^2+\sigma_j^2)/2+\lambda 1(i\neq j)$
SIMPLE	An alias for VC	q	$\sigma_k^2 1(i=j)$ for the kth effect
TOEP	Toeplitz	t	$\sigma_{\lvert i-j\rvert+1}$
TOEP(q)	Banded Toeplitz	q	$\sigma_{\lvert i-j\rvert+1}1(\lvert i-j\rvert<q)$
TOEPH	Heterogeneous TOEP	$2t-1$	$\sigma_i\sigma_j\rho_{\lvert i-j\rvert}$
TOEPH(q)	Banded heterogeneous TOEP	$t+q-1$	$\sigma_i\sigma_j\rho_{\lvert i-j\rvert}1(\lvert i-j\rvert<q)$
UN	Unstructured	$t(t+1)/2$	σ_{ij}
UN(q)	Banded	$\frac{q}{2}(2t-q+1)$	$\sigma_{ij}1(\lvert i-j\rvert<q)$
UNR	Unstructured correlation	$t(t+1)/2$	$\sigma_i\sigma_j\rho_{\max(i,j)\min(i,j)}$
UNR(q)	Banded correlations	$\frac{q}{2}(2t-q+1)$	$\sigma_i\sigma_j\rho_{\max(i,j)\min(i,j)}$
VC	Variance components	q	$\sigma_k^2 1(i=j)$ for the kth effect

In Table 15.5, the Parms column represents the number of covariance parameters in the structure, t is the overall dimension of the covariance matrix, and $1(A)$ equals 1 when A is true and 0 otherwise. For example, $1(i = j)$ equals 1 when $i = j$ and 0 otherwise, and $1(|i-j| < q)$ equals 1 when $|i-j| < q$ and 0 otherwise. For the TYPE=TOEPH structures, $\rho_0 = 1$; for the TYPE=UNR structures, $\rho_{ii} = 1$ for all i.

Table 15.6 lists some examples of the structures in Table 15.5.

Table 15.6 Covariance Structure Examples

Description	Structure	Example
Variance components	VC (default)	$\begin{bmatrix} \sigma_B^2 & 0 & 0 & 0 \\ 0 & \sigma_B^2 & 0 & 0 \\ 0 & 0 & \sigma_{AB}^2 & 0 \\ 0 & 0 & 0 & \sigma_{AB}^2 \end{bmatrix}$
Compound symmetry	CS	$\begin{bmatrix} \sigma^2+\sigma_1 & \sigma_1 & \sigma_1 & \sigma_1 \\ \sigma_1 & \sigma^2+\sigma_1 & \sigma_1 & \sigma_1 \\ \sigma_1 & \sigma_1 & \sigma^2+\sigma_1 & \sigma_1 \\ \sigma_1 & \sigma_1 & \sigma_1 & \sigma^2+\sigma_1 \end{bmatrix}$
Unstructured	UN	$\begin{bmatrix} \sigma_1^2 & \sigma_{21} & \sigma_{31} & \sigma_{41} \\ \sigma_{21} & \sigma_2^2 & \sigma_{32} & \sigma_{42} \\ \sigma_{31} & \sigma_{32} & \sigma_3^2 & \sigma_{43} \\ \sigma_{41} & \sigma_{42} & \sigma_{43} & \sigma_4^2 \end{bmatrix}$
Banded main diagonal	UN(1)	$\begin{bmatrix} \sigma_1^2 & 0 & 0 & 0 \\ 0 & \sigma_2^2 & 0 & 0 \\ 0 & 0 & \sigma_3^2 & 0 \\ 0 & 0 & 0 & \sigma_4^2 \end{bmatrix}$
First-order autoregressive	AR(1)	$\sigma^2 \begin{bmatrix} 1 & \rho & \rho^2 & \rho^3 \\ \rho & 1 & \rho & \rho^2 \\ \rho^2 & \rho & 1 & \rho \\ \rho^3 & \rho^2 & \rho & 1 \end{bmatrix}$
Toeplitz	TOEP	$\begin{bmatrix} \sigma^2 & \sigma_1 & \sigma_2 & \sigma_3 \\ \sigma_1 & \sigma^2 & \sigma_1 & \sigma_2 \\ \sigma_2 & \sigma_1 & \sigma^2 & \sigma_1 \\ \sigma_3 & \sigma_2 & \sigma_1 & \sigma^2 \end{bmatrix}$
Toeplitz with two bands	TOEP(2)	$\begin{bmatrix} \sigma^2 & \sigma_1 & 0 & 0 \\ \sigma_1 & \sigma^2 & \sigma_1 & 0 \\ 0 & \sigma_1 & \sigma^2 & \sigma_1 \\ 0 & 0 & \sigma_1 & \sigma^2 \end{bmatrix}$
Heterogeneous autoregressive(1)	ARH(1)	$\begin{bmatrix} \sigma_1^2 & \sigma_1\sigma_2\rho & \sigma_1\sigma_3\rho^2 & \sigma_1\sigma_4\rho^3 \\ \sigma_2\sigma_1\rho & \sigma_2^2 & \sigma_2\sigma_3\rho & \sigma_2\sigma_4\rho^2 \\ \sigma_3\sigma_1\rho^2 & \sigma_3\sigma_2\rho & \sigma_3^2 & \sigma_3\sigma_4\rho \\ \sigma_4\sigma_1\rho^3 & \sigma_4\sigma_2\rho & \sigma_4\sigma_3\rho & \sigma_4^2 \end{bmatrix}$

Table 15.6 *continued*

Description	Structure	Example
First-order autoregressive moving average	ARMA(1,1)	$\sigma^2 \begin{bmatrix} 1 & \gamma & \gamma\rho & \gamma\rho^2 \\ \gamma & 1 & \gamma & \gamma\rho \\ \gamma\rho & \gamma & 1 & \gamma \\ \gamma\rho^2 & \gamma\rho & \gamma & 1 \end{bmatrix}$
Heterogeneous compound symmetry	CSH	$\begin{bmatrix} \sigma_1^2 & \sigma_1\sigma_2\rho & \sigma_1\sigma_3\rho & \sigma_1\sigma_4\rho \\ \sigma_2\sigma_1\rho & \sigma_2^2 & \sigma_2\sigma_3\rho & \sigma_2\sigma_4\rho \\ \sigma_3\sigma_1\rho & \sigma_3\sigma_2\rho & \sigma_3^2 & \sigma_3\sigma_4\rho \\ \sigma_4\sigma_1\rho & \sigma_4\sigma_2\rho & \sigma_4\sigma_3\rho & \sigma_4^2 \end{bmatrix}$
First-order factor analytic	FA(1)	$\begin{bmatrix} \lambda_1^2+d_1 & \lambda_1\lambda_2 & \lambda_1\lambda_3 & \lambda_1\lambda_4 \\ \lambda_2\lambda_1 & \lambda_2^2+d_2 & \lambda_2\lambda_3 & \lambda_2\lambda_4 \\ \lambda_3\lambda_1 & \lambda_3\lambda_2 & \lambda_3^2+d_3 & \lambda_3\lambda_4 \\ \lambda_4\lambda_1 & \lambda_4\lambda_2 & \lambda_4\lambda_3 & \lambda_4^2+d_4 \end{bmatrix}$
Huynh-Feldt	HF	$\begin{bmatrix} \sigma_1^2 & \frac{\sigma_1^2+\sigma_2^2}{2}-\lambda & \frac{\sigma_1^2+\sigma_3^2}{2}-\lambda \\ \frac{\sigma_2^2+\sigma_1^2}{2}-\lambda & \sigma_2^2 & \frac{\sigma_2^2+\sigma_3^2}{2}-\lambda \\ \frac{\sigma_3^2+\sigma_1^2}{2}-\lambda & \frac{\sigma_3^2+\sigma_2^2}{2}-\lambda & \sigma_3^2 \end{bmatrix}$
First-order antedependence	ANTE(1)	$\begin{bmatrix} \sigma_1^2 & \sigma_1\sigma_2\rho_1 & \sigma_1\sigma_3\rho_1\rho_2 \\ \sigma_2\sigma_1\rho_1 & \sigma_2^2 & \sigma_2\sigma_3\rho_2 \\ \sigma_3\sigma_1\rho_2\rho_1 & \sigma_3\sigma_2\rho_2 & \sigma_3^2 \end{bmatrix}$
Heterogeneous Toeplitz	TOEPH	$\begin{bmatrix} \sigma_1^2 & \sigma_1\sigma_2\rho_1 & \sigma_1\sigma_3\rho_2 & \sigma_1\sigma_4\rho_3 \\ \sigma_2\sigma_1\rho_1 & \sigma_2^2 & \sigma_2\sigma_3\rho_1 & \sigma_2\sigma_4\rho_2 \\ \sigma_3\sigma_1\rho_2 & \sigma_3\sigma_2\rho_1 & \sigma_3^2 & \sigma_3\sigma_4\rho_1 \\ \sigma_4\sigma_1\rho_3 & \sigma_4\sigma_2\rho_2 & \sigma_4\sigma_3\rho_1 & \sigma_4^2 \end{bmatrix}$
Unstructured correlations	UNR	$\begin{bmatrix} \sigma_1^2 & \sigma_1\sigma_2\rho_{21} & \sigma_1\sigma_3\rho_{31} & \sigma_1\sigma_4\rho_{41} \\ \sigma_2\sigma_1\rho_{21} & \sigma_2^2 & \sigma_2\sigma_3\rho_{32} & \sigma_2\sigma_4\rho_{42} \\ \sigma_3\sigma_1\rho_{31} & \sigma_3\sigma_2\rho_{32} & \sigma_3^2 & \sigma_3\sigma_4\rho_{43} \\ \sigma_4\sigma_1\rho_{41} & \sigma_4\sigma_2\rho_{42} & \sigma_4\sigma_3\rho_{43} & \sigma_4^2 \end{bmatrix}$

The following list provides some further information about these covariance structures:

TYPE=ANTE(1) specifies the first-order antedependence structure (Kenward 1987; Patel 1991; Macchiavelli and Arnold 1994). In Table 15.5, σ_i^2 is the i variance parameter, and ρ_k is the k autocorrelation parameter that satisfies $|\rho_k| < 1$.

TYPE=AR(1) specifies a first-order autoregressive structure. PROC HPLMIXED imposes the constraint $|\rho| < 1$ for stationarity.

TYPE=ARH(1) specifies a heterogeneous first-order autoregressive structure. As with TYPE=AR(1), PROC HPLMIXED imposes the constraint $|\rho| < 1$ for stationarity.

TYPE=ARMA(1,1) specifies the first-order autoregressive moving average structure. In Table 15.5, ρ is the autoregressive parameter, γ models a moving average component, and σ^2

is the residual variance. In the notation of Fuller (1976, p. 68), $\rho = \theta_1$ and

$$\gamma = \frac{(1 + b_1\theta_1)(\theta_1 + b_1)}{1 + b_1^2 + 2b_1\theta_1}$$

The example in Table 15.6 and $|b_1| < 1$ imply that

$$b_1 = \frac{\beta - \sqrt{\beta^2 - 4\alpha^2}}{2\alpha}$$

where $\alpha = \gamma - \rho$ and $\beta = 1 + \rho^2 - 2\gamma\rho$. PROC HPLMIXED imposes the constraints $|\rho| < 1$ and $|\gamma| < 1$ for stationarity, although the resulting covariance matrix is not positive definite for some values of ρ and γ in this region. When the estimated value of ρ becomes negative, the computed covariance is multiplied by $\cos(\pi d_{ij})$ to account for the negativity.

TYPE=CS specifies the compound-symmetry structure, which has constant variance and constant covariance.

TYPE=CSH specifies the heterogeneous compound-symmetry structure. This structure has a different variance parameter for each diagonal element, and it uses the square roots of these parameters in the off-diagonal entries. In Table 15.5, σ_i^2 is the i variance parameter, and ρ is the correlation parameter that satisfies $|\rho| < 1$.

TYPE=FA(q) specifies the factor-analytic structure with q factors (Jennrich and Schluchter 1986). This structure is of the form $\mathbf{\Lambda}\mathbf{\Lambda}' + \mathbf{D}$, where $\mathbf{\Lambda}$ is a $t \times q$ rectangular matrix and $\mathbf{D}$ is a $t \times t$ diagonal matrix with t different parameters. When $q > 1$, the elements of $\mathbf{\Lambda}$ in its upper right corner (that is, the elements in the i row and j column for $j > i$) are set to zero to fix the rotation of the structure.

TYPE=FA0(q) is similar to the FA(q) structure except that no diagonal matrix $\mathbf{D}$ is included. When $q < t$ (that is, when the number of factors is less than the dimension of the matrix), this structure is nonnegative definite but not of full rank. In this situation, you can use this structure for approximating an unstructured $\mathbf{G}$ matrix in the RANDOM statement. When $q = t$, you can use this structure to constrain $\mathbf{G}$ to be nonnegative definite in the RANDOM statement.

TYPE=FA1(q) is similar to the TYPE=FA(q) structure except that all of the elements in $\mathbf{D}$ are constrained to be equal. This offers a useful and more parsimonious alternative to the full factor-analytic structure.

TYPE=HF specifies the Huynh-Feldt covariance structure (Huynh and Feldt 1970). This structure is similar to the TYPE=CSH structure in that it has the same number of parameters and heterogeneity along the main diagonal. However, it constructs the off-diagonal elements by taking arithmetic means rather than geometric means.

You can perform a likelihood ratio test of the Huynh-Feldt conditions by running PROC HPLMIXED twice, once with TYPE=HF and once with TYPE=UN, and then subtracting their respective values of -2 times the maximized likelihood.

If PROC HPLMIXED does not converge under your Huynh-Feldt model, you can specify your own starting values with the PARMS statement. The default MIVQUE(0) starting values can sometimes be poor for this structure. A good choice for starting values is often the parameter estimates that correspond to an initial fit that uses TYPE=CS.

TYPE=SIMPLE is an alias for TYPE=VC.

TYPE=TOEP<(*q*)> specifies a banded Toeplitz structure. This can be viewed as a moving average structure with order equal to $q-1$. The TYPE=TOEP option is a full Toeplitz matrix, which can be viewed as an autoregressive structure with order equal to the dimension of the matrix. The specification TYPE=TOEP(1) is the same as $\sigma^2 I$, where I is an identity matrix, and it can be useful for specifying the same variance component for several effects.

TYPE=TOEPH<(*q*)> specifies a heterogeneous banded Toeplitz structure. In Table 15.5, σ_i^2 is the i variance parameter and ρ_j is the j correlation parameter that satisfies $|\rho_j| < 1$. If you specify the order parameter *q*, then PROC HPLMIXED estimates only the first q bands of the matrix, setting all higher bands equal to 0. The option TOEPH(1) is equivalent to both the TYPE=UN(1) and TYPE=UNR(1) options.

TYPE=UN<(*q*)> specifies a completely general (unstructured) covariance matrix that is parameterized directly in terms of variances and covariances. The variances are constrained to be nonnegative, and the covariances are unconstrained. This structure is not constrained to be nonnegative definite in order to avoid nonlinear constraints. However, you can use the TYPE=FA0 structure if you want this constraint to be imposed by a Cholesky factorization. If you specify the order parameter *q*, then PROC HPLMIXED estimates only the first *q* bands of the matrix, setting all higher bands equal to 0.

TYPE=UNR<(*q*)> specifies a completely general (unstructured) covariance matrix that is parameterized in terms of variances and correlations. This structure fits the same model as the TYPE=UN(q) option but with a different parameterization. The i variance parameter is σ_i^2. The parameter ρ_{jk} is the correlation between the j and k measurements; it satisfies $|\rho_{jk}| < 1$. If you specify the order parameter r, then PROC HPLMIXED estimates only the first *q* bands of the matrix, setting all higher bands equal to zero.

TYPE=VC specifies standard variance components. This is the default structure for both the RANDOM and REPEATED statements. In the RANDOM statement, a distinct variance component is assigned to each effect.

Jennrich and Schluchter (1986) provide general information about the use of covariance structures, and Wolfinger (1996) presents details about many of the heterogeneous structures.

REPEATED Statement

REPEATED *repeated-effect* < / *options* > **;**

The REPEATED statement specifies the $\mathbf{R}$ matrix in the mixed model. If no REPEATED statement is specified, $\mathbf{R}$ is assumed to be equal to $\sigma^2\mathbf{I}$. For this release, you can use the REPEATED statement only with the BLUP option. The statement is ignored when no BLUP option is specified.

The *repeated-effect* is required, since the order of the input data is not necessarily reproducible in a distributed environment. The *repeated-effect* must contain only classification variables. Make sure that the levels of the *repeated-effect* are different for each observation within a subject; otherwise, PROC HPLMIXED

constructs identical rows in $\mathbf{R}$ that correspond to the observations with the same level. This results in a singular $\mathbf{R}$ matrix and an infinite likelihood.

Table 15.7 summarizes important options in the REPEATED statement. All options are subsequently discussed in alphabetical order.

Table 15.7 Summary of Important REPEATED Statement Options

Option	Description
Construction of Covariance Structure	
SUBJECT=	Identifies the subjects in the R-side model
TYPE=	Specifies the R-side covariance structure

You can specify the following *options* in the REPEATED statement after a slash (/).

SUBJECT=*effect*

SUB=*effect*

identifies the subjects in your mixed model. Complete independence is assumed across subjects; therefore, the SUBJECT= option produces a block-diagonal structure in $\mathbf{R}$ with identical blocks. When the SUBJECT= effect consists entirely of classification variables, the blocks of $\mathbf{R}$ correspond to observations that share the same level of that effect. These blocks are sorted according to this effect as well.

If you want to model nonzero covariance among all of the observations in your SAS data set, specify SUBJECT=Dummy_Intercept to treat the data as if they are all from one subject. You need to create this Dummy_Intercept variable in the data set. However, be aware that in this case PROC HPLMIXED manipulates an $\mathbf{R}$ matrix with dimensions equal to the number of observations.

TYPE=*covariance-structure*

specifies the covariance structure of the $\mathbf{R}$ matrix. The SUBJECT= option defines the blocks of $\mathbf{R}$, and the TYPE= option specifies the structure of these blocks. The default structure is VC. You can specify any of the covariance structures that are described in the TYPE= option in the RANDOM statement.

Details: HPLMIXED Procedure

Linear Mixed Models Theory

This section provides an overview of a likelihood-based approach to linear mixed models. This approach simplifies and unifies many common statistical analyses, including those that involve repeated measures, random effects, and random coefficients. The basic assumption is that the data are linearly related to unobserved multivariate normal random variables. For extensions to nonlinear and nonnormal situations, see the documentation of the GLIMMIX and NLMIXED procedures in the *SAS/STAT User's Guide*. Additional theory and examples are provided in Littell et al. (2006), Verbeke and Molenberghs (1997, 2000), and Brown and Prescott (1999).

Matrix Notation

Suppose that you observe n data points $y_1, \ldots, y_n$ and that you want to explain them by using n values for each of p explanatory variables $x_{11}, \ldots, x_{1p}, x_{21}, \ldots, x_{2p}, \ldots, x_{n1}, \ldots, x_{np}$. The x_{ij} values can be either regression-type continuous variables or dummy variables that indicate class membership. The standard linear model for this setup is

$$y_i = \sum_{j=1}^{p} x_{ij}\beta_j + \epsilon_i \quad i = 1, \ldots, n$$

where $\beta_1, \ldots, \beta_p$ are unknown fixed-effects parameters to be estimated and $\epsilon_1, \ldots, \epsilon_n$ are unknown independent and identically distributed normal (Gaussian) random variables with mean 0 and variance σ^2.

The preceding equations can be written simultaneously by using vectors and a matrix, as follows:

$$\begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix} = \begin{bmatrix} x_{11} & x_{12} & \ldots & x_{1p} \\ x_{21} & x_{22} & \ldots & x_{2p} \\ \vdots & \vdots & & \vdots \\ x_{n1} & x_{n2} & \ldots & x_{np} \end{bmatrix} \begin{bmatrix} \beta_1 \\ \beta_2 \\ \vdots \\ \beta_p \end{bmatrix} + \begin{bmatrix} \epsilon_1 \\ \epsilon_2 \\ \vdots \\ \epsilon_n \end{bmatrix}$$

For convenience, simplicity, and extendability, this entire system is written as

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \boldsymbol{\epsilon}$$

where $\mathbf{y}$ denotes the vector of observed y_i's, $\mathbf{X}$ is the known matrix of x_{ij}'s, $\boldsymbol{\beta}$ is the unknown fixed-effects parameter vector, and $\boldsymbol{\epsilon}$ is the unobserved vector of independent and identically distributed Gaussian random errors.

In addition to denoting data, random variables, and explanatory variables in the preceding fashion, the subsequent development makes use of basic matrix operators such as transpose ($'$), inverse ($^{-1}$), generalized inverse ($^{-}$), determinant ($|\cdot|$), and matrix multiplication. See Searle (1982) for details about these and other matrix techniques.

Formulation of the Mixed Model

The previous general linear model is certainly a useful one (Searle 1971), and it is the one fitted by the GLM procedure. However, many times the distributional assumption about ϵ is too restrictive. The mixed model extends the general linear model by allowing a more flexible specification of the covariance matrix of ϵ. In other words, it allows for both correlation and heterogeneous variances, although you still assume normality.

The mixed model is written as

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \mathbf{Z}\boldsymbol{\gamma} + \boldsymbol{\epsilon}$$

where everything is the same as in the general linear model except for the addition of the known design matrix, $\mathbf{Z}$, and the vector of unknown random-effects parameters, $\boldsymbol{\gamma}$. The matrix $\mathbf{Z}$ can contain either continuous or dummy variables, just like $\mathbf{X}$. The name *mixed model* comes from the fact that the model contains both fixed-effects parameters, $\boldsymbol{\beta}$, and random-effects parameters, $\boldsymbol{\gamma}$. See Henderson (1990) and Searle, Casella, and McCulloch (1992) for historical developments of the mixed model.

A key assumption in the foregoing analysis is that $\boldsymbol{\gamma}$ and $\boldsymbol{\epsilon}$ are normally distributed with

$$\mathrm{E}\begin{bmatrix} \boldsymbol{\gamma} \\ \boldsymbol{\epsilon} \end{bmatrix} = \begin{bmatrix} \mathbf{0} \\ \mathbf{0} \end{bmatrix}$$
$$\mathrm{Var}\begin{bmatrix} \boldsymbol{\gamma} \\ \boldsymbol{\epsilon} \end{bmatrix} = \begin{bmatrix} \mathbf{G} & \mathbf{0} \\ \mathbf{0} & \mathbf{R} \end{bmatrix}$$

Therefore, the variance of $\mathbf{y}$ is $\mathbf{V} = \mathbf{Z}\mathbf{G}\mathbf{Z}' + \mathbf{R}$. You can model $\mathbf{V}$ by setting up the random-effects design matrix $\mathbf{Z}$ and by specifying covariance structures for $\mathbf{G}$ and $\mathbf{R}$.

Note that this is a general specification of the mixed model, in contrast to many texts and articles that discuss only simple random effects. Simple random effects are a special case of the general specification with $\mathbf{Z}$ containing dummy variables, $\mathbf{G}$ containing variance components in a diagonal structure, and $\mathbf{R} = \sigma^2\mathbf{I}_n$, where $\mathbf{I}_n$ denotes the $n \times n$ identity matrix. The general linear model is a further special case with $\mathbf{Z} = \mathbf{0}$ and $\mathbf{R} = \sigma^2\mathbf{I}_n$.

The following two examples illustrate the most common formulations of the general linear mixed model.

Example: Growth Curve with Compound Symmetry

Suppose that you have three growth curve measurements for s individuals and that you want to fit an overall linear trend in time. Your $\mathbf{X}$ matrix is as follows:

$$\mathbf{X} = \begin{bmatrix} 1 & 1 \\ 1 & 2 \\ 1 & 3 \\ \vdots & \vdots \\ 1 & 1 \\ 1 & 2 \\ 1 & 3 \end{bmatrix}$$

The first column (coded entirely with 1s) fits an intercept, and the second column (coded with series of $1, 2, 3$) fits a slope. Here, $n = 3s$ and $p = 2$.

Suppose further that you want to introduce a common correlation among the observations from a single individual, with correlation being the same for all individuals. One way of setting this up in the general mixed model is to eliminate the $\mathbf{Z}$ and $\mathbf{G}$ matrices and let the $\mathbf{R}$ matrix be block-diagonal with blocks corresponding to the individuals and with each block having the *compound-symmetry* structure. This structure has two unknown parameters, one modeling a common covariance and the other modeling a residual variance. The form for $\mathbf{R}$ would then be

$$\mathbf{R} = \begin{bmatrix} \sigma_1^2+\sigma^2 & \sigma_1^2 & \sigma_1^2 & & & & & & \\ \sigma_1^2 & \sigma_1^2+\sigma^2 & \sigma_1^2 & & & & & & \\ \sigma_1^2 & \sigma_1^2 & \sigma_1^2+\sigma^2 & & & & & & \\ & & & \ddots & & & & & \\ & & & & \sigma_1^2+\sigma^2 & \sigma_1^2 & \sigma_1^2 & & \\ & & & & \sigma_1^2 & \sigma_1^2+\sigma^2 & \sigma_1^2 & & \\ & & & & \sigma_1^2 & \sigma_1^2 & \sigma_1^2+\sigma^2 & & \end{bmatrix}$$

where blanks denote zeros. There are $3s$ rows and columns altogether, and the common correlation is $\sigma_1^2/(\sigma_1^2+\sigma^2)$.

The following PROC HPLMIXED statements fit this model:

```
proc hplmixed;
   class indiv;
   model y = time;
   repeated morder/ type=cs subject=indiv;
run;
```

Here, INDIV is a classification variable that indexes individuals. The MODEL statement fits a straight line for TIME ; the intercept is fit by default just as in PROC GLM. The REPEATED statement models the $\mathbf{R}$ matrix: TYPE=CS specifies the compound symmetry structure, and SUBJECT=INDIV specifies the blocks of $\mathbf{R}$, and MORDER is the repeated effect that records the order of the measurements for each individual.

An alternative way of specifying the common intra-individual correlation is to let

$$\mathbf{Z} = \begin{bmatrix} 1 & & & \\ 1 & & & \\ 1 & & & \\ & 1 & & \\ & 1 & & \\ & 1 & & \\ & & \ddots & \\ & & & 1 \\ & & & 1 \\ & & & 1 \end{bmatrix}$$

$$\mathbf{G} = \begin{bmatrix} \sigma_1^2 & & & \\ & \sigma_1^2 & & \\ & & \ddots & \\ & & & \sigma_1^2 \end{bmatrix}$$

and $\mathbf{R} = \sigma^2 \mathbf{I}_n$. The $\mathbf{Z}$ matrix has $3s$ rows and s columns, and $\mathbf{G}$ is $s \times s$.

You can set up this model in PROC HPLMIXED in two different but equivalent ways:

```
proc hplmixed;
   class indiv;
   model y = time;
   random indiv;
run;

proc hplmixed;
   class indiv;
   model y = time;
   random intercept / subject=indiv;
run;
```

Both of these specifications fit the same model as the previous one that used the REPEATED statement. However, the RANDOM specifications constrain the correlation to be positive, whereas the REPEATED specification leaves the correlation unconstrained.

Example: Split-Plot Design

The split-plot design involves two experimental treatment factors, A and B, and two different sizes of experimental units to which they are applied (Winer 1971; Snedecor and Cochran 1980; Milliken and Johnson 1992; Steel, Torrie, and Dickey 1997). The levels of A are randomly assigned to the larger-sized experimental units, called *whole plots*, whereas the levels of B are assigned to the smaller-sized experimental units, the *subplots*. The subplots are assumed to be nested within the whole plots, so that a whole plot consists of a cluster of subplots and a level of A is applied to the entire cluster.

Such an arrangement is often necessary by nature of the experiment; the classical example is the application of fertilizer to large plots of land and different crop varieties planted in subdivisions of the large plots. For this example, fertilizer is the whole-plot factor A and variety is the subplot factor B.

The first example is a split-plot design for which the whole plots are arranged in a randomized block design. The appropriate PROC HPLMIXED statements are as follows:

```
proc hplmixed;
   class a b block;
   model y = a b a*b;
   random block a*block;
run;
```

Here

$$\mathbf{R} = \sigma^2 \mathbf{I}_{24}$$

and $\mathbf{X}$, $\mathbf{Z}$, and $\mathbf{G}$ have the following form:

$$\mathbf{X} = \begin{bmatrix}
1 & 1 & & & 1 & & 1 & & & & & \\
1 & 1 & & & & 1 & & 1 & & & & \\
1 & & 1 & & 1 & & & & 1 & & & \\
1 & & 1 & & & 1 & & & & 1 & & \\
1 & & & 1 & 1 & & & & & & 1 & \\
1 & & & 1 & & 1 & & & & & & 1 \\
\vdots & & \vdots & & \vdots & & & & \vdots & & & \\
1 & 1 & & & 1 & & 1 & & & & & \\
1 & 1 & & & & 1 & & 1 & & & & \\
1 & & 1 & & 1 & & & & 1 & & & \\
1 & & 1 & & & 1 & & & & 1 & & \\
1 & & & 1 & 1 & & & & & & 1 & \\
1 & & & 1 & & 1 & & & & & & 1
\end{bmatrix}$$

$$
\mathbf{Z} = \left[\begin{array}{cccccccccccccccc}
1&&&&1&&&&&&&&&&& \\
1&&&&1&&&&&&&&&&& \\
1&&&&&1&&&&&&&&&& \\
1&&&&&1&&&&&&&&&& \\
1&&&&&&1&&&&&&&&& \\
1&&&&&&1&&&&&&&&& \\
&1&&&&&&1&&&&&&&& \\
&1&&&&&&1&&&&&&&& \\
&1&&&&&&&1&&&&&&& \\
&1&&&&&&&1&&&&&&& \\
&1&&&&&&&&1&&&&&& \\
&1&&&&&&&&1&&&&&& \\
&&1&&&&&&&&1&&&&& \\
&&1&&&&&&&&1&&&&& \\
&&1&&&&&&&&&1&&&& \\
&&1&&&&&&&&&1&&&& \\
&&1&&&&&&&&&&1&&& \\
&&1&&&&&&&&&&1&&& \\
&&&1&&&&&&&&&&1&& \\
&&&1&&&&&&&&&&1&& \\
&&&1&&&&&&&&&&&1& \\
&&&1&&&&&&&&&&&1& \\
&&&1&&&&&&&&&&&&1 \\
&&&1&&&&&&&&&&&&1
\end{array}\right]
$$

$$
\mathbf{G} = \left[\begin{array}{cccccccc}
\sigma_B^2 &&&&&&& \\
& \sigma_B^2 &&&&&& \\
&& \sigma_B^2 &&&&& \\
&&& \sigma_B^2 &&&& \\
&&&& \sigma_{AB}^2 &&& \\
&&&&& \sigma_{AB}^2 && \\
&&&&&& \ddots & \\
&&&&&&& \sigma_{AB}^2
\end{array}\right]
$$

where σ_B^2 is the variance component for Block and σ_{AB}^2 is the variance component for A*Block. Changing the RANDOM statement as follows fits the same model, but with **Z** and **G** sorted differently:

```
random int a / subject=block;
```

$$\mathbf{Z} = \begin{bmatrix}
1 & 1 & & & & & & & & & & & & & & & & & & \\
1 & 1 & & & & & & & & & & & & & & & & & & \\
1 & & 1 & & & & & & & & & & & & & & & & & \\
1 & & 1 & & & & & & & & & & & & & & & & & \\
1 & & & 1 & & & & & & & & & & & & & & & & \\
1 & & & 1 & & & & & & & & & & & & & & & & \\
 & & & & 1 & 1 & & & & & & & & & & & & & & \\
 & & & & 1 & 1 & & & & & & & & & & & & & & \\
 & & & & 1 & & 1 & & & & & & & & & & & & & \\
 & & & & 1 & & 1 & & & & & & & & & & & & & \\
 & & & & 1 & & & 1 & & & & & & & & & & & & \\
 & & & & 1 & & & 1 & & & & & & & & & & & & \\
 & & & & & & & & 1 & 1 & & & & & & & & & & \\
 & & & & & & & & 1 & 1 & & & & & & & & & & \\
 & & & & & & & & 1 & & 1 & & & & & & & & & \\
 & & & & & & & & 1 & & 1 & & & & & & & & & \\
 & & & & & & & & 1 & & & 1 & & & & & & & & \\
 & & & & & & & & 1 & & & 1 & & & & & & & & \\
 & & & & & & & & & & & & 1 & 1 & & & & & & \\
 & & & & & & & & & & & & 1 & 1 & & & & & & \\
 & & & & & & & & & & & & 1 & & 1 & & & & & \\
 & & & & & & & & & & & & 1 & & 1 & & & & & \\
 & & & & & & & & & & & & 1 & & & 1 & & & & \\
 & & & & & & & & & & & & 1 & & & 1 & & & &
\end{bmatrix}$$

$$\mathbf{G} = \begin{bmatrix}
\sigma^2_B & & & & & & & & & & & & & & & & & & & \\
 & \sigma^2_{AB} & & & & & & & & & & & & & & & & & & \\
 & & \sigma^2_{AB} & & & & & & & & & & & & & & & & & \\
 & & & \sigma^2_{AB} & & & & & & & & & & & & & & & & \\
 & & & & \ddots & & & & & & & & & & & & & & & \\
 & & & & & \sigma^2_B & & & & & & & & & & & & & & \\
 & & & & & & \sigma^2_{AB} & & & & & & & & & & & & & \\
 & & & & & & & \sigma^2_{AB} & & & & & & & & & & & & \\
 & & & & & & & & \sigma^2_{AB} & & & & & & & & & & \\
 & & & & & & & & & & & & & & & & & & & \\
 & & & & & & & & & & & & & & & & & & & \\
 & & & & & & & & & & & & & & & & & & & \\
 & & & & & & & & & & & & & & & & & & & \\
 & & & & & & & & & & & & & & & & & & &
\end{bmatrix}$$

Estimating Covariance Parameters in the Mixed Model

Estimation is more difficult in the mixed model than in the general linear model. Not only do you have $\boldsymbol{\beta}$ as in the general linear model, but you also have unknown parameters in $\boldsymbol{\gamma}$, $\mathbf{G}$, and $\mathbf{R}$. Least squares is no longer the best method. Generalized least squares (GLS) is more appropriate, minimizing

$$(\mathbf{y} - \mathbf{X}\boldsymbol{\beta})'\mathbf{V}^{-1}(\mathbf{y} - \mathbf{X}\boldsymbol{\beta})$$

However, GLS requires knowledge of $\mathbf{V}$ and therefore knowledge of $\mathbf{G}$ and $\mathbf{R}$. Lacking such information, one approach is to use an *estimated* GLS, in which you insert some reasonable estimate for $\mathbf{V}$ into the minimization problem. The goal thus becomes finding a reasonable estimate of $\mathbf{G}$ and $\mathbf{R}$.

In many situations, the best approach is to use likelihood-based methods, exploiting the assumption that $\boldsymbol{\gamma}$ and $\boldsymbol{\epsilon}$ are normally distributed (Hartley and Rao 1967; Patterson and Thompson 1971; Harville 1977; Laird and Ware 1982; Jennrich and Schluchter 1986). PROC HPLMIXED implements two likelihood-based methods: maximum likelihood (ML) and restricted (residual) maximum likelihood (REML). A favorable theoretical property of ML and REML is that they accommodate data that are missing at random (Rubin 1976; Little 1995).

PROC HPLMIXED constructs an objective function associated with ML or REML and maximizes it over all unknown parameters. Using calculus, it is possible to reduce this maximization problem to one over only the parameters in $\mathbf{G}$ and $\mathbf{R}$. The corresponding log-likelihood functions are as follows:

$$\text{ML}: \quad l(\mathbf{G},\mathbf{R}) = -\frac{1}{2}\log|\mathbf{V}| - \frac{1}{2}\mathbf{r}'\mathbf{V}^{-1}\mathbf{r} - \frac{n}{2}\log(2\pi)$$

$$\text{REML}: \quad l_R(\mathbf{G},\mathbf{R}) = -\frac{1}{2}\log|\mathbf{V}| - \frac{1}{2}\log|\mathbf{X}'\mathbf{V}^{-1}\mathbf{X}| - \frac{1}{2}\mathbf{r}'\mathbf{V}^{-1}\mathbf{r} - \frac{n-p}{2}\log(2\pi)$$

where $\mathbf{r} = \mathbf{y} - \mathbf{X}(\mathbf{X}'\mathbf{V}^{-1}\mathbf{X})^{-}\mathbf{X}'\mathbf{V}^{-1}\mathbf{y}$ and p is the rank of $\mathbf{X}$. By default, PROC HPLMIXED actually minimizes a normalized form of -2 times these functions by using a ridge-stabilized Newton-Raphson algorithm by default. Lindstrom and Bates (1988) provide reasons for preferring Newton-Raphson to the expectation-maximum (EM) algorithm described in Dempster, Laird, and Rubin (1977) and Laird, Lange, and Stram (1987), in addition to analytical details for implementing a QR-decomposition approach to the problem. Wolfinger, Tobias, and Sall (1994) present the sweep-based algorithms that are implemented in PROC HPLMIXED. You can change the optimization technique with the TECHNIQUE= option in the PROC HPLMIXED statement.

One advantage of using the Newton-Raphson algorithm is that the second derivative matrix of the objective function evaluated at the optima is available upon completion. Denoting this matrix $\mathbf{H}$, the asymptotic theory of maximum likelihood (Serfling 1980) shows that $2\mathbf{H}^{-1}$ is an asymptotic variance-covariance matrix of the estimated parameters of $\mathbf{G}$ and $\mathbf{R}$. Thus, tests and confidence intervals based on asymptotic normality can be obtained. However, these can be unreliable in small samples, especially for parameters such as variance components that have sampling distributions that tend to be skewed to the right.

If a residual variance σ^2 is a part of your mixed model, it can usually be *profiled* out of the likelihood. This means solving analytically for the optimal σ^2 and plugging this expression back into the likelihood formula (Wolfinger, Tobias, and Sall 1994). This reduces the number of optimization parameters by 1 and can improve convergence properties. PROC HPLMIXED profiles the residual variance out of the log likelihood.

Estimating Fixed and Random Effects in the Mixed Model

ML and REML methods provide estimates of $\mathbf{G}$ and $\mathbf{R}$, which are denoted $\widehat{\mathbf{G}}$ and $\widehat{\mathbf{R}}$, respectively. To obtain estimates of $\boldsymbol{\beta}$ and predicted values of $\boldsymbol{\gamma}$, the standard method is to solve the *mixed model equations* (Henderson 1984):

$$\begin{bmatrix} \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{Z} \\ \mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{Z} + \widehat{\mathbf{G}}^{-1} \end{bmatrix} \begin{bmatrix} \widehat{\boldsymbol{\beta}} \\ \widehat{\boldsymbol{\gamma}} \end{bmatrix} = \begin{bmatrix} \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{y} \\ \mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{y} \end{bmatrix}$$

The solutions can also be written as

$$\widehat{\boldsymbol{\beta}} = (\mathbf{X}'\widehat{\mathbf{V}}^{-1}\mathbf{X})^{-}\mathbf{X}'\widehat{\mathbf{V}}^{-1}\mathbf{y}$$

$$\widehat{\boldsymbol{\gamma}} = \widehat{\mathbf{G}}\mathbf{Z}'\widehat{\mathbf{V}}^{-1}(\mathbf{y} - \mathbf{X}\widehat{\boldsymbol{\beta}})$$

and have connections with empirical Bayes estimators (Laird and Ware 1982; Carlin and Louis 1996). Note that the $\boldsymbol{\gamma}$ are random variables and not parameters (unknown constants) in the model. Technically, determining values for $\boldsymbol{\gamma}$ from the data is thus a prediction task, whereas determining values for $\boldsymbol{\beta}$ is an estimation task.

The mixed model equations are extended normal equations. The preceding expression assumes that $\widehat{\mathbf{G}}$ is nonsingular. For the extreme case where the eigenvalues of $\widehat{\mathbf{G}}$ are very large, $\widehat{\mathbf{G}}^{-1}$ contributes very little to the equations and $\widehat{\boldsymbol{\gamma}}$ is close to what it would be if $\boldsymbol{\gamma}$ actually contained fixed-effects parameters. On the other hand, when the eigenvalues of $\widehat{\mathbf{G}}$ are very small, $\widehat{\mathbf{G}}^{-1}$ dominates the equations and $\widehat{\boldsymbol{\gamma}}$ is close to 0. For intermediate cases, $\widehat{\mathbf{G}}^{-1}$ can be viewed as shrinking the fixed-effects estimates of $\boldsymbol{\gamma}$ toward 0 (Robinson 1991).

If $\widehat{\mathbf{G}}$ is singular, then the mixed model equations are modified (Henderson 1984) as follows:

$$\begin{bmatrix} \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{Z}\widehat{\mathbf{G}} \\ \widehat{\mathbf{G}}'\mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \widehat{\mathbf{G}}'\mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{Z}\widehat{\mathbf{G}}+\mathbf{G} \end{bmatrix} \begin{bmatrix} \widehat{\boldsymbol{\beta}} \\ \widehat{\boldsymbol{\tau}} \end{bmatrix} = \begin{bmatrix} \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{y} \\ \widehat{\mathbf{G}}'\mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{y} \end{bmatrix}$$

Denote the generalized inverses of the nonsingular $\widehat{\mathbf{G}}$ and singular $\widehat{\mathbf{G}}$ forms of the mixed model equations by $\mathbf{C}$ and $\mathbf{M}$, respectively. In the nonsingular case, the solution $\widehat{\boldsymbol{\gamma}}$ estimates the random effects directly. But in the singular case, the estimates of random effects are achieved through a back-transformation $\widehat{\boldsymbol{\gamma}} = \widehat{\mathbf{G}}\widehat{\boldsymbol{\tau}}$ where $\widehat{\boldsymbol{\tau}}$ is the solution to the modified mixed model equations. Similarly, while in the nonsingular case $\mathbf{C}$ itself is the estimated covariance matrix for $(\widehat{\boldsymbol{\beta}}, \widehat{\boldsymbol{\gamma}})$, in the singular case the covariance estimate for $(\widehat{\boldsymbol{\beta}}, \widehat{\mathbf{G}}\widehat{\boldsymbol{\tau}})$ is given by $\mathbf{PMP}$ where

$$\mathbf{P} = \begin{bmatrix} \mathbf{I} & \\ & \widehat{\mathbf{G}} \end{bmatrix}$$

An example of when the singular form of the equations is necessary is when a variance component estimate falls on the boundary constraint of 0.

Statistical Properties

If $\mathbf{G}$ and $\mathbf{R}$ are known, $\widehat{\boldsymbol{\beta}}$ is the best linear unbiased estimator (BLUE) of $\boldsymbol{\beta}$, and $\widehat{\boldsymbol{\gamma}}$ is the best linear unbiased predictor (BLUP) of $\boldsymbol{\gamma}$ (Searle 1971; Harville 1988, 1990; Robinson 1991; McLean, Sanders, and Stroup 1991). Here, "best" means minimum mean squared error. The covariance matrix of $(\widehat{\boldsymbol{\beta}} - \boldsymbol{\beta}, \widehat{\boldsymbol{\gamma}} - \boldsymbol{\gamma})$ is

$$\mathbf{C} = \begin{bmatrix} \mathbf{X}'\mathbf{R}^{-1}\mathbf{X} & \mathbf{X}'\mathbf{R}^{-1}\mathbf{Z} \\ \mathbf{Z}'\mathbf{R}^{-1}\mathbf{X} & \mathbf{Z}'\mathbf{R}^{-1}\mathbf{Z}+\mathbf{G}^{-1} \end{bmatrix}^{-}$$

where $^{-}$ denotes a generalized inverse (Searle 1971).

However, $\mathbf{G}$ and $\mathbf{R}$ are usually unknown and are estimated by using one of the aforementioned methods. These estimates, $\widehat{\mathbf{G}}$ and $\widehat{\mathbf{R}}$, are therefore simply substituted into the preceding expression to obtain

$$\widehat{\mathbf{C}} = \begin{bmatrix} \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \mathbf{X}'\widehat{\mathbf{R}}^{-1}\mathbf{Z} \\ \mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{X} & \mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{Z}+\widehat{\mathbf{G}}^{-1} \end{bmatrix}^{-}$$

as the approximate variance-covariance matrix of $(\widehat{\boldsymbol{\beta}}-\boldsymbol{\beta}, \widehat{\boldsymbol{\gamma}}-\boldsymbol{\gamma})$. In this case, the BLUE and BLUP acronyms no longer apply, but the word *empirical* is often added to indicate such an approximation. The appropriate acronyms thus become EBLUE and EBLUP.

McLean and Sanders (1988) show that $\widehat{\mathbf{C}}$ can also be written as

$$\widehat{\mathbf{C}} = \begin{bmatrix} \widehat{\mathbf{C}}_{11} & \widehat{\mathbf{C}}'_{21} \\ \widehat{\mathbf{C}}_{21} & \widehat{\mathbf{C}}_{22} \end{bmatrix}$$

where

$$\widehat{\mathbf{C}}_{11} = (\mathbf{X}'\widehat{\mathbf{V}}^{-1}\mathbf{X})^{-}$$
$$\widehat{\mathbf{C}}_{21} = -\widehat{\mathbf{G}}\mathbf{Z}'\widehat{\mathbf{V}}^{-1}\mathbf{X}\widehat{\mathbf{C}}_{11}$$
$$\widehat{\mathbf{C}}_{22} = (\mathbf{Z}'\widehat{\mathbf{R}}^{-1}\mathbf{Z} + \widehat{\mathbf{G}}^{-1})^{-1} - \widehat{\mathbf{C}}_{21}\mathbf{X}'\widehat{\mathbf{V}}^{-1}\mathbf{Z}\widehat{\mathbf{G}}$$

Note that $\widehat{\mathbf{C}}_{11}$ is the familiar estimated generalized least squares formula for the variance-covariance matrix of $\widehat{\boldsymbol{\beta}}$.

Computational Method

Distributed Computing

Distributed computing refers to the use of multiple autonomous computers that communicate through a secure network. Distributed computing solves computational problems by dividing them into many tasks, each of which is solved by one or more computers. Each computer in this distributed environment is referred to as a node.

You can specify the number of nodes to use with the NODES= option in the PERFORMANCE statement. Specify NODES=0 to force the execution to be done locally (often referred to as soloist-mode computing).

Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPLMIXED procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statements, the HPLMIXED procedure schedules threads as if it executes on a system with four CPUs, regardless of the actual CPU count:

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This specification overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement, which overrides the CPUCOUNT= system option and instructs the HPLMIXED procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output. The HPLMIXED procedure allocates two threads per CPU.

The tasks multithreaded by the HPLMIXED procedure are primarily defined by dividing the data processed on a single machine among the threads—that is, the HPLMIXED procedure implements multithreading through a data-parallel model. For example, if the input data set has 1,000 observations and you are running with four threads, then 250 observations are associated with each thread. All operations that require access to the data are then multithreaded. These operations include the following:

- variable levelization
- effect levelization
- formation of the crossproducts matrix
- the log-likelihood computation

In addition, operations on matrices such as sweeps might be multithreaded if the matrices are of sufficient size to realize performance benefits from managing multiple threads for the particular matrix operation.

Displayed Output

The following sections describe the output produced by PROC HPLMIXED. The output is organized into various tables, which are discussed in the order of their appearance.

Performance Information

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution and information about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

Model Information

The "Model Information" table describes the model, some of the variables it involves, and the method used in fitting it. The "Model Information" table also has a row labeled Fixed Effects SE Method. This row describes the method used to compute the approximate standard errors for the fixed-effects parameter estimates and related functions of them.

Class Level Information

The "Class Level Information" table lists the levels of every variable specified in the CLASS statement.

Dimensions

The "Dimensions" table lists the sizes of relevant matrices. This table can be useful in determining the requirements for CPU time and memory.

Number of Observations

The "Number of Observations" table shows the number of observations read from the data set and the number of observations used in fitting the model.

Optimization Information

The "Optimization Information" table displays important details about the optimization process.

The number of parameters that are updated in the optimization equals the number of parameters in this table minus the number of equality constraints. The number of constraints is displayed if you fix covariance parameters with the HOLD= option in the PARMS statement. The HPLMIXED procedure also lists the number of upper and lower boundary constraints. PROC HPLMIXED might impose boundary constraints for certain parameters, such as variance components and correlation parameters. If you specify the HOLD= option in the PARMS statement, covariance parameters have an upper and lower boundary equal to the parameter value.

Iteration History

The "Iteration History" table describes the optimization of the restricted log likelihood or log likelihood. The function to be minimized (the *objective function*) is $-2l$ for ML and $-2l_R$ for REML; the column name of the objective function in the "Iteration History" table is "-2 Log Like" for ML and "-2 Res Log Like" for REML. The minimization is performed by using a ridge-stabilized Newton-Raphson algorithm, and the rows of this table describe the iterations that this algorithm takes in order to minimize the objective function.

The Evaluations column of the "Iteration History" table tells how many times the objective function is evaluated during each iteration.

The Criterion column of the "Iteration History" table is, by default, a relative Hessian convergence quantity given by

$$\frac{\mathbf{g}_k' \mathbf{H}_k^{-1} \mathbf{g}_k}{|f_k|}$$

where f_k is the value of the objective function at iteration k, $\mathbf{g}_k$ is the gradient (first derivative) of f_k, and $\mathbf{H}_k$ is the Hessian (second derivative) of f_k. If $\mathbf{H}_k$ is singular, then PROC HPLMIXED uses the following relative quantity:

$$\frac{\mathbf{g}_k' \mathbf{g}_k}{|f_k|}$$

To prevent division by $|f_k|$, specify the ABSGCONV option in the PROC HPLMIXED statement. To use a relative function or gradient criterion, specify the FCONV or GCONV option, respectively.

The Hessian criterion is considered superior to function and gradient criteria because it measures orthogonality rather than lack of progress (Bates and Watts 1988). Provided that the initial estimate is feasible and the maximum number of iterations is not exceeded, the Newton-Raphson algorithm is considered to have converged when the criterion is less than the tolerance specified with the FCONV or GCONV option in the PROC HPLMIXED statement. The default tolerance is 1E–8. If convergence is not achieved, PROC HPLMIXED displays the estimates of the parameters at the last iteration.

A convergence criterion that is missing indicates that a boundary constraint has been dropped; it is usually not a cause for concern.

Convergence Status

The "Convergence Status" table displays the status of the iterative estimation process at the end of the optimization. The status appears as a message in the listing, and this message is repeated in the log. The ODS object "ConvergenceStatus" also contains several nonprinting columns that can be helpful in checking the success of the iterative process, in particular during batch processing. The Status variable takes on the value 0 for a successful convergence (even if the Hessian matrix might not be positive definite). The values 1 and 2 of the Status variable indicate lack of convergence and infeasible initial parameter values, respectively. The variable pdG can be used to check whether the G matrix is positive definite.

For models that are not fit iteratively, such as models without random effects or when the NOITER option is in effect, the "Convergence Status" is not produced.

Covariance Parameter Estimates

The "Covariance Parameter Estimates" table contains the estimates of the parameters in $\mathbf{G}$ and $\mathbf{R}$. (See the section "Estimating Covariance Parameters in the Mixed Model" on page 306.) Their values are labeled in the table along with Subject information if applicable. The estimates are displayed in the Estimate column and are the results of either the REML or the ML estimation method.

Fit Statistics

The "Fit Statistics" table provides some statistics about the estimated mixed model. Expressions for -2 times the log likelihood are provided in the section "Estimating Covariance Parameters in the Mixed Model" on page 306. If the log likelihood is an extremely large number, then PROC HPLMIXED has deemed the estimated $\mathbf{V}$ matrix to be singular. In this case, all subsequent results should be viewed with caution.

In addition, the "Fit Statistics" table lists three information criteria: AIC, AICC, and BIC. All these criteria are in smaller-is-better form and are described in Table 15.8.

Table 15.8 Information Criteria

Criterion	Formula	Reference
AIC	$-2\ell + 2d$	Akaike (1974)
AICC	$-2\ell + 2dn^*/(n^* - d - 1)$	Hurvich and Tsai (1989) Burnham and Anderson (1998)
BIC	$-2\ell + d \log n$ for $n > 0$	Schwarz (1978)

Here ℓ denotes the maximum value of the (possibly restricted) log likelihood, d is the dimension of the model. n equals the number of effective subjects as displayed in the "Dimensions" table, unless this value equals 1, in which case n equals the number of levels of the first random effect that you specify in a RANDOM statement. If the number of effective subjects equals 1 and you have no RANDOM statements, then n equals the number of valid observations for maximum likelihood estimation and $n - p$ for restricted maximum likelihood estimation, where p equals the rank of $\mathbf{X}$. For AICC (a finite-sample corrected version of AIC), n^* equals the number of valid observations for maximum likelihood estimation and $n - p$ equals the number of valid observations for restricted maximum likelihood estimation, unless this number is less than $d + 2$, in which case it equals $d + 2$. When $n = 0$, the value of the BIC is -2ℓ.

For restricted likelihood estimation, d equals q, the effective number of estimated covariance parameters. For maximum likelihood estimation, d equals $q + p$.

Timing Information

If you specify the DETAILS option in the PERFORMANCE statement, the procedure also produces a "Timing" table in which the elapsed time for each main task of the procedure is displayed.

ODS Table Names

Each table created by PROC HPLMIXED has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 15.9.

Table 15.9 ODS Tables Produced by PROC HPLMIXED

Table Name	Description	Required Statement / Option
ClassLevels	Level information from the CLASS statement	Default output
ConvergenceStatus	Convergence status	Default output
CovParms	Estimated covariance parameters	Default output
Dimensions	Dimensions of the model	Default output
FitStatistics	Fit statistics	Default output
IterHistory	Iteration history	Default output
ModelInfo	Model information	Default output
NObs	Number of observations read and used	Default output
OptInfo	Optimization information	Default output
ParmSearch	Parameter search values	PARMS
PerformanceInfo	Information about high-performance computing environment	Default output
SolutionF	Fixed-effects solution vector	MODEL / S
SolutionR	Random-effects solution vector	RANDOM / S
Timing	Timing breakdown by task	DETAILS option in the PERFORMANCE statement

Examples: HPLMIXED Procedure

Example 15.1: Computing BLUPs for a Large Number of Subjects

Suppose you are using health measurements on patients treated by each medical center to monitor the performance of those centers. Different measurements within each patient are correlated, and there is enough data to fit the parameters of an unstructured covariance model for this correlation. In fact, long experience with historical data provides you with values for the covariance model that are essentially known, and the task is to apply these known values in order to compute best linear unbiased predictors (BLUPs) of the ran-

dom effect of medical center. You can use these BLUPs to determine the best and worst performing medical centers, adjusting for other factors, on a weekly basis. Another reason why you want to do this with fixed values for the covariance parameters is to make the week-to-week BLUPs more comparable.

Although you cannot use the REPEATED statement in PROC HPLMIXED to fit models in this release, you can use it to compute BLUPs for such models with known values of the variance parameters. For illustration, the following statements create a simulated data set of a given week's worth of patient health measurements across 100 different medical centers. Measurements at three different times are simulated for each patient, and each center has about 50 patients. The simulated model includes a fixed gender effect, a random effect due to center, and covariance between different measurements on the same patient.

```
%let NCenter  = 100;
%let NPatient = %eval(&NCenter*50);
%let NTime    = 3;
%let SigmaC   = 2.0;
%let SigmaP   = 4.0;
%let SigmaE   = 8.0;
%let Seed     = 12345;

data WeekSim;
   keep Gender Center Patient Time Measurement;
   array PGender{&NPatient};
   array PCenter{&NPatient};
   array PEffect{&NPatient};
   array CEffect{&NCenter};
   array GEffect{2};

   do Center = 1 to &NCenter;
      CEffect{Center} = sqrt(&SigmaC)*rannor(&Seed);
      end;

   GEffect{1} = 10*ranuni(&Seed);
   GEffect{2} = 10*ranuni(&Seed);

   do Patient = 1 to &NPatient;
      PGender{Patient} = 1 + int(2       *ranuni(&Seed));
      PCenter{Patient} = 1 + int(&NCenter*ranuni(&Seed));
      PEffect{Patient} = sqrt(&SigmaP)*rannor(&Seed);
      end;

   do Patient = 1 to &NPatient;
      Gender = PGender{Patient};
      Center = PCenter{Patient};
      Mean = 1 + GEffect{Gender} + CEffect{Center} + PEffect{Patient};
      do Time = 1 to &nTime;
         Measurement = Mean + sqrt(&SigmaE)*rannor(&Seed);
      output;
      end;
   end;
run;
```

Suppose that the known values for the covariance parameters are

$$\text{Var(Center)} = 1.7564$$

$$\text{Cov(Patient)} = \begin{bmatrix} 11.4555 & 3.6883 & 4.5951 \\ 3.6883 & 11.2071 & 3.6311 \\ 4.5951 & 3.6311 & 12.1050 \end{bmatrix}$$

Incidentally, these are not precisely the same estimates you would get if you estimated these parameters based on the preceding data (for example, with the HPLMIXED procedure).

The following statements use PROC HPLMIXED to compute the BLUPs for the random medical center effect. Instead of simply displaying them (as PROC HPMIXED does), PROC HPLMIXED sorts them and displays the five highest and lowest values.

```
ods listing close;
proc hplmixed data=WeekSim blup;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC" nodes=20;
   class Gender Center Patient Time;
   model Measurement = Gender;
   random   Center / s;
   repeated Time   / sub=Patient type=un;
   parms   1.7564
          11.4555
           3.6883 11.2071
           4.5951  3.6311 12.1050;
   ods output SolutionR=BLUPs;
run;
ods listing;

proc sort data=BLUPs;
   by Estimate;
run;

data BLUPs; set BLUPs;
   Rank = _N_;
run;

proc print data=BLUPs;
   where ((Rank <= 5) | (Rank >= 96));
   var Center Estimate;
run;
```

Three parts of the PROC HPLMIXED syntax are required in order to compute BLUPs for this model: the BLUP option in the HPLMIXED statement, the REPEATED statement, and the PARMS statement with fixed values for all parameters. The resulting values of the best and worst performing medical centers for this week are shown in Output 15.1.1. Apparently, for this week's data, medical center 54 had the most decreasing effect, and medical center 48 the most increasing effect, on patient measurements overall.

Output 15.1.1 Highest and Lowest Medical Center BLUPs

Obs	Center	Estimate
1	54	-2.9369
2	7	-2.4614
3	50	-2.2467
4	51	-2.2281
5	93	-2.1644
96	26	2.1603
97	99	2.2718
98	44	2.4222
99	60	2.6089
100	48	2.6443

References

Akaike, H. (1974), "A New Look at the Statistical Model Identification," *IEEE Transaction on Automatic Control*, AC–19, 716–723.

Burdick, R. K. and Graybill, F. A. (1992), *Confidence Intervals on Variance Components,* New York: Marcel Dekker.

Burnham, K. P. and Anderson, D. R. (1998), *Model Selection and Inference: A Practical Information-Theoretic Approach,* New York: Springer-Verlag.

Brown, H. and Prescott, R. (1999), *Applied Mixed Models in Medicine*, New York: John Wiley & Sons.

Carlin, B. P. and Louis, T. A. (1996), *Bayes and Empirical Bayes Methods for Data Analysis,* London: Chapman and Hall.

Dempster, A. P., Laird, N. M., and Rubin, D. B. (1977), "Maximum Likelihood from Incomplete Data via the EM Algorithm," *Journal of the Royal Statistical Society*, Ser. B., 39, 1–38.

Fai, A. H. T. and Cornelius, P. L. (1996), "Approximate *F*-tests of Multiple Degree of Freedom Hypotheses in Generalized Least Squares Analyses of Unbalanced Split-Plot Experiments," *Journal of Statistical Computation and Simulation,* 54, 363–378.

Fuller, W. A. (1976), *Introduction to Statistical Time Series,* New York: John Wiley & Sons.

Giesbrecht, F. G. and Burns, J. C. (1985), "Two-Stage Analysis Based on a Mixed Model: Large-sample Asymptotic Theory and Small-Sample Simulation Results," *Biometrics*, 41, 477–486.

Hartley, H. O. and Rao, J. N. K. (1967), "Maximum-Likelihood Estimation for the Mixed Analysis of Variance Model," *Biometrika*, 54, 93–108.

Hurvich, C. M. and Tsai, C.-L. (1989), "Regression and Time Series Model Selection in Small Samples," *Biometrika*, 76, 297–307.

Harville, D. A. (1977), "Maximum Likelihood Approaches to Variance Component Estimation and to Related Problems," *Journal of the American Statistical Association*, 72, 320–338.

Harville, D. A. (1988), "Mixed-Model Methodology: Theoretical Justifications and Future Directions," *Proceedings of the Statistical Computing Section*, American Statistical Association, New Orleans, 41–49.

Harville, D. A. (1990), "BLUP (Best Linear Unbiased Prediction), and Beyond," in *Advances in Statistical Methods for Genetic Improvement of Livestock*, Springer-Verlag, 239–276.

Henderson, C. R. (1984), *Applications of Linear Models in Animal Breeding*, University of Guelph.

Henderson, C. R. (1990), "Statistical Method in Animal Improvement: Historical Overview," in *Advances in Statistical Methods for Genetic Improvement of Livestock*, New York: Springer-Verlag, 1–14.

Huynh, H. and Feldt, L. S. (1970), "Conditions Under Which Mean Square Ratios in Repeated Measurements Designs Have Exact F-Distributions," *Journal of the American Statistical Association*, 65, 1582–1589.

Jennrich, R. I. and Schluchter, M. D. (1986), "Unbalanced Repeated-Measures Models with Structured Covariance Matrices," *Biometrics*, 42, 805–820.

Kenward, M. G. (1987), "A Method for Comparing Profiles of Repeated Measurements," *Applied Statistics*, 36, 296–308.

Laird, N. M., Lange, N., and Stram, D. (1987), "Maximum Likelihood Computations with Repeated Measures: Application of the EM Algorithm," *Journal of the American Statistical Association*, 82, 97–105.

Laird, N. M. and Ware, J. H. (1982), "Random-Effects Models for Longitudinal Data," *Biometrics*, 38, 963–974.

Lindstrom, M. J. and Bates, D. M. (1988), "Newton-Raphson and EM Algorithms for Linear Mixed-Effects Models for Repeated-Measures Data," *Journal of the American Statistical Association*, 83, 1014–1022.

Littell, R. C., Milliken, G. A., Stroup, W. W., Wolfinger, R. D., and Schabenberger, O. (2006), *SAS for Mixed Models,* Second Edition, Cary, NC: SAS Institute Inc.

Little, R. J. A. (1995), "Modeling the Drop-Out Mechanism in Repeated-Measures Studies," *Journal of the American Statistical Association*, 90, 1112–1121.

Macchiavelli, R. E. and Arnold, S. F. (1994), "Variable Order Ante-dependence Models," *Communications in Statistics–Theory and Methods*, 23(9), 2683–2699.

McLean, R. A. and Sanders, W. L. (1988), "Approximating Degrees of Freedom for Standard Errors in Mixed Linear Models," *Proceedings of the Statistical Computing Section*, American Statistical Association, New Orleans, 50–59.

McLean, R. A., Sanders, W. L., and Stroup, W. W. (1991), "A Unified Approach to Mixed Linear Models," *The American Statistician*, 45, 54–64.

Milliken, G. A. and Johnson, D. E. (1992), *Analysis of Messy Data, Volume 1: Designed Experiments*, New York: Chapman and Hall.

Patel, H. I. (1991), "Analysis of Incomplete Data from a Clinical Trial with Repeated Measurements," *Biometrika*, 78, 609–619.

Patterson, H. D. and Thompson, R. (1971), "Recovery of Inter-block Information When Block Sizes Are Unequal," *Biometrika*, 58, 545–554.

Robinson, G. K. (1991), "That BLUP Is a Good Thing: The Estimation of Random Effects," *Statistical Science*, 6, 15–51.

Rubin, D. B. (1976), "Inference and Missing Data," *Biometrika*, 63, 581–592.

Schluchter, M. D. and Elashoff, J. D. (1990), "Small-Sample Adjustments to Tests with Unbalanced Repeated Measures Assuming Several Covariance Structures," *Journal of Statistical Computation and Simulation*, 37, 69–87.

Schwarz, G. (1978), "Estimating the Dimension of a Model," *Annals of Statistics*, 6, 461–464.

Searle, S. R. (1971), *Linear Models*, New York: John Wiley & Sons.

Searle, S. R. (1982), *Matrix Algebra Useful for Statisticians*, New York: John Wiley & Sons.

Searle, S. R., Casella, G., and McCulloch, C. E. (1992), *Variance Components*, New York: John Wiley & Sons.

Serfling, R. J. (1980), *Approximation Theorems of Mathematical Statistics*, New York: John Wiley & Sons.

Snedecor, G. W. and Cochran, W. G. (1980), *Statistical Methods*, Ames: Iowa State University Press.

Steel, R. G. D., Torrie, J. H., and Dickey D. (1997), *Principles and Procedures of Statistics: A Biometrical Approach*, Third Edition, New York: McGraw-Hill, Inc.

Verbeke, G. and Molenberghs, G., eds. (1997), *Linear Mixed Models in Practice: A SAS-Oriented Approach,* New York: Springer.

Verbeke, G. and Molenberghs, G. (2000), *Linear Mixed Models for Longitudinal Data,* New York: Springer.

Winer, B. J. (1971), *Statistical Principles in Experimental Design*, Second Edition, New York: McGraw-Hill, Inc.

Wolfinger, R. D. (1996), "Heterogeneous Variance-Covariance Structures for Repeated Measures," *Journal of Agricultural, Biological, and Environmental Statistics,* 1, 205–230.

Wolfinger, R. D., Tobias, R. D., and Sall, J. (1994), "Computing Gaussian Likelihoods and Their Derivatives for General Linear Mixed Models," *SIAM Journal on Scientific Computing*, 15(6), 1294–1310.

Chapter 16
The HPLOGISTIC Procedure

Contents

Overview: HPLOGISTIC Procedure **320**
PROC HPLOGISTIC Features 320
PROC HPLOGISTIC Contrasted with Other SAS Procedures 321
Getting Started: HPLOGISTIC Procedure **321**
Binary Logistic Regression 321
Syntax: HPLOGISTIC Procedure **328**
PROC HPLOGISTIC Statement 328
CLASS Statement 334
FREQ Statement 334
ID Statement 334
MODEL Statement 335
OUTPUT Statement 339
PERFORMANCE Statement 341
SELECTION Statement 341
WEIGHT Statement 342
Details: HPLOGISTIC Procedure **342**
Missing Values 342
Response Distributions 343
Log-Likelihood Functions 344
Generalized Coefficient of Determination 345
The Hosmer-Lemeshow Goodness-of-Fit Test 346
Computational Method: Multithreading 347
Choosing an Optimization Algorithm 348
First- or Second-Order Algorithms 348
Algorithm Descriptions 349
Displayed Output 351
ODS Table Names 355
Examples: HPLOGISTIC Procedure **356**
Example 16.1: Model Selection 356
Example 16.2: Modeling Binomial Data 360
Example 16.3: Ordinal Logistic Regression 365
Example 16.4: Conditional Logistic Regression for Matched Pairs Data 368
References **372**

Overview: HPLOGISTIC Procedure

The HPLOGISTIC procedure is a high-performance procedure that fits logistic regression models for binary, binomial, and multinomial data on the SAS appliance.

The HPLOGISTIC procedure fits logistic regression models in the broader sense; the procedure permits several link functions and can handle ordinal and nominal data with more than two response categories (multinomial data).

With the HPLOGISTIC procedure you can read and write data in distributed form and perform analyses in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details.

PROC HPLOGISTIC Features

The HPLOGISTIC procedure estimates the parameters of a logistic regression model by using maximum likelihood techniques. It also does the following:

- provides the ability to perform analyses on a massively parallel SAS high-performance appliance
- performs parallel reads of input data and parallel writes of output data when the data source is the appliance database
- is highly multithreaded during all phases of analytic execution
- provides model-building syntax with the CLASS and effect-based MODEL statements, which are familiar from SAS/STAT analytic procedures (in particular, the GLM, LOGISTIC, GLIMMIX, and MIXED procedures)
- provides response-variable options as in the LOGISTIC procedure
- performs maximum likelihood estimation
- provides multiple link functions
- provides cumulative link models for ordinal data and generalized logit modeling for unordered multinomial data
- enables model building (variable selection) through the SELECTION statement
- provides a WEIGHT statement for weighted analysis
- provides a FREQ statement for grouped analysis
- provides an OUTPUT statement to produce a data set with predicted probabilities and other observationwise statistics

PROC HPLOGISTIC Contrasted with Other SAS Procedures

For general contrasts, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16. The following remarks contrast the HPLOGISTIC procedure with the LOGISTIC procedure in SAS/STAT software.

The CLASS statement in the HPLOGISTIC procedure permits two parameterizations: the GLM parameterization and a reference parameterization. In contrast to the LOGISTIC, GENMOD, and other procedures that permit multiple parameterizations, the HPLOGISTIC procedure does not mix parameterizations across the variables in the CLASS statement. In other words, all classification variables have the same parameterization, and this parameterization is either the GLM or reference parameterization.

The default optimization technique used by the LOGISTIC procedure is Fisher scoring; the HPLOGISTIC procedure uses by default a modification of the Newton-Raphson algorithm with a ridged Hessian. You can choose different optimization techniques, including first-order methods that do not require a crossproducts matrix or Hessian, with the TECHNIQUE= option in the PROC HPLOGISTIC statement.

The default parameterization of CLASS variables in the HPLOGISTIC procedure is the GLM parameterization. The LOGISTIC procedure uses the EFFECT parameterization for the CLASS variables by default. In either procedure, you can change the parameterization with the PARAM= option in the CLASS statement.

The LOGISTIC procedure offers a wide variety of postfitting analyses, such as contrasts, estimates, tests of model effects, least squares means, and odds ratios. This release of the HPLOGISTIC procedure is limited in postfitting functionality, since with large data sets the focus is primarily on model fitting and scoring.

The HPLOGISTIC procedure is specifically designed to operate in the high-performance distributed environment. By default, PROC HPLOGISTIC performs computations in multiple threads. The LOGISTIC procedure executes in a single thread.

Getting Started: HPLOGISTIC Procedure

Binary Logistic Regression

The following DATA step contains 100 observations on a dichotomous response variable (y), a character variable (C), and 10 continuous variables (x1–x10):

```
data getStarted;
  input C$ y x1-x10;
  datalines;
D  0  10.2  6  1.6  38  15  2.4  20  0.8  8.5  3.9
F  1  12.2  6  2.6  42  61  1.5  10  0.6  8.5  0.7
D  1   7.7  1  2.1  38  61    1  90  0.6  7.5  5.2
J  1  10.9  7  3.5  46  42  0.3   0  0.2    6  3.6
E  0  17.3  6  3.8  26  47  0.9  10  0.4  1.5  4.7
A  0  18.7  4  1.8   2  34  1.7  80    1  9.5  2.2
B  0   7.2  1  0.3  48  61  1.1  10  0.8  3.5    4
D  0   0.1  3  2.4   0  65  1.6  70  0.8  3.5  0.7
H  1   2.4  4  0.7  38  22  0.2  20    0    3  4.2
```

```
J  0  15.6  7  1.4   0  98  0.3   0    1    5  5.2
J  0  11.1  3  2.4  42  55  2.2  60  0.6  4.5  0.7
F  0     4  6  0.9   4  36  2.1  30  0.8    9  4.6
A  0   6.2  2  1.8  14  79  1.1  70  0.2    0  5.1
H  0   3.7  3  0.8  12  66  1.3  40  0.4  0.5  3.3
A  1   9.2  3  2.3  48  51  2.3  50    0    6  5.4
G  0    14  3    2  18  12  2.2   0    0    3  3.4
E  1  19.5  6  3.7  26  81  0.1  30  0.6    5  4.8
C  0    11  3  2.8  38   9  1.7  50  0.8  6.5  0.9
I  0  15.3  7  2.2  20  98  2.7 100  0.4    7  0.8
H  1   7.4  4  0.5  28  65  1.3  60  0.2  9.5  5.4
F  0  11.4  2  1.4  42  12  2.4  10  0.4    1  4.5
C  1  19.4  1  0.4  42   4  2.4  10    0  6.5  0.1
G  0   5.9  4  2.6  12  57  0.8  50  0.4    2  5.8
G  1  15.8  6  3.7  34   8  1.3  90  0.6  2.5  5.7
I  0    10  3  1.9  16  80    3  90  0.4  9.5  1.9
E  0  15.7  1  2.7  32  25  1.7  20  0.2  8.5    6
G  0    11  5  2.9  48  53  0.1  50    1  3.5  1.2
J  1  16.8  0  0.9  14  86  1.4  40  0.8    9    5
D  1    11  4  3.2  48  63  2.8  90  0.6    0  2.2
J  1   4.8  7  3.6  24   1  2.2  20    1  8.5  0.5
J  1  10.4  5    2  42  56    1  20    0  3.5  4.2
G  0  12.7  7  3.6   8  56  2.1  70    1  4.5  1.5
G  0   6.8  1  3.2  30  27  0.6   0  0.8    2  5.6
E  0   8.8  0  3.2   2  67  0.7  10  0.4    1    5
I  1   0.2  0  2.9  10  41  2.3  60  0.2    9  0.3
J  1   4.6  7  3.9  50  61  2.1  50  0.4    3  4.9
J  1   2.3  2  3.2  36  98  0.1  40  0.6  4.5  4.3
I  0  10.8  3  2.7  28  58  0.8  80  0.8    3    6
B  0   9.3  2  3.3  44  44  0.3  50  0.8  5.5  0.4
F  0   9.2  6  0.6   4  64  0.1   0  0.6  4.5  3.9
D  0   7.4  0  2.9  14   0  0.2  30  0.8  7.5  4.5
G  0  18.3  3  3.1   8  60  0.3  60  0.2    7  1.9
F  0   5.3  4  0.2  48  63  2.3  80  0.2    8  5.2
C  0   2.6  5  2.2  24   4  1.3  20    0    2  1.4
F  0  13.8  4  3.6   4   7  1.1  10  0.4  3.5  1.9
B  1  12.4  6  1.7  30  44  1.1  60  0.2    6  1.5
I  0   1.3  1  1.3   8  53  1.1  70  0.6    7  0.8
F  0  18.2  7  1.7  26  92  2.2  30    1  8.5  4.8
J  0   5.2  2  2.2  18  12  1.4  90  0.8    4  4.9
G  1   9.4  2  0.8  22  86  0.4  30  0.4    1  5.9
J  1  10.4  2  1.7  26  31  2.4  10  0.2    7  1.6
J  0    13  1  1.8  14  11  2.3  50  0.6  5.5  2.6
A  0  17.9  4  3.1  46  58  2.6  90  0.6  1.5  3.2
D  1  19.4  6    3  20  50  2.8 100  0.2    9  1.2
I  0  19.6  3  3.6  22  19  1.2   0  0.6    5  4.1
I  1     6  2  1.5  30  30  2.2  20  0.4  8.5  5.3
G  0  13.8  1  2.7   0  52  2.4  20  0.8    6    2
B  0  14.3  4  2.9  30  11  0.6  90  0.6  0.5  4.9
E  0  15.6  0  0.4  38  79  0.4  80  0.4    1  3.3
D  0    14  2    1  22  61    3  90  0.6    2  0.1
C  1   9.4  5  0.4  12  53  1.7  40    0    3  1.1
H  0  13.2  1  1.6  40  15  0.7  40  0.2    9  5.5
A  0  13.5  5  2.4  18  89  1.6  20  0.4  9.5  4.7
```

```
  E  0   2.6  4  2.3  38   6  0.8  20  0.4    5  5.3
  E  0  12.4  3  1.3  26   8  2.8  10  0.8    6  5.8
  D  0   7.6  2  0.9  44  89  1.3  50  0.8    6  0.4
  I  0  12.7  1  2.3  42   6  2.4  10  0.4    1    3
  C  1  10.7  4  3.2  28  23  2.2  90  0.8  5.5  2.8
  H  0  10.1  2  2.3  10  62  0.9  50  0.4  2.5  3.7
  C  1  16.6  1  0.5  12  88  0.1  20  0.6  5.5  1.8
  I  1   0.2  3  2.2   8  71  1.7  80  0.4  0.5  5.5
  C  0  10.8  4  3.5  30  70  2.3  60  0.4  4.5  5.9
  F  0   7.1  4    3  14  63  2.4  70    0    7  3.1
  D  0  16.5  1  3.3  30  80  1.6  40    0  3.5  2.7
  H  0  17.1  7  2.1  30  45  1.5  60  0.6  0.5  2.8
  D  0   4.3  1  1.5  24  44    0  70    0    5  0.5
  H  0    15  2  0.2  14  87  1.8  50    0  4.5  4.7
  G  0  19.7  3  1.9  36  99  1.5  10  0.6    3  1.7
  H  1   2.8  6  0.6  34  21    2  60    1    9  4.7
  G  0  16.6  3  3.3  46   1  1.4  70  0.6  1.5  5.3
  E  0  11.7  5  2.7  48   4  0.9  60  0.8  4.5  1.6
  F  0  15.6  3  0.2   4  79  0.5   0  0.8  1.5  2.9
  C  1   5.3  6  1.4   8  64    2  80  0.4    9  4.2
  B  1   8.1  7  1.7  40  36  1.4  60  0.6    6  3.9
  I  0  14.8  2  3.2   8  37  0.4  10    0  4.5    3
  D  0   7.4  4    3  12   3  0.6  60  0.6    7  0.7
  D  0   4.8  3  2.3  44  41  1.9  60  0.2    3  3.1
  A  0   4.5  0  0.2   4  48  1.7  80  0.8    9  4.2
  D  0   6.9  6  3.3  14  92  0.5  40  0.4  7.5    5
  B  0   4.7  4  0.9  14  99  2.4  80    1  0.5  0.7
  I  1   7.5  4  2.1  20  79  0.4  40  0.4  2.5  0.7
  C  0   6.1  0  1.4  38  18  2.3  60  0.8  4.5  0.7
  C  0  18.3  1    1  26  98  2.7  20    1  8.5  0.5
  F  0  16.4  7  1.2  32  94  2.9  40  0.4  5.5  2.1
  I  0   9.4  2  2.3  32  42  0.2  70  0.4  8.5  0.3
  F  1  17.9  4  1.3  32  42    2  40  0.2    1  5.4
  H  0  14.9  3  1.6  36  74  2.6  60  0.2    1  2.3
  C  0  12.7  0  2.6   0  88  1.1  80  0.8  0.5  2.1
  F  0   5.4  4  1.5   2   1  1.8  70  0.4  5.5  3.6
  J  1  12.1  4  1.8  20  59  1.3  60  0.4    3  3.8
;
```

The following statements fit a logistic model to these data by using a classification effect for variable C and 10 regressor effects for x1–x10:

```
proc hplogistic data=getStarted;
   class C;
   model y = C x1-x10;
run;
```

The default output from this analysis is presented in Figure 16.1 through Figure 16.11.

The "Performance Information" table in Figure 16.1 shows that the procedure executes in client mode—that is, the model is fit on the machine where the SAS session executes. This run of the HPLOGISTIC procedure was performed on a multicore machine with the same number of CPUs as there are threads; that is, one computational thread was spawned per CPU.

Figure 16.1 Performance Information

The HPLOGISTIC Procedure

Performance Information

Execution Mode	On client
Number of Threads	8

Figure 16.2 displays the "Model Information" table. The HPLOGISTIC procedure uses a Newton-Raphson algorithm to model a binary distribution for the variable y with a logit link function. The CLASS variable C is parameterized using the GLM parameterization, which is the default.

Figure 16.2 Model Information

Model Information

Data Source	WORK.GETSTARTED
Response Variable	y
Class Parameterization	GLM
Distribution	Binary
Link Function	Logit
Optimization Technique	Newton-Raphson with Ridging

The CLASS variable C has 10 unique formatted levels, and these are displayed in the "Class Level Information" table in Figure 16.3.

Figure 16.3 Class Level Information

Class Level Information

Class	Levels	Values
C	10	A B C D E F G H I J

Figure 16.4 displays the "Number of Observations" table. All 100 observations in the data set are used in the analysis.

Figure 16.4 Number of Observations

Number of Observations Read	100
Number of Observations Used	100

The "Response Profile" table in Figure 16.5 is produced by default for binary and multinomial response variables. It shows the breakdown of the response variable levels by frequency. By default for binary data, the HPLOGISTIC procedure models the probability of the event with the lower-ordered value in the

"Response Profile" table—this is indicated by the note that follows the table. In this example, the values represented by y = '0' are modeled as the "successes" in the Bernoulli experiments.

Figure 16.5 Response Profile

Response Profile

Ordered Value	y	Total Frequency
1	0	69
2	1	31

You are modeling the probability that y='0'.

You can use the response-variable options in the MODEL statement to affect which value of the response variable is modeled.

Figure 16.6 displays the "Dimensions" table for this model. This table summarizes some important sizes of various model components. For example, it shows that there are 21 columns in the design matrix **X**, which correspond to one column for the intercept, 10 columns for the effect associated with the classification variable C, and one column each for the continuous variables x1–x10. However, the rank of the crossproducts matrix is only 20. Because the classification variable C uses GLM parameterization and because the model contains an intercept, there is one singularity in the crossproducts matrix of the model. Consequently, only 20 parameters enter the optimization.

Figure 16.6 Dimensions in Binomial Logistic Regression

Dimensions

Columns in X	21
Number of Effects	12
Max Effect Columns	10
Rank of Cross-product Matrix	20
Parameters in Optimization	20

The "Iteration History" table is shown in Figure 16.7. The Newton-Raphson algorithm with ridging converged after four iterations, not counting the initial setup iteration.

Figure 16.7 Iteration History

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	4	0.4493546916	.	0.410972
1	2	0.4436453992	0.00570929	0.081339
2	2	0.4435038109	0.00014159	0.003302
3	2	0.4435035933	0.00000022	5.623E-6
4	2	0.4435035933	0.00000000	1.59E-11

Figure 16.8 displays the final convergence status of the Newton-Raphson algorithm. The GCONV= relative convergence criterion is satisfied.

Figure 16.8 Convergence Status

Convergence criterion (GCONV=1E-8) satisfied.

The "Fit Statistics" table is shown in Figure 16.9. The –2 log likelihood at the converged estimates is 88.7007. You can use this value to compare the model to nested model alternatives by means of a likelihood-ratio test. To compare models that are not nested, information criteria such as AIC (Akaike's information criterion), AICC (Akaike's bias-corrected information criterion), and BIC (Schwarz' Bayesian information criterion) are used. These criteria penalize the –2 log likelihood for the number of parameters. Because of the large number of parameters relative to the number of observations, the discrepancy between the –2 log likelihood and, say, AIC, is substantial in this case.

Figure 16.9 Fit Statistics

Fit Statistics

-2 Log Likelihood	88.7007
AIC (smaller is better)	128.70
AICC (smaller is better)	139.33
BIC (smaller is better)	180.80

Figure 16.10 shows the global test for the null hypothesis that all model effects jointly do not affect the probability of success of the binary response. The test is significant (p-value = 0.0135). One or more of the model effects thus significantly affects the probability of observing an event.

Figure 16.10 Null Test

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	35.1194	19	0.0135

However, a look at the "Parameter Estimates" table in Figure 16.11 shows that many parameters have fairly large *p*-values, indicating that one or more of the model effects might not be necessary.

Figure 16.11 Parameter Estimates

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	1.2101	1.7507	Infty	0.69	0.4894
C A	3.4341	1.6131	Infty	2.13	0.0333
C B	2.1638	1.4271	Infty	1.52	0.1295
C C	0.6552	1.0810	Infty	0.61	0.5445
C D	2.4945	1.1094	Infty	2.25	0.0245
C E	3.2449	1.4321	Infty	2.27	0.0235
C F	3.6054	1.3070	Infty	2.76	0.0058
C G	2.0841	1.1898	Infty	1.75	0.0798
C H	2.9368	1.2939	Infty	2.27	0.0232
C I	1.3785	1.0319	Infty	1.34	0.1816
C J	0	.	.	.	.
x1	0.03218	0.05710	Infty	0.56	0.5730
x2	−0.3677	0.1538	Infty	−2.39	0.0168
x3	0.3146	0.3574	Infty	0.88	0.3787
x4	−0.05196	0.02443	Infty	−2.13	0.0334
x5	−0.00683	0.01056	Infty	−0.65	0.5177
x6	0.2539	0.3785	Infty	0.67	0.5024
x7	−0.00723	0.01073	Infty	−0.67	0.5004
x8	2.5370	0.9942	Infty	2.55	0.0107
x9	−0.1675	0.1068	Infty	−1.57	0.1168
x10	−0.2222	0.1577	Infty	−1.41	0.1590

Syntax: HPLOGISTIC Procedure

The following statements are available in the HPLOGISTIC procedure:

PROC HPLOGISTIC < *options* > **;**
CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < / *global-options* > **;**
MODEL *response*< **(***response-options***)** > **=** < *effects* > < / *model-options* > **;**
MODEL *events/trials*< **(***response-options***)** > **=** < *effects* > < / *model-options* > **;**
OUTPUT < **OUT=***SAS-data-set* >
< *keyword* < **=***name* > >. . .
< *keyword* < **=***name* > > < / *options* > **;**
PERFORMANCE *performance-options* **;**
SELECTION *selection-options* **;**
FREQ *variable* **;**
ID *variables* **;**
WEIGHT *variable* **;**

The PROC HPLOGISTIC statement and at least one MODEL statement is required. The CLASS statement can appear multiple times. If a CLASS statement is specified, it must precede the MODEL statements.

PROC HPLOGISTIC Statement

PROC HPLOGISTIC < *options* > **;**

The PROC HPLOGISTIC statement invokes the procedure. Table 16.1 summarizes the available options in the PROC HPLOGISTIC statement by function. The options are then described fully in alphabetical order.

Table 16.1 PROC HPLOGISTIC Statement Options

Option	Description
Basic Options	
ALPHA=	Specifies a global significance level
DATA=	Specifies the input data set
NAMELEN=	Limits the length of effect names
Options Related to Output	
ITDETAILS	Adds detail information to “Iteration History” table
ITSELECT	Displays the “Iteration History” table with model selection
NOPRINT	Suppresses ODS output
NOCLPRINT	Limits or suppresses the display of class levels
NOITPRINT	Suppresses generation of the iteration history table
NOSTDERR	Suppresses computation of covariance matrix and standard errors

Table 16.1 *continued*

Option	Description
Options Related to Optimization	
ABSCONV=	Tunes the absolute function convergence criterion
ABSFCONV=	Tunes the absolute function difference convergence criterion
ABSGCONV=	Tunes the absolute gradient convergence criterion
FCONV=	Tunes the relative function difference convergence criterion
GCONV=	Tunes the relative gradient convergence criterion
MAXITER=	Chooses the maximum number of iterations in any optimization
MAXFUNC=	Specifies the maximum number of function evaluations in any optimization
MAXTIME=	Specifies the upper limit of CPU time (in seconds) for any optimization
MINITER=	Specifies the minimum number of iterations in any optimization
NORMALIZE=	Specifies whether the objective function is normalized during optimization
TECHNIQUE=	Selects the optimization technique
Tolerances	
SINGCHOL=	Tunes the singularity criterion for Cholesky decompositions
SINGSWEEP=	Tunes the singularity criterion for the sweep operator
SINGULAR=	Tunes the general singularity criterion
User-Defined Formats	
FMTLIBXML=	Specifies the file reference for a format stream

You can specify the following options in the PROC HPLOGISTIC statement.

ABSCONV=*r*

ABSTOL=*r*

specifies an absolute function convergence criterion. For minimization, termination requires $f(\boldsymbol{\psi}^{(k)}) \leq r$, where $\boldsymbol{\psi}$ is the vector of parameters in the optimization and $f(\cdot)$ is the objective function. The default value of r is the negative square root of the largest double-precision value, which serves only as a protection against overflows.

ABSFCONV=*r* **<** *n* **>**

ABSFTOL=*r* **<** *n* **>**

specifies an absolute function difference convergence criterion. For all techniques except NMSIMP, termination requires a small change of the function value in successive iterations:

$$|f(\boldsymbol{\psi}^{(k-1)}) - f(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}(k)$ is defined as the vertex with the lowest function value and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The default value is $r = 0$. The optional integer value n specifies the number of successive iterations for which the criterion must be satisfied before the process can be terminated.

ABSGCONV=*r* **<** *n* **>**

ABSGTOL=*r* **<** *n* **>**

specifies an absolute gradient convergence criterion. Termination requires the maximum absolute gradient element to be small:

$$\max_j |g_j(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $g_j(\cdot)$ is the gradient of the objective function with respect to the jth parameter. This criterion is not used by the NMSIMP technique. The default value is *r*=1E–5. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process can be terminated.

ALPHA=*number*

specifies a global significance level for the construction of confidence intervals. The confidence level is 1–*number*. The value of *number* must be between 0 and 1; the default is 0.05. You can override the global specification with the ALPHA= option in the MODEL statement.

DATA=*SAS-data-set*

names the input SAS data set for PROC HPLOGISTIC to use. The default is the most recently created data set.

If the procedure executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. In that case the procedure reads the data alongside the distributed database. For information about the various execution modes, see the section "SMP and MPP Modes" on page 16; for information about the alongside-the-database model, see the section "Alongside-the-Database Execution" on page 22.

FCONV=*r* **<** *n* **>**

FTOL=*r* **<** *n* **>**

specifies a relative function difference convergence criterion. For all techniques except NMSIMP, termination requires a small relative change of the function value in successive iterations,

$$\frac{|f(\boldsymbol{\psi}^{(k)}) - f(\boldsymbol{\psi}^{(k-1)})|}{|f(\boldsymbol{\psi}^{(k-1)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}^{(k)}$ is defined as the vertex with the lowest function value, and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex.

The default value is *r*=2 × ϵ where ϵ is the machine precision. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process can terminate.

FMTLIBXML=*file-ref*

specifies the file reference for the XML stream that contains the user-defined format definitions. User-defined formats are handled differently in a distributed computing environment than they are in other SAS products. See the section "Working with Formats" on page 27 in Chapter 3, "Shared Concepts and Topics," for details about how to generate a XML stream for your formats.

GCONV=*r* **<** *n* **>**

GTOL=*r* **<** *n* **>**

specifies a relative gradient convergence criterion. For all techniques except CONGRA and NMSIMP, termination requires that the normalized predicted function reduction be small,

$$\frac{\mathbf{g}(\boldsymbol{\psi}^{(k)})'[\mathbf{H}^{(k)}]^{-1}\mathbf{g}(\boldsymbol{\psi}^{(k)})}{|f(\boldsymbol{\psi}^{(k)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, $f(\cdot)$ is the objective function, and $\mathbf{g}(\cdot)$ is the gradient. For the CONGRA technique (where a reliable Hessian estimate $\mathbf{H}$ is not available), the following criterion is used:

$$\frac{\| \mathbf{g}(\boldsymbol{\psi}^{(k)}) \|_2^2 \quad \| \mathbf{s}(\boldsymbol{\psi}^{(k)}) \|_2}{\| \mathbf{g}(\boldsymbol{\psi}^{(k)}) - \mathbf{g}(\boldsymbol{\psi}^{(k-1)}) \|_2 \; |f(\boldsymbol{\psi}^{(k)})|} \leq r$$

This criterion is not used by the NMSIMP technique. The default value is *r*=1E–8. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process can terminate.

ITDETAILS

adds to the "Iteration History" table the current values of the parameter estimates and their gradients. These quantities are reported only for parameters that participate in the optimization. The ITDETAILS option is not available with model selection.

ITSELECT

generates the "Iteration History" table when you perform a model selection.

MAXFUNC=*n*

MAXFU=*n*

specifies the maximum number *n* of function calls in the optimization process. The default values are as follows, depending on the optimization technique:

- TRUREG, NRRIDG, NEWRAP: 125
- QUANEW, DBLDOG: 500
- CONGRA: 1,000
- NMSIMP: 3,000

The optimization can terminate only after completing a full iteration. Therefore, the number of function calls that are actually performed can exceed the number that is specified by the MAXFUNC= option. You can choose the optimization technique with the TECHNIQUE= option.

MAXITER=*n*

MAXIT=*n*

specifies the maximum number *n* of iterations in the optimization process. The default values are as follows, depending on the optimization technique:

- TRUREG, NRRIDG, NEWRAP: 50
- QUANEW, DBLDOG: 200
- CONGRA: 400
- NMSIMP: 1,000

These default values also apply when *n* is specified as a missing value. You can choose the optimization technique with the TECHNIQUE= option.

MAXTIME=*r*

specifies an upper limit of *r* seconds of CPU time for the optimization process. The default value is the largest floating-point double representation of your computer. The time specified by the MAXTIME= option is checked only once at the end of each iteration. Therefore, the actual running time can be longer than that specified by the MAXTIME= option.

MINITER=*n*

MINIT=*n*

specifies the minimum number of iterations. The default value is 0. If you request more iterations than are actually needed for convergence to a stationary point, the optimization algorithms can behave strangely. For example, the effect of rounding errors can prevent the algorithm from continuing for the required number of iterations.

NAMELEN=*number*

specifies the length to which long effect names are shortened. The default and minimum value is 20.

NOCLPRINT< =*number* **>**

suppresses the display of the "Class Level Information" table if you do not specify *number*. If you specify *number*, the values of the classification variables are displayed for only those variables whose number of levels is less than *number*. Specifying a *number* helps to reduce the size of the "Class Level Information" table if some classification variables have a large number of levels.

NOITPRINT

suppresses the generation of the "Iteration History" table.

NOPRINT

suppresses the generation of ODS output.

NORMALIZE=YES | NO

specifies whether the objective function should be normalized during the optimization by the reciprocal of the used frequency count. The default is to normalize the objective function. This option affects the values reported in the "Iteration History" table. The results reported in the "Fit Statistics" are always displayed for the nonnormalized log-likelihood function.

NOSTDERR
suppresses the computation of the covariance matrix and the standard errors of the logistic regression coefficients. When the model contains many variables (thousands), the inversion of the Hessian matrix to derive the covariance matrix and the standard errors of the regression coefficients can be time-consuming.

SINGCHOL=*number*
tunes the singularity criterion in Cholesky decompositions. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

SINGSWEEP=*number*
tunes the singularity criterion for sweep operations. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

SINGULAR=*number*
tunes the general singularity criterion applied by the HPLOGISTIC procedure in sweeps and inversions. The default is 1E4 times the machine epsilon; this product is approximately 1E–12 on most computers.

TECHNIQUE=*keyword*
TECH=*keyword*
specifies the optimization technique for obtaining maximum likelihood estimates. You can choose from the following techniques by specifying the appropriate *keyword*:

CONGRA	performs a conjugate-gradient optimization.
DBLDOG	performs a version of double-dogleg optimization.
NEWRAP	performs a Newton-Raphson optimization with line search.
NMSIMP	performs a Nelder-Mead simplex optimization.
NONE	performs no optimization.
NRRIDG	performs a Newton-Raphson optimization with ridging.
QUANEW	performs a dual quasi-Newton optimization.
TRUREG	performs a trust-region optimization

The default value is TECHNIQUE=NRRIDG.

For more information, see the section "Choosing an Optimization Algorithm" on page 348.

CLASS Statement

CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < / *global-options* > **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. The CLASS statement must precede the MODEL statement. You can list the response variable for binary and multinomial models in the CLASS statement, but this is not necessary.

The CLASS statement for High-Performance Analytics procedures is documented in the section "CLASS Statement" on page 28 of Chapter 3, "Shared Concepts and Topics."

The HPLOGISTIC procedure does not support the SPLIT option in the CLASS statement. The HPLOGISTIC procedure additionally supports the following global-option in the CLASS statement:

UPCASE
uppercases the values of character-valued CLASS variables before levelizing them. For example, if the UPCASE option is in effect and a CLASS variable can take the values 'a', 'A', and 'b', then 'a' and 'A' represent the same level and the CLASS variable is treated as having only two values: 'A' and 'B'.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. High-Performance Analytics procedures that support the FREQ statement treat each observation as if it appeared f times, where the frequency value f is the value of the FREQ variable for the observation. If f is not an integer, then f is truncated to an integer. If f is less than 1 or missing, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

ID Statement

ID *variables* **;**

The ID statement lists one or more variables from the input data set that are to be transferred to output data sets created by High-Performance Analytics procedures, provided that the output data set produces one (or more) records per input observation.

For documentation about the common ID statement in High-Performance Analytics procedures, see the section "ID Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

MODEL Statement

MODEL *response* < **(***response-options***)** > **=** < *effects* > < / *model-options* > **;**

MODEL *events* / *trials* < **(***response-options***)** > **=** < *effects* > < / *model-options* > **;**

The MODEL statement defines the statistical model in terms of a response variable (the target) or an *events/trials* specification, model effects constructed from variables in the input data set, and options. An intercept is included in the model by default. You can remove the intercept with the NOINT option.

You can specify a single *response* variable that contains your binary, ordinal, or nominal response values. When you have binomial data, you can specify the *events/trials* form of the response, where one variable contains the number of positive responses (or events) and another variable contains the number of trials. Note that the values of both *events* and (*trials* – *events*) must be nonnegative and the value of *trials* must be positive.

For information about constructing the model effects, see the section "Specification and Parameterization of Model Effects" on page 44 of Chapter 3, "Shared Concepts and Topics."

There are two sets of options in the MODEL statement. The *response-options* determine how the HPLOGISTIC procedure models probabilities for binary data. The *model-options* control other aspects of model formation and inference. Table 16.2 summarizes these options.

Table 16.2 MODEL Statement Options

Option	Description
Response Variable Options	
DESCENDING	Reverses the response categories
EVENT=	Specifies the event category
ORDER=	Specifies the sort order
REF=	Specifies the reference category
Model Options	
ALPHA=	Specifies the confidence level for confidence limits
CL	Requests confidence limits
DDFM=	Specifies the degrees-of-freedom method
INCLUDE=	Includes effects in all models for model selection
LACKFIT	Requests the Hosmer and Lemeshow goodness-of-fit test
LINK=	Specifies the link function
NOINT	Suppresses the intercept
OFFSET=	Specifies the offset variable
RSQUARE	Requests a generalized coefficient of determination
START=	Includes effects in the initial model for model selection

Response Variable Options

Response variable options determine how the HPLOGISTIC procedure models probabilities for binary and multinomial data.

You can specify the following *response-options* by enclosing them in parentheses after the *response* or *trials* variable.

DESCENDING

DESC

reverses the order of the response categories. If both the DESCENDING and ORDER= options are specified, PROC HPLOGISTIC orders the response categories according to the ORDER= option and then reverses that order.

EVENT='*category***' | FIRST | LAST**

specifies the event category for the binary response model. PROC HPLOGISTIC models the probability of the event category. The EVENT= option has no effect when there are more than two response categories.

You can specify the value (formatted, if a format is applied) of the event category in quotes, or you can specify one of the following:

FIRST

designates the first ordered category as the event. This is the default.

LAST

designates the last ordered category as the event.

For example, the following statements specify that observations with formatted value '1' represent events in the data. The probability modeled by the HPLOGISTIC procedure is thus the probability that the variable def takes on the (formatted) value '1'.

```
proc hplogistic data=MyData;
   class A B C;
   model def(event ='1') = A B C x1 x2 x3;
run;
```

ORDER=DATA | FORMATTED | INTERNAL

ORDER=FREQ | FREQDATA | FREQFORMATTED | FREQINTERNAL

specifies the sort order for the levels of the *response* variable. When ORDER=FORMATTED (the default) for numeric variables for which you have supplied no explicit format (that is, for which there is no corresponding FORMAT statement in the current PROC HPLOGISTIC run or in the DATA step that created the data set), the levels are ordered by their internal (numeric) value. The following table shows the interpretation of the ORDER= option:

ORDER=	Levels Sorted By
DATA	Order of appearance in the input data set
FORMATTED	External formatted value, except for numeric variables with no explicit format, which are sorted by their unformatted (internal) value
FREQ	Descending frequency count (levels with the most observations come first in the order)

Table 16.2 *continued*

ORDER=	Levels Sorted By
FREQDATA	Order of descending frequency count; within counts by order of appearance in the input data set when counts are tied
FREQFORMATTED	Order of descending frequency count; within counts by formatted value (as above) when counts are tied
FREQINTERNAL	Order of descending frequency count; within counts by unformatted value when counts are tied
INTERNAL	Unformatted value

By default, ORDER=FORMATTED. For the FORMATTED and INTERNAL orders, the sort order is machine-dependent.

For more information about sort order, see the chapter on the SORT procedure in the *Base SAS Procedures Guide* and the discussion of BY-group processing in *SAS Language Reference: Concepts*.

REF='*category***' | FIRST | LAST**
specifies the reference category for the generalized logit model and the binary response model. For the generalized logit model, each logit contrasts a nonreference category with the reference category. For the binary response model, specifying one response category as the reference is the same as specifying the other response category as the event category. You can specify the value (formatted if a format is applied) of the reference category in quotes, or you can specify one of the following:

FIRST
designates the first ordered category as the reference

LAST
designates the last ordered category as the reference. This is the default.

Model Options

ALPHA=*number*
requests that confidence intervals for each of the parameters be constructed with confidence level 1–*number*. The value of *number* must be between 0 and 1; the default is 0.05.

CL
requests that confidence limits be constructed for each of the parameter estimates. The confidence level is 0.95 by default; this can be changed with the ALPHA= option.

DDFM=RESIDUAL | NONE
specifies how degrees of freedom for statistical inference be determined in the "Parameter Estimates Table."

The HPLOGISTIC procedure always displays the statistical tests and confidence intervals in the "Parameter Estimates" tables in terms of a t test and a two-sided probability from a t distribution. With the DDFM= option, you can control the degrees of freedom of this t distribution and thereby switch

between small-sample inference and large-sample inference based on the normal or chi-square distribution.

The default is DDFM=NONE, which leads to z-based statistical tests and confidence intervals. The HPLOGISTIC procedure then displays the degrees of freedom in the DF column as Infty, the p-values are identical to those from a Wald chi-square test, and the square of the t value equals the Wald chi-square statistic.

If you specify DDFM=RESIDUAL, the degrees of freedom are finite and determined by the number of usable frequencies (observations) minus the number of nonredundant model parameters. This leads to t-based statistical tests and confidence intervals. If the number of frequencies is large relative to the number of parameters, the inferences from the two degrees-of-freedom methods are almost identical.

INCLUDE=*n*

INCLUDE=*single-effect*

INCLUDE=(*effects***)**

forces effects to be included in all models. If you specify INCLUDE=*n*, then the first *n* effects that are listed in the MODEL statement are included in all models. If you specify INCLUDE=*single-effect* or if you specify a list of effects within parentheses, then the specified effects are forced into all models. The effects that you specify in the INCLUDE= option must be explanatory effects that are specified in the MODEL statement before the slash (*/*).

LACKFIT< (DFREDUCE=*r* **NGROUPS=***G***) >**

performs the Hosmer and Lemeshow goodness-of-fit test (Hosmer and Lemeshow 2000) for binary response models.

The subjects are divided into at most *G* groups of roughly the same size, based on the percentiles of the estimated probabilities. You can specify *G* as any integer greater than or equal to 5; by default, *G*=10. Let the actual number of groups created be g. The discrepancies between the observed and expected number of observations in these g groups are summarized by the Pearson chi-square statistic, which is then compared to a chi-square distribution with g–*r* degrees of freedom. You can specify a nonnegative integer *r* that satisfies $g–r \geq 1$; by default, *r*=2.

A small p-value suggests that the fitted model is not an adequate model. See the section "The Hosmer-Lemeshow Goodness-of-Fit Test" on page 346 for more information.

LINK=*keyword*

specifies the link function for the model. The *keywords* and the associated link functions are shown in Table 16.3.

Table 16.3 Built-in Link Functions of the HPLOGISTIC Procedure

LINK=	Link Function	$g(\mu) = \eta =$
CLOGLOG | CLL	Complementary log-log	$\log(-\log(1-\mu))$
GLOGIT | GENLOGIT	Generalized logit	
LOGIT	Logit	$\log(\mu/(1-\mu))$
LOGLOG	Log-log	$-\log(-\log(\mu))$
PROBIT	Probit	$\Phi^{-1}(\mu)$

For the probit and cumulative probit links, $\Phi^{-1}(\cdot)$ denotes the quantile function of the standard normal distribution.

If the response variable has more than two categories, the HPLOGISTIC procedure fits a model with a cumulative link function based on the specified link. However, if you specify LINK=GLOGIT, the procedure assumes a generalized logit model for nominal (unordered) data, regardless of the number of response categories.

NOINT
requests that no intercept be included in the model. An intercept is included by default. The NOINT option is not available in multinomial models.

OFFSET=*variable*
specifies a *variable* to be used as an offset to the linear predictor. An offset plays the role of an effect whose coefficient is known to be 1. The offset variable cannot appear in the CLASS statement or elsewhere in the MODEL statement. Observations with missing values for the offset variable are excluded from the analysis.

RSQUARE
R2
requests a generalized coefficient of determination (R square, R^2) and a scaled version thereof for the fitted model. The results are added to the "Fit Statistics" table. For more information about the computation of these measures, see the section "Generalized Coefficient of Determination" on page 345.

START=*n*
START=*single-effect*
START=(*effects***)**
begins the selection process from the designated initial model for the FORWARD and STEPWISE selection methods. If you specify START=*n*, then the starting model includes the first *n* effects that are listed in the MODEL statement. If you specify START=*single-effect* or if you specify a list of effects within parentheses, then the starting model includes those specified effects. The effects that you specify in the START= option must be explanatory effects that are specified in the MODEL statement before the slash (/). The START= option is not available when you specify METHOD=BACKWARD in the SELECTION statement.

OUTPUT Statement

OUTPUT < **OUT=***SAS-data-set* >
< *keyword* < =*name* > > . . . < *keyword* < =*name* > > < / *options* > **;**

The OUTPUT statement creates a data set that contains observationwise statistics that are computed after fitting the model. The variables in the input data set are *not* included in the output data set to avoid data duplication for large data sets; however, variables specified in the ID statement are included.

If the input data are in distributed form, where access of data in a particular order cannot be guaranteed, the HPLOGISTIC procedure copies the distribution or partition key to the output data set so that its contents can be joined with the input data.

The output statistics are computed based on the final parameter estimates. If the model fit does not converge, missing values are produced for the quantities that depend on the estimates.

When there are more than two response levels, only variables named by the XBETA and PREDICTED keywords have their values computed; the other variables have missing values. These statistics are computed for every response category, and the automatic variable _LEVEL_ identifies the response category upon which the computed values are based. If you also specify the OBSCAT option, then the observationwise statistics are computed only for the observed response category, as indicated by the value of the _LEVEL_ variable.

For observations in which only the response variable is missing, values of the XBETA and PREDICTED statistics are computed even though these observations do not affect the model fit. This enables, for instance, predicted probabilities to be computed for new observations.

You can specify the following syntax elements in the OUTPUT statement before the slash (/).

OUT=*SAS-data-set*

DATA=*SAS-data-set*

specifies the name of the output data set. If the OUT= (or DATA=) option is omitted, the procedure uses the DATA*n* convention to name the output data set.

keyword **<** **=***name* **>**

specifies a statistic to include in the output data set and optionally names the variable *name*. If you do not provide a *name*, the HPLOGISTIC procedure assigns a default name based on the type of statistic requested.

The following are valid *keywords* for adding statistics to the OUTPUT data set:

LINP | XBETA

requests the linear predictor $\eta = \mathbf{x}'\boldsymbol{\beta}$.

PREDICTED | PRED | P

requests predicted values (predicted probabilities of events) for the response variable.

RESIDUAL | RESID | R

requests the raw residual, $y - \mu$, where μ is the estimate of the predicted event probability. This statistic is not computed for multinomial models.

PEARSON | PEARS | RESCHI

requests the Pearson residual, $\frac{\sqrt{wn}(y/n-\mu)}{\sqrt{\mu(1-\mu)}}$, where μ is the estimate of the predicted event probability, w is the weight of the observation, and n is the number of binomial trials (n=1 for binary observations). This statistic is not computed for multinomial models.

You can specify the following *option* in the OUTPUT statement after the slash (/):

OBSCAT

requests (for multinomial models) that observationwise statistics be produced for the response level only. If the OBSCAT option is not specified and the response variable has J levels, then the following outputs are created: for cumulative link models, $J - 1$ records are output for every observation in the input data that corresponds to the $J - 1$ lower-ordered response categories; for generalized logit models, J records are output that correspond to all J response categories.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPLOGISTIC procedure.

With the PERFORMANCE statement you can also control whether the HPLOGISTIC procedure executes in SMP or MPP mode.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SELECTION Statement

SELECTION < *options* > **;**

The SELECTION statement performs model selection by examining whether effects should be added to or removed from the model according to rules defined by model selection methods. The statement is fully documented in the section "SELECTION Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

The HPLOGISTIC procedure supports the following effect-selection methods in the SELECTION statement:

METHOD=NONE	results in no model selection. This method fits the full model.
METHOD=FORWARD	performs forward selection. This method starts with no effects in the model and adds effects.
METHOD=BACKWARD	performs backward elimination. This method starts with all effects in the model and deletes effects.
METHOD=BACKWARD(FAST)	performs fast backward elimination. This method starts with all effects in the model and deletes effects without refitting the model.
METHOD=STEPWISE	performs stepwise regression. This method is similar to the FORWARD method except that effects already in the model do not necessarily stay there.

The only effect-selection criterion supported by the HPLOGISTIC procedure is SELECT=SL, where effects enter and leave the model based on an evaluation of the significance level. To determine this level of significance for each candidate effect, the HPLOGISTIC procedure calculates an approximate chi-square score test statistic.

The criteria available for the CHOOSE= and STOP= options in the SELECT statement are

SL	the significance level of the score test
AIC	Akaike's information criterion (Akaike 1974)
AICC	a small-sample bias corrected version of Akaike's information criterion as promoted in, for example, Hurvich and Tsai (1989) and Burnham and Anderson (1998)
BIC | SBC	Schwarz' Bayesian criterion (Schwarz 1978)

The calculation of the information criteria uses the following formulas, where p denotes the number of effective parameters in the candidate model, f denotes the number of frequencies used, and l is the log likelihood evaluated at the converged estimates:

$$\begin{aligned}
\text{AIC} &= -2l + 2p \\
\text{AICC} &= \begin{cases} -2l + 2pf/(f-p-1) & \text{when } f > p+2 \\ -2l + 2p(p+2) & \text{otherwise} \end{cases} \\
\text{BIC} &= -2l + p\log(f)
\end{aligned}$$

NOTE: If you use the fast backward elimination method, the –2 log likelihood, AIC, AICC, and BIC statistics are approximated at each step where the model is not refit, and hence do not match the values computed when that model is fit outside of the selection routine.

When you specify the DETAILS= option in the SELECTION statement, the HPLOGISTIC procedure produces the following:

DETAILS=SUMMARY	produces a summary table that shows the effect added or removed at each step along with the p-value. The summary table is produced by default if the DETAILS= option is not specified.
DETAILS=STEPS	produces a detailed listing of all candidates at each step and their ranking in terms of the significance level for entry into or removal from the model.
DETAILS=ALL	produces the preceding two tables and a table of selection details which displays fit statistics for the model at each step of the selection process and the approximate chi-square score statistic.

WEIGHT Statement

WEIGHT *variable* **;**

The *variable* in the WEIGHT statement is used as a weight to perform a weighted analysis of the data. Observations with nonpositive or missing weights are not included in the analysis. If a WEIGHT statement is not included, then all observations used in the analysis are assigned a weight of 1.

Details: HPLOGISTIC Procedure

Missing Values

Any observation with missing values for the response, frequency, weight, offset, or explanatory variables is excluded from the analysis; however, missing values are valid for response and explanatory variables that are specified with the MISSING option in the CLASS statement. Observations with a nonpositive weight or with a frequency less than 1 are also excluded.

The estimated linear predictor and the fitted probabilities are not computed for any observation that has missing offset or explanatory variable values. However, if only the response value is missing, the linear predictor and the fitted probabilities can be computed and output to a data set by using the OUTPUT statement.

Response Distributions

The response distribution is the probability distribution of the response (target) variable. The HPLOGISTIC procedure can fit data for the following distributions:

- binary distribution
- binomial distribution
- multinomial distribution

The expressions for the log-likelihood functions of these distributions are given in the next section.

The binary (or Bernoulli) distribution is the elementary distribution of a discrete random variable that can take on two values with probabilities p and $1 - p$. Suppose the random variable is denoted Y and

$$\Pr(Y = 1) = p$$
$$\Pr(Y = 0) = 1 - p$$

The value associated with probability p is often termed the *event* or "success"; the complementary event is termed the *non-event* or "failure." A Bernoulli experiment is a random draw from a binary distribution and generates events with probability p.

If $Y_1, \cdots, Y_n$ are n independent Bernoulli random variables, then their sum follows a binomial distribution. In other words, if $Y_i = 1$ denotes an event (success) in the ith Bernoulli trial, a binomial random variable is the number of events (successes) in n independent Bernoulli trials. If you use the events/trials syntax in the MODEL statement, the HPLOGISTIC procedure fits the model as if the data had arisen from a binomial distribution. For example, the following statements fit a binomial regression model with regressors `x1` and `x2`. The variables `e` and `t` represent the events and trials for the binomial distribution:

```
proc hplogistic;
   model e/t = x1 x2;
run;
```

If the events/trials syntax is used, then both variables must be numeric and the value of the events variable cannot be less than 0 or exceed the value of the trials variable. A "Response Profile" table is not produced for binomial data, since the response variable is not subject to levelization.

The multinomial distribution is a generalization of the binary distribution and allows for more than two outcome categories. Because there are more than two possible outcomes for the multinomial distribution, the terminology of "successes," "failures," "events," and "non-events" no longer applies. With multinomial data, these outcomes are generically referred to as "categories" or levels.

Whenever the HPLOGISTIC procedure determines that the response variable has more than two levels (unless the events/trials syntax is used), the procedure fits the model as if the data had arisen from a multinomial distribution. By default, it is then assumed that the response categories are ordered and a cumulative link model is fit by applying the default or specified link function. If the response categories are unordered, then you should fit a generalized logit model by choosing LINK=GLOGIT in the MODEL statement.

Log-Likelihood Functions

The HPLOGISTIC procedure forms the log-likelihood functions of the various models as

$$L(\boldsymbol{\mu};\mathbf{y}) = \sum_{i=1}^{n} f_i\, l(\mu_i; y_i, w_i)$$

where $l(\mu_i; y_i, w_i)$ is the log-likelihood contribution of the ith observation with weight w_i and f_i is the value of the frequency variable. For the determination of w_i and f_i, see the WEIGHT and FREQ statements. The individual log-likelihood contributions for the various distributions are as follows.

Binary Distribution

The HPLOGISTIC procedure computes the log-likelihood function $l(\mu_i(\boldsymbol{\beta}); y_i)$ for the ith binary observation as

$$\begin{aligned} \eta_i &= \mathbf{x}_i'\boldsymbol{\beta} \\ \mu_i(\boldsymbol{\beta}) &= g^{-1}(\eta_i) \\ l(\mu_i(\boldsymbol{\beta}); y_i) &= y_i \log\{\mu_i\} + (1-y_i)\log\{1-\mu_i\} \end{aligned}$$

Here, μ_i is the probability of an event, and the variable y_i takes on the value 1 for an event and the value 0 for a non-event. The inverse link function $g^{-1}(\cdot)$ maps from the scale of the linear predictor η_i to the scale of the mean. For example, for the logit link (the default),

$$\mu_i(\boldsymbol{\beta}) = \frac{\exp\{\eta_i\}}{1+\exp\{\eta_i\}}$$

You can control which binary outcome in your data is modeled as the event with the *response-options* in the MODEL statement, and you can choose the link function with the LINK= option in the MODEL statement.

If a WEIGHT statement is given and w_i denotes the weight for the current observation, the log-likelihood function is computed as

$$l(\mu_i(\boldsymbol{\beta}); y_i, w_i) = w_i\, l(\mu_i(\boldsymbol{\beta}); y_i)$$

Binomial Distribution

The HPLOGISTIC procedure computes the log-likelihood function $l(\mu_i(\boldsymbol{\beta}); y_i)$ for the ith binomial observation as

$$\begin{aligned} \eta_i &= \mathbf{x}_i'\boldsymbol{\beta} \\ \mu_i(\boldsymbol{\beta}) &= g^{-1}(\eta_i) \\ l(\mu_i(\boldsymbol{\beta}); y_i, w_i) &= w_i\,(y_i \log\{\mu_i\} + (n_i - y_i)\log\{1-\mu_i\}) \\ &\quad + w_i\,(\log\{\Gamma(n_i+1)\} - \log\{\Gamma(y_i+1)\} - \log\{\Gamma(n_i-y_i+1)\}) \end{aligned}$$

where y_i and n_i are the values of the events and trials of the ith observation, respectively. μ_i measures the probability of events (successes) in the underlying Bernoulli distribution whose aggregate follows the binomial distribution.

Multinomial Distribution

The multinomial distribution modeled by the HPLOGISTIC procedure is a generalization of the binary distribution; it is the distribution of a single draw from a discrete distribution with J possible values. The log-likelihood function for the ith observation is thus deceptively simple:

$$l(\boldsymbol{\mu}_i; \mathbf{y}_i, w_i) = w_i \sum_{j=1}^{J} y_{ij} \log\{\mu_{ij}\}$$

In this expression, J denotes the number of response categories (the number of possible outcomes) and μ_{ij} is the probability that the ith observation takes on the response value associated with category j. The category probabilities must satisfy

$$\sum_{j=1}^{J} \mu_j = 1$$

and the constraint is satisfied by modeling $J-1$ categories. In models with ordered response categories, the probabilities are expressed in cumulative form, so that the last category is redundant. In generalized logit models (multinomial models with unordered categories), one category is chosen as the reference category and the linear predictor in the reference category is set to zero.

Generalized Coefficient of Determination

The goal of a coefficient of determination, also known as an R-square measure, is to express the agreement between a stipulated model and the data in terms of variation in the data explained by the model. In linear models, the R-square measure is based on residual sums of squares; because these are additive, a measure bounded between 0 and 1 is easily derived.

In more general models where parameters are estimated by the maximum likelihood principle, Cox and Snell (1989, pp. 208–209) and Magee (1990) proposed the following generalization of the coefficient of determination:

$$R^2 = 1 - \left\{ \frac{L(\mathbf{0})}{L(\widehat{\boldsymbol{\beta}})} \right\}^{\frac{2}{n}}$$

Here, $L(\mathbf{0})$ is the likelihood of the intercept-only model, $L(\widehat{\boldsymbol{\beta}})$ is the likelihood of the specified model, and n denotes the number of observations used in the analysis. This number is adjusted for frequencies if a FREQ statement is present and is based on the trials variable for binomial models.

As discussed in Nagelkerke (1991), this generalized R-square measure has properties similar to the coefficient of determination in linear models. If the model effects do not contribute to the analysis, $L(\widehat{\boldsymbol{\beta}})$ approaches $L(\mathbf{0})$ and R^2 approaches zero.

However, R^2 does not have an upper limit of 1. Nagelkerke suggested a rescaled generalized coefficient of determination that achieves an upper limit of 1, by dividing R^2 by its maximum value,

$$R^2_{\max} = 1 - \{L(\mathbf{0})\}^{\frac{2}{n}}$$

If you specify the RSQUARE option in the MODEL statement, the HPLOGISTIC procedure computes R^2 and the rescaled coefficient of determination according to Nagelkerke:

$$\tilde{R}^2 = \frac{R^2}{R^2_{\max}}$$

The R^2 and $\tilde{R}^2$ measures are most useful for comparing competing models that are not necessarily nested—that is, models that cannot be reduced to one another by simple constraints on the parameter space. Larger values of the measures indicate better models.

The Hosmer-Lemeshow Goodness-of-Fit Test

To evaluate the fit of the model, Hosmer and Lemeshow (2000) proposed a statistic that they show, through simulation, is distributed as chi-square when there is no replication in any of the subpopulations. This goodness-of-fit test is available only for binary response models.

The unit interval is partitioned into 2,000 equal-sized bins, and each observation i is placed into the bin that contains its estimated event probability. This effectively sorts the observations in increasing order of their estimated event probability.

The observations (and frequencies) are further combined into G groups. By default G=10, but you can specify $G \geq 5$ with the NGROUPS= suboption of the LACKFIT option in the MODEL statement. Let F be the total frequency. The target frequency for each group is $T = \lfloor F/G + 0.5 \rfloor$, which is the integer part of $F/G + 0.5$. Load the first group ($g_j, j = 1$) with the first of the 2,000 bins that has nonzero frequency f_1, and let the next nonzero bin have a frequency of f. PROC HPLOGISTIC performs the following steps for each nonzero bin to create the groups:

1. If $j = G$, then add this bin to group g_j.
2. Otherwise, if $f_j < T$ and $f_j + \lfloor f/2 \rfloor \leq T$, then add this bin to group g_j.
3. Otherwise, start loading the next group (g_{j+1}) with $f_{j+1} = f$, and set $j = j + 1$.

If the final group g_j has frequency $f_j < T/2$, then add these observations to the preceding group. The total number of groups actually created, g, can be less than G.

The Hosmer-Lemeshow goodness-of-fit statistic is obtained by calculating the Pearson chi-square statistic from the $2 \times g$ table of observed and expected frequencies. The statistic is written

$$\chi^2_{HL} = \sum_{j=1}^{g} \frac{(O_j - F_j \bar{\pi}_j)^2}{F_j \bar{\pi}_j (1 - \bar{\pi}_j)}$$

where, for the jth group g_j, $F_j = \sum_{i \in g_j} f_i$ is the total frequency of subjects, O_j is the total frequency of event outcomes, and $\bar{\pi}_j = \sum_{i \in g_j} f_i \widehat{p}_i / F_j$ is the average estimated predicted probability of an event outcome. Let ϵ be the square root of the machine epsilon divided by 4,000, which is about 2.5E–12. Any $\bar{\pi}_j < \epsilon$ is set to ϵ; similarly, any $\bar{\pi}_j > 1 - \epsilon$ is set to $1 - \epsilon$.

The Hosmer-Lemeshow statistic is compared to a chi-square distribution with $g - r$ degrees of freedom. You can specify r with the DFREDUCE= suboption of the LACKFIT option in the MODEL statement. By default, $r = 2$, and to compute the Hosmer-Lemeshow statistic you must have $g - r \geq 1$. Large values of χ^2_{HL} (and small p-values) indicate a lack of fit of the model.

Computational Method: Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPLOGISTIC procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statement, the HPLOGISTIC procedure determines threading as if it executed on a system with four CPUs, regardless of the actual CPU count:

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to control the number of threads. This specification overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement, which overrides the CPUCOUNT system option and instructs the HPLOGISTIC procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Dimensions" table, which is part of the default output. The HPLOGISTIC procedure allocates one thread per CPU by default.

The tasks that are multithreaded by the HPLOGISTIC procedure are primarily defined by dividing the data processed on a single machine among the threads—that is, the HPLOGISTIC procedure implements multithreading through a data-parallel model. For example, if the input data set has 1,000 observations and you are running with four threads, then 250 observations are associated with each thread. All operations that require access to the data are then multithreaded. These operations include the following:

- variable levelization
- effect levelization
- formation of the initial crossproducts matrix
- formation of approximate Hessian matrices for candidate evaluation during model selection
- objective function calculation
- gradient calculation
- Hessian calculation
- scoring of observations

In addition, operations on matrices such as sweeps can be multithreaded provided that the matrices are of sufficient size to realize performance benefits from managing multiple threads for the particular matrix operation.

Choosing an Optimization Algorithm

First- or Second-Order Algorithms

The factors that go into choosing a particular optimization technique for a particular problem are complex. Trial and error can be involved.

For many optimization problems, computing the gradient takes more computer time than computing the function value. Computing the Hessian sometimes takes *much* more computer time and memory than computing the gradient, especially when there are many decision variables. Unfortunately, optimization techniques that do not use some kind of Hessian approximation usually require many more iterations than techniques that do use a Hessian matrix, and, as a result the total run time of these techniques is often longer. Techniques that do not use the Hessian also tend to be less reliable. For example, they can terminate more easily at stationary points than at global optima.

Table 16.4 shows which derivatives are required for each optimization technique.

Table 16.4 Derivatives Required

Algorithm	First-Order	Second-Order
TRUREG	x	x
NEWRAP	x	x
NRRIDG	x	x
QUANEW	x	-
DBLDOG	x	-
CONGRA	x	-
NMSIMP	-	-

The second-derivative methods TRUREG, NEWRAP, and NRRIDG are best for small problems for which the Hessian matrix is not expensive to compute. Sometimes the NRRIDG algorithm can be faster than the TRUREG algorithm, but TRUREG can be more stable. The NRRIDG algorithm requires only one matrix with $p(p+1)/2$ double words; TRUREG and NEWRAP require two such matrices. Here, p denotes the number of parameters in the optimization.

The first-derivative methods QUANEW and DBLDOG are best for medium-sized problems for which the objective function and the gradient can be evaluated much faster than the Hessian. In general, the QUANEW and DBLDOG algorithms require more iterations than TRUREG, NRRIDG, and NEWRAP, but each iteration can be much faster. The QUANEW and DBLDOG algorithms require only the gradient to update an approximate Hessian, and they require slightly less memory than TRUREG or NEWRAP.

The first-derivative method CONGRA is best for large problems for which the objective function and the gradient can be computed much faster than the Hessian and for which too much memory is required to store the (approximate) Hessian. In general, the CONGRA algorithm requires more iterations than QUANEW or DBLDOG, but each iteration can be much faster. Because CONGRA requires only a factor of p double-word memory, many large applications can be solved only by CONGRA.

The no-derivative method NMSIMP is best for small problems for which derivatives are not continuous or are very difficult to compute.

Each optimization method uses one or more convergence criteria that determine when it has converged. An algorithm is considered to have converged when any one of the convergence criteria is satisfied. For example, under the default settings, the QUANEW algorithm converges if ABSGCONV <1E–5, FCONV $< 2 \times \epsilon$, or GCONV <1E–8.

By default, the HPLOGISTIC procedure applies the NRRIDG algorithm because it can take advantage of multithreading in Hessian computations and inversions. If the number of parameters becomes large, specifying the TECHNIQUE=QUANEW option, which is a first-order method with good overall properties, is recommended.

Algorithm Descriptions

The following subsections provide details about each optimization technique and follow the same order as Table 16.4.

Trust Region Optimization (TRUREG)

The trust region method uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function $f(\boldsymbol{\psi})$ have continuous first- and second-order derivatives inside the feasible region.

The trust region method iteratively optimizes a quadratic approximation to the nonlinear objective function within a hyperelliptic trust region with radius Δ that constrains the step size that corresponds to the quality of the quadratic approximation. The trust region method is implemented based on Dennis, Gay, and Welsch (1981), Gay (1983), and Moré and Sorensen (1983).

The trust region method performs well for small- to medium-sized problems, and it does not need many function, gradient, and Hessian calls. However, if the computation of the Hessian matrix is computationally expensive, one of the dual quasi-Newton or conjugate gradient algorithms might be more efficient.

Newton-Raphson Optimization with Line Search (NEWRAP)

The NEWRAP technique uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function have continuous first- and second-order derivatives inside the feasible region. If second-order derivatives are computed efficiently and precisely, the NEWRAP method can perform well for medium-sized to large problems, and it does not need many function, gradient, and Hessian calls.

This algorithm uses a pure Newton step when the Hessian is positive-definite and when the Newton step reduces the value of the objective function successfully. Otherwise, a combination of ridging and line search is performed to compute successful steps. If the Hessian is not positive-definite, a multiple of the identity matrix is added to the Hessian matrix to make it positive-definite (Eskow and Schnabel 1991).

In each iteration, a line search is performed along the search direction to find an approximate optimum of the objective function. The line-search method uses quadratic interpolation and cubic extrapolation.

Newton-Raphson Ridge Optimization (NRRIDG)

The NRRIDG technique uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function have continuous first- and second-order derivatives inside the feasible region.

This algorithm uses a pure Newton step when the Hessian is positive-definite and when the Newton step reduces the value of the objective function successfully. If at least one of these two conditions is not satisfied, a multiple of the identity matrix is added to the Hessian matrix.

Because the NRRIDG technique uses an orthogonal decomposition of the approximate Hessian, each iteration of NRRIDG can be slower than that of the NEWRAP technique, which works with a Cholesky decomposition. However, NRRIDG usually requires fewer iterations than NEWRAP.

The NRRIDG method performs well for small- to medium-sized problems, and it does not require many function, gradient, and Hessian calls. However, if the computation of the Hessian matrix is computationally expensive, one of the dual quasi-Newton or conjugate gradient algorithms might be more efficient.

Quasi-Newton Optimization (QUANEW)

The dual quasi-Newton method uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$, and it does not need to compute second-order derivatives because they are approximated. It works well for medium-sized to moderately large optimization problems, where the objective function and the gradient can be computed much faster than the Hessian. However, in general the QUANEW technique requires more iterations than the TRUREG, NEWRAP, and NRRIDG techniques, which compute second-order derivatives. The QUANEW technique provides an appropriate balance between the speed and stability required for most nonlinear mixed model applications.

The QUANEW technique implemented by the HPLOGISTIC procedure is the dual quasi-Newton algorithm, which updates the Cholesky factor of an approximate Hessian.

In each iteration, a line search is performed along the search direction to find an approximate optimum. The line-search method uses quadratic interpolation and cubic extrapolation to obtain a step size α that satisfies the Goldstein conditions (Fletcher 1987). One of the Goldstein conditions can be violated if the feasible region defines an upper limit of the step size. Violating the left-side Goldstein condition can affect the positive-definiteness of the quasi-Newton update. In that case, either the update is skipped or the iterations are restarted with an identity matrix, resulting in the steepest descent or ascent search direction.

Double-Dogleg Optimization (DBLDOG)

The double-dogleg optimization method combines the ideas of the quasi-Newton and trust region methods. In each iteration, the double-dogleg algorithm computes the step $\mathbf{s}^{(k)}$ as the linear combination of the steepest descent or ascent search direction $\mathbf{s}_1^{(k)}$ and a quasi-Newton search direction $\mathbf{s}_2^{(k)}$:

$$\mathbf{s}^{(k)} = \alpha_1 \mathbf{s}_1^{(k)} + \alpha_2 \mathbf{s}_2^{(k)}$$

The step is requested to remain within a prespecified trust region radius (Fletcher 1987, p. 107). Thus, the DBLDOG subroutine uses the dual quasi-Newton update but does not perform a line search.

The double-dogleg optimization technique works well for medium-sized to moderately large optimization problems, where the objective function and the gradient can be computed much faster than the Hessian. The implementation is based on Dennis and Mei (1979) and Gay (1983), but it is extended for dealing with boundary and linear constraints. The DBLDOG technique generally requires more iterations than the TRUREG, NEWRAP, and NRRIDG techniques, which require second-order derivatives; however, each of the DBLDOG iterations is computationally cheap. Furthermore, the DBLDOG technique requires only gradient calls for the update of the Cholesky factor of an approximate Hessian.

Conjugate Gradient Optimization (CONGRA)

Second-order derivatives are not required by the CONGRA algorithm and are not even approximated. The CONGRA algorithm can be expensive in function and gradient calls, but it requires only $O(p)$ memory for unconstrained optimization. In general, many iterations are required to obtain a precise solution, but each of the CONGRA iterations is computationally cheap.

The CONGRA subroutine should be used for optimization problems with large p. For the unconstrained or boundary-constrained case, CONGRA requires only $O(p)$ bytes of working memory, whereas all other optimization methods require order $O(p^2)$ bytes of working memory. During p successive iterations, uninterrupted by restarts or changes in the working set, the conjugate gradient algorithm computes a cycle of p conjugate search directions. In each iteration, a line search is performed along the search direction to find an approximate optimum of the objective function. The line-search method uses quadratic interpolation and cubic extrapolation to obtain a step size α that satisfies the Goldstein conditions. One of the Goldstein conditions can be violated if the feasible region defines an upper limit for the step size.

Nelder-Mead Simplex Optimization (NMSIMP)

The Nelder-Mead simplex method does not use any derivatives and does not assume that the objective function has continuous derivatives. The objective function itself needs to be continuous. This technique is quite expensive in the number of function calls, and it might be unable to generate precise results for $p \gg 40$.

The original Nelder-Mead simplex algorithm is implemented and extended to boundary constraints. This algorithm does not compute the objective for infeasible points, but it changes the shape of the simplex adapting to the nonlinearities of the objective function. This change contributes to an increased speed of convergence and uses a special termination criterion.

Displayed Output

The following sections describe the output that PROC HPLOGISTIC produces by default. The output is organized into various tables, which are discussed in the order of appearance.

Performance Information

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution, whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

If you specify the DETAILS option in the PERFORMANCE statement, the procedure also produces a "Timing" table in which elapsed time (absolute and relative) for the main tasks of the procedure are displayed.

Model Information

The "Model Information" table displays basic information about the model, such as the response variable, frequency variable, link function, and the model category the HPLOGISTIC procedure determined based on your input and options. The "Model Information" table also displays the distribution of the data that is assumed by the HPLOGISTIC procedure. See the section "Response Distributions" on page 343 for how the procedure determines the response distribution.

Class Level Information

The "Class Level Information" table lists the levels of every variable specified in the CLASS statement. You should check this information to make sure that the data are correct. You can adjust the order of the CLASS variable levels with the ORDER= option in the CLASS statement. You can suppress the "Class

Level Information" table completely or partially with the NOCLPRINT= option in the PROC HPLOGISTIC statement.

If the classification variables use reference parameterization, the "Class Level Information" table also displays the reference value for each variable.

Number of Observations

The "Number of Observations" table displays the number of observations read from the input data set and the number of observations used in the analysis. If a FREQ statement is present, the sum of the frequencies read and used is displayed. If the events/trials syntax is used, the number of events and trials is also displayed.

Response Profile

The "Response Profile" table displays the ordered value from which the HPLOGISTIC procedure determines the probability being modeled as an event in binary models and the ordering of categories in multinomial models. For each response category level, the frequency used in the analysis is reported. You can affect the ordering of the response values with the *response-options* in the MODEL statement. For binary and generalized logit models, the note that follows the "Response Profile" table indicates which outcome is modeled as the event in binary models and which value serves as the reference category.

The "Response Profile" table is not produced for binomial data. You can find information about the number of events and trials in the "Number of Observations" table.

Selection Information

When you specify the SELECTION statement, the HPLOGISTIC procedure produces by default a series of tables with information about the model selection. The "Selection Information" table informs you about the model selection method, selection and stop criteria, and other parameters that govern the selection. You can suppress this table by specifying DETAILS=NONE in the SELECTION statement.

Selection Summary

When you specify the SELECTION statement, the HPLOGISTIC procedure produces the "Selection Summary" table with information about which effects were entered into or removed from the model at the steps of the model selection process. The p-value for the score chi-square test that led to the removal or entry decision is also displayed. You can request further details about the model selection steps by specifying DETAILS=STEPS or DETAILS=ALL in the SELECTION statement. You can suppress the display of the "Selection Summary" table by specifying DETAILS=NONE in the SELECTION statement.

Stop Reason

When you specify the SELECTION statement, the HPLOGISTIC procedure produces a simple table that tells you why model selection stopped.

Selection Reason

When you specify the SELECTION statement, the HPLOGISTIC procedure produces a simple table that tells you why the final model was selected.

Selected Effects

When you specify the SELECTION statement, the HPLOGISTIC procedure produces a simple table that tells you which effects were selected into the final model.

Iteration History

For each iteration of the optimization, the "Iteration History" table displays the number of function evaluations (including gradient and Hessian evaluations), the value of the objective function, the change in the objective function from the previous iteration and the absolute value of the largest (projected) gradient element. The objective function used in the optimization in the HPLOGISTIC procedure is normalized by default to enable comparisons across data sets with different sampling intensity. You can control normalization with the NORMALIZE= option in the PROC HPLOGISTIC statement.

If you specify the ITDETAILS option in the PROC HPLOGISTIC statement, information about the parameter estimates and gradients in the course of the optimization is added to the "Iteration History" table.

The "Iteration History" table is displayed by default unless you specify the NOITPRINT option or perform a model selection. To generate the history from a model selection process, specify the ITSELECT option.

Convergence Status

The convergence status table is a small ODS table that follows the "Iteration History" table in the default output. In the listing it appears as a message that indicates whether the optimization succeeded and which convergence criterion was met. If the optimization fails, the message indicates the reason for the failure. If you save the convergence status table to an output data set, a numeric Status variable is added that enables you to assess convergence programmatically. The values of the Status variable encode the following:

0 Convergence was achieved, or an optimization was not performed (because TECHNIQUE=NONE is specified).

1 The objective function could not be improved.

2 Convergence was not achieved because of a user interrupt or because a limit was exceeded, such as the maximum number of iterations or the maximum number of function evaluations. To modify these limits, see the MAXITER=, MAXFUNC=, and MAXTIME= options in the PROC HPLOGISTIC statement.

3 Optimization failed to converge because function or derivative evaluations failed at the starting values or during the iterations or because a feasible point that satisfies the parameter constraints could not be found in the parameter space.

Dimensions

The "Dimensions" table displays size measures that are derived from the model and the environment. For example, it displays the number of columns in the design matrix, the rank of the matrix, the largest number of design columns associated with an effect, the number of compute nodes in MPP mode, and the number of threads per node.

Fit Statistics

The "Fit Statistics" table displays a variety of likelihood-based measures of fit. All statistics are presented in "smaller is better" form.

The calculation of the information criteria uses the following formulas, where p denotes the number of effective parameters, f denotes the number of frequencies used, and l is the log likelihood evaluated at the converged estimates:

$$\begin{aligned}
\text{AIC} &= -2l + 2p \\
\text{AICC} &= \begin{cases} -2l + 2pf/(f-p-1) & \text{when } f > p+2 \\ -2l + 2p(p+2) & \text{otherwise} \end{cases} \\
\text{BIC} &= -2l + p\log(f)
\end{aligned}$$

If no FREQ statement is given, f equals n, the number of observations used.

The values displayed in the "Fit Statistics" table are not based on a normalized log-likelihood function.

Global Tests

The "Global Tests" table provides a statistical test for the hypothesis of whether the final model provides a better fit than a model without effects (an "intercept-only" model).

If you specify the NOINT option in the MODEL statement, the reference model is one where the linear predictor is 0 for all observations.

Partition for the Hosmer and Lemeshow Test

The "Partition for the Hosmer and Lemeshow Test" table displays the grouping used in the Hosmer-Lemeshow test. This table is displayed if you specify the LACKFIT option in the MODEL statement. See the section "The Hosmer-Lemeshow Goodness-of-Fit Test" on page 346 for details, and see Hosmer and Lemeshow (2000) for examples of using this partition.

Hosmer and Lemeshow Goodness-of-Fit Test

The "Hosmer and Lemeshow Goodness-of-Fit Test" table provides a test of the fit of the model; small p-values reject the null hypothesis that the fitted model is adequate. This table is displayed if you specify the LACKFIT option in the MODEL statement. See the section "The Hosmer-Lemeshow Goodness-of-Fit Test" on page 346 for further details.

Parameter Estimates

The parameter estimates, their estimated (asymptotic) standard errors, and p-values for the hypothesis that the parameter is 0 are presented in the "Parameter Estimates" table. If you request confidence intervals with the CL or ALPHA= options in the MODEL statement, confidence limits are produced for the estimate on the linear scale.

ODS Table Names

Each table created by the HPLOGISTIC procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 16.5.

Table 16.5 ODS Tables Produced by PROC HPLOGISTIC

Table Name	Description	Required Statement / Option
CandidateDetails	Details about candidates for entry into or removal from the model	SELECTION DETAILS=STEP
ClassLevels	Level information from the CLASS statement	CLASS
ConvergenceStatus	Status of optimization at conclusion of optimization	Default output
Dimensions	Model dimensions	Default output
FitStatistics	Fit statistics	Default output
GlobalTests	Test of the model versus the null model	Default output
IterHistory	Iteration history	Default output or PROC HPLOGISTIC ITSELECT
LackFitChiSq	Hosmer-Lemeshow chi-square test results	MODEL / LACKFIT
LackFitPartition	Partition for the Hosmer-Lemeshow test	MODEL / LACKFIT
ModelInfo	Information about the modeling environment	Default output
NObs	Number of observations read and used, and number of events and trials, if applicable	Default output
ParameterEstimates	Solutions for the parameter estimates associated with effects in MODEL statements	Default output
PerformanceInfo	Information about the high-performance computing environment	Default output
ResponseProfile	Response categories and category modeled in models for binary and multinomial data	Default output
SelectedEffects	List of effects selected into model	SELECTION
SelectionDetails	Details about model selection, including fit statistics by step	SELECTION DETAILS=ALL
SelectionInfo	Information about the settings for model selection	SELECTION
SelectionReason	Reason why the particular model was selected	SELECTION
SelectionSummary	Summary information about model selection steps	SELECTION

Table 16.5 *continued*

Table Name	Description	Required Statement / Option
StopReason	Reason for termination of model selection	SELECTION
Timing	Absolute and relative times for tasks performed by the procedure	PERFORMANCE DETAILS

Examples: HPLOGISTIC Procedure

Example 16.1: Model Selection

The following HPLOGISTIC statements examine the same data as in the section "Getting Started: HPLOGISTIC Procedure" on page 321, but they request model selection via the forward selection technique. Model effects are added in the order of their significance until no more effects make a significant improvement of the current model. The DETAILS=ALL option in the SELECTION statement requests that all tables related to model selection be produced.

```
proc hplogistic data=getStarted;
   class C;
   model y = C x1-x10;
   selection method=forward details=all;
run;
```

The model selection tables are shown in Output 16.1.1 through Output 16.1.4.

The "Selection Information" table in Output 16.1.1 summarizes the settings for the model selection. Effects are added to the model only if they produce a significant improvement as judged by comparing the *p*-value of a score test to the entry significance level (SLE), which is 0.05 by default. The forward selection stops when no effect outside the model meets this criterion.

Output 16.1.1 Selection Information

The HPLOGISTIC Procedure

Selection Information

Selection Method	Forward
Select Criterion	Significance Level
Stop Criterion	Significance Level
Effect Hierarchy Enforced	None
Entry Significance Level (SLE)	0.05
Stop Horizon	1

The "Selection Summary" table in Output 16.1.2 shows the effects that were added to the model and their significance level. Step 0 refers to the null model that contains only an intercept. In the next step, effect x8 made the most significant contribution to the model among the candidate effects ($p = 0.0381$). In step 2 the most significant contribution when adding an effect to a model that contains the intercept and x8 was made by x2. In the subsequent step no effect could be added to the model that would produce a p-value less than 0.05, so variable selection stops.

Output 16.1.2 Selection Summary Information

```
                          Selection Summary

                          Effect         Number         p
                    Step  Entered    Effects In     Value

                       0  Intercept            1     .
                    ----------------------------------------
                       1  x8                   2    0.0381
                       2  x2                   3    0.0255


Selection stopped because no candidate for entry is significant at the 0.05
level.


                     Selected Effects: Intercept x2 x8
```

The DETAILS=ALL option requests further detail information about the steps of the model selection. The "Candidate Details" table in Output 16.1.3 list all candidates for each step in the order of significance of their score tests. The effect with smallest p-value less than the SLE level of 0.05 is added in each step.

Output 16.1.3 Candidate Details

Candidate Entry and Removal Details

Step	Rank	Effect	Candidate For	P Value
1	1	x8	Entry	0.0381
	2	x2	Entry	0.0458
	3	x4	Entry	0.0557
	4	x9	Entry	0.1631
	5	C	Entry	0.1858
	6	x1	Entry	0.2715
	7	x10	Entry	0.4434
	8	x5	Entry	0.7666
	9	x3	Entry	0.8006
	10	x7	Entry	0.8663
	11	x6	Entry	0.9626
2	1	x2	Entry	0.0255
	2	x4	Entry	0.0721
	3	x9	Entry	0.1080
	4	C	Entry	0.1241
	5	x1	Entry	0.2778
	6	x10	Entry	0.5250
	7	x5	Entry	0.6993
	8	x7	Entry	0.7103
	9	x3	Entry	0.8743
	10	x6	Entry	0.9577

The DETAILS=ALL option also produces the "Selection Details" table, which provides fit statistics and the value of the score test chi-square statistic at each step.

Output 16.1.4 Selection Details

Selection Details

Step	Description	Effects In Model	Chi-Square	Pr > ChiSq	-2 LogL	AIC
0	Initial Model	1			123.820	125.820
1	x8 entered	2	4.2986	0.0381	119.462	123.462
2	x2 entered	3	4.9882	0.0255	114.396	120.396

Selection Details

Step	AICC	BIC
0	125.861	128.425
1	123.586	128.672
2	120.646	128.212

Output 16.1.5 displays information about the selected model. Notice that the –2 log likelihood value in the "Fit Statistics" table is larger than the value for the full model in Figure 16.9. This is expected because the selected model contains only a subset of the parameters. Because the selected model is more parsimonious than the full model, the discrepancy between the –2 log likelihood and the information criteria is less severe than previously noted.

Output 16.1.5 Fit Statistics and Null Test

Fit Statistics

-2 Log Likelihood	114.40
AIC (smaller is better)	120.40
AICC (smaller is better)	120.65
BIC (smaller is better)	128.21

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	9.4237	2	0.0090

The parameter estimates of the selected model are given in Output 16.1.6. Notice that the effects are listed in the "Parameter Estimates" table in the order in which they were specified in the MODEL statement and not in the order in which they were added to the model.

Output 16.1.6 Parameter Estimates

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	0.8584	0.5503	Infty	1.56	0.1188
x2	-0.2502	0.1146	Infty	-2.18	0.0290
x8	1.7840	0.7908	Infty	2.26	0.0241

You can construct the prediction equation for this model from the parameter estimates as follows. The estimated linear predictor for an observation is

$$\widehat{\eta} = 0.8584 - 0.2503 \times x_2 + 1.7840 \times x_8$$

and the predicted probability that variable y takes on the value 0 is

$$\widehat{\Pr}(Y = 0) = \frac{1}{1 + \exp\{-\widehat{\eta}\}}$$

Example 16.2: Modeling Binomial Data

If $Y_1, \cdots, Y_n$ are independent binary (Bernoulli) random variables with common success probability π, then their sum is a binomial random variable. In other words, a binomial random variable with parameters n and π can be generated as the sum of n Bernoulli(π) random experiments. The HPLOGISTIC procedure uses a special syntax to express data in binomial form, the *events/trials* syntax.

Consider the following data, taken from Cox and Snell (1989, pp. 10–11), of the number, r, of ingots not ready for rolling, out of n tested, for a number of combinations of heating time and soaking time. If each test is carried out independently and if for a particular combination of heating and soaking time there is a constant probability that the tested ingot is not ready for rolling, then the random variable r follows a Binomial(n, π) distribution, where the success probability π is a function of heating and soaking time.

```
data Ingots;
   input Heat Soak r n @@;
   Obsnum= _n_;
   datalines;
7 1.0 0 10  14 1.0 0 31  27 1.0 1 56  51 1.0 3 13
7 1.7 0 17  14 1.7 0 43  27 1.7 4 44  51 1.7 0  1
7 2.2 0  7  14 2.2 2 33  27 2.2 0 21  51 2.2 0  1
7 2.8 0 12  14 2.8 0 31  27 2.8 1 22  51 4.0 0  1
7 4.0 0  9  14 4.0 0 19  27 4.0 1 16
;
```

The following statements show the use of the events/trials syntax to model the binomial response. The *events* variable in this situation is r, the number of ingots not ready for rolling, and the *trials* variable is n, the number of ingots tested. The dependency of the probability of not being ready for rolling is modeled as a function of heating time, soaking time, and their interaction. The OUTPUT statement stores the linear predictors and the predicted probabilities in the Out data set along with the ID variable.

```
proc hplogistic data=Ingots;
   model r/n = Heat Soak Heat*Soak;
   id Obsnum;
   output out=Out xbeta predicted=Pred;
run;
```

The "Performance Information" table in Output 16.2.1 shows that the procedure executes in client (SMP) mode. The example is executed on a single machine with the same number of cores as the number of threads used; that is, one computational thread was spawned per CPU.

Output 16.2.1 Performance Information

```
                    The HPLOGISTIC Procedure

                    Performance Information

                Execution Mode       On client
                Number of Threads    8
```

The "Model Information" table shows that the data are modeled as binomially distributed with a logit link

function (Output 16.2.2). This is the default link function in the HPLOGISTIC procedure for binary and binomial data. The procedure estimates the parameters of the model by a Newton-Raphson algorithm.

Output 16.2.2 Model Information and Number of Observations

Model Information

Data Source	WORK.INGOTS
Response Variable (Events)	r
Response Variable (Trials)	n
Distribution	Binomial
Link Function	Logit
Optimization Technique	Newton-Raphson with Ridging

Number of Observations Read	19
Number of Observations Used	19
Number of Events	12
Number of Trials	387

The second table in Output 16.2.2 shows that all 19 observations in the data set were used in the analysis, and that the total number of events and trials equal 12 and 387, respectively. These are the sums of the variables r and n across all observations.

Output 16.2.3 displays the "Iteration History" and convergence status tables for this run. The HPLOGISTIC procedure converged after four iterations (not counting the initial setup iteration) and meets the GCONV= convergence criterion.

Output 16.2.3 Iteration History and Convergence Status

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	4	0.7676329445	.	6.378002
1	2	0.7365832479	0.03104970	0.754902
2	2	0.7357086248	0.00087462	0.023623
3	2	0.7357075299	0.00000109	0.00003
4	2	0.7357075299	0.00000000	5.42E-11

Convergence criterion (GCONV=1E-8) satisfied.

Output 16.2.4 displays the "Dimensions" table for the model. There are four columns in the design matrix of the model (the $\mathbf{X}$ matrix); they correspond to the intercept, the Heat effect, the Soak effect, and the interaction of the Heat and Soak effects. The model is nonsingular, since the rank of the crossproducts matrix equals the number of columns in $\mathbf{X}$. All parameters are estimable and participate in the optimization.

Output 16.2.4 Dimensions in Binomial Logistic Regression

Dimensions	
Columns in X	4
Number of Effects	4
Max Effect Columns	1
Rank of Cross-product Matrix	4
Parameters in Optimization	4

Output 16.2.5 displays the "Fit Statistics" table for this run. Evaluated at the converged estimates, –2 times the value of the log-likelihood function equals 27.9569. Further fit statistics are also given, all of them in "smaller is better" form. The AIC, AICC, and BIC criteria are used to compare non-nested models and to penalize the model fit for the number of observations and parameters. The –2 log-likelihood value can be used to compare nested models by way of a likelihood ratio test.

Output 16.2.5 Fit Statistics

Fit Statistics	
-2 Log Likelihood	27.9569
AIC (smaller is better)	35.9569
AICC (smaller is better)	38.8140
BIC (smaller is better)	39.7346

Output 16.2.6 shows the test of the global hypothesis that the effects jointly do not impact the probability of ingot readiness. The chi-square test statistic can be obtained by comparing the –2 log-likelihood value of the model with covariates to the value in the intercept-only model. The test is significant with a p-value of 0.0082. One or more of the effects in the model have a significant impact on the probability of ingot readiness.

Output 16.2.6 Null Test

Testing Global Null Hypothesis: BETA=0			
Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	11.7663	3	0.0082

The "Parameter Estimates" table in Output 16.2.7 displays the estimates and standard errors of the model effects.

Output 16.2.7 Parameter Estimates

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	-5.9902	1.6666	Infty	-3.59	0.0003
Heat	0.09634	0.04707	Infty	2.05	0.0407
Soak	0.2996	0.7551	Infty	0.40	0.6916
Heat*Soak	-0.00884	0.02532	Infty	-0.35	0.7270

You can construct the prediction equation of the model from the "Parameter Estimates" table. For example, an observation with Heat equal to 14 and Soak equal to 1.7 has linear predictor

$$\widehat{\eta} = -5.9902 + 0.09634 \times 14 + 0.2996 \times 1.7 - 0.00884 \times 14 \times 7 = -4.34256$$

The probability that an ingot with these characteristics is not ready for rolling is

$$\widehat{\pi} = \frac{1}{1 + \exp\{-(-4.34256)\}} = 0.01284$$

The OUTPUT statement computes these linear predictors and probabilities and stores them in the Out data set. This data set also contains the ID variable, which is used by the following statements to attach the covariates to these statistics. Output 16.2.8 shows the probability that an ingot with Heat equal to 14 and Soak equal to 1.7 is not ready for rolling.

```
data Out;
   merge Out Ingots;
   by Obsnum;
proc print data=Out;
   where Heat=14 & Soak=1.7;
run;
```

Output 16.2.8 Predicted Probability for Heat=14 and Soak=1.7

Obs	Obsnum	Pred	Xbeta	Heat	Soak	r	n
6	6	0.012836	-4.34256	14	1.7	0	43

Binomial data are a form of grouped binary data where "successes" in the underlying Bernoulli trials are totaled. You can thus unwind data for which you use the events/trials syntax and fit it with techniques for binary data.

The following DATA step expands the Ingots data set with 12 events in 387 trials into a binary data set with 387 observations.

```
data Ingots_binary;
   set Ingots;
   do i=1 to n;
     if i <= r then y=1; else y = 0;
     output;
   end;
run;
```

The following HPLOGISTIC statements fit the model with Heat effect, Soak effect, and their interaction to the binary data set. The **event='1'** response-variable option in the MODEL statement ensures that the HPLOGISTIC procedure models the probability that the variable y takes on the value ('1').

```
proc hplogistic data=Ingots_binary;
   model y(event='1') = Heat Soak Heat*Soak;
run;
```

Output 16.2.9 displays the "Performance Information", "Model Information," "Number of Observations," and the "Response Profile" tables. The data are now modeled as binary (Bernoulli distributed) with a logit link function. The "Response Profile" table shows that the binary response breaks down into 375 observations where y equals zero and 12 observations where y equals 1.

Output 16.2.9 Model Information in Binary Model

```
                    The HPLOGISTIC Procedure

                    Performance Information

                 Execution Mode       On client
                 Number of Threads    8


                      Model Information

Data Source                WORK.INGOTS_BINARY
Response Variable          y
Distribution               Binary
Link Function              Logit
Optimization Technique     Newton-Raphson with Ridging


     Number of Observations Read             387
     Number of Observations Used             387


                   Response Profile

                Ordered              Total
                  Value    y     Frequency

                      1    0           375
                      2    1            12

     You are modeling the probability that y='1'.
```

Output 16.2.10 displays the result for the test of the global null hypothesis and the parameter estimates. These results match those in Output 16.2.6 and Output 16.2.7.

Output 16.2.10 Null Test and Parameter Estimates

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	11.7663	3	0.0082

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	-5.9902	1.6666	Infty	-3.59	0.0003
Heat	0.09634	0.04707	Infty	2.05	0.0407
Soak	0.2996	0.7551	Infty	0.40	0.6916
Heat*Soak	-0.00884	0.02532	Infty	-0.35	0.7270

Example 16.3: Ordinal Logistic Regression

Consider a study of the effects of various cheese additives on taste. Researchers tested four cheese additives and obtained 52 response ratings for each additive. Each response was measured on a scale of nine categories ranging from strong dislike (1) to excellent taste (9). The data, given in McCullagh and Nelder (1989, p. 175) in the form of a two-way frequency table of additive by rating, are saved in the data set Cheese by using the following program. The variable y contains the response rating. The variable Additive specifies the cheese additive (1, 2, 3, or 4). The variable freq gives the frequency with which each additive received each rating.

```
data Cheese;
   do Additive = 1 to 4;
      do y = 1 to 9;
         input freq @@;
         output;
      end;
   end;
   label y='Taste Rating';
   datalines;
0  0  1  7  8  8 19  8  1
6  9 12 11  7  6  1  0  0
1  1  6  8 23  7  5  1  0
0  0  0  1  3  7 14 16 11
;
```

The response variable y is ordinally scaled. A cumulative logit model is used to investigate the effects of the cheese additives on taste. The following statements invoke PROC HPLOGISTIC to fit this model with y as the response variable and three indicator variables as explanatory variables, with the fourth additive as the reference level. With this parameterization, each Additive parameter compares an additive to the fourth additive.

```
proc hplogistic data=Cheese;
   freq freq;
   class Additive(ref='4') / param=ref ;
   model y=Additive;
   title 'Multiple Response Cheese Tasting Experiment';
run;
```

Results from the logistic analysis are shown in Output 16.3.1 through Output 16.3.3.

The "Response Profile" table in Output 16.3.1 shows that the strong dislike (y=1) end of the rating scale is associated with lower Ordered Values in the "Response Profile" table; hence the probability of disliking the additives is modeled.

Output 16.3.1 Proportional Odds Model Regression Analysis

```
          Multiple Response Cheese Tasting Experiment

                    The HPLOGISTIC Procedure

                    Performance Information

                  Execution Mode       On client
                  Number of Threads    8


                       Model Information

Data Source                 WORK.CHEESE
Response Variable           y
Frequency Variable          freq
Class Parameterization      Reference
Distribution                Multinomial (ordered)
Link Function               Cumulative Logit
Optimization Technique      Newton-Raphson with Ridging


                    Class Level Information

                                Reference
          Class       Levels    Value        Values

          Additive         4    4            1 2 3 4


          Number of Observations Read              36
          Number of Observations Used              28
          Sum of Frequencies Read                 208
          Sum of Frequencies Used                 208
```

Output 16.3.1 *continued*

Response Profile

Ordered Value	Taste Rating	Total Frequency
1	1	7
2	2	10
3	3	19
4	4	27
5	5	41
6	6	28
7	7	39
8	8	25
9	9	12

You are modeling the probabilities of levels of y having lower Ordered Values in the Response Profile Table.

Output 16.3.2 Proportional Odds Model Regression Analysis

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	4	2.0668312595	.	0.137412
1	2	1.7319560317	0.33487523	0.062757
2	2	1.7105150048	0.02144103	0.008919
3	2	1.7099716191	0.00054339	0.00035
4	2	1.7099709251	0.00000069	6.981E-7
5	2	1.7099709251	0.00000000	2.98E-12

Convergence criterion (GCONV=1E-8) satisfied.

Dimensions

Columns in X	11
Number of Effects	2
Max Effect Columns	3
Rank of Cross-product Matrix	11
Parameters in Optimization	11

Fit Statistics

-2 Log Likelihood	711.35
AIC (smaller is better)	733.35
AICC (smaller is better)	734.69
BIC (smaller is better)	770.06

Output 16.3.2 *continued*

Testing Global Null Hypothesis: BETA=0			
Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	148.4539	3	<.0001

The positive value (1.6128) for the parameter estimate for Additive=1 in Output 16.3.3 indicates a tendency toward the lower-numbered categories of the first cheese additive relative to the fourth. In other words, the fourth additive tastes better than the first additive. Similarly, the second and third additives are both less favorable than the fourth additive. The relative magnitudes of these slope estimates imply the preference ordering: fourth, first, third, second.

Output 16.3.3 Proportional Odds Model Regression Analysis

Parameter Estimates						
Parameter	Taste Rating	Estimate	Standard Error	DF	t Value	Pr > |t|
Intercept	1	−7.0802	0.5640	Infty	−12.55	<.0001
Intercept	2	−6.0250	0.4764	Infty	−12.65	<.0001
Intercept	3	−4.9254	0.4257	Infty	−11.57	<.0001
Intercept	4	−3.8568	0.3880	Infty	−9.94	<.0001
Intercept	5	−2.5206	0.3453	Infty	−7.30	<.0001
Intercept	6	−1.5685	0.3122	Infty	−5.02	<.0001
Intercept	7	−0.06688	0.2738	Infty	−0.24	0.8071
Intercept	8	1.4930	0.3357	Infty	4.45	<.0001
Additive 1		1.6128	0.3805	Infty	4.24	<.0001
Additive 2		4.9646	0.4767	Infty	10.41	<.0001
Additive 3		3.3227	0.4218	Infty	7.88	<.0001

Example 16.4: Conditional Logistic Regression for Matched Pairs Data

In matched pairs (*case-control*) studies, conditional logistic regression is used to investigate the relationship between an outcome of being an event (case) or a non-event (control) and a set of prognostic factors.

The following data are a subset of the data from the Los Angeles Study of the Endometrial Cancer Data in Breslow and Day (1980). There are 63 matched pairs, each consisting of a case of endometrial cancer (Outcome=1) and a control (Outcome=0). The case and corresponding control have the same ID. Two prognostic factors are included: Gall (an indicator variable for gall bladder disease) and Hyper (an indicator variable for hypertension). The goal of the case-control analysis is to determine the relative risk for gall bladder disease, controlling for the effect of hypertension.

```
data Data1;
  do ID=1 to 63;
    do Outcome = 1 to 0 by -1;
      input Gall Hyper @@;
```

```
      output;
    end;
  end;
  datalines;
0 0  0 0    0 0  0 0    0 1  0 1    0 0  1 0    1 0  0 1
0 1  0 0    1 0  0 0    1 1  0 1    0 0  0 0    0 0  0 0
1 0  0 0    0 0  0 1    1 0  0 1    1 0  1 0    1 0  0 1
0 1  0 0    0 0  1 1    0 0  1 1    0 0  0 1    0 1  0 0
0 0  1 1    0 1  0 1    0 1  0 0    0 0  0 0    0 0  0 0
0 0  0 1    1 0  0 1    0 0  0 1    1 0  0 0    0 1  0 0
0 1  0 0    0 1  0 0    0 1  0 0    0 0  0 0    1 1  1 1
0 0  0 1    0 1  0 0    0 1  0 1    0 1  0 1    0 1  0 0
0 0  0 0    0 1  1 0    0 0  0 1    0 0  0 0    1 0  0 0
0 0  0 0    1 1  0 0    0 1  0 0    0 0  0 0    0 1  0 1
0 0  0 0    0 1  0 1    0 1  0 0    0 1  0 0    1 0  0 0
0 0  0 0    1 1  1 0    0 0  0 0    0 0  0 0    1 1  0 0
1 0  1 0    0 1  0 0    1 0  0 0
;
```

When each matched set consists of one event and one non-event, the conditional likelihood is given by

$$\prod_i (1 + \exp(-(\boldsymbol{x}_{i1} - \boldsymbol{x}_{i0})'\boldsymbol{\psi})^{-1}$$

where $\boldsymbol{x}_{i1}$ and $\boldsymbol{x}_{i0}$ are vectors that represent the prognostic factors for the event and non-event, respectively, of the ith matched set. This likelihood is identical to the likelihood of fitting a logistic regression model to a set of data with constant response, where the model contains no intercept term and has explanatory variables given by $\boldsymbol{d}_i = \boldsymbol{x}_{i1} - \boldsymbol{x}_{i0}$ (Breslow 1982).

To apply this method, the following DATA step transforms each matched pair into a single observation, where the variables Gall and Hyper contain the differences between the corresponding values for the case and the control (case – control). The variable Outcome, which is used as the response variable in the logistic regression model, is given a constant value of 0 (which is the Outcome value for the control, although any constant, numeric or character, suffices).

```
data Data2;
   set Data1;
   drop id1 gall1 hyper1;
   retain id1 gall1 hyper1 0;
   if (ID = id1) then do;
      Gall=gall1-Gall; Hyper=hyper1-Hyper;
      output;
   end;
   else do;
      id1=ID; gall1=Gall; hyper1=Hyper;
   end;
run;
```

Note that there are 63 observations in the data set, one for each matched pair. Since the number of observations (n) is halved, statistics that depend on n such as R^2 will be incorrect. The variable Outcome has a constant value of 0.

In the following statements, PROC HPLOGISTIC is invoked with the NOINT option to obtain the conditional logistic model estimates. Because the option CL is specified, PROC HPLOGISTIC computes a 95% confidence interval for the parameter.

```
proc hplogistic data=Data2;
   model outcome=Gall / noint cl;
run;
```

Results from the conditional logistic analysis are shown in Output 16.4.1 through Output 16.4.3.

Output 16.4.1 shows that you are fitting a binary logistic regression where the response variable Outcome has only one level.

Output 16.4.1 Conditional Logistic Regression (Gall as Risk Factor)

```
          Multiple Response Cheese Tasting Experiment

                    The HPLOGISTIC Procedure

                    Performance Information

                  Execution Mode       On client
                  Number of Threads    8


                       Model Information

Data Source                 WORK.DATA2
Response Variable           Outcome
Distribution                Binary
Link Function               Logit
Optimization Technique      Newton-Raphson with Ridging


          Number of Observations Read              63
          Number of Observations Used              63


                      Response Profile

                Ordered                     Total
                  Value    Outcome       Frequency

                      1    0                    63

        You are modeling the probability that Outcome='0'.
```

Output 16.4.2 shows that the model is marginally significant (p=0.0550).

Output 16.4.2 Conditional Logistic Regression (Gall as Risk Factor)

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	4	0.6662698453	.	0.015669
1	2	0.6639330101	0.00233684	0.001351
2	2	0.6639171997	0.00001581	6.88E-6
3	2	0.6639171993	0.00000000	1.83E-10

Convergence criterion (GCONV=1E-8) satisfied.

Dimensions

Columns in X	1
Number of Effects	1
Max Effect Columns	1
Rank of Cross-product Matrix	1
Parameters in Optimization	1

Fit Statistics

-2 Log Likelihood	83.6536
AIC (smaller is better)	85.6536
AICC (smaller is better)	85.7191
BIC (smaller is better)	87.7967

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	3.6830	1	0.0550

Note that there is no intercept term in the "Parameter Estimates" table in Output 16.4.3. The intercepts have been *conditioned out* of the analysis.

Output 16.4.3 Conditional Logistic Regression (Gall as Risk Factor)

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|	Alpha
Gall	0.9555	0.5262	Infty	1.82	0.0694	0.05

Parameter Estimates

Parameter	Lower	Upper
Gall	-0.07589	1.9869

The odds ratio estimate for Gall is $\exp(0.9555) = 2.60$, which is marginally significant (p=0.0694) and which is an estimate of the relative risk for gall bladder disease. A subject who has gall bladder disease has 2.6 times the odds of having endometrial cancer as a subject who does not have gall bladder disease. A 95% confidence interval for this relative risk, produced by exponentiating the confidence interval for the parameter, is (0.927, 7.293).

References

Akaike, H. (1974), "A New Look at the Statistical Model Identification," *IEEE Transaction on Automatic Control*, AC-19, 716–723.

Breslow, N. E. (1982), "Covariance Adjustment of Relative-Risk Estimates in Matched Studies," *Biometrics*, 38, 661–672.

Breslow, N. E. and Day, N. E. (1980), *Statistical Methods in Cancer Research, Volume I: The Analysis of Case-Control Studies*, IARC Scientific Publications, No. 32, Lyon, France: International Agency for Research on Cancer.

Burnham, K. P. and Anderson, D. R. (1998), *Model Selection and Inference: A Practical Information-Theoretic Approach*, New York: Springer-Verlag.

Cox, D. R. and Snell, E. J. (1989), *The Analysis of Binary Data*, Second Edition, London: Chapman & Hall.

Dennis, J. E., Gay, D. M., and Welsch, R. E. (1981), "An Adaptive Nonlinear Least-Squares Algorithm," *ACM Transactions on Mathematical Software*, 7, 348–368.

Dennis, J. E. and Mei, H. H. W. (1979), "Two New Unconstrained Optimization Algorithms Which Use Function and Gradient Values," *Journal of Optimization Theory Applications*, 28, 453–482.

Eskow, E. and Schnabel, R. B. (1991), "Algorithm 695: Software for a New Modified Cholesky Factorization," *ACM Transactions on Mathematical Software*, 17, 306–312.

Fletcher, R. (1987), *Practical Methods of Optimization*, Second Edition, Chichester, UK: John Wiley & Sons.

Gay, D. M. (1983), "Subroutines for Unconstrained Minimization," *ACM Transactions on Mathematical Software*, 9, 503–524.

Hosmer, D. W., Jr. and Lemeshow, S. (2000), *Applied Logistic Regression*, Second Edition, New York: John Wiley & Sons.

Hurvich, C. M. and Tsai, C.-L. (1989), "Regression and Time Series Model Selection in Small Samples," *Biometrika*, 76, 297–307.

Magee, L. (1990), "R^2 Measures Based on Wald and Likelihood Ratio Joint Significant Tests," *The American Statistician*, 44, 250–253.

McCullagh, P. and Nelder, J. A. (1989), *Generalized Linear Models*, Second Edition, London: Chapman & Hall.

Moré, J. J. and Sorensen, D. C. (1983), "Computing a Trust-Region Step," *SIAM Journal on Scientific and Statistical Computing*, 4, 553–572.

Nagelkerke, N. J. D. (1991), "A Note on a General Definition of the Coefficient of Determination," *Biometrika*, 78, 691–692.

Schwarz, G. (1978), "Estimating the Dimension of a Model," *Annals of Statistics*, 6, 461–464.

Chapter 17
The HPLSO Procedure

Contents

Overview: HPLSO Procedure **375**
Getting Started: HPLSO Procedure **377**
Introductory Examples 377
Syntax: HPLSO Procedure **382**
PROC HPLSO Statement 382
PERFORMANCE Statement 386
Details: HPLSO Procedure **387**
The FCMP Procedure 387
The Variable Data Set 387
Describing the Objective Function 388
Describing Linear Constraints 392
Describing Nonlinear Constraints 393
The HPLSO Algorithm 394
Specifying and Returning Trial Points 396
Function Value Caching 397
Iteration Log 398
Procedure Termination Messages 398
ODS Tables 399
Macro Variable _ORHPLSO_ 400
Examples: HPLSO Procedure **401**
Example 17.1: Using Dense Format 401
Example 17.2: Using MPS Format 403
Example 17.3: Using QPS Format 405
Example 17.4: Linear Constraints and a Nonlinear Objective 407
Example 17.5: Using Nonlinear Constraints 408
Example 17.6: Using External Data Sets 411
References **415**

Overview: HPLSO Procedure

The HPLSO procedure performs general optimization of nonlinear functions that are defined by the Base SAS FCMP procedure over both continuous and integer variables. These functions can be nonsmooth, discontinuous, and possibly computationally expensive to evaluate.

The general problem formulation is given by

$$\begin{array}{rlcccl} \min & & & f(x) & & \\ \text{subject to} & x_\ell & \leq & x & \leq & x_u \\ & b_\ell & \leq & Ax & \leq & b_u \\ & c_\ell & \leq & c(x) & \leq & c_u \\ & x_i & \in & \mathbb{Z},\ i \in \mathcal{I}. & & \end{array}$$

where $x \in \mathbb{R}^n$ is the vector of the decision variables; $f(x) : \mathbb{R}^n \rightarrow \mathbb{R}$ is the objective function; A is an $m \times n$ linear coefficient matrix; $c(x) : \mathbb{R}^n \rightarrow \mathbb{R}^p$ is the vector of nonlinear constraint functions—that is, $c = (c_1, \ldots, c_p)$; x_ℓ and x_u are the vectors of the lower and upper bounds, respectively, on the decision variables; b_ℓ and b_u are the vectors of the lower and upper bounds, respectively, on the linear constraints; and c_ℓ and c_u are the vectors of the lower and upper bounds, respectively, on the nonlinear constraint functions. Equality constraints can be represented by equating the lower and upper bounds of the desired variable or constraint.

Because of the limited assumptions made on $f(x)$ and $c(x)$, the HPLSO procedure uses a parallel hybrid derivative-free approach similar to approaches used in Taddy et al. (2009); Plantenga (2009); Gray, Fowler, and Griffin (2010); Griffin and Kolda (2010a). Derivative-free methods are effective whether or not derivatives are available, provided the dimension of x is not too large (Gray and Fowler 2011). As a rule of thumb, derivative-free algorithms are rarely applied to black-box optimization problems with more than 100 variables. The term *black-box* emphasizes that the function is used only as a mapping operator with no implicit assumption about or requirement on the structure of the functions themselves. In contrast, derivative-based algorithms commonly require that the nonlinear objectives be continuous, smooth, and have an exploitable analytic representation.

The HPLSO procedure solves general nonlinear problems by simultaneously applying multiple instances of global and local search algorithms in parallel. This streamlines the process of needing to first apply a global algorithm to determine a good starting point to initialize a local algorithm. For example, if the problem is convex, a local algorithm should be sufficient, and the application of the global algorithm would create unnecessary overhead. If the problem instead has many local minima, failing to first run a global search algorithm could result in an inferior solution. Rather than attempting to guess which paradigm is best, PROC HPLSO simultaneously performs global and local searches, while continuously sharing computational resources and function evaluations. The resulting run time and solution quality should be similar to having automatically selected the best global and local search combination, given a suitable number of threads and processors. Moreover, because information is shared, the robustness of the hybrid approach can be increased over hybrid combinations that simply use the output of one algorithm to hot-start the second algorithm. In this chapter, the term "solver" refers to an implementation of one or more algorithms that can be used to solve a problem.

The HPLSO procedure uses different strategies to handle different types of constraints. Linear constraints are handled by using strategies similar to those in Griffin, Kolda, and Lewis (2008), where tangent directions to nearby constraints are constructed and used as search directions. Nonlinear constraints are handled by using an ensemble of smooth and nonsmooth merit functions (Griffin and Kolda 2010b). Integer and categorical variables are handled by using strategies and concepts similar to those in Griffin et al. (2011). This approach can be viewed as a genetic algorithm that includes an additional "growth" step, in which selected points from the population are allotted a small fraction of the total evaluation budget to improve their fitness score (that is, the objective function value) by using local optimization over the continuous variables.

Getting Started: HPLSO Procedure

All nonlinear objective and constraint functions should be defined by using PROC FCMP. In PROC FCMP, you specify the objective and constraint functions by using SAS statements that are similar to syntax that is used in the SAS DATA step; these functions are then compiled into function libraries for subsequent use. The SAS CMPLIB= system option specifies where to look for previously compiled functions and subroutines. All procedures (including PROC FCMP) that support the use of FCMP functions and subroutines use this system option. After your objective and constraint functions have been specified in a library, PROC HPLSO requires the names and context of the functions within this library that are relevant to the current optimization problem. You can provide this information to PROC HPLSO by using SAS data sets. You use additional data sets to describe variables and linear constraints in either a sparse or a dense format.

Introductory Examples

The following introductory examples illustrate how to get started using the HPLSO procedure.

A Bound-Constrained Problem

Consider the simple example of minimizing the Branin function,

$$f(x) = \left(x_2 - \frac{5.1}{4\pi^2}x_1^2 + \frac{5}{\pi}x_1 - 6\right)^2 + 10\left(1 - \frac{1}{8\pi}\right)\cos(x_1) + 10;$$

subject to $-5 \leq x_1 \leq 10$ and $0 \leq x_2 \leq 15$ (Jones, Perttunen, and Stuckman 1993). The minimum function value is $f(x^*) = 0.397887$ at $x^* = (-\pi, 12.275), (\pi, 2.275), (9.42478, 2.475)$. The following statements can be used to solve this problem:

```
data vardata;
   input _id_ $ _lb_ _ub_;
   datalines;
x1 -5 10
x2  0 15
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function branin(x1, x2);
      pi = constant('PI');
      y1 = (x2-(5.1/(4*pi**2))*x1*x1+5*x1/pi-6)**2;
      y2 = 10*(1-1/(8*pi))*cos(x1);
      return (y1+y2+10);
   endsub;

data objdata;
   input _id_ $ _function_ $ _sense_ $;
   datalines;
f branin min
;
```

```
options cmplib = sasuser.myfuncs;
proc hplso
   variables = vardata
   objective = objdata;
run;
```

The OBJECTIVE= option in the PROC HPLSO statement refers to the OBJDATA data set, which identifies BRANIN as the name of the objective function that is defined in the FCMP library sasuser.myfuncs and specifies that BRANIN should be minimized. The VARIABLES= option in the PROC HPLSO statement names the decision variables x1 and x2 and specifies lower and upper bounds.

Figure 17.1 shows the ODS tables that the HPLSO procedure produces by default.

Figure 17.1 Bound-Constrained Problem: Output

Performance Information

Execution Mode	On client
Number of Threads	2
Parallel Mode	Deterministic

Problem Summary

Name	Value
Problem Type	NLP
Variables	2
Integer Variables	0
Continuous Variables	2
Implicit Variables	0
Linear Constraints	0
Nonlinear Constraints	0
Linear Objective Coefficients	0
Quadratic Objective Coefficients	0
FCMP functions	1

Solution Summary

Name	Value
Status	Function convergence
Objective	0.3978873578
Infeasibility	0
Iterations	32
Evaluations	1781
Cached Evaluations	443
Nglobal	1
Popsize	80
Seed	1

Adding a Linear Constraint

You can use a LINCON= option to specify general linear equality or inequality constraints of the following form:

$$\sum_{j=1}^{n} a_{ij} x_j \; \{\leq \mid = \mid \geq\} \; b_i \quad \text{for } i = 1, \ldots, m.$$

For example, suppose that in addition to the bound constraints on the decision variables, you need to guarantee that the sum $x_1 + x_2$ is less than or equal to 0.6. To guarantee this, you can add a LINCON= option to the previous data set definitions, as in the following statements:

```
data lindata;
   input _id_ $ _lb_ x1 x2 _ub_;
   datalines;
a1  . 1 1  0.6
;

proc hplso
   variables = vardata
   objective = objdata
   lincon    = lindata;
run;
```

Here the symbol A1 denotes the name of the given linear constraints that are specified in column _ID_. The corresponding lower and upper bounds are specified in columns _LB_ and _UB_, respectively.

Nonlinear Constraints on the Decision Variables

You can specify general nonlinear equality or inequality constraints by using the NLINCON= option and adding its definition to the existing PROC FCMP library. Consider the previous problem with the following additional constraint:

$$x_1^2 - 2x_2 \geq 14$$

You can specify this constraint by adding a new FCMP function library and providing it a corresponding name and bounds in the NLINCON= option, as in the following statements:

```
data condata;
   input _id_ $ _lb_ _ub_;
   datalines;
c1  14 .
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function c1(x1, x2);
      return (x1**2 - 2*x2);
   endsub;

proc hplso
   variables = vardata
   objective = objdata
   lincon    = lindata
   nlincon   = condata;
run;
```

By calling PROC FCMP a second time, you can append the definition of C1 to your existing user library. That is, you do not need to redefine BRANIN after it has been added.

A Simple Maximum Likelihood Example

The following is a very simple example of a maximum likelihood estimation problem with the log-likelihood function:

$$l(\mu,\sigma) = -\log(\sigma) - \frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2$$

The maximum likelihood estimates of the parameters μ and σ form the solution to

$$\max_{\mu,\sigma} \sum_i l_i(\mu,\sigma)$$

where $\sigma > 0$ and

$$l_i(\mu,\sigma) = -\log(\sigma) - \frac{1}{2}\left(\frac{x_i-\mu}{\sigma}\right)^2$$

The following statements demonstrate two ways to formulate this example problem:

```
data lkhvar;
   input _id_ $ _lb_;
   datalines;
mu    .
sigma 0
;

data lkhobj1;
   input _id_ $ _function_ $ _sense_ $;
   datalines;
f loglkh1 max
;
```

In the following statements, the FCMP function is "stand-alone" because all the necessary data are defined within the function itself:

```
proc fcmp outlib=sasuser.myfuncs.mypkg;
   function loglkh1(mu, sigma);
      array x[5] / nosym;
      x[1]=1; x[2]=3; x[3]=4; x[4]=5; x[5]=7;
      s=0;
      do j=1 to 5;
         s = s - log(sigma) - 0.5*((x[j]-mu)/sigma)**2;
      end;
      return (s);
   endsub;
run;

proc hplso
   variables = lkhvar
   objective = lkhobj1;
run;
```

Alternatively, you can use an external data set to store the necessary observations and run PROC HPLSO to feed each observation to an FCMP function that processes a single line of data. In this case, PROC HPLSO sums the results for you. This mode is particularly useful when the data set is large and possibly distributed over a set of nodes, as shown in "Example 17.6: Using External Data Sets" on page 411.

The following statements demonstrate how to store the necessary observations in an external data set for use with PROC FCMP:

```
data logdata;
   input x @@;
   datalines;
1 3 4 5 7
;

data lkhobj2;
   input _id_ $ _function_ $ _sense_ $ _dataset_ $;
   datalines;
f loglkh2 max logdata
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function loglkh2(mu, sigma, x);
      s = - log(sigma) - 0.5*((x-mu)/sigma)**2;
      return (s);
   endsub;
run;

proc hplso
   variables = lkhvar
   objective = lkhobj2;
run;
```

In this case, for each line of data in logdata, the FCMP function LOGLKH2 is called. It is important that the non-variable arguments of LOGLKH2 coincide with a subset of the column names for the data set logdata, in this case X. However, the order in which the variables and data column names appear is not important. The following definition would work as well:

```
data lkhobj3;
   input _id_ $ _function_ $ _sense_ $ _dataset_ $;
   datalines;
f loglkh3 max logdata
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function loglkh3(x, sigma, mu);
      s = - log(sigma) - 0.5*((x-mu)/sigma)**2;
      return (s);
   endsub;
run;

proc hplso
   variables = lkhvar
   objective = lkhobj3;
run;
```

Syntax: HPLSO Procedure

The following statements are available in the HPLSO procedure:

PROC HPLSO *options* **;**
  PERFORMANCE *options* **;**

PROC HPLSO Statement

PROC HPLSO *options* **;**

The PROC HPLSO statement invokes the HPLSO procedure.

Functional Summary

Table 17.1 outlines the *options* available in the PROC HPLSO statement.

Table 17.1 Summary of PROC HPLSO Options

Description	*option*
Input Data Set Options	
Specifies the input cache file	CACHEIN=
Specifies the initial genetic algorithm population	FIRSTGEN=
Describes the linear constraints	LINCON=
Indicates that the description uses the mathematical programming system (MPS) data format	MPSDATA=
Describes the nonlinear constraints	NLINCON=
Describes the objective function	OBJECTIVE=
Specifies the initial trial points	PRIMALIN=
Indicates that the description uses the quadratic programming system (QPS) data format	QPSDATA=
Describes the variables	VARIABLES=
Output Data Set Options	
Specifies the output cache file	CACHEOUT=
Specifies the local solutions and best feasible solution	PRIMALOUT=
Specifies the members of the genetic algorithm population on exit	LASTGEN=
Stopping Condition Options	
Specifies the absolute function convergence criterion	ABSFCONV=
Specifies the maximum number of function evaluations	MAXFUNC=
Specifies the maximum number of genetic algorithm iterations	MAXGEN=
Specifies the upper limit on real time	MAXTIME=

Description	*option*
Optimization Control Options	
Specifies the feasibility tolerance	FEASTOL=
Specifies the number of global searches	NGLOBAL=
Genetic algorithm population size	POPSIZE=
Technical Options	
Specifies the cache tolerance	CACHETOL=
Specifies the maximum cache size	CACHEMAX=
Specifies how frequently to print the solution progress	LOGFREQ=
Specifies how much detail of solution progress to print in the log	LOGLEVEL=
Enables or disables the printing summary	PRINTLEVEL=
Initializes the seed for sampling routines	SEED=

Input Data Set Options

You can specify the following *options* that are related to input data sets:

CACHEIN=*SAS-data-set*
names a previously computed sample set. Using a previously computed sample set enables PROC HPLSO to warm-start. It is crucial that the nonlinear objective and function values be identical to those that were used when the cache data set was generated. For more information, see the section "Specifying and Returning Trial Points" on page 396.

FIRSTGEN=*SAS-data-set*
specifies an initial sample set that defines a subset of the initial population. The columns of this data set should coincide with the same format that is used by the PRIMALIN= data set. If the population size p is smaller than the size of this set, only the first p points of this set are used. For more information, see the section "Specifying and Returning Trial Points" on page 396.

LINCON=*SAS-data-set*
uses a dense format to describe the optimization problem's linear constraints. The corresponding data set should have columns _LB_ and _UB_ to describe lower and upper bounds, respectively. The column _ID_ is reserved for the corresponding constraint name. The remaining columns must correspond to the linear coefficients of the variables that are listed in the VARIABLES= option. For more information, see the section "Describing Linear Constraints" on page 392.

MPSDATA=*SAS-data-set*
specifies a data set that can be used as a sparse alternative to the LINCON= option, which uses a dense format to define variables. Mathematical programming system (MPS) is a common file format for representing linear and mixed-integer mathematical programs. For an example of using the OPTMODEL procedure to create the corresponding MPS file, see "Example 17.2: Using MPS Format" on page 403. Internally, binary variables are converted into integer variables with lower and upper bounds of 0 and 1, respectively. For more information, see the section "Describing Linear Constraints" on page 392.

NLINCON=*SAS-data-set*
names the FCMP functions to be used from the current library as nonlinear constraints, along with respective bounds. This data set should contain three columns: _ID_ to specify the corresponding FCMP function names and _LB_ and _UB_ to specify the lower and upper bounds for the corresponding constraints, respectively. For more information, see the section "Describing Nonlinear Constraints" on page 393.

OBJECTIVE=*SAS-data-set*
names the FCMP functions to be used from the current library to form the objective. At a minimum, this data set should have three columns: _ID_ to specify the function name to be used internally by the solver, _FUNCTION_ to specify the corresponding FCMP function, and _SENSE_ to specify whether the objective is to be minimized or maximized. PROC HPLSO enables you to implicitly define your objective function by using an external data set and an intermediate FCMP function definition that can be used as placeholders to store temporary terms with respect to the external data set. For more information, see the section "Describing the Objective Function" on page 388.

PRIMALIN=*SAS-data-set*
specifies an initial sample set to be evaluated. Initial data sets might be useful over a sequence of runs, when you want to ensure that PROC HPLSO generates points that are at least as good as your current best solution. This option is more general than the FIRSTGEN= option because points defined in this data set might or might not be used to define the initial population for the genetic algorithm (GA). For more details, see the section "Specifying and Returning Trial Points" on page 396.

QPSDATA=*SAS-data-set*
specifies a data set that can be used as a sparse alternative to the LINCON= option, which uses a dense format to define variables. Quadratic programming system (QPS) is a common file format for representing linear and mixed-integer mathematical programs with quadratic terms in the objective function. This option differs from the MPSDATA= option in that any quadratic terms in the objective can be included in the data set. Do not use this option if the problem does not have quadratic terms. For an example of using PROC OPTMODEL to create the corresponding QPS file, see "Example 17.3: Using QPS Format" on page 405. Internally, binary variables are converted into integer variables with lower and upper bounds of 0 and 1, respectively.

VARIABLES=*SAS-data-set*
stores the variable names, bounds, type, and scale. These names must match corresponding names, FCMP functions, and related data sets. For more information, see the section "The Variable Data Set" on page 387.

Output Data Set Options

You can specify the following *options* that are related to output data sets:

CACHEOUT=*SAS-data-set*
specifies the data set to which all completed function evaluations are output. For more information, see the section "Specifying and Returning Trial Points" on page 396.

LASTGEN=*SAS-data-set*
specifies the data set to which the members of the current genetic algorithm population are returned on exit. If more than one genetic algorithm is used, the data set combines the members from each population into a single data set.

PRIMALOUT=*SAS-data-set*
specifies the output solution set. You can use this data set in future solves as the input set for the PRIMALIN= option. For more information, see the section "Specifying and Returning Trial Points" on page 396.

Stopping Condition Options

You can specify the following *options* that determine when to stop optimization:

ABSFCONV=*r*[*n*]
specifies an absolute function convergence criterion. PROC HPLSO stops when the changes in the objective function and constraint violation values in successive iterations meet the following criterion:

$$|f(x^{(k-1)}) - f(x^{(k)})| + |\theta(x^{(k-1)}) - \theta(x^{(k)})| \leq r$$

where $\theta(x)$ denotes the maximum constraint violation at point x. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process is terminated. The default is *r*=1E–6 and *n*=10. To cause an early exit you must specify a value for *n* that is less than the value of the MAXGEN= option.

MAXFUNC=*i*
specifies the maximum number of function calls in the optimization process. The actual number of function evaluations can exceed this number in order to ensure deterministic results.

MAXGEN=*i*
specifies the maximum number of genetic algorithm iterations. The default is 500.

MAXTIME=*r*
specifies an upper limit on the real time (in seconds) used in the optimization process. The actual running time of PROC HPLSO optimization might be longer because the actual running time includes the remaining time needed to finish current function evaluations, time for the output of the (temporary) results, and (if required) the time for saving the results to appropriate data sets. By default, the MAXTIME= option is not used.

Optimization Control Options

You can specify the following *options* to tailor the solver to your specific optimization problem:

FEASTOL=r
specifies a feasibility tolerance for provided constraints. Specify $r \geq 0$. The default is *r*=1E–3.

NGLOBAL=*i*
specifies the number of genetic algorithms to create, with each algorithm working on a separate population of the size specified by the POPSIZE= option. Specify *i* as an integer greater than 0.

POPSIZE=*i*
specifies the population size used by the genetic algorithm. The default is $40 \times \text{ceil}(\log(n) + 1)$, where n denotes the number of variables.

Technical Options

You can specify the following technical *options*:

CACHEMAX=*i*
specifies the maximum number of points that can be cached. By default, PROC HPLSO automatically calculates the maximum number of points.

CACHETOL=*r*
specifies the cache tolerance to be used for caching and referencing previously evaluated points. For more information about this tolerance, see the section "Function Value Caching" on page 397. The value of *r* can be any number in the interval [0, 1]. The default is 1E–9.

LOGFREQ=*i*
specifies that the solution progress be printed to the iteration log after every *i* iterations if the value of the LOGLEVEL= option is greater than or equal to 0. The value *i*=0 disables the printing of the solution progress. The final iteration is always printed if $i \geq 1$ and LOGLEVEL is nonzero. The default is 1.

LOGLEVEL=0 | 1
controls the verbosity of the log file. If LOGLEVEL=0, nothing is printed. If LOGLEVEL=1, a short summary of the problem description and final solution status is printed. If LOGLEVEL=0, this option overrides the LOGFREQ= option. By default, LOGLEVEL=1.

PRINTLEVEL=0 | 1
specifies whether to print a summary of the problem and solution. If PRINTLEVEL=1, then the Output Delivery System (ODS) tables ProblemSummary, SolutionSummary, and PerformanceInfo are produced and printed. If PRINTLEVEL=0, then no ODS tables are produced. By default, PRINTLEVEL=1.

For more information about the ODS tables created by PROC HPLSO, see the section "ODS Tables" on page 399.

SEED=*i*
specifies a nonnegative integer as a seed value for the pseudorandom number generator. Pseudorandom numbers are used within the genetic algorithm.

PERFORMANCE Statement

PERFORMANCE *options* **;**

The PERFORMANCE statement defines performance parameters for distributed and multithreaded computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a High-Performance Analytics procedure.

You can also use the PERFORMANCE statement to control whether a High-Performance Analytics procedure executes in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics." PROC HPLSO uses threads and nodes to perform the evaluation process in parallel. When data are distributed, a

single evaluation is performed in parallel. Alternatively, if a function evaluation can be completed without communication, then the PROC FCMP evaluations are performed in parallel.

You can run the HPLSO procedure in grid mode without specifying the PERFORMANCE statement. For more information, see Chapter 3, "Shared Concepts and Topics."

The HPLSO procedure supports both the DETERMINISTIC and NONDETERMINISTIC values of the PARALLELMODE= option in the PERFORMANCE statement. The default is DETERMINISTIC. For more information about the PARALLELMODE= option, see Chapter 3, "Shared Concepts and Topics" (*SAS/OR User's Guide: Mathematical Programming*).

Details: HPLSO Procedure

The HPLSO procedure uses a hybrid combination of genetic algorithms (Goldberg 1989; Holland 1975), which optimize integer and continuous variables, and generating set search (Kolda, Lewis, and Torczon 2003), which optimizes the continuous variables to improve the robustness of both algorithms. Both genetic algorithms (GAs) and the generating set search (GSS) have proven to be effective algorithms for many classes of derivative-free optimization problems. When only continuous variables are present, a GA usually requires more function evaluations than a GSS to converge to a minimum. This is partly due to the GA's need to simultaneously perform a global search of the solution space. In a hybrid setting, the requirement for the GA to find accurate local minima can be relaxed, and internal parameters can be tuned toward finding promising starting points for the GSS.

The FCMP Procedure

The FCMP procedure is part of Base SAS software and can be used to encapsulate many SAS data steps. The HPLSO procedure uses PROC FCMP to provide a general gateway for describing nonlinear objective and constraint functions. (See the sections "Describing the Objective Function" on page 388 and "Describing Nonlinear Constraints" on page 393.) You can use most of the SAS programming statements and SAS functions that you can use in a DATA step to define FCMP functions and subroutines. However, there are a few differences in the capabilities of the DATA step and the FCMP procedure. See the documentation of the FCMP procedure to learn more. Further, not all FCMP functionality can be compiled and sent to the grid. In particular, the following FCMP functions are not supported: READ_ARRAY, WRITE_ARRAY, RUN_MACRO, and RUN_SASFILE.

After you define your objective and constraint functions, you must specify the libraries by using the CMPLIB= system option in the OPTIONS statement. For more information about the OPTIONS statement, see *SAS Statements: Reference*. For more information about the CMPLIB= system option, see *SAS System Options: Reference*.

The Variable Data Set

The variable data set can have up to five columns. The variable names are described in the _ID_ column. These names are used to map variable values to identically named FCMP function variable arguments.

Lower and upper bounds on the variables are defined in columns _LB_ and _UB_, respectively. You can manually enter scaling for each variable by using the column _SCALE_. Derivative-free optimization performance can often be greatly improved by scaling the variables appropriately. By default, the scale vector is defined in a manner similar to that described in Griffin, Kolda, and Lewis (2008). If integer variables are present, the _TYPE_ column value signifies that a given variable is either `C` for continuous or `I` for integer. By default, all variables are assumed to be continuous.

You can use the VARIABLES= option to specify the SAS data set that describes the variables to be optimized. For example, suppose you want to specify the following set of variables, where x_1 and x_2 are continuous and x_3 is an integer variable:

$$\begin{aligned} 0 &\leq x_1 \leq 1000 \\ 0 &\leq x_2 \leq .001 \\ 0 &\leq x_3 \leq 4 \end{aligned}$$

You can specify this set of variables with the following DATA step:

```
data vardata;
   input _id_ $ _lb_ _ub_ _type_ $;
   datalines;
x1  0 1000 C
x2  0 .001 C
x3  0 4    I
;
```

By default, variables are automatically scaled. PROC HPLSO uses this scaling along with the cache tolerance when PROC HPLSO builds the function value cache. For more information about scaling, see the section "Function Value Caching" on page 397. You can provide your own scaling by setting a _SCALE_ column in the variable data set as follows:

```
data vardata;
   input _id_ $ _lb_ _ub_ _type_ $ _scale_;
   datalines;
x1  0 1000 C  1000
x2  0 .001 C  .5
x3  0 4    I   2
;
```

When derivative-free optimization is performed, proper scaling of variables can dramatically improve performance. Default scaling takes into account the lower and upper bounds, so you are encouraged to provide the best estimates possible.

Describing the Objective Function

If your objective function is simple enough, PROC HPLSO enables you to define the function explicitly by using PROC FCMP. The following statements describe the objective function of "Example 17.4: Linear Constraints and a Nonlinear Objective" on page 407:

```
proc fcmp outlib=sasuser.myfuncs.mypkg;
   function sixhump(x1,x2);
      r = (4 - 2.1*x1**2 + x1**4/3)*x1**2 + x1*x2 + (-4 + 4*x2**2)*x2**2;
      return(r);
   endsub;
run;
```

PROC HPLSO also enables you to define your objective function implicitly by using a single external data set. To facilitate this process, PROC HPLSO requires the following additional information about how to construct the objective function:

- one or more FCMP functions that define what operations should be done on each row of the data
- a keyword that specifies how to combine the resulting vector of values (the size of the vector equals the number of rows in the data set)
- a final FCMP function that defines how the resulting building blocks of the objective should be aggregated

Consider the following unconstrained optimization problem, where k is a very large integer (for example, 10^6), $\mathbf{A}$ denotes a $k \times 5$ matrix, and $\mathbf{b}$ denotes the corresponding right-hand side target vector:

$$\min_{x \in \mathbb{R}^5} f(x) = \|Ax - b\|_2 + \|x\|_1$$

To evaluate the objective function, the following operations must be performed:

$$\begin{aligned} f_1(x) &= \sum_{i=1}^{k} d_i \\ f_2(x) &= \sum_{j=1}^{5} |x_i| \\ f(x) &= \sqrt{f_1(x)} + f_2(x), \end{aligned}$$

where

$$d_i = \left(-b_i + \sum_{j=1}^{5} a_{ij} x_j \right)^2$$

and a_{ij} denotes the jth entry of row i of the matrix $\mathbf{A}$. Assume that there is an existing SAS data set that stores numerical entries for $\mathbf{A}$ and $\mathbf{b}$. The following DATA step shows an example data set with $k = 3$:

```
data Abdata;
   input _id_ $ a1 a2 a3 a4 a5 b;
   datalines;
row1  1 2 3  4  5  6
row2  7 8 9 10 11 12
row3  13 14 15 16 17 18
;
```

The following statements pass this information to PROC HPLSO by adding the corresponding functions to the FCMP function library Sasuser.Myfuncs.Mypkg:

```
proc fcmp outlib=sasuser.myfuncs.mypkg;
   function axbi(x1,x2,x3,x4,x5,a1,a2,a3,a4,a5,b);
      array x[5] /nosym;
      array a[5] /nosym;
      x[1]=x1; x[2]=x2; x[3]=x3; x[4]=x4; x[5]=x5;
      a[1]=a1; a[2]=a2; a[3]=a3; a[4]=a4; a[5]=a5;
      di = -b;
      do j=1 to 5;
         di = di + a[j]*x[j];
      end;
      di = di*di;
      return (di);
   endsub;

   function onenorm(x1,x2,x3,x4,x5);
      array x[5] /nosym;
      x[1]=x1; x[2]=x2; x[3]=x3; x[4]=x4; x[5]=x5;
      f2 = 0;
      do j=1 to 5;
         f2 = f2 + abs(x[j]);
      end;
      return (f2);
   endsub;

   function combine(f1, f2);
      return (sqrt(f1)+f2);
   endsub;
```

The next DATA step then defines the objective name with a given target:

```
data lsqobj1;
   input _id_ $ _function_$ _sense_ $ _dataset_ $;
   datalines;
f1        axbi          .      Abdata
f2        onenorm       .      .
f         combine      min     .
;
```

The following DATA step declares the variables:

```
data xvar;
   input _id_ $ @@;
   datalines;
   x1 x2 x3 x4 x5
   ;
```

The following statements call the HPLSO procedure:

```
options cmplib=sasuser.myfuncs;
proc hplso
   variables = xvar
   objective = lsqobj1;
run;
```

The contents of the OBJECTIVE= data set (lsqobj1) direct PROC HPLSO to search for the three FCMP functions AXBI, ONENORM, and COMBINE in the library that is specified by the CMPLIB= option. The missing values in the _SENSE_ columns indicate that AXBI and ONENORM are intermediate functions to be used as arguments of the objective function COMBINE which is of type MIN. Of the three FCMP functions, only F1 has requested data. The entry Abdata specifies that the FCMP function AXBI should be called on each row of the data set Abdata, and that the results should be summed. This value is then specified as the first argument to the FCMP function COMBINE.

In this example, Abdata is a data set that comes from the Work library. However, Abdata could just as easily come from a data set in a user-defined library or even a data set that had been previously distributed on a High-Performance Analytics appliance (such as Teradata or Greenplum). If the data set Abdata is stored in a different library, replace **Abdata** by **libref.Abdata** in the data set lsqob1. The source of the data set is irrelevant to PROC HPLSO.

You can omit F2 if you want to form the one-norm directly in the aggregate function. Thus, an equivalent formulation would be as follows:

```
proc fcmp outlib=sasuser.myfuncs.mypkg;
   function combine2(x1,x2,x3,x4,x5, f1);
      array x[5] /nosym;
      x[1]=x1; x[2]=x2; x[3]=x3; x[4]=x4; x[5]=x5;
      f2 = 0;
      do j=1 to 5;
         f2 = f2 + abs(x[j]);
      end;
      return (sqrt(f1)+f2);
   endsub;
```

In this case, you define the objective name with a given target in a data set:

```
data lsqobj2;
   input _id_ $ _function_$ _sense_ $ _dataset_ $;
   datalines;
f1        axbi          .          Abdata
f         combine2     min         .
;

options cmplib=sasuser.myfuncs;
proc hplso
   variables = xvar
   objective = lsqobj2;
run;
```

Thus, any of the intermediate functions used within the OBJECTIVE= data set (objdata) are permitted to have arguments that form a subset of the variables that are listed in the VARIABLES= data set (xvar) and the numerical columns from the data set that is specified in the _DATASET_ column of the OBJECTIVE= data set. Only numerical values are supported from external data sets. Only one function can be of type MIN or MAX. This function can take as arguments any of the variables listed in the VARIABLES= data set, any of the numerical columns from an external data set for the objective (if specified), and any implicit variables listed in the _ID_ column of the OBJECTIVE= data set.

The following rules for the objective data set are used during parsing:

- Only one data set can be used for a given problem definition.
- The objective function can take as input a data set only if no intermediate functions are being used. Otherwise, only the intermediate functions can be linked to the corresponding data set.
- Intermediate functions cannot take the objective function ID as an argument. This could create circular dependencies.

The data set is used in a distributed format either if the NODES= option is specified in the PERFORMANCE statement or if the data set is a distributed library.

Describing Linear Constraints

The preferred method for describing linear constraints is to use the LINCON=, MPSDATA=, or QPSDATA= option. Linear constraints should not be described by using the NLINCON= option because they are treated as black-box constraints and can degrade performance.

If you have only a few variables and linear constraints, you might prefer the dense format for describing your linear constraints by using the LINCON= option in conjunction with the VARIABLES= option. Suppose a problem has the following linear constraints:

$$\begin{aligned} -1 \leq \quad & 2x_1 - 4x_3 \quad && \leq 15 \\ 1 \leq \quad & -3x_1 + 7x_2 \quad && \leq 13 \\ & x_1 + x_2 + x_3 \quad && = 11 \end{aligned}$$

The following DATA step formulates this information as an input data set for PROC HPLSO:

```
data lcondata;
   input _id_ $ _lb_ x1-x3 _ub_;
   datalines;
a1 -1    2 0 -4 15
a2  1   -3 7  0 13
a3  11   1 1  1 11
;
```

Linear constraints are handled by using tangent search directions that are defined with respect to nearby constraints. The metric used to determine when a constraint is sufficiently near might cause the algorithm to temporarily treat range constraints as equality constraints. For this reason, it is preferable that you do not separate a range constraint into two inequality constraints. For example, although both

$$-1 \leq \quad 2x_1 - 4x_3 \quad \leq 15$$

and

$$\begin{aligned} & 2x_1 - 4x_3 \quad && \leq 15 \\ -1 \leq \quad & 2x_1 - 4x_3 \end{aligned}$$

are equivalent, the former range constraint formulation is preferred.

Even for a moderate number of variables and constraints, describing the linear constraints via dense format can be burdensome. As an alternative, you can construct a sparse formulation by using MPS-format and QPS-format SAS data sets and the MPSDATA= option in PROC HPLSO. For more information about these data sets, see Chapter 14, "The MPS-Format SAS Data Set" (*SAS/OR User's Guide: Mathematical Programming*). These data sets can easily be created by using the OPTMODEL procedure, as demonstrated in "Example 17.1: Using Dense Format" on page 401 and "Example 17.2: Using MPS Format" on page 403. The OPTMODEL procedure is documented in Chapter 4, "The OPTMODEL Procedure" (*SAS/OR User's Guide: Mathematical Programming*).

In sparse formulation, if you provide objective data, they are used in conjunction with the provided FCMP function definitions. Thus a problem of the following form is solved, where c is defined within the provided MPS data set:

$$\begin{array}{rlcccl} \min & & & f(x) + c^T x & & \\ \text{subject to} & x_\ell & \le & x & \le & x_u \\ & b_\ell & \le & Ax & \le & b_u \\ & g_\ell & \le & g(x) & \le & g_u \\ & x_i & \in & \mathbb{Z},\ i \in \mathcal{I}. & & \end{array}$$

If the problem has quadratic terms, you can use the QPSDATA= option. In this case, the data are used in conjunction with the provided FCMP function definition. Thus, a problem of the following form is solved, where c, Q, and the constant term K are defined within the provided data set:

$$\begin{array}{rlcccl} \min & & & f(x) + c^T x + \frac{1}{2} x^T Q x + K & & \\ \text{subject to} & x_\ell & \le & x & \le & x_u \\ & b_\ell & \le & Ax & \le & b_u \\ & g_\ell & \le & g(x) & \le & g_u \\ & x_i & \in & \mathbb{Z},\ i \in \mathcal{I}. & & \end{array}$$

The MPS standard does not support constant terms; thus any constant term defined in PROC OPTMODEL is naturally dropped and not included in the corresponding data set. For more information about creating MPS data sets with PROC OPTMODEL, see *SAS/OR User's Guide: Mathematical Programming*.

Describing Nonlinear Constraints

Nonlinear constraints are treated as black-box functions and are described by using the FCMP procedure. You should use the NLINCON= option to provide PROC HPLSO with the corresponding FCMP function names and lower and upper bounds. Suppose a problem has the following nonlinear constraints:

$$\begin{array}{rcl} -1 \le & x_1 x_2 x_3 + \sin(x_2) & \le 1 \\ & x_1 x_2 + x_1 x_3 + x_2 x_3 & = 1 \end{array}$$

The following statements pass this information to PROC HPLSO by adding two corresponding functions to the FCMP function library, Sasuser.Myfuncs.Mypkg:

```
proc fcmp outlib=sasuser.myfuncs.mypkg;
   function con1(x1, x2, x3);
      return (x1*x2*x3 + sin(x2));
   endsub;
   function con2(x1, x2, x3);
      return (x1*x2 + x1*x3 + x3*x3);
   endsub;
```

Next, the following DATA step defines nonlinear constraint names and provides their corresponding bounds in the data set condata:

```
data condata;
   input _id_ $ _lb_ _ub_;
   datalines;
con1 -1 1
con2  1 1
;
```

Finally, you can call PROC HPLSO and specify NLINCON=CONDATA. For another example with nonlinear constraints, see "Example 17.5: Using Nonlinear Constraints" on page 408.

The HPLSO Algorithm

The HPLSO algorithm is based on a genetic algorithm (GA). GAs are a family of local search algorithms that seek optimal solutions to problems by applying the principles of natural selection and evolution. Genetic algorithms can be applied to almost any optimization problem and are especially useful for problems for which other calculus-based techniques do not work, such as when the objective function has many local optima, when the objective function is not differentiable or continuous, or when solution elements are constrained to be integers or sequences. In most cases, genetic algorithms require more computation than specialized techniques that take advantage of specific problem structures or characteristics. However, for optimization problems with no such techniques available, genetic algorithms provide a robust general method of solution.

In general, genetic algorithms use some variation of the following process to search for an optimal solution:

initialization: An initial population of solutions is randomly generated, and the objective function is evaluated for each member of this initial iteration.

selection: Individual members of the current iteration are chosen stochastically either to parent the next iteration or to be passed on to it such that the members that are the fittest are more likely to be selected. A solution's fitness is based on its objective value, with better objective values reflecting greater fitness.

crossover: Some of the selected solutions are passed to a crossover operator. The crossover operator combines two or more parents to produce new offspring solutions for the next iteration. The crossover operator tends to produce new offspring that retain the common characteristics of the parent solutions while combining the other traits in new ways. In this way, new areas of the search space are explored while attempting to retain optimal solution characteristics.

mutation: Some of the next-iteration solutions are passed to a mutation operator, which introduces random variations in the solutions. The purpose of the mutation operator is to ensure that the solution space is adequately searched to prevent premature convergence to a local optimum.

repeat: The current iteration of solutions is replaced by the new iteration. If the stopping criterion is not satisfied, the process returns to the *selection* phase.

The crossover and mutation operators are commonly called *genetic operators*. Selection and crossover distinguish genetic algorithms from a purely random search and direct the algorithm toward finding an optimum.

There are many ways to implement the general strategy just outlined, and it is also possible to combine the genetic algorithm approach with other heuristic solution improvement techniques. In the traditional genetic algorithm, the solutions space is composed of bit strings, which are mapped to an objective function, and the genetic operators are modeled after biological processes. Although there is a theoretical foundation for the convergence of genetic algorithms formulated in this way, in practice most problems do not fit naturally into this paradigm. Modern research has shown that optimizations can be set up by using the natural solution domain (for example, a real vector or integer sequence) and applying crossover and mutation operators that are analogous to the traditional genetic operators but are more appropriate to the natural formulation of the problem.

Although genetic algorithms have been demonstrated to work well for a variety of problems, there is no guarantee of convergence to a global optimum. Also, the convergence of genetic algorithms can be sensitive to the choice of genetic operators, mutation probability, and selection criteria, so that some initial experimentation and fine-tuning of these parameters is often required.

The HPLSO procedure seeks to automate this process by using hybrid optimization in which several genetic algorithms can run in parallel and each algorithm is initialized with different default option settings. PROC HPLSO also adds a step to the GA; this step permits generating set search (GSS) algorithms to be used on a selected subset of the current population. GSS algorithms are designed for problems with continuous variables and have the advantage that, in practice, they often require significantly fewer evaluations than GAs to converge. Furthermore, GSS can provide a measure of local optimality that is very useful when performing multimodal optimization.

The following additional "growth steps" are used whenever continuous variables are present:

local search selection: A small subset of points are selected based upon their fitness score and distance to (1) other points and (2) preexisting locally optimal points.

local search optimization: Local search optimization begins concurrently for each point selected. The only modification made to the original optimization problem is that the variables' lower and upper bounds are modified to temporarily fix integer variables to their current setting.

These additional growth steps are performed for each iteration; they permit selected members of the population (based on diversity and fitness) to benefit from local optimization over the continuous variables. If only integer variables are present, this step is not used.

Specifying and Returning Trial Points

You can use the following options to initialize PROC HPLSO with user-specified points: CACHEIN=, FIRSTGEN=, and PRIMALIN=. You can use the following options to have trial points returned to you: CACHEOUT=, LASTGEN=, and PRIMALOUT=.

Both input and output point data sets have the following columns:

SOL
specifies the point's unique solution tag.

_ID_
specifies the variable and (function) ID name.

VALUE
specifies the variable (function) value.

Input Data Sets

The following DATA step generates 30 random points for the initial population if the variables $x \in \mathbb{R}^5$ have bounds $-5 \leq x_i \leq 10$:

```
data popin;
   low = -5.0;
   upp = 10.0;
   numpoints = 30;
   dim = 5;
   do _sol_=1 to numpoints;
      do i=1 to dim;
         _id_= compress("x" || put(i, 4.0));
         _value_ = low + (upp-low)*ranuni(2);
         output;
```

```
      end;
   end;
   keep _sol_ _id_ _value_;
run;
```

You can then use this data set as input for the HPLSO procedure by using the FIRSTGEN= option.

Output Data Sets

PROC HPLSO dynamically creates and reports on two metadata functions for you: the true objective (which is a combination of the FCMP objective and the linear and quadratic terms) and the maximum constraint violation. These functions are assigned the following function ID names (therefore, these names should not be used as variable, constraint, or function names):

OBJ
specifies the point's objective.

INF
specifies the point's maximum constraint violation.

Output data sets have additional rows that correspond to the problem's FCMP functions. These rows must exist for the CACHEIN= data sets, but they should be omitted for the FIRSTGEN= and PRIMALIN= data sets.

When you observe the solution output, it might be easier to compare points if they are listed as rows, rather than as columns. SAS provides a variety of ways to transform the results for your purposes. For example, if you prefer that the rows of the data sets correspond to individual points, you can use the following statements to transpose the returned data set, where popout denotes the data set returned by PROC HPLSO:

```
proc transpose data=popout out=poprow label=_sol_ name=_sol_;
   by _sol_;
   var _value_;
   id _id_;
run;
```

Function Value Caching

To improve performance, the HPLSO procedure has implemented a caching system. This caching system helps reduce the overall workload of the solver by eliminating duplicate function evaluations. As the individual optimizers (citizens) submit new trial points for evaluation, the points are saved in the cache along with their function evaluation values. Then, before beginning the potentially expensive function evaluations for a new trial point, PROC HPLSO determines whether a similar point already exists within the cache. If a similar point is found in the cache, its function values are immediately returned for the newly submitted point. Returning function values from the cache instead of duplicating the effort of computing new function values can lead to significant performance improvements for the overall procedure.

The cache is implemented as a splay tree, similar to that used in Gray and Kolda (2006); Hough, Kolda, and Patrick (2000). The splay tree rebalances itself as new points are added to the cache. This rebalancing ensures that recently added or accessed points are maintained at the root of the tree and are therefore available for quick retrieval. This splay tree data structure lends itself nicely to the needs of a caching system.

When determining whether a newly submitted trial point has a similar point already in the cache, PROC HPLSO compares the new trial point to all previous trial points by using the CACHETOL= value that is specified as an option in the PROC HPLSO statement. This value specifies a tolerance to use when comparing two points and determining whether the two points are similar enough. In addition to the CACHETOL= value, the cache comparison also takes into account the _SCALE_ values that are specified as part of the variable data set that is specified in the VARIABLES= option.

Two points x and y are considered *cache equivalent* if

$$|x_i - y_i| \leq s_i \epsilon, \text{ for } i = 1, \ldots, n$$

where s denotes the corresponding scaling vector. Thus, if a point x has been evaluated (or is being evaluated) and a point y is submitted for evaluation and satisfies the preceding criteria, y is "cache evaluated" instead of being evaluated directly. In this case, y is associated with $f(x)$ and $c(x)$. Although the splay tree is very efficient, the cache lookup time for quick evaluation might eventually dominate the evaluation process time. You can use the CACHEMAX= option to limit the size of the cache.

Even without FCMP functions defined, the cache system helps to avoid redundant computations when the linear constraints are explicitly handled.

Iteration Log

The iteration log provides detailed information about the progress of the HPLSO procedure. The log appears by default or if LOGLEVEL=1. The iteration log provides the following information:

Iterations	Displays the number of genetic algorithm iterations completed.
Best Objective	Displays the best objective found at each iteration with respect to the current setting of the FEASTOL= option.
Infeasibility	Displays the aggregate constraint violation of the current best point.
Evals	Displays the cumulative number of function evaluations.
Time	Displays the time needed to achieve current best solution.

Procedure Termination Messages

After PROC HPLSO terminates, one of the following messages is displayed:

User interrupted.
The procedure was interrupted by the user.

Function convergence criteria reached.
The best objective value and feasibility have not sufficiently improved for the specified number of iterations. This criterion is a typical exit state if the global optimum is reached early in the algorithm.

Maximum function evaluations reached.
PROC HPLSO has attempted to exceed the maximum number of function evaluations.

Generations complete.
The maximum number of GA generations (iterations) has been reached. At this point, no new points are generated, and the algorithm exits.

Maximum time reached.
PROC HPLSO has attempted to exceed the maximum time allotted.

Problem may be unbounded.
The objective value appears to take on arbitrarily large values at points that satisfy the feasibility tolerance.

Infeasible.
The problem is infeasible.

Failed.
The algorithm exited for any reason other than the above. For example, this message is returned if the provided FCMP function does not exist or cannot be evaluated.

ODS Tables

PROC HPLSO creates three Output Delivery System (ODS) tables by default. The first table, ProblemSummary, is a summary of the input problem. The second table, SolutionSummary, is a brief summary of the solution status. The third table, PerformanceInfo, is a summary of performance options. You can use ODS table names to select tables and create output data sets. For more information about ODS, see *SAS Output Delivery System: Procedures Guide*.

If you specify the DETAILS option in the PERFORMANCE statement, then the Timing table is also produced.

Table 17.4 lists all the ODS tables that can be produced by the HPLSO procedure, along with the statement and option specifications required to produce each table.

Table 17.4 ODS Tables Produced by PROC HPLSO

ODS Table Name	Description	Statement	Option
ProblemSummary	Summary of the input LP problem	PROC HPLSO	PRINTLEVEL=1 (default)
SolutionSummary	Summary of the solution status	PROC HPLSO	PRINTLEVEL=1 (default)
PerformanceInfo	List of performance options and their values	PROC HPLSO	PRINTLEVEL=1 (default)
Timing	Detailed solution timing	PERFORMANCE	DETAILS

Macro Variable _ORHPLSO_

The HPLSO procedure defines a macro variable named _ORHPLSO_. This variable contains a character string that indicates the status of the procedure upon termination. The contents of the macro variable are interpreted as follows.

STATUS
indicates the procedure's status at termination. It can take one of the following values:

OK	The procedure terminated normally.
SYNTAX_ERROR	The use of syntax is incorrect.
DATA_ERROR	The input data are inconsistent.
OUT_OF_MEMORY	Insufficient memory was allocated to the procedure.
IO_ERROR	A problem in reading or writing of data has occurred.
SEMANTIC_ERROR	An evaluation error, such as an invalid operand type, has occurred.
ERROR	The status cannot be classified into any of the preceding categories.

SOLUTION_STATUS
indicates the status of the solution at termination. It can take one of the following values:

ABORTED	The user signaled that the procedure should terminate.
ABSFCONV	The procedure terminated on the absolute function convergence criterion.
INFEASIBLE	Problem is infeasible.
MAXFUNC	The procedure terminated on the maximum number of function evaluations.
MAXGEN	The maximum number of genetic algorithm iterations was completed.
MAXTIME	The maximum time limit was reached.
UNBOUNDED	The problem might be unbounded.
FAILED	The status cannot be classified into any of the preceding categories.

OBJECTIVE
indicates the objective value that is obtained by the procedure at termination.

INFEASIBILITY
indicates the level of infeasibility of the constraints at the solution.

EVALUATIONS
indicates the total number of evaluations that were not cached.

ITERATIONS
indicates the number of iterations that were required to solve the problem.

SETUP_TIME
indicates the real time (in seconds) taken to set up the optimization problem and distribute data.

SOLUTION_COUNT
indicates number of solutions returned in the PRIMALIN= data set if that option was specified.

SOLUTION_TIME
indicates the real time (in seconds) taken by the procedure to perform iterations for solving the problem.

Examples: HPLSO Procedure

Example 17.1: Using Dense Format

This example uses data from Floudas and Pardalos (1992) and illustrates how to use the VARIABLES= and LINCON= options in conjunction with the OBJECTIVE= option. The problem has nine linear constraints and a quadratic objective function. Suppose you want to minimize

$$f(x) = 5\sum_{i=1}^{4} x_i - 5\sum_{i=1}^{4} x_i^2 - \sum_{i=5}^{13} x_i$$

subject to

$$\begin{aligned}
&2x_1 + 2x_2 + x_{10} + x_{11} \le 10\\
&2x_1 + 2x_3 + x_{10} + x_{12} \le 10\\
&2x_1 + 2x_3 + x_{11} + x_{12} \le 10\\
&-8x_1 + x_{10} \le 0\\
&-8x_2 + x_{11} \le 0\\
&-8x_3 + x_{12} \le 0\\
&-2x_4 - x_5 + x_{10} \le 0\\
&-2x_6 - x_7 + x_{11} \le 0\\
&-2x_8 - x_9 + x_{12} \le 0
\end{aligned}$$

and

$$\begin{aligned}
&0 \le x_i \le 1, && i = 1, 2, \ldots, 9\\
&0 \le x_i \le 100, && i = 10, 11, 12\\
&0 \le x_{13} \le 1
\end{aligned}$$

The following statements use the dense format to define the linear constraints:

```
data vardata;
   input _id_ $ _lb_ _ub_;
   datalines;
 x1 0   1
 x2 0   1
 x3 0   1
```

```
 x4 0   1
 x5 0   1
 x6 0   1
 x7 0   1
 x8 0   1
 x9 0   1
x10 0 100
x11 0 100
x12 0 100
x13 0   1
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function quadobj(x1,x2,x3,x4,x5,x6,x7,x8,x9,x10,x11,x12,x13);
      sum1 = 5*(x1 + x2 + x3 + x4);
      sum2 = 5*(x1**2 + x2**2 + x3**2 + x4**2);
      sum3 = (x5 + x6 + x7 + x8 + x9 + x10 + x11 + x12 + x13);
      return (sum1 - sum2 - sum3);
   endsub;
run;

data objdata;
   input _id_ $ _function_ $ _sense_ $;
   datalines;
f   quadobj   min
;

data lindata;
   input _id_ $ _lb_ x1-x13 _ub_;
   datalines;
a1 .  2  2  0  0  0  0  0  0  0 1 1 0 0 10
a2 .  2  0  2  0  0  0  0  0  0 1 0 1 0 10
a3 .  2  0  2  0  0  0  0  0  0 0 1 1 0 10
a4 . -8  0  0  0  0  0  0  0  0 1 0 0 0  0
a5 .  0 -8  0  0  0  0  0  0  0 0 1 0 0  0
a6 .  0  0 -8  0  0  0  0  0  0 0 0 1 0  0
a7 .  0  0  0 -2 -1  0  0  0  0 1 0 0 0  0
a8 .  0  0  0  0  0 -2 -1  0  0 0 1 0 0  0
a9 .  0  0  0  0  0  0  0 -2 -1 0 0 1 0  0
;

options cmplib = sasuser.myfuncs;
proc hplso
   objective = objdata
   variables = vardata
   lincon    = lindata;
run;
```

The VARIABLES=VARDATA option in the PROC HPLSO statement specifies the variables and their respective bounds. The objective function is defined using PROC FCMP, and the objective function name, QUADOBJ, and other properties are described in the SAS data set objdata. The linear constraints are specified using the SAS data set lindata in which each row stores the (zero and nonzero) coefficients of the corresponding linear constraint along with their respective lower and upper bounds. The problem description is then passed to the HPLSO procedure by using the options VARIABLES=VARDATA,

OBJECTIVE=OBJDATA, and LINCON=LINDATA.

Output 17.1.1 shows the output from running these statements.

Output 17.1.1 Using Dense Format

```
                Performance Information

            Execution Mode       On client
            Number of Threads    2
            Parallel Mode        Deterministic


                    Problem Summary

        Name                                  Value

        Problem Type                          NLP
        Variables                             13
        Integer Variables                     0
        Continuous Variables                  13
        Implicit Variables                    0
        Linear Constraints                    9
        Nonlinear Constraints                 0
        Linear Objective Coefficients         0
        Quadratic Objective Coefficients      0
        FCMP functions                        1


                    Solution Summary

        Name                    Value

        Status                  Function convergence
        Objective               -15.0009214
        Infeasibility           0.0009211734
        Iterations              22
        Evaluations             3393
        Cached Evaluations      1326
        Nglobal                 1
        Popsize                 160
        Seed                    1
```

Example 17.2: Using MPS Format

In this example, the linear component of the same problem definition as in Example 17.1 is described by using the OPTMODEL procedure and is saved as an MPS data set. The quadratic objective is then defined using the FCMP function QUADOBJ.

Because PROC OPTMODEL outputs an MPS data set that uses array notation, you can use the following macro definition to strip brackets from the resulting data set.

```
%macro lsompsmod(setold,setnew);
   data &setnew(drop=i);
      set &setold;
      array FC{*} _CHARACTER_;
      do i=1 to dim(FC);
         FC[i] = compress(FC[i], "[]");
      end;
   run;
%mend;
```

For more complicated array structures, take care to ensure that the resulting transformation is well defined.

```
proc optmodel;
   num nItems = 13;
   set<num> Items = {1..nItems};
   var x{Items} >= 0;
   for {i in Items} x[i].ub = 1;
   for {i in 10..12} x[i].ub = 100;
   min z = 0;
   con a1: 2*x[1] + 2*x[2] + x[10] + x[11] <= 10;
   con a2: 2*x[1] + 2*x[3] + x[10] + x[12] <= 10;
   con a3: 2*x[1] + 2*x[3] + x[11] + x[12] <= 10;
   con a4: -8*x[1] + x[10] <= 0;
   con a5: -8*x[2] + x[11] <= 0;
   con a6: -8*x[3] + x[12] <= 0;
   con a7: -2*x[4] - x[5] + x[10] <= 0;
   con a8: -2*x[6] - x[7] + x[11] <= 0;
   con a9: -2*x[8] - x[9] + x[12] <= 0;
   save mps lindataOld;
quit;

%lsompsmod(lindataOld, lindata);

proc hplso
   mpsdata   = lindata
   objective = objdata;
run;
```

Output 17.2.1 shows the output from running these statements.

Output 17.2.1 Using MPS Format

```
                Performance Information

Execution Mode       On client
Number of Threads    2
Parallel Mode        Deterministic
```

Output 17.2.1 *continued*

Problem Summary

Name	Value
Problem Type	NLP
Variables	13
Integer Variables	0
Continuous Variables	13
Implicit Variables	0
Linear Constraints	9
Nonlinear Constraints	0
Linear Objective Coefficients	0
Quadratic Objective Coefficients	0
FCMP functions	1

Solution Summary

Name	Value
Status	Function convergence
Objective	-15.0009214
Infeasibility	0.0009211734
Iterations	22
Evaluations	3393
Cached Evaluations	1326
Nglobal	1
Popsize	160
Seed	1

Example 17.3: Using QPS Format

In this example, the entire problem definition is first described in PROC OPTMODEL and is then saved as a QPS data set. In this case, no FCMP function needs to be defined.

```
proc optmodel;
   num nItems = 13;
   set<num> Items = {1..nItems};
   var x{Items} >= 0;
   for {i in Items} x[i].ub = 1;
   for {i in 10..12} x[i].ub = 100;
   min z = 5*sum{i in 1..4} x[i]
      - 5*sum{i in 1..4} x[i]**2 - sum{i in 5..13} x[i];
   con a1: 2*x[1] + 2*x[2] + x[10] + x[11] <= 10;
   con a2: 2*x[1] + 2*x[3] + x[10] + x[12] <= 10;
   con a3: 2*x[1] + 2*x[3] + x[11] + x[12] <= 10;
   con a4: -8*x[1] + x[10] <= 0;
   con a5: -8*x[2] + x[11] <= 0;
   con a6: -8*x[3] + x[12] <= 0;
   con a7: -2*x[4] - x[5] + x[10] <= 0;
   con a8: -2*x[6] - x[7] + x[11] <= 0;
```

```
   con a9: -2*x[8] - x[9] + x[12] <= 0;
   save qps qpdata;
quit;

proc hplso
   qpsdata = qpdata;
run;
```

Output 17.3.1 shows the output from running these statements.

Output 17.3.1 Using QPS Format

Performance Information

Execution Mode	On client
Number of Threads	2
Parallel Mode	Deterministic

Problem Summary

Name	Value
Problem Type	QP
Variables	13
Integer Variables	0
Continuous Variables	13
Implicit Variables	0
Linear Constraints	9
Nonlinear Constraints	0
Linear Objective Coefficients	13
Quadratic Objective Coefficients	4
FCMP functions	0

Solution Summary

Name	Value
Status	Function convergence
Objective	-15.0009214
Infeasibility	0.0009211734
Iterations	22
Evaluations	3393
Cached Evaluations	1326
Nglobal	1
Popsize	160
Seed	1

Example 17.4: Linear Constraints and a Nonlinear Objective

The problem in this example is to minimize the six-hump camel-back function (Michalewicz 1996, Appendix B). Minimize

$$f(x) = \left(4 - 2.1x_1^2 + \frac{x_1^4}{3}\right) x_1^2 + x_1 x_2 + \left(-4 + 4x_2^2\right) x_2^2$$

subject to

$$\begin{aligned} 2x_1 + x_2 &\leq 2 \\ x_1 + x_2 &\geq -2 \\ x_1 + 2x_2 &\geq -2 \end{aligned}$$

Providing derivative-free algorithms with good estimates for lower and upper bounds often greatly improves performance because it prevents the algorithm from unnecessarily sampling in regions that you do not want to be explored. For this problem, the following statements add the explicit variable bounds $-2 \leq x_1 \leq 2$ and $-2 \leq x_2 \leq 2$:

```
data xbnds;
   input _id_ $ _lb_ _ub_;
   datalines;
x1 -2 2
x2 -2 2
;

data lindata;
   input _id_ $ _lb_ x1 x2 _ub_;
   datalines;
a1   . 2 1 2
a2  -2 1 1 .
a3  -2 1 2 .
;

data objdata;
   input _id_ $ _function_ $ _sense_ $;
   datalines;
f   sixhump     min
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function sixhump(x1,x2);
      r = (4 - 2.1*x1**2 + x1**4/3)*x1**2 + x1*x2 + (-4 + 4*x2**2)*x2**2;
      return(r);
   endsub;
run;

options cmplib = sasuser.myfuncs;
proc hplso
   variables = xbnds
   objective = objdata
   lincon    = lindata;
run;
```

Output 17.4.1 shows the output from running these statements.

Output 17.4.1 Linear Constraints and a Nonlinear Objective

Performance Information

Execution Mode	On client
Number of Threads	2
Parallel Mode	Deterministic

Problem Summary

Name	Value
Problem Type	NLP
Variables	2
Integer Variables	0
Continuous Variables	2
Implicit Variables	0
Linear Constraints	3
Nonlinear Constraints	0
Linear Objective Coefficients	0
Quadratic Objective Coefficients	0
FCMP functions	1

Solution Summary

Name	Value
Status	Function convergence
Objective	-1.031628449
Infeasibility	0
Iterations	32
Evaluations	1884
Cached Evaluations	329
Nglobal	1
Popsize	80
Seed	1

Example 17.5: Using Nonlinear Constraints

The following optimization problem is discussed in Haverly (1978); Liebman et al. (1986). This example illustrates how to use PROC FCMP to define nonlinear constraints and use an MPS data set to define linear constraints. Minimize

$$f(x) = 9x_1 + 15x_2 - 6x_3 - 16x_4 - 10x_5;$$

subject to

$$
\begin{aligned}
& x_3 + x_4 = x_6 + x_7 \\
& x_6 + x_8 = x_1 \\
& x_7 + x_9 = x_2 \\
& x_8 + x_9 = x_5 \\
& 2.5x_1 - x_{10}x_6 - 2x_8 \geq 0 \\
& 1.5x_2 - x_{10}x_7 - 2x_9 \geq 0 \\
& 3x_3 + x_4 - x_{10}(x_3 + x_4) = 0
\end{aligned}
$$

and

$$
\begin{aligned}
& 0 \leq x_1 \leq 100 \\
& 0 \leq x_2 \leq 200 \\
& 1 \leq x_{10} \leq 3 \\
& 0 \leq x_i, \text{ for } i = 3, \ldots, 9
\end{aligned}
$$

In this example, the linear component of the problem definition is first described in PROC OPTMODEL and then saved as an MPS data set. Because the objective is linear, no FCMP objective function needs to be used. In the second section of statements, the nonlinear constraints are defined using FCMP functions, and their corresponding names and lower and upper bounds are stored in the data set condata. The HPLSO procedure is then called with the options NLINCON=CONDATA and MPSDATA=NLCEX.

```
proc optmodel;
   num nItems = 10;
   set<num> Items = {1..nItems};
   var x{Items} >= 0;
   x[10].lb = 1;
   x[10].ub = 3;
   x[1].ub = 100;
   x[2].ub = 200;
   con x[3] + x[4] = x[6] + x[7],
   x[6] + x[8] = x[1],
   x[7] + x[9] = x[2],
   x[8] + x[9] = x[5];
   max f = 9*x[1] + 15*x[2] - 6*x[3] - 16*x[4] - 10*x[5];
   save mps nlcexOld;
quit;

%lsompsmod(nlcexOld, nlcex);

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function nlc1(x1,x6,x8,x10);
      return (2.5*x1 - x10*x6 - 2*x8);
   endsub;
   function nlc2(x2,x7,x9,x10);
      return (1.5*x2 - x10*x7 - 2*x9);
   endsub;
   function nlc3(x3,x4,x10);
      return (3*x3 + x4 - x10*(x3 + x4));
   endsub;
run;
```

```
data condata;
   input _id_ $ _lb_ _ub_;
   datalines;
nlc1 0 .
nlc2 0 .
nlc3 0 0
;

options cmplib = sasuser.myfuncs;
proc hplso
   mpsdata   = nlcex
   nlincon   = condata
   logfreq   = 10;
run;
```

Output 17.5.1 shows the ODS tables that are produced.

Output 17.5.1 Using Nonlinear Constraints: ODS Tables

Performance Information

Execution Mode	On client
Number of Threads	2
Parallel Mode	Deterministic

Problem Summary

Name	Value
Problem Type	NLP
Variables	10
Integer Variables	0
Continuous Variables	10
Implicit Variables	0
Linear Constraints	4
Nonlinear Constraints	3
Linear Objective Coefficients	5
Quadratic Objective Coefficients	0
FCMP functions	3

Solution Summary

Name	Value
Status	Function convergence
Objective	400.04952732
Infeasibility	0.000987404
Iterations	87
Evaluations	14177
Cached Evaluations	1189
Nglobal	1
Popsize	160
Seed	1

Output 17.5.2 shows the iteration log.

Output 17.5.2 Using Nonlinear Constraints: Log

```
NOTE: The HPLSO procedure is executing on the client.
NOTE: The HPLSO algorithm is using up to 2 threads.
NOTE: The problem has 10 variables (0 integer, 10 continuous).
NOTE: The problem has 7 constraints (4 linear, 3 nonlinear).
NOTE: The problem has 3 FCMP function definitions.
NOTE: The deterministic parallel mode is enabled.
                        Best
        Iteration       Objective    Infeasibility    Evals      Time
                1               0                0      240         0
               11       399.95527                0     1777         1
               21       400.00969    0.00082542599     3392         1
               31        400.0191    0.00096821324     5025         1
               41       400.02987    0.00097785263     6676         2
               51        400.0336    0.00095750196     8340         2
               61       400.03479    0.00097924191     9971         3
               71       400.04444     0.000841962    11544         3
               81       400.04953    0.00098740401    13164         4
               87       400.04953    0.00098740401    14177         4
NOTE: Function convergence criteria reached.
NOTE: There were 3 observations read from the data set WORK.CONDATA.
```

Example 17.6: Using External Data Sets

This example illustrates the use of external data sets that are specified in the OBJECTIVE= option. The Bard function (Moré, Garbow, and Hillstrom 1981) is a least squares problem with $n = 3$ parameters and $m = 15$ functions f_k;

$$f(x) = \frac{1}{2}\sum_{k=1}^{15} f_k^2(x), \quad x = (x_1, x_2, x_3)$$

where

$$f_k(x) = y_k - \left(x_1 + \frac{k}{v_k x_2 + w_k x_3}\right)$$

with $v_k = 16 - k$, $w_k = \min(u_k, v_k)$, and

$$y = (0.14, 0.18, 0.22, 0.25, 0.29, 0.32, 0.35, 0.39, 0.37, 0.58, 0.73, 0.96, 1.34, 2.10, 4.39)$$

The minimum function value $f(x^*)$ = 4.107E–3 occurs at the point $(0.08, 1.13, 2.34)$. The starting point $x^0 = (1, 1, 1)$ is used. In this example, the additional variable bounds $-1000 \le x_i \le 1000$ for $i = 1, 2, 3$ are added.

There are two approaches to specifying the objective function. The first approach assumes that the necessary data are stored within the FCMP function. In this case, you can specify the objective function without using an external data set, as follows:

```
data vardata;
   input _id_ $ _lb_ _ub_ ;
   datalines;
x1  -1000 1000
x2  -1000 1000
x3  -1000 1000
;

data objdata;
   input _id_ $ _function_ $ _sense_ $;
   datalines;
f   bard     min
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function bard(x1, x2, x3);
      array y[15] /nosym (.14 .18 .22 .25 .29 .32 .35 .39 .37 .58
      .73 .96 1.34 2.10 4.39);
      fx = 0;
      do k=1 to 15;
         vk = 16 - k;
         wk = min(k,vk);
         fxk = y[k] - (x1 + k/(vk*x2 + wk*x3));
         fx = fx + fxk**2;
      end;
      return (.5*fx);
   endsub;
run;

options cmplib = sasuser.myfuncs;
proc hplso
   variables = vardata
   objective = objdata;
run;
```

Output 17.6.1 shows the output from running these statements.

Output 17.6.1 Using External Data Sets (I)

Performance Information

Execution Mode	On client
Number of Threads	2
Parallel Mode	Deterministic

Output 17.6.1 *continued*

Problem Summary

Name	Value
Problem Type	NLP
Variables	3
Integer Variables	0
Continuous Variables	3
Implicit Variables	0
Linear Constraints	0
Nonlinear Constraints	0
Linear Objective Coefficients	0
Quadratic Objective Coefficients	0
FCMP functions	1

Solution Summary

Name	Value
Status	Function convergence
Objective	0.0041074417
Infeasibility	0
Iterations	73
Evaluations	6517
Cached Evaluations	1149
Nglobal	1
Popsize	120
Seed	1

This approach is cumbersome if the size of the required data increases. Furthermore, this approach is not possible if you are working in a distributed-data setting. As a second approach to specifying the objective function, PROC HPLSO provides an alternate data input gateway that is described in the OBJECTIVE= data set, as shown in the following statements:

```
data vardata;
   input _id_ $ _lb_ _ub_ ;
   datalines;
x1  -1000 1000
x2  -1000 1000
x3  -1000 1000
;

data barddata;
   k = _n_;
   input y @@;
   datalines;
.14 .18 .22 .25 .29 .32 .35 .39
.37 .58 .73 .96 1.34 2.10 4.39
;
```

```
data objdata;
   input _id_ $ _function_ $ _sense_ $ _dataset_ $;
   datalines;
fx   bard     min  barddata
;

proc fcmp outlib=sasuser.myfuncs.mypkg;
   function bard(x1, x2, x3, k, y);
      vk = 16 - k;
      wk = min(k,vk);
      fxk = y - (x1 + k/(vk*x2 + wk*x3));
      return (.5*fxk**2);
   endsub;
run;

options cmplib = sasuser.myfuncs;
proc hplso
   variables=vardata
   objective=objdata;
   performance nodes=2 host=&GRIDHOST install=&GRIDINSTALLLOC;
run;
```

Output 17.6.2 shows the output from running these statements.

Output 17.6.2 Using External Data Sets (II)

Performance Information

Host Node	<< your grid host >>
Install Location	<< your grid install location >>
Execution Mode	Distributed
Number of Compute Nodes	2
Number of Threads per Node	8
Parallel Mode	Deterministic

Problem Summary

Name	Value
Problem Type	NLP
Variables	3
Integer Variables	0
Continuous Variables	3
Implicit Variables	0
Linear Constraints	0
Nonlinear Constraints	0
Linear Objective Coefficients	0
Quadratic Objective Coefficients	0
FCMP functions	1
Input Data Set	barddata

Output 17.6.2 *continued*

Solution Summary

Name	Value
Status	Function convergence
Objective	0.0041074417
Infeasibility	0
Iterations	73
Evaluations	6517
Cached Evaluations	1149
Nglobal	1
Popsize	120
Seed	1

References

Floudas, C. A. and Pardalos, P. M. (1992), *Recent Advances in Global Optimization*, Princeton, NJ: Princeton University Press.

Goldberg, D. E. (1989), *Genetic Algorithms in Search, Optimization and Machine Learning*, Reading, MA: Addison-Wesley.

Gray, G., Fowler, K., and Griffin, J. (2010), "Hybrid Optimization Schemes for Simulation-Based Optimization," in *Procedia Computer Science*, 1349–1357.

Gray, G. A. and Fowler, K. R. (2011), "The Effectiveness of Derivative-Free Hybrid Methods for Black-Box Optimization," *International Journal of Mathematical Modeling and Numerical Optimization*, 2, 112–133.

Gray, G. A. and Kolda, T. G. (2006), "Algorithm 856: APPSPACK 4.0: Asynchronous Parallel Pattern Search for Derivative-Free Optimization," *ACM Transactions on Mathematical Software*, 32, 485–507.

Griffin, J., Fowler, K. R., Gray, G. A., and Hemker, T. (2011), "Derivative-Free Optimization via Evolutionary Algorithms Guiding Local Search (EAGLS) for MINLP," *Pacific Journal of Optimization*, 7, 425–443.

Griffin, J. D. and Kolda, T. G. (2010a), "Asynchronous Parallel Hybrid Optimization Combining DIRECT and GSS," *Optimization Methods and Software*, 25, 797–817.

Griffin, J. D. and Kolda, T. G. (2010b), "Nonlinearly Constrained Optimization Using Heuristic Penalty Methods and Asynchronous Parallel Generating Set Search," *Applied Mathematics Research Express*, 2010, 36–62.

Griffin, J. D., Kolda, T. G., and Lewis, R. M. (2008), "Asynchronous Parallel Generating Set Search for Linearly Constrained Optimization," *SIAM Journal on Scientific Computing*, 30, 1892–1924.

Haverly, C. A. (1978), "Studies of the Behavior of Recursion for the Pooling Problem," *SIGMAP Bulletin, Association for Computing Machinery*.

Holland, J. H. (1975), *Adaptation in Natural and Artificial Systems*, Ann Arbor: University of Michigan Press.

Hough, P. D., Kolda, T. G., and Patrick, H. A. (2000), *Usage Manual for APPSPACK 2.0*, Technical Report SAND2000-8843, Sandia National Laboratories, Albuquerque, New Mexico and Livermore, California.

Jones, D. R., Perttunen, C. D., and Stuckman, B. E. (1993), "Lipschitzian Optimization without the Lipschitz Constant," *Journal of Optimization Theory and Applications*, 79, 157–181.

Kolda, T. G., Lewis, R. M., and Torczon, V. (2003), "Optimization by Direct Search: New Perspectives on Some Classical and Modern Methods," *SIAM Review*, 45, 385–482.

Liebman, J., Lasdon, L., Schrage, L., and Waren, A. (1986), *Modeling and Optimization with GINO*, California: The Scientific Press.

Michalewicz, Z. (1996), *Genetic Algorithms + Data Structures = Evolution Programs*, New York: Springer-Verlag.

Moré, J. J., Garbow, B. S., and Hillstrom, K. E. (1981), "Testing Unconstrained Optimization Software," *ACM Transactions on Mathematical Software*, 7, 17–41.

Plantenga, T. (2009), *HOPSPACK 2.0 User Manual (v 2.0.2)*, Technical report, Sandia National Laboratories.

Taddy, M. A., Lee, H. K. H., Gray, G. A., and Griffin, J. D. (2009), "Bayesian Guided Pattern Search for Robust Local Optimization," *Technometrics*, 51(4), 389–401.

Chapter 18
The HPNEURAL Procedure

Contents

Overview: HPNEURAL Procedure **417**
PROC HPNEURAL Features 418
PROC HPNEURAL Contrasted with Other SAS Procedures 419
Getting Started: HPNEURAL Procedure **420**
Training 420
Stand-Alone Scoring 423
Syntax: HPNEURAL Procedure **424**
PROC HPNEURAL Statement 424
ARCHITECTURE Statement 425
CODE Statement 426
HIDDEN Statement 426
ID Statement 427
INPUT Statement 427
PARTITION Statement 428
PERFORMANCE Statement 428
SCORE Statement 429
TARGET Statement 429
TRAIN Statement 430
WEIGHT Statement 431
Details: HPNEURAL Procedure **432**
Computational Method 432
Multithreading 433
Output Data Set 433
Displayed Output 434
ODS Table Names 435
References **435**

Overview: HPNEURAL Procedure

The HPNEURAL procedure is a high-performance procedure that trains a multilayer perceptron neural network. For more information about multilayer perceptron neural networks, see Bishop (1995). PROC HPNEURAL can also use a previously trained network to score a data set (referred to as stand-alone scoring), or it can generate SAS DATA step statements that can be used to score a data set.

PROC HPNEURAL reads and writes data in distributed form and makes full use of multicore computers and distributed computing environments to perform training and scoring. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details.

Training a multilayer perceptron neural network requires the unconstrained minimization of a nonlinear objective function. Because there are currently no practical methods to guarantee finding a global minimum of that objective function, one way to be reasonably sure of finding a good solution is to train the network multiple times using different sets of initial values for the weights. Thus, even problems with smaller numbers of variables and training observations can benefit from the use of multicore computers and distributed computing environments.

PROC HPNEURAL Features

The HPNEURAL procedure was designed with two goals in mind: to perform efficient, high-speed training of neural networks, and to be as easy to use as possible while still creating models that fit the training data well and generalize well. With these goals in mind, most parameters for the neural network are automatically selected.

The following list summarizes some basic features of PROC HPNEURAL:

- ability to train and score on a massively parallel SAS high-performance appliance
- parallel read of input data and parallel write of output data when the data source is the appliance database
- high degree of multithreading during all phases of training and scoring
- automatic standardization of input and target variables
- intelligent defaults for most neural network parameters such as activation and error functions
- either automatic or manual selection and use of a validation data subset
- automatic termination of training when the validation error stops improving
- ability to weight individual observations or automatically use inverse prior probabilities as weights

PROC HPNEURAL Contrasted with Other SAS Procedures

For general contrasts between SAS High-Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16. Table 18.1 compares the HPNEURAL procedure with the SAS Enterprise Miner Neural Network Node.

Table 18.1 Comparison of PROC HPNEURAL and SAS Enterprise Miner Neural Network Node

PROC HPNEURAL	Neural Network Node
Multithreaded	Single-threaded
Can execute in a distributed computing environment	Can execute only on a single computer
Has few required user-specified parameters so that users with minimal experience with neural networks can obtain good solutions to problems that are amenable to supervised training	Gives you fine control over the myriad of possible choices of parameters that control the training of a neural network
Automatically selects the data standardization methods, network architecture, activation functions, error functions, and weight initialization method	Can use many different user-specified data standardization methods, network architectures, activation functions, error functions, and ways of selecting initial weights
Uses the limited memory Broyden–Fletcher–Goldfarb–Shanno (LBFGS) optimization method (Nocedal and Liu 1989) with proprietary enhancements. LBFGS was chosen for the HPNEURAL procedure because of both its speed of training and its limited use of memory, which can be especially important for problems with large amounts of training data.	Can use a variety of conjugate gradient or quasi-Newton optimization methods, but not LBFGS

Getting Started: HPNEURAL Procedure

Training

The HPNEURAL procedure can either train a neural network model or use a previously trained model to score a data set. We will first discuss training.

The HPNEURAL procedure does not have many parameters that you must specify. It simply needs to know where the training data are (the DATA= option in the PROC statement), the names and types of the input variables (the INPUT statement), the names and types of the target variables (the TARGET statement), the number of hidden neurons (the HIDDEN statement), the number of training tries with each using different randomly generated initial weights (the TRAIN statement), and, optionally, where to write the score file that contains targets from the input file and predicted targets from the trained network and where to write the model file that contains the parameters of the trained network (the SCORE statement).

The single most important parameter you can specify is the number of hidden neurons in the network. A good strategy is to start with a small number and slowly increase the number until the validation error stops improving.

The next most important parameter you can specify is the number of times the network is to be retrained using different sets of initial weights (the NUMTRIES option in the TRAIN statement). A good strategy is to start with 5 (the default) and increase by 2 until the validation error stops improving.

The following small example trains a neural network to predict the type of iris plant, given several measurements, and then scores the same data set that was used for training. The DATA step contains 150 observations derived from the R. A. Fisher (1936) Iris data set:

```
title 'Fisher (1936) Iris Data';

proc format;
   value specname
      1='Setosa    '
      2='Versicolor'
      3='Virginica ';
run;

data iris;
   input SepalLength SepalWidth PetalLength PetalWidth Species @@;
   format Species specname.;
   datalines;
50 33 14 02 1 64 28 56 22 3 65 28 46 15 2 67 31 56 24 3
63 28 51 15 3 46 34 14 03 1 69 31 51 23 3 62 22 45 15 2
59 32 48 18 2 46 36 10 02 1 61 30 46 14 2 60 27 51 16 2
65 30 52 20 3 56 25 39 11 2 65 30 55 18 3 58 27 51 19 3
68 32 59 23 3 51 33 17 05 1 57 28 45 13 2 62 34 54 23 3
77 38 67 22 3 63 33 47 16 2 67 33 57 25 3 76 30 66 21 3
49 25 45 17 3 55 35 13 02 1 67 30 52 23 3 70 32 47 14 2
64 32 45 15 2 61 28 40 13 2 48 31 16 02 1 59 30 51 18 3
55 24 38 11 2 63 25 50 19 3 64 32 53 23 3 52 34 14 02 1
49 36 14 01 1 54 30 45 15 2 79 38 64 20 3 44 32 13 02 1
```

```
67 33 57 21 3 50 35 16 06 1 58 26 40 12 2 44 30 13 02 1
77 28 67 20 3 63 27 49 18 3 47 32 16 02 1 55 26 44 12 2
50 23 33 10 2 72 32 60 18 3 48 30 14 03 1 51 38 16 02 1
61 30 49 18 3 48 34 19 02 1 50 30 16 02 1 50 32 12 02 1
61 26 56 14 3 64 28 56 21 3 43 30 11 01 1 58 40 12 02 1
51 38 19 04 1 67 31 44 14 2 62 28 48 18 3 49 30 14 02 1
51 35 14 02 1 56 30 45 15 2 58 27 41 10 2 50 34 16 04 1
46 32 14 02 1 60 29 45 15 2 57 26 35 10 2 57 44 15 04 1
50 36 14 02 1 77 30 61 23 3 63 34 56 24 3 58 27 51 19 3
57 29 42 13 2 72 30 58 16 3 54 34 15 04 1 52 41 15 01 1
71 30 59 21 3 64 31 55 18 3 60 30 48 18 3 63 29 56 18 3
49 24 33 10 2 56 27 42 13 2 57 30 42 12 2 55 42 14 02 1
49 31 15 02 1 77 26 69 23 3 60 22 50 15 3 54 39 17 04 1
66 29 46 13 2 52 27 39 14 2 60 34 45 16 2 50 34 15 02 1
44 29 14 02 1 50 20 35 10 2 55 24 37 10 2 58 27 39 12 2
47 32 13 02 1 46 31 15 02 1 69 32 57 23 3 62 29 43 13 2
74 28 61 19 3 59 30 42 15 2 51 34 15 02 1 50 35 13 03 1
56 28 49 20 3 60 22 40 10 2 73 29 63 18 3 67 25 58 18 3
49 31 15 01 1 67 31 47 15 2 63 23 44 13 2 54 37 15 02 1
56 30 41 13 2 63 25 49 15 2 61 28 47 12 2 64 29 43 13 2
51 25 30 11 2 57 28 41 13 2 65 30 58 22 3 69 31 54 21 3
54 39 13 04 1 51 35 14 03 1 72 36 61 25 3 65 32 51 20 3
61 29 47 14 2 56 29 36 13 2 69 31 49 15 2 64 27 53 19 3
68 30 55 21 3 55 25 40 13 2 48 34 16 02 1 48 30 14 01 1
45 23 13 03 1 57 25 50 20 3 57 38 17 03 1 51 38 15 03 1
55 23 40 13 2 66 30 44 14 2 68 28 48 14 2 54 34 17 02 1
51 37 15 04 1 52 35 15 02 1 58 28 51 24 3 67 30 50 17 2
63 33 60 25 3 53 37 15 02 1
;

proc hpneural data=iris;
   input SepalLength SepalWidth PetalLength PetalWidth;
   target Species / level=nom;
   hidden 2;
   train outmodel=model_iris;
   score out=scores_iris;
run;
```

Figure 18.1 displays the SAS log output, which shows the percentage of validation observations that were misclassified by the trained network. If there had been any interval targets, the log would have shown the absolute average percentage error and the absolute maximum percentage error for each interval target.

Figure 18.1 SAS Log Output

```
NOTE: The HPNEURAL procedure is executing on the client.
NOTE: Reading data...
NOTE: 150 usable observations in input data set.
NOTE: Training...
NOTE: Try 1 complete after 26 iterations. Reason for stopping: Training
      error=0.000000
NOTE: Try 2 complete after 27 iterations. Reason for stopping: Training
      error=0.000000
NOTE: Try 3 complete after 28 iterations. Reason for stopping: Training
      error=0.000000
NOTE: Try 4 complete after 26 iterations. Reason for stopping: Training
      error=0.000000
NOTE: Try 5 complete after 28 iterations. Reason for stopping: Training
      error=0.000000
NOTE: Scoring...
NOTE: Misclassification Error for target Species:   5.2632%
NOTE: There were 150 observations read from the data set WORK.IRIS.
NOTE: The data set WORK.SCORES_IRIS has 150 observations and 6 variables.
```

Figure 18.2 displays the "Model Information," "Performance Information," and "Number of Observations" tables. The HPNEURAL procedure creates a neural network model for the nominal variable Species. Of the 150 observations, 38 are used as a validation subset, which consists of the first observation and every fourth observation thereafter. The other 112 observations make up the training subset.

PROC HPNEURAL executes in client mode. That is, the model is trained on the machine where the SAS session executes.

Figure 18.2 Model Information, Performance Information, and Number of Observations Tables

```
                    Fisher (1936) Iris Data

                     The HPNEURAL Procedure

                    Performance Information

                 Execution Mode       On client
                 Number of Threads    2


                       Model Information

            Data Source                   WORK.IRIS
            Architecture                  One Hidden Layer
            Optimization Technique        Limited Memory BFGS
            Number of Input Variables     4
            Number of Target Variables    1
            Number of Hidden Neurons      2
            Number of Weights             19
```

Figure 18.2 *continued*

Number of Observations Read	150
Number of Observations Used	150
Number Used for Training	112
Number Used for Validation	38

Figure 18.3 displays the "Misclassification Table." It shows the results of scoring the validation subset by using the neural network model that is trained on the training subset. This example shows two incorrect classifications: two observations whose target value was "Virginica" were incorrectly classified as "Versicolor."

Figure 18.3 Misclassification Table for Species

Misclassification Table for Species

Class:	SETOSA	VERSICOLOR	VIRGINICA
SETOSA	13	0	0
VERSICOLOR	0	11	0
VIRGINICA	0	2	12

Stand-Alone Scoring

The primary purpose for training a neural network model is to use the trained model to score new data that was not seen during training. It is very important that the new data have the same statistical characteristics as the data that were used for training. The following statements use the model that was trained in the preceding section to score some new observations:

```
title 'New Iris Data';

data new_iris;
   input SepalLength SepalWidth PetalLength PetalWidth;
   datalines;
50 33 14 02
64 28 56 22
65 28 46 15
67 31 56 24
63 28 51 15
46 34 14 03
69 31 51 23
62 22 45 15
59 32 48 18
46 36 10 02
61 30 46 14
60 27 51 16
65 30 52 20
56 25 39 11
```

```
65 30 55 18
58 27 51 19
;

proc hpneural data=new_iris;
   score model=model_iris out=scores_new_iris;
run;
```

Syntax: HPNEURAL Procedure

The following statements are available in the HPNEURAL procedure:

PROC HPNEURAL <**DATA=***SAS-data-set*> <**DISTR=ALL** | **SPLIT**> <**NOPRINT**> **;**
PERFORMANCE *performance-options* **;**
ARCHITECTURE *architecture-option* **;**
ID *variables* **;**
INPUT *variables* </ **LEVEL=INT** | **LEVEL=NOM** <**MISSING=MAP**>> **;**
WEIGHT *variable* | **_INVERSE_PRIORS_ ;**
HIDDEN *number* **;**
TARGET *variables* </ **LEVEL=INT** | **LEVEL=NOM** > **;**
PARTITION ROLEVAR=*variable(* **TRAIN=***'value'* | **VALIDATE=***'value')* **;**
PARTITION FRACTION(**TRAIN=***number* | **VALIDATE=***number)* **;**
TRAIN <**NUMTRIES=***number*> <**MAXITER=***number*>
<**VALID=_NONE_** > <**OUTMODEL=***SAS-data-set*> **;**
SCORE **OUT=***SAS-data-set* <**MODEL=***SAS-data-set*> **;**
CODE FILE=*'external-file'* | *fileref* **;**

When you train a neural network, the PROC HPNEURAL, INPUT, TARGET, and TRAIN statements are required. The HIDDEN statement is required unless you use the logistic architecture (in which case, the HIDDEN statement is not allowed).

When you use a previously trained neural network to score a data set, only the PROC HPNEURAL, SCORE, ID, PERFORMANCE, and CODE statements are allowed.

PROC HPNEURAL Statement

PROC HPNEURAL <**DATA=***SAS-data-set*> <**DISTR=ALL** | **SPLIT**> <**NOPRINT**> **;**

The PROC HPNEURAL statement invokes the procedure. You can specify the following options in the PROC HPNEURAL statement:

DATA=*SAS-data-set*
names the SAS data set that contains the training and validation observations to be used by PROC HPNEURAL to train the neural network or that contains the observations to be scored when you are performing stand-alone scoring. The default input data set is the most recently created data set.

When you use PROC HPNEURAL to train a neural network, each observation must contain the input, weight, validation, ID, and target variables that are specified in the associated INPUT, WEIGHT, PARTITION, ID, and TARGET statements.

When you use PROC HPNEURAL to perform stand-alone scoring, the input data set must contain the input variables that were specified when the network was trained (as saved in the model data set) and optionally the target variables that were specified when the network was trained. In addition, if you applied formats to variables when training, the same formats must be applied when you do stand-alone scoring. Only the target variables (if they exist) and the network's predictions are written to the output data set, which is specified in the SCORE statement.

For nominal variables of character type, levels are truncated to 32 bytes and converted to upper case. Also, when you train a network, if all observations that have a specific level for a nominal variable contain missing values in other input, target, weight, or validation variables, then that specific level is discarded and does not appear in the analysis.

If PROC HPNEURAL executes in a distributed environment, the input data are distributed to memory on the appliance nodes and analyzed in parallel. For information about the alongside-the-database model, see the section "Alongside-the-Database Execution" on page 22.

When PROC HPNEURAL runs on the client, the input data set must fit into the available memory on the client. When PROC HPNEURAL runs in a distributed environment, the input data set must fit into the total memory available across the distributed environment.

DISTR=ALL | SPLIT

specifies whether the input data set is to be replicated in the memory of each node in a distributed computing environment. If this option is not specified, PROC HPNEURAL makes this decision automatically based on the size of the input data set. This option is ignored if PROC HPNEURAL is not running in a distributed computing environment.

When PROC HPNEURAL runs in a distributed computing environment, PROC HPNEURAL usually divides the input data set among all the nodes to minimize the time it takes to optimize each try. However, if the input data set is small, dividing the data in this way might be inefficient because of the interconnect delay (the time it takes to send partial results between nodes). It might be more efficient to have each node have a complete copy of the data and run each try in parallel on separate nodes. Each try might take longer because it uses only a single node, but it could take less time to finish all the tries because the tries are running in parallel.

You can force the data to be redistributed so that each node has a complete in-memory copy by specifying DISTR=ALL. You can prevent the data from being redistributed by specifying DISTR=SPLIT.

NOPRINT

specifies that no ODS tables be created.

ARCHITECTURE Statement

ARCHITECTURE *architecture-option* **;**

The ARCHITECTURE statement specifies the architecture of the neural network to be trained. The *architecture-option* must be one of the following:

LOGISTIC
specifies a multilayer perceptron with no hidden units (which is equivalent to a logistic regression). If you specify this architecture, the HIDDEN statement is not allowed.

LAYER1
specifies a multilayer perceptron with a single hidden layer.

LAYER1SKIP
specifies a multilayer perceptron with a single hidden layer and additional connections between each input and each target neuron. Logistic regression is used to initialize the network for the first try.

LAYER2
specifies a multilayer perceptron with two hidden layers. The number of hidden neurons is split equally between the first and second layer. If the number of hidden neurons is odd, the first hidden layer has the extra neuron.

LAYER2SKIP
specifies a multilayer perceptron with two hidden layers and additional connections between each input and each target neuron. The number of hidden neurons is split equally between the first and second layer. If the number of hidden neurons is odd, the first hidden layer has the extra neuron. Logistic regression is used to initialize the network for the first try.

When you use PROC HPNEURAL to train a neural network, the ARCHITECTURE statement is optional. The default is LAYER1. The ARCHITECTURE statement is not allowed when you use PROC HPNEURAL to perform stand-alone scoring.

CODE Statement

CODE FILE=*'external-file'* | *fileref* **;**

The CODE statement uses the current neural network model to generate SAS DATA step statements and save them in an external text file that can later be used to score a data set. The file does not contain the surrounding PROC and RUN statements. The DATA step statements can be used with the standard DATA step, PROC DS2, or PROC HPDS2.

The CODE statement is optional.

FILE=*'external-file'*
specifies an external text file where the generated statements are saved.

FILE=*fileref*
specifies a fileref that refers to an external text file where the generated statements are saved.

HIDDEN Statement

HIDDEN *number* **;**

The HIDDEN statement specifies the *number* of hidden neurons in the network. The *number* must be an integer greater than or equal to 1 (2 for two-layer architectures). For two-layer architectures (LAYER2

and LAYER2SKIP in the ARCHITECTURE statement), the hidden neurons are split between the first and second layer. In this case, if the number of hidden neurons is odd, the first hidden layer has the extra neuron.

All hidden neurons use a hyperbolic-tangent activation function.

When training, you must include exactly one HIDDEN statement, unless you specify ARCHITECTURE LOGISTIC (in which case the HIDDEN statement is not allowed). The HIDDEN statement is not allowed when you do stand-alone scoring.

ID Statement

ID *variables* **;**

The ID statement lists one or more *variables* from the input data set that are transferred to the output data set, which is specified in the SCORE statement.

For documentation about the common ID statement in High-Performance Analytics procedures, see the section "ID Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

The ID statement is optional.

INPUT Statement

INPUT *variables* < / **LEVEL=INT** | **LEVEL=NOM** < **MISSING=MAP** > > **;**

The INPUT statement identifies the *variables* in the input data set that are inputs to the neural network.

LEVEL=INT
specifies that the *variables* are interval variables, which must be numeric. The default for the LEVEL option is INT.

LEVEL=NOM
specifies that the *variables* are nominal variables, also known as classification variables, which can be numeric or character.

MISSING=MAP
specifies that the missing value for nominal variables should be treated as a valid level (mapped to level 0). This option is not allowed for interval variables.

When training, you must include one or more INPUT statements. You need more than one INPUT statement when you have both interval and nominal input variables. The INPUT statement is not allowed when you do stand-alone scoring.

All interval input variables are automatically standardized to the range [–1, 1].

If an observation has missing values for any of the specified input variables, the observation is not used for training or for computing validation error.

If an interval input variable is missing when PROC HPNEURAL scores, its mean (as observed when training) is used. If a nominal input variable is missing, all input neurons associated with the variable (one per class level, except for binary variables, which have a single neuron) are set to 0.

PARTITION Statement

PARTITION ROLEVAR=*variable(* **TRAIN=***'value'* | **VALIDATE=***'value')* **;**

PARTITION FRACTION*(* **TRAIN=***number* | **VALIDATE=***number)* **;**

The PARTITION statement specifies how to divide the input data set into a training subset and a validation subset.

The statement implements two alternate methods of specifying the split between the training and validation data. Either you can explicitly specify training observations and validation observations by specifying ROLEVAR=*variable*, where *variable* is a variable in the input data set, or you can specify that an approximate fraction of the input data set be used for training observations or validation observations by specifying FRACTION(TRAIN=*number*) or FRACTION(VALIDATE=*number*).

ROLEVAR=*variable***(TRAIN=***'value'* | **VALIDATE=***'value'* **)**

specifies that the *variable* in the input data set be used to decide whether an observation is used for training or for validation. Either you can specify the value used to identify training observations or the value used to identify validation observations. If you specify TRAIN=*'value'*, then an observation is used for training if the value of *variable* equals *'value'*; otherwise the observation is used for validation. If you specify VALIDATE=*'value'*, then an observation is used for validation if the value of *variable* equals *'value'*; otherwise the observation is used for training.

FRACTION(TRAIN=*number* | **VALIDATE=***number* **)**

specifies the approximate fraction of the input data set to be used for training or validation. If you specify TRAIN=*number*, then approximately the fraction of the data set specified by *number* is used as training observations, and the rest are used for validation observations. If you specify VALIDATE=*number*, then approximately the fraction of the data set specified by *number* is used as validation observations. The split between training and validation observations can only approximate the requested fraction because that fraction is used as a cutoff value for a random number generator to determine the actual split. If you require a more accurate split or a split that is guaranteed to be identical across different distributed computing environments, you must use the ROLEVAR option to specify the split explicitly.

When you are training, the PARTITION statement is optional. If you do not include the PARTITION statement, every fourth observation (starting with the first observation) is used as a validation observation, unless you specify VALID=_NONE_ in the TRAIN statement. In this case, no validation is performed. The PARTITION statement is not allowed when you are doing stand-alone scoring.

Fit statistics reported after training are only computed using validation observations. Fit statistics reported after stand-alone scoring are computed using all observations.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing. The PERFORMANCE statement for High-Performance Analytics procedures is documented in the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics."

The PERFORMANCE statement is optional.

SCORE Statement

SCORE OUT=*SAS-data-set* < **MODEL=***SAS-data-set* > **;**

The SCORE statement causes the HPNEURAL procedure to write the network's target and predicted output for each observation in the input data set to the output data set that is specified by the OUT option, along with any variables from the input data set that are specified in the ID statement.

OUT=*SAS-data-set*
specifies the data set to contain the predicted values of the target variables. For nominal variables, each observation also contains the computed probabilities of each class level. This keyword is required.

MODEL=*SAS-data-set*
specifies the data set that contains the model parameters for a previously trained network. You can specify this keyword only when you are doing stand-alone scoring.

When you are training, the SCORE statement is optional but the MODEL= keyword is not allowed. When you are doing stand-alone scoring, the SCORE statement is required and the MODEL= keyword must be used.

TARGET Statement

TARGET *variables* < / **LEVEL=INT** | **LEVEL=NOM** > **;**

The TARGET statement identifies the *variables* in the input data set that the network is to be trained to predict. The default for the LEVEL= option is INT.

LEVEL=INT
specifies that the *variables* are interval variables, which must be numeric.

LEVEL=NOM
specifies that the *variables* are nominal variables, also known as classification variables, which can be numeric or character.

When training, you must include one or more TARGET statements. You need more than one TARGET statement when you have both interval and nominal target variables. The TARGET statement is not allowed when you do stand-alone scoring.

All interval target variables are automatically standardized to the range [0.1, 0.9]. The HPNEURAL procedure automatically converts them back to their original scale before it computes fit statistics and writes predictions to the scoring data set.

For interval variables, all target neurons use a sigmoid activation function.

Nominal variables have one target neuron per class level. Each of these neurons uses the softmax activation function to ensure that the sum of the outputs for all neurons is 1.0. The output of each neuron can then be interpreted as the probability that the variable is the corresponding class level.

If an observation has missing values for any of the specified target variables, the observation is not used for training or for computing validation error.

You cannot specify the same *variable* in both an INPUT statement and a TARGET statement.

TRAIN Statement

TRAIN <**NUMTRIES=***number*> <**MAXITER=***number*>
<**VALID=_NONE_**> <**OUTMODEL=***SAS-data-set*> **;**

The TRAIN statement causes the HPNEURAL procedure to use the training data that are specified in the PROC HPNEURAL statement to train a neural network model whose structure is specified in the ARCHITECTURE, INPUT, TARGET, and HIDDEN statements. The goal of training is to determine a set of network weights that best predicts the targets in the training data while still doing a good job of predicting targets of unseen data (that is, generalizing well and not overfitting).

Except for the first try when you specify LAYER1SKIP or LAYER2SKIP in the ARCHITECTURE statement, training starts with a pseudorandomly generated initial set of weights. For the first try in LAYER1SKIP or LAYER2SKIP architectures, the initial set of weights is generated by performing a logistic regression. PROC HPNEURAL then computes the objective function for the training subset (the sum of the squared differences between the target values of each observation and the outputs of the network), and the minimization algorithm adjusts the weights. This process is repeated until any one of the following conditions is met:

- The objective function that is computed using the training subset stops improving.
- The objective function that is computed using the validation subset stops improving.
- The process has been repeated the *number* of times specified in the MAXITER= option.

By default, every fourth observation that is read (starting with the first observation) is used as a validation observation. You can override this by specifying VALID=_NONE_ in the TRAIN statement or by using the PARTITION statement. Any observations with missing values for input, weight, validation, or target variables are not used for training or validation error calculation, although they are scored if a SCORE statement is present. Fit statistics reported after training are only computed using validation observations. Fit statistics reported after stand-alone scoring are computed using all observations.

In a distributed computing environment, the order of the observations that are read is not guaranteed to be the same across different environments. Therefore, different validations observations might be selected in different environments when the default method is used for choosing validation observations, causing results to be somewhat different between different environments. You can avoid this by using the ROLEVAR= option in a PARTITION statement to explicitly specify which observations are validation observations.

The weights that result in the smallest value of the objective function for the validation subset are saved and used for calculating fit statistics and for scoring.

When you are training, you must include exactly one TRAIN statement. The TRAIN statement is not allowed when you are doing stand-alone scoring.

NUMTRIES=*number*

specifies the *number* of times the network is to be trained using a different starting points. Specifying this option helps ensure that the optimizer finds the set of weights that truly minimizes the objective function and does not return a local minimum. The value of *number* must be an integer between 1 and 99,999. The default is 5.

MAXITER=*number*

specifies the maximum number of iterations (weight adjustments) for the optimizer to make before terminating.

Setting *number* to a large value does not mean that the optimizer actually iterates that many times. Often, training or validation error stops improving much sooner, usually after a few hundred iterations.

When you are training using large data sets, you can do a training run with MAXITER=1 to determine approximately how long each iteration will take.

The default is 50.

VALID=_NONE_

specifies that a validation subset not be used to help determine when to stop training.

If you specify VALID=_NONE_ in the TRAIN statement, you cannot have a PARTITION statement.

OUTMODEL=*SAS-data-set*

specifies the data set to which to save the model parameters for the trained network. These parameters include the network architecture, input and target variable names and types, and trained weights.

You can use the model data set later to score a different input data set as long as the variable names and types of the variables in the new input data set match those of the training data set.

WEIGHT Statement

WEIGHT *variable* | **_INVERSE_PRIORS_ ;**

If you specify a WEIGHT statement, *variable* identifies a numeric *variable* in the input data set that contains the weight to be placed on the prediction error (the difference between the output of the network and the target value specified in the input data set) for each observation during training.

If, instead of specifying a *variable*, you specify the keyword _INVERSE_PRIORS_, the HPNEURAL procedure calculates the weight applied to the prediction error of each nominal target variable as the total number of observations divided by the number of observations whose target class is the same as the current observation (in other words, the inverse of the fraction of the number of times that the target class occurs in the input data set).

If *variable* is less than or equal to 0 or is missing, the observation is not used for training or for computing validation error. When validation error is computed during training, the weights on the validation observations are used even though weights are not used when scoring.

The WEIGHT statement is optional. If a WEIGHT statement is not included, all observations are assigned a weight of 1.

Details: HPNEURAL Procedure

Computational Method

PROC HPNEURAL trains a multilayer perceptron neural network with one or two hidden layers. For more information about multilayer perceptron neural networks, see Bishop (1995).

All continuous input variables are scaled to be in the range [–1, 1].

For all nominal input variables, except binary variables (which have a single input neuron), there is one input neuron per level. The value assigned to each input neuron is 0 except for the neuron which represents the actual input level for an observation, which has an input value of 1.

All activation functions for hidden neurons are hyperbolic tangents.

For all continuous target variables, the output activation function is the sigmoid function, and the error function is the squared difference between the scaled target value and the network output. Because the output of the sigmoid function is limited to the range [0, 1], continuous target variables must be scaled so as not to exceed this range. PROC HPNEURAL automatically scales target variables to the range [0.1, 0.9] so that the network can predict any target variable without forcing the output neurons into their saturation region. PROC HPNEURAL automatically rescales the network output back to the original scale before writing the predicted output to the score file.

For all nominal target variables, the output activation function is the softmax function, and the error function is the cross entropy function. There is one output neuron per level, except for binary variables (which have a single output neuron). The target value for each output neuron is 0 except for the neuron that represents the actual target level for an observation, which has a target value of 1.

The error function for the network is a scalar function of the network weights. This function defines an error surface on which the optimization algorithm attempts to locate a minimum. Optimization is done in two parts: the limited memory Broyden–Fletcher–Goldfarb–Shanno (LBFGS) algorithm (Nocedal and Liu 1989) computes a direction along the error surface; then the Moré Thuente line search algorithm (Moré and Thuente 1992) finds a new minimum of the error function on the surface along that direction. If a sufficient decrease in the error function can be found, the weights that generated the new minimum are then used by the LBFGS algorithm to calculate a new descent direction. The process is repeated until a sufficient decrease in the error function cannot be obtained.

Both the LBFGS search direction algorithm and the Moré Thuente line search algorithm need to know the gradient of the error surface at several different points (sets of weights). This gradient is calculated by using the algorithm described in Bishop (1995).

Besides terminating due to the inability to improve the error function, the optimization algorithm also stops if the validation error (which is calculated after each line search) lacks improvement 40 times in a row. The validation error is computed as the sum, over each validation observation, of the absolute difference between the target and the network output. By default, every fourth observation is used as a validation observation, starting with the first observation. This default can be changed by using the PARTITION statement. Validation observations are not used in any other way by the optimization algorithm. Fit statistics reported after training are only computed using validation observations. Fit statistics reported after stand-alone scoring are computed using all observations.

Multithreading

Threading refers to the organization of the computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPNEURAL procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, the following statement causes the HPNEURAL procedure to determine threading as if it executed on a system with four CPUs, regardless of the actual CPU count:

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This option overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement. This option overrides the CPUCOUNT= system option and instructs the HPNEURAL procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output. By default, the HPNEURAL procedure allocates one thread per CPU.

The tasks multithreaded by the HPNEURAL procedure are primarily defined by dividing the data that are processed on a single machine among the threads; that is, the HPNEURAL procedure implements multithreading through a data-parallel model. For example, if the input data set has 1,000 observations and PROC HPNEURAL is running with four threads, then 250 observations are associated with each thread.

Output Data Set

The output data set is specified by the OUT= option in the SCORE statement. If there is no SCORE statement, then no output data set is created, but fit statistics are still displayed in ODS tables.

Table 18.2 describes the columns of the output data set.

Table 18.2 Output Data Set Columns

Column	Name
Target value of the variable from the input data set	Same as the name of the variable in the input data set
Predicted value of the variable from the trained network	A name of the form:P_Vn for interval variables and I_Vn for nominal variables, where n is the variable number starting from 1. A descriptive label is generated that specifies the actual variable name.
For nominal values, additional columns for the raw network output for each level of each nominal variable. Because nominal variables use the softmax activation function, the raw value for a specific level is usually interpreted as the probability that the target variable is that level.	P_VnLm where n is the variable number starting from 1 and m is the level number starting from 0. A descriptive label is generated that specifies the actual variable name and level name.

Displayed Output

PROC HPNEURAL displays basic fit statistics in the SAS log and more detailed information in several ODS tables.

When you are training, the statistics are based on the network's prediction accuracy on the validation subset, unless there is no validation subset, in which case the statistics are based on the entire input data set.

When you are performing stand-alone scoring, the statistics depend on whether the target variables exist in the input data set: if the target variables exist in the input data set, the statistics are based on the network's prediction accuracy on the entire input data set; otherwise no fits statistics can be computed.

For interval variables, PROC HPNEURAL displays the average absolute percentage error and maximum absolute percentage error. The percentage is the percentage of the range of the variable across the entire input data set (not just the validation observations). For nominal variables, PROC HPNEURAL displays the percentage of observations that were misclassified.

In addition to information displayed in the SAS log, PROC HPNEURAL generates ODS tables that give detailed information about the model structure, input data, detailed training results, and timings.

Other fit statistics can be computed from information in the score data set.

ODS Table Names

Each table created by the HPNEURAL procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. The names of each table and a short description of the contents are listed in Table 18.3.

Table 18.3 ODS Tables Produced by PROC HPNEURAL

Table Name	Description	Required Statement / Option
ClassLevels	Level information for nominal input variables	INPUT with LEVEL=NOM
Details	Detailed real times for each phase of the procedure	PERFORMANCE with DETAILS option
ErrorSummary	Average and maximum errors for interval targets	TARGET with LEVEL=INT (the default)
Iteration	Training and validation error for each iteration of the best try	Default output
Misclassification	Misclassification matrix for nominal target variables	TARGET with LEVEL=NOM
ModelInformation	Information about the modeling environment	Default output
Nobs	Number of observations read and used; number of validation observations used	Default output
PerformanceInfo	Information about the high-performance computing environment	Default output
Training	Training error, validation error, and reason for stopping for each try	Default output

References

Bishop, C. M. (1995), *Neural Networks for Pattern Recognition*, Oxford University Press.

Moré, J. J. and Thuente, D. J. (1992), "Line Search Algorithms with Guaranteed Sufficient Decrease," *ACM Transactions on Mathematical Software*, 20, 286–307.

Nocedal, J. and Liu, D. C. (1989), "On the Limited Memory BFGS Method for Large Scale Optimization," *Mathematical Programming*, 45, 503–528.

Chapter 19
The HPNLIN Procedure

Contents

Overview: HPNLIN Procedure **437**
PROC HPNLIN Features 438
PROC HPNLIN Contrasted with Other SAS Procedures 438
Getting Started: HPNLIN Procedure **439**
Least Squares Model 439
Binomial Model 440
Syntax: HPNLIN Procedure **441**
PROC HPNLIN Statement 441
BOUNDS Statement 446
ESTIMATE Statement 447
MODEL Statement 447
PARAMETERS Statement 448
PERFORMANCE Statement 451
PREDICT Statement 451
RESTRICT Statement 452
Programming Statements 452
Details: HPNLIN Procedure **454**
Least Squares Estimation 454
Built-in Log-Likelihood Functions 455
Computational Method 457
Choosing an Optimization Algorithm 458
Displayed Output 461
ODS Table Names 464
Examples: HPNLIN Procedure **465**
Example 19.1: Segmented Model 465
References **469**

Overview: HPNLIN Procedure

The HPNLIN procedure is a high-performance procedure that uses either nonlinear least squares or maximum likelihood to fit nonlinear regression models on the SAS appliance. PROC HPNLIN enables you to specify the model with SAS programming statements, which gives you greater flexibility in modeling the relationship between the response variable and independent (regressor) variables than SAS procedures that use a more structured MODEL statement.

With the HPNLIN procedure you can read and write data in distributed form and perform analyses in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details.

PROC HPNLIN Features

The HPNLIN procedure does the following:

- can perform analysis on a massively parallel SAS high-performance appliance
- reads input data in parallel and writes output data in parallel when the data source is the appliance database
- is highly multithreaded during all phases of analytic execution
- computes analytical derivatives of user-provided expressions for more robust parameter estimations
- evaluates user-provided expressions and their confidence limits with the ESTIMATE and PREDICT statements
- estimates parameters without specifying a particular distribution function by using the least squares method
- estimates parameters by using the maximum likelihood method when either a built-in distribution function is specified or a likelihood function is provided

PROC HPNLIN Contrasted with Other SAS Procedures

For general contrasts between SAS High Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16. The following remarks contrast the HPNLIN procedure with the NLIN and NLMIXED procedures in SAS/STAT software:

Like the NLIN procedure, the HPNLIN procedure estimates parameters by using least squares minimization for models that are specified by SAS programming statements. However, PROC HPNLIN can also perform maximum likelihood estimation when information about the response variable's distribution is provided. PROC HPNLIN also has a RESTRICT statement for specifying restrictions on parameter estimates that are more general than those that are available in PROC NLIN. Because the HPNLIN and NLIN procedures use different optimization techniques, the available options that control the estimation process and resulting parameter estimates can differ between these procedures when equivalent models and data are analyzed.

Although it does not support the specification of random effects, PROC HPNLIN is similar to PROC NLMIXED. Both procedures perform maximum likelihood estimation by using the same programming syntax and set of distributions to specify the model's mean term. Additionally, both PROC HPNLIN and PROC NLMIXED use the same optimization techniques and options. However, PROC NLMIXED does not support least squares parameter estimation.

Getting Started: HPNLIN Procedure

The most common use of the HPNLIN procedure is to estimate the parameters in a model in which the response variable is a nonlinear function of one or more of the parameters.

Least Squares Model

The Michaelis-Menten model of enzyme kinetics (Ratkowsky 1990, p. 59) relates a substrate's concentration to its catalyzed reaction rate. The Michaelis-Menten model can be analyzed using a least squares estimation because it does not specify how the reaction rate is distributed about its predicted value. The relationship between reaction rate and substrate concentration is

$$f(\mathbf{x}, \boldsymbol{\theta}) = \frac{\theta_1 x_i}{\theta_2 + x_i}, \quad \text{for } i = 1, 2, \ldots, n$$

where x_i represents the concentration for n trials and $f(\mathbf{x}, \boldsymbol{\theta})$ is the reaction rate. The vector $\boldsymbol{\theta}$ contains the rate parameters.

For this model with experimental measurements of reaction rate and concentration stored in the enzyme data set, the following SAS statements estimate the parameters θ_1 and θ_2:

```
proc hpnlin data=enzyme;
   parms theta1=0 theta2=0;
   model rate ~ residual(theta1*conc / (theta2 + conc));
run;
```

The least squares estimation performed by PROC HPNLIN for this enzyme kinetics problem produces the analysis of variance table displayed in Figure 19.1. The table displays the degrees of freedom, sums of squares, and mean squares along with the model F test.

Figure 19.1 Nonlinear Least Squares Analysis of Variance

The HPNLIN Procedure

Analysis of Variance

Source	DF	Sum of Squares	Mean Square	F Value	Approx Pr > F
Model	2	290116	145058	88537.2	<.0001
Error	12	19.6606	1.6384		
Uncorrected Total	14	290135			

An intercept was not specified for this model.

Finally, Figure 19.2 displays the parameter estimates, standard errors, t statistics, and 95% confidence intervals for θ_1 and θ_2.

Figure 19.2 Parameter Estimates and Approximate 95% Confidence Intervals

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|	Approximate 95% Confidence Limits	
theta1	158.10	0.6737	12	234.67	<.0001	156.64	159.57
theta2	0.07413	0.003129	12	23.69	<.0001	0.06731	0.08095

In the enzyme kinetics model, no information was supplied concerning the distribution of the reaction rate about the model's mean value. Therefore, the *residual* model distribution was specified to perform a least squares parameter fit.

Binomial Model

In Example 63.3 (*SAS/STAT User's Guide*) cancer remission is modeled by expressing the maximum likelihood function for a binary distribution as a nonlinear least squares optimization in PROC NLIN. The following statements show an equivalent formulation of this model that uses PROC HPNLIN and specifies the binary distribution explicitly:

```
proc hpnlin data=remiss corr;
   parms int=-10 a=-2 b=-1 c=6;
   linp = int + a*cell + b*li + c*temp;
   p = probnorm(linp);
   model remiss ~ binary(1-p);
run;
```

This binary distribution model displays information about the quality of the estimation that is different from the information displayed in the section "Least Squares Model" on page 439. No analysis of variance table is produced for this model, and fit statistics based on the value of the likelihood function are displayed in Figure 19.3.

Figure 19.3 Nonlinear Likelihood Function Statistics

The HPNLIN Procedure

Fit Statistics

-2 Log Likelihood	21.9002
AIC (smaller is better)	29.9002
AICC (smaller is better)	31.7183
BIC (smaller is better)	35.0835

Parameter estimates for the binary distribution model are displayed in Figure 19.4 using the same quantities as are used in the section "Least Squares Model" on page 439.

Figure 19.4 Parameter Estimates and Approximate 95% Confidence Intervals

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|	Approximate 95% Confidence Limits	
int	−36.7548	32.3607	27	−1.14	0.2660	−103.15	29.6439
a	−5.6298	4.6376	27	−1.21	0.2353	−15.1454	3.8858
b	−2.2513	0.9790	27	−2.30	0.0294	−4.2599	−0.2426
c	45.1815	34.9095	27	1.29	0.2065	−26.4469	116.81

Syntax: HPNLIN Procedure

The following statements are available in the HPNLIN procedure:

PROC HPNLIN < *options* > ;
BOUNDS *inequality* < ,. . . ,*inequality* > ;
ESTIMATE *'label' expression* < *options* > ;
MODEL *model specification* ;
PARAMETERS < *parameter-specification* > < ,. . . , *parameter-specification* > ;
PERFORMANCE < *performance-options* > ;
PREDICT *'label' expression keyword=names* < . . . *keyword=names* > < *options* > ;
RESTRICT *restriction1* < , *restriction2* . . . > ;
Programming Statements ;

The PROC HPNLIN statement and exactly one MODEL statement are required.

PROC HPNLIN Statement

PROC HPNLIN < *options* > ;

The PROC HPNLIN statement invokes the procedure. Table 19.1 summarizes important options in the PROC HPNLIN statement by function. These and other options in the PROC HPNLIN statement are then described fully in alphabetical order.

Table 19.1 PROC HPNLIN Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
OUT=	Specifies the output data set
Options Related to Output	
CORR	Specifies the correlation matrix

Table 19.1 *continued*

Option	Description
COV	Specifies the covariance matrix
ECORR	Specifies the correlation matrix of additional estimates
ECOV	Specifies the covariance matrix of additional estimates
DF	Specifies the default degrees of freedom
NOPRINT	Suppresses ODS output
NOITPRINT	Suppresses output concerning iterations within the optimization process
Options Related to Optimization	
ABSCONV=	Tunes an absolute function convergence criterion
ABSFCONV=	Tunes an absolute difference function convergence criterion
ABSGCONV=	Tunes the absolute gradient convergence criterion
FCONV=	Tunes the relative function convergence criterion
GCONV=	Tunes the relative gradient convergence criterion
MAXITER=	Chooses the maximum number of iterations in any optimization
MAXFUNC=	Specifies the maximum number of function evaluations in any optimization
MAXTIME=	Specifies the upper limit seconds of CPU time for any optimization
MINITER=	Specifies the minimum number of iterations in any optimization
TECHNIQUE=	Selects the optimization technique
Tolerances	
SINGULAR=	Tunes the general singularity criterion
User-defined Formats	
FMTLIBXML=	Specifies a file reference for a format stream
XMLFORMAT=	Specifies a file name for a format stream

You can specify the following options in the PROC HPNLIN statement.

ABSCONV=*r*

ABSTOL=*r*

specifies an absolute function convergence criterion. For minimization, termination requires $f(\boldsymbol{\psi}^{(k)}) \leq r$, where $\boldsymbol{\psi}$ is the vector of parameters in the optimization and $f(\cdot)$ is the objective function. The default value of r is the negative square root of the largest double-precision value, which serves only as a protection against overflows.

ABSFCONV=*r* **<** *n* **>**

ABSFTOL=*r* **<** *n* **>**

specifies an absolute difference function convergence criterion. For all techniques except the Nelder-Mead simplex (NMSIMP) technique, termination requires a small change of the function value in successive iterations:

$$|f(\boldsymbol{\psi}^{(k-1)}) - f(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}(k)$ is defined as the vertex with the lowest function value, and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The default value is $r = 0$. The optional integer value n specifies the number of successive iterations for which the criterion must be satisfied before the process can be terminated.

ABSGCONV=*r* **<** *n* **>**

ABSGTOL=*r* **<** *n* **>**

specifies an absolute gradient convergence criterion. Termination requires the maximum absolute gradient element to be small:

$$\max_j |g_j(\boldsymbol{\psi}^{(k)})| \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $g_j(\cdot)$ is the gradient of the objective function with respect to the jth parameter. This criterion is not used by the NMSIMP technique. The default value is r =1E−5. The optional integer value n specifies the number of successive iterations for which the criterion must be satisfied before the process can be terminated.

ALPHA=*α*

specifies the level of significance α used in the construction of $100(1-\alpha)\%$ confidence intervals. The value must be strictly between 0 and 1; the default value of $\alpha = 0.05$ results in 95% intervals. This value is used as the default confidence level for limits computed in the "Parameter Estimates" table and is used in the LOWER and UPPER options in the PREDICT statement.

CORR

requests the approximate correlation matrix for the parameter estimates.

COV

requests the approximate covariance matrix for the parameter estimates.

DATA=*SAS-data-set*

names the SAS data set to be used by PROC HPNLIN. The default is the most recently created data set.

If the procedure executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. In the latter case, the procedure reads the data alongside the distributed database. For more information about the various execution modes, see the section "SMP and MPP Modes" on page 16; for more information about on the alongside-the-database model, see the section "Alongside-the-Database Execution" on page 22.

DF=*n*

specifies the default number of degrees of freedom to use in the calculation of p-values and confidence limits for additional parameter estimates.

ECORR

requests the approximate correlation matrix for all expressions that are specified in ESTIMATE statements.

ECOV

requests the approximate covariance matrix for all expressions that are specified in ESTIMATE statements.

FCONV=*r*< *n* >

FTOL=*r*< *n* >

specifies a relative function convergence criterion. For all techniques except NMSIMP, termination requires a small relative change of the function value in successive iterations:

$$\frac{|f(\boldsymbol{\psi}^{(k)}) - f(\boldsymbol{\psi}^{(k-1)})|}{|f(\boldsymbol{\psi}^{(k-1)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, and $f(\cdot)$ is the objective function. The same formula is used for the NMSIMP technique, but $\boldsymbol{\psi}^{(k)}$ is defined as the vertex with the lowest function value, and $\boldsymbol{\psi}^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The

The default is $r = 10^{-\mathrm{FDIGITS}}$, where FDIGITS is by default $-\log_{10}\{\epsilon\}$ and ϵ is the machine precision. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process can terminate.

FMTLIBXML=*file-ref*

specifies the file reference for the XML stream that contains the user-defined format definitions. User-defined formats are handled differently in a distributed computing environment than they are handled in other SAS products. See the section "Working with Formats" on page 27 for details about how to generate a XML stream for your formats.

GCONV=*r*< *n* >

GTOL=*r*< *n* >

specifies a relative gradient convergence criterion. For all techniques except the conjugate gradient (CONGRA) and NMSIMP techniques, termination requires that the normalized predicted function reduction be small,

$$\frac{\mathrm{g}(\boldsymbol{\psi}^{(k)})'[\mathbf{H}^{(k)}]^{-1}\mathrm{g}(\boldsymbol{\psi}^{(k)})}{|f(\boldsymbol{\psi}^{(k)})|} \leq r$$

Here, $\boldsymbol{\psi}$ denotes the vector of parameters that participate in the optimization, $f(\cdot)$ is the objective function, and $\mathrm{g}(\cdot)$ is the gradient. For the CONGRA technique (where a reliable Hessian estimate $\mathbf{H}$ is not available), the following criterion is used:

$$\frac{\| \mathrm{g}(\boldsymbol{\psi}^{(k)}) \|_2^2 \quad \| \mathrm{s}(\boldsymbol{\psi}^{(k)}) \|_2}{\| \mathrm{g}(\boldsymbol{\psi}^{(k)}) - \mathrm{g}(\boldsymbol{\psi}^{(k-1)}) \|_2 \; |f(\boldsymbol{\psi}^{(k)})|} \leq r$$

This criterion is not used by the NMSIMP technique. The default value is r =1E−8. The optional integer value *n* specifies the number of successive iterations for which the criterion must be satisfied before the process can terminate.

MAXFUNC=*n*

MAXFU=*n*

specifies the maximum number *n* of function calls in the optimization process. The default values are as follows, depending on the optimization technique (which you specify in the TECHNIQUE= option):

- TRUREG, NRRIDG, NEWRAP: 125
- QUANEW, DBLDOG: 500
- CONGRA: 1,000
- NMSIMP: 3,000

Optimization can terminate only after completing a full iteration. Therefore, the number of function calls that are actually performed can exceed the number that is specified by the MAXFUNC= option.

MAXITER=*n*

MAXIT=*n*

specifies the maximum number *n* of iterations in the optimization process. The default values are as follows, depending on the optimization technique (which you specify in the TECHNIQUE= option):

- TRUREG, NRRIDG, NEWRAP: 50
- QUANEW, DBLDOG: 200
- CONGRA: 400
- NMSIMP: 1,000

These default values also apply when *n* is specified as a missing value.

MAXTIME=*r*

specifies an upper limit of *r* seconds of CPU time for the optimization process. The default value is the largest floating-point double representation of your computer. The time specified by the MAXTIME= option is checked only once at the end of each iteration. Therefore, the actual running time can be longer than that specified by the MAXTIME= option.

MINITER=*n*

MINIT=*n*

specifies the minimum number of iterations. The default value is 0. If you request more iterations than are actually needed for convergence to a stationary point, the optimization algorithms can behave strangely. For example, the effect of rounding errors can prevent the algorithm from continuing for the required number of iterations.

NOITPRINT

suppresses the display of the "Iteration History" table.

NOPRINT

suppresses the generation of ODS output.

OUT=*SAS-data-set*

names the SAS data set to be created when one or more PREDICT statements are specified. A single OUT= data set is created to contain all predicted values when more than one PREDICT statement is specified. An error message is produced if a PREDICT statement is specified and an OUT= data set is not specified. See the section "Output Data Sets" on page 26 for more information about output data sets in SAS High-Performance Analytics procedures.

SINGULAR=*number*

tunes the general singularity criterion applied by the HPNLIN procedure in sweeps and inversions. The default is 1E4 times the machine epsilon; this product is approximately 1E−12 on most computers.

TECHNIQUE=*keyword*

TECH=*keyword*

specifies the optimization technique for obtaining maximum likelihood estimates. You can choose from the following techniques by specifying the appropriate *keyword*:

CONGRA	performs a conjugate-gradient optimization.
DBLDOG	performs a version of double-dogleg optimization.
LEVMAR	performs a Levenberg-Marquardt optimization.
NEWRAP	performs a Newton-Raphson optimization that combines a line-search algorithm with ridging.
NMSIMP	performs a Nelder-Mead simplex optimization.
NONE	performs no optimization.
NRRIDG	performs a Newton-Raphson optimization with ridging.
QUANEW	performs a quasi-Newton optimization.
TRUREG	performs a trust-region optimization.

The default value is TECHNIQUE=LEVMAR for least squares regression models and TECHNIQUE=NRRIDG for models where the distribution is specified.

XMLFORMAT=*filename*

specifies the file name for the XML stream that contains the user-defined format definitions. User-defined formats are handled differently in a distributed computing environment than they are handled in other SAS products. See the section "Working with Formats" on page 27 for details about how to generate a XML stream for your formats.

BOUNDS Statement

BOUNDS *constraint* < , *constraint . . .* > **;**

where *constraint* represents

< *number operator* > *parameter-list* < *operator number* >

Boundary constraints are specified with a BOUNDS statement. One- or two-sided boundary constraints are allowed. The list of boundary constraints are separated by commas. For example:

```
bounds 0 <= a1-a9 X <= 1, -1 <= c2-c5;
bounds b1-b10 y >= 0;
```

You can specify more than one BOUNDS statement. If you specify more than one lower (or upper) bound for the same parameter, the maximum (or minimum) of these is taken.

If the maximum l_j of all lower bounds is larger than the minimum of all upper bounds u_j for the same parameter θ_j, the boundary constraint is replaced by $\theta_j := l_j := \min(u_j)$ defined by the minimum of all upper bounds specified for θ_j.

ESTIMATE Statement

ESTIMATE *'label' expression* < *options* > **;**

The ESTIMATE statement enables you to compute an additional estimate that is a function of the parameter values. You must provide a quoted string to identify the estimate and then provide a valid SAS expression. Multiple ESTIMATE statements are permitted, and results from all statements are listed in a common table. PROC HPNLIN computes approximate standard errors for the estimates by using the delta method (Billingsley 1986). It uses these standard errors to compute corresponding t statistics, p-values, and confidence limits.

The ECOV option in the PROC HPNLIN statement produces a table that contains the approximate covariance matrix of all the additional estimates you specify. The ECORR option produces the corresponding correlation matrix.

The following options are available in the ESTIMATE statement:

ALPHA=α
: specifies the alpha level to be used in computing confidence limits. The default value corresponds to the ALPHA= option in the PROC HPNLIN statement.

DF=d
: specifies the degrees of freedom to be used in computing p-values and confidence limits. The default value corresponds to the DF= option in the PROC HPNLIN statement.

MODEL Statement

MODEL *dependent-variable* ∼ *distribution* **;**

The MODEL statement is the mechanism for either using a distribution specification to specify the distribution of the data or using the RESIDUAL distribution to specify a predicted value. You must specify a single dependent variable from the input data set, a tilde (∼), and then a distribution with its parameters. You can specify the following values for *distribution*:

RESIDUAL(*m*) or **LS**(*m*)
: specifies no particular distribution. Instead minimize the sum of squares of the differences between *m* and the dependent variable.

NORMAL(*m*, *v*)
: specifies a normal (Gaussian) distribution with mean *m* and variance *v*.

BINARY(*p*) specifies a binary (Bernoulli) distribution with probability *p*.

BINOMIAL(*n*, *p*) specifies a binomial distribution with count *n* and probability *p*.

GAMMA(*a*, *b*) specifies a gamma distribution with shape *a* and scale *b*.

NEGBIN(*n*, *p*) specifies a negative binomial distribution with count *n* and probability *p*.

POISSON(*m*) specifies a Poisson distribution with mean *m*.

GENERAL(*ll*) specifies a general log-likelihood function that you construct by using SAS programming statements.

The MODEL statement must follow any SAS programming statements you specify for computing parameters of the preceding distributions. See the section "Built-in Log-Likelihood Functions" on page 455 for expressions of the built-in log-likelihood functions.

PARAMETERS Statement

PARAMETERS < *parameter-specification* > < *, . . . , parameter-specification* > < */ options* > **;**

PARMS < *parameter-specification* > < *, . . . , parameter-specification* > < */ options* > **;**

The purpose of the PARAMETERS (PARMS) statement is to provide starting values for the HPNLIN procedure. You can provide values that define a single point in the parameter space or a set of points. For more information about *parameter-specification*, see the section "Assigning Starting Values with Parameter-Specification" on page 449.

You can specify the following *options* in the PARMS statement after the slash (/).

BEST=*i* > 0
specifies the maximum number of parameter grid points and corresponding objective function values to display in the "Parameters" table. If the BEST= option is specified, parameter grid points are listed in ascending order of objective function value. By default, all parameter grid points are displayed.

PDATA=*SAS-data-set*

DATA=*SAS-data-set*
specifies the data set used to provide parameter starting values.

START=*value*

DEFSTART=*value*
specifies a default starting value for all parameters.

There are four methods available for providing starting values to the optimization process. In descending order of precedence, the methods are as follows:

1. Specify values directly in the PARMS statement.
2. Specify values in the PARMS / PDATA= data set.
3. Specify a single value for all parameters by using the START= option.
4. Use the default value 1.0.

The names assigned to parameters must be valid SAS names and must not coincide with names of variables in the input data set (see the DATA= option in the PROC HPNLIN statement). Parameters that are assigned starting values through the PARAMETERS statement can be omitted from the estimation if the expression in the MODEL statement does not depend on them.

Assigning Starting Values with Parameter-Specification

A *parameter-specification* has the following general form where *name* identifies the parameter and *value-list* provides the set of starting values for the parameter:

name **=** *value-list*

Very often the *value-list* contains only a single value, but more general and flexible list specifications such as the following are possible:

m	a single value
m1, *m2*, . . . , *mn*	several values
m TO *n*	a sequence in which *m* equals the starting value, *n* equals the ending value, and the increment equals 1
m TO *n* BY *i*	a sequence in which *m* equals the starting value, *n* equals the ending value, and the increment is *i*
m1, *m2* TO *m3*	mixed values and sequences

When you specify more than one value for a parameter, PROC HPNLIN sorts the values in ascending sequence and removes duplicate values from the parameter list before forming the grid for the parameter search. If you specify several values for each parameter, PROC HPNLIN evaluates the model at each point on the grid. The iterations then commence from the point on the grid that yields the smallest objective function value.

For example, the following PARMS statement specifies five parameters and sets their possible starting values as shown in the table:

```
parms  b0 = 0
       b1 = 4 to 8
       b2 = 0 to .6 by .2
       b3 = 1, 10, 100
       b4 = 0, .5, 1 to 4;
```

Possible Starting Values				
B0	B1	B2	B3	B4
0	4	0.0	1	0.0
	5	0.2	10	0.5
	6	0.4	100	1.0
	7	0.6		2.0
	8			3.0
				4.0

The objective function values are calculated for each of the $1 \times 5 \times 4 \times 3 \times 6 = 360$ combinations of possible starting values. Each grid point's objective function value is computed by using the execution mode specified in the PERFORMANCE statement.

If you specify a starting value with a *parameter-specification*, any starting values provided for this parameter through the PDATA= data set are ignored. The *parameter-specification* overrides the information in the PDATA= data set.

Assigning Starting Values from a SAS Data Set

The PDATA= option in the PARAMETERS statement enables you to assign starting values for parameters through a SAS data set. The data set must contain at least two variables: a character variable named Parameter or Parm that identifies the parameter and a numeric variable named Estimate or Est that contains the starting values. For example, the PDATA= option enables you to use the contents of the "ParameterEstimates" table from one PROC HPNLIN run to supply starting values for a subsequent run, as follows:

```
proc hpnlin data=d(obs=30);
   parameters alpha=100 beta=3 gamma=4;
   Switch = 1/(1+gamma*exp(beta*log(dose)));
   model y ~ residual(alpha*Switch);
   ods output ParameterEstimates=pest;
run;

proc hpnlin data=d;
   parameters / pdata=pest;
   Switch = 1/(1+gamma*exp(beta*log(dose)));
   model y ~ residual(alpha*Switch);
run;
```

You can specify multiple values for a parameter in the PDATA= data set, and the parameters can appear in any order. The starting values are collected by parameter and arranged in ascending order, and duplicate values are removed. The parameter names in the PDATA= data set are not case sensitive. For example, the following DATA step defines starting values for three parameters and a starting grid with $1 \times 3 \times 1 = 3$ points:

```
data test;
   input Parameter $ Estimate;
   datalines;
alpha  100
 BETA   4
 beta   4.1
beta    4.2
beta    4.1
 gamma 30
;
```

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement, you can also control whether a SAS High-Performance Analytics procedure executes in symmetric multiprocessing or massively parallel processing mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

PREDICT Statement

PREDICT *'label' expression* < *options* > **;**

PREDICT *'label'* **MEAN** < *options* > **;**

The PREDICT statement enables you to construct predictions of an expression across all of the observations in the input data set. Multiple PREDICT statements are permitted. You must provide a quoted string to identify the predicted expression and then provide the predicted value. You can specify the predicted value either with a SAS programming expression that involves the input data set variables and parameters or by using the keyword MEAN. If you specify the keyword MEAN, the predicted mean value for the distribution specified in the MODEL statement is used. Predicted values are computed using the final parameter estimates. Standard errors of prediction are computed using the delta method (Billingsley 1986; Cox 1998). Results for all PREDICT statements are placed in the output data set that you specify with the OUT= option in the PROC HPNLIN statement. See the section "Output Data Sets" on page 26 for more details about output data sets in High-Performance Analytics procedures.

The following options are available in the PREDICT statement.

ALPHA=*α*
specifies the alpha level to be used in computing confidence limits. The default value corresponds to the ALPHA= option in the PROC HPNLIN statement.

DF=*d*
specifies the degrees of freedom to be used in computing confidence limits. The default value corresponds to the DF= option in the PROC HPNLIN statement.

LOWER=*name*
specifies a variable that contains the lower confidence limit of the predicted value.

PRED=*name*
specifies a variable that contains the predicted value.

PROBT=*name*
specifies a variable that contains the p-value of the predicted value.

STDERR=*name*
specifies a variable that contains the standard error of the predicted value.

TVALUE=*name*
specifies a variable that contains the t statistic for the predicted value.

UPPER=*name*
specifies a variable that contains the upper confidence limit of the predicted value.

RESTRICT Statement

RESTRICT *restriction1* < , *restriction2 . . .* > **;**

The RESTRICT statement imposes linear restrictions on the model's parameters estimates. You can specify any number of RESTRICT statements.

Each *restriction* is written as an expression, optionally followed by an equality operator (=) or an inequality operator (<, >, <=, >=), followed by a second expression as follows:

expression **<** *operator expression* **>**

The *operator* can be =, <, >, <= , or >=. The operator and second expression are optional. When they are omitted, the *operator* defaults to = and the second *expression* defaults to the value 0.

Restriction expressions can be composed of parameter names, arithmetic operators, functions, and constants. Comparison operators (such as = or <) and logical operators (such as &) cannot be used in RESTRICT statement expressions. Parameters named in restriction expressions must be among the parameters estimated by the model. Restriction expressions cannot refer to other variables defined in the program or the DATA= data set. The restriction expressions must be linear functions of the parameters.

The following example illustrates how to use the RESTRICT statement to impose a linear constraint on parameters:

```
proc hpnlin;
   parms alpha beta;
   f = (x/alpha + beta)**2
   model y ~ residual(f);
   restrict beta < 2*(alpha + constant('pi'));
run;
```

The preceding RESTRICT statement represents the following model constraint:

$$\beta < 2(\alpha + \pi)$$

Programming Statements

Programming statements define the arguments of the MODEL, ESTIMATE, and PREDICT statements in PROC HPNLIN. Most of the programming statements that can be used in the SAS DATA step can also be used in the HPNLIN procedure. See *SAS Language Reference: Concepts* for a description of SAS programming statements. The following are valid programming statements:

ABORT;
CALL *name* **[(** *expression* **[,** *expression* **. . .])];**
DELETE;
DO[*variable* **=** *expression*
[TO *expression***] [BY** *expression***]**
[, *expression* **[TO** *expression***] [BY** *expression* **] . . .]**
]
[WHILE *expression* **] [UNTIL** *expression* **] ;**
END;
GOTO *statement_label*;
IF *expression*;
IF *expression* **THEN** *program_statement*;
ELSE *program_statement*;
variable **=** *expression*;
variable **+** *expression*;
LINK *statement_label*;
PUT [*variable***] [=] [...];**
RETURN;
SELECT[(*expression***)];**
STOP;
SUBSTR(*variable***,** *index***,** *length* **)=** *expression*;
WHEN (*expression***)** *program_statement*;
OTHERWISE *program_statement*;

For the most part, the SAS programming statements work the same as they do in the SAS DATA step, as documented in *SAS Language Reference: Concepts*. However, they differ as follows differences:

- The ABORT statement does not allow any arguments.
- The DO statement does not allow a character index variable. Thus

  ```
  do i = 1,2,3;
  ```

  is supported, but the following statement is not supported:

  ```
  do i = 'A','B','C';
  ```

- In contrast to other procedures that share PROC HPNLIN's programming syntax, PROC HPNLIN does not support the LAG function. Because observations are not processed sequentially when High-Performance Analytics procedures perform the parameter optimization, information for computing lagged values is not available.
- The PUT statement, used mostly for program debugging in PROC HPNLIN, supports only some of the features of the DATA step PUT statement, and it has some new features that the DATA step PUT statement does not have:
  - The PROC HPNLIN PUT statement does not support line pointers, factored lists, iteration factors, overprinting, _INFILE_, the colon (:) format modifier, or "$".
  - The PROC HPNLIN PUT statement supports expressions, but the expression must be enclosed in parentheses. For example, the following statement displays the square root of x:

```
put  (sqrt(x));
```

  - The PROC HPNLIN PUT statement supports the item _PDV_ to display a formatted listing of all variables in the program. For example, the following statement displays a much more readable listing of the variables than the _ALL_ print item:

```
put _pdv_;
```

- The WHEN and OTHERWISE statements enable you to specify more than one target statement. That is, DO/END groups are not necessary for multiple statement WHENs. For example, the following syntax is valid:

```
select;
   when (exp1) stmt1;
               stmt2;
   when (exp2) stmt3;
               stmt4;
end;
```

When you code your programming statements, avoid defining variables that begin with an underscore (_) because they might conflict with internal variables that are created by PROC HPNLIN. The MODEL statement must come after any SAS programming statements that define or modify terms that are used to specify the model.

Details: HPNLIN Procedure

Least Squares Estimation

The most general models estimated by PROC HPNLIN can be represented using the equations

$$\begin{aligned} \mathbf{Y} &= \mathbf{f}(\boldsymbol{\beta}; \mathbf{z}_1, \cdots, \mathbf{z}_k) + \boldsymbol{\epsilon} \\ \mathrm{E}[\boldsymbol{\epsilon}] &= \mathbf{0} \\ \mathrm{Var}[\boldsymbol{\epsilon}] &= \sigma^2 \mathbf{I} \end{aligned}$$

where

$\mathbf{Y}$	is the $(n \times 1)$ vector of observed responses
$\mathbf{f}$	is the nonlinear prediction function of parameters and regressor variables
$\boldsymbol{\beta}$	is the vector of model parameters to be estimated
$\mathbf{z}_1, \cdots, \mathbf{z}_k$	are the $(n \times 1)$ vectors for each of the k regressor variables
$\boldsymbol{\epsilon}$	is the $(n \times 1)$ vector of residuals
σ^2	is the variance of the residuals

In these models, the distribution of the residuals is not specified and the model parameters are estimated using the least squares method. For the standard errors and confidence limits in the "ParameterEstimates" table to apply, the errors are assumed to be homoscedastic, uncorrelated, and have zero mean.

Built-in Log-Likelihood Functions

For models in which the distribution of model errors is specified, the HPNLIN procedure estimates parameters by maximizing the value of a log-likelihood function for the specified distribution. The log-likelihood functions used by PROC HPNLIN for the supported error distributions are as follows:

$Y \sim \text{normal}(m, v)$

$$
\begin{aligned}
l(m, v; y) &= -\frac{1}{2}\left(\log\{2\pi\} + \frac{(y-m)^2}{v} + \log\{v\}\right) \\
\mathrm{E}[Y] &= m \\
\mathrm{Var}[Y] &= v \\
v &> 0
\end{aligned}
$$

$Y \sim \text{binary}(p)$

$$
\begin{aligned}
l_1(p; y) &= \begin{cases} y \ \log\{p\} & y > 0 \\ 0 & \text{otherwise} \end{cases} \\
l_2(p; y) &= \begin{cases} (1-y) \ \log\{1-p\} & y < 1 \\ 0 & \text{otherwise} \end{cases} \\
l(p; y) &= l_1(p; y) + l_2(p; y) \\
\mathrm{E}[Y] &= p \\
\mathrm{Var}[Y] &= p\,(1-p) \\
0 &< p < 1
\end{aligned}
$$

$Y \sim \text{binomial}(n, p)$

$$
\begin{aligned}
l_c &= \log\{\Gamma(n+1)\} - \log\{\Gamma(y+1)\} - \log\{\Gamma(n-y+1)\} \\
l_1(n, p; y) &= \begin{cases} y \ \log\{p\} & y > 0 \\ 0 & \text{otherwise} \end{cases} \\
l_2(n, p; y) &= \begin{cases} (n-y) \ \log\{1-p\} & n-y > 0 \\ 0 & \text{otherwise} \end{cases} \\
l(n, p; y) &= l_c + l_1(n, p; y) + l_2(n, p; y) \\
\mathrm{E}[Y] &= n\,p \\
\mathrm{Var}[Y] &= n\,p\,(1-p) \\
0 &< p < 1
\end{aligned}
$$

$Y \sim \text{gamma}(a, b)$

$$
\begin{aligned}
l(a, b; y) &= -a \log\{b\} - \log\{\Gamma(a)\} + (a-1)\log\{y\} - y/b \\
\text{E}[Y] &= ab \\
\text{Var}[Y] &= ab^2 \\
a &> 0 \\
b &> 0
\end{aligned}
$$

This parameterization of the gamma distribution differs from the parameterization used in the GLIMMIX and GENMOD procedures. The scale parameter in PROC HPNLIN is expressed as the inverse of the scale parameter in PROC GLIMMIX and PROC GENMOD. The PROC HPNLIN parameter represents the scale of the magnitude of the residuals. The scale parameter in PROC GLIMMIX can be estimated by using the following statements:

```
proc glimmix;
   model y = x / dist=gamma s;
run;
```

The following statements show how to estimate the equivalent scale parameter using PROC HPNLIN:

```
proc hpnlin;
   parms b0=1 b1=0 scale=14;
   linp = b0 + b1*x;
   mu   = exp(linp);
   b    = mu*scale;
   model y ~ gamma(1/scale,b);
run;
```

$Y \sim \text{negbin}(n, p)$

$$
\begin{aligned}
l(n, p; y) &= \log\{\Gamma(n+y)\} - \log\{\Gamma(n)\} - \log\{\Gamma(y+1)\} \\
&\quad + n\log\{p\} + y\log\{1-p\} \\
\text{E}[Y] &= n\left(\frac{1-p}{p}\right) \\
\text{Var}[Y] &= n\left(\frac{1-p}{p^2}\right) \\
n &\geq 0 \\
0 &< p < 1
\end{aligned}
$$

The parameter n can be real-numbered; it does not have to be integer-valued.

$Y \sim \text{Poisson}(m)$

$$
\begin{aligned}
l(m; y) &= y\log\{m\} - m - \log\{\Gamma(y+1)\} \\
\text{E}[Y] &= m \\
\text{Var}[Y] &= m \\
m &> 0
\end{aligned}
$$

Computational Method

Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPNLIN procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statement, the HPNLIN procedure determines threading as if it executed on a system with four CPUs, regardless of the actual CPU count:

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This specification overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement. Specifying this option overrides the CPUCOUNT system option and instructs the HPNLIN procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output. The HPNLIN procedure allocates one thread per CPU.

The HPNLIN procedure divides the data processed on a single machine among the threads—that is, the HPNLIN procedure implements multithreading by parallelizing computations across the data. For example, if the input data set has $1,000$ observations and you are running with four threads, then 250 observations are associated with each thread. All operations that require access to the data are then multithreaded. These operations include the following:

- calculation of objective function values for the initial parameter grid
- objective function calculation
- gradient calculation
- Hessian calculation
- scoring of observations

In addition, operations on matrices such as sweeps might be multithreaded provided that the matrices are of sufficient size to realize performance benefits from managing multiple threads for the particular matrix operation.

Choosing an Optimization Algorithm

First- or Second-Order Algorithms

The factors that go into choosing a particular optimization technique for a particular problem are complex. Trial and error can be involved.

For many optimization problems, computing the gradient takes more computer time than computing the function value. Computing the Hessian sometimes takes *much* more computer time and memory than computing the gradient, especially when there are many decision variables. Unfortunately, optimization techniques that do not use some kind of Hessian approximation usually require many more iterations than techniques that do use a Hessian matrix, and, as a result the total run time of these techniques is often longer. Techniques that do not use the Hessian also tend to be less reliable. For example, they can terminate more easily at stationary points than at global optima.

Table 19.3 shows which derivatives are required for each optimization technique.

Table 19.3 Derivatives Required

Algorithm	First-Order	Second-Order
TRUREG	x	x
NEWRAP	x	x
NRRIDG	x	x
QUANEW	x	-
DBLDOG	x	-
CONGRA	x	-
NMSIMP	-	-
LEVMAR	x	-

The second-derivative methods TRUREG, NEWRAP, and NRRIDG are best for small problems for which the Hessian matrix is not expensive to compute. Sometimes the NRRIDG algorithm can be faster than the TRUREG algorithm, but TRUREG can be more stable. The NRRIDG algorithm requires only one matrix with $p(p+1)/2$ double words; TRUREG and NEWRAP require two such matrices. Here, p denotes the number of parameters in the optimization.

The first-derivative methods QUANEW and DBLDOG are best for medium-sized problems for which the objective function and the gradient are much faster to evaluate than the Hessian. In general, the QUANEW and DBLDOG algorithms require more iterations than TRUREG, NRRIDG, and NEWRAP, but each iteration can be much faster. The QUANEW and DBLDOG algorithms require only the gradient to update an approximate Hessian, and they require slightly less memory than TRUREG or NEWRAP.

The first-derivative method CONGRA is best for large problems for which the objective function and the gradient can be computed much faster than the Hessian and for which too much memory is required to store the (approximate) Hessian. In general, the CONGRA algorithm requires more iterations than QUANEW or DBLDOG, but each iteration can be much faster. Because CONGRA requires only a factor of p double-word memory, many large applications can be solved only by CONGRA.

The no-derivative method NMSIMP is best for small problems for which derivatives are not continuous or are very difficult to compute.

The LEVMAR method is only appropriate for least squares optimization problems.

Each optimization method uses one or more convergence criteria that determine when it has converged. An algorithm is considered to have converged when any one of the convergence criteria is satisfied. For example, under the default settings the QUANEW algorithm converges if ABSGCONV <1E−5, FCONV $< 2 \times \epsilon$, or GCONV <1E−8.

By default, the HPNLIN procedure applies the NRRIDG algorithm because it can take advantage of mutli-threading in Hessian computations and inversions. If the number of parameters becomes large, specifying TECHNIQUE=QUANEW, which is a first-order method with good overall properties, is recommended.

Algorithm Descriptions

The following subsections provide details about each optimization technique and follow the same order as Table 19.3.

Trust Region Optimization (TRUREG)

The trust region method uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function $f(\boldsymbol{\psi})$ have continuous first- and second-order derivatives inside the feasible region.

The trust region method iteratively optimizes a quadratic approximation to the nonlinear objective function within a hyperelliptic trust region with radius Δ that constrains the step size that corresponds to the quality of the quadratic approximation. The trust region method is implemented based on Dennis, Gay, and Welsch (1981); Gay (1983); Moré and Sorensen (1983).

The trust region method performs well for small- to medium-sized problems, and it does not need many function, gradient, and Hessian calls. However, if the computation of the Hessian matrix is computationally expensive, one of the quasi-Newton or conjugate gradient algorithms might be more efficient.

Newton-Raphson Optimization with Line Search (NEWRAP)

The NEWRAP technique uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function have continuous first- and second-order derivatives inside the feasible region. If second-order derivatives are computed efficiently and precisely, the NEWRAP method can perform well for medium-sized to large problems, and it does not need many function, gradient, and Hessian calls.

This algorithm uses a pure Newton step when the Hessian is positive-definite and when the Newton step reduces the value of the objective function successfully. Otherwise, a combination of ridging and line search is performed to compute successful steps. If the Hessian is not positive-definite, a multiple of the identity matrix is added to the Hessian matrix to make it positive-definite (Eskow and Schnabel 1991).

In each iteration, a line search is performed along the search direction to find an approximate optimum of the objective function. The default line-search method uses quadratic interpolation and cubic extrapolation (LIS=2).

Newton-Raphson Ridge Optimization (NRRIDG)

The NRRIDG technique uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$ and the Hessian matrix $\mathbf{H}(\boldsymbol{\psi}^{(k)})$; thus, it requires that the objective function have continuous first- and second-order derivatives inside the feasible region.

This algorithm uses a pure Newton step when the Hessian is positive-definite and when the Newton step reduces the value of the objective function successfully. If at least one of these two conditions is not satisfied, a multiple of the identity matrix is added to the Hessian matrix.

The NRRIDG method performs well for small- to medium-sized problems, and it does not require many function, gradient, and Hessian calls. However, if the computation of the Hessian matrix is computationally expensive, one of the quasi-Newton or conjugate gradient algorithms might be more efficient.

Because the NRRIDG technique uses an orthogonal decomposition of the approximate Hessian, each iteration of NRRIDG can be slower than that of the NEWRAP technique, which works with a Cholesky decomposition. However, NRRIDG usually requires fewer iterations than NEWRAP.

Quasi-Newton Optimization (QUANEW)

The (dual) quasi-Newton method uses the gradient $\mathbf{g}(\boldsymbol{\psi}^{(k)})$, and it does not need to compute second-order derivatives because they are approximated. It works well for medium-sized to moderately large optimization problems, where the objective function and the gradient can be computed much faster than the Hessian. However, in general it requires more iterations than the TRUREG, NEWRAP, and NRRIDG techniques, which compute second-order derivatives. QUANEW is the default optimization algorithm because it provides an appropriate balance between the speed and stability required for most nonlinear mixed model applications.

The QUANEW technique implemented by the HPNLIN procedure is the dual quasi-Newton algorithm, which updates the Cholesky factor of an approximate Hessian.

In each iteration, a line search is performed along the search direction to find an approximate optimum. The line-search method uses quadratic interpolation and cubic extrapolation to obtain a step size α that satisfies the Goldstein conditions. One of the Goldstein conditions can be violated if the feasible region defines an upper limit of the step size. Violating the left-side Goldstein condition can affect the positive-definiteness of the quasi-Newton update. In that case, either the update is skipped or the iterations are restarted with an identity matrix, resulting in the steepest descent or ascent search direction.

The QUANEW algorithm uses its own line-search technique.

Double-Dogleg Optimization (DBLDOG)

The double-dogleg optimization method combines the ideas of the quasi-Newton and trust region methods. In each iteration, the double-dogleg algorithm computes the step $\mathbf{s}^{(k)}$ as the linear combination of the steepest descent or ascent search direction $\mathbf{s}_1^{(k)}$ and a quasi-Newton search direction $\mathbf{s}_2^{(k)}$:

$$\mathbf{s}^{(k)} = \alpha_1 \mathbf{s}_1^{(k)} + \alpha_2 \mathbf{s}_2^{(k)}$$

The step is requested to remain within a prespecified trust region radius (Fletcher 1987, p. 107). Thus, the DBLDOG subroutine uses the dual quasi-Newton update but does not perform a line search.

The double-dogleg optimization technique works well for medium-sized to moderately large optimization problems, where the objective function and the gradient are much faster to compute than the Hessian. The implementation is based on Dennis and Mei (1979); Gay (1983), but it is extended for dealing with boundary and linear constraints. The DBLDOG technique generally requires more iterations than the TRUREG, NEWRAP, and NRRIDG techniques, which require second-order derivatives; however, each of the DBLDOG iterations is computationally cheap. Furthermore, the DBLDOG technique requires only gradient calls for the update of the Cholesky factor of an approximate Hessian.

Conjugate Gradient Optimization (CONGRA)

Second-order derivatives are not required by the CONGRA algorithm and are not even approximated. The CONGRA algorithm can be expensive in function and gradient calls, but it requires only $O(p)$ memory for

unconstrained optimization. In general, many iterations are required to obtain a precise solution, but each of the CONGRA iterations is computationally cheap.

The CONGRA subroutine should be used for optimization problems with large p. For the unconstrained or boundary-constrained case, CONGRA requires only $O(p)$ bytes of working memory, whereas all other optimization methods require order $O(p^2)$ bytes of working memory. During p successive iterations, uninterrupted by restarts or changes in the working set, the conjugate gradient algorithm computes a cycle of p conjugate search directions. In each iteration, a line search is performed along the search direction to find an approximate optimum of the objective function. The default line-search method uses quadratic interpolation and cubic extrapolation to obtain a step size α that satisfies the Goldstein conditions. One of the Goldstein conditions can be violated if the feasible region defines an upper limit for the step size. Other line-search algorithms can be specified with the LIS= option.

Nelder-Mead Simplex Optimization (NMSIMP)

The Nelder-Mead simplex method does not use any derivatives and does not assume that the objective function has continuous derivatives. The objective function itself needs to be continuous. This technique is quite expensive in the number of function calls, and it might be unable to generate precise results for $p \gg 40$.

The original Nelder-Mead simplex algorithm is implemented and extended to boundary constraints. This algorithm does not compute the objective for infeasible points, but it changes the shape of the simplex adapting to the nonlinearities of the objective function, which contributes to an increased speed of convergence. It uses a special termination criterion.

Displayed Output

The following sections describe the output that PROC HPNLIN produces by default. The output is organized into various tables, which are discussed in the order of their appearance.

Performance Information

The "Performance Information" table is produced by default and displays information about the grid host for distributed execution and about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The numbers of compute nodes and threads are also displayed, depending on the environment.

Specifications

The "Specifications" table displays basic information about the model such as the data source, the dependent variable, the distribution being modeled, and the optimization technique.

Number of Observations

The "Number of Observations" table displays the number of observations read from the input data set and the number of observations used in the analysis.

Dimensions

The "Dimensions" table displays the number of parameters estimated in the model and the number of upper and lower bounds which are imposed on the parameters.

Parameters

The "Parameters" table displays the initial values of parameters used to start the estimation process. This information can be limited by using the BEST= option in the PARAMETERS statement when a large number of initial parameter value combinations are specified. The parameter combinations and their corresponding objective function values are listed in increasing order of objective function value.

Iteration History

The "Iteration History" table displays for each iteration of the optimization the number of function evaluations (including gradient and Hessian evaluations), the value of the objective function, the change in the objective function from the previous iteration, and the absolute value of the largest (projected) gradient element.

Convergence Status

The convergence status table is a small ODS table that follows the "Iteration History" table in the default output. In the listing it appears as a message that identifies whether the optimization succeeded and which convergence criterion was met. If the optimization fails, the message indicates the reason for the failure. If you save the convergence status table to an output data set, a numeric Status variable is added that enables you to assess convergence programmatically. The values of the Status variable encode the following:

0	Convergence was achieved or an optimization was not performed (because of TECHNIQUE=NONE).
1	The objective function could not be improved.
2	Convergence was not achieved because of a user interrupt or because a limit was exceeded, such as the maximum number of iterations or the maximum number of function evaluations. To modify these limits, see the MAXITER=, MAXFUNC=, and MAXTIME= options in the PROC HPNLIN statement.
3	Optimization failed to converge because function or derivative evaluations failed at the starting values or during the iterations or because a feasible point that satisfies the parameter constraints could not be found in the parameter space.

Linear Constraints

The "Linear Constraints" table summarizes the linear constraints that were applied to the model using the RESTRICT statements. All the constraints specified in the model are listed in the "Linear Constraints" table together with information about whether each constraint represents an inequality or equality condition and whether that constraint is active for the final parameter estimates.

Fit Statistics

The "Fit Statistics" table displays a variety of measures of fit depending on whether the model was estimated using least squares or maximum likelihood. In both cases, smaller values of the fit statistics indicate better fit.

For least squares estimations, the "Fit Statistics" table displays the sum of squares of errors and the variance of errors.

For maximum likelihood estimations, the table displays information criteria using the following formulas, where p denotes the number of effective parameters, n denotes the number of observations used, and l is the log likelihood evaluated at the converged estimates

$$\begin{aligned}
\text{AIC} &= -2l + 2p \\
\text{AICC} &= \begin{cases} -2l + 2pn/(n-p-1) & f > p+2 \\ -2l + 2p(p+2) & \text{otherwise} \end{cases} \\
\text{BIC} &= -2l + p\log(f)
\end{aligned}$$

The information criteria values displayed in the "Fit Statistics" table are not based on a normalized log-likelihood function.

ANOVA

The "Analysis of Variance" table is displayed only for least squares estimations. The ANOVA table displays the number of degrees of freedom and the sum of squares attributed to the model, the error, and the total. The ANOVA table also reports the variance of the model and the errors, the F statistic, and its probability for the model.

Parameter Estimates

The parameter estimates, their estimated (asymptotic) standard errors t statistics, and associated p-values for the hypothesis that the parameter is 0 are presented in the "Parameter Estimates" table. Confidence limits are displayed for each parameter based on the value of the ALPHA= option in the PROC HPNLIN statement.

Additional Estimates

The "Additional Estimates" table displays identical information to the "Parameter Estimates" table for the expressions that appear in the optional ESTIMATE statements. The table is generated when one or more ESTIMATE statements are specified. Because a separate ALPHA= option can be specified for each ESTIMATE statement, the "Additional Estimates" table also includes a column that indicates each confidence interval's corresponding significance level.

Covariance

The "Covariance" table appears when the COV option is specified in the PROC HPNLIN statement. The "Covariance" table displays a matrix of covariances between each pair of estimated parameters.

Correlation

The "Correlation" table appears when the CORR option is specified in the PROC HPNLIN statement. The "Correlation" table displays the correlation matrix for the estimated parameters.

Additional Estimates Covariance

The "Covariance of Additional Estimates" table appears when the ECOV option is specified in the PROC HPNLIN statement. The "Covariance of Additional Estimates" table displays a matrix of covariances between each pair of expressions specified in ESTIMATE statements.

Additional Estimates Correlation

The "Correlation of Additional Estimates" table appears when the ECORR option is specified in the PROC HPNLIN statement. The "Correlation of Additional Estimates" table displays the correlation matrix for the expressions specified in ESTIMATE statements.

Procedure Task Timing

If you specify the DETAILS option in the PERFORMANCE statement, the procedure also produces a "Procedure Task Timing" table in which elapsed times (absolute and relative) for the main tasks of the procedure are displayed.

ODS Table Names

Each table created by the HPNLIN procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 19.4.

Table 19.4 ODS Tables Produced by PROC HPNLIN

Table Name	Description	Required Statement / Option
AdditionalEstimates	Functions of estimated parameters and their associated statistics	ESTIMATE statement
ANOVA	Least squares analysis of variance information	RESIDUAL distribution in the MODEL statement
Constraints	Information about the model's linear constraints	RESTRICT statement
ConvergenceStatus	Optimization success and convergence information	Default output
CorrB	Parameter correlation matrix	CORR option in the PROC HPNLIN statement
CovB	Parameter covariance matrix	COV option in the PROC HPNLIN statement
Dimensions	Number of parameters and their bounds	Default output

Table 19.4 *continued*

Table Name	Description	Required Statement / Option
ECorrB	Additional estimates' correlation matrix	ECORR option in the PROC HPNLIN statement
ECovB	Additional estimates' covariance matrix	ECOV option in the PROC HPNLIN statement
FitStatistics	Statistics concerning the quality of the fit	Default output
IterHistory	Optimizer iteration information	Default output
NObs	Number of observations read and used	Default output
ParameterEstimates	Parameter estimates and associated statistics	Default output
Parameters	Initial parameter values	Default output
PerformanceInfo	Information about high-performance computing environment	Default output
Specifications	Basic model characteristics	Default output

Examples: HPNLIN Procedure

Example 19.1: Segmented Model

Suppose you are interested in fitting a model that consists of two segments that connect in a smooth fashion. For example, the following model states that for values of x less than x_0 the mean of Y is a quadratic function in x, and for values of x greater than x_0 the mean of Y is constant:

$$\mathrm{E}[Y|x] = \begin{cases} \alpha + \beta x + \gamma x^2 & \text{if } x < x_0 \\ c & \text{if } x \geq x_0 \end{cases}$$

In this model equation α, β, and γ are the coefficients of the quadratic segment, and c is the plateau of the mean function. The HPNLIN procedure can fit such a segmented model even when the join point, x_0, is unknown.

You also want to impose conditions on the two segments of the model. First, the curve should be continuous—that is, the quadratic and the plateau section need to meet at x_0. Second, the curve should be smooth—that is, the first derivative of the two segments with respect to x need to coincide at x_0.

The continuity condition requires that

$$c = \mathrm{E}[Y|x_0] = \alpha + \beta x_0 + \gamma x_0^2$$

The smoothness condition requires that

$$\frac{\partial \mathrm{E}[Y|x_0]}{\partial x} = \beta + 2\gamma x_0 \equiv 0$$

If you solve for x_0 and substitute into the expression for c, the two conditions jointly imply that

$$x_0 = -\beta/2\gamma$$
$$c = \alpha - \beta^2/4\gamma$$

Although there are five unknowns, the model contains only three independent parameters. The continuity and smoothness restrictions together completely determine two parameters given the other three.

The following DATA step creates the SAS data set for this example:

```
data a;
   input y x @@;
   datalines;
.46 1  .47  2 .57  3 .61  4 .62  5 .68  6 .69  7
.78 8  .70  9 .74 10 .77 11 .78 12 .74 13 .80 13
.80 15 .78 16
 ;
```

The following PROC HPNLIN statements fit this segmented model:

```
proc hpnlin data=a out=b;
   parms alpha=.45 beta=.05 gamma=-.0025;

   x0 = -.5*beta / gamma;

   if (x < x0) then
        yp = alpha + beta*x  + gamma*x*x;
   else
        yp = alpha + beta*x0 + gamma*x0*x0;

   model y ~ residual(yp);

   estimate 'join point' -beta/2/gamma;
   estimate 'plateau value c' alpha - beta**2/(4*gamma);
   predict 'predicted' yp pred=yp;
   predict 'response' y pred=y;
   predict 'x' x pred=x;
run;
```

The parameters of the model are α, β, and γ. They are represented in the PROC HPNLIN statements by the variables alpha, beta, and gamma, respectively. In order to model the two segments, a conditional statement assigns the appropriate expression to the mean function depending on the value of x_0. ESTIMATE statements compute the values of x_0 and c. The PREDICT statement computes predicted values for plotting and saves them to data set b.

The results from fitting this model with PROC HPNLIN are shown in Output 19.1.1 through Output 19.1.3. The iterative optimization converges after six iterations (Output 19.1.1). Output 19.1.2 shows the estimated parameters. Output 19.1.3 indicates that the join point is 12.7477 and the plateau value is 0.7775.

Output 19.1.1 Nonlinear Least Squares Iterative Phase

Quadratic Model with Plateau

The HPNLIN Procedure

Iteration History

Iteration	Evaluations	Objective Function	Change	Max Gradient
0	5	0.0035144531	.	7.184063
1	2	0.0007352716	0.00277918	2.145337
2	2	0.0006292751	0.00010600	0.032551
3	2	0.0006291261	0.00000015	0.002952
4	2	0.0006291244	0.00000000	0.000238
5	2	0.0006291244	0.00000000	0.000023
6	2	0.0006291244	0.00000000	2.313E-6

Convergence criterion (GCONV=1E-8) satisfied.

Output 19.1.2 Least Squares Analysis for the Quadratic Model

Analysis of Variance

Source	DF	Sum of Squares	Mean Square	F Value	Approx Pr > F
Model	2	0.1769	0.0884	114.22	<.0001
Error	13	0.0101	0.000774		
Corrected Total	15	0.1869			

Parameter Estimates

Parameter	Estimate	Standard Error	DF	t Value	Pr > |t|	Approximate 95% Confidence Limits	
alpha	0.3921	0.02667	13	14.70	<.0001	0.3345	0.4497
beta	0.06046	0.008423	13	7.18	<.0001	0.04227	0.07866
gamma	-0.00237	0.000551	13	-4.30	0.0009	-0.00356	-0.00118

Output 19.1.3 Additional Estimates for the Quadratic Model

Additional Estimates

Label	Estimate	Standard Error	DF	t Value	Pr > |t|	Alpha
join point	12.7477	1.2781	13	9.97	<.0001	0.05
plateau	0.7775	0.01232	13	63.11	<.0001	0.05

Additional Estimates

Label	Approximate Confidence Limits	
join point	9.9864	15.5089
plateau	0.7509	0.8041

The following statements produce a graph of the observed and predicted values with reference lines for the join point and plateau estimates (Output 19.1.4):

```
proc sgplot data=b noautolegend;
   yaxis label='Observed or Predicted';
   refline 0.7775  / axis=y label="Plateau"    labelpos=min;
   refline 12.7477 / axis=x label="Join point" labelpos=min;
   scatter y=y  x=x;
   series  y=yp x=x;
run;
```

Output 19.1.4 Observed and Predicted Values for the Quadratic Model



References

Billingsley, P. (1986), *Probability and Measure*, Second Edition, New York: John Wiley & Sons.

Cox, C. (1998), "Delta Method," *Encyclopedia of Biostatistics*, 1125–1127.

Dennis, J. E., Gay, D. M., and Welsch, R. E. (1981), "An Adaptive Nonlinear Least-Squares Algorithm," *ACM Transactions on Mathematical Software*, 7, 348–368.

Dennis, J. E. and Mei, H. H. W. (1979), "Two New Unconstrained Optimization Algorithms Which Use Function and Gradient Values," *Journal of Optimization Theory Applications*, 28, 453–482.

Eskow, E. and Schnabel, R. B. (1991), "Algorithm 695: Software for a New Modified Cholesky Factorization," *ACM Transactions on Mathematical Software*, 17, 306–312.

Fletcher, R. (1987), *Practical Methods of Optimization*, Second Edition, Chichester, UK: John Wiley & Sons.

Gay, D. M. (1983), "Subroutines for Unconstrained Minimization," *ACM Transactions on Mathematical Software*, 9, 503–524.

Moré, J. J. and Sorensen, D. C. (1983), "Computing a Trust-Region Step," *SIAM Journal on Scientific and Statistical Computing*, 4, 553–572.

Ratkowsky, D. (1990), *Handbook of Nonlinear Regression Models*, New York: Marcel Dekker.

Chapter 20
The HPQLIM Procedure

Contents

Overview: HPQLIM Procedure **472**
PROC HPQLIM Features 472
Getting Started: HPQLIM Procedure **473**
Syntax: HPQLIM Procedure **475**
Functional Summary 475
PROC HPQLIM Statement 477
BOUNDS Statement 480
ENDOGENOUS Statement 481
FREQ Statement 482
HETERO Statement 482
INIT Statement 483
MODEL Statement 484
OUTPUT Statement 485
PERFORMANCE Statement 486
RESTRICT Statement 487
TEST Statement 487
WEIGHT Statement 488
Details: HPQLIM Procedure **489**
Limited Dependent Variable Models 489
Stochastic Frontier Production and Cost Models 490
Heteroscedasticity 493
Tests on Parameters 493
Output to SAS Data Set 494
OUTEST= Data Set 498
Naming 498
ODS Table Names 499
Examples: The HPQLIM Procedure **500**
Example 20.1: High-Performance Model with Censoring 500
References **505**

Overview: HPQLIM Procedure

The HPQLIM (high-performance qualitative and limited dependent variable model) procedure is a high-performance version of the QLIM procedure in SAS/ETS software, which analyzes univariate limited dependent variable models in which dependent variables are observed only in a limited range of values. Unlike the QLIM procedure, which can be run only on an individual workstation, the HPQLIM procedure takes advantage of a computing environment that enables it to distribute the optimization task among one or more nodes. In addition, each node can use one or more threads to carry out the optimization on its subset of the data. When several nodes are used with each node using several threads to carry out its part of the work, the result is a highly parallel computation that provides a dramatic gain in performance.

With the HPQLIM procedure you can read and write data in distributed form and perform analyses in massively parallel processing (MPP) and symmetric multiprocessing (SMP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about how to affect the execution mode of SAS High-Performance Analytics procedures.

The HPQLIM procedure is specifically designed to operate in the high-performance distributed environment. By default, PROC HPQLIM performs computations in multiple threads.

The HPQLIM procedure is similar in use to the other SAS procedures that support regression or simultaneous equations models. For example, the standard model with censoring or truncation is estimated by specifying the endogenous variable to be truncated or censored. When the data are limited by specific values or variables, the limits of the dependent variable can be specified with the CENSORED or TRUNCATED option in the ENDOGENOUS or MODEL statement. For example, the two-limit censored model requires two variables: one that contains the lower (bottom) bound and one that contains the upper (top) bound. The following statements execute the model in the distributed computing environment with two threads and four nodes:

```
proc hpqlim data=a;
   model y = x1 x2 x3;
   endogenous y ~ censored(lb=bottom ub=top);
   performance nthreads=2 nodes=4 details;
run;
```

The bounds can be numbers if they are fixed for all observations in the data set. For example, the standard Tobit model can be specified as follows:

```
proc hpqlim data=a;
   model y = x1 x2 x3;
   endogenous y ~ censored(lb=0);
   performance nthreads=2 nodes=4 details;
run;
```

PROC HPQLIM Features

The HPQLIM procedure supports the following models:

- linear regression models with heteroscedasticity
- Tobit models (censored and truncated) with heteroscedasticity
- stochastic frontier production and cost models

In linear regression models with heteroscedasticity, the assumption that error variance is constant across observations is relaxed. The HPQLIM procedure allows for a number of different linear and nonlinear variance specifications.

The HPQLIM procedure also offers a class of models in which the dependent variable is censored or truncated from below or above or both. When a continuous dependent variable is observed only within a certain range, and values outside this range are not available, the HPQLIM procedure offers a class of models that adjust for truncation. In some cases, the dependent variable is continuous only in a certain range and all values outside this range are reported as being on its boundary. For example, if it is not possible to observe negative values, the value of the dependent variable is reported as equal to 0. Because the data are censored, ordinary least squares (OLS) results are inconsistent, and it cannot be guaranteed that the predicted values from the model fall in the appropriate region.

Stochastic frontier production and cost models allow for random shocks of the production or cost. They include a systematic positive component in the error term that adjusts for technological or cost inefficiency.

The HPQLIM procedure uses maximum likelihood methods. Initial starting values for the nonlinear optimizations are typically calculated by OLS.

Getting Started: HPQLIM Procedure

This example illustrates the use of the HPQLIM procedure. The data were originally published by Mroz (1987) and downloaded from Wooldridge (2002). The following statements show a subset of the Mroz (1987) data set:

```
title1 'Estimating a Tobit model';

data subset;
   input Hours Yrs_Ed Yrs_Exp @@;
   if Hours eq 0 then Lower=.;
      else               Lower=Hours;
datalines;
0 8 9 0 8 12 0 9 10 0 10 15 0 11 4 0 11 6
1000 12 1 1960 12 29 0 13 3 2100 13 36
3686 14 11 1920 14 38 0 15 14 1728 16 3
1568 16 19 1316 17 7 0 17 15
;
```

In these data, Hours is the number of hours the wife worked outside the household in a given year, Yrs_Ed is the years of education, and Yrs_Exp is the years of work experience.

By the nature of the data it is clear, that there are a number of women who committed some positive number of hours to outside work ($y_i > 0$ is observed). There are also a number of women who did not work outside

the home at all ($y_i = 0$ is observed). This yields the following model:

$$y_i^* = \mathbf{x}_i'\boldsymbol{\beta} + \epsilon_i$$

$$y_i = \begin{cases} y_i^* & \text{if } y_i^* > 0 \\ 0 & \text{if } y_i^* \leq 0 \end{cases}$$

where $\epsilon_i \sim iidN(0, \sigma^2)$ and the set of explanatory variables is denoted by $\mathbf{x}_i$. The following statements fit a Tobit model to the hours worked with years of education and experience as covariates:

```
/*-- Tobit Model --*/
proc hpqlim data=subset;
   model hours = yrs_ed yrs_exp;
   endogenous hours ~ censored(lb=0);
   performance nthreads=2 nodes=4 details;
run;
```

The output of the HPQLIM procedure is shown in Output 20.1.

Figure 20.1 Tobit Analysis Results

Estimating a Tobit model

The HPQLIM Procedure

Model Fit Summary

Number of Endogenous Variables	1
Endogenous Variable	Hours
Number of Observations	17
Log Likelihood	-74.93700
Maximum Absolute Gradient	1.18953E-6
Number of Iterations	23
Optimization Method	Quasi-Newton
AIC	157.87400
Schwarz Criterion	161.20685

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Approx Pr > |t|
Intercept	1	-5598.295129	27.692220	-202.16	<.0001
Yrs_Ed	1	373.123254	53.988877	6.91	<.0001
Yrs_Exp	1	63.336247	36.551299	1.73	0.0831
_Sigma	1	1582.859635	390.076480	4.06	<.0001

The "Parameter Estimates" table contains four rows. The first three of these rows correspond to the vector estimate of the regression coefficients $\boldsymbol{\beta}$. The last row is called _Sigma, which corresponds to the estimate of the error variance σ.

Syntax: HPQLIM Procedure

The following statements are available in the HPQLIM procedure:

```
PROC HPQLIM options ;
  BOUNDS bound1 < , bound2 . . . > ;
  FREQ variable ;
  ENDOGENOUS variables ~ options ;
  HETERO dependent variables ~ exogenous variables / options ;
  INIT initvalue1 < , initvalue2 . . . > ;
  MODEL dependent variables = regressors / options ;
  OUTPUT options ;
  RESTRICT restriction1 < , restriction2 . . . > ;
  TEST options ;
  WEIGHT variable ;
```

One MODEL statement is required. If a FREQ or WEIGHT statement is specified more than once, the variable specified in the first instance is used.

Functional Summary

Table 20.1 summarizes the statements and options used with the HPQLIM procedure.

Table 20.1 HPQLIM Functional Summary

Description	Statement	Option
Data Set Options		
Specifies the input data set	HPQLIM	DATA=
Writes parameter estimates to an output data set	HPQLIM	OUTEST=
Writes predictions to an output data set	OUTPUT	OUT=
Declaring the Role of Variables		
Specifies a frequency variable	FREQ	
Specifies a weight variable	WEIGHT	NONORMALIZE
Printing Control Options		
Requests all printing options	HPQLIM	PRINTALL
Prints the correlation matrix of the estimates	HPQLIM	CORRB
Prints the covariance matrix of the estimates	HPQLIM	COVB
Prints a summary iteration listing	HPQLIM	ITPRINT
Suppresses the normal printed output	HPQLIM	NOPRINT
Optimization Process Control Options		
Specifies the maximum number of iterations allowed	MODEL	MAXITER=
Selects the iterative minimization method to use	HPQLIM	METHOD=

Table 20.1 *continued*

Description	Statement	Option
Specifies the maximum number of iterations allowed	HPQLIM	MAXITER=
Specifies the maximum number of function calls	HPQLIM	MAXFUNC=
Specifies the upper limit of CPU time in seconds	HPQLIM	MAXTIME=
Specifies an absolute convergence criterion	HPQLIM	ABSCONV=
Specifies an absolute function convergence criterion	HPQLIM	ABSFCONV=
Specifies an absolute gradient convergence criterion	HPQLIM	ABSGCONV=
Specifies a relative function convergence criterion	HPQLIM	FCONV=
Specifies a relative gradient convergence criterion	HPQLIM	GCONV=
Specifies an absolute parameter convergence criterion	HPQLIM	ABSXCONV=
Specifies a matrix singularity criterion	HPQLIM	SINGULAR=
Sets boundary restrictions on parameters	BOUNDS	
Sets initial values for parameters	INIT	
Sets linear restrictions on parameters	RESTRICT	
Model Estimation Options		
Specifies options specific to Box-Cox transformation	MODEL	BOXCOX()
Suppresses the intercept parameter	MODEL	NOINT
Specifies the method to calculate parameter covariance	HPQLIM	COVEST=
Endogenous Variable Options		
Specifies a censored variable	ENDOGENOUS	CENSORED()
Specifies a truncated variable	ENDOGENOUS	TRUNCATED()
Specifies a stochastic frontier variable	ENDOGENOUS	FRONTIER()
Heteroscedasticity Model Options		
Specifies the function for heteroscedasticity models	HETERO	LINK=
Squares the function for heteroscedasticity models	HETERO	SQUARE
Specifies no constant for heteroscedasticity models	HETERO	NOCONST
Output Control Options		
Outputs predicted values	OUTPUT	PREDICTED
Outputs the structured part	OUTPUT	XBETA
Outputs residuals	OUTPUT	RESIDUAL
Outputs the error standard deviation	OUTPUT	ERRSTD
Outputs marginal effects	OUTPUT	MARGINAL
Outputs the expected value	OUTPUT	EXPECTED
Outputs the conditional expected value	OUTPUT	CONDITIONAL
Outputs technical efficiency measures	OUTPUT	TE1
	OUTPUT	TE2

Table 20.1 *continued*

Description	Statement	Option
Includes covariances in the OUTEST= data set	HPQLIM	COVOUT
Includes correlations in the OUTEST= data set	HPQLIM	CORROUT
Test Request Options		
Requests Wald, Lagrange multiplier, and likelihood ratio tests	TEST	ALL
Requests the WALD test	TEST	WALD
Requests the Lagrange multiplier test	TEST	LM
Requests the likelihood ratio test	TEST	LR

PROC HPQLIM Statement

PROC HPQLIM *options* **;**

The PROC HPQLIM statement invokes the HPQLIM procedure. You can specify the following *options*.

Data Set Options

DATA=*SAS-data-set*
specifies the input SAS data set. If this option is not specified, PROC HPQLIM uses the most recently created SAS data set.

Output Data Set Options

OUTEST=*SAS-data-set*
writes the parameter estimates to an output data set.

COVOUT
writes the covariance matrix for the parameter estimates to the OUTEST= data set. This option is valid only if the OUTEST= option is specified.

CORROUT
writes the correlation matrix for the parameter estimates to the OUTEST= data set. This option is valid only if the OUTEST= option is specified.

Printing Options

NOPRINT
suppresses the normal printed output but does not suppress error listings. If this option is specified, then any other print option is turned off.

PRINTALL
turns on all the printing options. The options set by PRINTALL are COVB and CORRB.

CORRB
prints the correlation matrix of the parameter estimates.

COVB
prints the covariance matrix of the parameter estimates.

ITPRINT
prints the initial parameter estimates, convergence criteria, and all constraints of the optimization. At each iteration, the objective function value, step size, maximum gradient, and slope of search direction are also printed.

Model Estimation Options

COVEST=*covariance-option*
specifies the method to calculate the covariance matrix of parameter estimates. You can specify the following *covariance-options*:

OP	specifies the covariance from the outer product matrix.
HESSIAN	specifies the covariance from the inverse Hessian matrix.
QML	specifies the covariance from the outer product and Hessian matrices (the quasi-maximum likelihood estimates).

The default is COVEST=HESSIAN.

Optimization Control Options

PROC HPQLIM uses the nonlinear optimization (NLO) subsystem to perform nonlinear optimization tasks. You can specify the following *options*:

ABSCONV=*r*

ABSTOL=*r*
specifies an absolute function value convergence criterion by which minimization stops when $f(\theta^{(k)}) \leq r$. The default value of r is the negative square root of the largest double-precision value, which serves only as a protection against overflows.

ABSFCONV=*r*

ABSFTOL=*r*
specifies an absolute function difference convergence criterion by which minimization stops when the function value has a small change in successive iterations:

$$|f(\theta^{(k-1)}) - f(\theta^{(k)})| \leq r$$

The default value is $r = 0$.

ABSGCONV=*r*

ABSGTOL=*r*
specifies an absolute gradient convergence criterion. Optimization stops when the maximum absolute gradient element is small:

$$\max_j |g_j(\theta^{(k)})| \leq r$$

The default value is r=1E–5.

ABSXCONV=*r*

ABSXTOL=*r*

specifies an absolute parameter convergence criterion. Optimization stops when the Euclidean distance between successive parameter vectors is small:

$$\| \theta^{(k)} - \theta^{(k-1)} \|_2 \leq r$$

The default is 0.

FCONV=*r*

FTOL=*r*

specifies a relative function convergence criterion. Optimization stops when a relative change of the function value in successive iterations is small:

$$\frac{|f(\theta^{(k)}) - f(\theta^{(k-1)})|}{|f(\theta^{(k-1)})|} \leq r$$

The default value is $r = 2\epsilon$, where ϵ denotes the machine precision constant, which is the smallest double-precision floating-point number such that $1 + \epsilon > 1$.

GCONV=*r*

GTOL=*r*

specifies a relative gradient convergence criterion. For all techniques except CONGRA, optimization stops when the normalized predicted function reduction is small:

$$\frac{g(\theta^{(k)})^T [H^{(k)}]^{-1} g(\theta^{(k)})}{|f(\theta^{(k)})|} \leq r$$

For the CONGRA technique (where a reliable Hessian estimate H is not available), the following criterion is used:

$$\frac{\| g(\theta^{(k)}) \|_2^2 \quad \| s(\theta^{(k)}) \|_2}{\| g(\theta^{(k)}) - g(\theta^{(k-1)}) \|_2 \, |f(\theta^{(k)})|} \leq r$$

The default value is $r =$1E–8.

MAXFUNC=*i*

MAXFU=*i*

specifies the maximum number of function calls in the optimization process. The default is 1,000.

The optimization can terminate only after completing a full iteration. Therefore, the number of function calls that is actually performed can exceed the number that is specified by this option.

MAXITER=*i*

MAXIT=*i*

specifies the maximum number of iterations in the optimization process. The default value is 200.

MAXTIME=*r*

specifies an upper limit of *r* seconds of CPU time for the optimization process. The default value is the largest floating-point double representation of your computer. The time specified by this option is checked only once at the end of each iteration. Therefore, the actual running time can be much longer than *r*. The actual running time includes the remaining time needed to finish the iteration and the time needed to generate the output of the results.

METHOD=*value*

specifies the iterative minimization method to use. The default is METHOD=NEWRAP. You can specify the following *values*:

CONGRA	specifies the conjugate-gradient method.
	[DBLDOG] specifies the double dogleg method.
NONE	specifies that no optimization be performed beyond using the ordinary least squares method to compute the parameter estimates.
NEWRAP	specifies the Newton-Raphson method (the default).
NRRIDG	specifies the Newton-Raphson Ridge method.
QUANEW	specifies the quasi-Newton method.
TRUREG	specifies the trust region method.

BOUNDS Statement

BOUNDS *bound1* < , *bound2* . . . > ;

The BOUNDS statement imposes simple boundary constraints on the parameter estimates. BOUNDS statement constraints refer to the parameters that are estimated by the HPQLIM procedure. You can specify any number of BOUNDS statements.

Each *bound* is composed of parameters, constants, and inequality operators. Parameters associated with regressor variables are referred to by the names of the corresponding regressor variables. Specify each bound as follows:

item operator item < *operator item* < *operator item* . . . > >

Each *item* is a constant, the name of a parameter, or a list of parameter names. See the section "Naming of Parameters" on page 498 for more information about how parameters are named in the HPQLIM procedure. Each *operator* is <, >, <=, or >=.

You can use both the BOUNDS statement and the RESTRICT statement to impose boundary constraints; however, the BOUNDS statement provides a simpler syntax for specifying these types of constraints. See the section"RESTRICT Statement" on page 487 for more information.

The following BOUNDS statement constrains the estimates of the parameters that are associated with the variable ttime and the variables x1 through x10 to be between 0 and 1. This example illustrates the use of parameter lists to specify boundary constraints.

```
bounds 0 < ttime x1-x10 < 1;
```

The following BOUNDS statement constrains the estimates of the correlation (_RHO) and sigma (_SIGMA) in the bivariate model:

```
bounds _rho >= 0, _sigma.y1 > 1, _sigma.y2 < 5;
```

ENDOGENOUS Statement

ENDOGENOUS *variables* ~ *options* **;**

The ENDOGENOUS statement specifies the type of dependent variables that appear on the left-hand side of the equation. The listed endogenous variables refer to the dependent variables that appear on the left-hand side of the equation. Currently, no right-hand side endogeneity is handled in PROC HPQLIM. All variables that appear on the right-hand side of the equation are treated as exogenous.

Censored Variable Options

CENSORED < (*censored-options* **) >**
specifies that the endogenous variables in this statement be censored. You can specify the following *censored-options*:

LB=*value* | *variable*

LOWERBOUND=*value* | *variable*
specifies the lower bound of the censored variables. If *value* is missing or the value in *variable* is missing, no lower bound is set. By default, no lower bound is set.

UB=*value* | *variable*

UPPERBOUND=*value* | *variable*
specifies the upper bound of the censored variables. If *value* is missing or the value in *variable* is missing, no upper bound is set. By default, no upper bound is set.

Truncated Variable Options

TRUNCATED < (*truncated-options* **) >**
You can specify the following *truncated-options*:

LB=*value* | *variable*

LOWERBOUND=*value* | *variable*
specifies the lower bound of the truncated variables. If *value* is missing or the value in *variable* is missing, no lower bound is set. By default, no lower bound is set.

UB=*value* | *variable*

UPPERBOUND=*value* | *variable*
specifies the upper bound of the truncated variables. If *value* is missing or the value in *variable* is missing, no upper bound is set. By default, no upper bound is set.

Stochastic Frontier Variable Options

FRONTIER < (*frontier-options* **) >**
You can specify the following *frontier-options*:

TYPE=HALF | EXPONENTIAL | TRUNCATED
specifies the model type.

HALF
specifies half-normal model.

EXPONENTIAL
specifies exponential model.

TRUNCATED
specifies truncated normal model.

PRODUCTION
specifies that the estimated model be a production function.

COST
specifies that the estimated model be a cost function.

If neither PRODUCTION nor COST is specified, a production function is estimated by default.

FREQ Statement

FREQ *variable* **;**

The FREQ statement identifies a variable that contains the frequency of occurrence of each observation. PROC HPQLIM treats each observation as if it appeared n times, where n is the value of the FREQ variable for the observation. If the frequency value is not an integer, it is truncated to an integer. If the frequency value is less than 1 or missing, the observation is not used in the model fitting. When the FREQ statement is not specified, each observation is assigned a frequency of 1. If you specify more than one FREQ statement, then the first FREQ statement is used.

HETERO Statement

HETERO *dependent variables* $\sim$ *exogenous variables* < / *options* > **;**

The HETERO statement specifies variables that are related to the heteroscedasticity of the residuals and the way these variables are used to model the error variance. PROC HPQLIM supports the following heteroscedastic regression model:

$$y_i = \mathbf{x}_i'\boldsymbol{\beta} + \epsilon_i$$

$$\epsilon_i \sim \mathrm{N}(0, \sigma_i^2)$$

See the section "Heteroscedasticity" on page 493 for more information about the specification of functional forms. The following *options* specify the functional forms of heteroscedasticity.

LINK=EXP | LINEAR
specifies the functional form.

EXP

specifies the exponential link function:

$$\sigma_i^2 = \sigma^2(1 + \exp(\mathbf{z}_i'\boldsymbol{\gamma}))$$

LINEAR

specifies the linear link function:

$$\sigma_i^2 = \sigma^2(1 + \mathbf{z}_i'\boldsymbol{\gamma})$$

The default is LINK=EXP.

NOCONST

specifies that there be no constant in the linear or exponential heteroscedasticity model:

$$\sigma_i^2 = \sigma^2(\mathbf{z}_i'\boldsymbol{\gamma})$$
$$\sigma_i^2 = \sigma^2\exp(\mathbf{z}_i'\boldsymbol{\gamma})$$

This option is ignored if you do not specify the LINK= option.

SQUARE

estimates the model by using the square of the linear heteroscedasticity function. For example, you can specify the following heteroscedasticity function:

$$\sigma_i^2 = \sigma^2(1 + (\mathbf{z}_i'\boldsymbol{\gamma})^2)$$

```
model y = x1 x2 / censored(lb=0);
hetero y ~ z1 / link=linear square;
```

The SQUARE option does not apply to the exponential heteroscedasticity function because the square of an exponential function of $\mathbf{z}_i'\boldsymbol{\gamma}$ is the same as the exponential of $2\mathbf{z}_i'\boldsymbol{\gamma}$. Hence, the only difference is that all $\boldsymbol{\gamma}$ estimates are divided by two.

This option is ignored if you do not specify the LINK= option.

INIT Statement

INIT *initvalue1* < , *initvalue2* . . . > **;**

The INIT statement sets initial values for parameters in the optimization. You can specify any number of INIT statements.

Each *initvalue* is written as a parameter or parameter list, followed by an optional equality operator (=), followed by a number:

parameter **<=>** *number*

MODEL Statement

MODEL *dependent* **=** *regressors* **<** */ options* **>** **;**

The MODEL statement specifies the dependent variable and independent regressor variables for the regression model.

You can specify the following *options* after a slash (/).

NOINT
suppresses the intercept parameter.

You can also specify the following endogenous variable options, which are the same as the options specified in the ENDOGENOUS statement. If an endogenous variable has an endogenous option specified in both the MODEL statement and the ENDOGENOUS statement, the option in the ENDOGENOUS statement is used.

Censored Variable Options

CENSORED < (*censored-options* **) >**
specifies that the endogenous variables in this statement be censored. You can specify the following *censored-options*:

LB=*value* | *variable*

LOWERBOUND=*value* | *variable*
specifies the lower bound of the censored variables. If *value* is missing or the value in *variable* is missing, no lower bound is set. By default, no lower bound is set.

UB=*value* | *variable*

UPPERBOUND=*value* | *variable*
specifies the upper bound of the censored variables. If *value* is missing or the value in *variable* is missing, no upper bound is set. By default, no upper bound is set.

Truncated Variable Options

TRUNCATED < (*truncated-options* **) >**
You can specify the following *truncated-options*:

LB=*value* | *variable*

LOWERBOUND=*value* | *variable*
specifies the lower bound of the truncated variables. If *value* is missing or the value in *variable* is missing, no lower bound is set. By default, no lower bound is set.

UB=*value* | *variable*

UPPERBOUND=*value* | *variable*
specifies the upper bound of the truncated variables. If *value* is missing or the value in *variable* is missing, no upper bound is set. By default, no upper bound is set.

Stochastic Frontier Variable Options

FRONTIER < (*frontier-options* **) >**
You can specify the following *frontier-options*:

TYPE=HALF|EXPONENTIAL|TRUNCATED
specifies the model type.

HALF
specifies half-normal model.

EXPONENTIAL
specifies exponential model.

TRUNCATED
specifies truncated normal model.

PRODUCTION
specifies that the estimated model be a production function.

COST
specifies that the estimated model be a cost function.

If neither PRODUCTION nor COST is specified, a production function is estimated by default.

OUTPUT Statement

OUTPUT OUT=*SAS-data-set* < *output-options* > **;**

The OUTPUT statement creates a new SAS data set to contain variables specified with the OUTVAR option and the following data if they are specified by *output-options*: estimates of $\mathbf{x}'\boldsymbol{\beta}$, predicted value, residual, marginal effects, probability, standard deviation of the error, expected value, conditional expected value, technical efficiency measures, and inverse Mills ratio. When the response values are missing for the observation, all output estimates except the residual are still computed as long as none of the explanatory variables is missing. This enables you to compute these statistics for prediction. You can specify only one OUTPUT statement.

You must specify the OUT= option:

OUT=*SAS-data-set*
names the output data set.

You can specify one or more of the following *output-options*:

CONDITIONAL
outputs estimates of conditional expected values of continuous endogenous variables.

ERRSTD
outputs estimates of σ_j, the standard deviation of the error term.

EXPECTED
outputs estimates of expected values of continuous endogenous variables.

MARGINAL
outputs marginal effects.

OUTVAR(*SAS-variable-names***)**
adds SAS variables to the output data set.

PREDICTED
outputs estimates of predicted endogenous variables.

RESIDUAL
outputs estimates of residuals of continuous endogenous variables.

XBETA
outputs estimates of $\mathbf{x}'\boldsymbol{\beta}$.

TE1
outputs estimates of technical efficiency for each producer in the stochastic frontier model that is suggested by Battese and Coelli (1988).

TE2
outputs estimates of technical efficiency for each producer in the stochastic frontier model that is suggested by Jondrow et al. (1982).

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement specifies *performance-options* to control the multithreaded and distributed computing environment and requests detailed results about the performance characteristics of the HPQLIM procedure. With the PERFORMANCE statement, you can also control whether the HPQLIM procedure executes in SMP or MPP mode. You can specify the following *performance-options* in the PERFORMANCE statement include the following:

DETAILS
requests a table that shows a timing breakdown of the procedure steps.

NODES=*n*
specifies the number of nodes in the distributed computing environment, provided that the data are not processed alongside the database.

NTHREADS=*n*
specifies the number of threads for analytic computations and overrides the SAS system option THREADS | NOTHREADS. If you do not specify the NTHREADS= option, PROC HPQLIM creates one thread per CPU for the analytic computations.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in more detail in the section "PERFORMANCE Statement" on page 38 in Chapter 3, "Shared Concepts and Topics."

RESTRICT Statement

RESTRICT *restriction1* < *, restriction2 . . .* > **;**

The RESTRICT statement imposes linear restrictions on the parameter estimates. You can specify any number of RESTRICT statements, but the number of restrictions imposed is limited by the number of regressors.

Each *restriction* is written as an expression, followed by an equality operator (=) or an inequality operator (<, >, <=, >=), followed by a second expression:

expression operator expression

The *operator* can be =, <, >, <= , or >=. The *operator* and second *expression* are optional.

Restriction expressions can be composed of parameter names, multiplication (∗), addition (+), and substitution (−) operators, and constants. Parameters named in restriction expressions must be among the parameters that are estimated by the model. Parameters that are associated with a regressor variable are referred to by the name of the corresponding regressor variable. The restriction expressions must be a linear function of the parameters.

The following statements illustrate the use of the RESTRICT statement:

```
proc hpqlim data=one;
   model y = x1-x10 / censored(lb=0);
   restrict x1*2 <= x2 + x3;
run;
```

TEST Statement

<'label':> **TEST** *<'string':> equation* < *,equation. . .* > */ options* **;**

The TEST statement performs Wald, Lagrange multiplier, and likelihood ratio tests of linear hypotheses about the regression parameters in the preceding MODEL statement. Each equation specifies a linear hypothesis to be tested. All hypotheses in one TEST statement are tested jointly. Variable names in the equations must correspond to regressors in the preceding MODEL statement, and each name represents the coefficient of the corresponding regressor. Use the keyword INTERCEPT for a test that includes a constant.

You can specify the following *options* after the slash (/):

ALL
requests Wald, Lagrange multiplier, and likelihood ratio tests.

LM
requests the Lagrange multiplier test.

LR
requests the likelihood ratio test.

WALD
requests the Wald test.

The following statements illustrate the use of the TEST statement (note the use of the INTERCEPT keyword in the second TEST statement):

```
proc hpqlim;
   model y = x1 x2 x3;
   test x1 = 0, x2 * .5 + 2 * x3 = 0;
   test _int: test intercept = 0, x3 = 0;
run;
```

The first TEST statement investigates the joint hypothesis that

$$\beta_1 = 0$$

and

$$0.5\beta_2 + 2\beta_3 = 0$$

Only linear equality restrictions and tests are permitted in PROC HPQLIM. Tests expressions can be composed only of algebraic operations that involve the addition symbol (+), subtraction symbol (–), and multiplication symbol (*).

The TEST statement accepts labels that are reproduced in the printed output. You can label a TEST statement in two ways: You can specify a label followed by a colon before the TEST keyword, or you can specify a quoted string following the TEST keyword. If you specify both a label before the TEST keyword and a quoted string after the keyword, PROC HPQLIM uses the label that precedes the colon. If no label or quoted string is specified, PROC HPQLIM labels the test automatically.

WEIGHT Statement

WEIGHT *variable* < / *option* > **;**

The WEIGHT statement specifies a variable that supplies weighting values to use for each observation in estimating parameters. The log likelihood for each observation is multiplied by the corresponding weight variable value.

If the weight of an observation is nonpositive, that observation is not used in the estimation.

You can add the following *option* after a slash (/).

NONORMALIZE
specifies that the weights must be used as is. When this option is not specified, the weights are normalized so that they add up to the actual sample size. Weights w_i are normalized by multiplying them by $\frac{n}{\sum_{i=1}^{n} w_i}$, where n is the sample size.

Details: HPQLIM Procedure

Limited Dependent Variable Models

Censored Regression Models

When the dependent variable is censored, values in a certain range are all transformed to a single value. For example, the standard Tobit model can be defined as

$$y_i^* = \mathbf{x}_i'\boldsymbol{\beta} + \epsilon_i$$

$$y_i = \begin{cases} y_i^* & \text{if} y_i^* > 0 \\ 0 & \text{if} y_i^* \leq 0 \end{cases}$$

where $\epsilon_i \sim iidN(0, \sigma^2)$. The log-likelihood function of the standard censored regression model is

$$\ell = \sum_{i \in \{y_i = 0\}} \ln[1 - \Phi(\mathbf{x}_i'\boldsymbol{\beta}/\sigma)] + \sum_{i \in \{y_i > 0\}} \ln\left[\phi(\frac{y_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})/\sigma\right]$$

where $\Phi(\cdot)$ is the cumulative density function of the standard normal distribution and $\phi(\cdot)$ is the probability density function of the standard normal distribution.

The Tobit model can be generalized to handle observation-by-observation censoring. The censored model on both the lower and upper limits can be defined as

$$y_i = \begin{cases} R_i & \text{if } y_i^* \geq R_i \\ y_i^* & \text{if } L_i < y_i^* < R_i \\ L_i & \text{if } y_i^* \leq L_i \end{cases}$$

The log-likelihood function can be written as

$$\begin{aligned} \ell \quad = \quad & \sum_{i \in \{L_i < y_i < R_i\}} \ln\left[\phi(\frac{y_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})/\sigma\right] + \sum_{i \in \{y_i = R_i\}} \ln\left[\Phi(-\frac{R_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})\right] + \\ & \sum_{i \in \{y_i = L_i\}} \ln\left[\Phi(\frac{L_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})\right] \end{aligned}$$

Log-likelihood functions of the lower-limit or upper-limit censored model are easily derived from the two-limit censored model. The log-likelihood function of the lower-limit censored model is

$$\ell = \sum_{i \in \{y_i > L_i\}} \ln\left[\phi(\frac{y_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})/\sigma\right] + \sum_{i \in \{y_i = L_i\}} \ln\left[\Phi(\frac{L_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})\right]$$

The log-likelihood function of the upper-limit censored model is

$$\ell = \sum_{i \in \{y_i < R_i\}} \ln\left[\phi(\frac{y_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})/\sigma\right] + \sum_{i \in \{y_i = R_i\}} \ln\left[1 - \Phi(\frac{R_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma})\right]$$

Truncated Regression Models

In a truncated model, the observed sample is a subset of the population where the dependent variable falls in a certain range. For example, when neither a dependent variable nor exogenous variables are observed for $y_i^* \leq 0$, the truncated regression model can be specified as

$$\ell = \sum_{i \in \{y_i > 0\}} \left\{ -\ln \Phi(\mathbf{x}_i' \boldsymbol{\beta}/\sigma) + \ln \left[\frac{\phi((y_i - \mathbf{x}_i' \boldsymbol{\beta})/\sigma)}{\sigma} \right] \right\}$$

The two-limit truncation model is defined as

$$y_i = y_i^* \text{if } L_i < y_i^* < R_i$$

The log-likelihood function of the two-limit truncated regression model is

$$\ell = \sum_{i=1}^{N} \left\{ \ln \left[\phi(\frac{y_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma})/\sigma \right] - \ln \left[\Phi(\frac{R_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma}) - \Phi(\frac{L_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma}) \right] \right\}$$

The log-likelihood function of the lower-limit truncation model is

$$\ell = \sum_{i=1}^{N} \left\{ \ln \left[\phi(\frac{y_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma})/\sigma \right] - \ln \left[1 - \Phi(\frac{L_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma}) \right] \right\}$$

The log-likelihood function of the upper-limit truncation model is

$$\ell = \sum_{i=1}^{N} \left\{ \ln \left[\phi(\frac{y_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma})/\sigma \right] - \ln \left[\Phi(\frac{R_i - \mathbf{x}_i' \boldsymbol{\beta}}{\sigma}) \right] \right\}$$

Stochastic Frontier Production and Cost Models

Stochastic frontier production models were first developed by Aigner, Lovell, and Schmidt (1977) and Meeusen and van den Broeck (1977). Specification of these models allow for random shocks of the production or cost but also include a term for technological or cost inefficiency. Assuming that the production function takes a log-linear Cobb-Douglas form, the stochastic frontier production model can be written as

$$ln(y_i) = \beta_0 + \sum_n \boldsymbol{\beta}_n \ln(x_{ni}) + \epsilon_i$$

where $\epsilon_i = v_i - u_i$. The v_i term represents the stochastic error component, and the u_i term represents the nonnegative, technology inefficiency error component. The v_i error component is assumed to be distributed iid normal and independently from u_i. If $u_i > 0$, the error term ϵ_i is negatively skewed and represents technology inefficiency. If $u_i < 0$, the error term ϵ_i is positively skewed and represents cost inefficiency. PROC HPQLIM models the u_i error component as a half-normal, exponential, or truncated normal distribution.

The Normal-Half Normal Model

When v_i is iid $N(0, \sigma_v^2)$ in a normal-half normal model, u_i is iid $N^+(0, \sigma_u^2)$, with v_i and u_i independent of each other. Given the independence of error terms, the joint density of v and u can be written as

$$f(u, v) = \frac{2}{2\pi\sigma_u\sigma_v} \exp\left\{-\frac{u^2}{2\sigma_u^2} - \frac{v^2}{2\sigma_v^2}\right\}$$

Substituting $v = \epsilon + u$ into the preceding equation gives

$$f(u, \epsilon) = \frac{2}{2\pi\sigma_u\sigma_v} \exp\left\{-\frac{u^2}{2\sigma_u^2} - \frac{(\epsilon + u)^2}{2\sigma_v^2}\right\}$$

Integrating u out to obtain the marginal density function of ϵ results in the following form:

$$\begin{aligned} f(\epsilon) &= \int_0^\infty f(u, \epsilon) du \\ &= \frac{2}{\sqrt{2\pi}\sigma}\left[1 - \phi\left(\frac{\epsilon\lambda}{\sigma}\right)\right] \exp\left\{-\frac{\epsilon^2}{2\sigma^2}\right\} \\ &= \frac{2}{\sigma}\phi\left(\frac{\epsilon}{\sigma}\right)\Phi\left(-\frac{\epsilon\lambda}{\sigma}\right) \end{aligned}$$

where $\lambda = \sigma_u/\sigma_v$ and $\sigma = \sqrt{\sigma_u^2 + \sigma_v^2}$.

In the case of a stochastic frontier cost model, $v = \epsilon - u$ and

$$f(\epsilon) = \frac{2}{\sigma}\phi\left(\frac{\epsilon}{\sigma}\right)\Phi\left(\frac{\epsilon\lambda}{\sigma}\right)$$

The log-likelihood function for the production model with N producers is written as

$$\ln L = \text{constant} - N \ln\sigma + \sum_i \ln\Phi\left(-\frac{\epsilon_i\lambda}{\sigma}\right) - \frac{1}{2\sigma^2}\sum_i \epsilon_i^2$$

The Normal-Exponential Model

Under the normal-exponential model, v_i is iid $N(0, \sigma_v^2)$ and u_i is iid exponential. Given the independence of error term components u_i and v_i, the joint density of v and u can be written as

$$f(u, v) = \frac{1}{\sqrt{2\pi}\sigma_u\sigma_v} \exp\left\{-\frac{u}{\sigma_u} - \frac{v^2}{2\sigma_v^2}\right\}$$

The marginal density function of ϵ for the production function is

$$\begin{aligned} f(\epsilon) &= \int_0^\infty f(u, \epsilon) du \\ &= \left(\frac{1}{\sigma_u}\right)\Phi\left(-\frac{\epsilon}{\sigma_v} - \frac{\sigma_v}{\sigma_u}\right) \exp\left\{\frac{\epsilon}{\sigma_u} + \frac{\sigma_v^2}{2\sigma_u^2}\right\} \end{aligned}$$

The marginal density function for the cost function is equal to

$$f(\epsilon) = \left(\frac{1}{\sigma_u}\right) \Phi\left(\frac{\epsilon}{\sigma_v} - \frac{\sigma_v}{\sigma_u}\right) \exp\left\{-\frac{\epsilon}{\sigma_u} + \frac{\sigma_v^2}{2\sigma_u^2}\right\}$$

The log-likelihood function for the normal-exponential production model with N producers is

$$\ln L = \text{constant} - N \ln \sigma_u + N\left(\frac{\sigma_v^2}{2\sigma_u^2}\right) + \sum_i \frac{\epsilon_i}{\sigma_u} + \sum_i \ln \Phi\left(\frac{\epsilon_i}{\sigma_v} - \frac{\sigma_v}{\sigma_u}\right)$$

The Normal-Truncated Normal Model

The normal-truncated normal model is a generalization of the normal-half normal model that allows the mean of u_i to differ from zero. Under the normal-truncated normal model, the error term component v_i is iid $N^+(0, \sigma_v^2)$ and u_i is iid $N(\mu, \sigma_u^2)$. The joint density of v_i and u_i can be written as

$$f(u, v) = \frac{1}{\sqrt{2\pi}\sigma_u \sigma_v \Phi\left(\mu/\sigma_u\right)} \exp\left\{-\frac{(u-\mu)^2}{2\sigma_u^2} - \frac{v^2}{2\sigma_v^2}\right\}$$

The marginal density function of ϵ for the production function is

$$\begin{aligned} f(\epsilon) &= \int_0^\infty f(u, \epsilon) du \\ &= \frac{1}{\sqrt{2\pi}\sigma \Phi\left(\mu/\sigma_u\right)} \Phi\left(\frac{\mu}{\sigma\lambda} - \frac{\epsilon\lambda}{\sigma}\right) \exp\left\{-\frac{(\epsilon+\mu)^2}{2\sigma^2}\right\} \\ &= \frac{1}{\sigma}\phi\left(\frac{\epsilon+\mu}{\sigma}\right) \Phi\left(\frac{\mu}{\sigma\lambda} - \frac{\epsilon\lambda}{\sigma}\right) \left[\Phi\left(\frac{\mu}{\sigma_u}\right)\right]^{-1} \end{aligned}$$

The marginal density function for the cost function is

$$f(\epsilon) = \frac{1}{\sigma}\phi\left(\frac{\epsilon-\mu}{\sigma}\right) \Phi\left(\frac{\mu}{\sigma\lambda} + \frac{\epsilon\lambda}{\sigma}\right) \left[\Phi\left(\frac{\mu}{\sigma_u}\right)\right]^{-1}$$

The log-likelihood function for the normal-truncated normal production model with N producers is

$$\begin{aligned} \ln L &= \text{constant} - N \ln \sigma - N \ln \Phi\left(\frac{\mu}{\sigma_u}\right) + \sum_i \ln \Phi\left(\frac{\mu}{\sigma\lambda} + \frac{\epsilon_i \lambda}{\sigma}\right) \\ &\quad -\frac{1}{2}\sum_i \left(\frac{\epsilon_i + \mu}{\sigma}\right)^2 \end{aligned}$$

For more information about normal-half normal, normal-exponential, and normal-truncated models, see Kumbhakar and Knox Lovell (2000) and Coelli, Prasada Rao, and Battese (1998).

Heteroscedasticity

If the variance of regression disturbance, (ϵ_i), is heteroscedastic, the variance can be specified as a function of variables

$$E(\epsilon_i^2) = \sigma_i^2 = f(\mathbf{z}_i'\boldsymbol{\gamma})$$

The following table shows various functional forms of heteroscedasticity and the corresponding options to request each model.

Number	Model	Options
1	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2(1 + \exp(\mathbf{z}_i'\gamma))$	LINK=EXP (default)
2	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2 \exp(\mathbf{z}_i'\gamma)$	LINK=EXP NOCONST
3	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2(1 + \sum_{l=1}^{L} \gamma_l z_{li})$	LINK=LINEAR
4	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2(1 + (\sum_{l=1}^{L} \gamma_l z_{li})^2)$	LINK=LINEAR SQUARE
5	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2(\sum_{l=1}^{L} \gamma_l z_{li})$	LINK=LINEAR NOCONST
6	$f(\mathbf{z}_i'\boldsymbol{\gamma}) = \sigma^2((\sum_{l=1}^{L} \gamma_l z_{li})^2)$	LINK=LINEAR SQUARE NOCONST

In models 3 and 5, variances of some observations might be negative. Although the HPQLIM procedure assigns a large penalty to move the optimization away from such region, the optimization might not be able to improve the objective function value and might become locked in the region. Signs of such an outcome include extremely small likelihood values or missing standard errors in the estimates. In models 2 and 6, variances are guaranteed to be greater than or equal to zero, but variances of some observations might be very close to 0. In these scenarios, standard errors might be missing. Models 1 and 4 do not have such problems. Variances in these models are always positive and never close to 0.

The heteroscedastic regression model is estimated using the following log-likelihood function, where $e_i = y_i - \mathbf{x}_i'\boldsymbol{\beta}$:

$$\ell = -\frac{N}{2}\ln(2\pi) - \sum_{i=1}^{N}\frac{1}{2}\ln(\sigma_i^2) - \frac{1}{2}\sum_{i=1}^{N}(\frac{e_i}{\sigma_i})^2$$

Tests on Parameters

In general, the tested hypothesis can be written as

$$H_0 : \mathbf{h}(\theta) = 0$$

where $\mathbf{h}(\theta)$ is an $r \times 1$ vector-valued function of the parameters θ given by the r expressions that are specified in the TEST statement.

Let $\hat{V}$ be the estimate of the covariance matrix of $\hat{\theta}$. Let $\hat{\theta}$ be the unconstrained estimate of θ and $\tilde{\theta}$ be the constrained estimate of θ such that $h(\tilde{\theta}) = 0$. Let

$$A(\theta) = \partial h(\theta)/\partial\theta \mid_{\hat{\theta}}$$

Using this notation, the test statistics for the three types of tests are computed as follows.

- The Wald test statistic is defined as

$$W = h'(\hat{\theta}) \left(A(\hat{\theta}) \hat{V} A'(\hat{\theta}) \right)^{-1} h(\hat{\theta})$$

  The Wald test is not invariant to reparameterization of the model (Gregory and Veall 1985; Gallant 1987, p. 219). For more information about the theoretical properties of the Wald test, see Phillips and Park (1988).

- The Lagrange multiplier test statistic is

$$LM = \lambda' A(\tilde{\theta}) \tilde{V} A'(\tilde{\theta}) \lambda$$

  where λ is the vector of Lagrange multipliers from the computation of the restricted estimate $\tilde{\theta}$.

- The likelihood ratio test statistic is

$$LR = 2 \left(L(\hat{\theta}) - L(\tilde{\theta}) \right)$$

  where $\tilde{\theta}$ represents the constrained estimate of θ and L is the concentrated log-likelihood value.

For each type of test, under the null hypothesis the test statistic is asymptotically distributed as a χ^2 random variable with r degrees of freedom, where r is the number of expressions in the TEST statement. The p-values reported for the tests are computed from the $\chi^2(r)$ distribution and are only asymptotically valid.

Monte Carlo simulations suggest that the asymptotic distribution of the Wald test is a poorer approximation to its small sample distribution than that of the other two tests. However, the Wald test has the lowest computational cost, since it does not require computation of the constrained estimate $\tilde{\theta}$.

The following statements use the TEST statement to perform a likelihood ratio test:

```
proc hpqlim;
   model y = x1 x2 x3;
   test x1 = 0, x2 * .5 + 2 * x3 = 0 /lr;
run;
```

Output to SAS Data Set

XBeta, Predicted, and Residual

Xbeta is the structural part on the right-hand side of the model. The predicted value is the predicted dependent variable value. For censored variables, if the predicted value is outside the boundaries, it is reported as the closest boundary. The residual is defined only for continuous variables and is defined as

$$\text{Residual} = \text{Observed} - \text{Predicted}$$

Error Standard Deviation

The error standard deviation is σ_i in the model. It varies only when the HETERO statement is used.

Marginal Effects

A marginal effect is defined as a contribution of one control variable to the response variable. For a binary choice model with two response categories, $\mu_0 = -\infty$ and $\mu_1 = 0$, $\mu_2 = \infty$. For an ordinal response model with M response categories, $\mu_0, \cdots, \mu_M$, define

$$R_{i,j} = \mu_j - \mathbf{x}_i'\boldsymbol{\beta}$$

The probability that the unobserved dependent variable is contained in the jth category can be written as

$$P[\mu_{j-1} < y_i^* \le \mu_j] = F(R_{i,j}) - F(R_{i,j-1})$$

The marginal effect of changes in the regressors on the probability of $y_i = j$ is then

$$\frac{\partial Prob[y_i = j]}{\partial \mathbf{x}} = [f(\mu_{j-1} - \mathbf{x}_i'\boldsymbol{\beta}) - f(\mu_j - \mathbf{x}_i'\boldsymbol{\beta})]\boldsymbol{\beta}$$

where $f(x) = \frac{dF(x)}{dx}$. In particular,

$$f(x) = \frac{dF(x)}{dx} = \begin{cases} \frac{1}{\sqrt{2\pi}} e^{-x^2/2} & \text{(probit)} \\ \frac{e^{-x}}{[1+e^{(-x)}]^2} & \text{(logit)} \end{cases}$$

The marginal effects in the Box-Cox regression model are

$$\frac{\partial E[y_i]}{\partial \mathbf{x}} = \boldsymbol{\beta} \frac{x^{\lambda_k - 1}}{y^{\lambda_0 - 1}}$$

The marginal effects in the truncated regression model are

$$\frac{\partial E[y_i | L_i < y_i^* < R_i]}{\partial \mathbf{x}} = \boldsymbol{\beta} \left[1 - \frac{(\phi(a_i) - \phi(b_i))^2}{(\Phi(b_i) - \Phi(a_i))^2} + \frac{a_i \phi(a_i) - b_i \phi(b_i)}{\Phi(b_i) - \Phi(a_i)} \right]$$

where $a_i = \frac{L_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma_i}$ and $b_i = \frac{R_i - \mathbf{x}_i'\boldsymbol{\beta}}{\sigma_i}$.

The marginal effects in the censored regression model are

$$\frac{\partial E[y | \mathbf{x}_i]}{\partial \mathbf{x}} = \boldsymbol{\beta} \times Prob[L_i < y_i^* < R_i]$$

Expected and Conditionally Expected Values

The expected value is the unconditional expectation of the dependent variable. For a censored variable, it is

$$E[y_i] = \Phi(a_i) L_i + (\mathbf{x}_i'\boldsymbol{\beta} + \lambda\sigma_i)(\Phi(b_i) - \Phi(a_i)) + (1 - \Phi(b_i)) R_i$$

For a left-censored variable ($R_i = \infty$), this formula is

$$E[y_i] = \Phi(a_i) L_i + (\mathbf{x}_i'\boldsymbol{\beta} + \lambda\sigma_i)(1 - \Phi(a_i))$$

where $\lambda = \frac{\phi(a_i)}{1-\Phi(a_i)}$.

For a right-censored variable ($L_i = -\infty$), this formula is

$$E[y_i] = (\mathbf{x}_i'\boldsymbol{\beta} + \lambda\sigma_i)\Phi(b_i) + (1 - \Phi(b_i))R_i$$

where $\lambda = -\frac{\phi(b_i)}{\Phi(b_i)}$.

For a noncensored variable, this formula is

$$E[y_i] = \mathbf{x}_i'\boldsymbol{\beta}$$

The conditional expected value is the expectation given that the variable is inside the boundaries:

$$E[y_i | L_i < y_i < R_i] = \mathbf{x}_i'\boldsymbol{\beta} + \lambda\sigma_i$$

Technical Efficiency

Technical efficiency for each producer is computed only for stochastic frontier models.

In general, the stochastic production frontier can be written as

$$y_i = f(x_i;\beta)\exp\{v_i\}TE_i$$

where y_i denotes producer i's actual output, $f(\cdot)$ is the deterministic part of production frontier, $\exp\{v_i\}$ is a producer-specific error term, and TE_i is the technical efficiency coefficient, which can be written as

$$TE_i = \frac{y_i}{f(x_i;\beta)\exp\{v_i\}}$$

For a Cobb-Douglas production function, $TE_i = \exp\{-u_i\}$. See the section "Stochastic Frontier Production and Cost Models" on page 490.

The cost frontier can be written in general as

$$E_i = c(y_i, w_i;\beta)\exp\{v_i\}/CE_i$$

where w_i denotes producer i's input prices, $c(\cdot)$ is the deterministic part of cost frontier, $\exp\{v_i\}$ is a producer-specific error term, and CE_i is the cost efficiency coefficient, which can be written as

$$CE_i = \frac{c(x_i, w_i;\beta)\exp\{v_i\}}{E_i}$$

For a Cobb-Douglas cost function, $CE_i = \exp\{-u_i\}$. See the section "Stochastic Frontier Production and Cost Models" on page 490. Hence, both technical and cost efficiency coefficients are the same. The estimates of technical efficiency are provided in the following subsections.

Normal-Half Normal Model

Define $\mu_* = -\epsilon\sigma_u^2/\sigma^2$ and $\sigma_*^2 = \sigma_u^2\sigma_v^2/\sigma^2$. Then, as shown by Jondrow et al. (1982), conditional density is as follows:

$$f(u|\epsilon) = \frac{f(u,\epsilon)}{f(\epsilon)} = \frac{1}{\sqrt{2\pi}\sigma_*}\exp\left\{-\frac{(u-\mu_*)^2}{2\sigma_*^2}\right\} \Big/ \left[1 - \Phi\left(-\frac{\mu_*}{\sigma_*}\right)\right]$$

Hence, $f(u|\epsilon)$ is the density for $N^+(\mu_*, \sigma_*^2)$.

Using this result, it follows that the estimate of technical efficiency (Battese and Coelli, 1988) is

$$TE1_i = E(\exp\{-u_i\}|\epsilon_i) = \left[\frac{1-\Phi(\sigma_* - \mu_{*i}/\sigma_*)}{1-\Phi(-\mu_{*i}/\sigma_*)}\right]\exp\left\{-\mu_{*i} + \frac{1}{2}\sigma_*^2\right\}$$

The second version of the estimate (Jondrow et al. 1982) is

$$TE2_i = \exp\{-E(u_i|\epsilon_i)\}$$

where

$$E(u_i|\epsilon_i) = \mu_{*i} + \sigma_*\left[\frac{\phi(-\mu_{*i}/\sigma_*)}{1-\Phi(-\mu_{*i}/\sigma_*)}\right] = \sigma_*\left[\frac{\phi(\epsilon_i\lambda/\sigma)}{1-\Phi(\epsilon_i\lambda/\sigma)} - \left(\frac{\epsilon_i\lambda}{\sigma}\right)\right]$$

Normal-Exponential Model

Define $A = -\tilde{\mu}/\sigma_v$ and $\tilde{\mu} = -\epsilon - \sigma_v^2/\sigma_u$. Then, as shown by Kumbhakar and Lovell (2000), conditional density is as follows:

$$f(u|\epsilon) = \frac{1}{\sqrt{2\pi}\sigma_v\Phi(-\tilde{\mu}/\sigma_v)}\exp\left\{-\frac{(u-\tilde{\mu})^2}{2\sigma^2}\right\}$$

Hence, $f(u|\epsilon)$ is the density for $N^+(\tilde{\mu}, \sigma_v^2)$.

Using this result, it follows that the estimate of technical efficiency is

$$TE1_i = E(\exp\{-u_i\}|\epsilon_i) = \left[\frac{1-\Phi(\sigma_v - \tilde{\mu}_i/\sigma_v)}{1-\Phi(-\tilde{\mu}_i/\sigma_v)}\right]\exp\left\{-\tilde{\mu}_i + \frac{1}{2}\sigma_v^2\right\}$$

The second version of the estimate is

$$TE2_i = \exp\{-E(u_i|\epsilon_i)\}$$

where

$$E(u_i|\epsilon_i) = \tilde{\mu}_i + \sigma_v\left[\frac{\phi(-\tilde{\mu}_i/\sigma_v)}{1-\Phi(-\tilde{\mu}_i/\sigma_v)}\right] = \sigma_v\left[\frac{\phi(A)}{\Phi(-A)} - A\right]$$

Normal-Truncated Normal Model

Define $\tilde{\mu} = (-\sigma_u^2\epsilon_i + \mu\sigma_v^2)/\sigma^2$ and $\sigma_*^2 = \sigma_u^2\sigma_v^2/\sigma^2$. Then, as shown by Kumbhakar and Lovell (2000), conditional density is as follows:

$$f(u|\epsilon) = \frac{1}{\sqrt{2\pi}\sigma_*[1-\Phi(-\tilde{\mu}/\sigma_*)]}\exp\left\{-\frac{(u-\tilde{\mu})^2}{2\sigma_*^2}\right\}$$

Hence, $f(u|\epsilon)$ is the density for $N^+(\tilde{\mu}, \sigma_*^2)$.

Using this result, it follows that the estimate of technical efficiency is

$$TE1_i = E(\exp\{-u_i\}|\epsilon_i) = \frac{1-\Phi(\sigma_* - \tilde{\mu}_i/\sigma_*)}{1-\Phi(-\tilde{\mu}_i/\sigma_*)}\exp\left\{-\tilde{\mu}_i + \frac{1}{2}\sigma_*^2\right\}$$

The second version of the estimate is

$$TE2_i = \exp\{-E(u_i|\epsilon_i)\}$$

where

$$E(u_i|\epsilon_i) = \tilde{\mu}_i + \sigma_*\left[\frac{\phi(\tilde{\mu}_i/\sigma_*)}{1-\Phi(-\tilde{\mu}_i/\sigma_*)}\right]$$

OUTEST= Data Set

The OUTEST= data set contains all the parameters that are estimated by a MODEL statement. Each parameter contains the estimate for the corresponding parameter in the corresponding model. In addition, the OUTEST= data set contains the following variables:

NAME indicates the name of the independent variable.

TYPE indicates the type of observation. PARM indicates the row of coefficients; STD indicates the row of standard deviations of the corresponding coefficients.

STATUS indicates the convergence status for optimization.

The rest of the columns correspond to the explanatory variables.

The OUTEST= data set contains one observation for the MODEL statement, which shows the parameter estimates for that model. If you specify the COVOUT option in the PROC HPQLIM statement, the OUTEST= data set includes additional observations for the MODEL statement, which show the rows of the covariance matrix of parameter estimates. For covariance observations, the value of the _TYPE_ variable is COV, and the _NAME_ variable identifies the parameter that is associated with that row of the covariance matrix. If you specify the CORROUT option in the PROC HPQLIM statement, the OUTEST= data set includes additional observations for the MODEL statement, which show the rows of the correlation matrix of parameter estimates. For correlation observations, the value of the _TYPE_ variable is CORR, and the _NAME_ variable identifies the parameter that is associated with that row of the correlation matrix.

Naming

Naming of Parameters

The parameters are named in the same way as in other SAS procedures such as the REG and PROBIT procedures. The constant in the regression equation is called Intercept. The coefficients on independent variables are named by the independent variables. The standard deviation of the errors is called _Sigma. If the HETERO statement is included, the coefficients of the independent variables in the HETERO statement are called _H.x, where x is the name of the independent variable.

Naming of Output Variables

The following table shows the *options* in the OUTPUT statement, with the corresponding variable names and their explanations.

Table 20.2 OUTPUT Statement Options

output-option	**Variable Name**	**Explanation**
CONDITIONAL	CEXPCT_y	Conditional expected value of y, condition on the truncation
ERRSTD	ERRSTD_y	Standard deviation of error term
EXPECTED	EXPCT_y	Unconditional expected value of y
MARGINAL	MEFF_x	Marginal effect of x on y ($\frac{\partial y}{\partial x}$) with single equation
OUTVAR	The variable name used in the input data set	Input data variables are added to the output data set
PREDICTED	P_y	Predicted value of y
RESIDUAL	RESID_y	Residual of y, (y–PredictedY)
TE1	TE1	Technical efficiency estimate for each producer proposed by Battese and Coelli (1988)
TE2	TE2	Technical efficiency estimate for each producer proposed by Jondrow et al. (1982)
XBETA	XBETA_y	Structure part ($\mathbf{x}'\boldsymbol{\beta}$) of y equation

If you prefer to name the output variables differently, you can use the RENAME option in the data set. For example, the following statements rename the residual of y as *Resid*:

```
proc hpqlim data=one;
   model y = x1-x10 / censored;
   output out=outds(rename=(resid_y=resid)) residual;
run;
```

ODS Table Names

PROC HPQLIM assigns a name to each table it creates. You can use these names to refer to the table when you use the Output Delivery System (ODS) to select tables and create output data sets. These names are listed in the Table 20.3.

Table 20.3 ODS Tables Produced in PROC HPQLIM

ODS Table Name	**Description**	**Option**
ODS Tables Created by the MODEL Statement and TEST Statement		
FitSummary	Summary of nonlinear estimation	Default
ParameterEstimates	Parameter estimates	Default
SummaryContResponse	Summary of continuous response	Default
CovB	Covariance of parameter estimates	COVB

Table 20.3 *(continued)*

ODS Table Name	Description	Option
CorrB	Correlation of parameter estimates	CORRB
IterStart	Optimization start summary	ITPRINT
IterHistory	Iteration history	ITPRINT
IterStop	Optimization results	ITPRINT
ConvergenceStatus	Convergence status	ITPRINT
ODS Tables Created by the TEST Statement		
TestResults	Test results	Default

Examples: The HPQLIM Procedure

Example 20.1: High-Performance Model with Censoring

This example shows the use of the HPQLIM procedure with an emphasis on processing a large data set and the performance improvements that are achieved by executing in the high-performance distributed environment.

The following DATA step generates 10 million replicates from the model with censoring. The model contains seven variables.

```
data simulate;
     call streaminit(12345);
     array vars x1-x7;
     array parms{7}  (3 4 2 4 -3 -5 -3);

     intercept=2;

     do i=1 to 10000000;
        sum_xb=0;
        do j=1 to 7;
           vars[j]=rand('NORMAL',0,1);
           sum_xb=sum_xb+parms[j]*vars[j];
        end;
        y=intercept+sum_xb+400*rand('NORMAL',0,1);
        if y>400 then y=400;
        if y<0 then y=0;
        output;
     end;
  keep y x1-x7;
  run;
```

The following statements estimate a model with censoring. The model is executed in the distributed computing environment with two threads and only one node. These settings are used to obtain a hypothetical environment that might resemble running the HPQLIM procedure on a desktop workstation with a dual core CPU. To run these statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to the macro variables in the example with the appropriate values.

```
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";


proc hpqlim data=simulate ;
   performance nthreads=2 nodes=1 details ;
   model y=x1-x7 /censored(lb=0 ub=400);
run;
```

Output 20.1.1 shows the results for the model with censoring. The "Performance Information" table shows that the model was estimated on the grid defined in a macro variable named GRIDHOST in a distributed environment on only one node and that two threads were employed. The "Model Fit Summary" table shows detailed information about the model and indicates that all 10 million observations were used to fit the model. All parameter estimates in the "Parameter Estimates" table are highly significant and correspond to their theoretical values that were set during the data generating process. The optimization of the model with 10 million observations took 183.84 seconds.

Output 20.1.1 Censored Model with One Node and Two Threads

Estimating a Tobit model

The HPQLIM Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	1
Number of Threads per Node	2

Model Information

Data Source	WORK.SIMULATE
Response Variable	y
Optimization Technique	Quasi-Newton
Execution Mode	Distributed

Number of Observations

Number of Observations Read	10000000
Number of Observations Used	10000000

Output 20.1.1 *continued*

Summary Statistics of Continuous Responses

Variable	Mean	Standard Error	Type	Lower Bound	Upper Bound	N Obs Lower Bound	N Obs Upper Bound
y	127.0777	159.495135	Censored	0	400	498E4	16E5

Convergence criterion (FCONV=2.220446E-16) satisfied.

Model Fit Summary

Number of Endogenous Variables	1
Endogenous Variable	y
Number of Observations	10000000
Log Likelihood	-30551869
Maximum Absolute Gradient	0.00175
Number of Iterations	12
Optimization Method	Quasi-Newton
AIC	61103755
Schwarz Criterion	61103883

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Approx Pr > |t|
Intercept	1	2.442636	0.156989	15.56	<.0001
x1	1	3.018273	0.142447	21.19	<.0001
x2	1	4.013531	0.142462	28.17	<.0001
x3	1	1.856284	0.142449	13.03	<.0001
x4	1	3.900566	0.142404	27.39	<.0001
x5	1	-3.075784	0.142387	-21.60	<.0001
x6	1	-5.152160	0.142431	-36.17	<.0001
x7	1	-2.953773	0.142459	-20.73	<.0001
_Sigma	1	399.786656	0.185042	2160.52	<.0001

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	5.51	3.00%
Communication to client	0.20	0.11%
Optimization	178.13	96.9%
Post-optimization	0.00	0.00%

In the following statements, the PERFORMANCE statement is modified to use a grid with 10 nodes, with each node capable of spawning eight threads:

```
proc hpqlim data=simulate ;
   performance nthreads=8 nodes=10 details ;
   model y=x1-x7 /censored(lb=0 ub=400);
run;
```

Since the two models being estimated are identical, it is reasonable to expect that Output 20.1.1 and Output 20.1.2 would show the same results except for the performance. The second model, which was run on a grid using 10 nodes with eight threads each, took only 5.34 seconds instead of 183.84 seconds to optimize.

In certain circumstances, you might observe slight numerical differences in the results (depending on the number of nodes and threads involved) because the order in which partial results are accumulated, the limits of numerical precision, and the propagation of error in numerical computations can make a difference in final result.

Output 20.1.2 Censored Model on 10 Nodes with Eight Threads Each

Estimating a Tobit model

The HPQLIM Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	10
Number of Threads per Node	8

Model Information

Data Source	WORK.SIMULATE
Response Variable	y
Optimization Technique	Quasi-Newton
Execution Mode	Distributed

Number of Observations

Number of Observations Read	10000000
Number of Observations Used	10000000

Summary Statistics of Continuous Responses

Variable	Mean	Standard Error	Type	Lower Bound	Upper Bound	N Obs Lower Bound	N Obs Upper Bound
y	127.0777	159.495135	Censored	0	400	498E4	16E5

Convergence criterion (FCONV=2.220446E-16) satisfied.

Output 20.1.2 *continued*

Model Fit Summary

Number of Endogenous Variables	1
Endogenous Variable	y
Number of Observations	10000000
Log Likelihood	−30551869
Maximum Absolute Gradient	0.0004886
Number of Iterations	11
Optimization Method	Quasi-Newton
AIC	61103755
Schwarz Criterion	61103883

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Approx Pr > |t|
Intercept	1	2.442636	0.156989	15.56	<.0001
x1	1	3.018273	0.142447	21.19	<.0001
x2	1	4.013531	0.142462	28.17	<.0001
x3	1	1.856284	0.142449	13.03	<.0001
x4	1	3.900566	0.142404	27.39	<.0001
x5	1	−3.075784	0.142387	−21.60	<.0001
x6	1	−5.152160	0.142431	−36.17	<.0001
x7	1	−2.953773	0.142459	−20.73	<.0001
_Sigma	1	399.786657	0.185042	2160.52	<.0001

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	0.37	6.88%
Communication to client	0.12	2.31%
Optimization	4.85	90.8%
Post-optimization	0.00	0.00%

As this example suggests, increasing the number of nodes and the number of threads per node improves performance significantly. When you use the parallelism afforded by a high-performance distributed environment, you can see an even more dramatic reduction in the time required for the optimization as the number of observations in the data set increases. When the data set is extremely large, the computations might not even be possible with the typical memory resources and computational constraints of a desktop computer. Under such circumstances the high-performance distributed environment becomes a necessity.

References

Aigner, C., Lovell, C. A. K., Schmidt, P. (1977), "Formulation and Estimation of Stochastic Frontier Production Function Models," *Journal of Econometrics*, 6:1 (July), 21–37

Battese, G. E. and Coelli, T. J. (1988) "Prediction of Firm-Level Technical Efficiencies with a Generalized Frontier Production Function and Panel Data," *Journal of Econometrics*, 38, 387–99.

Christensen, L. and W. Greene, 1976, "Economies of Scale in U.S. Electric Power Generation," *Journal of Political Economy*, 84, pp. 655–676.

Coelli, T. J., Prasada Rao, D. S., Battese, G. E. (1998), *An Introduction to Efficiency and Productivity Analysis*, London: Kluwer Academic Publisher.

Gallant, A. R. (1987), *Nonlinear Statistical Models*, New York: Wiley.

Gregory, A. W. and Veall, M. R. (1985), "On Formulating Wald Tests for Nonlinear Restrictions," *Econometrica*, 53, 1465–1468.

Jondrow, J., Lovell, C. A. K., Materov, I. S., and Schmidt, P. (1982) "On the Estimation of Technical Efficiency in the Stochastic Frontier Production Function Model," *Journal of Econometrics*, 19:2/3 (August), 233–38.

Kumbhakar, S. C. and Knox Lovell, C. A. (2000), *Stochastic Frontier Anaysis*, New York: Cambridge University Press.

Meeusen, W. and van Den Broeck, J. (1977), "Efficiency Estimation from Cobb-Douglas Production Functions with Composed Error," *International Economic Review*, 18:2(Jun), 435–444

Mroz, T. A. (1987), "The Sensitivity of an Empirical Model of Married Women's Hours of Work to Economic and Statistical Assumptions," *Econometrica*, 55, 765–799.

Phillips, C. B. and Park, J. Y. (1988), "On Formulating Wald Tests of Nonlinear Restrictions," *Econometrica*, 56, 1065–1083.

Wooldridge, J. M. (2002), *Econometric Analysis of Cross Section of Panel Data*, Cambridge, MA: MIT Press.

Chapter 21
The HPREDUCE Procedure

Contents

Overview: HPREDUCE Procedure **508**
PROC HPREDUCE Features 508
PROC HPREDUCE Contrasted with Other SAS Procedures 509
Getting Started: HPREDUCE Procedure **509**
Unsupervised Variable Selection with the HPREDUCE Procedure 512
Supervised Variable Selection with HPREDUCE Procedure 514
Syntax: HPREDUCE Procedure **517**
PROC HPREDUCE Statement 517
CLASS Statement 519
REDUCE Statement 520
PERFORMANCE Statement 521
Details: HPREDUCE Procedure **521**
Unsupervised Variable Selection 521
Supervised Variable Selection 522
Variable Selection for Regression 522
Variable Selection for Classification 523
Computational Method 523
Displayed Output 524
Performance Information 524
Model Information 525
Number of Observations 525
Class Level Information 525
Selection Summary 525
Selection Effects 525
Procedure Task Timing 525
ODS Table Names 526
Examples: HPREDUCE Procedure **526**
Example 21.1: Running in Soloist Mode 526
Example 21.2: Running in Distributed Mode 529
Example 21.3: Output a Correlation Matrix to a SAS Data File 531
Example 21.4: Output the Correlation Matrix in LIL Format 532
Example 21.5: Output an ODS Table as A Local Data File 533
References **534**

Overview: HPREDUCE Procedure

The HPREDUCE procedure is a high-performance procedure that performs both supervised and unsupervised variable selection on the SAS appliance. With the HPREDUCE procedure you can read data in distributed form and perform variable selection in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about how to configure the execution mode of SAS High-Performance Analytics procedures.

The HPREDUCE procedure performs unsupervised variable selection by identifying a set of variables that jointly explain the maximum amount of data variance. Unlike principal component analysis (PCA), which reduces dimensionality by generating a set of new variables (variable extraction), the HPREDUCE procedure reduces dimensionality by selecting a subset of the original variables (variable selection). Thus, this technique preserves model interpretation.

The HPREDUCE procedure performs supervised variable selection by identifying a set of variables that jointly explain the maximum amount of variance contained in the response variables. The HPREDUCE procedure supports variable selection in both the regression setting and the classification (categorization) setting.

The HPREDUCE procedure can also be used to output the sums of squares and crossproducts (SSCP) matrix, the correlation (CORR) matrix, or the covariance (COV) matrix for exploratory data analysis and direct input to statistical procedures that accept that form. This step saves time by eliminating redundant matrix aggregations.

PROC HPREDUCE Features

The HPREDUCE procedure conducts a variance analysis and reduces dimensionality by selecting the variables that contribute the most to the overall variance of the data (or the dependent variables). The following list summarizes the basic features of the HPREDUCE procedure:

- Variable selection is based on covariance analysis.
- Analysis can be performed on a massively parallel SAS high-performance appliance.
- Input data can be read in parallel when the data source is the appliance database.
- Computation of the CORR, COV, or SSCP matrix is distributed.
- Computation of the variable selection steps is distributed.
- All phases of analytic execution use of high degree of multithreading.
- Both supervised and unsupervised variable selection are supported.

- Multiple response variables are supported in variable selection for regression.
- The CLASS statement supports categorical inputs.
- The REDUCE statement supports main and interaction effects.
- The OUTCP statement supports outputting a CORR, COV, or SSCP matrix.

PROC HPREDUCE Contrasted with Other SAS Procedures

For general contrasts between High-Performance Analaytics procedures and other SAS procedures, see the session "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16. The following remarks compare the HPREDUCE procedure with the FACTOR, PRINCOMP, GLMSELECT, and DISCRIM procedures in SAS/STAT software.

When PROC HPREDUCE performs unsupervised variable selection, it conducts variance analysis and reduces dimensionality by forward selection of the variables that contribute the most to the overall data variance. The output lists the variables in order of their contribution to data variance and can be used directly for reporting or for selecting variables for model building procedures. In contrast, principal component analysis (PCA) conducts a variance analysis and then projects the data space to an orthogonal set of axes by a linear combination of the original variables. These new principal components best explain the data variance and can be used as input to model building procedures. In either case, the number of inputs to the modeling procedure has been reduced from the original set. PCA can be done through the SAS/STAT FACTOR and PRINCOMP procedures. The primary difference between PCA and PROC HPREDUCE is that PCA generates new variables, while PROC HPREDUCE reduces data dimensionality by selecting a subset of the original variables. This feature of PROC HPREDUCE is beneficial in applications where retaining the original variables is important for model exploration and interpretation.

When PROC HPREDUCE performs supervised variable selection, it conducts variance analysis and reduces dimensionality by forward selection of the variables that contribute the most to explaining the overall variance of the response variables (targets). The output lists the variables in order of their contribution to explaining response variance. The output can be used directly for reporting or for selecting variables for model building procedures. When PROC HPREDUCE is used to perform supervised variable selection, it most resembles the GLMSELECT procedure. However, PROC HPREDUCE allows multiple response variables, which is not supported by PROC GLMSELECT. When the response variable is a classification variable and its levelization is done in a special format, PROC HPREDUCE conducts variance analysis in the same way as linear discriminant analysis (LDA) does. LDA can be done through the SAS/STAT DISCRIM procedure. Like PCA, LDA generates new variables by linearly combining all original variables, while PROC HPREDUCE reduces data dimensionality by selecting a subset of the original variables.

Getting Started: HPREDUCE Procedure

The following DATA step contains 100 observations with one character variable (C), one classification variable (y), and 10 continuous variables (x1–x10). This data set is used for both of the getting-started examples in the following sections.

```
data getStarted;
  input C$ y x1-x10;
  datalines;
  D  0  10.2  6  1.6  38  15  2.4  20  0.8  8.5  3.9
  F  1  12.2  6  2.6  42  61  1.5  10  0.6  8.5  0.7
  D  1   7.7  1  2.1  38  61    1  90  0.6  7.5  5.2
  J  1  10.9  7  3.5  46  42  0.3   0  0.2    6  3.6
  E  0  17.3  6  3.8  26  47  0.9  10  0.4  1.5  4.7
  A  0  18.7  4  1.8   2  34  1.7  80    1  9.5  2.2
  B  0   7.2  1  0.3  48  61  1.1  10  0.8  3.5    4
  D  0   0.1  3  2.4   0  65  1.6  70  0.8  3.5  0.7
  H  1   2.4  4  0.7  38  22  0.2  20    0    3  4.2
  J  0  15.6  7  1.4   0  98  0.3   0    1    5  5.2
  J  0  11.1  3  2.4  42  55  2.2  60  0.6  4.5  0.7
  F  0     4  6  0.9   4  36  2.1  30  0.8    9  4.6
  A  0   6.2  2  1.8  14  79  1.1  70  0.2    0  5.1
  H  0   3.7  3  0.8  12  66  1.3  40  0.4  0.5  3.3
  A  1   9.2  3  2.3  48  51  2.3  50    0    6  5.4
  G  0    14  3    2  18  12  2.2   0    0    3  3.4
  E  1  19.5  6  3.7  26  81  0.1  30  0.6    5  4.8
  C  0    11  3  2.8  38   9  1.7  50  0.8  6.5  0.9
  I  0  15.3  7  2.2  20  98  2.7 100  0.4    7  0.8
  H  1   7.4  4  0.5  28  65  1.3  60  0.2  9.5  5.4
  F  0  11.4  2  1.4  42  12  2.4  10  0.4    1  4.5
  C  1  19.4  1  0.4  42   4  2.4  10    0  6.5  0.1
  G  0   5.9  4  2.6  12  57  0.8  50  0.4    2  5.8
  G  1  15.8  6  3.7  34   8  1.3  90  0.6  2.5  5.7
  I  0    10  3  1.9  16  80    3  90  0.4  9.5  1.9
  E  0  15.7  1  2.7  32  25  1.7  20  0.2  8.5    6
  G  0    11  5  2.9  48  53  0.1  50    1  3.5  1.2
  J  1  16.8  0  0.9  14  86  1.4  40  0.8    9    5
  D  1    11  4  3.2  48  63  2.8  90  0.6    0  2.2
  J  1   4.8  7  3.6  24   1  2.2  20    1  8.5  0.5
  J  1  10.4  5    2  42  56    1  20    0  3.5  4.2
  G  0  12.7  7  3.6   8  56  2.1  70    1  4.5  1.5
  G  0   6.8  1  3.2  30  27  0.6   0  0.8    2  5.6
  E  0   8.8  0  3.2   2  67  0.7  10  0.4    1    5
  I  1   0.2  0  2.9  10  41  2.3  60  0.2    9  0.3
  J  1   4.6  7  3.9  50  61  2.1  50  0.4    3  4.9
  J  1   2.3  2  3.2  36  98  0.1  40  0.6  4.5  4.3
  I  0  10.8  3  2.7  28  58  0.8  80  0.8    3    6
  B  0   9.3  2  3.3  44  44  0.3  50  0.8  5.5  0.4
  F  0   9.2  6  0.6   4  64  0.1   0  0.6  4.5  3.9
  D  0   7.4  0  2.9  14   0  0.2  30  0.8  7.5  4.5
  G  0  18.3  3  3.1   8  60  0.3  60  0.2    7  1.9
  F  0   5.3  4  0.2  48  63  2.3  80  0.2    8  5.2
  C  0   2.6  5  2.2  24   4  1.3  20    0    2  1.4
  F  0  13.8  4  3.6   4   7  1.1  10  0.4  3.5  1.9
  B  1  12.4  6  1.7  30  44  1.1  60  0.2    6  1.5
  I  0   1.3  1  1.3   8  53  1.1  70  0.6    7  0.8
  F  0  18.2  7  1.7  26  92  2.2  30    1  8.5  4.8
  J  0   5.2  2  2.2  18  12  1.4  90  0.8    4  4.9
  G  1   9.4  2  0.8  22  86  0.4  30  0.4    1  5.9
```

```
  J  1  10.4  2  1.7  26  31  2.4  10  0.2    7  1.6
  J  0    13  1  1.8  14  11  2.3  50  0.6  5.5  2.6
  A  0  17.9  4  3.1  46  58  2.6  90  0.6  1.5  3.2
  D  1  19.4  6    3  20  50  2.8 100  0.2    9  1.2
  I  0  19.6  3  3.6  22  19  1.2   0  0.6    5  4.1
  I  1     6  2  1.5  30  30  2.2  20  0.4  8.5  5.3
  G  0  13.8  1  2.7   0  52  2.4  20  0.8    6    2
  B  0  14.3  4  2.9  30  11  0.6  90  0.6  0.5  4.9
  E  0  15.6  0  0.4  38  79  0.4  80  0.4    1  3.3
  D  0    14  2    1  22  61    3  90  0.6    2  0.1
  C  1   9.4  5  0.4  12  53  1.7  40    0    3  1.1
  H  0  13.2  1  1.6  40  15  0.7  40  0.2    9  5.5
  A  0  13.5  5  2.4  18  89  1.6  20  0.4  9.5  4.7
  E  0   2.6  4  2.3  38   6  0.8  20  0.4    5  5.3
  E  0  12.4  3  1.3  26   8  2.8  10  0.8    6  5.8
  D  0   7.6  2  0.9  44  89  1.3  50  0.8    6  0.4
  I  0  12.7  1  2.3  42   6  2.4  10  0.4    1    3
  C  1  10.7  4  3.2  28  23  2.2  90  0.8  5.5  2.8
  H  0  10.1  2  2.3  10  62  0.9  50  0.4  2.5  3.7
  C  1  16.6  1  0.5  12  88  0.1  20  0.6  5.5  1.8
  I  1   0.2  3  2.2   8  71  1.7  80  0.4  0.5  5.5
  C  0  10.8  4  3.5  30  70  2.3  60  0.4  4.5  5.9
  F  0   7.1  4    3  14  63  2.4  70    0    7  3.1
  D  0  16.5  1  3.3  30  80  1.6  40    0  3.5  2.7
  H  0  17.1  7  2.1  30  45  1.5  60  0.6  0.5  2.8
  D  0   4.3  1  1.5  24  44    0  70    0    5  0.5
  H  0    15  2  0.2  14  87  1.8  50    0  4.5  4.7
  G  0  19.7  3  1.9  36  99  1.5  10  0.6    3  1.7
  H  1   2.8  6  0.6  34  21    2  60    1    9  4.7
  G  0  16.6  3  3.3  46   1  1.4  70  0.6  1.5  5.3
  E  0  11.7  5  2.7  48   4  0.9  60  0.8  4.5  1.6
  F  0  15.6  3  0.2   4  79  0.5   0  0.8  1.5  2.9
  C  1   5.3  6  1.4   8  64    2  80  0.4    9  4.2
  B  1   8.1  7  1.7  40  36  1.4  60  0.6    6  3.9
  I  0  14.8  2  3.2   8  37  0.4  10    0  4.5    3
  D  0   7.4  4    3  12   3  0.6  60  0.6    7  0.7
  D  0   4.8  3  2.3  44  41  1.9  60  0.2    3  3.1
  A  0   4.5  0  0.2   4  48  1.7  80  0.8    9  4.2
  D  0   6.9  6  3.3  14  92  0.5  40  0.4  7.5    5
  B  0   4.7  4  0.9  14  99  2.4  80    1  0.5  0.7
  I  1   7.5  4  2.1  20  79  0.4  40  0.4  2.5  0.7
  C  0   6.1  0  1.4  38  18  2.3  60  0.8  4.5  0.7
  C  0  18.3  1    1  26  98  2.7  20    1  8.5  0.5
  F  0  16.4  7  1.2  32  94  2.9  40  0.4  5.5  2.1
  I  0   9.4  2  2.3  32  42  0.2  70  0.4  8.5  0.3
  F  1  17.9  4  1.3  32  42    2  40  0.2    1  5.4
  H  0  14.9  3  1.6  36  74  2.6  60  0.2    1  2.3
  C  0  12.7  0  2.6   0  88  1.1  80  0.8  0.5  2.1
  F  0   5.4  4  1.5   2   1  1.8  70  0.4  5.5  3.6
  J  1  12.1  4  1.8  20  59  1.3  60  0.4    3  3.8
;
```

Unsupervised Variable Selection with the HPREDUCE Procedure

The following statements use PROC HPREDUCE for unsupervised variable selection. The statements specify that the technique used for variable selection is variance analysis. The maximum number of variables to select is 5, and the maximum percentage of the total variance to explain is 95%. The procedure stops when either of two conditions is satisfied.

```
proc hpreduce data=getstarted technique=VarianceAnalysis;
    class C;
    reduce unsupervised C x1-x10 / maxeffects=5 varexp=0.95;
    performance details;
run;
```

The output from this analysis is presented in Figure 21.1 through Figure 21.5.

Figure 21.1 shows the "Performance Information" table, which indicates that the procedure executes in client mode. That is, the procedure runs on the machine where the SAS system is running. The table also shows that two threads are used for computing.

Figure 21.1 Performance Information

Performance Information

Execution Mode	On client
Number of Threads	2

Figure 21.2 displays the "Model Information" and "Number of Observations" tables. The "Model Information" table shows that the HPREDUCE procedure is used for unsupervised variable selection. The CLASS variable C is parameterized in the general linear model (GLM) parameterization, which is the default. The total number of variables is 11. The technique used for variable selection is variance analysis. The maximum number of variables to select is 5, and the maximum percentage of the total variance to explain is 95%. The "Number of Observations" table shows that all 100 observations in the data set are used in the analysis.

Figure 21.2 Model Information and Number of Observations

Model Information

Data Source	WORK.GETSTARTED
Model Type	Unsupervised
Class Parameterization	GLM
Selection Technique	Variance Analysis
Number of Variables	11
Number of Variables to Select	5
Variance to Explain	0.95

Number of Observations Read	100
Number of Observations Used	100

Figure 21.3 shows the "Class Level Information" table, which indicates that the CLASS variable C has 10 unique formatted levels.

Figure 21.3 Class Level Information and Response Profile

Class Level Information

Class	Levels	Values
C	10	A B C D E F G H I J

Figure 21.4 shows the "Selection Summary" and "Selected Effects" tables. The "Selection Summary" table shows which variable (or level for CLASS variables) is selected in each step, in addition to the total variance that is explained by the variables selected so far. The "Selected Effects" table presents all the selected variables and their corresponding variable types.

Figure 21.4 Selection Summary and Selected Effects

Selection Summary

Iteration	Selected Variables	Levels	Variance Explained
1	x3	-	0.0681
2	x7	-	0.1326
3	x10	-	0.1933
4	C	I	0.2529
5	C	F	0.312
6	C	J	0.369
7	C	B	0.4257
8	C	G	0.4813
9	C	D	0.5351
10	C	H	0.5889
11	C	A	0.6407
12	x5	-	0.6916

Selected Effects

Number	Selected Variables	Variable Type
1	x3	INTERVAL
2	x7	INTERVAL
3	x10	INTERVAL
4	C	CLASS
5	x5	INTERVAL

Figure 21.5 shows the "Procedure Task Timing" table, which provides details about how much time is used by each processing step.

Figure 21.5 Procedure Task Timing

Procedure Task Timing		
Task	Time (sec.)	
Data read and variable levelization	0.03	91.2%
Effect Levelization	0.00	0.00%
Cross-product accumulation	0.00	5.88%
Variable selection	0.00	2.94%

Supervised Variable Selection with HPREDUCE Procedure

The following statements use PROC HPREDUCE for supervised variable selection. The statements specify that y is the response variable, the technique used for variable selection is discriminant analysis, and the maximum number of variables to select is 5.

```
proc hpreduce data=getstarted technique=DiscriminantAnalysis;
    class C y;
    reduce supervised y = C x1-x10 / maxeffects=5;
    performance details;
run;
```

The output from this analysis is presented in Figure 21.6 through Figure 21.10.

Figure 21.6 shows the "Performance Information" table, which indicates that the procedure executes in client mode. That is, the procedure runs on the machine where the SAS system is running. The table also shows that two threads are used for computing.

Figure 21.6 Performance Information

Performance Information	
Execution Mode	On client
Number of Threads	2

Figure 21.7 displays the "Model Information" and "Number of Observations" tables. The "Model Information" table shows that HPREDUCE procedure performed supervised variable selection. The CLASS variables are parameterized in the general linear model (GLM) parameterization, which is the default. The total number of variables is 12. The technique used for variable selection is discriminant analysis, and the maximum number of variables to select is 5. The "Number of Observations" table shows that all 100 observations in the data set are used in the analysis.

Figure 21.7 Model Information and Number of Observations

Model Information

Data Source	WORK.GETSTARTED
Model Type	Supervised
Class Parameterization	GLM
Selection Technique	Discriminant Analysis
Number of Variables	12
Number of Variables to Select	5

Number of Observations Read	100
Number of Observations Used	100

Figure 21.8 shows the "Class Level Information" table, which indicates that the CLASS variable C has 10 unique formatted levels and the CLASS variable y has two levels.

Figure 21.8 Class Level Information and Response Profile

Class Level Information

Class	Levels	Values
C	10	A B C D E F G H I J
y	2	0 1

Figure 21.9 shows the "Selection Summary" and "Selected Effects" tables. The "Selection Summary" table shows which variable (or level for CLASS variables) is selected in each step, in addition to the total variance that is explained by the variables selected so far. The "Selected Effects" table presents all the selected variables and their corresponding variable types.

Figure 21.9 Selection Summary and Selected Effects

Selection Summary

Iteration	Selected Variables	Levels	Variance Explained
1	C	J	0.0811
2	x8	–	0.1323
3	x2	–	0.1687
4	C	C	0.1992
5	x4	–	0.2184
6	x9	–	0.2369

Selected Effects

Number	Selected Variables	Variable Type
1	C	CLASS
2	x8	INTERVAL
3	x2	INTERVAL
4	x4	INTERVAL
5	x9	INTERVAL

Figure 21.10 shows the "Procedure Task Timing" table, which provides details about how much time is used by each processing step.

Figure 21.10 Procedure Task Timing

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	0.04	70.7%
Effect Levelization	0.00	0.00%
Data preparation for discriminant analysis	0.00	0.00%
Cross-product accumulation	0.02	27.6%
Variable selection	0.00	1.72%

Syntax: HPREDUCE Procedure

The following statements are available in the HPREDUCE procedure:

PROC HPREDUCE < *options* > **;**
  CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < */ global-options* > **;**
  REDUCE UNSUPERVISED *effects* < */ reduce-options* > **;**
  REDUCE SUPERVISED *response* . . . < *response* > **=** *effects* < */ reduce-options* > **;**
  PERFORMANCE *performance-options* **;**

The PROC HPREDUCE statement and the REDUCE statement are required. The CLASS statement can appear multiple times. If a CLASS statement is specified, it must precede the REDUCE statement.

PROC HPREDUCE Statement

PROC HPREDUCE < *options* > **;**

The PROC HPREDUCE statement invokes the procedure. Table 21.1 summarizes the important options in the PROC HPREDUCE statement by function. The options are then described fully in alphabetical order.

Table 21.1 PROC HPREDUCE Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
NAMELEN=	Limits the length of effect names
TECHNIQUE=	Selects the variable selection technique
Options Related to Output	
NOPRINT	Suppresses ODS output
NOCLPRINT	Limits or suppresses the display of CLASS levels
NOSUMPRINT	Suppresses generation of the selection summary table
TIMEPRINT	Prints the time used by each variable selection iteration
OUTCP=	Outputs the CORR, COV, or SSCP matrix
Pearson Correlation Statistics	
COV	Computes covariances
CORR	Computes correlations (default)
SSCP	Computes sums of squares and crossproducts
User-Defined Formats	
FMTLIBXML=	Specifies the file reference for a format stream

You can specify the following *options* in the PROC HPREDUCE statement.

CORR
selects variables based on the correlation matrix. Assuming that X and Y are two variables, the correlation between X and Y is computed by:

$$Corr(X,Y) = \frac{E\left((X - E(X))(Y - E(Y))\right)}{\sqrt{E(X - E(X))^2 \, E(Y - E(Y))^2}}$$

This is the default option for computing the Pearson correlation statistics in PROC HPREDUCE.

COV
selects variables based on the covariance matrix. Assuming that X and Y are two variables, the covariance between X and Y is computed by:

$$Cov(X,Y) = E\left((X - E(X))(Y - E(Y))\right)$$

DATA=*SAS-data-set*
names the input SAS data set to be used by PROC HPREDUCE. The default is the most recently created data set. If the procedure executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. When data are already distributed, the procedure reads the data alongside the distributed database. See the sections "SMP and MPP Modes" on page 16 and "Alongside-the-Database Execution" on page 22.

FMTLIBXML=*file-ref*
specifies the file reference for the XML stream that contains the user-defined format definitions. In a distributed computing environment, user-defined formats are handled differently than they are in other SAS products. See the section "Working with Formats" on page 27 in Chapter 3, "Shared Concepts and Topics," for details about how to generate an XML stream for your formats.

NAMELEN=*number*
specifies the length to which long effect names are shortened ($20 \leq$ *number* ≤ 128). The default and minimum value is 20.

NOCLPRINT<=*number***>**
suppresses the display of the "Class Level Information" table if you do not specify *number*. If you specify *number*, the values of the classification variables are displayed for only those variables whose number of levels is less than *number*. Specifying a *number* helps to reduce the size of the "Class Level Information" table if some classification variables have a large number of levels.

NOPRINT
suppresses the generation of ODS output.

NOSUMPRINT
suppresses the generation of the "Selection Summary" table.

OUTCP=*SAS-data-set***<(LIST<(EPS =** *number***)>)>**
creates both a data set that contains a symmetric matrix that depicts the relationships among variables and also a set of statistics about the input data set and variables. Depending on the Pearson correlation statistics option specified in the PROC HPREDUCE statement, the symmetric matrix can be a correlation (CORR) matrix, a covariance (COV) matrix, or a sums of squares and crossproducts (SSCP) matrix.

When the LIST option is specified, the symmetric matrix is output in the list-of-list (LIL) format. In this format, the matrix is represented as a set of tuples $(i,\ j,\ x)$, where x is an entry in the matrix and i and j denote its row and column indices, respectively. LIL format can be used when the output contains too many columns to fit in a data set. For example, in most database systems the maximum number of columns in a table is usually limited to several thousand. If an output matrix contains more columns than the limit, you must use the LIST option to avoid errors that would arise from writing too many columns to the table. When LIL format is used, all 0 entries in the matrix are ignored in the output.

When EPS= *number* is specified in the LIST option, matrix entries that have an absolute value smaller than *number* are ignored in the output. This feature helps omit unreliable estimations and generate a compact representation for the matrix. When the EPS= option is not specified, only the 0 entries in the matrix are ignored in the output.

SSCP

selects variables based on the sums of squares and crossproducts matrix. Assuming that X and Y are two variables and that $\mathbf{x}$ and $\mathbf{y}$ are their corresponding variable vectors, the SSCP between X and Y is computed by:

$$SSCP(X, Y) = \mathbf{x}^{\top}\mathbf{y}$$

TECHNIQUE=*keyword*

TECH=*keyword*

specifies the variable selection technique. You can specify the following *keyword*s:

VARIANCEANALYSIS | VAR performs variance analysis for variable selection.

DISCRIMINANTANALYSIS | DSC performs discriminant analysis for variable selection.

The default value is TECHNIQUE=VAR.

You can use variance analysis for both supervised and unsupervised variable selection. You can use discriminant analysis only for supervised variable selection with one classification variable as the response. For more information, see the section "Variable Selection for Classification" on page 523.

TIMEPRINT

prints the time (in seconds) used by each variable selection iteration in the "Selection Summary" table. If this option does not appear in the PROC HPREDUCE statement, the time information is not printed.

CLASS Statement

CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < / *global-options* > **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. The CLASS statement must precede the REDUCE statement.

The CLASS statement for High-Performance Analytics procedures is documented in the section "CLASS Statement" on page 28 of Chapter 3, "Shared Concepts and Topics."

The HPREDUCE procedure does not support the SPLIT option in the CLASS statement. For CLASS variable parameterization, the HPREDUCE procedure only support the GLM method.

REDUCE Statement

REDUCE UNSUPERVISED *effects* < / *reduce-options* > **;**

REDUCE SUPERVISED *response* . . . < *response* > = *effects* < / *reduce-options* > **;**

PROC HPREDUCE can be used for both supervised and unsupervised variable selection. In unsupervised case, the REDUCE statement specifies the effects to be considered in the variable selection process. An effect can be an original variable in the input data set or a variable constructed from the original variables. In the supervised case, you need to specify both the effects and the response variables. A response variable can be an original variable in the input data set or a variable constructed from the original variables. For the regression case, you can specify more than one response variable.

Table 21.2 summarizes the *reduce-options*, which control the number of variables to be selected.

Table 21.2 *reduce-options*

Option	Description
MAXSTEPS=	Specifies the maximum number of steps to take for variable selection; the number must be greater than or equal to 1.
MAXEFFECTS=	Specifies the number of effects to select; the number must be greater than or equal to 1.
VARIANCEEXPLAINED | VAREXP=	Specifies the fraction of the total variance to be explained; the value must be between 0 and 1.
MINVARIANCEINCREMENT | VARINC=	Specifies the minimum increment of explained variance (in a fraction of the total variance); the value must be between 0 and 1.

The *reduce-options* determine the number of variables to be selected. You can specify the following *reduce-options*. When any of the options is satisfied, the HPREDUCE procedure stops.

MAXSTEPS=*n*
stops PROC HPREDUCE after it runs *n* steps.

MAXEFFECTS=*n*
stops PROC HPREDUCE after *n* effects have been selected. Since individual levels of one classification variable can be selected in different steps of the variable selection process, PROC HPREDUCE might take more than *n* steps to select *n* effects.

VARIANCEEXPLAINED=*fraction*

VAREXP=*fraction*
stops PROC HPREDUCE when the *fraction* of the total variance can be explained by the selected variables.

MINVARIANCEINCREMENT=*fraction*

VARINC=*fraction*

stops PROC HPREDUCE when the minimum increment of the explained variance is less than *fraction* of the total variance.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPREDUCE procedure.

With the PERFORMANCE statement, you can also control whether the HPREDUCE procedure executes in SMP or MPP mode.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

Details: HPREDUCE Procedure

The performance of a learning model usually decreases in terms of accuracy and efficiency when the dimensionality of the input data is high. The problem is known as the "curse of dimensionality." Variable selection techniques can reduce the dimensionality of a data set by removing irrelevant and redundant variables (Liu and Motoda 1998).

The HPREDUCE procedure performs both supervised and unsupervised variable selection. It selects variables by identifying a set of variables that can jointly explain the maximum amount of data variance.

Unsupervised Variable Selection

When no response variable is specified, PROC HPREDUCE conducts unsupervised variable selection. Assume that k variables need to be selected. Let $\mathbf{X} \in \mathbb{R}^{n \times m}$ be a data set that contains n samples and m variables; let $\mathbf{X} = (\mathbf{X}_1, \mathbf{X}_2)$, where $\mathbf{X}_1 \in \mathbb{R}^{n \times k}$ is the data set that contains the k selected variables and $\mathbf{X}_2 \in \mathbb{R}^{n \times (m-k)}$ contains the remaining $m - k$ variables. PROC HPREDUCE selects the variables by minimizing the equation:

$$\min Trace\left(\mathbf{X}_2^{\top}\left(\mathbf{I} - \mathbf{X}_1\left(\mathbf{X}_1^{\top}\mathbf{X}_1\right)^{-1}\mathbf{X}_1^{\top}\right)\mathbf{X}_2\right)$$

$\left(\mathbf{I} - \mathbf{X}_1\left(\mathbf{X}_1^{\top}\mathbf{X}_1\right)^{-1}\mathbf{X}_1^{\top}\right)^{\frac{1}{2}}\mathbf{X}_2$ projects $\mathbf{X}_2$ to the null space of $\mathbf{X}_1$. Therefore, the above equation measures the data variance that resides in the null space of $\mathbf{X}_1$, which is the data variance that cannot be explained by the variables in $\mathbf{X}_1$. Minimizing this equation leads to the selection of the variables that jointly explain the maximum amount of the variance in the original data.

Let $\mathbf{C}_{11} = \mathbf{X}_1^\top \mathbf{X}_1$, $\mathbf{C}_{12} = \mathbf{X}_1^\top \mathbf{X}_2$, and $\mathbf{C}_{21} = \mathbf{X}_2^\top \mathbf{X}_1$. The following equations hold:

$$\mathbf{C} = \mathbf{X}^\top \mathbf{X} = \begin{pmatrix} \mathbf{C}_{11} & \mathbf{C}_{12} \\ \mathbf{C}_{21} & \mathbf{C}_{22} \end{pmatrix}$$

$$\mathbf{X}_2^\top \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right) \mathbf{X}_2 = \mathbf{C}_{22} - \mathbf{C}_{21} \mathbf{C}_{11}^{-1} \mathbf{C}_{21}$$

When all the variables are centralized to have a zero mean, $\mathbf{C}$ is the covariance matrix. This corresponds to setting the COV option in the PROC HPREDUCE statement, which specifies that the covariance matrix be used for variable selection. Similarly, if variables need to be both centralized and normalized to have unit length, you should specify the CORR option in the PROC HPREDUCE statement, which leads to the use of the correlation matrix for variable selection. If neither centralization nor normalization should be applied, you need to specify the SSCP option in the PROC HPREDUCE statement.

Principal component analysis (PCA) (Jolliffe 2002) also reduces dimensionality by preserving data variance. The key difference between PCA and PROC HPREDUCE is that PCA generates a small set of new variables (variable extraction) by linearly combining the original variables, while PROC HPREDUCE selects a small set of the original variables (variable selection). The variables returned by PROC HPREDUCE are the original variables. This feature is very important in applications where retaining the original variables is important for model exploration or interpretation (for example, genetic analysis, and text mining).

Supervised Variable Selection

When response variables are specified in a REDUCE statement, PROC HPREDUCE conducts supervised variable selection. The procedure supports variable selection both in a regression context and in a classification (categorization) context.

Variable Selection for Regression

In a regression setting, all response variables should be numerical. When a classification variable is in the response, this variable needs to be levelized to multiple dummy variables, with each dummy variable corresponding to a level of the classification variable. You can achieve this levelization by adding this variable to the variable list of the CLASS statement.

Let $\mathbf{Y} \in \mathbb{R}^{n \times t}$ be the response data that contain t response variables. Assume that k variables need to be selected. Let $\mathbf{X} \in \mathbb{R}^{n \times m}$ be a data set that contains n samples and m variables; let $\mathbf{X} = (\mathbf{X}_1, \mathbf{X}_2)$, where $\mathbf{X}_1 \in \mathbb{R}^{n \times k}$ is the data set that contains the k selected variables and $\mathbf{X}_2 \in \mathbb{R}^{n \times (m-k)}$ contains the remaining $m - k$ variables. PROC HPREDUCE selects the variables by minimizing the following equation:

$$\min Trace \left(\mathbf{Y}^\top \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right) \mathbf{Y} \right)$$

$\left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right)^{\frac{1}{2}} \mathbf{Y}$ projects $\mathbf{Y}$ to the null space of $\mathbf{X}_1$. Therefore, the equation measures the response variance that resides in the null space of $\mathbf{X}_1$, which is the variance of the response variables that cannot be explained by the variables in $\mathbf{X}_1$. Minimizing the equation leads to the selection of the variables that jointly explain the maximum amount of the variance of the response variables.

Variable Selection for Classification

In a classification setting, one classification variable is specified as the response, with each of its levels corresponding to a category of the classification problem. Let the classification variable be $\mathbf{y}$ with c levels $\{1, \ldots, c\}$. Then $\mathbf{y}$ can be levelized in a special way to generate a response data $\mathbf{Y} \in \mathbb{R}^{n \times c}$ as:

$$\mathbf{Y}_{i,j} = \begin{cases} \frac{1}{\sqrt{n}} \left(\sqrt{\frac{n}{n_j}} - \sqrt{\frac{n_j}{n}} \right), & \mathbf{y}_i = j \\ -\frac{1}{\sqrt{n}} \sqrt{\frac{n_j}{n}} & , \quad \mathbf{y}_i \neq j \end{cases}$$

By using this $\mathbf{Y}$ in the variance analysis, PROC HPREDUCE selects variables by using the discriminant criterion specified in linear discriminant analysis (LDA) (Fisher 1936; Cooley and Lohnes 1971). LDA also reduces dimensionality. The key difference between LDA and PROC HPREDUCE is that LDA generates a small set of new variables (variable extraction) by linearly combining the original variables, while PROC HPREDUCE selects a small set of the original variables (variable selection).

Computational Method

Given m variables, finding the k variables that minimize the proposed equations is a combinatorial problem, which is NP-hard (nondeterministic polynomial-time hard). To select k variables, PROC HPREDUCE applies k steps of a greedy search to generate a suboptimal solution for the problem.

Assume that q features have been selected, that $\mathbf{X}_1$ contains the q selected variables, and that $\mathbf{X}_2$ contains the remaining variables. PROC HPREDUCE selects the $q+1$ variable, F, by minimizing the equation

$$arg \min_{F} Trace \left(\hat{\mathbf{X}}_2^\top \left(\mathbf{I} - \hat{\mathbf{X}}_1 \left(\hat{\mathbf{X}}_1^\top \hat{\mathbf{X}}_1 \right)^{-1} \hat{\mathbf{X}}_1^\top \right) \hat{\mathbf{X}}_2 \right)$$

where $\hat{\mathbf{X}}_1$ is the data set that contains the feature F and the q selected variables, and $\hat{\mathbf{X}}_2$ is the data set that contains the remaining variables. Minimizing the preceding problem is equivalent to maximizing the following problem:

$$\frac{\left\| \mathbf{X}_2^\top \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right) \mathbf{f} \right\|_2^2}{\left\| \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right)^{\frac{1}{2}} \mathbf{f} \right\|_2^2}$$

In the preceding equation, $\left\| \mathbf{X}_2^\top \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right) \mathbf{f} \right\|_2^2$ is the summation of the squares of the covariance between the variable $\mathbf{f}$ and all the unselected variables in the null space of $\mathbf{X}_1$. And $\left\| \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right)^{\frac{1}{2}} \mathbf{f} \right\|_2^2$ is the square of the variance of $\mathbf{f}$ in the null space of $\mathbf{X}_1$, which is used as a normalization factor.

This problem can be solved efficiently. Assuming that $m \gg k$, the time complexity for solving it is

$$O\left(m^2 \left(n + k^2\right)\right)$$

where m is the number of variables, n is the number of samples, and k is the number of selected variables. In the equation, m^2n corresponds to the time for computing the covariance (or correlation, or SSCP) matrix. And m^2k^2 corresponds to the time for selecting k variables out of m.

Similar analysis also applies to supervised variable selection with PROC HPREDUCE. In this case, the following problem is maximized for variable selection:

$$\frac{\left\| \mathbf{Y}^\top \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right) \mathbf{f} \right\|_2^2}{\left\| \left(\mathbf{I} - \mathbf{X}_1 \left(\mathbf{X}_1^\top \mathbf{X}_1 \right)^{-1} \mathbf{X}_1^\top \right)^{\frac{1}{2}} \mathbf{f} \right\|_2^2}$$

Here, $\mathbf{Y}$ is the response data. Let c be the number of columns in $\mathbf{Y}$. The time complexity for selecting k variables by solving the preceding problem is

$$O\left(k^2 (c+k) m + m^2 n\right)$$

Note that for most data of very high dimensionality, $c + k \ll m$.

PROC HPREDUCE is fully threaded and distributed. When there are p machines used for computing, the time complexity for unsupervised variable selection is

$$CPU\left(\frac{m^2\left(n+k^2\right)}{p} + m^2 \log p\right) + NET\left(m^2 \log p\right)$$

And the time complexity for supervised variable selection is

$$CPU\left(\frac{k^2 (c+k) m + m^2 n}{p} + m^2 \log p\right) + NET\left(m^2 \log p\right)$$

where CPU corresponds to the time used for computing and NET corresponds to the time used for communication among computers.

Displayed Output

The following sections describe the output that PROC HPREDUCE produces by default. The output is organized into various tables, which are discussed in the order of appearance.

Performance Information

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution and information about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

Model Information

The "Model Information" table displays basic information about the model, such as the data source, the selection technique, the number of selected variables, and the execution mode that the HPREDUCE procedure determines based on your input and options. If you want to know whether the procedure executed on the client machine or in distributed form or whether data were sent from the client or processed alongside the database, check the execution mode entry of this table.

Number of Observations

The "Number of Observations" table displays the number of observations read from the input data set and the number of observations used in the analysis.

Class Level Information

The "Class Level Information" table lists the levels of every variable specified in the CLASS statement. You should check this information to make sure that the data are correct. You can adjust the order of the CLASS variable levels with the ORDER= option in the CLASS statement.

If the classification variables are in reference parameterization, the "Class Level Information" table also displays the reference value for each variable.

Selection Summary

The "Selection Summary" table displays for each iteration the name of the selected effect, the name of the selected level, and the total variance explained after the iteration. If you specify the TIMEPRINT option in the PROC HPREDUCE statement, information about the time used by each iteration is added to the "Selection Summary" table.

Selection Effects

The "Selected Effects" table summarizes which effects were selected in the selection process. It also provides information about the variable type of each selected effect.

Procedure Task Timing

If you specify the DETAILS option in the PERFORMANCE statement, the procedure produces a "Procedure Task Timing" table, which displays the elapsed time (absolute and relative) for the main tasks of the procedure.

ODS Table Names

Each table created by the HPREDUCE procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 21.3.

Table 21.3 ODS Tables Produced by PROC HPREDUCE

Table Name	Description	Required Statement / Option
ClassLevels	Level information from the CLASS statement	CLASS
ModelInfo	Information about modeling environment	Default output
NObs	Number of observations read and used; number of events and trials, if applicable	Default output
SelectedEffects	Summary of selected variables	Default output
SelectionSummary	Selection summary	Default output
Timing	Absolute and relative times for tasks performed by the procedure	DETAILS option in the PERFORMANCE statement

Examples: HPREDUCE Procedure

Example 21.1: Running in Soloist Mode

This example first generates a data set, which has 2,000 observations and contains both interval variables (x1–x10) and CLASS variables (b1–b3, c1–c10). Then PROC HPREDUCE is run to select variables. When a host for distributed computing is not specified or the NODES option in the PERFORMANCE statement is not specified, PROC HPREDUCE runs automatically in soloist mode.

```
data one;
  array x{10};
  array c{10};
  do i=1 to 2000;
    do j=1 to 10;
       x{j}=ranuni(1);
       c{j}=int(ranuni(1)*4);
    end;
    if c{1} eq 0 then b1 = 'aa';
    if c{1} eq 1 then b1 = 'bb';
    if c{1} eq 2 then b1 = 'cc';
    if c{1} eq 3 then b1 = 'dd';
    if c{1} eq 4 then b1 = 'ee';

    if c{2} eq 0 then b2 = 'ff';
    if c{2} eq 1 then b2 = 'gg';
    if c{2} eq 2 then b2 = 'hh';
    if c{2} eq 3 then b2 = 'ii';
    if c{2} eq 4 then b2 = 'jj';

    if c{3} eq 0 then b3 = 'kk';
    if c{3} eq 1 then b3 = 'll';
    if c{3} eq 2 then b3 = 'mm';
    if c{3} eq 3 then b3 = 'nn';
    if c{3} eq 4 then b3 = 'oo';
    output;
  end;
run;

proc hpreduce data=one;
    class b1-b3 c1-c3;
    reduce unsupervised b1 b1*b2 b3 c1-c3 x1-x10/maxsteps=5;
    performance details;
run;
```

Output 21.1.1 shows the results for PROC HPREDUCE running in soloist mode. Notice that the "Performance Information" table shows that the "Execution mode" is "On client."

Output 21.1.1 PROC HPREDUCE Running in Soloist Mode

Performance Information

Execution Mode	On client
Number of Threads	2

Model Information

Data Source	WORK.ONE
Model Type	Unsupervised
Class Parameterization	GLM
Selection Technique	Variance Analysis
Number of Variables	16
Maximal Number of Steps	5

Number of Observations Read	2000
Number of Observations Used	2000

Class Level Information

Class	Levels	Values
b1	4	aa bb cc dd
b2	4	ff gg hh ii
b3	4	kk ll mm nn
c1	4	0 1 2 3
c2	4	0 1 2 3
c3	4	0 1 2 3

Selection Summary

Iteration	Selected Variables	Levels	Variance Explained
1	b1	cc	0.0821
2	b1	bb	0.1637
3	b1	aa	0.2443
4	b3	kk	0.3036
5	b3	mm	0.3619

Selected Effects

Number	Selected Variables	Variable Type
1	b1	CLASS
2	b3	CLASS

Procedure Task Timing

Task	Time (sec.)	
Data read and variable levelization	0.03	56.5%
Effect Levelization	0.00	8.70%
Cross-product accumulation	0.02	34.8%
Variable selection	0.00	0.00%

Example 21.2: Running in Distributed Mode

When a host for distributed computing is specified and the NODES option in the PERFORMANCE statement is specified, PROC HPREDUCE uses the specified host for computing and runs in distributed mode.

```
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";

data one;
    array x{10};
    array c{10};
    do i=1 to 2000;
        do j=1 to 10;
            x{j}=ranuni(1);
            c{j}=int(ranuni(1)*4);
        end;
        y=int(ranuni(1)*2);
        output;
    end;
run;

proc hpreduce data=one tech=var;
    class c1 c2 c3;
    reduce supervised y = c1-c3 x1-x10/maxsteps=5;
    performance nodes=2;
run;
```

To run the preceding example successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to the macro variables in the example with the appropriate values.

Output 21.2.1 shows the results for PROC HPREDUCE running in distributed mode. Notice that the "Performance Information" table shows that the "Execution mode" is "Distributed."

Output 21.2.1 PROC HPREDUCE Running in Distributed Mode

Performance Information

Host Node	<< your grid host >>
Install Location	<< your grid install location >>
Execution Mode	Distributed
Number of Compute Nodes	2
Number of Threads per Node	8

Model Information

Data Source	WORK.ONE
Model Type	Supervised
Class Parameterization	GLM
Selection Technique	Variance Analysis
Number of Variables	14
Maximal Number of Steps	5

Number of Observations Read	2000
Number of Observations Used	2000

Class Level Information

Class	Levels	Values
c1	4	0 1 2 3
c2	4	0 1 2 3
c3	4	0 1 2 3

Selection Summary

Iteration	Selected Variables	Levels	Variance Explained
1	c2	0	0.0017
2	c3	0	0.0026
3	c3	3	0.0034
4	x2	–	0.0042
5	x8	–	0.0045

Selected Effects

Number	Selected Variables	Variable Type
1	c2	CLASS
2	c3	CLASS
3	x2	INTERVAL
4	x8	INTERVAL

Example 21.3: Output a Correlation Matrix to a SAS Data File

This example shows how to output a correlation matrix to a SAS data file. The OUTCP option creates an output data set named corr.

```
data one;
    array x{2};
    array c{2};
    do i=1 to 2000;
        do j=1 to 2;
            x{j}=ranuni(1);
            c{j}=int(ranuni(1)*2);
        end;
        output;
    end;
run;

title  "Output the Correlation Matrix";

proc hpreduce data=one corr outcp=corr;
    class a;
    reduce unsupervised a x1-x2 /maxsteps=4;
run;

proc print data=corr;
run;
```

Output 21.3.1 shows the content of the data file generated by PROC HPREDUCE.

Output 21.3.1 Output the Correlation Matrix

Obs	_ID_	_TYPE_	_VAR_	_LEV_	_vID_	v1	v2	v3	v4
1	1	MEAN/FREQ				979.00	1021.00	0.49	0.50
2	2	N				2000.00	2000.00	2000.00	2000.00
3	3	CORR	a	0	v1	1.00	-1.00	0.03	0.00
4	4	CORR	a	1	v2	-1.00	1.00	-0.03	-0.00
5	5	CORR	x1		v3	0.03	-0.03	1.00	0.00
6	6	CORR	x2		v4	0.00	-0.00	0.00	1.00

The values in the column _VAR_ are the name of the variables. The _LEV_ column shows the name of a CLASS variable's levels, but is empty for interval variables. Assuming that you have n effects (the total number of interval variables and the levels of CLASS variables), the _vID_ column contains n markers, v1 to vn, where vi denotes the ith effect. The column _TYPE_ defines the role of each row. When the _TYPE_ column shows MEAN/FREQ, the corresponding row contains either the mean for an interval variable or the frequency for a level of a CLASS variable. When the _TYPE_ column shows N, the corresponding row contains the number of samples. And when the _TYPE_ column shows CORR, COV, or SSCP, the corresponding row contains a row of the CORR, COV, or SSCP matrix. In this example, the CORR matrix is 4×4, and it resides in the table in row 3 through row 6 and column 7 through column 10.

Example 21.4: Output the Correlation Matrix in LIL Format

By using the LIST option in the OUTCP option, you can output a correlation matrix in LIL format.

```
data one;
    array x{2};
    do i=1 to 2000;
        a=int(ranuni(1)*2);
        do j=1 to 2;
            x{j}=ranuni(1);
        end;
        output;
    end;
run;

title  "Output the Correlation Matrix in LIL format";

proc hpreduce data=one corr outcp=corr_lil/list(eps=0.01);
    class a;
    reduce unsupervised a x1-x2 /maxsteps=4;
run;

proc print data=corr_lil;
run;
```

Output 21.4.1 shows the correlation matrix in LIL format.

Output 21.4.1 Output the Correlation Matrix in LIL Format

Obs	_TYPE_	_ID_	_NAME1_	_NAME2_	_VAL_
1	S	1	samples		2000.00
2	S	2	nVar		3.00
3	S	3	nEff		4.00
4	F	1	a	0	979.00
5	F	2	a	1	1021.00
6	M	3	x1		0.49
7	M	4	x2		0.50
8	R	1	1	1	1.00
9	R	2	2	1	-1.00
10	R	3	2	2	1.00
11	R	4	3	1	0.03
12	R	5	3	2	-0.03
13	R	6	3	3	1.00
14	R	10	4	4	1.00

The column _TYPE_ defines the type of each row:

- When the _TYPE_ column shows S, the corresponding row contains the statistics of the data set. More specifically, when the _TYPE_ column shows S and the _NAME1_ column shows samples, the

VAL column in the corresponding row contains the number of samples in the data set. Similarly, when the _TYPE_ column shows S and the _NAME1_ column shows nVar, the _VAL_ column contains the number of variables. And when the _TYPE_ column show S and the _NAME1_ column shows nEff, the _VAL_ column in the corresponding row contains the number of effects.

- When the _TYPE_ column shows F, the row contains the frequency of a level of a CLASS variable. In this case, the _NAME1_ column contains the name of the CLASS variable and the _NAME2_ column contains the name of the corresponding level.
- When the _TYPE_ column shows M, the row contains the mean of an interval variable. In this case, the _NAME1_ column contains the name of the variable and the _NAME2_ column is empty.
- When the _TYPE_ column shows R, the row contains an entry in the correlation matrix. In this case, the _NAME1_ column contains the row ID, the _NAME2_ column contains the column ID, and the _VAL_ column contains the value.
- When the _TYPE_ column shows V or P, the corresponding row contains an entry of a COV matrix or an SSCP matrix, respectively.

Only entries in the lower triangle of the correlation matrix are written to the file, because the correlation matrix is symmetric. Also any entry of the matrix that has a value smaller than 0.01 is ignored in the output (EPS = 0.01), which saves storage space.

Example 21.5: Output an ODS Table as A Local Data File

The ODS output of PROC HPREDUCE can be stored in a local data file. The following example shows how the “Iteration History” table can be stored as a local file named IterHist by using the ODS output statement:

```
data one;
  array x{10};
  array c{10};
  do i=1 to 2000;
    do j=1 to 10;
       x{j}=ranuni(1);
       c{j}=int(ranuni(1)*4);
    end;

    if c{1} eq 0 Then b1 = 'aa';
    if c{1} eq 1 Then b1 = 'bb';
    if c{1} eq 2 then b1 = 'cc';
    if c{1} eq 3 then b1 = 'dd';
    if c{1} eq 4 then b1 = 'ee';

    if c{2} eq 0 Then b2 = 'ff';
    if c{2} eq 1 Then b2 = 'gg';
    if c{2} eq 2 then b2 = 'hh';
    if c{2} eq 3 then b2 = 'ii';
    if c{2} eq 4 then b2 = 'jj';

    if c{3} eq 0 Then b3 = 'kk';
```

```
    if c{3} eq 1 Then b3 = 'll';
    if c{3} eq 2 then b3 = 'mm';
    if c{3} eq 3 then b3 = 'nn';
    if c{3} eq 4 then b3 = 'oo';
    output;
  end;
run;

proc hpreduce data=one;
    ods output SelectionSummary=Summary;
    class b1-b3 c1-c3;
    reduce  unsupervised b1 b1*b2 b3 c1-c3 x1-x10 /maxsteps =5;
    performance details;
run;
```

References

Cooley, W. W. and Lohnes, P. R. (1971), *Multivariate Data Analysis*, New York: John Wiley & Sons.

Fisher, R. A. (1936), "The Use of Multiple Measurements in Taxonomic Problems," *Annals of Eugenics*, 7, 179–188.

Jolliffe, I. T. (2002), *Principal Component Analysis*, New York: Springer-Verlag.

Liu, H. and Motoda, H. (1998), *Feature Selection for Knowledge Discovery and Data Mining*, Norwell, MA: Kluwer Academic.

Chapter 22
The HPREG Procedure

Contents

Overview: HPREG Procedure **536**
PROC HPREG Features 536
PROC HPREG Contrasted with Other SAS Procedures 538
Getting Started: HPREG Procedure **538**
Syntax: HPREG Procedure **544**
PROC HPREG Statement 545
BY Statement 546
CODE Statement 547
CLASS Statement 547
FREQ Statement 548
ID Statement 548
MODEL Statement 548
PARTITION Statement 550
PERFORMANCE Statement 550
SELECTION Statement 550
OUTPUT Statement 551
WEIGHT Statement 553
Details: HPREG Procedure **554**
Criteria Used in Model Selection 554
Diagnostic Statistics 555
Classification Variables and the SPLIT Option 556
Using Validation and Test Data 558
Using the Validation ASE as the STOP= Criterion 559
Using the Validation ASE as the CHOOSE= Criterion 559
Using the Validation ASE as the SELECT= Criterion 559
Computational Method 559
Multithreading 559
Output Data Set 560
Displayed Output 561
Performance Information 561
Model Information 561
Selection Information 561
Number of Observations 561
Class Level Information 561
Dimensions 562
Entry and Removal Candidates 562

Selection Summary 562
Stop Reason 562
Selection Reason 563
Selected Effects 563
ANOVA 563
Fit Statistics 563
Parameter Estimates 564
Timing Information 564
ODS Table Names 565
Examples: HPREG Procedure **566**
Example 22.1: Model Selection with Validation 566
Example 22.2: Backward Selection in SMP and MPP Modes 572
Example 22.3: Forward-Swap Selection 576
References **579**

Overview: HPREG Procedure

The HPREG procedure is a high-performance procedure that fits and performs model selection for ordinary linear least squares models. The models supported are standard independently and identically distributed general linear models, which can contain main effects that consist of both continuous and classification variables and interaction effects of these variables. The procedure offers extensive capabilities for customizing the model selection with a wide variety of selection and stopping criteria, from traditional and computationally efficient significance-level-based criteria to more computationally intensive validation-based criteria. PROC HPREG also provides a variety of regression diagnostics that are conditional on the selected model.

With the HPREG procedure you can read and write data in distributed form and perform analyses in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details.

PROC HPREG Features

The main features of the HPREG procedure are as follows:

- **High-performance features**
  - can perform analysis on a massively parallel SAS high-performance appliance
  - reads input data in parallel and writes output data in parallel when the data source is the appliance database
  - is highly multithreaded during all phases of analytic execution

- **Model specification**
  - supports GLM and reference parameterization for classification effects
  - supports any degree of interaction (crossed effects) and nested effects
  - supports hierarchy among effects
  - supports partitioning of data into training, validation, and testing roles
  - supports a FREQ statement for grouped analysis
  - supports a WEIGHT statement for weighted analysis
- **Selection control**
  - provides multiple effect-selection methods
  - enables selection from a very large number of effects (tens of thousands)
  - offers selection of individual levels of classification effects
  - provides effect selection based on a variety of selection criteria
  - provides stopping rules based on a variety of model evaluation criteria
  - supports stopping and selection rules based on external validation and leave-one-out cross validation
- **Display and output**
  - produces output data sets that contain predicted values, residuals, studentized residuals, confidence limits, and influence statistics

The HPREG procedure supports the following effect selection methods. For a more detailed description of these methods, see the section "Methods" on page 52 in Chapter 3, "Shared Concepts and Topics."

FORWARD	The forward selection method starts with no effects in the model and adds effects.
BACKWARD	The backward elimination method starts with all effects in the model and deletes effects.
STEPWISE	The stepwise regression method is similar to the FORWARD method except that effects already in the model do not necessarily stay there.
FORWARDSWAP	The forward swap selection method is a modification of forward selection where before any addition step, all pairwise swaps of effects in and out of the current model that improve the selection criterion are made. When the selection criterion is R square, this method coincides with the MAXR method in the REG procedure in SAS/STAT software.
LAR	The least angle regression method, like forward selection, starts with no effects in the model and adds effects. The parameter estimates at any step are "shrunk" when compared to the corresponding least squares estimates.
LASSO	The lasso method adds and deletes parameters based on a version of ordinary least squares in which the sum of the absolute regression coefficients is constrained. PROC HPREG also supports adaptive lasso selection where weights are applied to each of the parameters in forming the lasso constraint.

Hybrid versions of LAR and LASSO methods are also supported. They use LAR or LASSO to select the model, but then estimate the regression coefficients by ordinary weighted least squares.

PROC HPREG Contrasted with Other SAS Procedures

For general contrasts between SAS High-Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16 in Chapter 3, "Shared Concepts and Topics." The following remarks contrast the HPREG procedure with the GLMSELECT, GLM, and REG procedures in SAS/STAT software.

A major functional difference between the HPREG and REG procedures is that the HPREG procedure enables you to specify general linear models that include classification variables. In this respect it is similar to the GLM and GLMSELECT procedures. In terms of the supported model selection methods, the HPREG procedure most resembles the GLMSELECT procedure. Like the GLMSELECT procedure but different from the REG procedure, the HPREG procedure supports the LAR and LASSO methods, the ability to use external validation data and cross validation as selection criteria, and extensive options to customize the selection process. The HPREG procedure does not support the MAXR and MINR methods that are available in the REG procedure. Nor does the HPREG procedure include any support for the all-subset-based methods that you can find in the REG procedure.

The CLASS statement in the HPREG procedure permits two parameterizations: the GLM-type parameterization and a reference parameterization. In contrast to the GLMSELECT, GENMOD, LOGISTIC, and other procedures that permit multiple parameterizations, the HPREG procedure does not mix parameterizations across the variables in the CLASS statement. In other words, all classification variables are in the same parameterization, and this parameterization is either the GLM or reference parameterization.

Like the REG procedure but different from the GLMSELECT procedure, the HPREG procedure does not perform model selection by default. If you request model selection by using the SELECTION statement then the default selection method is stepwise selection based on the SBC criterion. This default matches the default method used in PROC GLMSELECT.

As with the REG procedure but not supported with the GLMSELECT procedure, you can request observation-wise residual and influence diagnostics in the OUTPUT statement and variance inflation and tolerance statistics for the parameter estimates. If the fitted model has been obtained by performing model selection, then these statistics are conditional on the selected model and do not take the variability introduced by the selection process into account.

Getting Started: HPREG Procedure

The following example is closely modeled on the example in the section "Getting Started: GLMSELECT Procedure" in the *SAS/STAT User's Guide*. The data set contains salary and performance information for Major League Baseball players (excluding pitchers) who played at least one game in both the 1986 and 1987 seasons. The salaries are for the 1987 season (*Sports Illustrated,* April 20, 1987) and the performance measures are from 1986 (Collier Books, *The 1987 Baseball Encyclopedia Update*).

```
data baseball;
  length name $ 18;
  length team $ 12;
  input name $ 1-18 nAtBat nHits nHome nRuns nRBI nBB
        yrMajor crAtBat crHits crHome crRuns crRbi crBB
        league $ division $ team $ position $ nOuts nAssts
        nError salary;
  label name="Player's Name"
     nAtBat="Times at Bat in 1986"
     nHits="Hits in 1986"
     nHome="Home Runs in 1986"
     nRuns="Runs in 1986"
     nRBI="RBIs in 1986"
     nBB="Walks in 1986"
     yrMajor="Years in the Major Leagues"
     crAtBat="Career times at bat"
     crHits="Career Hits"
     crHome="Career Home Runs"
     crRuns="Career Runs"
     crRbi="Career RBIs"
     crBB="Career Walks"
     league="League at the end of 1986"
     division="Division at the end of 1986"
     team="Team at the end of 1986"
     position="Position(s) in 1986"
     nOuts="Put Outs in 1986"
     nAssts="Assists in 1986"
     nError="Errors in 1986"
     salary="1987 Salary in $ Thousands";
     logSalary = log(Salary);
  datalines;
Allanson, Andy       293    66     1    30    29    14
                       1   293    66     1    30    29    14
                    American East Cleveland C 446 33 20 .
Ashby, Alan          315    81     7    24    38    39
                      14  3449   835    69   321   414   375
                    National West Houston C 632 43 10 475
Davis, Alan          479   130    18    66    72    76

   ... more lines ...

Wilson, Willie       631   170     9    77    44    31
                      11  4908  1457    30   775   357   249
                    American West KansasCity CF 408 4 3 1000
;
```

Suppose you want to investigate whether you can model the players' salaries for the 1987 season based on performance measures for the previous season. The aim is to obtain a parsimonious model that does not overfit this particular data, making it useful for prediction. This example shows how you can use PROC HPREG as a starting point for such an analysis. Since the variation of salaries is much greater for the higher salaries, it is appropriate to apply a log transformation to the salaries before doing the model selection.

The following statements select a model with the default settings for stepwise selection:

```
proc hpreg data=baseball;
  class league division;
  model logSalary = nAtBat nHits nHome nRuns nRBI nBB
                    yrMajor crAtBat crHits crHome crRuns crRbi
                    crBB league division nOuts nAssts nError;
  selection method=stepwise;
run;
```

The default output from this analysis is presented in Figure 22.1 through Figure 22.5.

Figure 22.1 Performance, Model, and Selection Information

```
                        The HPREG Procedure

                     Performance Information

                 Execution Mode       On client
                 Number of Threads    4


                       Model Information

              Data Source                WORK.BASEBALL
              Dependent Variable         logSalary
              Class Parameterization     GLM


                     Selection Information

               Selection Method              Stepwise
               Select Criterion              SBC
               Stop Criterion                SBC
               Effect Hierarchy Enforced     None
               Stop Horizon                  3
```

Figure 22.1 displays the "Performance Information," "Model Information," and "Selection Information" tables. The "Performance Information" table shows that procedure executes in client mode—that is, the model is fit on the machine where the SAS session executes. This run of the HPREG procedure was performed on a multicore machine with four CPUs; one computational thread was spawned per CPU.

The "Model Information" table identifies the data source and response and shows that the CLASS variables are parameterized in the GLM parameterization, which is the default.

The "Selection Information" provides details about the method and criteria used to perform the model selection. The requested selection method is a variant of the traditional stepwise selection where the decisions about what effects to add or drop at any step and when to terminate the selection are both based on the Schwarz Bayesian information criterion (SBC). The effect in the current model whose removal yields the maximal decrease in the SBC statistic is dropped provided this lowers the SBC value. When no further decrease in the SBC value can be obtained by dropping an effect in the model, the effect whose addition to the model yields the lowest SBC statistic is added and the whole process is repeated. The method terminates when dropping or adding any effect increases the SBC statistic.

Figure 22.2 displays the "Number of Observations," "Class Levels," and "Dimensions" tables. The "Number of Observations" table shows that of the 322 observations in the input data, only 263 observations are used in the analysis because there are observations with incomplete data. The "Class Level Information" table lists the levels of the classification variables "division" and "league." When you specify effects that contain classification variables, the number of parameters is usually larger than the number of effects. The "Dimensions" table shows the number of effects and the number of parameters considered.

Figure 22.2 Number of Observations, Class Levels, and Dimensions

```
Number of Observations Read            322
Number of Observations Used            263


          Class Level Information

  Class       Levels    Values

  league           2    American National
  division         2    East West


                Dimensions

      Number of Effects             19
      Number of Parameters          21
```

The "Stepwise Selection Summary" table in Figure 22.3 shows the effect that was added or dropped at each step of the selection process together with fit statistics for the model at each step. In this case, both selection and stopping are based on the SBC statistic.

Figure 22.3 Selection Summary Table

```
                    The HPREG Procedure

                    Selection Summary

            Effect     Effect       Number
      Step  Entered    Removed   Effects In          SBC

         0  Intercept                    1     -57.2041
-------------------------------------------------------------
         1  crRuns                       2    -194.3166
         2  nHits                        3    -252.5794
         3  yrMajor                      4    -262.7322
         4             crRuns            3    -262.8353
         5  nBB                          4    -269.7804*

              * Optimal Value of Criterion
```

Figure 22.4 displays the "Stop Reason," "Selection Reason," and "Selected Effects" tables. Note that these tables are displayed without any titles. The "Stop Reason" table indicates that selection stopped because

adding or removing any effect would worsen the SBC value that is used as the selection criterion. In this case, because no CHOOSE= criterion is specified in the SELECTION statement, the final model is the selected model; this is indicated in the "Selection Reason" table. The "Selected Effects" table lists the effects in the selected model.

Figure 22.4 Stopping and Selection Reasons

```
Stepwise selection stopped because adding or removing an effect does not improve
the SBC criterion.

                    The model at step 5 is selected.

              Selected Effects: Intercept nHits nBB yrMajor
```

The "Analysis of Variance," "Fit Statistics," and "Parameter Estimates" tables shown in Figure 22.5 give details of the selected model.

Figure 22.5 Details of the Selected Model

Analysis of Variance

Source	DF	Sum of Squares	Mean Square	F Value	Pr > F
Model	3	120.52553	40.17518	120.12	<.0001
Error	259	86.62820	0.33447		
Corrected Total	262	207.15373			

Root MSE	0.57834
R-Square	0.58182
Adj R-Sq	0.57697
AIC	-19.06903
AICC	-18.83557
SBC	-269.78041
ASE	0.32938

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	4.013911	0.111290	36.07	<.0001
nHits	1	0.007929	0.000994	7.98	<.0001
nBB	1	0.007280	0.002049	3.55	0.0005
yrMajor	1	0.100663	0.007551	13.33	<.0001

You might want to examine regression diagnostics for the selected model to investigate whether collinearity among the selected parameters or the presence of outlying or high leverage observations might be impacting the fit produced. The following statements include some options and statements to obtain these diagnostics:

```
proc hpreg data=baseball;
  id name;
  class league division;
  model logSalary = nAtBat nHits nHome nRuns nRBI nBB
                    yrMajor crAtBat crHits crHome crRuns crRbi
                    crBB league division nOuts nAssts nError / vif clb;
  selection method=stepwise;
  output out=baseballOut p=predictedLogSalary r h cookd rstudent;
run;
```

The VIF and CLB options in the MODEL statement request variance inflation factors and 95% confidence limits for the parameter estimates. Figure 22.6 shows the "Parameter Estimates" with these requested statistics. The variance inflation factors (VIF) measure the inflation in the variances of the parameter estimates due to collinearities that exist among the regressor (independent) variables. Although there are no formal criteria for deciding whether a VIF is large enough to affect the predicted values, the VIF values for the selected effects in this example are small enough to indicate that there are no collinearity issues among the selected regressors.

Figure 22.6 Parameter Estimates with Additional Statistics

The HPREG Procedure
Selected Model

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Pr > |t|	Variance Inflation
Intercept	1	4.013911	0.111290	36.07	<.0001	0
nHits	1	0.007929	0.000994	7.98	<.0001	1.49642
nBB	1	0.007280	0.002049	3.55	0.0005	1.52109
yrMajor	1	0.100663	0.007551	13.33	<.0001	1.02488

Parameter Estimates

Parameter	95% Confidence Limits	
Intercept	3.79476	4.23306
nHits	0.00597	0.00989
nBB	0.00325	0.01131
yrMajor	0.08579	0.11553

By default, High-Performance Analytics procedures do not include all variables from the input data set in output data sets. The ID statement specifies that the variable name in the input data set be added as an identification variable in the baseballOut data set that is produced by the OUTPUT statement. In addition to this variable, the OUTPUT statement requests that predicted values, raw residuals, leverage values, Cook's D statistics, and studentized residuals be added in the output data set. Note that default names are used for these statistics except for the predicted values for which a specified name, predictedLogSalary, is supplied. The following statements use PROC PRINT to display the first five observations of this output data set:

```
proc print data=baseballOut(obs=5);
run;
```

Figure 22.7 First 5 Observations of the baseballOut Data Set

Obs	name	predicted LogSalary	Residual	H	COOKD	RSTUDENT
1	Allanson, Andy	4.73980	.	0.016087	.	.
2	Ashby, Alan	6.34935	−0.18603	0.012645	.000335535	−0.32316
3	Davis, Alan	5.89993	0.27385	0.019909	.001161794	0.47759
4	Dawson, Andre	6.50852	−0.29392	0.011060	.000730178	−0.51031
5	Galarraga, Andres	5.12344	−0.60711	0.009684	.002720358	−1.05510

Syntax: HPREG Procedure

The following statements are available in the HPREG procedure:

PROC HPREG < *options* > ;
  BY *variables* ;
  CODE < *options* > ;
  CLASS *variables* ;
  MODEL *dependent* **=** < *effects* > < / *model-options* > ;
  OUTPUT < **OUT=***SAS-data-set* >
    < *keyword* < **=***name* > >. . .
    < *keyword* < **=***name* > > < / *options* > ;
  PARTITION < *partition-options* > ;
  PERFORMANCE *performance-options* ;
  SELECTION *selection-options* ;
  FREQ *variable* ;
  ID *variables* ;
  WEIGHT *variable* ;

The PROC HPREG statement and a single MODEL statement are required. All other statements are optional. The CLASS statement can appear multiple times. If a CLASS statement is specified, it must precede the MODEL statement.

PROC HPREG Statement

PROC HPREG < *options* > **;**

The PROC HPREG statement invokes the procedure. Table 22.1 summarizes the options in the PROC HPREG statement by function.

Table 22.1 PROC HPREG Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
NAMELEN=	Limits the length of effect names
Options Related to Output	
NOPRINT	Suppresses ODS output
NOCLPRINT	Limits or suppresses the display of class levels
User-Defined Formats	
FMTLIBXML=	Specifies a file reference for a format stream
Other Options	
ALPHA=	Sets the significance level used for the construction of confidence intervals
SEED=	Sets the seed used for pseudorandom number generation

Following are explanations of the *options* that you can specify in the PROC HPREG statement (in alphabetical order):

ALPHA=*number*

sets the significance level used for the construction of confidence intervals. The value must be between 0 and 1; the default value of 0.05 results in 95% intervals. This option affects the OUTPUT statement keywords LCL, LCLM, UCL, and UCLM, and the CLB option in the MODEL statement.

DATA=*SAS-data-set*

names the input SAS data set to be used by PROC HPREG. The default is the most recently created data set.

If the procedure executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. In that case the procedure reads the data alongside the distributed database. See the section "SMP and MPP Modes" on page 16 about the various execution modes and the section "Alongside-the-Database Execution" on page 22 about the alongside-the-database model. Both sections are in Chapter 3, "Shared Concepts and Topics."

FMTLIBXML=*file-ref*

specifies the file reference for the XML stream that contains the user-defined format definitions. User-defined formats are handled differently in a distributed computing environment than they are in other

SAS products. See the section "Working with Formats" on page 27 in Chapter 3, "Shared Concepts and Topics," for details about how to generate a XML stream for your formats.

NAMELEN=*number*
specifies the length to which long effect names are shortened. The default and minimum value is 20.

NOCLPRINT<=*number***>**
suppresses the display of the "Class Level Information" table if you do not specify *number*. If you specify *number*, the values of the classification variables are displayed for only those variables whose number of levels is less than *number*. Specifying a *number* helps to reduce the size of the "Class Level Information" table if some classification variables have a large number of levels.

NOPRINT
suppresses the generation of ODS output.

SEED=*number*
specifies an integer used to start the pseudorandom number generator for random partitioning of data for training, testing, and validation. If you do not specify a seed, or if you specify a value less than or equal to 0, the seed is generated from reading the time of day from the computer's clock.

BY Statement

BY *variables* **;**

You can specify a BY statement with PROC HPREG to obtain separate analyses of observations in groups that are defined by the BY variables. When a BY statement appears, the procedure expects the input data set to be sorted in order of the BY variables. If you specify more than one BY statement, only the last one specified is used.

If your input data set is not sorted in ascending order, use one of the following alternatives:

- Sort the data by using the SORT procedure with a similar BY statement.
- Specify the NOTSORTED or DESCENDING option in the BY statement for the HPREG procedure. The NOTSORTED option does not mean that the data are unsorted but rather that the data are arranged in groups (according to values of the BY variables) and that these groups are not necessarily in alphabetical or increasing numeric order.
- Create an index on the BY variables by using the DATASETS procedure (in Base SAS software).

BY statement processing is not supported when the HPREG procedure runs alongside the database or alongside the Hadoop Distributed File System (HDFS). These modes are used if the input data are stored in a database or HDFS and the grid host is the appliance that houses the data.

For more information about BY-group processing, see the discussion in *SAS Language Reference: Concepts*. For more information about the DATASETS procedure, see the discussion in the *Base SAS Procedures Guide*.

CODE Statement

CODE < *options* > **;**

The CODE statement enables you to write SAS DATA step code for computing predicted values of the fitted model either to a file or to a catalog entry. This code can then be included in a DATA step to score new data.

Table 22.2 summarizes the *options* available in the CODE statement.

Table 22.2 CODE Statement Options

Option	Description
CATALOG=	Names the catalog entry where the generated code is saved
DUMMIES	Retains the dummy variables in the data set
ERROR	Computes the error function
FILE=	Names the file where the generated code is saved
FORMAT=	Specifies the numeric format for the regression coefficients
GROUP=	Specifies the group identifier for array names and statement labels
IMPUTE	Imputes predicted values for observations with missing or invalid covariates
LINESIZE=	Specifies the line size of the generated code
LOOKUP=	Specifies the algorithm for looking up CLASS levels
RESIDUAL	Computes residuals

For details about the syntax of the CODE statement, see the section "CODE Statement" (Chapter 19, *SAS/STAT User's Guide*) in Chapter 19, "Shared Concepts and Topics" (*SAS/STAT User's Guide*).

CLASS Statement

CLASS *variable* < *(options)* >. . . < *variable* < *(options)* > > < / *global-options* > **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. The CLASS statement must precede the MODEL statement.

The CLASS statement for SAS High-Performance Analytics procedures is documented in the section "CLASS Statement" on page 28 of Chapter 3, "Shared Concepts and Topics." The HPREG procedure also supports the following *global-option* in the CLASS statement:

UPCASE

uppercases the values of character-valued CLASS variables before levelizing them. For example, if the UPCASE option is in effect and a CLASS variable can take the values 'a', 'A', and 'b', then 'a' and 'A' represent the same level and the CLASS variable is treated as having only two values: 'A' and 'B'.

FREQ Statement

FREQ *variable* **;**

The *variable* in the FREQ statement identifies a numeric variable in the data set that contains the frequency of occurrence for each observation. SAS High-Performance Analytics procedures that support the FREQ statement treat each observation as if it appeared f times, where f is the value of the FREQ variable for the observation. If the frequency value is not an integer, it is truncated to an integer. If the frequency value is less than 1 or missing, the observation is not used in the analysis. When the FREQ statement is not specified, each observation is assigned a frequency of 1.

ID Statement

ID *variables* **;**

The ID statement lists one or more variables from the input data set that are transferred to output data sets created by SAS High-Performance Analytics procedures, provided that the output data set produces one (or more) records per input observation.

For documentation on the common ID statement in SAS High-Performance Analytics procedures, see the section "ID Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

MODEL Statement

MODEL *dependent*=< *effects* > / < *options* > **;**

The MODEL statement names the dependent variable and the explanatory effects, including covariates, main effects, interactions, and nested effects. If you omit the explanatory effects, the procedure fits an intercept-only model.

After the keyword MODEL, the dependent (response) variable is specified, followed by an equal sign. The explanatory effects follow the equal sign. For information about constructing the model effects, see the section "Specification and Parameterization of Model Effects" on page 44, of Chapter 3, "Shared Concepts and Topics."

You can specify the following *options* in the MODEL statement after a slash (/):

CLB

requests the $100(1-\alpha)\%$ upper and lower confidence limits for the parameter estimates. By default, the 95% limits are computed; the ALPHA= option in the PROC HPREG statement can be used to change the α level. The CLB option is not supported when you request METHOD=LAR or METHOD=LASSO in the SELECTION statement.

INCLUDE=*n*

INCLUDE=*single-effect*

INCLUDE=(*effects***)**

forces effects to be included in all models. If you specify INCLUDE=*n*, then the first *n* effects listed in the MODEL statement are included in all models. If you specify INCLUDE=*single-effect* or if you specify a list of effects within parentheses, then the specified effects are forced into all models. The effects that you specify in the INCLUDE= option must be explanatory effects defined in the MODELstatement before the slash (/). The INCLUDE= option is not available when you specify METHOD=LAR or METHOD=LASSO in the SELECTION statement.

NOINT

suppresses the intercept term that is otherwise included in the model.

ORDERSELECT

specifies that, for the selected model, effects be displayed in the order in which they first entered the model. If you do not specify the ORDERSELECT option, then effects in the selected model are displayed in the order in which they appear in the MODEL statement.

START=*n*

START=*single-effect*

START=(*effects***)**

is used to begin the selection process in the FORWARD, FORWARDSWAP, and STEPWISE selection methods from the initial model that you designate. If you specify START=*n*, then the starting model consists of the first *n* effects listed in the MODEL statement. If you specify START=*single-effect* or if you specify a list of effects within parentheses, then the starting model consists of these specified effects. The effects that you specify in the START= option must be explanatory effects defined in the MODELstatement before the slash (/). The START= option is not available when you specify METHOD=BACKWARD, METHOD=LAR, or METHOD=LASSO in the SELECTION statement.

STB

produces standardized regression coefficients. A standardized regression coefficient is computed by dividing a parameter estimate by the ratio of the sample standard deviation of the dependent variable to the sample standard deviation of the regressor.

TOL

produces tolerance values for the estimates. Tolerance for a parameter is defined as $1 - R^2$, where R^2 is obtained from the regression of the parameter on all other parameters in the model. The TOL option is not supported when you request METHOD=LAR or METHOD=LASSO in the SELECTION statement.

VIF

produces variance inflation factors with the parameter estimates. Variance inflation is the reciprocal of tolerance. The VIF option is not supported when you request METHOD=LAR or METHOD=LASSO in the SELECTION statement.

PARTITION Statement

PARTITION < *partition-options* > **;**

The PARTITION statement specifies how observations in the input data set are logically partitioned into disjoint subsets for model training, validation, and testing. Either you can designate a variable in the input data set and a set of formatted values of that variable to determine the role of each observation, or you can specify proportions to use for random assignment of observations for each role.

The following mutually exclusive *partition-options* are available:

ROLEVAR | ROLE=*variable***(< TEST='***value***' > < TRAIN='***value***' > < VALIDATE='***value***' >)**
names the variable in the input data set whose values are used to assign roles to each observation. The formatted values of this variable that are used to assign observations roles are specified in the TEST=, TRAIN=, and VALIDATE= suboptions. If you do not specify the TRAIN= suboption, then all observations whose role is not determined by the TEST= or VALIDATE= suboptions are assigned to training.

FRACTION(< TEST=*fraction* **> < VALIDATE=***fraction* **>)**
requests that specified proportions of the observations in the input data set be randomly assigned training and validation roles. You specify the proportions for testing and validation by using the TEST= and VALIDATE= suboptions. If you specify both the TEST= and the VALIDATE= suboptions, then the sum of the specified fractions must be less than 1 and the remaining fraction of the observations are assigned to the training role.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement you can also control whether a SAS High-Performance Analytics procedure executes in SMP or MPP mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SELECTION Statement

SELECTION < *options* > **;**

The SELECTION statement performs variable selection. The statement is fully documented in the section "SELECTION Statement" on page 32 in Chapter 3, "Shared Concepts and Topics."

The HPREG procedure supports the following variable selection methods in the METHOD= option in the SELECTION statement:

NONE — No model selection.

FORWARD — The forward selection method starts with no effects in the model and adds effects.

BACKWARD — The backward elimination method starts with all effects in the model and deletes effects.

STEPWISE — The stepwise regression method is similar to the FORWARD method except that effects already in the model do not necessarily stay there.

FORWARDSWAP — The forward-swap selection method is an extension of the forward selection method. Before any addition step, PROC HPREG makes all pairwise swaps of effects in and out of the current model that improve the selection criterion. When the selection criterion is R square, this method is the same as the MAXR method in the REG procedure in SAS/STAT software.

LAR — The least angle regression method, like forward selection, starts with no effects in the model and adds effects. The parameter estimates at any step are "shrunk" when compared to the corresponding least squares estimates. If the model contains classification variables, then these classification variables are split. See the SPLIT option in the CLASS statement for details.

LASSO — The lasso method adds and deletes parameters based on a version of ordinary least squares where the sum of the absolute regression coefficients is constrained. If the model contains classification variables, then these classification variables are split. See the SPLIT option in the CLASS statement for details.

The DETAILS=ALL and DETAILS=STEPS options produce the "ANOVA," "Fit Statistics," and "Parameter Estimates" tables, which provide information about the model that is selected at each step of the selection process.

OUTPUT Statement

OUTPUT < **OUT=***SAS-data-set* >
< *keyword* < *=name* > >. . . < *keyword* < *=name* > > **;**

The OUTPUT statement creates a data set that contains observationwise statistics, which are computed after fitting the model. The variables in the input data set are *not* included in the output data set to avoid data duplication for large data sets.

If the input data are in distributed form, where access of data in a particular order cannot be guaranteed, the HPREG procedure copies the distribution or partition key to the output data set so that its contents can be joined with the input data.

The output statistics are computed based on the parameter estimates for the selected model.

You can specify the following syntax elements in the OUTPUT statement:

OUT=*SAS-data-set*

DATA=*SAS-data-set*

specifies the name of the output data set. If the OUT= (or DATA=) option is omitted, the procedure uses the DATA*n* convention to name the output data set.

keyword **<** **=***name* **>**

specifies the statistics to include in the output data set and optionally names the new variables that contain the statistics. Specify a keyword for each desired statistic (see the following list of keywords), followed optionally by an equal sign and a variable to contain the statistic.

If you specify *keyword=name*, the new variable that contains the requested statistic has the specified name. If you omit the optional *=name* after a *keyword*, then a default name is used.

The following are valid values for *keyword* to request statistics that are available with all selection methods:

PREDICTED

PRED

P

requests predicted values for the response variable. The default name is `pred`.

RESIDUAL

RESID

R

requests the residual, calculated as ACTUAL–PREDICTED. The default name is `residual`.

ROLE

requests a numeric variable that indicates the role played by each observation in fitting the model. The default name is `role`. For each observation the interpretation of this variable is shown in Table 22.3:

Table 22.3 Role Interpretation

Value	Observation Role
0	Not used
1	Training
2	Validation
3	Testing

If you do not partition the input data by using a PARTITION statement, then the role variable value is 1 for observations used in fitting the model, and 0 for observations that have at least one missing or invalid value for the response, regressors, frequency or weight variables.

In addition to the preceding statistics, you can also use the *keywords* listed in Table 22.4 in the OUTPUT statement to obtain additional statistics. These statistics are not available if you use METHOD=LAR or METHOD=LASSO in the SELECTION statement, unless you also specify the LSCOEFFS option. See the section "Diagnostic Statistics" on page 555 for computational formulas. All the statistics available in the OUTPUT statement are conditional on the selected model and do not take into account the variability introduced by doing model selection.

Table 22.4 Keywords for OUTPUT Statement

Keyword	Description
COOKD	Cook's D influence statistic
COVRATIO	Standard influence of observation on covariance of betas
DFFIT	Standard influence of observation on predicted value
H	Leverage, $x_i(\mathbf{X}'\mathbf{X})^{-1}x_i'$
LCL	Lower bound of a $100(1-\alpha)\%$ confidence interval for an individual prediction. This includes the variance of the error, as well as the variance of the parameter estimates.
LCLM	Lower bound of a $100(1-\alpha)\%$ confidence interval for the expected value (mean) of the dependent variable
PRESS	ith residual divided by $(1-h)$, where h is the leverage, and where the model has been refit without the ith observation
RSTUDENT	A studentized residual with the current observation deleted
STDI	Standard error of the individual predicted value
STDP	Standard error of the mean predicted value
STDR	Standard error of the residual
STUDENT	Studentized residuals, which are the residuals divided by their standard errors
UCL	Upper bound of a $100(1-\alpha)\%$ confidence interval for an individual prediction
UCLM	Upper bound of a $100(1-\alpha)\%$ confidence interval for the expected value (mean) of the dependent variable

WEIGHT Statement

WEIGHT *variable* **;**

The *variable* in the WEIGHT statement is used as a weight to perform a weighted analysis of the data. Observations with nonpositive or missing weights are not included in the analysis. If a WEIGHT statement is not included, all observations used in the analysis are assigned a weight of 1.

Details: HPREG Procedure

Criteria Used in Model Selection

The HPREG procedure supports a variety of fit statistics that you can specify as criteria for the CHOOSE=, SELECT=, and STOP= options in the SELECTION statement. The following statistics are available:

ADJRSQ	Adjusted R-square statistic (Darlington 1968; Judge et al. 1985)
AIC	Akaike's information criterion (Akaike 1969; Judge et al. 1985)
AICC	Corrected Akaike's information criterion (Hurvich and Tsai 1989)
BIC | SBC	Schwarz Bayesian information criterion (Schwarz 1978; Judge et al. 1985)
CP	Mallows C_p statistic (Mallows 1973; Hocking 1976)
PRESS	Predicted residual sum of squares statistic
RSQUARE	R-square statistic (Darlington 1968; Judge et al. 1985)
SL	Significance used to assess an effect's contribution to the fit when it is added to or removed from a model
VALIDATE	Average square error over the validation data

When you use SL as a criterion for effect selection, the definition depends on whether an effect is being considered as a drop or an add candidate. If the current model has p parameters excluding the intercept, and if you denote its residual sum of squares by RSS_p and you add an effect with k degrees of freedom and denote the residual sum of squares of the resulting model by RSS_{p+k}, then the F statistic for entry with k numerator degrees of freedom and $n-(p+k)-1$ denominator degrees of freedom is given by

$$F = \frac{(\mathrm{RSS}_p - \mathrm{RSS}_{p+k})/k}{\mathrm{RSS}_{p+k}/(n-(p+k)-1)}$$

where n is number of observations used in the analysis. The significance level for entry is the p-value of this F statistic, and is deemed significant if it is smaller than the SLENTRY limit. Among several such add candidates, the effect with the smallest p-value (most significant) is deemed best.

If you drop an effect with k degrees of freedom and denote the residual sum of squares of the resulting model by RSS_{p-k}, then the F statistic for removal with k numerator degrees of freedom and $n-p-k$ denominator degrees of freedom is given by

$$F = \frac{(\mathrm{RSS}_{p-k} - \mathrm{RSS}_p)/k}{\mathrm{RSS}_p/(n-p-k)}$$

where n is number of observations used in the analysis. The significance level for removal is the p-value of this F statistic, and the effect is deemed not significant if this p-value is larger than the SLSTAY limit. Among several such removal candidates, the effect with the largest p-value (least significant) is deemed the best removal candidate.

It is known that the "F-to-enter" and "F-to-delete" statistics do not follow an F distribution (Draper, Guttman, and Kanemasu 1971).. Hence the SLENTRY and SLSTAY values cannot reliably be viewed

as probabilities. One way to address this difficulty is to replace hypothesis testing as a means of selecting a model with information criteria or out-of-sample prediction criteria. While Harrell (2001) points out that information criteria were developed for comparing only prespecified models, Burnham and Anderson (2002) note that AIC criteria have routinely been used for several decades for performing model selection in time series analysis.

Table 22.5 provides formulas and definitions for these fit statistics.

Table 22.5 Formulas and Definitions for Model Fit Summary Statistics

Statistic	Definition or Formula
n	Number of observations
p	Number of parameters including the intercept
$\hat{\sigma}^2$	Estimate of pure error variance from fitting the full model
SST	Total sum of squares corrected for the mean for the dependent variable
SSE	Error sum of squares
ASE	$\frac{\text{SSE}}{n}$
MSE	$\frac{\text{SSE}}{n-p}$
R^2	$1-\frac{\text{SSE}}{\text{SST}}$
ADJRSQ	$1-\frac{(n-1)(1-R^2)}{n-p}$
AIC	$n\ln\left(\frac{\text{SSE}}{n}\right)+2p$
AICC	$1+\ln\left(\frac{\text{SSE}}{n}\right)+\frac{2(p+1)}{n-p-2}$
CP (C_p)	$\frac{\text{SSE}}{\hat{\sigma}^2}+2p-n$
PRESS	$\sum_{i=1}^{n}\frac{r_i^2}{(1-h_i)^2}$ where $r_i =$ residual at observation i and $h_i =$ leverage of observation $i = \mathbf{x}_i(\mathbf{X}'\mathbf{X})^{-}\mathbf{x}_i'$
RMSE	$\sqrt{\text{MSE}}$
SBC	$n\ln\left(\frac{\text{SSE}}{n}\right)+p\ln(n)$

Diagnostic Statistics

This section gathers the formulas for the statistics available in the OUTPUT statement. All the statistics available in the OUTPUT statement are conditional on the selected model and do not take into account the variability introduced by doing model selection.

The model to be fit is $\mathbf{Y} = \mathbf{X}\boldsymbol{\beta} + \boldsymbol{\epsilon}$, and the parameter estimate is denoted by $\mathbf{b} = (\mathbf{X}'\mathbf{X})^{-}\mathbf{X}'\mathbf{Y}$. The subscript i denotes values for the ith observation, and the parenthetical subscript (i) means that the statistic is computed by using all observations except the ith observation.

The ALPHA= option in the PROC HPREG statement is used to set the α value for the confidence limit statistics.

Table 22.6 contains the diagnostic statistics and their formulas. Each statistic is computed for each observation.

Table 22.6 Formulas and Definitions for Diagnostic Statistics

MODEL Option or Statistic	**Formula**
PRED ($\widehat{\mathbf{Y}}_i$)	$\mathbf{X}_i\mathbf{b}$
RES (r_i)	$\mathbf{Y}_i - \widehat{\mathbf{Y}}_i$
H (h_i)	$\mathbf{x}_i(\mathbf{X}'\mathbf{X})^{-}\mathbf{x}_i'$
STDP	$\sqrt{h_i\widehat{\sigma}^2}$
STDI	$\sqrt{(1+h_i)\widehat{\sigma}^2}$
STDR	$\sqrt{(1-h_i)\widehat{\sigma}^2}$
LCL	$\widehat{Y}_i - t_{\frac{\alpha}{2}}\text{STDI}$
LCLM	$\widehat{Y}_i - t_{\frac{\alpha}{2}}\text{STDP}$
UCL	$\widehat{Y}_i + t_{\frac{\alpha}{2}}\text{STDI}$
UCLM	$\widehat{Y}_i + t_{\frac{\alpha}{2}}\text{STDP}$
STUDENT	$\dfrac{r_i}{\text{STDR}_i}$
RSTUDENT	$\dfrac{r_i}{\hat{\sigma}_{(i)}\sqrt{1-h_i}}$
COOKD	$\dfrac{1}{p}\text{STUDENT}^2\dfrac{\text{STDP}^2}{\text{STDR}^2}$
COVRATIO	$\dfrac{\det(\hat{\sigma}^2_{(i)}(\mathbf{x}'_{(i)}\mathbf{x}_{(i)})^{-1}}{\det(\hat{\sigma}^2(\mathbf{X}'\mathbf{X})^{-1})}$
DFFITS	$\dfrac{(\widehat{\mathbf{Y}}_i - \widehat{\mathbf{Y}}_{(i)})}{(\hat{\sigma}_{(i)}\sqrt{h_i})}$
PRESS(predr$_i$)	$\dfrac{r_i}{1-h_i}$

Classification Variables and the SPLIT Option

PROC HPREG supports the ability to split classification variables when doing model selection. You use the SPLIT option in the CLASS statement to specify that the columns of the design matrix that correspond

to effects that contain a split classification variable can enter or leave a model independently of the other design columns of that effect. The following statements illustrate the use of SPLIT option:

```
data splitExample;
   length c2 $6;
   drop i;
   do i=1 to 1000;
     c1 = 1 + mod(i,6);
     if      i < 250 then c2 = 'low';
     else if i < 500 then c2 = 'medium';
     else                 c2 = 'high';
     x1 = ranuni(1);
     x2 = ranuni(1);
     y = x1+3*(c2 ='low')  + 10*(c1=3) +5*(c1=5) + rannor(1);
     output;
   end;
run;

proc hpreg data=splitExample;
   class c1(split) c2(order=data);
   model y = c1 c2 x1 x2/orderselect;
   selection method=forward;
run;
```

The "Class Levels" table shown in Figure 22.8 is produced by default whenever you specify a CLASS statement.

Figure 22.8 Class Levels

The HPREG Procedure

Class Level Information

Class	Levels	Values
c1	6 *	1 2 3 4 5 6
c2	3	low medium high

* Associated Parameters Split

The SPLIT option has been specified for the classification variable `c1`. This permits the parameters associated with the effect `c1` to enter or leave the model individually. The "Parameter Estimates" table in Figure 22.9 shows that for this example the parameters that correspond to only levels 3 and 5 of `c1` are in the selected model. Finally, note that the ORDERSELECT option in the MODEL statement specifies that the parameters be displayed in the order in which they first entered the model.

Figure 22.9 Parameter Estimates

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	−0.308111	0.075387	−4.09	<.0001
c1_3	1	10.161702	0.087601	116.00	<.0001
c1_5	1	5.018407	0.087587	57.30	<.0001
c2 low	1	3.139941	0.078495	40.00	<.0001
c2 medium	1	0.221539	0.078364	2.83	0.0048
c2 high	0	0	.	.	.
x1	1	1.317420	0.109510	12.03	<.0001

Using Validation and Test Data

When you have sufficient data, you can subdivide your data into three parts called the training, validation, and test data. During the selection process, models are fit on the training data, and the prediction error for the models so obtained is found by using the validation data. This prediction error on the validation data can be used to decide when to terminate the selection process or to decide what effects to include as the selection process proceeds. Finally, after a selected model has been obtained, the test set can be used to assess how the selected model generalizes on data that played no role in selecting the model.

In some cases you might want to use only training and test data. For example, you might decide to use an information criterion to decide what effects to include and when to terminate the selection process. In this case no validation data are required, but test data can still be useful in assessing the predictive performance of the selected model. In other cases you might decide to use validation data during the selection process but forgo assessing the selected model on test data. Hastie, Tibshirani, and Friedman (2001) note that it is difficult to give a general rule for how many observations you should assign to each role. They note that a typical split might be 50% for training and 25% each for validation and testing.

You use a PARTITION statement to logically subdivide the DATA= data set into separate roles. You can name the fractions of the data that you want to reserve as test data and validation data. For example, the following statements randomly subdivide the "inData" data set, reserving 50% for training and 25% each for validation and testing:

```
proc hpreg data=inData;
  partition fraction(test=0.25 validate=0.25);
  ...
run;
```

In some cases you might need to exercise more control over the partitioning of the input data set. You can do this by naming a both variable in the input data set and also a formatted value of that variable that correspond to each role. For example, the following statements assign roles to the observations in the "inData" data set based on the value of the variable group in that data set. Observations where the value of group is 'group 1' are assigned for testing, and those with value 'group 2' are assigned to training. All other observations are ignored.

```
proc hpreg data=inData;
  partition roleVar=group(test='group 1' train='group 2')
  ...
run;
```

When you have reserved observations for training, validation, and testing, a model fit on the training data is scored on the validation and test data, and the average squared error (ASE) is computed separately for each of these subsets. The ASE for each data role is the error sum of squares for observations in that role divided by the number of observations in that role.

Using the Validation ASE as the STOP= Criterion

If you have provided observations for validation, then you can specify STOP=VALIDATE as a suboption of the METHOD= option in the SELECTION statement. At step k of the selection process, the best candidate effect to enter or leave the current model is determined. Here "best candidate" means the effect that gives the best value of the SELECT= criterion; this criterion need not be based on the validation data. The validation ASE for the model with this candidate effect added or removed is computed. If this validation ASE is greater than the validation ASE for the model at step k, then the selection process terminates at step k.

Using the Validation ASE as the CHOOSE= Criterion

When you specify the CHOOSE=VALIDATE suboption of the METHOD= option in the SELECTION statement, the validation ASE is computed for the models at each step of the selection process. The smallest model at any step that yields the smallest validation ASE is selected.

Using the Validation ASE as the SELECT= Criterion

You request the validation ASE as the selection criterion by specifying the SELECT=VALIDATE suboption of the METHOD= option in the SELECTION statement. At step k of the selection process, the validation ASE is computed for each model in which a candidate for entry is added or candidate for removal is dropped. The selected candidate for entry or removal is the one that yields a model with the minimal validation ASE. This method is computationally very expensive because validation statistics need to be computed for every candidate at every step; it should be used only with small data sets or models with a small number of regressors.

Computational Method

Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPREG procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statements, the HPREG procedure schedules threads as if it executes on a system with four CPUs, regardless of the actual CPU count.

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This specification overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement, which overrides the CPUCOUNT system option and instructs the HPREG procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output. The HPREG procedure allocates one thread per CPU.

The tasks multithreaded by the HPREG procedures are primarily defined by dividing the data processed on a single machine among the threads—that is, the HPREG procedure implements multithreading through a data-parallel model. For example, if the input data set has 1,000 observations and you are running with four threads, then 250 observations are associated with each thread. All operations that require access to the data are then multithreaded. This operations include the following:

- variable levelization
- effect levelization
- formation of the crossproducts matrix
- evaluation of predicted residual sums of squares on validation and test data
- scoring of observations

In addition, operations on matrices such as sweeps might be multithreaded if the matrices are of sufficient size to realize performance benefits from managing multiple threads for the particular matrix operation.

Output Data Set

Many procedures in SAS software add the variables from the input data set when an observationwise output data set is created. The assumption of High-Performance Analytics procedures is that the input data sets can be large and contain many variables. For performance reasons, the output data set contains the following:

- those variables explicitly created by the statement
- variables listed in the ID statement
- distribution keys or hash keys that are transferred from the input data set

This enables you to add output data set information that is necessary for subsequent SQL joins without copying the entire input data set to the output data set. For further details about output data sets when PROC HPREG is run in distributed (MPP) mode, see the section "Output Data Sets" on page 26 in Chapter 3, "Shared Concepts and Topics."

Displayed Output

The following sections describe the output produced by PROC HPREG. The output is organized into various tables, which are discussed in the order of appearance.

Performance Information

The "Performance Information" table is produced by default and displays information about the grid host for distributed execution and about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

Model Information

The "Model Information" table displays basic information about the model, such as the response variable, frequency variable, weight variable, and the type of parameterization used for classification variables named in the CLASS statement.

Selection Information

When you specify the SELECTION statement, the HPREG procedure produces by default a series of tables with information about the model selection. The "Selection Information" table informs you about the model selection method; select, stop, and choose criteria; and other parameters that govern the selection. You can suppress this table by specifying DETAILS=NONE in the SELECTION statement.

Number of Observations

The "Number of Observations" table displays the number of observations read from the input data set and the number of observations used in the analysis. If you specify a FREQ statement, the table also displays the sum of frequencies read and used. If you use a PARTITION statement, the table also displays the number of observations used for each data role.

Class Level Information

The "Class Level Information" table lists the levels of every variable specified in the CLASS statement. You should check this information to make sure that the data are correct. You can adjust the order of the CLASS variable levels with the ORDER= option in the CLASS statement. You can suppress the "Class Level Information" table completely or partially with the NOCLPRINT= option in the PROC HPREG statement.

If the classification variables are in the reference parameterization, the "Class Level Information" table also displays the reference value for each variable. The "Class Level Information" table also indicates which, if any, of the classification variables are split by using the SPLIT option in the CLASS statement.

Dimensions

The "Dimensions" table displays information about the number of effects and the number of parameters from which the selected model is chosen. If you use split classification variables, then this table also includes the number of effects after splitting is taken into account.

Entry and Removal Candidates

When you specify the DETAILS=ALL or DETAILS=STEPS option in the SELECTION statement, the HPREG procedure produces "Entry Candidates" and "Removal Candidates" tables that display the effect names and values of the criterion used to select entering or departing effects at each step of the selection process. The effects are displayed in sorted order from best to worst of the selection criterion.

Selection Summary

When you specify the SELECTION statement, the HPREG procedure produces the "Selection Summary" table with information about the sequence of steps of the selection process. For each step, the effect that was entered or dropped is displayed along with the statistics used to select the effect, stop the selection, and choose the selected model. For all criteria that you can use for model selection, the steps at which the optimal values of these criteria occur are also indicated.

The display of the "Selection Summary" table can be suppressed by specifying DETAILS=NONE in the SELECTION statement.

Stop Reason

The "Stop Reason" table displays the reason why the selection stopped. To facilitate programmatic use of this table, an integer code is assigned to each reason and is included if you output this table by using an ODS OUTPUT statement. The reasons and their associated codes follow:

Code	Stop Reason
1	All eligible effects are in the model.
2	All eligible effects have been removed.
3	Specified maximum number of steps done.
4	The model contains the specified maximum number of effects.
5	The model contains the specified minimum number of effects (for backward selection).
6	The stopping criterion is at a local optimum.
7	No suitable add or drop candidate could be found.
8	Adding or dropping any effect does not improve the selection criterion.
9	No candidate meets the appropriate SLE or SLS significance level.
10	Stepwise selection is cycling.
11	The model is an exact fit.
12	Dropping an effect would result in an empty model.

The display of the "Stop Reason" table can be suppressed by specifying DETAILS=NONE in the SELECTION statement.

Selection Reason

When you specify the SELECTION statement, the HPREG procedure produces a simple table that contains text informing you about the reason why the final model was selected.

The display of the "Selection Reason" table can be suppressed by specifying DETAILS=NONE in the SELECTION statement.

Selected Effects

When you specify the SELECTION statement, the HPREG procedure produces a simple table that contains text informing you about which effects were selected into the final model.

ANOVA

The "ANOVA" table displays an analysis of variance for the selected model. This table includes the following:

- the Source of the variation, Model for the fitted regression, Error for the residual error, and C Total for the total variation after correcting for the mean. The Uncorrected Total Variation is produced when the NOINT option is used.
- the degrees of freedom (DF) associated with the source
- the Sum of Squares for the term
- the Mean Square, the sum of squares divided by the degrees of freedom
- the *F* Value for testing the hypothesis that all parameters are 0 except for the intercept. This is formed by dividing the mean square for Model by the mean square for Error.
- the Prob>*F*, the probability of getting a greater *F* statistic than that observed if the hypothesis is true. When you do model selection, these *p*-values are generally liberal because they are not adjusted for the fact that the terms in the model have been selected.

You can request "ANOVA" tables for the model at each step of the selection process with the DETAILS= option in the SELECTION statement.

Fit Statistics

The "Fit Statistics" table displays fit statistics for the selected model. The statistics displayed include the following:

- Root MSE, an estimate of the standard deviation of the error term. It is calculated as the square root of the mean square error.
- R-square, a measure between 0 and 1 that indicates the portion of the (corrected) total variation attributed to the fit rather than left to residual error. It is calculated as SS(Model) divided by SS(Total). It is also called the *coefficient of determination*. It is the square of the multiple correlation—in other words, the square of the correlation between the dependent variable and the predicted values.

- Adj R-Sq, the adjusted R-square, a version of R-square that has been adjusted for degrees of freedom. It is calculated as

$$\bar{R}^2 = 1 - \frac{(n-i)(1-R^2)}{n-p}$$

  where i is equal to 1 if there is an intercept and 0 otherwise, n is the number of observations used to fit the model, and p is the number of parameters in the model.

- fit criteria AIC, AICC, BIC, CP, and PRESS if they are used in the selection process. See Table 22.5 for the formulas for evaluating these criteria.

- the average square errors (ASE) on the training, validation, and test data.

You can request "Fit Statistics" tables for the model at each step of the selection process with the DETAILS= option in the SELECTION statement.

Parameter Estimates

The "Parameter Estimates" table displays the parameters in the selected model and their estimates. The information displayed for each parameter in the selected model includes the following:

- the parameter label that includes the effect name and level information for effects that contain classification variables

- the degrees of freedom (DF) for the parameter. There is one degree of freedom unless the model is not full rank.

- the parameter estimate

- the standard error, which is the estimate of the standard deviation of the parameter estimate

- t Value, the t test that the parameter is 0. This is computed as the parameter estimate divided by the standard error.

- the Pr > |t|, the probability that a t statistic would obtain a greater absolute value than that observed given that the true parameter is 0. This is the two-tailed significance probability.

  When you do model selection, these p-values are generally liberal because they are not adjusted for the fact that the terms in the model have been selected.

You can request "Parameter Estimates" tables for the model at each step of the selection process with the DETAILS= option in the SELECTION statement.

Timing Information

If you specify the DETAILS option in the PERFORMANCE statement, the procedure also produces a "Timing" table in which the elapsed time for each main task of the procedure is displayed.

ODS Table Names

Each table created by the HPREG procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 22.7.

Table 22.7 ODS Tables Produced by PROC HPREG

Table Name	Description	Required Statement / Option
ANOVA	Selected model ANOVA table	Default output
Candidates	Swap candidates at step	SELECTION DETAILS=ALL|STEPS
ClassLevels	Level information from the CLASS statement	CLASS
Dimensions	Model dimensions	Default output
EntryCandidates	Candidates for entry at step	SELECTION DETAILS=ALL|STEPS
FitStatistics	Fit statistics	Default output
ModelInfo	Information about the modeling environment	Default output
NObs	Number of observations read and used	Default output
ParameterEstimates	Solutions for the parameter estimates associated with effects in MODEL statement	Default output
PerformanceInfo	Information about high-performance computing environment	Default output
RemovalCandidates	Candidates for removal at step	SELECTION DETAILS=ALL|STEPS
SelectedEffects	List of selected effects	SELECTION
SelectionInfo	Information about selection settings	Default output
SelectionReason	Reason for selecting the final model	SELECTION
SelectionSummary	Summary information about the model selection steps	SELECTION
StopReason	Reason selection was terminated	SELECTION
Timing	Timing breakdown by task	SELECTION DETAILS

Examples: HPREG Procedure

Example 22.1: Model Selection with Validation

This example is based on the example "Using Validation and Cross Validation" in the documentation for the GLMSELECT procedure in the *SAS/STAT User's Guide*. This example shows how you can use validation data to monitor and control variable selection. It also demonstrates the use of split classification variables.

The following DATA step produces analysis data that contains a variable that you can use to assign observations to the training, validation, and testing roles. In this case, each role has 5,000 observations.

```
data analysisData;
   drop i j c3Num;
   length c3$ 7;

   array x{20} x1-x20;

   do i=1 to 15000;
      do j=1 to 20;
         x{j} = ranuni(1);
      end;

      c1 = 1 + mod(i,8);
      c2 = ranbin(1,3,.6);

      if      i < 50   then do; c3 = 'tiny';     c3Num=1;end;
      else if i < 250  then do; c3 = 'small';    c3Num=1;end;
      else if i < 600  then do; c3 = 'average';  c3Num=2;end;
      else if i < 1200 then do; c3 = 'big';      c3Num=3;end;
      else                  do; c3 = 'huge';     c3Num=5;end;

      yTrue = 10 + x1 + 2*x5 + 3*x10 + 4*x20  + 3*x1*x7 + 8*x6*x7
                 + 5*(c1=3)*c3Num + 8*(c1=7);

      error = 5*rannor(1);

      y = yTrue + error;

           if mod(i,3)=1 then Role = 'TRAIN';
      else if mod(i,3)=2 then Role = 'VAL';
      else                    Role = 'TEST';

      output;
  end;
run;
```

By construction, the true model consists of main effects x1, x5, x10, x20, and c1 and interaction effects x1*x7, x6*x7, and c1*c3. Furthermore, you can see that only levels 3 and 7 of the classification variable c1 are systematically related to the response.

Because the error term for each observation is five times a value drawn from a standard normal distribution, the expected error variance is 25. For the data in each role, you can compute an estimate of this error variance by forming the average square error (ASE) for the observations in the role. Output 22.1.1 shows the ASE for each role that you can compute with the following statements:

```
proc summary data=analysisData;
   class role;
   ways 1;
   var error;
   output out=ASE uss=uss n=n;
data ASE; set ASE;
   OracleASE = uss / n;
   label OracleASE = 'Oracle ASE';
   keep Role OracleASE;
proc print data=ASE label noobs;
run;

proc print data=ASE label noobs;
run;
```

Output 22.1.1 Oracle ASE Values by Role

Role	Oracle ASE
TEST	25.5784
TRAIN	25.4008
VAL	25.8993

The ASE values shown Output 22.1.1 are labeled as "Oracle ASE" because you need to know the true underlying model if you want to compute these values from the response and underlying regressors. In a modeling context, a good predictive model produces values that are close to these oracle values. An overfit model produces a smaller ASE on the training data but higher values on the validation and test data. An underfit model exhibits higher values for all data roles.

Suppose you suspect that the dependent variable depends on both main effects and two-way interactions. You can use the following statements to select a model:

```
proc hpreg data=analysisData;
   partition roleVar=role(train='TRAIN' validate='VAL' test='TEST');
   class c1 c2 c3(order=data);
   model y =  c1|c2|c3|x1|x2|x3|x4|x5|x5|x6|x7|x8|x9|x10
             |x11|x12|x13|x14|x15|x16|x17|x18|x19|x20 @2 /stb;
   selection method = stepwise(select=sl sle=0.1 sls=0.15 choose=validate)
                      hierarchy=single details=steps;
run;
```

A PARTITION statement assigns observations to training, validation, and testing roles based on the values of the input variable named role. The SELECTION statement requests STEPWISE selection based on significance level where the SLE and SLS values are set to use the defaults of PROC REG. The CHOOSE=VALIDATE option selects the model that yields the smallest ASE value on the validation data.

The "Number Of Observation" table in Output 22.1.2 confirms that there are 5,000 observations for each data role. The "Dimensions" table shows that the selection is from 278 effects with a total of 661 parameters.

Output 22.1.2 Number of Observations, Class Levels, and Dimensions

The HPREG Procedure

Number of Observations Read	15000
Number of Observations Used	15000
Number of Observations Used for Training	5000
Number of Observations Used for Validation	5000
Number of Observations Used for Testing	5000

Class Level Information

Class	Levels	Values
c1	8	1 2 3 4 5 6 7 8
c2	4	0 1 2 3
c3	5	tiny small average big huge

Dimensions

Number of Effects	278
Number of Parameters	661

Output 22.1.3 shows the "Selection Summary" table. You see that 18 steps are done, at which point all effects in the model are significant at the SLS value of 0.15 and all the remaining effects if added individually would not be significant at the SLE significance level of 0.1. However, because you have specified the CHOOSE=VALIDATE option, the model at step 18 is not used as the selected model. Instead the model at step 10 (where the validation ASE achieves a local minimum value) is selected. The "Stop Reason," "Selection Reason," and "Selected Effects" in Output 22.1.4 provide this information.

Output 22.1.3 Selection Summary

The HPREG Procedure

Selection Summary

Step	Effect Entered	Number Effects In	Validation ASE	p Value
0	Intercept	1	98.3895	1.0000
1	c1	2	34.8572	<.0001
2	x7	3	32.5531	<.0001
3	x6	4	31.0646	<.0001
4	x20	5	29.7078	<.0001
5	x6*x7	6	29.2210	<.0001
6	x10	7	28.6683	<.0001
7	x1	8	28.3250	<.0001
8	x5	9	27.9766	<.0001
9	c3	10	27.8288	<.0001
10	c1*c3	11	25.9701*	<.0001
11	x10*c1	12	26.0696	0.0109
12	x4	13	26.1594	0.0128
13	x4*x10	14	26.1814	0.0035
14	x20*c1	15	26.3294	0.0156
15	x1*c3	16	26.3945	0.0244
16	x1*x7	17	26.3632	0.0270
17	x7*x10	18	26.4120	0.0313
18	x1*x20	19	26.4330	0.0871

* Optimal Value of Criterion

Output 22.1.4 Stopping and Selection Reasons

```
Selection stopped because all candidates for removal are significant at the 0.15
level and no candidate for entry is significant at the 0.1 level.

        The model at step 10 is selected where Validation ASE is 25.9701.

       Selected Effects: Intercept c1 c3 c1*c3 x1 x5 x6 x7 x6*x7 x10 x20
```

You can see that the selected effects include all the main effects in the true model and two of the three true interaction terms. Furthermore, the selected model does not include any variables that are not in the true model. Note that these statements are not true of the larger model at the final step of the selection process.

Output 22.1.5 shows the fit statistics of the selected model. You can see that the ASE values on the training, validation, and test data are all similar, which is indicative of a reasonable predictive model. In this case where the true model is known, you can see that all three ASE values are close to oracle values for the true model, as shown in Output 22.1.1.

Output 22.1.5 Fit Statistics for the Selected Model

Root MSE	5.03976
R-Square	0.74483
Adj R-Sq	0.74246
AIC	21222
AICC	21223
SBC	16527
ASE (Train)	25.16041
ASE (Validate)	25.97010
ASE (Test)	25.83436

Because you specified the DETAILS=STEPS option in the SELECTION statement, you can see the "Fit Statistics" for the model at each step of the selection process. Output 22.1.6 shows these fit statistics for final model at step 18. You see that for this model, the ASE value on the training data is smaller than the ASE values on the validation and test data. This is indicative an overfit model that might not generalize well to new data. You see the ASE values on the validation and test data are now worse in comparison to the oracle values than the values for the selected model at step 10.

Output 22.1.6 Fit Statistics for the Model at Step 18

Root MSE	5.01386
R-Square	0.74862
Adj R-Sq	0.74510
AIC	21194
AICC	21196
SBC	16648
ASE (Train)	24.78688
ASE (Validate)	26.43304
ASE (Test)	26.07078

Output 22.1.7 shows part of the "Parameter Estimates" table for the selected model at step 10 that includes the estimates for the main effect `c1`. Because the STB option is specified in the MODEL statement, this table includes standardized estimates.

Output 22.1.7 Part of the Parameter Estimates Table for the Selected Model

Parameter Estimates

Parameter	DF	Estimate	Standardized Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	9.479114	0	0.422843	22.42	<.0001
c1 1	1	0.279417	0.009306	0.297405	0.94	0.3475
c1 2	1	0.615589	0.020502	0.297332	2.07	0.0385
c1 3	1	25.678601	0.855233	0.297280	86.38	<.0001
c1 4	1	0.420360	0.014000	0.297283	1.41	0.1574
c1 5	1	0.473986	0.015786	0.297265	1.59	0.1109
c1 6	1	0.394044	0.013124	0.297299	1.33	0.1851
c1 7	1	8.469793	0.282089	0.297345	28.48	<.0001
c1 8	0	0	0	.	.	.

The magnitudes of the standardized estimates and the *t* statistics of the parameters of the effect c1 reveal that only levels 3 and 7 of this effect contribute appreciably to the model. This suggests that a more parsimonious model with similar or better predictive power might be obtained if parameters that correspond to the levels of c1 can enter or leave the model independently. You request this with the SPLIT option in the CLASS statement as shown in the following statements:

```
proc hpreg data=analysisData;
   partition roleVar=role(train='TRAIN' validate='VAL' test='TEST');
   class c1(split) c2 c3(order=data);
   model y =  c1|c2|c3|x1|x2|x3|x4|x5|x5|x6|x7|x8|x9|x10
             |x11|x12|x13|x14|x15|x16|x17|x18|x19|x20 @2 /stb;
   selection method = stepwise(select=sl sle=0.1 sls=0.15 choose=validate)
                      hierarchy=single details=steps;
run;
```

Output 22.1.8 shows the "Dimensions" table. You can see that because the columns in the design matrix that correspond to levels of c1 are treated as separate effects, the selection is now from 439 effects, even though the number of parameters is unchanged.

Output 22.1.8 Dimensions with c1 Split

The HPREG Procedure

Dimensions

Number of Effects	278
Number of Effects after Splits	439
Number of Parameters	661

Output 22.1.9 shows the selected effects. You can see that as anticipated the selected model now depends on only levels 3 and 7 of c1.

Output 22.1.9 Selected Effects with c1 Split

```
Selected Effects: Intercept c1_3 c1_7 c3 c1_3*c3 x1 x5 x6 x7 x6*x7 x10 x20
```

Finally, the fit statistics for the selected model are shown Output 22.1.10.

Output 22.1.10 Fit Statistics for the Selected Model with c1 Split

Root MSE	5.04060
R-Square	0.74325
Adj R-Sq	0.74238
AIC	21195
AICC	21195
SBC	16311
ASE (Train)	25.31622
ASE (Validate)	25.98055
ASE (Test)	25.76059

If you compare the ASE values for this model in Output 22.1.10 with the oracle values in Output 22.1.1 and the values for the model without splitting c1 in Output 22.1.5, you see that this more parsimonious model produces the best predictive performance on the test data of all the models considered in this example.

Example 22.2: Backward Selection in SMP and MPP Modes

This example shows how you can run PROC HPREG in SMP and MPP modes. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about the execution modes of SAS High-Performance Analytics procedures. The focus of this example is to simply show how you can switch the modes of execution of PROC HPREG, rather than on any statistical features of the procedure. The following DATA step generates the data for this example. The response y depends on 20 of the 1,000 regressors.

```
data ex2Data;
   array x{1000};

   do i=1 to 10000;
      y=1;
      sign=1;

      do j=1 to 1000;
         x{j} = ranuni(1);
         if j<=20  then do;
           y = y + sign*j*x{j};
           sign=-sign;
         end;
      end;
      y = y + 5*rannor(1);
      output;
  end;
run;
```

The following statements use PROC HPREG to select a model by using BACKWARD selection:

```
proc hpreg data=ex2Data;
    model y = x: ;
    selection method = backward;
    performance details;
run;
```

Output 22.2.1 shows the "Performance Information" table. This shows that the HPREG procedure executes in client (SMP) mode using four threads because the client machine has four CPUs. You can force a certain number of threads on any machine involved in the computations with the NTHREADS option in the PERFORMANCE statement.

Output 22.2.1 Performance Information

The HPREG Procedure

Performance Information

Execution Mode	On client
Number of Threads	4

Output 22.2.2 shows the parameter estimates for the selected model. You can see that the default BACKWARD selection with selection and stopping based on the SBC criterion retains all 20 of the true effects but also keeps two extraneous effects.

Output 22.2.2 Parameter Estimates for the Selected Model

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	1.506615	0.419811	3.59	0.0003
x1	1	1.054402	0.176930	5.96	<.0001
x2	1	-1.996080	0.176967	-11.28	<.0001
x3	1	3.293331	0.177032	18.60	<.0001
x4	1	-3.741273	0.176349	-21.22	<.0001
x5	1	4.908310	0.176047	27.88	<.0001
x6	1	-5.772356	0.176642	-32.68	<.0001
x7	1	7.398822	0.175792	42.09	<.0001
x8	1	-7.958471	0.176281	-45.15	<.0001
x9	1	8.899407	0.177624	50.10	<.0001
x10	1	-9.687667	0.176431	-54.91	<.0001
x11	1	11.083373	0.175195	63.26	<.0001
x12	1	-12.046504	0.176324	-68.32	<.0001
x13	1	13.009052	0.176967	73.51	<.0001
x14	1	-14.456393	0.175968	-82.15	<.0001
x15	1	14.928731	0.174868	85.37	<.0001
x16	1	-15.762907	0.177651	-88.73	<.0001
x17	1	16.842889	0.177037	95.14	<.0001
x18	1	-18.468844	0.176502	-104.64	<.0001
x19	1	18.810193	0.176616	106.50	<.0001
x20	1	-20.212291	0.176325	-114.63	<.0001
x87	1	-0.542384	0.176293	-3.08	0.0021
x362	1	-0.560999	0.176594	-3.18	0.0015

Output 22.2.3 shows timing information for the PROC HPREG run. This table is produced when you specify the DETAILS option in the PERFORMANCE statement. You can see that, in this case, the majority of time is spent forming the crossproducts matrix for the model that contains all the regressors.

Output 22.2.3 Timing

Procedure Task Timing

Task	Time (sec.)	
Reading and Levelizing Data	0.97	5.32%
Loading Design Matrix	0.75	4.12%
Computing Moments	0.06	0.35%
Computing Cross Products Matrix	13.24	72.9%
Performing Model Selection	3.15	17.3%

You can switch to running PROC HPREG in MPP mode by specifying valid values for the NODES=, INSTALL=, and HOST= options in the PERFORMANCE statement. An alternative to specifying the INSTALL= and HOST= options in the PERFORMANCE statement is to set appropriate values for the GRIDHOST and GRIDINSTALLLOC environment variables by using OPTIONS SET commands. See the

section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about setting these options or environment variables.

The following statements provide an example. To run these statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to macro variables with appropriate values.

```
proc hpreg data=ex2Data;
    model y = x: ;
    selection method = backward;
    performance details nodes = 10
                host="&GRIDHOST" install="&GRIDINSTALLLOC";
run;
```

The execution mode in the "Performance Information" table shown in Output 22.2.4 indicates that the calculations were performed in a distributed environment that uses 10 nodes, each of which uses eight threads.

Output 22.2.4 Performance Information in MPP Mode

Performance Information

Host Node	<< your grid host >>
Install Location	<< your grid install location >>
Execution Mode	Distributed
Number of Compute Nodes	10
Number of Threads per Node	8

Another indication of distributed (MPP) execution is the following message issued by all High-Performance Analytics procedures in the SAS Log:

```
NOTE: The HPREG procedure is executing in the distributed
      computing environment with 10 worker nodes.
```

Output 22.2.5 shows timing information for this distributed run of the HPREG procedure. In contrast to the SMP case (where forming the crossproducts matrix dominated the time spent), the majority of time in the MPP run is spent performing the model selection.

Output 22.2.5 Timing

Procedure Task Timing

Task	Time (sec.)	
Distributing Data	0.90	19.6%
Reading and Levelizing Data	0.04	0.88%
Loading Design Matrix	0.03	0.55%
Computing Moments	0.01	0.19%
Computing Cross Products Matrix	0.64	14.0%
Performing Model Selection	2.51	54.7%
Waiting on Client	0.46	10.1%

Example 22.3: Forward-Swap Selection

This example highlights the use of the forward-swap selection method, which is a generalization of the maximum R-square improvement (MAXR) method that is available in the REG procedure in SAS/STAT software. This example also demonstrates the use of the INCLUDE and START options.

The following DATA step produces the simulated data in which the response y depends on six main effects and three 2-way interactions from a set of 20 regressors.

```
data ex3Data;
   array x{20};
   do i=1 to 10000;
      do j=1 to 20;
         x{j} = ranuni(1);
      end;
      y = 3*x1 + 7*x2 -5*x3 + 5*x1*x3 +
          4*x2*x13 + x7 + x11 -x13  + x1*x4 + rannor(1);
      output;
   end;
run;
```

Suppose you want to find the best model of each size in a range of sizes for predicting the response y. You can use the forward-swap selection method to produce good models of each size without the computational expense of examining all possible models of each size. In this example, the criterion used to evaluate the models of each size is the model R square. With this criterion, the forward-swap method coincides with the MAXR method that is available in the REG procedure in SAS/STAT software. The model of a given size for which no pairwise swap of an effect in the model with any candidate effect improves the R-square value is deemed to be the best model of that size.

Suppose that you have prior knowledge that the regressors x1, x2, and x3 are needed in modeling the response y. Suppose that you also believe that some of the two-way interactions of these variables are likely to be important in predicting y and that some other two-way interactions might also be needed. You can use this prior information by specifying the selection process shown in the following statements:

```
proc hpreg data=ex3Data;
    model y = x1|x2|x3|x4|x5|x6|x7|x8|x9|x10|X11|
              x12|x13|x14|x5|x16|x7|x18|x19|x20@2 /
                  include=(x1 x2 x3) start=(x1*x2 x1*x3 x2*x3);
    selection method=forwardswap(select=rsquare maxef=15 choose=sbc) details=all;
run;
```

The MODEL statement specifies that all main effects and two-way interactions are candidates for selection. The INCLUDE= option specifies that the effects x1, x2, and x3 must appear in all models that are examined. The START= option specifies that all the two-way interactions of these variables should be used in the initial model that is considered but that these interactions are eligible for removal during the forward-swap selection.

The "Selection Summary" table is shown in Output 22.3.1.

Output 22.3.1 Selection Summary

The HPREG Procedure

Selection Summary

Step	Effect Entered	Effect Removed	Number Effects In	SBC	Model R-Square
0	Intercept		1		
	x1		2		
	x2		3		
	x1*x2		4		
	x3		5		
	x1*x3		6		
	x2*x3		7	3307.6836	0.8837
1	x2*x13		8	1892.8403	0.8992
2	x7*x11	x1*x2	8	618.9298	0.9112
3	x1*x4	x2*x3	8	405.3751	0.9131
4	x13		9	213.6140	0.9148
5	x7		10	180.4457	0.9152
6	x11	x7*x11	10	1.4039*	0.9167
7	x10*x11		11	2.3393	0.9168
8	x3*x7		12	4.5000	0.9168
9	x6*x7		13	10.0589	0.9169
10	x3*x6		14	13.1113	0.9169
11	x5*x20		15	19.4612	0.9169
12	x13*x20	x3*x6	15	18.3678	0.9169
13	x5*x5	x6*x7	15	12.1398	0.9170*

* Optimal Value of Criterion

You see that starting from the model with an intercept and the effects specified in the INCLUDE= and START= options at step 0, the forward-swap selection method adds the effect x2*x13 at step one, because this yields the maximumum improvement in R square that can be obtained by adding a single effect. The forward-swap selection method now evaluates whether any effect swap yields a better eight-effect model (one with a higher R-square value). Because you specified the DETAILS=ALL option in the SELECTION statement, at each step where a swap is made you obtain a "Candidates" table that shows the R-square values for the evaluated swaps. Output 22.3.2 shows the "Candidates" for step 2. By default, only the best 10 swaps are displayed.

Output 22.3.2 Swap Candidates at Step 2

Best 10 Candidates

Rank	Effect Dropped	Effect Added	R-Square
1	x1*x2	x7*x11	0.9112
2	x2*x3	x7*x11	0.9112
3	x1*x2	x7	0.9065
4	x2*x3	x7	0.9065
5	x1*x2	x7*x7	0.9060
6	x2*x3	x7*x7	0.9060
7	x1*x2	x4*x7	0.9060
8	x2*x3	x4*x7	0.9060
9	x1*x2	x11	0.9058
10	x2*x3	x11	0.9058

You see that the best swap adds x7*x11 and drops x1*x2. This yields an eight-effect model whose R-square value (0.9112) is larger than the R-square value (0.8992) of the eight-effect model at step 1. Hence this swap is made at step 2. At step 3, an even better eight-effect model than the model at step 2 is obtained by dropping x2*x3 and adding x1*x4. No additional swap improves the R-square value, and so the model at step 3 is deemed to be the best eight-effect model. Although this is the best eight-effect model that can be found by this method given the starting model, it is not guaranteed that this model that has the highest R-square value among all possible models that consist of seven effects and an intercept.

Because the DETAILS=ALL option is specified in the SELECTION statement, details for the model at each step of the selection process are displayed. Output 22.3.3 provides details of the model at step 3.

Output 22.3.3 Model Details at Step 3

Analysis of Variance

Source	DF	Sum of Squares	Mean Square	F Value	Pr > F
Model	7	108630	15519	15000.3	<.0001
Error	9992	10337	1.03455		
Corrected Total	9999	118967			

Root MSE	1.01713
R-Square	0.91311
Adj R-Sq	0.91305
AIC	10350
AICC	10350
SBC	405.37511
ASE	1.03373

Output 22.3.3 *continued*

Parameter Estimates

Parameter	DF	Estimate	Standard Error	t Value	Pr > |t|
Intercept	1	0.012095	0.045712	0.26	0.7913
x1	1	3.087078	0.076390	40.41	<.0001
x2	1	7.775180	0.046815	166.08	<.0001
x3	1	-4.957140	0.070995	-69.82	<.0001
x1*x3	1	4.910115	0.122503	40.08	<.0001
x1*x4	1	0.890436	0.060523	14.71	<.0001
x7*x11	1	1.708469	0.045939	37.19	<.0001
x2*x13	1	2.584078	0.061506	42.01	<.0001

The forward-swap method continues to find the best nine-effect model, best 10-effect model, and so on until it obtains the best 15-effect model. At this point the selection terminates because you specified the MAXEF=15 option in the SELECTION statement. The R-square value increases at each step of the selection process. However, because you specified the CHOOSE=SBC criterion in the SELECTION statement, the final model selected is the model at step 6.

References

Akaike, H. (1969), "Fitting Autoregressive Models for Prediction," *Annals of the Institute of Statistical Mathematics*, 21, 243–247.

Burnham, K. P. and Anderson, D. R. (2002), *Model Selection and Multimodel Inference*, Second Edition, New York: Springer-Verlag.

Collier Books (1987), *The 1987 Baseball Encyclopedia Update*, Macmillan.

Darlington, R. B. (1968), "Multiple Regression in Psychological Research and Practice," *Psychological Bulletin*, 69, 161–182.

Draper, N. R., Guttman, I., and Kanemasu, H. (1971), "The Distribution of Certain Regression Statistics," *Biometrika*, 58, 295–298.

Harrell, F. E. (2001), *Regression Modeling Strategies*, New York: Springer-Verlag.

Hastie, T., Tibshirani, R., and Friedman, J. (2001), *The Elements of Statistical Learning*, New York: Springer-Verlag.

Hocking, R. R. (1976), "The Analysis and Selection of Variables in a Linear Regression," *Biometrics*, 32, 1–50.

Hurvich, C. M. and Tsai, C.-L. (1989), "Regression and Time Series Model Selection in Small Samples," *Biometrika*, 76, 297–307.

Judge, G. G., Griffiths, W. E., Hill, R. C., Lutkepohl, H., and Lee, T. C. (1985), *The Theory and Practice of Econometrics*, Second Edition, New York: John Wiley & Sons.

Mallows, C. L. (1973), "Some Comments on C_p," *Technometrics*, 15, 661–675.

Schwarz, G. (1978), "Estimating the Dimension of a Model," *Annals of Statistics*, 6, 461–464.

Time Inc. (1987), "What They Make," *Sports Illustrated*, 54–81.

Chapter 23
The HPSAMPLE Procedure

Contents

Overview: HPSAMPLE Procedure **581**
Getting Started: HPSAMPLE Procedure **582**
Syntax: HPSAMPLE Procedure **583**
PROC HPSAMPLE Statement 583
CLASS Statement 584
PERFORMANCE Statement 584
TARGET Statement 585
VAR Statement 585
Details: HPSAMPLE Procedure **585**
Class Level 585
Displayed Output 585
ODS Table Names 586
Examples: HPSAMPLE Procedure **587**
Example 23.1: Running PROC HPSAMPLE on the Client 587
Example 23.2: Running with Client Data on the SAS appliance 588
Example 23.3: Running with Data on the SAS appliance 590

Overview: HPSAMPLE Procedure

The HPSAMPLE procedure is a high-performance procedure that performs either simple random sampling or stratified sampling. The HPSAMPLE procedure creates the following:

- one output data set, which contains the sample data set
- one performance table, which contains performance information
- one frequency table, which contains the frequency information for the population and sample

The HPSAMPLE procedure is high-performance in that it takes advantage of distributed computing environments (currently using only a single thread) when the input data are stored on the SAS appliance.

Getting Started: HPSAMPLE Procedure

The following example shows a 10% stratified sampling with the target variable BAD used by the HPSAMPLE procedure as a stratum:

```
proc hpsample data=Sampsio.Hmeq  out=Smp samppct=10 seed=1234 partition;
    var loan derog mortdue value yoj delinq
        clage ninq clno debtinc;
    class bad reason job;
    target bad;
run;
proc print data=Smp;run;
```

The input data set Sampsio.Hmeq includes information about 5,960 fictitious mortgages. Each observation represents an applicant for a home equity loan, and all applicants have an existing mortgage. The SAMPPCT=10 option specifies that 10% of the input data be sampled. The SEED option specifies the random seed used in the sampling process is 1234. The PARTITION option specifies that the output data set, Smp, include an indicator that shows whether each observation is selected to the sample (1) or not (0). The VAR statement specifies ten numeric input variables, and the CLASS statement specifies three classification input variables. All these variables are included in the output sample. The binary TARGET variable BAD indicates whether an applicant eventually defaulted or was ever seriously delinquent. The displayed output contains a performance table (Figure 23.1) which shows the performance environment information, and a frequency table (Figure 23.2), which shows the frequency of observations in each level of BAD.

Figure 23.1 Performance Information

Performance Information

Execution Mode	On client
Number of Threads	1

Figure 23.2 Frequency Table

Stratified Sampling Frequency Table

Target Level	Number of Obs	Number of Sample
0	4771	478
1	1189	118

Syntax: HPSAMPLE Procedure

The following statements are available in the HPSAMPLE procedure:

PROC HPSAMPLE < *options* > **;**
VAR *variable* < *variable ... variable* > **;**
CLASS *variable* < *variable ... variable* > **;**
TARGET *variable* < *variable ... variable* > **;**
PERFORMANCE *performance-options* **;**

Either a VAR or a CLASS statement is required for simple random sampling; both the CLASS and TARGET statements are required for stratified sampling.

PROC HPSAMPLE Statement

PROC HPSAMPLE < *options* > **;**

The PROC HPSAMPLE statement invokes the procedure.

You can specify the following *options*:

DATA=< *libref.* **>***table*
names the table (SAS data set or database table) that you want to sample from. The default is the most recently opened or created data set. If the data are already distributed, the procedure reads the data alongside the distributed database. See the section "SMP and MPP Modes" on page 10 for the various execution modes and the section "Alongside-the-Database Execution" on page 15 for the alongside-the-database model.

OUT=< *libref.* **>***SAS-data-set*
names the SAS data set that you want to output the sample to. If you run alongside database, you need to specify a data set with the same database *libref* as the input data and make sure it does not already exist in the database. This option is required.

SAMPPCT=*sample-percentage*
names sample percentage to be used by PROC HPSAMPLE. The value of *sample-percentage* should be a positive number less than 100. For example, SAMPPCT=50.5 specifies that you want to sample 50.5 percent of data.

SAMPOBS=*number*
names the minimal number of observations you want to sample from the input data. The value of *number* must be a positive integer. If it exceeds the total number of observations in the input data, the output sample has the same number of observations as the input data set.

NOTE: You must specify either the SAMPPCT or the SAMPOBS option. If both are specified, only the SAMPPCT option is honored.

SEED=*random-seed*
specifies the seed for the random number generator. If *random-seed* is not specified or it is specified as a negative number, the seed is set to be the default 12345. The SEED option enables you to reproduce the same sample output.

PARTITION
produces an output data set with the same number of rows as the input data set but with an additional partition indicator (_PARTIND_), which indicates whether an observation is selected to the sample (1) or not (0).

NONORM
distinguishes target values that share the same normalized value when you do stratified sampling. For example, if a target has three distinct values, "A", "B", and "b", and you want to treat "B" and "b" as different levels, you need to use NONORM. By default, "B" and "b" are treated as the same level. PROC HPSAMPLE normalizes a value as follows:

1. Leading blanks are removed.
2. The value is truncated to 32 characters.
3. Letters are changed from lowercase to uppercase.

CLASS Statement

CLASS *variable* < *variable ... variable* > **;**

The CLASS statement specifies one or more classification variables to be included in the sample. At least one *variable* is required. A *variable* can be character or numeric. The CLASS and VAR statements are mutually exclusive.

NOTE: Each *variable* in the TARGET statement must be specified in the CLASS statement.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a SAS High-Performance Analytics procedure.

With the PERFORMANCE statement you can also control whether a SAS High-Performance Analytics procedure executes in symmetric multiprocessor (SMP) or massively parallel processor (MPP) mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

NOTE: PROC HPSAMPLE does not support multithreading in this release.

TARGET Statement

TARGET *variable* < *variable ... variable* > **;**

The TARGET statement specifies one or two classification variables to be used for stratificaiton. Each *variable* must be specified in the CLASS statement. Currently up to two target variables are supported. The maximum number of levels (that is, distinct values) in any target variable is 256.

VAR Statement

VAR *variable* < *variable ... variable* > **;**

The VAR statement specifies one or more numeric variables to be included in the sample. At least one *variable* is required; all *variables* must be numeric. You can use this statement to include only the variables of interests in your sample. The CLASS and VAR statements are mutually exclusive.

Details: HPSAMPLE Procedure

Class Level

For classification variables, a *level* is an observed value that is distinct after formatting, removal of beginning and ending white space, and capitalization. For example, the values **`MyLevel`** and **`MYLEVEL`** are treated as a single level in the data set. Class variables can be numeric, and the same levelization rules apply. For example, **`3.000002`** and **`3.0000001`** are treated as the same level if they are formatted using **`BEST3`**.

Displayed Output

The following sections describe the output that PROC HPSAMPLE produces by default. The output is organized into various tables, which are discussed in the order of their appearance.

Performance Information

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution and information about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The numbers of compute nodes and threads are also displayed, depending on the environment.

Timing Table

The "Timing Table" lists the timing information for various computational stages of the procedure.

Frequency Information Table

For simple random sampling, the "Frequency Information Table" lists the number of observations in the input data set and in the sample output data set.

For stratified sampling, the "Frequency Information Table" table lists the respective frequency in each stratum for the input data and the sample. If one target variable is specified, each level of the target variable represents a stratum; if two target variables are specified, a combination of the levels of two target variables represents a stratum.

ODS Table Names

Each table created by the HPSAMPLE procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 23.1.

Table 23.1 ODS Tables Produced by PROC HPSAMPLE

Table Name	Description	Required Statement / Option
PerformanceInfo	Information about the high-performance computing environment	Default output
Timing	Timing information for various computational stages of the procedure	DETAILS (PERFORMANCE statement)
FreqTable	Frequency table of input data set and output sample (when target variables are used, this table contains stratification information for population and sample)	Default output

Examples: HPSAMPLE Procedure

Example 23.1: Running PROC HPSAMPLE on the Client

This example demonstrates how to use PROC HPSAMPLE to perform a simple random sampling on the Sampsio.Hmeq data set, which resides on the client.

When the input data set resides on the client and no PERFORMANCE statement is specified, as in the following statements, the client performs all computations:

```
/*sampsio is a libname for a data source on the client.*/
proc hpsample data=sampsio.hmeq out=out1 sampobs=20 seed=13579;
    class job reason;
    var loan value delinq derog;
run;
proc print data=out1;
run;
```

Output 23.1.1 shows the performance environment information.

Output 23.1.1 Performance Information

```
Performance Information

Execution Mode       On client
Number of Threads    1
```

Output 23.1.2 shows the number of observations in the data set sampsio.hmeq and the number of samples.

Output 23.1.2 Frequency Table

```
Simple Random Sampling
   Frequency Table

Number of Obs    Number of Sample

         5960                  22
```

Output 23.1.3 shows the sample data.

Output 23.1.3 Sample Data

Obs	JOB	REASON	LOAN	VALUE	DELINQ	DEROG
1	Other	HomeImp	4900	65774	2	1
2	Other	HomeImp	5700	82923	0	0
3	Other	HomeImp	7000	124827	.	.
4		DebtCon	8300	75081	0	0
5	Office	DebtCon	10000	125500	0	0
6	Other		11100	61406	0	0
7	Other	HomeImp	11500	64037	0	0
8	ProfExe	HomeImp	11900	105454	0	0
9	Mgr	HomeImp	15000	122400	2	0
10	Other	HomeImp	15000	107207	0	0
11	ProfExe	HomeImp	15600	106824	0	0
12	Office	DebtCon	17000	69000	0	0
13	ProfExe	DebtCon	17300	49100	0	0
14	Other	DebtCon	18000	60000	0	2
15	Office	DebtCon	21100	98000	2	0
16	Other	HomeImp	21400	103427	0	0
17	Mgr	HomeImp	22400	121601	0	0
18	Other	HomeImp	25000	202500	0	0
19	Other	DebtCon	25500	43031	.	.
20	Mgr	DebtCon	27500	149877	0	0
21	ProfExe	DebtCon	36500	195729	0	0
22	Self	DebtCon	70300	294169	0	0

Example 23.2: Running with Client Data on the SAS appliance

This example uses the same data set as is used in Example 23.1.

When the input data set resides on the client and a PERFORMANCE statement with a NODES= option is specified, as in the following statements, PROC HPSAMPLE copies the data set to the SAS appliance, where the sampling is performed:

```
/*Perform the computation on the SAS appliance using 2 nodes*/
option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";
proc hpsample data=sampsio.hmeq out=out2 samppct=10 seed=13579 partition;
    var loan value delinq derog;
    class job reason;
    target job;
    performance nodes=2;
run;
proc print data=out2(obs=15);
run;
```

Output 23.2.1 shows the performance environment information.

Output 23.2.1 Performance Information

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	2
Number of Threads per Node	1

Output 23.2.2 shows the frequency information for each level of target variable JOB in the data set Sampsio.Hmeq and in the sample.

Output 23.2.2 Frequency Table

Stratified Sampling Frequency Table

Target Level	Number of Obs	Number of Sample
	279	28
Mgr	767	77
Office	948	95
Other	2388	239
ProfExe	1276	127
Sales	109	11
Self	193	19

Output 23.2.3 shows first 15 output sample observations which contain an indicator "_PARTIND_" to indicate whether the observation is selected to the sample (1) or not (0).

Output 23.2.3 Sample Output with Partition Indicator

Obs	JOB	REASON	LOAN	VALUE	DELINQ	DEROG	_ Part Ind_
1	Other	HomeImp	1100	39025	0	0	0
2	Other	HomeImp	1300	68400	2	0	0
3	Other	HomeImp	1500	16700	0	0	0
4			1500	.	.	.	0
5	Office	HomeImp	1700	112000	0	0	0
6	Other	HomeImp	1700	40320	0	0	0
7	Other	HomeImp	1800	57037	2	3	0
8	Other	HomeImp	1800	43034	0	0	0
9	Other	HomeImp	2000	46740	2	0	0
10	Sales	HomeImp	2000	62250	0	0	0
11			2000	.	.	.	0
12	Office	HomeImp	2000	29800	1	0	0
13	Other	HomeImp	2000	55000	0	0	0
14	Mgr		2000	87400	0	0	0
15	Other	HomeImp	2100	83850	1	0	0

Example 23.3: Running with Data on the SAS appliance

This example uses the same data set as is used in Example 23.1.

When the input data set resides on the SAS appliance, the SAS appliance performs all samplings, writes out a sample on the SAS appliance, and reports the frequency results back to the client. In the following statements, the input data resides in the MyLib library (which is a distributed data source), and the output data set is a distributed data set in the MyLib library. You can use PROC DATASETS to delete the output table if it already exists on the SAS appliance. The **ods output FreqTable=Freqtab;** statement saves the frequency table to a SAS data set called Freqtab on the client.

```
/*MyLib is a libname for a distributed data source
  In this case, the computation is automatically done
  on the SAS appliance.*/
option set=GRIDHOST       = "&GRIDHOST";
option set=GRIDINSTALLLOC = "&GRIDINSTALLLOC";
libname MyLib &LIBTYPE
        server  ="&GRIDDATASERVER"
        user    =&USER
        password=&PASSWORD
        database=&DATABASE;

proc datasets lib=Mylib nolist; delete out1;
run;
proc hpsample data=MyLib.hmeq out=MyLib.out1 samppct=10 seed=1;
    var loan value delinq derog;
    class job reason;
    target  job reason;
    ods output FreqTable=Freqtab;
run;
```

Output 23.3.1 shows the performance environment information.

Output 23.3.1 Performance Information

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed, alongside Greenplum
Number of Compute Nodes	32
Number of Threads per Node	1

Output 23.3.2 shows the number of observations in each stratum (constructed by a combination of the levels of each of the two targets) in the data set MyLib.Hmeq and in the sample.

Output 23.3.2 Frequency Table

Stratified Sampling1 Frequency Table

Target1 Level	Target2 Level
	DebtCon
	HomeImp
Mgr	
Mgr	DebtCon
Mgr	HomeImp
Office	
Office	DebtCon
Office	HomeImp
Other	
Other	DebtCon
Other	HomeImp
ProfExe	
ProfExe	DebtCon
ProfExe	HomeImp
Sales	DebtCon
Sales	HomeImp
Self	
Self	DebtCon
Self	HomeImp

Stratified Sampling1
Frequency Table

Number of Obs	Number of Sample
107	6
115	10
57	1
21	0
572	58
174	20
27	0
620	64
301	33
68	1
1604	164
716	73
24	0
847	87
405	43
97	5
12	0
5	0
73	2
115	11

Chapter 24
The HPSEVERITY Procedure

Contents

Overview: HPSEVERITY Procedure **594**
Getting Started: HPSEVERITY Procedure **595**
A Simple Example of Fitting Predefined Distributions 595
An Example with Left-Truncation and Right-Censoring 598
An Example of Modeling Regression Effects 603
Syntax: HPSEVERITY Procedure **607**
Functional Summary 607
PROC HPSEVERITY Statement 610
DIST Statement 616
LOSS Statement 618
NLOPTIONS Statement 620
PERFORMANCE Statement 624
SCALEMODEL Statement 625
WEIGHT Statement 626
Programming Statements (Experimental) 626
Details: HPSEVERITY Procedure **627**
Predefined Distributions 627
Censoring and Truncation 637
Parameter Estimation Method 638
Details of Optimization Algorithms 640
Parameter Initialization 642
Estimating Regression Effects 643
Empirical Distribution Function Estimation Methods 647
Statistics of Fit 653
Distributed and Multithreaded Computation 657
Defining a Severity Distribution Model with the FCMP Procedure 660
Predefined Utility Functions 672
Custom Objective Functions (Experimental) 677
Input Data Sets 680
Output Data Sets 681
Displayed Output 684
Examples: HPSEVERITY Procedure **686**
Example 24.1: Defining a Model for Gaussian Distribution 686
Example 24.2: Defining a Model for the Gaussian Distribution with a Scale Parameter 691
Example 24.3: Defining a Model for Mixed-Tail Distributions 696
Example 24.4: Fitting a Scaled Tweedie Model with Regressors 703

Example 24.5: Fitting Distributions to Interval-Censored Data 706
Example 24.6: Benefits of Distributed and Multithreaded Computing 708
Example 24.7: Estimating Parameters Using Cramér-von Mises Estimator 714
References **716**

Overview: HPSEVERITY Procedure

The HPSEVERITY procedure is a high-performance version of the SEVERITY procedure in SAS/ETS software. PROC HPSEVERITY estimates parameters of any arbitrary continuous probability distribution that is used to model the magnitude (severity) of a continuous-valued event of interest. Some examples of such events are loss amounts paid by an insurance company and demand of a product as depicted by its sales. PROC HPSEVERITY is especially useful when the severity of an event does not follow typical distributions (such as the normal distribution) that are often assumed by standard statistical methods.

PROC HPSEVERITY provides a default set of probability distribution models that includes the Burr, exponential, gamma, generalized Pareto, inverse Gaussian (Wald), lognormal, Pareto, Tweedie, and Weibull distributions. In the simplest form, you can estimate the parameters of any of these distributions by using a list of severity values that are recorded in a SAS data set. PROC HPSEVERITY computes the estimates of the model parameters, their standard errors, and their covariance structure by using the maximum likelihood method.

PROC HPSEVERITY can fit multiple distributions at the same time and choose the best distribution according to a specified selection criterion. Seven different statistics of fit can be used as selection criteria. They are log likelihood, Akaike's information criterion (AIC), corrected Akaike's information criterion (AICC), Schwarz Bayesian information criterion (BIC), Kolmogorov-Smirnov statistic (KS), Anderson-Darling statistic (AD), and Cramér-von Mises statistic (CvM).

You can request the procedure to output the status of the estimation process, the parameter estimates and their standard errors, the estimated covariance structure of the parameters, and the statistics of fit.

The following key features make PROC HPSEVERITY and PROC SEVERITY unique among SAS procedures that can estimate continuous probability distributions:

- Both procedures enable you to fit a distribution model when the severity values are truncated or censored or both. You can specify any combination of the following types of censoring and truncation effects: left-censoring, right-censoring, left-truncation, or right-truncation. This is especially useful in applications with an insurance-type model where a severity (loss) is reported and recorded only if it is greater than the deductible amount (left-truncation) and where a severity value greater than or equal to the policy limit is recorded at the limit (right-censoring). Another useful application is that of interval-censored data, where you know both the lower limit (right-censoring) and upper limit (left-censoring) on the severity, but you do not know the exact value.

  Both procedures use an appropriate estimator of the empirical distribution function (EDF). EDF is required to compute the KS, AD, and CvM statistics-of-fit. The procedures also provide the EDF estimates to your custom parameter initialization method. When truncation or censoring is specified, the EDF is estimated by using either Kaplan-Meier's product-limit estimator or Turnbull's estimator. The former is used by default when only one form of censoring effect (right-censoring or left-censoring)

is specified, whereas the latter is used by default when both left-censoring and right-censoring effects are specified.

- Both procedures enable you to define any arbitrary continuous parametric distribution model and to estimate its parameters. You just need to define the key components of the distribution, such as its probability density function (PDF) and cumulative distribution function (CDF), as a set of functions and subroutines written with the FCMP procedure, which is part of Base SAS software. As long as the functions and subroutines follow certain rules, the SEVERITY and HPSEVERITY procedures can fit the distribution model defined by them.
- Both procedures can model the effect of exogenous or regressor variables on a probability distribution, as long as the distribution has a scale parameter. A linear combination of the regressor variables is assumed to affect the scale parameter via an exponential link function.

  If a distribution does not have a scale parameter, then either it needs to have another parameter that can be derived from a scale parameter by using a supported transformation or it needs to be reparameterized to have a scale parameter. If neither of these is possible, then regression effects cannot be modeled.
- Both procedures enable you to specify your own objective function to be optimized for estimating the parameters of a model. You can write SAS programming statements to specify the contribution of each observation to the objective function. You can use keyword functions such as _PDF_ and _CDF_ to generalize the objective function to any distribution. If you do not specify your own objective function, then the parameters of a model are estimated by maximizing the likelihood function of the data.
- PROC HPSEVERITY employs multithreading and distributed processing to significantly reduce the time it takes to fit the distribution model. The PERFORMANCE statement enables you to control the threading and distributed processing parameters.

Getting Started: HPSEVERITY Procedure

This section outlines the use of the HPSEVERITY procedure to fit continuous probability distribution models. Three examples illustrate different features of the procedure.

A Simple Example of Fitting Predefined Distributions

The simplest way to use PROC HPSEVERITY is to fit all the predefined distributions to a set of values and let the procedure identify the best fitting distribution.

Consider a lognormal distribution, whose probability density function (PDF) f and cumulative distribution function (CDF) F are as follows, respectively, where Φ denotes the CDF of the standard normal distribution:

$$f(x;\mu,\sigma) = \frac{1}{x\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{\log(x)-\mu}{\sigma}\right)^2} \quad \text{and} \quad F(x;\mu,\sigma) = \Phi\left(\frac{\log(x)-\mu}{\sigma}\right)$$

The following DATA step statements simulate a sample from a lognormal distribution with population parameters $\mu = 1.5$ and $\sigma = 0.25$, and store the sample in the variable Y of a data set Work.Test_sev1:

```
/*------------- Simple Lognormal Example -------------*/
data test_sev1(keep=y label='Simple Lognormal Sample');
   call streaminit(45678);
   label y='Response Variable';
   Mu = 1.5;
   Sigma = 0.25;
   do n = 1 to 100;
      y = exp(Mu) * rand('LOGNORMAL')**Sigma;
      output;
   end;
run;
```

The following statements fit all the predefined distribution models to the values of Y and identify the best distribution according to the corrected Akaike's information criterion (AICC):

```
proc hpseverity data=test_sev1 crit=aicc;
   loss y;
   dist _predefined_;
run;
```

The PROC HPSEVERITY statement specifies the input data set along with the model selection criterion, the LOSS statement specifies the variable to be modeled, and the DIST statement with the _PREDEFINED_ keyword specifies that all the predefined distribution models be fitted.

Some of the default output displayed by this step is shown in Figure 24.1 through Figure 24.3. First, information about the input data set is displayed followed by the "Model Selection Table", as shown in Figure 24.1. The model selection table displays the convergence status, the value of the selection criterion, and the selection status for each of the candidate models. The Converged column indicates whether the estimation process for a given distribution model has converged, might have converged, or failed. The Selected column indicates whether a given distribution has the best fit for the data according to the selection criterion. For this example, the lognormal distribution model is selected, because it has the lowest value for the selection criterion.

Figure 24.1 Data Set Information and Model Selection Table

```
                    The HPSEVERITY Procedure

                         Input Data Set

                Name              WORK.TEST_SEV1
                Label    Simple Lognormal Sample
```

Figure 24.1 *continued*

Model Selection Table

Distribution	Converged	Corrected Akaike's Information Criterion	Selected
Burr	Yes	322.50845	No
Exp	Yes	508.12287	No
Gamma	Yes	320.50264	No
Igauss	Yes	319.61652	No
Logn	Yes	319.56579	Yes
Pareto	Yes	510.28172	No
Gpd	Yes	510.20576	No
Weibull	Yes	334.82373	No

Next, the estimation information for each of the candidate models is displayed. The information for the lognormal model, which is the best fitting model, is shown in Figure 24.2. The first table displays a summary of the distribution. The second table displays the convergence status. This is followed by a summary of the optimization process which indicates the technique used, the number of iterations, the number of times the objective function was evaluated, and the log likelihood attained at the end of the optimization. Since the model with lognormal distribution has converged, PROC HPSEVERITY displays its statistics of fit and parameter estimates. The estimates of *Mu*=1.49605 and *Sigma*=0.26243 are quite close to the population parameters of *Mu*=1.5 and *Sigma*=0.25 from which the sample was generated. The p-value for each estimate indicates the rejection of the null hypothesis that the estimate is 0, implying that both the estimates are significantly different from 0.

Figure 24.2 Estimation Details for the Lognormal Model

The HPSEVERITY Procedure

Distribution Information

Name	Logn
Description	Lognormal Distribution
Number of Distribution Parameters	2

Convergence Status for Logn Distribution

Convergence criterion (GCONV=1E-8) satisfied.

Optimization Summary for Logn Distribution

Optimization Technique	Trust Region
Number of Iterations	2
Number of Function Evaluations	8
Log Likelihood	-157.72104

Figure 24.2 *continued*

Fit Statistics for Logn Distribution

-2 Log Likelihood	315.44208
Akaike's Information Criterion	319.44208
Corrected Akaike's Information Criterion	319.56579
Schwarz's Bayesian Information Criterion	324.65242
Kolmogorov-Smirnov Statistic	0.50641
Anderson-Darling Statistic	0.31240
Cramer-von Mises Statistic	0.04353

Parameter Estimates for Logn Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Mu	1.49605	0.02651	56.43	<.0001
Sigma	0.26243	0.01874	14.00	<.0001

The parameter estimates of the Burr distribution are shown in Figure 24.3. These estimates are used in the next example.

Figure 24.3 Parameter Estimates for the Burr Model

Parameter Estimates for Burr Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Theta	4.62348	0.46181	10.01	<.0001
Alpha	1.15706	0.47493	2.44	0.0167
Gamma	6.41227	0.99039	6.47	<.0001

An Example with Left-Truncation and Right-Censoring

PROC HPSEVERITY enables you to specify that the response variable values are left-truncated or right-censored. The following DATA step expands the data set of the previous example to simulate a scenario that is typically encountered by an automobile insurance company. The values of the variable Y represent the loss values on claims that are reported to an auto insurance company. The variable THRESHOLD records the deductible on the insurance policy. If the actual value of Y is less than or equal to the deductible, then it is unobservable and does not get recorded. In other words, THRESHOLD specifies the left-truncation of Y. LIMIT records the policy limit. If the value of Y is equal to or greater than the recorded value, then the observation is right-censored.

```
/*----- Lognormal Model with left-truncation and censoring -----*/
data test_sev2(keep=y threshold limit
        label='A Lognormal Sample With Censoring and Truncation');
   set test_sev1;
   label y='Censored & Truncated Response';
   if _n_ = 1 then call streaminit(45679);

   /* make about 20% of the observations left-truncated */
   if (rand('UNIFORM') < 0.2) then
      threshold = y * (1 - rand('UNIFORM'));
   else
      threshold = .;
   /* make about 15% of the observations right-censored */
   iscens = (rand('UNIFORM') < 0.15);
   if (iscens) then
      limit = y;
   else
      limit = .;
run;
```

The following statements use the AICC criterion to analyze which of the four predefined distributions (lognormal, Burr, gamma, and Weibull) has the best fit for the data:

```
proc hpseverity data=test_sev2 crit=aicc print=all ;
   loss y / lt=threshold rc=limit;

   dist logn burr gamma weibull;
   performance nthreads=2;
run;
```

The LOSS statement specifies the left-truncation and right-censoring variables. Each candidate distribution needs to be specified by using a separate DIST statement. The PRINT= option in the PROC HPSEVERITY statement requests that all the displayed output be prepared. The NTHREADS option in the PERFORMANCE statement specifies that two threads of computation be used. The option is shown here just for illustration. You should use it only when you want to restrict the procedure to use a different number of threads than the value of the CPUCOUNT= system option, which typically defaults to the number of physical CPU cores available on your machine, thereby allowing the procedure to fully utilize the computational power of your machine.

Some of the key results prepared by PROC HPSEVERITY are shown in Figure 24.4 through Figure 24.7. In addition to the estimates of the range, mean, and standard deviation of Y, the "Descriptive Statistics for Variable y" table shown in Figure 24.4 also indicates the number of observations that are left-truncated or right-censored. The "Model Selection Table" in Figure 24.4 shows that models with all the candidate distributions have converged and that the Logn (lognormal) model has the best fit for the data according to the AICC criterion.

Figure 24.4 Summary Results for the Truncated and Censored Data

The HPSEVERITY Procedure

Input Data Set

Name	WORK.TEST_SEV2
Label	A Lognormal Sample With Censoring and Truncation

Descriptive Statistics for Variable y

Number of Observations	100
Number of Observations Used for Estimation	100
Minimum	2.30264
Maximum	8.34116
Mean	4.62007
Standard Deviation	1.23627
Number of Left Truncated Observations	23
Number of Right Censored Observations	14

Model Selection Table

Distribution	Converged	Corrected Akaike's Information Criterion	Selected
Logn	Yes	298.92672	Yes
Burr	Yes	302.66229	No
Gamma	Yes	299.45293	No
Weibull	Yes	309.26779	No

PROC HPSEVERITY also prepares a table that shows all the fit statistics for all the candidate models. It is useful to see which model would be the best fit according to each of the criteria. The "All Fit Statistics Table" prepared for this example is shown in Figure 24.5. It indicates that the lognormal model is chosen by all the criteria.

Figure 24.5 Comparing All Statistics of Fit for the Truncated and Censored Data

All Fit Statistics Table

Distribution	-2 Log Likelihood	AIC	AICC	BIC	KS
Logn	294.80301*	298.80301*	298.92672*	304.01335*	0.51824*
Burr	296.41229	302.41229	302.66229	310.22780	0.66984
Gamma	295.32921	299.32921	299.45293	304.53955	0.62511
Weibull	305.14408	309.14408	309.26779	314.35442	0.93307

All Fit Statistics Table

Distribution	AD	CvM
Logn	0.34736*	0.05159*
Burr	0.36712	0.05726
Gamma	0.42921	0.05526
Weibull	1.40699	0.17465

Specifying Initial Values for Parameters

All the predefined distributions have parameter initialization functions built into them. For the current example, Figure 24.6 shows the initial values that are obtained by the predefined method for the Burr distribution. It also shows the summary of the optimization process and the final parameter estimates.

Figure 24.6 Burr Model Summary for the Truncated and Censored Data

Initial Parameter Values and Bounds for Burr Distribution

Parameter	Initial Value	Lower Bound	Upper Bound
Theta	4.78102	1.05367E-8	Infty
Alpha	2.00000	1.05367E-8	Infty
Gamma	2.00000	1.05367E-8	Infty

Optimization Summary for Burr Distribution

Optimization Technique	Trust Region
Number of Iterations	8
Number of Function Evaluations	23
Log Likelihood	-148.20614

Figure 24.6 *continued*

Parameter Estimates for Burr Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Theta	4.76980	0.62492	7.63	<.0001
Alpha	1.16363	0.58859	1.98	0.0509
Gamma	5.94081	1.05004	5.66	<.0001

You can specify a different set of initial values if estimates are available from fitting the distribution to similar data. For this example, the parameters of the Burr distribution can be initialized with the final parameter estimates of the Burr distribution that were obtained in the first example (shown in Figure 24.3). One of the ways in which you can specify the initial values is as follows:

```
/*------ Specifying initial values using INIT= option -------*/
proc hpseverity data=test_sev2 crit=aicc print=all;
   loss y / lt=threshold rc=limit;

   dist burr(init=(theta=4.62348 alpha=1.15706 gamma=6.41227));
   performance nthreads=2;
run;
```

The names of the parameters specified in the INIT option must match the names used in the definition of the distribution. The results obtained with these initial values are shown in Figure 24.7. These results indicate that new set of initial values causes the optimizer to reach the same solution with fewer iterations and function evaluations as compared to the default initialization.

Figure 24.7 Burr Model Optimization Summary for the Truncated and Censored Data

The HPSEVERITY Procedure

Optimization Summary for Burr Distribution

Optimization Technique	Trust Region
Number of Iterations	5
Number of Function Evaluations	16
Log Likelihood	−148.20614

Parameter Estimates for Burr Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Theta	4.76980	0.62492	7.63	<.0001
Alpha	1.16363	0.58859	1.98	0.0509
Gamma	5.94081	1.05004	5.66	<.0001

An Example of Modeling Regression Effects

Consider a scenario in which the magnitude of the response variable might be affected by some regressor (exogenous or independent) variables. The HPSEVERITY procedure enables you to model the effect of such variables on the distribution of the response variable via an exponential link function. In particular, if you have k random regressor variables denoted by x_j $(j = 1, \ldots, k)$, then the distribution of the response variable Y is assumed to have the form

$$Y \sim \exp(\sum_{j=1}^{k} \beta_j x_j) \cdot \mathcal{F}(\Theta)$$

where $\mathcal{F}$ denotes the distribution of Y with parameters Θ and $\beta_j (j = 1, \ldots, k)$ denote the regression parameters (coefficients).

For the effective distribution of Y to be a valid distribution from the same parametric family as $\mathcal{F}$, it is necessary for $\mathcal{F}$ to have a scale parameter. The effective distribution of Y can be written as

$$Y \sim \mathcal{F}(\theta, \Omega)$$

where θ denotes the scale parameter and Ω denotes the set of nonscale parameters. The scale θ is affected by the regressors as

$$\theta = \theta_0 \cdot \exp(\sum_{j=1}^{k} \beta_j x_j)$$

where θ_0 denotes a *base* value of the scale parameter.

Given this form of the model, PROC HPSEVERITY allows a distribution to be a candidate for modeling regression effects only if it has an untransformed or a log-transformed scale parameter.

All the predefined distributions, except the lognormal distribution, have a direct scale parameter (that is, a parameter that is a scale parameter without any transformation). For the lognormal distribution, the parameter μ is a log-transformed scale parameter. This can be verified by replacing μ with a parameter $\theta = e^{\mu}$, which results in the following expressions for the PDF f and the CDF F in terms of θ and σ, respectively, where Φ denotes the CDF of the standard normal distribution:

$$f(x; \theta, \sigma) = \frac{1}{x\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{\log(x)-\log(\theta)}{\sigma}\right)^2} \quad \text{and} \quad F(x; \theta, \sigma) = \Phi\left(\frac{\log(x) - \log(\theta)}{\sigma}\right)$$

With this parameterization, the PDF satisfies the $f(x; \theta, \sigma) = \frac{1}{\theta} f(\frac{x}{\theta}; 1, \sigma)$ condition and the CDF satisfies the $F(x; \theta, \sigma) = F(\frac{x}{\theta}; 1, \sigma)$ condition. This makes θ a scale parameter. Hence, $\mu = \log(\theta)$ is a log-transformed scale parameter and the lognormal distribution is eligible for modeling regression effects.

The following DATA step simulates a lognormal sample whose scale is decided by the values of the three regressors X1, X2, and X3 as follows:

$$\mu = \log(\theta) = 1 + 0.75\ \mathrm{X1} - \mathrm{X2} + 0.25\ \mathrm{X3}$$

```
/*----------- Lognormal Model with Regressors ------------*/
data test_sev3(keep=y x1-x3
               label='A Lognormal Sample Affected by Regressors');
   array x{*} x1-x3;
   array b{4} _TEMPORARY_ (1 0.75 -1 0.25);
   call streaminit(45678);
   label y='Response Influenced by Regressors';
   Sigma = 0.25;
   do n = 1 to 100;
      Mu = b(1); /* log of base value of scale */
      do i = 1 to dim(x);
         x(i) = rand('UNIFORM');
         Mu = Mu + b(i+1) * x(i);
      end;
      y = exp(Mu) * rand('LOGNORMAL')**Sigma;
      output;
   end;
run;
```

The following PROC HPSEVERITY step fits the lognormal, Burr, and gamma distribution models to this data. The regressors are specified in the SCALEMODEL statement.

```
proc hpseverity data=test_sev3 crit=aicc print=all;
   loss y;
   scalemodel x1-x3;

   dist logn burr gamma;
run;
```

Some of the key results prepared by PROC HPSEVERITY are shown in Figure 24.8 through Figure 24.12. The descriptive statistics of all the variables are shown in Figure 24.8.

Figure 24.8 Summary Results for the Regression Example

The HPSEVERITY Procedure

Input Data Set

Name	WORK.TEST_SEV3
Label	A Lognormal Sample Affected by Regressors

Descriptive Statistics for Variable y

Number of Observations	100
Number of Observations Used for Estimation	100
Minimum	1.17863
Maximum	6.65269
Mean	2.99859
Standard Deviation	1.12845

Figure 24.8 *continued*

Descriptive Statistics for the Regressor Variables

Variable	N	Minimum	Maximum	Mean	Standard Deviation
x1	100	0.0005115	0.97971	0.51689	0.28206
x2	100	0.01883	0.99937	0.47345	0.28885
x3	100	0.00255	0.97558	0.48301	0.29709

The comparison of the fit statistics of all the models is shown in Figure 24.9. It indicates that the lognormal model is the best model according to each of the likelihood-based statistics.

Figure 24.9 Comparison of Statistics of Fit for the Regression Example

All Fit Statistics Table

Distribution	−2 Log Likelihood	AIC	AICC	BIC	KS
Logn	187.49609*	197.49609*	198.13439*	210.52194*	1.97544
Burr	190.69154	202.69154	203.59476	218.32256	2.09334
Gamma	188.91483	198.91483	199.55313	211.94069	1.94472*

All Fit Statistics Table

Distribution	AD	CvM
Logn	17.24618	1.21665
Burr	13.93436*	1.28529
Gamma	15.84787	1.17617*

The distribution information and the convergence results of the lognormal model are shown in Figure 24.10. The iteration history gives you a summary of how the optimizer is traversing the surface of the log-likelihood function in its attempt to reach the optimum. Both the change in the log likelihood and the maximum gradient of the objective function with respect to any of the parameters typically approach 0 if the optimizer converges.

Figure 24.10 Convergence Results for the Lognormal Model with Regressors

The HPSEVERITY Procedure

Distribution Information

Name	Logn
Description	Lognormal Distribution
Number of Distribution Parameters	2
Number of Regression Parameters	3

Figure 24.10 *continued*

Convergence Status for Logn Distribution

Convergence criterion (GCONV=1E-8) satisfied.

Optimization Iteration History for Logn Distribution

Iter	Number of Function Evaluations	Log Likelihood	Change in Log Likelihood	Maximum Gradient
0	2	-93.75285	.	-6.16002
1	4	-93.74805	0.0048055	-0.11031
2	6	-93.74805	1.50188E-6	-0.0000338
3	10	-93.74805	1.4211E-13	-3.112E-12

Optimization Summary for Logn Distribution

Optimization Technique	Trust Region
Number of Iterations	3
Number of Function Evaluations	10
Log Likelihood	-93.74805

The final parameter estimates of the lognormal model are shown in Figure 24.11. All the estimates are significantly different from 0. The estimate that is reported for the parameter *Mu* is the base value for the log-transformed scale parameter μ. Let $x_i (1 \leq i \leq 3)$ denote the observed value for regressor X*i*. If the lognormal distribution is chosen to model Y, then the effective value of the parameter μ varies with the observed values of regressors as

$$\mu = 1.04047 + 0.65221\, x_1 - 0.91116\, x_2 + 0.16243\, x_3$$

These estimated coefficients are reasonably close to the population parameters (that is, within one or two standard errors).

Figure 24.11 Parameter Estimates for the Lognormal Model with Regressors

Parameter Estimates for Logn Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Mu	1.04047	0.07614	13.66	<.0001
Sigma	0.22177	0.01609	13.78	<.0001
x1	0.65221	0.08167	7.99	<.0001
x2	-0.91116	0.07946	-11.47	<.0001
x3	0.16243	0.07782	2.09	0.0395

The estimates of the gamma distribution model, which is the next best model according to the fit statistics, are shown in Figure 24.12. The estimate that is reported for the parameter *Theta* is the base value for the

scale parameter θ. If the gamma distribution is chosen to model Y, then the effective value of the scale parameter is $\theta = 0.14293 \exp(0.64562\, x_1 - 0.89831\, x_2 + 0.14901\, x_3)$.

Figure 24.12 Parameter Estimates for the Gamma Model with Regressors

Parameter Estimates for Gamma Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Theta	0.14293	0.02329	6.14	<.0001
Alpha	20.37726	2.93277	6.95	<.0001
x1	0.64562	0.08224	7.85	<.0001
x2	-0.89831	0.07962	-11.28	<.0001
x3	0.14901	0.07870	1.89	0.0613

Syntax: HPSEVERITY Procedure

The following statements are available in the HPSEVERITY procedure:

PROC HPSEVERITY *options* ;
  LOSS < *response-variable* > < / *censoring-truncation-options* > ;
  WEIGHT *weight-variable* ;
  SCALEMODEL *regressor-variable-list* < / *scalemodel-option* > ;
  DIST *distribution-name-or-keyword* < *(distribution-option)* < *distribution-name-or-keyword* < *(distribution-option)* > > ... > < / *preprocess-options* > ;
  NLOPTIONS *options* ;
  PERFORMANCE *options* ;
  Programming statements ;

Functional Summary

Table 24.1 summarizes the statements and options that control the HPSEVERITY procedure.

Table 24.1 HPSEVERITY Functional Summary

Description	Statement	Option
Statements		
Specifies the response variable to model along with censoring and truncation effects	LOSS	
Specifies the weight variable	WEIGHT	
Specifies the regression variables to model	SCALEMODEL	
Specifies distributions to fit	DIST	
Specifies optimization options	NLOPTIONS	

Table 24.1 *continued*

Description	Statement	Option
Specifies performance options	PERFORMANCE	
Specifies programming statements that define an objective function	Programming statements	
Data Set Options		
Specifies that the OUTEST= data set contain covariance estimates	PROC HPSEVERITY	COVOUT
Specifies the input data set	PROC HPSEVERITY	DATA=
Specifies the input data set for parameter estimates	PROC HPSEVERITY	INEST=
Specifies the output data set for parameter estimates	PROC HPSEVERITY	OUTEST=
Specifies the output data set for model information	PROC HPSEVERITY	OUTMODELINFO=
Specifies the output data set for statistics of fit	PROC HPSEVERITY	OUTSTAT=
Data Interpretation Options		
Specifies left-censoring	LOSS	LEFTCENSORED=
Specifies left-truncation	LOSS	LEFTTRUNCATED=
Specifies right-censoring	LOSS	RIGHTCENSORED=
Specifies right-truncation	LOSS	RIGHTTRUNCATED=
Model Estimation Options		
Specifies the model selection criterion	PROC HPSEVERITY	CRITERION=
Specifies the method for computing mixture distribution	SCALEMODEL	DFMIXTURE=
Specifies initial values for model parameters	DIST	INIT=
Specifies the objective function symbol	PROC HPSEVERITY	OBJECTIVE=
Specifies the optimization technique	NLOPTIONS	TECHNIQUE=
Specifies the denominator for computing covariance estimates	PROC HPSEVERITY	VARDEF=
Optimization Termination Criteria		
Absolute function value criterion	NLOPTIONS	ABSCONV=
Absolute function difference convergence criterion	NLOPTIONS	ABSFCONV=
Absolute gradient convergence criterion	NLOPTIONS	ABSGCONV=
Absolute parameter convergence criterion	NLOPTIONS	ABSXCONV=
Relative function convergence criterion	NLOPTIONS	FCONV=
Another relative function convergence criterion	NLOPTIONS	FCONV2=
Used in FCONV, GCONV criterion	NLOPTIONS	FSIZE=
Relative gradient convergence criterion	NLOPTIONS	GCONV=
Maximum number of function calls	NLOPTIONS	MAXFUNC=
Maximum number of iterations	NLOPTIONS	MAXITER=
Upper limit on CPU time in seconds	NLOPTIONS	MAXTIME=

Table 24.1 *continued*

Description	Statement	Option
Minimum number of iterations	NLOPTIONS	MINITER=
Relative parameter convergence criterion	NLOPTIONS	XCONV=
Used in XCONV criterion	NLOPTIONS	XSIZE=
Empirical Distribution Function (EDF) Estimation Options		
Specifies the nonparametric method of CDF estimation	PROC HPSEVERITY	EMPIRICALCDF=
Specifies the sample to be used for computing the EDF estimates	PROC HPSEVERITY	INITSAMPLE
EMPIRICALCDF=MODIFIEDKM Options		
Specifies the α value for the lower bound on risk set size	PROC HPSEVERITY	ALPHA=
Specifies the c value for the lower bound on risk set size	PROC HPSEVERITY	C=
Specifies the absolute lower bound on risk set size	PROC HPSEVERITY	RSLB=
EMPIRICALCDF=TURNBULL Options		
Specifies that the final EDF estimates be maximum likelihood estimates	PROC HPSEVERITY	ENSUREMLE
Specifies the relative convergence criterion	PROC HPSEVERITY	EPS=
Specifies the maximum number of iterations	PROC HPSEVERITY	MAXITER=
Specifies the threshold below which an EDF estimate is deemed to be 0	PROC HPSEVERITY	ZEROPROB=
Displayed Output Options		
Specifies that distributions be listed to the log without estimating any models that use them	DIST	LISTONLY
Suppresses all displayed output	PROC HPSEVERITY	NOPRINT
Specifies which output to display	PROC HPSEVERITY	PRINT=
Specifies the verbosity of messages printed to the log	PROC HPSEVERITY	VERBOSE=
Specifies that distributions be validated without estimating any models that use them	DIST	VALIDATEONLY

PROC HPSEVERITY Statement

PROC HPSEVERITY *options* **;**

The PROC HPSEVERITY statement invokes the procedure. You can specify two types of *options* in the PROC HPSEVERITY statement. One set of *options* controls input and output. The other set of *options* controls the model estimation and selection process.

The following *options* control the input data sets used by PROC HPSEVERITY and various forms of output generated by PROC HPSEVERITY. The *options* are listed in alphabetical order:

COVOUT
specifies that the OUTEST= data set contain the estimate of the covariance structure of the parameters. This option has no effect if the OUTEST= option is not specified. For more information about how the covariance is reported in the OUTEST= data set, see the section "OUTEST= Data Set" on page 681.

DATA=*SAS-data-set*
names the input data set. If the DATA= option is not specified, then the most recently created SAS data set is used.

INEST=*SAS-data-set*
names the input data set that contains the initial values of the parameter estimates to start the optimization process. The initial values specified in the INIT= option in the DIST statement take precedence over any initial values specified in this data set. For more information about the variables in this data set, see the section "INEST= Data Set" on page 680.

INITSAMPLE (*initsample-option***)**
INITSAMPLE (*initsample-option . . . initsample-option***)**
specifies that a sample of the input data be used for initializing the distribution parameters. If you specify more than one *initsample-option*, then separate them with spaces.

When you do not specify initial values for the distribution parameters, PROC HPSEVERITY needs to compute the empirical distribution function (EDF) estimates as part of the default method for parameter initialization. The EDF estimation process can be expensive, especially when you specify censoring or truncation effects for the loss variable. Furthermore, it is not amenable to parallelism due to the sequential nature of the algorithm for truncation effects. You can use the INITSAMPLE option to specify that only a fraction of the input data be used in order to reduce the time taken to compute the EDF estimates. PROC HPSEVERITY uses the uniform random sampling method to select the sample, the size and randomness of which is controlled by the following *initsample-options*:

FRACTION=*number*
specifies the fraction, between 0 and 1, of the input data to be used for sampling.

SEED=*number*
specifies the seed to be used for the uniform random number generator. This option enables you to select the same sample from the same input data across different runs of PROC HPSEVERITY, which can be useful for replicating the results across different runs. If you do not specify the seed value, PROC HPSEVERITY generates a seed that is based on the system clock.

SIZE=*number*
specifies the size of the sample. If the data are distributed across different nodes, then this size applies to the sample that is prepared at each node. For example, let the input data set of size 100,000 observations be distributed across 10 nodes such that each node has 10,000 observations. If you specify SIZE=1000, then each node computes a local EDF estimate by using a sample of size 1,000 selected randomly from its 10,000 observations. If you specify both of the SIZE= and FRACTION= options, then the value specified in the SIZE= option is used and the FRACTION= option is ignored.

If you do not specify the INITSAMPLE option, then a uniform random sample of at most 10,000 observations is used for EDF estimation.

NOPRINT
turns off all displayed output. If specified, any value specified for the PRINT= option is ignored.

OUTEST=*SAS-data-set*
names the output data set to contain estimates of the parameter values and their standard errors for each model whose parameter estimation process converges. For more information about the variables in this data set, see the section "OUTEST= Data Set" on page 681.

OUTMODELINFO=*SAS-data-set*
names the output data set to contain the status of each fitted model. The status information includes the convergence status of the optimization process that is used to estimate the parameters, the status of estimating the covariance matrix, and whether a model is the best according to the specified selection criterion. For more information about the variables in this data set, see the section "OUTMODELINFO= Data Set" on page 682.

OUTSTAT=*SAS-data-set*
names the output data set to contain the values of statistics of fit for each model whose parameter estimation process converges. For more information about the variables in this data set, see the section "OUTSTAT= Data Set" on page 683.

PRINT <(*global-display-option***)> <=***display-option***>**

PRINT <(*global-display-option***)> <= (***display-option . . . display-option***) >**
specifies the desired displayed output. If you specify more than one *display-option*, then separate them with spaces and enclose them in parentheses.

The following *global-display-option* is available:

ONLY
turns off the default displayed output and displays only the requested output.

The following *display-options* are available:

ALL
displays all the output.

ALLFITSTATS
displays the comparison of all the statistics of fit for all the models in one table. The table does not include the models whose parameter estimation process does not converge.

CONVSTATUS
displays the convergence status of the parameter estimation process.

DESCSTATS
displays the descriptive statistics for the response variable and the regressor variables, if they are specified.

DISTINFO
displays the information about each specified distribution. For each distribution, the information includes the name, description, validity status, and number of distribution parameters.

ESTIMATES

PARMEST
displays the final estimates of parameters. The estimates are not displayed for models whose parameter estimation process does not converge.

ESTIMATIONDETAILS
displays the details of the estimation process for all the models in one table.

INITIALVALUES
displays the initial values and bounds used for estimating each model.

NLOHISTORY
displays the iteration history of the nonlinear optimization process used for estimating the parameters.

NLOSUMMARY
displays the summary of the nonlinear optimization process used for estimating the parameters.

NONE
displays none of the output. If specified, this option overrides all the other display options. The default displayed output is also suppressed.

SELECTION

SELECT
displays the model selection table.

STATISTICS

FITSTATS
displays the statistics of fit for each model. The statistics of fit are not displayed for models whose parameter estimation process does not converge.

If the PRINT= option is not specified or the ONLY *global-display-option* is not specified, then the default displayed output is equivalent to specifying PRINT=(SELECTION CONVSTATUS NLOSUMMARY STATISTICS ESTIMATES).

VARDEF=*option*
specifies the denominator to use for computing the covariance estimates. You can specify one of the following values for *option*:

DF
specifies that the number of nonmissing observations minus the model degrees of freedom (number of parameters) be used.

N
specifies that the number of nonmissing observations be used.

For more information about the covariance estimation, see the section "Estimating Covariance and Standard Errors" on page 639.

VERBOSE=*verbosity-level*
specifies the amount of messages printed to the SAS log by PROC HPSEVERITY. A higher number prints messages with the same or more detail.

The following *options* control the model estimation and selection process:

CRITERION=*criterion-option*

CRITERIA=*criterion-option*

CRIT=*criterion-option*
specifies the model selection criterion.

If two or more models are specified for estimation, then the one with the best value for the selection criterion is chosen as the best model. If the OUTMODELINFO= data set is specified, then the best model's observation has a value of 1 for the _SELECTED_ variable. You can specify one of the following *criterion-options*:

AD
specifies the Anderson-Darling (AD) statistic value, which is computed by using the empirical distribution function (EDF) estimate, as the selection criterion. A lower value is deemed better.

AIC
specifies Akaike's information criterion (AIC) as the selection criterion. A lower value is deemed better.

AICC
specifies the finite-sample corrected Akaike's information criterion (AICC) as the selection criterion. A lower value is deemed better.

BIC
specifies the Schwarz Bayesian information criterion (BIC) as the selection criterion. A lower value is deemed better.

CUSTOM
specifies the custom objective function as the selection criterion. You can specify this only if you also specify the OBJECTIVE= option. A lower value is deemed better.

CVM
specifies the Cramér-von Mises (CvM) statistic value, which is computed by using the empirical distribution function (EDF) estimate, as the selection criterion. A lower value is deemed better.

KS

specifies the Kolmogorov-Smirnov (KS) statistic value, which is computed by using the empirical distribution function (EDF) estimate, as the selection criterion. A lower value is deemed better.

LOGLIKELIHOOD

LL

specifies $-2 * \log(L)$ as the selection criterion, where L is the likelihood of the data. A lower value is deemed better. This is the default.

For more information about these *criterion-options*, see the section "Statistics of Fit" on page 653.

EMPIRICALCDF | EDF=*method*

specifies the method to use for computing the nonparametric or empirical estimate of the cumulative distribution function of the data. You can specify one of the following values for *method*:

AUTOMATIC | AUTO

specifies that the method be chosen automatically based on the data specification.

If you do not specify any censoring or truncation, then the standard empirical estimation method (STANDARD) is chosen. If you specify both right-censoring and left-censoring, then Turnbull's estimation method (TURNBULL) is chosen. For all other combinations of censoring and truncation, the Kaplan-Meier method (KAPLANMEIER) is chosen.

KAPLANMEIER | KM

specifies that the product limit estimator proposed by Kaplan and Meier (1958) be used. Specification of this method has no effect when both right-censoring and left-censoring are specified.

MODIFIEDKM | MKM <(*options***)>**

specifies that the modified product limit estimator be used. Specification of this method has no effect when both right-censoring and left-censoring are specified.

This method allows Kaplan-Meier's product limit estimates to be more robust by ignoring the contributions to the estimate due to small risk-set sizes. The risk set is the set of observations at the risk of failing, where an observation is said to fail if it has not been processed yet and might experience censoring or truncation. The minimum risk-set size that makes it eligible to be included in the estimation can be specified either as an absolute lower bound on the size (RSLB= option) or a relative lower bound determined by the formula cn^{α} proposed by Lai and Ying (1991). Values of c and α can be specified by using the C= and ALPHA= options, respectively. By default, the relative lower bound is used with values of $c = 1$ and $\alpha = 0.5$. However, you can modify the default by using the following *options*:

ALPHA | A=*number*

specifies the value to use for α when the lower bound on the risk set size is defined as cn^{α}. This value must satisfy $0 < \alpha < 1$.

C=*number*

specifies the value to use for c when the lower bound on the risk set size is defined as cn^{α}. This value must satisfy $c > 0$.

RSLB=*number*
specifies the absolute lower bound on the risk set size to be included in the estimate.

NOTURNBULL
specifies that the method be chosen automatically based on the data specification and that Turnbull's method not be used. This is the default.

This method first replaces each left-censored or interval-censored observation with an uncensored observation. If the resulting set of observations has any truncated or right-censored observations, then the Kaplan-Meier method (KAPLANMEIER) is chosen. Otherwise, the standard empirical estimation method (STANDARD) is chosen. The observations are modified only for the purpose of computing the EDF estimates; the modification does not affect the parameter estimation process.

STANDARD | STD
specifies that the standard empirical estimation method be used. This ignores any censoring or truncation information even if specified, and can thus result in estimates that are more biased than those obtained with other methods more suitable for such data. Specification of this method has no effect when both right-censoring and left-censoring are specified.

TURNBULL | EM <(*options***)>** (Experimental)
specifies that the Turnbull's method be used. An iterative expectation-maximization (EM) algorithm proposed by Turnbull (1976) is used to compute the empirical estimates. If truncation is also specified, then the modification suggested by Frydman (1994) is used.

This method is used if both right-censoring and left-censoring are specified and if you have explicitly specified the EMPIRICALCDF=TURNBULL option.

You can modify the default behavior of the EM algorithm by using the following *options*:

ENSUREMLE
specifies that the final EDF estimates be maximum likelihood estimates. The Kuhn-Tucker conditions are computed for the likelihood maximization problem and checked to ensure that EM algorithm converges to maximum likelihood estimates. The method generalizes the method proposed by Gentleman and Geyer (1994) by taking into account the truncation information, if specified.

EPS=*number*
specifies the maximum relative error to be allowed between estimates of two consecutive iterations. This criterion is used to check the convergence of the algorithm. If you do not specify this option, then PROC HPSEVERITY uses a default value of 1.0E–8.

MAXITER=*number*
specifies the maximum number of iterations to attempt to find the empirical estimates. If you do not specify this option, then PROC HPSEVERITY uses a default value of 500.

ZEROPROB=*number*
specifies the threshold below which an empirical estimate of the probability is considered zero. This option is used to decide if the final estimate is a maximum likelihood estimate. This option does not have an effect if you do not specify the ENSUREMLE option. If you specify the ENSUREMLE option, but do not specify this option, then PROC HPSEVERITY uses a default value of 1.0E–8.

For more information about each of the methods, see the section "Empirical Distribution Function Estimation Methods" on page 647.

OBJECTIVE=*symbol-name* (Experimental)
names the symbol that represents the objective function in the specified SAS programming statements. For each model to be estimated, PROC HPSEVERITY executes the programming statements to compute the value of this symbol for each observation. The values are added across all observations to obtain the value of the objective function. The optimization algorithm estimates the model parameters such that the objective function value is *minimized*. A separate optimization problem is solved for each candidate distribution.

For more information about writing SAS programming statements to define your own objective function, see the section "Custom Objective Functions (Experimental)" on page 677.

DIST Statement

DIST *distribution-name-or-keyword* < *(distribution-option)* > < *distribution-name-or-keyword* < *(distribution-option)* > > ... **;**

The DIST statement specifies candidate distributions to be estimated by the HPSEVERITY procedure. You can specify multiple DIST statements, and each statement can contain one or more distribution specifications.

For your convenience, PROC HPSEVERITY provides the following 10 different predefined distributions (the name in the parentheses is the name to use in the DIST statement): Burr (BURR), exponential (EXP), gamma (GAMMA), generalized Pareto (GPD), inverse Gaussian or Wald (IGAUSS), lognormal (LOGN), Pareto (PARETO), Tweedie (TWEEDIE), scaled Tweedie (STWEEDIE), and Weibull (WEIBULL). These are described in detail in the section "Predefined Distributions" on page 627.

You can specify any of the predefined distributions or any distribution that you have defined. If the specified distribution is not a predefined distribution, then you must submit the CMPLIB= system option with appropriate libraries before you submit the PROC HPSEVERITY step to enable the procedure to find the functions associated with your distribution. The predefined distributions are defined in the Sashelp.Hpsevdst library. However, you are not required to specify this library in the CMPLIB= system option.

As a convenience, you can also use a shortcut keyword to indicate a list of distributions. You can specify one or more of the following keywords:

ALL
specifies all the predefined distributions and the distributions that you have defined in the libraries that are specified in the CMPLIB= system option. In addition to the eight predefined distributions included by the _PREDEFINED_ keyword, this list also includes the Tweedie and scaled Tweedie distributions that are defined in the Sashelp.Hpsevdst library.

PREDEFINED
specifies the list of eight predefined distributions: BURR, EXP, GAMMA, GPD, IGAUSS, LOGN, PARETO, and WEIBULL. Although the TWEEDIE and STWEEDIE distributions are available in the Sashelp.Hpsevdst library along with these eight distributions, they are not included by this keyword. If you want to fit the TWEEDIE and STWEEDIE distributions, then you must specify them explicitly or use the _ALL_ keyword.

USER
specifies the list of all the distributions that you have defined in the libraries that are specified in the CMPLIB= system option. This list does not include the distributions defined in the Sashelp.Hpsevdst library, even if you have specified Sashelp.Hpsevdst in the CMPLIB= option.

The use of these keywords, especially _ALL_, can result in a large list of distributions, which might take a longer time to estimate. A warning is printed to the SAS log if the number of total distribution models to estimate exceeds 10.

The following *distribution-option* values can be used in the DIST statement for a distribution name that is not a shortcut keyword:

INIT=*(name=value . . . name=value)*
specifies the initial values to be used for the distribution parameters to start the parameter estimation process. The values must be specified by parameter names. The parameter names must match the names used in the model definition. For example, let a model M's definition contain a M_PDF function with following signature:

```
function M_PDF(x, alpha, beta);
```

For this model, the names **alpha** and **beta** must be used for the INIT option. The names are case-insensitive. If you do not specify initial values for some parameters in the INIT statement, then a default value of 0.001 is assumed for those parameters. If you specify an incorrect parameter, PROC HPSEVERITY prints a warning to the SAS log and does not fit the model. All specified values must be nonmissing.

If you are modeling regression effects, then the initial value of the first distribution parameter (**alpha** in the preceding example) should be the initial *base* value of the scale parameter or log-transformed scale parameter. For more information, see the section "Estimating Regression Effects" on page 643.

The use of INIT= option is one of the three methods available for initializing the parameters. For more information, see the section "Parameter Initialization" on page 642. If none of the initialization methods is used, then PROC HPSEVERITY initializes all parameters to 0.001.

You can specify the following *preprocess-options* in the DIST statement:

LISTONLY
specifies that the list of all candidate distributions be printed to the SAS log without doing any further processing on them. This option is especially useful when you use a shortcut keyword to include a list of distributions. It enables you to find out which distributions are included by the keyword.

VALIDATEONLY
specifies that all candidate distributions be checked for validity without doing any further processing on them. If a distribution is invalid, the reason for invalidity is written to the SAS log. If all distributions are valid, then the distribution information is written to the SAS log. The information includes name, description, validity status (valid or invalid), and number of distribution parameters. The information is not written to the SAS log if you have specified an OUTMODELINFO= data set or the PRINT=DISTINFO or PRINT=ALL option in the PROC HPSEVERITY statement. This option is especially useful when you specify your own distributions or when you specify the _USER_ or _ALL_ keywords in the DIST statement. It enables you to check whether your custom distribution

definitions satisfy PROC HPSEVERITY's requirements for the specified modeling task. It is recommended that you specify the SCALEMODEL statement if you intend to fit a model with regression effects, because the SCALEMODEL statement instructs PROC HPSEVERITY to perform additional checks to validate whether regression effects can be modeled on each candidate distribution.

LOSS Statement

LOSS < *response-variable-name* > < / *censoring-truncation-options* > **;**

The LOSS statement specifies the name of the response or loss variable whose distribution needs to be modeled. You can also specify additional options to indicate any truncation or censoring of the response. The specification of response variable is optional if at least one type of censoring is specified. You must specify a response variable if no censoring is specified. If you specify more than one LOSS statement, then the first statement is used.

All the analysis variables specified in this statement must be present in the input data set that is specified by using the DATA= option in the PROC HPSEVERITY statement. The response variable is expected to have nonmissing values. If the variable has a missing value in an observation, then a warning is written to the SAS log and that observation is ignored.

The following *censoring-truncation-options* can be used in the LOSS statement:

LEFTCENSORED=*variable-name*

LC=*variable-name*

LEFTCENSORED=*number*

LC=*number*

specifies the left-censoring variable or a global left-censoring limit.

You can use the *variable-name* argument to specify a data set variable that contains the left-censoring limit. If the value of this variable is missing, then PROC HPSEVERITY assumes that such observations are not left-censored.

Alternatively, you can use the *number* argument to specify a left-censoring limit value that applies to all the observations in the data set. This limit must be a nonzero positive number.

By the definition of left-censoring, an exact value of the response is not known when it is less than or equal to the left-censoring limit. If the response variable is specified and the value of that variable is less than or equal to the value of the left-censoring limit for some observations, then PROC HPSEVERITY treats such observations as left-censored and the value of the response variable is ignored. If the response variable is specified and the value of that variable is greater than the value of the left-censoring limit for some observations, then PROC HPSEVERITY assumes that such observations are not left-censored.

If both right-censoring and left-censoring limits are specified, then the left-censoring limit must be greater than or equal to the right-censoring limit. If both limits are identical, then the observation is assumed to be uncensored.

For more information about left-censoring, see the section "Censoring and Truncation" on page 637.

LEFTTRUNCATED | LT=*variable-name*

LT=*variable-name*

LEFTTRUNCATED=*number*

LT=*number*

specifies the left-truncation variable or a global left-truncation threshold.

You can use the *variable-name* argument to specify a data set variable that contains the left-truncation threshold. If the value of this variable is missing or 0 for some observations, then PROC HPSEVERITY assumes that such observations are not left-truncated.

Alternatively, you can use the *number* argument to specify a left-truncation threshold that applies to all the observations in the data set. This threshold must be a nonzero positive number.

It is assumed that the response variable contains the observed values. By the definition of left-truncation, you can observe only a value that is greater than the left-truncation threshold. If a response variable value is less than or equal to the left-truncation threshold, a warning is printed to the SAS log, and the observation is ignored. For more information about left-truncation, see the section "Censoring and Truncation" on page 637.

RIGHTCENSORED | RC=*variable-name*

RC=*variable-name*

RIGHTCENSORED=*number*

RC=*number*

specifies the right-censoring variable or a global right-censoring limit.

You can use the *variable-name* argument to specify a data set variable that contains the right-censoring limit. If the value of this variable is missing, then PROC HPSEVERITY assumes that such observations are not right-censored.

Alternatively, you can use the *number* argument to specify a right-censoring limit value that applies to all the observations in the data set. This limit must be a nonzero positive number.

By the definition of right-censoring, an exact value of the response is not known when it is greater than or equal to the right-censoring limit. If the response variable is specified and the value of that variable is greater than or equal to the value of the right-censoring limit for some observations, then PROC HPSEVERITY treats such observations as right-censored and the value of the response variable is ignored. If the response variable is specified and the value of that variable is less than the value of the right-censoring limit for some observations, then PROC HPSEVERITY assumes that such observations are not right-censored and the value of the right-censoring limit is ignored.

If both right-censoring and left-censoring limits are specified, then the left-censoring limit must be greater than or equal to the right-censoring limit. If both limits are identical, then the observation is assumed to be uncensored.

For more information about right-censoring, see the section "Censoring and Truncation" on page 637.

RIGHTTRUNCATED | RT=*variable-name*

RT=*variable-name*

RIGHTTRUNCATED=*number*

RT=*number*

specifies the right-truncation variable or a global right-truncation threshold.

You can use the *variable-name* argument to specify a data set variable that contains the right-truncation threshold. If the value of this variable is missing for some observations, then PROC HPSEVERITY assumes that such observations are not right-truncated.

Alternatively, you can use the *number* argument to specify a right-truncation threshold that applies to all the observations in the data set. This threshold must be a nonzero positive number.

It is assumed that the response variable contains the observed values. By the definition of right-truncation, you can observe only a value that is less than or equal to the right-truncation threshold. If a response variable value is greater than the right-truncation threshold, a warning is printed to the SAS log, and the observation is ignored. For more information about right-truncation, see the section "Censoring and Truncation" on page 637.

NLOPTIONS Statement

NLOPTIONS *options* **;**

The HPSEVERITY procedure uses the nonlinear optimization (NLO) subsystem to perform nonlinear optimization of the likelihood function to obtain the estimates of distribution and regression parameters. You can use the NLOPTIONS statement to control different aspects of this optimization process. If you specify more than one NLOPTIONS statement, then the first statement is used.

For most problems, the default settings of the optimization process are adequate. However, in some cases it might be useful to change the optimization technique or to change the maximum number of iterations. The following statement uses the MAXITER= option to set the maximum number of iterations to 200 and uses the TECH= option to change the optimization technique to the double-dogleg optimization (DBLDOG) rather than the default technique, the trust region optimization (TRUREG), used in the HPSEVERITY procedure:

```
nloptions tech=dbldog maxiter=200;
```

The following *options* values can be used in the NLOPTIONS statement:

ABSCONV=*r*

ABSTOL=*r*

specifies an absolute function value convergence criterion. For minimization, termination requires $f(\theta^{(k)}) \leq r$. The default value of *r* is the negative square root of the largest double-precision value, which serves only as a protection against overflows.

ABSFCONV=*r*

ABSFTOL=*r*

specifies an absolute function difference convergence criterion. For all techniques except NMSIMP, termination requires a small change of the function value in successive iterations:

$$|f(\theta^{(k-1)}) - f(\theta^{(k)})| \leq r$$

The same formula is used for the NMSIMP technique, but $\theta^{(k)}$ is defined as the vertex with the lowest function value, and $\theta^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The default value is $r = 0$.

ABSGCONV=*r*

ABSGTOL=*r*

specifies an absolute gradient convergence criterion. Termination requires the maximum absolute gradient element to be small:

$$\max_j |g_j(\theta^{(k)})| \leq r$$

This criterion is not used by the NMSIMP technique. The default value is *r*=1E–5.

ABSXCONV=*r*

ABSXTOL=*r*

specifies an absolute parameter convergence criterion. For all techniques except NMSIMP, termination requires a small Euclidean distance between successive parameter vectors,

$$\| \theta^{(k)} - \theta^{(k-1)} \|_2 \leq r$$

For the NMSIMP technique, termination requires either a small length $\alpha^{(k)}$ of the vertices of a restart simplex,

$$\alpha^{(k)} \leq r$$

or a small simplex size,

$$\delta^{(k)} \leq r$$

where the simplex size $\delta^{(k)}$ is defined as the L1 distance from the simplex vertex $\xi^{(k)}$ with the smallest function value to the other simplex points $\theta_l^{(k)} \neq \xi^{(k)}$:

$$\delta^{(k)} = \sum \| \theta_l^{(k)} - \xi^{(k)} \|_1$$

The default is *r*=1E–8 for the NMSIMP technique and $r = 0$ otherwise.

FCONV=*r*

FTOL=*r*

specifies a relative function convergence criterion. For all techniques except NMSIMP, termination requires a small relative change of the function value in successive iterations,

$$\frac{|f(\theta^{(k)}) - f(\theta^{(k-1)})|}{\max(|f(\theta^{(k-1)})|, \text{FSIZE})} \leq r$$

where FSIZE is defined by the FSIZE= option. The same formula is used for the NMSIMP technique, but $\theta^{(k)}$ is defined as the vertex with the lowest function value, and $\theta^{(k-1)}$ is defined as the vertex with the highest function value in the simplex.

The default value is $r = 2\epsilon$, where ϵ denotes the machine precision constant, which is the smallest double-precision floating-point number such that $1 + \epsilon > 1$.

FCONV2=*r*

FTOL2=*r*

specifies another function convergence criterion.

For all techniques except NMSIMP, termination requires a small predicted reduction of the objective function:

$$df^{(k)} \approx f(\theta^{(k)}) - f(\theta^{(k)} + s^{(k)})$$

The predicted reduction

$$\begin{aligned} df^{(k)} &= -g^{(k)T} s^{(k)} - \frac{1}{2} s^{(k)T} H^{(k)} s^{(k)} \\ &= -\frac{1}{2} s^{(k)T} g^{(k)} \\ &\leq r \end{aligned}$$

is computed by approximating the objective function f by the first two terms of the Taylor series and substituting the Newton step

$$s^{(k)} = -[H^{(k)}]^{-1} g^{(k)}$$

For the NMSIMP technique, termination requires a small standard deviation of the function values of the $p+1$ simplex vertices $\theta_l^{(k)}$, $l = 0, \ldots, p$, $\sqrt{\frac{1}{p+1} \sum_l \left[f(\theta_l^{(k)}) - \overline{f}(\theta^{(k)}) \right]^2} \leq r$ where $\overline{f}(\theta^{(k)}) = \frac{1}{p+1} \sum_l f(\theta_l^{(k)})$. If there are p_{act} boundary constraints active at $\theta^{(k)}$, the mean and standard deviation are computed only for the $p + 1 - p_{act}$ unconstrained vertices.

The default value is *r*=1E–6 for the NMSIMP technique and $r = 0$ otherwise.

FSIZE=*r*

specifies the FSIZE parameter of the relative function and relative gradient termination criteria. The default value is *r*= 0. For more information, see the FCONV= and GCONV= options.

GCONV=*r*

GTOL=*r*

specifies a relative gradient convergence criterion. For all techniques except CONGRA and NMSIMP, termination requires that the normalized predicted function reduction is small,

$$\frac{g(\theta^{(k)})^T [H^{(k)}]^{-1} g(\theta^{(k)})}{\max(|f(\theta^{(k)})|, \text{FSIZE})} \leq r$$

where FSIZE is defined by the FSIZE= option. For the CONGRA technique (where a reliable Hessian estimate H is not available), the following criterion is used:

$$\frac{\| g(\theta^{(k)}) \|_2^2 \quad \| s(\theta^{(k)}) \|_2}{\| g(\theta^{(k)}) - g(\theta^{(k-1)}) \|_2 \max(|f(\theta^{(k)})|, \text{FSIZE})} \leq r$$

This criterion is not used by the NMSIMP technique. The default value is $r = 1E - 8$.

MAXFUNC=*i*

MAXFU=*i*

specifies the maximum number *i* of function calls in the optimization process. The default values are

- TRUREG, NRRIDG, NEWRAP: 125
- QUANEW, DBLDOG: 500
- CONGRA: 1000
- NMSIMP: 3000

Note that the optimization can terminate only after completing a full iteration. Therefore, the number of function calls that is actually performed can exceed the number that is specified by the MAXFUNC= option.

MAXITER=*i*

MAXIT=*i*

specifies the maximum number *i* of iterations in the optimization process. The default values are

- TRUREG, NRRIDG, NEWRAP: 50
- QUANEW, DBLDOG: 200
- CONGRA: 400
- NMSIMP: 1000

These default values are also valid when *i* is specified as a missing value.

MAXTIME=*r*

specifies an upper limit of *r* seconds of CPU time for the optimization process. The default value is the largest floating-point double representation of your computer. The time specified by the MAXTIME= option is checked only once at the end of each iteration. Therefore, the actual running time can be much longer than that specified by the MAXTIME= option. The actual running time includes the rest of the time needed to finish the iteration and the time needed to generate the output of the results.

MINITER=*i*

MINIT=*i*

specifies the minimum number of iterations. The default value is 0. If you request more iterations than are actually needed for convergence to a stationary point, the optimization algorithms can behave strangely. For example, the effect of rounding errors can prevent the algorithm from continuing for the required number of iterations.

TECHNIQUE=*name*

TECH=*name*

specifies the optimization technique. Valid values for *name* are as follows:

CONGRA	performs a conjugate-gradient optimization.
DBLDOG	performs a version of double-dogleg optimization.
NMSIMP	performs a Nelder-Mead simplex optimization.

NONE	does not perform any optimization. This option can be used as follows: • to perform a grid search without optimization • to compute estimates and predictions that cannot be obtained efficiently with any of the optimization techniques
NEWRAP	performs a Newton-Raphson optimization that combines a line-search algorithm with ridging.
NRRIDG	performs a Newton-Raphson optimization with ridging.
QUANEW	performs a quasi-Newton optimization
TRUREG	performs a trust region optimization. This is the default estimation method.

For more information about optimization algorithms, see the section "Details of Optimization Algorithms" on page 640.

XCONV=*r*

XTOL=*r*

specifies the relative parameter convergence criterion. For all techniques except NMSIMP, termination requires a small relative parameter change in subsequent iterations.

$$\frac{\max_j |\theta_j^{(k)} - \theta_j^{(k-1)}|}{\max(|\theta_j^{(k)}|, |\theta_j^{(k-1)}|, \text{XSIZE})} \leq r$$

For the NMSIMP technique, the same formula is used, but $\theta_j^{(k)}$ is defined as the vertex with the lowest function value and $\theta_j^{(k-1)}$ is defined as the vertex with the highest function value in the simplex. The default value is *r*=1E–8 for the NMSIMP technique and $r = 0$ otherwise.

XSIZE=*r*

specifies the XSIZE parameter of the relative parameter termination criterion. The value of *r* must be greater than or equal to 0; default is $r = 0$. For more detail, see the XCONV= option.

PERFORMANCE Statement

PERFORMANCE *options* **;**

The PERFORMANCE statement defines performance parameters for distributed and multithreaded computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a High-Performance Analytics procedure.

With the PERFORMANCE statement, you can also control whether a High-Performance Analytics procedure executes in SMP or MPP mode.

The PERFORMANCE statement for SAS High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SCALEMODEL Statement

SCALEMODEL *regressor-variable-list* < / *scalemodel-option* > **;**

The SCALEMODEL statement specifies regression variables. All the variables specified in this statement must be present in the input data set that is specified by the DATA= option in the PROC HPSEVERITY statement. The scale parameter of each candidate distribution is linked to a linear combination of these regression variables along with an intercept. If a distribution does not have a scale parameter, then a model based on that distribution is not estimated. If you specify more than one SCALEMODEL statement, then the first statement is used.

The regressor variables are expected to have nonmissing values. If any of the variables has a missing value in an observation, then a warning is written to the SAS log and that observation is ignored.

For more information about modeling regression effects, see the section "Estimating Regression Effects" on page 643.

You can specify the following *scalemodel-option* in the SCALEMODEL statement:

DFMIXTURE=*method-name* < *(method-options)* >
specifies the method for computing representative estimates of the cumulative distribution function (CDF).

When regression variables are specified, the scale of the distribution depends on the values of the regressors. For a given distribution family, each observation in the input data set implies a different scaled version of the distribution. To compute estimates of CDF that are comparable across different distribution families, PROC HPSEVERITY needs to construct a single representative distribution from all such distributions. You can specify one of the following *method-name* values to specify the method that is used to construct the representative distribution. For more information about each of the methods, see the section "CDF Estimates with Regression Effects" on page 645.

FULL
specifies that the representative distribution be the mixture of N distributions such that each distribution has a scale value that is implied by each of the N observations that are used for estimation. This method is the slowest.

MEAN
specifies that the representative distribution be the one-point mixture of the distribution whose scale value is the mean of the N scale values that are implied by the N observations that are used for estimation. If you do not specify the DFMIXTURE= option, then this method is used by default. This is also the fastest method.

QUANTILE < (K=*q*) >
specifies that the representative distribution be the mixture of a fixed number of distributions whose scale values are the quantiles from the sample of N scale values that are implied by the N observations in the current BY group (or in the entire DATA= data set if the BY statement is not specified).

You can use the K= option to specify the number of distributions in the mixture. If you specify K=q, then the mixture contains $(q-1)$ distributions such that each distribution has as its scale one of the $(q-1)$-quantiles.

If you do not specify the K= option, then PROC HPSEVERITY uses the default of 2, which implies the use of a one-point mixture with a distribution whose scale value is the median of all scale values.

RANDOM <(*random-method-options***)>**
specifies that the representative distribution be the mixture of a fixed number of distributions whose scale values are the scale values that are implied by a randomly chosen subset of the set of all observations in the current BY group (or in the entire DATA= data set if the BY statement is not specified). The same subset of observations is used for each distribution family.

You can specify the following *random-method-options* to specify how the subset is chosen:

K=*r*
specifies the number of distributions to include in the mixture. If you do not specify this option, then PROC HPSEVERITY uses the default of 15.

SEED=*number*
specifies the seed that is used to generate the uniform random sample of observation indices. If you do not specify this option, then PROC HPSEVERITY generates a seed internally that is based on the current value of the system clock.

WEIGHT Statement

WEIGHT *variable-name* **;**

The WEIGHT statement specifies the name of a variable whose values represent the weight of each observation. PROC HPSEVERITY associates a weight of w to each observation, where w is the value of the WEIGHT variable for the observation. If the weight value is missing or less than or equal to 0, then the observation is ignored and a warning is written to the SAS log. When the WEIGHT statement is not specified, each observation is assigned a weight of 1. If you specify more than one WEIGHT statement, then the last statement is used.

The weights are normalized so that they add up to the actual sample size. In particular, the weight of each observation is multiplied by $\frac{N}{\sum_{i=1}^{N} w_i}$, where N is the sample size.

Programming Statements (Experimental)

You can use a series of programming statements that use variables in the input data set specified by DATA= option in the PROC HPSEVERITY statement to assign a value to an objective function symbol. The objective function symbol must be specified using the OBJECTIVE= option in the PROC HPSEVERITY statement. If you do not specify the OBJECTIVE= option in the PROC HPSEVERITY statement, then the programming statements are ignored and models are estimated using the maximum likelihood method.

You can use most DATA step statements and functions in your program. Any additional functions, restrictions, and differences are listed in the section "Custom Objective Functions (Experimental)" on page 677.

Details: HPSEVERITY Procedure

Predefined Distributions

PROC HPSEVERITY assumes the following model for the response variable Y

$$Y \sim \mathcal{F}(\Theta)$$

where $\mathcal{F}$ is a continuous probability distribution with parameters Θ. The model hypothesizes that the observed response is generated from a stochastic process that is governed by the distribution $\mathcal{F}$. This model is typically referred to as the error model. Given a representative input sample of response variable values, PROC HPSEVERITY estimates the model parameters for any distribution $\mathcal{F}$ and computes the statistics of fit for each model. This enables you to find the distribution that is most likely to generate the observed sample.

A set of predefined distributions is provided with the HPSEVERITY procedure. A summary of the distributions is provided in Table 24.2. For each distribution, the table lists the name of the distribution that should be used in the DIST statement, the parameters of the distribution along with their bounds, and the mathematical expressions for the probability density function (PDF) and cumulative distribution function (CDF) of the distribution.

All the predefined distributions, except LOGN and TWEEDIE, are parameterized such that their first parameter is the scale parameter. For LOGN, the first parameter μ is a log-transformed scale parameter. TWEEDIE does not have a scale parameter. The presence of scale parameter or a log-transformed scale parameter enables you to use all of the predefined distributions, except TWEEDIE, as a candidate for estimating regression effects.

A distribution model is associated with each predefined distribution. You can also define your own distribution model, which is a set of functions and subroutines that you define by using the FCMP procedure. For more information, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660.

Table 24.2 Predefined HPSEVERITY Distributions

Name	Distribution	Parameters	PDF (f) and CDF (F)
BURR	Burr	$\theta > 0, \alpha > 0,$ $\gamma > 0$	$f(x) = \frac{\alpha\gamma z^{\gamma}}{x(1+z^{\gamma})^{(\alpha+1)}}$ $F(x) = 1 - \left(\frac{1}{1+z^{\gamma}}\right)^{\alpha}$
EXP	Exponential	$\theta > 0$	$f(x) = \frac{1}{\theta}e^{-z}$ $F(x) = 1 - e^{-z}$
GAMMA	Gamma	$\theta > 0, \alpha > 0$	$f(x) = \frac{z^{\alpha}e^{-z}}{x\Gamma(\alpha)}$ $F(x) = \frac{\gamma(\alpha,z)}{\Gamma(\alpha)}$
GPD	Generalized Pareto	$\theta > 0, \xi > 0$	$f(x) = \frac{1}{\theta}(1+\xi z)^{-1-1/\xi}$ $F(x) = 1 - (1+\xi z)^{-1/\xi}$
IGAUSS	Inverse Gaussian (Wald)	$\theta > 0, \alpha > 0$	$f(x) = \frac{1}{\theta}\sqrt{\frac{\alpha}{2\pi z^3}}\, e^{\frac{-\alpha(z-1)^2}{2z}}$ $F(x) = \Phi\left((z-1)\sqrt{\frac{\alpha}{z}}\right) +$ $\Phi\left(-(z+1)\sqrt{\frac{\alpha}{z}}\right) e^{2\alpha}$
LOGN	Lognormal	μ (no bounds), $\sigma > 0$	$f(x) = \frac{1}{x\sigma\sqrt{2\pi}}e^{-\frac{1}{2}\left(\frac{\log(x)-\mu}{\sigma}\right)^2}$ $F(x) = \Phi\left(\frac{\log(x)-\mu}{\sigma}\right)$
PARETO	Pareto	$\theta > 0, \alpha > 0$	$f(x) = \frac{\alpha\theta^{\alpha}}{(x+\theta)^{\alpha+1}}$ $F(x) = 1 - \left(\frac{\theta}{x+\theta}\right)^{\alpha}$
TWEEDIE	Tweedie[6]	$\mu > 0, \phi > 0,$ $p > 1$	$f(x) = a(x,\phi)\exp\left[\frac{1}{\phi}\left(\frac{x\mu^{1-p}}{1-p} - \kappa(\mu,p)\right)\right]$ $F(x) = \int_0^x f(t)dt$
STWEEDIE	Scaled Tweedie[6]	$\theta > 0, \lambda > 0,$ $1 < p < 2$	$f(x) = a(x,\theta,\lambda,p)\exp\left(-\frac{x}{\theta} - \lambda\right)$ $F(x) = \int_0^x f(t)dt$
WEIBULL	Weibull	$\theta > 0, \tau > 0$	$f(x) = \frac{1}{x}\tau z^{\tau}e^{-z^{\tau}}$ $F(x) = 1 - e^{-z^{\tau}}$

Notes:
1. $z = x/\theta$, wherever z is used.
2. θ denotes the scale parameter for all the distributions. For LOGN, $\log(\theta) = \mu$.
3. Parameters are listed in the order in which they are defined in the distribution model.
4. $\gamma(a,b) = \int_0^b t^{a-1}e^{-t}dt$ is the lower incomplete gamma function.
5. $\Phi(y) = \frac{1}{2}\left(1 + \mathrm{erf}\left(\frac{y}{\sqrt{2}}\right)\right)$ is the standard normal CDF.
6. For more information, see the section "Tweedie Distributions" on page 629.

Tweedie Distributions

Tweedie distributions are a special case of the exponential dispersion family (Jørgensen, 1987) with a property that the variance of the distribution is equal to $\phi\mu^p$, where μ is the mean of the distribution, ϕ is a dispersion parameter, and p is an index parameter as discovered by Tweedie (1984). The distribution is defined for all values of p except for values of p in the open interval $(0, 1)$. Many important known distributions are a special case of Tweedie distributions including normal (p=0), Poisson (p=1), gamma (p=2), and the inverse Gaussian (p=3). Apart from these special cases, the probability density function (PDF) of the Tweedie distribution does not have an analytic expression. For $p > 1$, it has the form (Dunn and Smyth 2005),

$$f(x; \mu, \phi, p) = a(x, \phi) \exp\left[\frac{1}{\phi}\left(\frac{x\mu^{1-p}}{1-p} - \kappa(\mu, p)\right)\right]$$

where $\kappa(\mu, p) = \mu^{2-p}/(2-p)$ for $p \neq 2$ and $\kappa(\mu, p) = \log(\mu)$ for $p = 2$. The function $a(x, \phi)$ does not have an analytical expression. It is typically evaluated using series expansion methods described in Dunn and Smyth (2005).

For $1 < p < 2$, the Tweedie distribution is a compound Poisson-gamma mixture distribution, which is the distribution of S defined as

$$S = \sum_{i=1}^{N} X_i$$

where $N \sim \text{Poisson}(\lambda)$ and $X_i \sim \text{gamma}(\alpha, \theta)$ are independent and identically distributed gamma random variables with shape parameter α and scale parameter θ. At $X = 0$, the density is a probability mass that is governed by the Poisson distribution, and for values of $X > 0$, it is a mixture of gamma variates with Poisson mixing probability. The parameters λ, α, and θ are related to the natural parameters μ, ϕ, and p of the Tweedie distribution as

$$\lambda = \frac{\mu^{2-p}}{\phi(2-p)}$$
$$\alpha = \frac{2-p}{p-1}$$
$$\theta = \phi(p-1)\mu^{p-1}$$

The mean of a Tweedie distribution is positive for $p > 1$.

Two predefined versions of the Tweedie distribution are provided with the HPSEVERITY procedure. The first version, named TWEEDIE and defined for $p > 1$, has the natural parameterization with parameters μ, ϕ, and p. The second version, named STWEEDIE and defined for $1 < p < 2$, is the version with a scale parameter. It corresponds to the compound Poisson-gamma distribution with gamma scale parameter θ, Poisson mean parameter λ, and the index parameter p. The index parameter decides the shape parameter α of the gamma distribution as

$$\alpha = \frac{2-p}{p-1}$$

The parameters θ and λ of the STWEEDIE distribution are related to the parameters μ and ϕ of the TWEEDIE distribution as

$$\mu = \lambda\theta\alpha$$
$$\phi = \frac{(\lambda\theta\alpha)^{2-p}}{\lambda(2-p)} = \frac{\theta}{(p-1)(\lambda\theta\alpha)^{p-1}}$$

You can fit either version when there are no regression variables. Each version has its own merits. If you fit the TWEEDIE version, you have the direct estimate of the overall mean of the distribution. If you are interested in the most practical range of the index parameter $1 < p < 2$, then you can fit the STWEEDIE version, which provides you direct estimates of the Poisson and gamma components that comprise the distribution (an estimate of the gamma shape parameter α is easily obtained from the estimate of p).

If you want to estimate the effect of exogenous (regression) variables on the distribution, then you must use the STWEEDIE version, because PROC HPSEVERITY requires a distribution to have a scale parameter in order to estimate regression effects. For more information, see the section "Estimating Regression Effects" on page 643. The gamma scale parameter θ is the scale parameter of the STWEEDIE distribution. If you are interested in determining the effect of regression variables on the mean of the distribution, you can do so by first fitting the STWEEDIE distribution to determine the effect of the regression variables on the scale parameter θ. Then, you can easily estimate how the mean of the distribution μ is affected by the regression variables using the relationship $\mu = c\theta$, where $c = \lambda\alpha = \lambda(2-p)/(p-1)$. The estimates of the regression parameters remain the same, whereas the estimate of the intercept parameter is adjusted by the estimates of the λ and p parameters.

Parameter Initialization for Predefined Distributions

The parameters are initialized by using the method of moments for all the distributions, except for the gamma and the Weibull distributions. For the gamma distribution, approximate maximum likelihood estimates are used. For the Weibull distribution, the method of percentile matching is used.

Given n observations of the severity value y_i $(1 \le i \le n)$, the estimate of kth raw moment is denoted by m_k and computed as

$$m_k = \frac{1}{n}\sum_{i=1}^{n} y_i^k$$

The $100p$th percentile is denoted by π_p $(0 \le p \le 1)$. By definition, π_p satisfies

$$F(\pi_p-) \le p \le F(\pi_p)$$

where $F(\pi_p-) = \lim_{h\downarrow 0} F(\pi_p - h)$. PROC HPSEVERITY uses the following practical method of computing π_p. Let $\hat{F}_n(y)$ denote the empirical distribution function (EDF) estimate at a severity value y. Let y_p^- and y_p^+ denote two consecutive values in the ascending sequence of y values such that $\hat{F}_n(y_p^-) < p$ and $\hat{F}_n(y_p^+) \ge p$. Then, the estimate $\hat{\pi}_p$ is computed as

$$\hat{\pi}_p = y_p^- + \frac{p - \hat{F}_n(y_p^-)}{\hat{F}_n(y_p^+) - \hat{F}_n(y_p^-)}(y_p^+ - y_p^-)$$

Let ϵ denote the smallest double-precision floating-point number such that $1 + \epsilon > 1$. This machine precision constant can be obtained by using the CONSTANT function in Base SAS software.

The details of how parameters are initialized for each predefined distribution are as follows:

BURR The parameters are initialized by using the method of moments. The kth raw moment of the Burr distribution is:

$$E[X^k] = \frac{\theta^k \Gamma(1 + k/\gamma)\Gamma(\alpha - k/\gamma)}{\Gamma(\alpha)}, \quad -\gamma < k < \alpha\gamma$$

Three moment equations $E[X^k] = m_k$ $(k = 1, 2, 3)$ need to be solved for initializing the three parameters of the distribution. In order to get an approximate closed form solution, the second shape parameter $\hat{\gamma}$ is initialized to a value of 2. If $2m_3 - 3m_1m_2 > 0$, then simplifying and solving the moment equations yields the following feasible set of initial values:

$$\hat{\theta} = \sqrt{\frac{m_2 m_3}{2m_3 - 3m_1 m_2}}, \quad \hat{\alpha} = 1 + \frac{m_3}{2m_3 - 3m_1 m_2}, \quad \hat{\gamma} = 2$$

If $2m_3 - 3m_1m_2 < \epsilon$, then the parameters are initialized as follows:

$$\hat{\theta} = \sqrt{m_2}, \quad \hat{\alpha} = 2, \quad \hat{\gamma} = 2$$

EXP The parameters are initialized by using the method of moments. The kth raw moment of the exponential distribution is:

$$E[X^k] = \theta^k \Gamma(k + 1), \quad k > -1$$

Solving $E[X] = m_1$ yields the initial value of $\hat{\theta} = m_1$.

GAMMA The parameter α is initialized by using its *approximate* maximum likelihood (ML) estimate. For a set of n independent and identically distributed observations y_i $(1 \leq i \leq n)$ drawn from a gamma distribution, the log likelihood l is defined as follows:

$$\begin{aligned} l &= \sum_{i=1}^{n} \log\left(y_i^{\alpha-1} \frac{e^{-y_i/\theta}}{\theta^\alpha \Gamma(\alpha)}\right) \\ &= (\alpha - 1)\sum_{i=1}^{n} \log(y_i) - \frac{1}{\theta}\sum_{i=1}^{n} y_i - n\alpha \log(\theta) - n \log(\Gamma(\alpha)) \end{aligned}$$

Using a shorter notation of $\sum$ to denote $\sum_{i=1}^{n}$ and solving the equation $\partial l/\partial\theta = 0$ yields the following ML estimate of θ:

$$\hat{\theta} = \frac{\sum y_i}{n\alpha} = \frac{m_1}{\alpha}$$

Substituting this estimate in the expression of l and simplifying gives

$$l = (\alpha - 1)\sum \log(y_i) - n\alpha - n\alpha \log(m_1) + n\alpha \log(\alpha) - n \log(\Gamma(\alpha))$$

Let d be defined as follows:

$$d = \log(m_1) - \frac{1}{n}\sum \log(y_i)$$

Solving the equation $\partial l/\partial\alpha = 0$ yields the following expression in terms of the digamma function, $\psi(\alpha)$:

$$\log(\alpha) - \psi(\alpha) = d$$

The digamma function can be approximated as follows:

$$\hat{\psi}(\alpha) \approx \log(\alpha) - \frac{1}{\alpha}\left(0.5 + \frac{1}{12\alpha + 2}\right)$$

This approximation is within 1.4% of the true value for all the values of $\alpha > 0$ except when α is arbitrarily close to the positive root of the digamma function (which is approximately 1.461632). Even for the values of α that are close to the positive root, the absolute error between true and approximate values is still acceptable ($|\hat{\psi}(\alpha) - \psi(\alpha)| < 0.005$ for $\alpha > 1.07$). Solving the equation that arises from this approximation yields the following estimate of α:

$$\hat{\alpha} = \frac{3 - d + \sqrt{(d-3)^2 + 24d}}{12d}$$

If this approximate ML estimate is infeasible, then the method of moments is used. The kth raw moment of the gamma distribution is:

$$E[X^k] = \theta^k \frac{\Gamma(\alpha + k)}{\Gamma(\alpha)}, \quad k > -\alpha$$

Solving $E[X] = m_1$ and $E[X^2] = m_2$ yields the following initial value for α:

$$\hat{\alpha} = \frac{m_1^2}{m_2 - m_1^2}$$

If $m_2 - m_1^2 < \epsilon$ (almost zero sample variance), then α is initialized as follows:

$$\hat{\alpha} = 1$$

After computing the estimate of α, the estimate of θ is computed as follows:

$$\hat{\theta} = \frac{m_1}{\hat{\alpha}}$$

Both the maximum likelihood method and the method of moments arrive at the same relationship between $\hat{\alpha}$ and $\hat{\theta}$.

GPD

The parameters are initialized by using the method of moments. Notice that for $\xi > 0$, the CDF of the generalized Pareto distribution (GPD) is:

$$\begin{aligned} F(x) &= 1 - \left(1 + \frac{\xi x}{\theta}\right)^{-1/\xi} \\ &= 1 - \left(\frac{\theta/\xi}{x + \theta/\xi}\right)^{1/\xi} \end{aligned}$$

This is equivalent to a Pareto distribution with scale parameter $\theta_1 = \theta/\xi$ and shape parameter $\alpha = 1/\xi$. Using this relationship, the parameter initialization method used for the PARETO distribution is used to get the following initial values for the parameters of the GPD distribution:

$$\hat{\theta} = \frac{m_1 m_2}{2(m_2 - m_1^2)}, \quad \hat{\xi} = \frac{m_2 - 2m_1^2}{2(m_2 - m_1^2)}$$

If $m_2 - m_1^2 < \epsilon$ (almost zero sample variance) or $m_2 - 2m_1^2 < \epsilon$, then the parameters are initialized as follows:

$$\hat{\theta} = \frac{m_1}{2}, \quad \hat{\xi} = \frac{1}{2}$$

IGAUSS The parameters are initialized by using the method of moments. The standard parameterization of the inverse Gaussian distribution (also known as the Wald distribution), in terms of the location parameter μ and shape parameter λ, is as follows (Klugman, Panjer, and Willmot 1998, p. 583):

$$f(x) = \sqrt{\frac{\lambda}{2\pi x^3}}\ \exp\left(\frac{-\lambda(x-\mu)^2}{2\mu^2 x}\right)$$
$$F(x) = \Phi\left(\left(\frac{x}{\mu}-1\right)\sqrt{\frac{\lambda}{x}}\right) + \Phi\left(-\left(\frac{x}{\mu}+1\right)\sqrt{\frac{\lambda}{x}}\right)\ \exp\left(\frac{2\lambda}{\mu}\right)$$

For this parameterization, it is known that the mean is $E[X] = \mu$ and the variance is $Var[X] = \mu^3/\lambda$, which yields the second raw moment as $E[X^2] = \mu^2(1+\mu/\lambda)$ (computed by using $E[X^2] = Var[X] + (E[X])^2$).

The predefined IGAUSS distribution in PROC HPSEVERITY uses the following alternate parameterization to allow the distribution to have a scale parameter, θ:

$$f(x) = \sqrt{\frac{\alpha\theta}{2\pi x^3}}\ \exp\left(\frac{-\alpha(x-\theta)^2}{2x\theta}\right)$$
$$F(x) = \Phi\left(\left(\frac{x}{\theta}-1\right)\sqrt{\frac{\alpha\theta}{x}}\right) + \Phi\left(-\left(\frac{x}{\theta}+1\right)\sqrt{\frac{\alpha\theta}{x}}\right)\ \exp\left(2\alpha\right)$$

The parameters θ (scale) and α (shape) of this alternate form are related to the parameters μ and λ of the preceding form such that $\theta = \mu$ and $\alpha = \lambda/\mu$. Using this relationship, the first and second raw moments of the IGAUSS distribution are:

$$E[X] = \theta$$
$$E[X^2] = \theta^2\left(1 + \frac{1}{\alpha}\right)$$

Solving $E[X] = m_1$ and $E[X^2] = m_2$ yields the following initial values:

$$\hat{\theta} = m_1, \quad \hat{\alpha} = \frac{m_1^2}{m_2 - m_1^2}$$

If $m_2 - m_1^2 < \epsilon$ (almost zero sample variance), then the parameters are initialized as follows:

$$\hat{\theta} = m_1, \quad \hat{\alpha} = 1$$

LOGN The parameters are initialized by using the method of moments. The kth raw moment of the lognormal distribution is:

$$E[X^k] = \exp\left(k\mu + \frac{k^2\sigma^2}{2}\right)$$

Solving $E[X] = m_1$ and $E[X^2] = m_2$ yields the following initial values:

$$\hat{\mu} = 2\log(m1) - \frac{\log(m2)}{2}, \quad \hat{\sigma} = \sqrt{\log(m2) - 2\log(m1)}$$

PARETO The parameters are initialized by using the method of moments. The kth raw moment of the Pareto distribution is:

$$E[X^k] = \frac{\theta^k \Gamma(k+1)\Gamma(\alpha-k)}{\Gamma(\alpha)}, -1 < k < \alpha$$

Solving $E[X] = m_1$ and $E[X^2] = m_2$ yields the following initial values:

$$\hat{\theta} = \frac{m_1 m_2}{m_2 - 2m_1^2}, \quad \hat{\alpha} = \frac{2(m_2 - m_1^2)}{m_2 - 2m_1^2}$$

If $m_2 - m_1^2 < \epsilon$ (almost zero sample variance) or $m_2 - 2m_1^2 < \epsilon$, then the parameters are initialized as follows:

$$\hat{\theta} = m_1, \quad \hat{\alpha} = 2$$

TWEEDIE The parameter p is initialized by assuming that the sample is generated from a gamma distribution with shape parameter α and by computing $\hat{p} = \frac{\hat{\alpha}+2}{\hat{\alpha}+1}$. The initial value $\hat{\alpha}$ is obtained from using the method previously described for the GAMMA distribution. The parameter μ is the mean of the distribution. Hence, it is initialized to the sample mean as

$$\hat{\mu} = m_1$$

Variance of a Tweedie distribution is equal to $\phi\mu^p$. Thus, the sample variance is used to initialize the value of ϕ as

$$\hat{\phi} = \frac{m_2 - m_1^2}{\hat{\mu}^{\hat{p}}}$$

STWEEDIE STWEEDIE is a compound Poisson-gamma mixture distribution with mean $\mu = \lambda\theta\alpha$, where α is the shape parameter of the gamma random variables in the mixture and the parameter p is determined solely by α. First, the parameter p is initialized by assuming that the sample is generated from a gamma distribution with shape parameter α and by computing $\hat{p} = \frac{\hat{\alpha}+2}{\hat{\alpha}+1}$. The initial value $\hat{\alpha}$ is obtained from using the method previously described for the GAMMA distribution. As done for initializing the parameters of the TWEEDIE distribution, the sample mean and variance are used to compute the values $\hat{\mu}$ and $\hat{\phi}$ as

$$\hat{\mu} = m_1$$
$$\hat{\phi} = \frac{m_2 - m_1^2}{\hat{\mu}^{\hat{p}}}$$

Based on the relationship between the parameters of TWEEDIE and STWEEDIE distributions described in the section "Tweedie Distributions" on page 629, values of θ and λ are initialized as

$$\hat{\theta} = \hat{\phi}(\hat{p}-1)\hat{\mu}^{p-1}$$
$$\hat{\lambda} = \frac{\hat{\mu}}{\hat{\theta}\hat{\alpha}}$$

WEIBULL The parameters are initialized by using the percentile matching method. Let $q1$ and $q3$ denote the estimates of the 25th and 75th percentiles, respectively. Using the formula for the CDF of Weibull distribution, they can be written as

$$1 - \exp(-(q1/\theta)^{\tau}) = 0.25$$
$$1 - \exp(-(q3/\theta)^{\tau}) = 0.75$$

Simplifying and solving these two equations yields the following initial values:

$$\hat{\theta} = \exp\left(\frac{r\log(q1) - \log(q3)}{r-1}\right), \quad \hat{\tau} = \frac{\log(\log(4))}{\log(q3) - \log(\hat{\theta})}$$

where $r = \log(\log(4))/\log(\log(4/3))$. These initial values agree with those suggested in Klugman, Panjer, and Willmot (1998).

A summary of the initial values of all the parameters for all the predefined distributions is given in Table 24.3. The table also provides the names of the parameters to use in the INIT= option in the DIST statement if you want to provide a different initial value.

Table 24.3 Parameter Initialization for Predefined Distributions

Distribution	Parameter	Name for INIT option	Default Initial Value
BURR	θ	theta	$\sqrt{\frac{m_2 m_3}{2m_3 - 3m_1 m_2}}$
	α	alpha	$1 + \frac{m_3}{2m_3 - 3m_1 m_2}$
	γ	gamma	2
EXP	θ	theta	m_1
GAMMA	θ	theta	m_1/α
	α	alpha	$\frac{3-d+\sqrt{(d-3)^2+24d}}{12d}$
GPD	θ	theta	$m_1 m_2/(2(m_2 - m_1^2))$
	ξ	xi	$(m_2 - 2m_1^2)/(2(m_2 - m_1^2))$
IGAUSS	θ	theta	m_1
	α	alpha	$m_1^2/(m_2 - m_1^2)$
LOGN	μ	mu	$2\log(m1) - \log(m2)/2$
	σ	sigma	$\sqrt{\log(m2) - 2\log(m1)}$
PARETO	θ	theta	$m_1 m_2/(m_2 - 2m_1^2)$
	α	alpha	$2(m_2 - m_1^2)/(m_2 - 2m_1^2)$
TWEEDIE	μ	mu	m_1
	ϕ	phi	$(m_2 - m_1^2)/m_1^p$
	p	p	$(\alpha + 2)/(\alpha + 1)$ where $\alpha = \frac{3-d+\sqrt{(d-3)^2+24d}}{12d}$
STWEEDIE	θ	theta	$(m_2 - m_1^2)(p-1)/m_1$
	λ	lambda	$m_1^2/(\alpha(m_2 - m_1^2)(p-1))$
	p	p	$(\alpha + 2)/(\alpha + 1)$ where $\alpha = \frac{3-d+\sqrt{(d-3)^2+24d}}{12d}$
WEIBULL	θ	theta	$\exp\left(\frac{r\log(q1)-\log(q3)}{r-1}\right)$
	τ	tau	$\log(\log(4))/(\log(q3) - \log(\hat{\theta}))$

Notes:

- m_k denotes the kth raw moment
- $d = \log(m_1) - (\sum \log(y_i))/n$
- $q1$ and $q3$ denote the 25th and 75th percentiles, respectively
- $r = \log(\log(4))/\log(\log(4/3))$

Censoring and Truncation

One of the key features of PROC HPSEVERITY is that it enables you to specify whether the severity event's magnitude is observable and if it is observable, then whether the exact value of the magnitude is known. If an event is unobservable when the magnitude is in certain intervals, then it is referred to as a truncation effect. If the exact magnitude of the event is not known, but it is known to have a value in a certain interval, then it is referred to as a censoring effect.

PROC HPSEVERITY allows a severity event to be subject to any combination of the following four censoring and truncation effects:

- Left-truncation: An event is said to be left-truncated if it is observed only when $Y > T^l$, where Y denotes the random variable for the magnitude and T^l denotes a random variable for the truncation threshold. You can specify left-truncation using the LEFTTRUNCATED= option in the LOSS statement.
- Right-truncation: An event is said to be right-truncated if it is observed only when $Y \leq T^r$, where Y denotes the random variable for the magnitude and T^r denotes a random variable for the truncation threshold. You can specify right-truncation using the RIGHTTRUNCATED= option in the LOSS statement.
- Left-censoring: An event is said to be left-censored if it is known that the magnitude is $Y \leq C^l$, but the exact value of Y is not known. C^l is a random variable for the censoring limit. You can specify left-censoring using the LEFTCENSORED= option in the LOSS statement.
- Right-censoring: An event is said to be right-censored if it is known that the magnitude is $Y > C^r$, but the exact value of Y is not known. C^r is a random variable for the censoring limit. You can specify right-censoring using the RIGHTCENSORED= option in the LOSS statement.

For each effect, you can specify a different threshold or limit for each observation or specify a single threshold or limit that applies to all the observations.

If all the four types of effects are present on an event, then the following relationship holds: $T^l < C^r \leq C^l \leq T^r$. PROC HPSEVERITY checks these relationships and write a warning to the SAS log if any is violated.

If the response variable is specified in the LOSS statement, then PROC HPSEVERITY also checks whether each observation satisfies the definitions of the specified censoring and truncation effects. If left-truncation is specified, then PROC HPSEVERITY ignores observations where $Y \leq T^l$, because such observations are not observable by definition. Similarly, if right-truncation is specified, then PROC HPSEVERITY ignores observations where $Y > T^r$. If left-censoring is specified, then PROC HPSEVERITY treats an observation with $Y > C^l$ as uncensored and ignores the value of C^l. The observations with $Y \leq C^l$ are considered as left-censored, and the value of Y is ignored. If right-censoring is specified, then PROC HPSEVERITY treats an observation with $Y \leq C^r$ as uncensored and ignores the value of C^r. The observations with $Y > C^r$ are considered as right-censored, and the value of Y is ignored. The specification of both left-censoring and right-censoring is referred to as interval-censoring. If $C^r < C^l$ is satisfied for an observation, then it is considered as interval-censored and the value of the response variable is ignored. If $C^r = C^l$ for an observation, then PROC HPSEVERITY assumes that observation to be uncensored. If all the observations in a data set are censored in some form, then the specification of the response variable in the LOSS statement is optional, because the actual value of the response variable is not required for the purposes of estimating a model.

Specification of censoring and truncation affects the likelihood of the data (see the section "Likelihood Function" on page 638) and how the empirical distribution function (EDF) is estimated (see the section "Empirical Distribution Function Estimation Methods" on page 647).

Truncation and Conditional CDF Estimates

If left-truncation or right-truncation is specified, then the EDF estimates that are computed by all methods except the STANDARD method are conditional on the truncation information. See the section "EDF Estimates and Truncation" on page 652 for more information. In such cases, PROC HPSEVERITY uses conditional estimates of the CDF when it computes the EDF-based statistics of fit.

Let $t^l_{\min} = \min_i\{t^l_i\}$ be the smallest value of the left-truncation threshold (t^l_i is the left-truncation threshold for observation i) and $t^r_{\max} = \max_i\{t^r_i\}$ be the largest value of the right-truncation threshold (t^r_i is the right-truncation threshold for observation i). If $\hat{F}(y)$ denotes the unconditional estimate of the CDF at y, then the conditional estimate $\hat{F}^c(y)$ is computed as follows:

- If an observation is both left-truncated and right-truncated, then

$$\hat{F}^c(y) = \frac{\hat{F}(y) - \hat{F}(t^l_{\min})}{\hat{F}(t^r_{\max}) - \hat{F}(t^l_{\min})}$$

- If an observation is left-truncated but not right-truncated, then

$$\hat{F}^c(y) = \frac{\hat{F}(y) - \hat{F}(t^l_{\min})}{1 - \hat{F}(t^l_{\min})}$$

- If an observation is right-truncated but not left-truncated, then

$$\hat{F}^c(y) = \frac{\hat{F}(y)}{\hat{F}(t^r_{\max})}$$

If regressors are specified, then $\hat{F}(y)$, $\hat{F}(t^l_{\min})$, and $\hat{F}(t^r_{\max})$ are all computed from a mixture distribution, as described in the section "CDF Estimates with Regression Effects" on page 645.

Parameter Estimation Method

PROC HPSEVERITY uses the maximum likelihood (ML) method to estimate the parameters of each model. A nonlinear optimization process is used to maximize the log of the likelihood function.

Likelihood Function

Let $f_\Theta(x)$ and $F_\Theta(x)$ denote the PDF and CDF, respectively, evaluated at x for a set of parameter values Θ. Let Y denote the random response variable, and let y denote its value recorded in an observation in the input data set. Let T^l and T^r denote the random variables for the left-truncation and right-truncation threshold, respectively, and let t^l and t^r denote their values for an observation, respectively. If there is no left-truncation, then $t^l = \tau^l$, where τ^l is the smallest value in the support of the distribution; so $F(t^l) = 0$. If there is no right-truncation, then $t^r = \tau_h$, where τ_h is the largest value in the support of the distribution;

so $F(t^r) = 1$. Let C^l and C^r denote the random variables for the left-censoring and right-censoring limit, respectively, and let c^l and c^r denote their values for an observation, respectively. If there is no left-censoring, then $c^l = \tau_h$; so $F(c^l) = 1$. If there is no right-censoring, then $c^r = \tau^l$; so $F(c^r) = 0$.

The set of input observations can be categorized into the following four subsets:

- E is the set of uncensored and untruncated observations. The likelihood of an observation in E is

$$l_E = \Pr(Y = y) = f_\Theta(y)$$

- E_t is the set of uncensored observations that are truncated. The likelihood of an observation in E_t is

$$l_{E_t} = \Pr(Y = y | t^l < Y \leq t^r) = \frac{f_\Theta(y)}{F_\Theta(t^r) - F_\Theta(t^l)}$$

- C is the set of censored observations that are not truncated. The likelihood of an observation C is

$$l_C = \Pr(c^r < Y \leq c^l) = F_\Theta(c^l) - F_\Theta(c^r)$$

- C_t is the set of censored observations that are truncated. The likelihood of an observation C_t is

$$l_{C_t} = \Pr(c^r < Y \leq c^l | t^l < Y \leq t^r) = \frac{F_\Theta(c^l) - F_\Theta(c^r)}{F_\Theta(t^r) - F_\Theta(t^l)}$$

Note that $(E \cup E_t) \cap (C \cup C_t) = \emptyset$. Also, the sets E_t and C_t are empty when no truncation is specified, and the sets C and C_t are empty when no censoring is specified.

Given this, the likelihood of the data L is as follows:

$$L = \prod_E f_\Theta(y) \prod_{E_t} \frac{f_\Theta(y)}{F_\Theta(t^r) - F_\Theta(t^l)} \prod_C F_\Theta(c^l) - F_\Theta(c^r) \prod_{C_t} \frac{F_\Theta(c^l) - F_\Theta(c^r)}{F_\Theta(t^r) - F_\Theta(t^l)}$$

The maximum likelihood procedure used by PROC HPSEVERITY finds an optimal set of parameter values $\hat{\Theta}$ that maximizes $\log(L)$ subject to the boundary constraints on parameter values. For a distribution *dist*, such boundary constraints can be specified by using the *dist*_LOWERBOUNDS and *dist*_UPPERBOUNDS subroutines. For more information, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660. Some aspects of the optimization process can be controlled by using the NLOPTIONS statement.

Estimating Covariance and Standard Errors

PROC HPSEVERITY computes an estimate of the covariance matrix of the parameters by using the asymptotic theory of the maximum likelihood estimators (MLE). If N denotes the number of observations used for estimating a parameter vector $\boldsymbol{\theta}$, then the theory states that as $N \to \infty$, the distribution of $\hat{\boldsymbol{\theta}}$, the estimate of $\boldsymbol{\theta}$, converges to a normal distribution with mean $\boldsymbol{\theta}$ and covariance $\hat{\mathbf{C}}$ such that $\mathbf{I}(\boldsymbol{\theta}) \cdot \hat{\mathbf{C}} \to 1$, where $\mathbf{I}(\boldsymbol{\theta}) = -E\left[\nabla^2 \log(L(\boldsymbol{\theta}))\right]$ is the information matrix for the likelihood of the data, $L(\boldsymbol{\theta})$. The covariance estimate is obtained by using the inverse of the information matrix.

In particular, if $\mathbf{G} = \nabla^2 \log(-L(\boldsymbol{\theta}))$ denotes the Hessian matrix of the negative of log likelihood, then the covariance estimate is computed as

$$\hat{\mathbf{C}} = \frac{N}{d}\mathbf{G}^{-1}$$

where d is a denominator that is determined by the VARDEF= option. If VARDEF=N, then $d = N$, which yields the asymptotic covariance estimate. If VARDEF=DF, then $d = N - k$, where k is number of parameters (the model's degrees of freedom). The VARDEF=DF option is the default, because it attempts to correct the potential bias introduced by the finite sample.

The standard error s_i of the parameter θ_i is computed as the square root of the ith diagonal element of the estimated covariance matrix; that is, $s_i = \sqrt{\hat{C}_{ii}}$.

If you have specified a custom objective function, then the covariance matrix of the parameters is still computed by inverting the information matrix, except that the Hessian matrix $\mathbf{G}$ is computed as $\mathbf{G} = \nabla^2 \log(U(\boldsymbol{\theta}))$, where U denotes your custom objective function that is minimized by the optimizer.

Covariance and standard error estimates might not be available if the Hessian matrix is found to be singular at the end of the optimization process. This can especially happen if the optimization process stops without converging.

Details of Optimization Algorithms

Overview

There are several optimization techniques available. You can choose a particular optimizer with the TECH=*name* option in the PROC statement or NLOPTIONS statement.

Table 24.4 Optimization Techniques

Algorithm	TECH=
Trust region Method	TRUREG
Newton-Raphson method with line search	NEWRAP
Newton-Raphson method with ridging	NRRIDG
Quasi-Newton methods (DBFGS, DDFP, BFGS, DFP)	QUANEW
Double-dogleg method (DBFGS, DDFP)	DBLDOG
Conjugate gradient methods (PB, FR, PR, CD)	CONGRA
Nelder-Mead simplex method	NMSIMP

No algorithm for optimizing general nonlinear functions exists that always finds the global optimum for a general nonlinear minimization problem in a reasonable amount of time. Since no single optimization technique is invariably superior to others, NLO provides a variety of optimization techniques that work well in various circumstances. However, you can devise problems for which none of the techniques in NLO can find the correct solution. Moreover, nonlinear optimization can be computationally expensive in terms of time and memory, so you must be careful when matching an algorithm to a problem.

All optimization techniques in NLO use $O(n^2)$ memory except the conjugate gradient methods, which use only $O(n)$ of memory and are designed to optimize problems with many parameters. These iterative techniques require repeated computation of the following:

- the function value (optimization criterion)
- the gradient vector (first-order partial derivatives)
- for some techniques, the (approximate) Hessian matrix (second-order partial derivatives)

However, since each of the optimizers requires different derivatives, some computational efficiencies can be gained. Table 24.5 shows which derivatives are required for each optimization technique. (FOD means that first-order derivatives or the gradient is computed; SOD means that second-order derivatives or the Hessian is computed.)

Table 24.5 Optimization Computations

Algorithm	FOD	SOD
TRUREG	x	x
NEWRAP	x	x
NRRIDG	x	x
QUANEW	x	-
DBLDOG	x	-
CONGRA	x	-
NMSIMP	-	-

Each optimization method uses one or more convergence criteria that determine when it has converged. The various termination criteria are listed and described in the previous section. An algorithm is considered to have converged when any one of the convergence criteria is satisfied. For example, under the default settings, the QUANEW algorithm converges if ABSGCONV $<$ 1E–5, FCONV $<$ $10^{-\text{FDIGITS}}$, or GCONV $<$ 1E–8.

Choosing an Optimization Algorithm

The factors for choosing a particular optimization technique for a particular problem are complex and might involve trial and error.

For many optimization problems, computing the gradient takes more computer time than computing the function value, and computing the Hessian sometimes takes *much* more computer time and memory than computing the gradient, especially when there are many decision variables. Unfortunately, optimization techniques that do not use some kind of Hessian approximation usually require many more iterations than techniques that do use a Hessian matrix. As a result the total run time of these techniques is often longer. Techniques that do not use the Hessian also tend to be less reliable. For example, they can more easily terminate at stationary points rather than at global optima.

A few general remarks about the various optimization techniques follow:

- The second-derivative methods TRUREG, NEWRAP, and NRRIDG are best for small problems where the Hessian matrix is not expensive to compute. Sometimes the NRRIDG algorithm can be faster than the TRUREG algorithm, but TRUREG can be more stable. The NRRIDG algorithm requires only one matrix with $n(n+1)/2$ double words; TRUREG and NEWRAP require two such matrices.

- The first-derivative methods QUANEW and DBLDOG are best for medium-sized problems where the objective function and the gradient are much faster to evaluate than the Hessian. The QUANEW and DBLDOG algorithms generally require more iterations than TRUREG, NRRIDG, and NEWRAP, but each iteration can be much faster. The QUANEW and DBLDOG algorithms require only the gradient to update an approximate Hessian, and they require slightly less memory than TRUREG or NEWRAP (essentially one matrix with $n(n+1)/2$ double words). QUANEW is the default optimization method.
- The first-derivative method CONGRA is best for large problems where the objective function and the gradient can be computed much faster than the Hessian and where too much memory is required to store the (approximate) Hessian. The CONGRA algorithm generally requires more iterations than QUANEW or DBLDOG, but each iteration can be much faster. Since CONGRA requires only a factor of n double-word memory, many large applications can be solved only by CONGRA.
- The no-derivative method NMSIMP is best for small problems where derivatives are not continuous or are very difficult to compute.

Parameter Initialization

PROC HPSEVERITY enables you to initialize parameters of a model in different ways. A model can have two kinds of parameters: distribution parameters and regression parameters.

The distribution parameters can be initialized by using one of the following three methods:

INIT= option	You can use the INIT= option in the DIST statement.
INEST= data set	You can use the INEST= data set.
PARMINIT subroutine	You can define a *dist*_PARMINIT subroutine in the distribution model. For more information, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660.

Note that only one of the initialization methods is used. You cannot combine them. They are used in the following order:

- The method that uses the INIT= option takes the highest precedence. If you use the INIT= option to provide an initial value for at least one parameter, then other initialization methods (INEST= and PARMINIT) are not used. If you specify initial values for some but not all the parameters by using the INIT= option, then the uninitialized parameters are initialized to the default value of 0.001.

  If this option is used when regression effects are specified, then the value of the first distribution parameter must be related to the initial value for the *base* value of the scale or log-transformed scale parameter. For more information, see the section "Estimating Regression Effects" on page 643.
- The method that uses the INEST= data set takes the second precedence. If there is a nonmissing value specified for even one distribution parameter, then the PARMINIT method is not used and any uninitialized parameters are initialized to the default value of 0.001.
- If none of the distribution parameters are initialized by using the INIT= option or the INEST= data set, but the distribution model defines a PARMINIT subroutine, then PROC HPSEVERITY invokes that subroutine with appropriate inputs to initialize the parameters. If the PARMINIT subroutine returns missing values for some parameters, then those parameters are initialized to the default value of 0.001.

- If none of the initialization methods are used, each distribution parameter is initialized to the default value of 0.001.

For more information about regression models and initialization of regression parameters, see the section "Estimating Regression Effects" on page 643.

PARMINIT-Based Parameter Initialization Method and Distributed Data

If you have specified a MPP model of execution for the procedure, then the input data is distributed across the computational nodes. For more information about the distributed computing model, see the section "Distributed and Multithreaded Computation" on page 657. If the PARMINIT subroutine is used for initializing the distribution parameters, then PROC HPSEVERITY invokes that subroutine on each computational node with the data that are local to that node. The EDF estimates that are supplied to the PARMINIT subroutine are also computed using the local data. The initial values of the parameters that are supplied to the optimizer are the average of the local estimates computed on each node. This approach works well if the data are distributed randomly across nodes. If you distribute the data on the appliance before you run the procedure (alongside-the-database model), then you should try to make the distribution as random as possible in order to increase the chances of computing good initial values. If you specify a data set that is not distributed before you run the procedure, then PROC HPSEVERITY distributes the data for you in a round-robin manner. That is, it sends the first observation to the first node, second observation to the second node, and so forth. If the order of observations is random, then this method ensures random distribution of data across the computational nodes.

Estimating Regression Effects

The HPSEVERITY procedure enables you to estimate the effects of regressor (exogenous) variables while fitting a distribution if the distribution has a scale parameter or a log-transformed scale parameter.

Let x_j $(j = 1, \ldots, k)$ denote the k regressor variables. Let β_j denote the regression parameter that corresponds to the regressor x_j. If regression effects are not specified, then the model for the response variable Y is of the form

$$Y \sim \mathcal{F}(\Theta)$$

where $\mathcal{F}$ is the distribution of Y with parameters Θ. This model is typically referred to as the error model. The regression effects are modeled by extending the error model to the following form:

$$Y \sim \exp(\sum_{j=1}^{k} \beta_j x_j) \cdot \mathcal{F}(\Theta)$$

Under this model, the distribution of Y is valid and belongs to the same parametric family as $\mathcal{F}$ if and only if $\mathcal{F}$ has a scale parameter. Let θ denote the scale parameter and Ω denote the set of nonscale distribution parameters of $\mathcal{F}$. Then the model can be rewritten as

$$Y \sim \mathcal{F}(\theta, \Omega)$$

such that θ is affected by the regressors as

$$\theta = \theta_0 \cdot \exp(\sum_{j=1}^{k} \beta_j x_j)$$

where θ_0 is the *base* value of the scale parameter. Thus, the regression model consists of the following parameters: θ_0, Ω, and $\beta_j (j = 1, \ldots, k)$.

Given this form of the model, distributions without a scale parameter cannot be considered when regression effects are to be modeled. If a distribution does not have a direct scale parameter, then PROC HPSEVERITY accepts it only if it has a log-transformed scale parameter — that is, if it has a parameter $p = \log(\theta)$.

Parameter Initialization for Regression Models

The regression parameters are initialized either by using the values you specify or by the default method.

- If you provide initial values for the regression parameters, then you must provide valid, nonmissing initial values for θ_0 and β_j parameters for all j.

  You can specify the initial value for θ_0 using either the INEST= data set or the INIT= option in the DIST statement. If the distribution has a direct scale parameter (no transformation), then the initial value for the first parameter of the distribution is used as an initial value for θ_0. If the distribution has a log-transformed scale parameter, then the initial value for the first parameter of the distribution is used as an initial value for $\log(\theta_0)$.

  You can use only the INEST= data set to specify the initial values for β_j. The INEST= data set must contain nonmissing initial values for all the regressors specified in the SCALEMODEL statement. The only missing value allowed is the special missing value .R, which indicates that the regressor is linearly dependent on other regressors. If you specify .R for a regressor for one distribution, you must specify it so for all the distributions.

- If you do not specify valid initial values for θ_0 or β_j parameters for all j, then PROC HPSEVERITY initializes those parameters using the following method:

  Let a random variable Y be distributed as $\mathcal{F}(\theta, \Omega)$, where θ is the scale parameter. By the definition of the scale parameter, a random variable $W = Y/\theta$ is distributed as $\mathcal{G}(\Omega)$ such that $\mathcal{G}(\Omega) = \mathcal{F}(1, \Omega)$. Given a random error term e that is generated from a distribution $\mathcal{G}(\Omega)$, a value y from the distribution of Y can be generated as

  $$y = \theta \cdot e$$

  Taking the logarithm of both sides and using the relationship of θ with the regressors yields:

  $$\log(y) = \log(\theta_0) + \sum_{j=1}^{k} \beta_j x_j + \log(e)$$

  PROC HPSEVERITY makes use of the preceding relationship to initialize parameters of a regression model with distribution *dist* as follows:

  1. The following linear regression problem is solved to obtain initial estimates of β_0 and β_j:

     $$\log(y) = \beta_0 + \sum_{j=1}^{k} \beta_j x_j$$

     The estimates of $\beta_j (j = 1, \ldots, k)$ in the solution of this regression problem are used to initialize the respective regression parameters of the model. The estimate of β_0 is later used to initialize the value of θ_0.

The results of this regression are also used to detect whether any regressors are linearly dependent on the other regressors. If any such regressors are found, then a warning is written to the SAS log and the corresponding regressor is eliminated from further analysis. The estimates for linearly dependent regressors are denoted by a special missing value of .R in the OUTEST= data set and in any displayed output.

2. Let s_0 denote the initial value of the scale parameter.

   If the distribution model of *dist* does not contain the *dist*_PARMINIT subroutine, then s_0 and all the nonscale distribution parameters are initialized to the default value of 0.001.

   However, it is strongly recommended that each distribution's model contain the *dist*_PARMINIT subroutine. For more information, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660. If that subroutine is defined, then s_0 is initialized as follows: Each input value y_i of the response variable is transformed to its scale-normalized version w_i as

   $$w_i = \frac{y_i}{\exp(\beta_0 + \sum_{j=1}^{k} \beta_j x_{ij})}$$

   where x_{ij} denotes the value of jth regressor in the ith input observation. These w_i values are used to compute the input arguments for the *dist*_PARMINIT subroutine. The values that are computed by the subroutine for nonscale parameters are used as their respective initial values. If the distribution has an untransformed scale parameter, then s_0 is set to the value of the scale parameter that is computed by the subroutine. If the distribution has a log-transformed scale parameter P, then s_0 is computed as $s_0 = \exp(l_0)$, where l_0 is the value of P computed by the subroutine.

3. The value of θ_0 is initialized as

   $$\theta_0 = s_0 \cdot \exp(\beta_0)$$

Reporting Estimates of Regression Parameters

When you request estimates to be written to the output (either ODS displayed output or in the OUTEST= data set), the estimate of the base value of the first distribution parameter is reported. If the first parameter is the log-transformed scale parameter, then the estimate of $\log(\theta_0)$ is reported; otherwise, the estimate of θ_0 is reported. The transform of the first parameter of a distribution *dist* is controlled by the *dist*_SCALETRANSFORM function that is defined for it.

CDF Estimates with Regression Effects

When regression effects are estimated, the estimate of the scale parameter depends on the values of the regressors and the estimates of the regression parameters. This dependency results in a potentially different distribution for each observation. PROC HPSEVERITY needs to compute the estimates of the cumulative distribution function (CDF) to compute the EDF-based statistics of fit that compare the nonparametric and parametric estimates of the distribution function. To make the CDF estimates comparable across distributions and comparable to the empirical distribution function (EDF), PROC HPSEVERITY computes the CDF estimates from a representative distribution. The *representative distribution* is a mixture of a certain number of distributions, where each distribution differs only in the value of the scale parameter. You can specify the number of distributions in the mixture and how their scale values are chosen by using the DFMIXTURE= option in the SCALEMODEL statement.

Let N denote the number of observations used for EDF estimation, K denote the number of components in the mixture distribution, s_k denote the scale parameter of the kth mixture component, and d_k denote the weight associated with kth mixture component.

Let $F(y; s_k, \hat{\Omega})$ denote the CDF of the kth component distribution, where $\hat{\Omega}$ denotes the set of estimates of all parameters of the distribution other than the scale parameter. Then, the CDF estimates, $F^*(y)$, of the mixture distribution at y are computed as

$$F^*(y) = \frac{1}{D} \sum_{k=1}^{K} d_k F(y; s_k, \hat{\Omega})$$

where D is the normalization factor ($D = \sum_{k=1}^{K} d_k$). The $F^*(y)$ values are used for computing the EDF-based statistics of fit.

The scale values s_k for the K mixture components are derived from the set $\{\hat{\theta}_i\}$ ($i = 1 \ldots N$) of N scale values, where $\hat{\theta}_i$ denotes the estimate of the scale parameter due to observation i. It is computed as

$$\hat{\theta}_i = \hat{\theta}_0 \cdot \exp(\sum_{j=1}^{k} \hat{\beta}_j x_{ij})$$

where $\hat{\theta}_0$ is an estimate of the base value of the scale parameter, $\hat{\beta}_j$ are the estimates of regression coefficients, and x_{ij} is the value of regressor j in observation i.

Let w_i denote the weight of observation i. If the WEIGHT statement is specified, then it is equal to the value of the specified weight variable for the corresponding observation in the DATA= data set; otherwise, it is set to 1.

You can specify one of the following *method-names* in the DFMIXTURE= option in the SCALEMODEL statement to specify the method of choosing K and the corresponding s_k and d_k values:

FULL
: In this method, there are as many mixture components as the number of observations that are used for estimation. In other words, $K = N$, $s_k = \hat{\theta}_k$, and $d_k = w_k$ ($k = 1 \ldots N$). This is the slowest method, because it requires $O(N)$ computations to compute the mixture CDF $F^*(y_i)$ of one observation. For N observations, the computational complexity in terms of number of CDF evaluations is $O(N^2)$. Even for moderately large values of N, the time taken to compute the mixture CDF can significantly exceed the time taken to estimate the model parameters. So, it is recommended that you use this method only for small data sets.

MEAN
: In this method, the mixture contains only one distribution, whose scale value is the mean of the scale values that are implied by all the observations. In other words, s_1 is computed as

$$s_1 = \frac{1}{W} \sum_{i=1}^{N} w_i \hat{\theta}_i$$

where W is the total weight ($W = \sum_{i=1}^{N} w_i$).

This method is the fastest because it requires only one CDF evaluation per observation. The computational complexity is $O(N)$ for N observations.

If you do not specify the DFMIXTURE= option in the SCALEMODEL statement, then this is the default method.

QUANTILE

In this method, a certain number of quantiles are chosen from the set of all scale values. If you specify a value of q for the K= option when specifying this method, then $K = q-1$ and s_k are set to be the $(q-1)$ q-quantiles from the set $\{\hat{\theta}_i\}$ $(i = 1 \ldots N)$. The weight of each of the components (d_k) is assumed to be 1 for this method.

The default value of q is 2, which implies a one-point mixture with a distribution whose scale value is equal to the median scale value.

For this method, PROC HPSEVERITY needs to sort the N scale values in the set $\{\hat{\theta}_i\}$, which requires $O(N \log(N))$ computations. Then, computing mixture estimate of one observation requires $(q-1)$ CDF evaluations. Hence, the computational complexity of this method is $O(qN) + O(N \log(N))$ for computing a mixture CDF of N observations. For $q << N$, it is significantly faster than the FULL method.

RANDOM

In this method, a uniform random sample of observations is chosen and the mixture contains the distributions that are implied by those observations. If you specify a value of r for the K= option when specifying this method, then the size of the sample is r. Hence, $K = r$. If l_j denotes the index of jth observation in the sample $(j = 1 \ldots r)$, such that $1 \leq l_j \leq N$, then the scale of kth component distribution in the mixture is $s_k = \hat{\theta}_{l_k}$ and the weight associated with it is $d_k = w_{l_k}$.

You can also specify the seed to be used for generating the random sample by using the SEED= option for this method. The same sample of observations is used for all models.

Computing a mixture estimate of one observation requires r CDF evaluations. Hence, the computational complexity of this method is $O(rN)$ for computing a mixture CDF of N observations. For $r << N$, it is significantly faster than the FULL method.

Empirical Distribution Function Estimation Methods

The empirical distribution function (EDF) is a nonparametric estimate of the cumulative distribution function (CDF) of the distribution. PROC HPSEVERITY computes EDF estimates for two purposes: one is to send the estimates to a distribution's PARMINIT subroutine to initialize the distribution parameters, and the other is to compute the EDF-based statistics of fit.

To reduce the time taken to compute the EDF estimates, you can use the INITSAMPLE option to specify that only a fraction of the input data be used. If you do not specify the INITSAMPLE option and the data set has more than 10,000 valid observations, then a uniform random sample of at most 10,000 observations is used for EDF estimation.

In the MPP mode of execution, where data is distributed across the grid nodes, the EDF estimates are computed on each node, using the portion of the input data that is located on that node. These local EDF estimates are an approximation to the global EDF estimates, which would been computed by using the entire input data. PROC HPSEVERITY does not compute global EDF estimates. Let X denote a quantity that depends on the EDF estimates. X can be either an EDF-based initial value of a distribution parameter or an EDF-based statistic of fit. PROC HPSEVERITY estimates X as follows: First, each grid node k computes an estimate X_k by using the local EDF estimates that are computed on that node. Then, the estimate $\hat{X}$ of X is computed as an average of all the X_k values; that is, $\hat{X} = \sum_{i=1}^{K} X_k$, where K denotes the total number of nodes where the data reside.

This section describes the methods that are used for computing EDF estimates.

Notation

Let there be a set of N observations, each containing a quintuplet of values $(y_i, t_i^l, t_i^r, c_i^r, c_i^l), i = 1, \ldots, N$, where y_i is the value of the response variable, t_i^l is the value of the left-truncation threshold, t_i^r is the value of the right-truncation threshold, and c_i^r is the value of the right-censoring limit, c_i^l is the value of the left-censoring limit.

If an observation is not left-truncated, then $t_i^l = \tau^l$, where τ^l is the smallest value in the support of the distribution; so $F(t_i^l) = 0$. If an observation is not right-truncated, then $t_i^r = \tau_h$, where τ_h is the largest value in the support of the distribution; so $F(t_i^r) = 1$. If an observation is not right-censored, then $c_i^r = \tau^l$; so $F(c_i^r) = 0$. If an observation is not left-censored, then $c_i^l = \tau_h$; so $F(c_i^l) = 1$.

Let w_i denote the weight associated with ith observation. If you have specified the WEIGHT statement, then w_i is the normalized value of the weight variable; otherwise, it is set to 1. The weights are normalized such that they sum up to N.

An indicator function $I[e]$ takes a value of 1 or 0 if the expression e is true or false, respectively.

Estimation Methods

If the response variable is subject to both left-censoring and right-censoring effects and if you have not specified the EMPIRICALCDF=NOTURNBULL method, then PROC HPSEVERITY uses the Turnbull's method. This section describes methods other than Turnbull's method. For Turnbull's method, see the next section "Turnbull's EDF Estimation Method (Experimental)" on page 650.

The method descriptions assume that all observations are either uncensored or right-censored; that is, each observation is of the form $(y_i, t_i^l, t_i^r, \tau^l, \tau_h)$ or $(y_i, t_i^l, t_i^r, c_i^r, \tau_h)$.

If all observations are either uncensored or left-censored, then each observation is of the form $(y_i, t_i^l, t_i^r, \tau_l, c_i^l)$. It is converted to an observation $(-y_i, -t_i^r, -t_i^l, -c_i^l, \tau_h)$; that is, the signs of all the response variable values are reversed, the new left-truncation threshold is equal to the negative of the original right-truncation threshold, the new right-truncation threshold is equal to the negative of the original left-truncation threshold, and the negative of the original left-censoring limit becomes the new right-censoring limit. With this transformation, each observation is either uncensored or right-censored. The methods described for handling uncensored or right-censored data are now applicable. After the EDF estimates are computed, the observations are transformed back to the original form and EDF estimates are adjusted such $F_n(y_i) = 1 - F_n(-y_i-)$, where $F_n(-y_i-)$ denotes the EDF estimate of the value slightly less than the transformed value $-y_i$.

Further, a set of uncensored or right-censored observations can be converted to a set of observations of the form $(y_i, t_i^l, t_i^r, \delta_i)$, where δ_i is the indicator of right-censoring. $\delta_i = 0$ indicates a right-censored observation, in which case y_i is assumed to record the right-censoring limit c_i^r. $\delta_i = 1$ indicates an uncensored observation, and y_i records the exact observed value. In other words, $\delta_i = I[Y \leq C^r]$ and $y_i = \min(y_i, c_i^r)$.

Given this notation, the EDF is estimated as

$$F_n(y) = \begin{cases} 0 & \text{if } y < y^{(1)} \\ \hat{F}_n(y^{(k)}) & \text{if } y^{(k)} \leq y < y^{(k+1)}, k = 1, \ldots, N-1 \\ \hat{F}_n(y^{(N)}) & \text{if } y^{(N)} \leq y \end{cases}$$

where $y^{(k)}$ denotes the kth order statistic of the set $\{y_i\}$ and $\hat{F}_n(y^{(k)})$ is the estimate computed at that value. The definition of $\hat{F}_n$ depends on the estimation method. You can specify a particular method or let

PROC HPSEVERITY choose an appropriate method by using the EMPIRICALCDF= option in the PROC HPSEVERITY statement. Each method computes $\hat{F}_n$ as follows:

NOTURNBULL This is the default method. First, censored observations, if any, are processed as follows:

- An observation that is left-censored but not right-censored is converted to an uncensored observation $(y_i^u, t_i^l, t_i^r, \tau^l, \tau_h)$, where $y_i^u = c_i^l/2$.
- An observation that is both left-censored and right-censored is converted to an uncensored observation $(y_i^u, t_i^l, t_i^r, \tau^l, \tau_h)$, where $y_i^u = (c_i^r + c_i^l)/2$.
- An observation that is right-censored but not left-censored is left unchanged.

If the processed set of observations contains any truncated or right-censored observations, the KAPLANMEIER method is used. Otherwise, the STANDARD method is used.

The observations are modified only for the purpose of computing the EDF estimates. The original censoring information is used by the parameter estimation process.

STANDARD This method is chosen when no censoring or truncation information is specified. It is the standard way of computing EDF. The EDF estimate at observation i is computed as follows:

$$\hat{F}_n(y_i) = \frac{1}{N}\sum_{j=1}^{N} I[y_j \le y_i]$$

KAPLANMEIER This method is chosen when at least one form of censoring or truncation is specified. The Kaplan-Meier (KM) estimator, also known as the product-limit estimator, was first introduced by Kaplan and Meier (1958) for censored data. Lynden-Bell (1971) derived a similar estimator for left-truncated data. PROC HPSEVERITY uses the definition that combines both censoring and truncation information (Klein and Moeschberger 1997, Lai and Ying 1991).

The EDF estimate at observation i is computed as

$$\hat{F}_n(y_i) = 1 - \prod_{\tau \le y_i}\left(1 - \frac{n_\tau}{R_n(\tau)}\right)$$

where n_τ and $R_n(\tau)$ are defined as follows:

- $n_\tau = \sum_{k=1}^{N} w_k \cdot I[y_k = \tau \text{ and } \tau \le t_k^r \text{ and } \delta_k = 1]$, which is the number of uncensored observations ($\delta_k = 1$) for which the response variable value is equal to τ and τ is observable according to the right-truncation threshold of that observation ($\tau \le t_k^r$).
- $R_n(\tau) = \sum_{k=1}^{N} w_k \cdot I[y_k \ge \tau > t_k^l]$, which is the size (cardinality) of the risk set at τ. The term *risk set* has its origins in survival analysis; it contains the events that are at risk of failure at a given time, τ. In other words, it contains the events that have survived up to time τ and might fail at or after τ. For PROC HPSEVERITY, *time* is equivalent to the magnitude of the event and *failure* is equivalent to an uncensored and observable event, where observable means it satisfies the truncation thresholds.

MODIFIEDKM

The product-limit estimator used by the KAPLANMEIER method does not work well if the risk set size becomes very small. For right-censored data, the size can become small towards the right tail. For left-truncated data, the size can become small at the left tail and can remain so for the entire range of data. This was demonstrated by Lai and Ying (1991). They proposed a modification to the estimator that ignores the effects due to small risk set sizes.

The EDF estimate at observation i is computed as

$$\hat{F}_n(y_i) = 1 - \prod_{\tau \le y_i} \left(1 - \frac{n(\tau)}{R_n(\tau)} \cdot I[R_n(\tau) \ge cN^{\alpha}]\right)$$

where the definitions of $n(\tau)$ and $R_n(\tau)$ are identical to those used for the KAPLANMEIER method described previously.

You can specify the values of c and α by using the C= and ALPHA= options. If you do not specify a value for c, the default value used is $c = 1$. If you do not specify a value for α, the default value used is $\alpha = 0.5$.

As an alternative, you can also specify an absolute lower bound, say L, on the risk set size by using the RSLB= option, in which case $I[R_n(\tau) \ge cN^{\alpha}]$ is replaced by $I[R_n(\tau) \ge L]$ in the definition.

Turnbull's EDF Estimation Method (Experimental)

If the response variable is subject to both left-censoring and right-censoring effects and if you have not specified the NOTURNBULL method, then the HPSEVERITY procedure uses a method proposed by Turnbull (1976) to compute the nonparametric estimates of the cumulative distribution function. The original Turnbull's method is modified using the suggestions made by Frydman (1994) when truncation effects are present.

Let the input data consist of N observations in the form of quintuplets of values $(y_i, t_i^l, t_i^r, c_i^r, c_i^l), i = 1, \ldots, N$ with notation described in the section "Notation" on page 648. For each observation, let $A_i = (c_i^r, c_i^l]$ be the censoring interval; that is, the response variable value is known to lie in the interval A_i, but the exact value is not known. If an observation is uncensored, then $A_i = (y_i - \epsilon, y_i]$ for any arbitrarily small value of $\epsilon > 0$. If an observation is censored, then the value y_i is ignored. Similarly, for each observation, let $B_i = (t_i^l, t_i^r]$ be the truncation interval; that is, the observation is drawn from a truncated (conditional) distribution $F(y, B_i) = P(Y \le y | Y \in B_i)$.

Two sets, L and R, are formed using A_i and B_i as follows:

$$L = \{c_i^r, 1 \le i \le N\} \cup \{t_i^r, 1 \le i \le N\}$$
$$R = \{c_i^l, 1 \le i \le N\} \cup \{t_i^l, 1 \le i \le N\}$$

The sets L and R represent the left endpoints and right endpoints, respectively. A set of disjoint intervals $C_j = [q_j, p_j]$, $1 \le j \le M$ is formed such that $q_j \in L$ and $p_j \in R$ and $q_j \le p_j$ and $p_j < q_{j+1}$. The value of M is dependent on the nature of censoring and truncation intervals in the input data. Turnbull (1976) showed that the maximum likelihood estimate (MLE) of the EDF can increase only inside intervals C_j. In other words, the MLE estimate is constant in the interval (p_j, q_{j+1}). The likelihood is independent

of the behavior of F_n inside any of the intervals C_j. Let s_j denote the increase in F_n inside an interval C_j. Then, the EDF estimate is as follows:

$$F_n(y) = \begin{cases} 0 & \text{if } y < q_1 \\ \sum_{k=1}^{j} s_k & \text{if } p_j < y < q_{j+1}, 1 \le j \le M-1 \\ 1 & \text{if } y > p_M \end{cases}$$

PROC HPSEVERITY computes the estimates $F_n(p_j+) = F_n(q_{j+1}-) = \sum_{k=1}^{j} s_k$ at points p_j and q_{j+1} and computes $F_n(q_1-) = 0$ at point q_1, where $F_n(x+)$ denotes the limiting estimate at a point that is infinitesimally larger than x when approaching x from values larger than x and where $F_n(x-)$ denotes the limiting estimate at a point that is infinitesimally smaller than x when approaching x from values smaller than x.

PROC HPSEVERITY uses the expectation-maximization (EM) algorithm proposed by Turnbull (1976), who referred to the algorithm as the self-consistency algorithm. By default, the algorithm runs until one of the following criteria is met:

- Relative-error criterion: The maximum relative error between the two consecutive estimates of s_j falls below a threshold ϵ. If l indicates an index of the current iteration, then this can be formally stated as

$$\arg \max_{1 \le j \le M} \left\{ \frac{|s_j^l - s_j^{l-1}|}{s_j^{l-1}} \right\} \le \epsilon$$

  You can control the value of ϵ by specifying the EPS= suboption of the EDF=TURNBULL option in the PROC HPSEVERITY statement. The default value is 1.0E–8.

- Maximum-iteration criterion: The number of iterations exceeds an upper limit specified by the MAXITER= suboption of the EDF=TURNBULL option in the PROC HPSEVERITY statement. The default number of maximum iterations is 500.

The self-consistent estimates obtained in this manner might not be maximum likelihood estimates. Gentleman and Geyer (1994) suggested the use of the Kuhn-Tucker conditions for the maximum likelihood problem to ensure that the estimates are MLE. If you specify the ENSUREMLE suboption of the EDF=TURNBULL option in the PROC HPSEVERITY statement, then PROC HPSEVERITY computes the Kuhn-Tucker conditions at the end of each iteration to determine whether the estimates $\{s_j\}$ are MLE. If no truncation effects are specified, then the Kuhn-Tucker conditions derived by Gentleman and Geyer (1994) are used. If truncation effects are specified, then PROC HPSEVERITY uses modified Kuhn-Tucker conditions that account for the truncation effects. An integral part of checking the conditions is to determine whether an estimate s_j is zero or whether an estimate of the Lagrange multiplier or the reduced gradient associated with the estimate s_j is zero. PROC HPSEVERITY declares these values to be zero if they are less than or equal to a threshold δ. You can control the value of δ by specifying the ZEROPROB= suboption of the EDF=TURNBULL option in the PROC HPSEVERITY statement. The default value is 1.0E–8. The algorithm continues until the Kuhn-Tucker conditions are satisfied or the number of iterations exceeds the upper limit. The relative-error criterion stated previously is not used when the ENSUREMLE option is specified.

EDF Estimates and Truncation

If truncation is specified, then the estimate $\hat{F}_n(y)$ computed by any method other than the STANDARD method is a *conditional* estimate. In other words, $\hat{F}_n(y) = \Pr(Y \leq y | \tau_G < Y \leq \tau_H)$, where G and H denote the (unknown) distribution functions of the left-truncation threshold variable T^l and the right-truncation threshold variable T^r, respectively, τ_G denotes the smallest left-truncation threshold with a nonzero cumulative probability, and τ_H denotes the largest right-truncation threshold with a nonzero cumulative probability. Formally, $\tau_G = \inf\{s : G(s) > 0\}$ and $\tau_H = \sup\{s : H(s) > 0\}$. For computational purposes, PROC HPSEVERITY estimates τ_G and τ_H by $t^l_{\min}$ and $t^r_{\max}$, respectively, defined as

$$t^l_{\min} = \min\{t^l_k : 1 \leq k \leq N\}$$
$$t^r_{\max} = \max\{t^r_k : 1 \leq k \leq N\}$$

These estimates of $t^l_{\min}$ and $t^r_{\max}$ are used to compute the conditional estimates of the CDF as described in the section "Truncation and Conditional CDF Estimates" on page 638.

Supplying EDF Estimates to Functions and Subroutines

The parameter initialization subroutines in distribution models and some predefined utility functions require EDF estimates. For more information, see the sections "Defining a Severity Distribution Model with the FCMP Procedure" on page 660 and "Predefined Utility Functions" on page 672.

PROC HPSEVERITY supplies the EDF estimates to these subroutines and functions by using two arrays, x and F, the dimension of each array, and a type of the EDF estimates. The type identifies how the EDF estimates are computed and stored. They are as follows:

Type 1 specifies that EDF estimates are computed using the STANDARD method; that is, the data used for estimation are neither censored nor truncated.

Type 2 specifies that EDF estimates are computed using the KAPLANMEIER method; that is, the data used for estimation are subject to at least one form of truncation or censoring.

Type 3 specifies that EDF estimates are computed using the TURNBULL method; that is, the data used for estimation are subject to both left- and right-censoring. The data might or might not be truncated.

For Types 1 and 2, the EDF estimates are stored in arrays x and F of dimension N such that the following holds:

$$F_n(y) = \begin{cases} 0 & \text{if } y < x[1] \\ F[k] & \text{if } x[k] \leq y < x[k+1], k = 1, \ldots, N-1 \\ F[N] & \text{if } x[N] \leq y \end{cases}$$

where $[k]$ denotes kth element of the array ([1] denotes the first element of the array).

For Type 3, the EDF estimates are stored in arrays x and F of dimension N such that the following holds:

$$F_n(y) = \begin{cases} 0 & \text{if } y < x[1] \\ \text{undefined} & \text{if } x[2k-1] \leq y < x[2k], k = 1, \ldots, (N-1)/2 \\ F[2k] = F[2k+1] & \text{if } x[2k] \leq y < x[2k+1], k = 1, \ldots, (N-1)/2 \\ F[N] & \text{if } x[N] \leq y \end{cases}$$

Although the behavior of EDF is theoretically undefined for the interval $[x[2k-1], x[2k])$, for computational purposes, all predefined functions and subroutines assume that the EDF increases linearly from $F[2k-1]$ to $F[2k]$ in that interval if $x[2k-1] < x[2k]$. If $x[2k-1] = x[2k]$, which can happen when the EDF is estimated from a combination of uncensored and interval-censored data, the predefined functions and subroutines assume that $F_n(x[2k-1]) = F_n(x[2k]) = F[2k]$.

Statistics of Fit

PROC HPSEVERITY computes and reports various statistics of fit to indicate how well the estimated model fits the data. The statistics belong to two categories: likelihood-based statistics and EDF-based statistics. Statistics Neg2LogLike, AIC, AICC, and BIC are likelihood-based statistics, and statistics KS, AD, and CvM are EDF-based statistics.

In the MPP mode of execution, where data are distributed across the grid nodes, the EDF estimates are computed by using the local data. The EDF-based statistics are computed by using these local EDF estimates. The reported value of each EDF-based statistic is an average of the values of the statistic that are computed by all the grid nodes where the data reside. Also, for large data sets, in both SMP and MPP modes of execution, the EDF estimates are computed by using a fraction of the input data that is governed by either the INITSAMPLE option or the default sample size. Due to this nature of computing the EDF estimates, the EDF-based statistics of fit are an approximation to the values that would have been computed if the entire input data were used for computing the EDF estimates. So the values reported for EDF-based statistics should be used only for comparing different models on the same data set. The reported values should not be interpreted as true estimates of the corresponding statistics.

The likelihood-based statistics are reported for the entire input data in both SMP and MPP modes of execution.

The following subsections provide definitions of each category of statistics.

Likelihood-Based Statistics of Fit

Let $y_i, i = 1, \ldots, N$ denote the response variable values. Let L be the likelihood as defined in the section "Likelihood Function" on page 638. Let p denote the number of model parameters estimated. Note that $p = p_d + (k - k_r)$, where p_d is the number of distribution parameters, k is the number of regressors specified in the SCALEMODEL statement, and k_r is the number of regressors found to be linearly dependent (redundant) on other regressors. Given this notation, the likelihood-based statistics are defined as follows:

Neg2LogLike The log likelihood is reported as

$$\text{Neg2LogLike} = -2\log(L)$$

The multiplying factor -2 makes it easy to compare it to the other likelihood-based statistics. A model with a smaller value of Neg2LogLike is deemed better.

AIC The Akaike's information criterion (AIC) is defined as

$$\text{AIC} = -2\log(L) + 2p$$

A model with a smaller value of AIC is deemed better.

AICC The corrected Akaike's information criterion (AICC) is defined as

$$\text{AICC} = -2\log(L) + \frac{2Np}{N-p-1}$$

A model with a smaller value of AICC is deemed better. It corrects the finite-sample bias that AIC has when N is small compared to p. AICC is related to AIC as

$$\text{AICC} = \text{AIC} + \frac{2p(p+1)}{N-p-1}$$

As N becomes large compared to p, AICC converges to AIC. AICC is usually recommended over AIC as a model selection criterion.

BIC The Schwarz Bayesian information criterion (BIC) is defined as

$$\text{BIC} = -2\log(L) + p\log(N)$$

A model with a smaller value of BIC is deemed better.

EDF-Based Statistics

This class of statistics is based on the difference between the estimate of the cumulative distribution function (CDF) and the estimate of the empirical distribution function (EDF). Let $y_i, i = 1, \ldots, N$ denote the sample of N values of the response variable. Let $r_i = \sum_{j=1}^{N} I[y_j \leq y_i]$ denote the number of observations with a value less than or equal to y_i, where I is an indicator function. Let $F_n(y_i)$ denote the EDF estimate that is computed by using the method specified in the EMPIRICALCDF= option. Let $Z_i = \hat{F}(y_i)$ denote the estimate of the CDF. Let $F_n(Z_i)$ denote the EDF estimate of Z_i values that are computed using the same method that is used to compute the EDF of y_i values. Using the probability integral transformation, if $F(y)$ is the true distribution of the random variable Y, then the random variable $Z = F(y)$ is uniformly distributed between 0 and 1 (D'Agostino and Stephens 1986, Ch. 4). Thus, comparing $F_n(y_i)$ with $\hat{F}(y_i)$ is equivalent to comparing $F_n(Z_i)$ with $\hat{F}(Z_i) = Z_i$ (uniform distribution).

Note the following two points regarding which CDF estimates are used for computing the test statistics:

- If regressor variables are specified, then the CDF estimates Z_i used for computing the EDF test statistics are from a mixture distribution. See the section "CDF Estimates with Regression Effects" on page 645 for more information.
- If the EDF estimates are conditional because of the truncation information, then each unconditional estimate Z_i is converted to a conditional estimate using the method described in the section "Truncation and Conditional CDF Estimates" on page 638.

In the following, it is assumed that Z_i denotes an appropriate estimate of the CDF if truncation or regression effects are specified. Given this, the EDF-based statistics of fit are defined as follows:

KS The Kolmogorov-Smirnov (KS) statistic computes the largest vertical distance between the CDF and the EDF. It is formally defined as follows:

$$\text{KS} = \sup_y |F_n(y) - F(y)|$$

If the STANDARD method is used to compute the EDF, then the following formula is used:

$$D^+ = \max_i(\frac{r_i}{N} - Z_i)$$
$$D^- = \max_i(Z_i - \frac{r_{i-1}}{N})$$
$$\text{KS} = \sqrt{N}\ \max(D^+, D^-) + \frac{0.19}{\sqrt{N}}$$

Note that r_0 is assumed to be 0.

If the method used to compute the EDF is any method other than the STANDARD method, then the following formula is used:

$$D^+ = \max_i(F_n(Z_i) - Z_i), \text{ if } F_n(Z_i) \geq Z_i$$
$$D^- = \max_i(Z_i - F_n(Z_i)), \text{ if } F_n(Z_i) < Z_i$$
$$\text{KS} = \sqrt{N}\ \max(D^+, D^-) + \frac{0.19}{\sqrt{N}}$$

AD The Anderson-Darling (AD) statistic is a quadratic EDF statistic that is proportional to the expected value of the weighted squared difference between the EDF and CDF. It is formally defined as follows:

$$\text{AD} = N \int_{-\infty}^{\infty} \frac{(F_n(y) - F(y))^2}{F(y)(1 - F(y))} dF(y)$$

If the STANDARD method is used to compute the EDF, then the following formula is used:

$$\text{AD} = -N - \frac{1}{N} \sum_{i=1}^{N} [(2r_i - 1)\log(Z_i) + (2N + 1 - 2r_i)\log(1 - Z_i)]$$

If the method used to compute the EDF is any method other than the STANDARD method, then the statistic can be computed by using the following two pieces of information:

- If the EDF estimates are computed using the KAPLANMEIER or MODIFIEDKM methods, then EDF is a step function such that the estimate $F_n(z)$ is a constant equal to $F_n(Z_{i-1})$ in interval $[Z_{i-1}, Z_i]$. If the EDF estimates are computed using the TURNBULL method, then there are two types of intervals: one in which the EDF curve is constant and the other in which the EDF curve is theoretically undefined. For computational purposes, it is assumed that the EDF curve is linear for the latter type of the interval. For each method, the EDF estimate $F_n(y)$ at y can be written as

  $$F_n(z) = F_n(Z_{i-1}) + S_i(z - Z_{i-1}), \text{ for } z \in [Z_{i-1}, Z_i]$$

  where S_i is the slope of the line defined as

  $$S_i = \frac{F_n(Z_i) - F_n(Z_{i-1})}{Z_i - Z_{i-1}}$$

  For the KAPLANMEIER or MODIFIEDKM method, $S_i = 0$ in each interval.

- Using the probability integral transform $z = F(y)$, the formula simplifies to

$$\text{AD} = N \int_{-\infty}^{\infty} \frac{(F_n(z) - z)^2}{z(1-z)} dz$$

The computation formula can then be derived from the following approximation:

$$\begin{aligned}
\text{AD} &= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} \frac{(F_n(z) - z)^2}{z(1-z)} dz \\
&= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} \frac{(F_n(Z_{i-1}) + S_i(z - Z_{i-1}) - z)^2}{z(1-z)} dz \\
&= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} \frac{(P_i - Q_i z)^2}{z(1-z)} dz
\end{aligned}$$

where $P_i = F_n(Z_{i-1}) - S_i Z_{i-1}$, $Q_i = 1 - S_i$, and K is the number of points at which the EDF estimate are computed. For the TURNBULL method, $K = 2k$ for some k.

Assuming $Z_0 = 0$, $Z_{K+1} = 1$, $F_n(0) = 0$, and $F_n(Z_K) = 1$ yields the following computation formula:

$$\begin{aligned}
\text{AD} = &- N(Z_1 + \log(1 - Z_1) + \log(Z_K) + (1 - Z_K)) \\
&+ N \sum_{i=2}^{K} \left[P_i^2 A_i - (Q_i - P_i)^2 B_i - Q_i^2 C_i \right]
\end{aligned}$$

where $A_i = \log(Z_i) - \log(Z_{i-1})$, $B_i = \log(1 - Z_i) - \log(1 - Z_{i-1})$, and $C_i = Z_i - Z_{i-1}$.

If EDF estimates are computed using the KAPLANMEIER or MODIFIEDKM method, then $P_i = F_n(Z_{i-1})$ and $Q_i = 1$, which simplifies the formula as

$$\begin{aligned}
\text{AD} = &- N(1 + \log(1 - Z_1) + \log(Z_K)) \\
&+ N \sum_{i=2}^{K} \left[F_n(Z_{i-1})^2 A_i - (1 - F_n(Z_{i-1}))^2 B_i \right]
\end{aligned}$$

CvM The Cramér-von Mises (CvM) statistic is a quadratic EDF statistic that is proportional to the expected value of the squared difference between the EDF and CDF. It is formally defined as follows:

$$\text{CvM} = N \int_{-\infty}^{\infty} (F_n(y) - F(y))^2 dF(y)$$

If the STANDARD method is used to compute the EDF, then the following formula is used:

$$\text{CvM} = \frac{1}{12N} + \sum_{i=1}^{N} \left(Z_i - \frac{(2r_i - 1)}{2N} \right)^2$$

If the method used to compute the EDF is any method other than the STANDARD method, then the statistic can be computed by using the following two pieces of information:

- As described previously for the AD statistic, the EDF estimates are assumed to be piecewise linear such that the estimate $F_n(y)$ at y is

$$F_n(z) = F_n(Z_{i-1}) + S_i(z - Z_{i-1}), \text{ for } z \in [Z_{i-1}, Z_i]$$

  where S_i is the slope of the line defined as

$$S_i = \frac{F_n(Z_i) - F_n(Z_{i-1})}{Z_i - Z_{i-1}}$$

  For the KAPLANMEIER or MODIFIEDKM method, $S_i = 0$ in each interval.

- Using the probability integral transform $z = F(y)$, the formula simplifies to:

$$\text{CvM} = N \int_{-\infty}^{\infty} (F_n(z) - z)^2 dz$$

The computation formula can then be derived from the following approximation:

$$\begin{aligned}
\text{CvM} &= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} (F_n(z) - z)^2 dz \\
&= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} (F_n(Z_{i-1}) + S_i(z - Z_{i-1}) - z)^2 dz \\
&= N \sum_{i=1}^{K+1} \int_{Z_{i-1}}^{Z_i} (P_i - Q_i z)^2 dz
\end{aligned}$$

where $P_i = F_n(Z_{i-1}) - S_i Z_{i-1}$, $Q_i = 1 - S_i$, and K is the number of points at which the EDF estimate are computed. For the TURNBULL method, $K = 2k$ for some k.

Assuming $Z_0 = 0$, $Z_{K+1} = 1$, and $F_n(0) = 0$ yields the following computation formula:

$$\text{CvM} = N \frac{Z_1^3}{3} + N \sum_{i=2}^{K+1} \left[P_i^2 A_i - P_i Q_i B_i - \frac{Q_i^2}{3} C_i \right]$$

where $A_i = Z_i - Z_{i-1}$, $B_i = Z_i^2 - Z_{i-1}^2$, and $C_i = Z_i^3 - Z_{i-1}^3$.

If EDF estimates are computed using the KAPLANMEIER or MODIFIEDKM method, then $P_i = F_n(Z_{i-1})$ and $Q_i = 1$, which simplifies the formula as

$$\text{CvM} = \frac{N}{3} + N \sum_{i=2}^{K+1} \left[F_n(Z_{i-1})^2 (Z_i - Z_{i-1}) - F_n(Z_{i-1})(Z_i^2 - Z_{i-1}^2) \right]$$

which is similar to the formula proposed by Koziol and Green (1976).

Distributed and Multithreaded Computation

PROC HPSEVERITY makes an attempt to use all the computational resources that you specify in the PERFORMANCE statement in order to complete the assigned tasks as fast as possible. This section describes the distributed and multithreading computing methods that PROC HPSEVERITY uses.

Distributed Computing

Distributed computing refers to the organization of computation work into multiple tasks that are processed on different nodes, where a node refers to one of the machines that constitute the grid. The number of nodes used by PROC HPSEVERITY is determined by the execution model for massively parallel processing (MPP). If you specify the client-data (or local-data) model of execution, then the number of nodes is determined by the NODES= option in the PERFORMANCE statement. If you are using the alongside-database model of execution, then the number of nodes is determined internally by PROC HPSEVERITY using the information associated with the DATA= data set and the grid information that you specify either in the PERFORMANCE statement or in the grid environment variables. See the section "SMP and MPP Modes" on page 16 for a detailed description of MPP execution models.

In the client-data model, PROC HPSEVERITY distributes the input data across the number of nodes that you specify. It uses the round-robin method; that is, it sends the first observation to the first node, second observation to the second node, and so forth.

In the alongside-the-database model, PROC HPSEVERITY uses the existing distributed organization of the data, and knows about the number of nodes. So, you do not need to specify the NODES= option.

The number of nodes that are used for distributed computing is displayed in the "Performance Information" table, which is part of the default output.

Multithreading

Threading refers to the organization of computational work into multiple tasks (processing units that can be scheduled by the operating system). A task is associated with a thread. Multithreading refers to the concurrent execution of threads. When multithreading is possible, substantial performance gains can be realized compared to sequential (single-threaded) execution.

The number of threads spawned by the HPSEVERITY procedure is determined by the number of CPUs on a machine and can be controlled in the following ways:

- You can specify the CPU count with the CPUCOUNT= SAS system option. For example, if you specify the following statements, the HPSEVERITY procedure schedules threads as if it executes on a system with four CPUs, regardless of the actual CPU count.

```
options cpucount=4;
```

- You can specify the NTHREADS= option in the PERFORMANCE statement to determine the number of threads. This specification overrides the system option. Specify NTHREADS=1 to force single-threaded execution.
- You can specify the CPUCOUNT=*n* option in the PERFORMANCE statement, which overrides the CPUCOUNT= system option and instructs the HPSEVERITY procedure to operate as if it executed on a machine with *n* CPUs.

The number of threads per machine is displayed in the "Performance Information" table, which is part of the default output.

Combining the Power of Distributed and Multithreading Computing

The HPSEVERITY procedure combines the powers of distributed and multithreading paradigms by using a data-parallel model. In particular, the distributed tasks are defined by dividing the data among multiple nodes, and within one node, the multithreading tasks are defined by further dividing the local data among the threads. For example, if the input data set has 10,000 observations and you are running on a grid with 5 nodes, then each node processes 2,000 observations (this assumes that if you have specified an alongside-the-database model, then you have equally and randomly divided the input data among the nodes). Further, if each node has eight CPUs, then 250 observations are associated with each thread within the node. All computations that require access to the data are then distributed and multithreaded.

Note that in the SMP mode (see the section "SMP and MPP Modes" on page 16), only multithreading is available.

When you specify more than one candidate distribution model, for some tasks PROC HPSEVERITY exploits the independence among models by processing multiple models in parallel on a single node such that each model is assigned to one of the threads executing in parallel. When a thread finishes processing the assigned model, it starts processing the next unprocessed model, if one exists.

The computations that take advantage of the distributed and multithreaded model include the following:

- Validation and preparation of data: In this stage, the observations in the input data set are validated and transformed, if necessary. The summary statistics of the data are prepared. Since each observation is independent, the computations can be distributed among nodes and threads-within-nodes without significant communication overhead.

- Initialization of distribution parameters: In this stage, the parallelism is achieved by initializing multiple models in parallel. The only computational step that is not fully parallelized in this release is the step of computing empirical distribution function (EDF) estimates, which are required when PROC HPSEVERITY needs to invoke a distribution's PARMINIT subroutine to initialize distribution parameters. The EDF estimation step is not amenable to full-fledged parallelism because it requires sequential access to sorted data, especially when the loss variable is modified by truncation effects. When the data are distributed across nodes, the EDF computations take place on local data and the PARMINIT function is invoked on the local data using the local EDF estimates. The initial values that are supplied to the nonlinear optimizer are computed by averaging the local estimates of the distribution parameters returned by the PARMINIT functions on each node.

- Initialization of regression parameters (if SCALEMODEL statement is specified): In this stage, if you have not specified initial values for the regression parameters by using the INEST= data set, then PROC HPSEVERITY initializes those parameters by solving a linear regression problem $\log(y) = \beta_0 + \sum_{i=1}^{k} \beta_j x_j$. For more information, see the section "Parameter Initialization for Regression Models" on page 644. The most computationally intensive step is the formation of the crossproducts matrix. PROC HPSEVERITY exploits the parallelism by observing the fact that the contribution to the crossproducts matrix due to one observation is independent from the contribution due to another observation. Each node computes the contribution of its local data to each entry of the crossproducts matrix. Within each node, each thread computes the contribution of its chunk of data to each entry of the crossproducts matrix. On each node, the contributions from all the threads are added up to form the contribution due to all of the local data. The partial crossproducts matrices are then gathered from all nodes on a central node, which sums them up to form the final crossproducts matrix.

- Optimization: In this stage, the nonlinear optimizer iterates over the parameter space in search of the optimal set of parameters. In each iteration, it evaluates the objective function along with the gradient and Hessian of the objective function, if needed by the optimization method. Within one iteration, for the current estimates of the parameters, each observation's contribution to the objective function, gradient, and Hessian is independent of another observation. This enables PROC HPSEVERITY to fully exploit the distributed and multithreaded paradigms to efficiently parallelize each iteration of the algorithm.

Defining a Severity Distribution Model with the FCMP Procedure

A *severity distribution model* consists of a set of functions and subroutines that are defined using the FCMP procedure. The FCMP procedure is part of Base SAS software. Each function or subroutine must be named as <*distribution-name*>_<*keyword*>, where *distribution-name* is the identifying short name of the distribution and *keyword* identifies one of the functions or subroutines. The total length of the name should not exceed 32. Each function or subroutine must have a specific signature, which consists of the number of arguments, sequence and types of arguments, and return value type. The summary of all the recognized function and subroutine names and their expected behavior is given in Table 24.6.

Consider the following points when you define a distribution model:

- When you define a function or subroutine requiring parameter arguments, the names and order of those arguments must be the same. Arguments other than the parameter arguments can have any name, but they must satisfy the requirements on their type and order.
- When the HPSEVERITY procedure invokes any function or subroutine, it provides the necessary input values according to the specified signature, and expects the function or subroutine to prepare the output and return it according to the specification of the return values in the signature.
- You can typically use most of the SAS programming statements and SAS functions that you can use in a DATA step for defining the FCMP functions and subroutines. However, there are a few differences in the capabilities of the DATA step and the FCMP procedure. To learn more, see the documentation of the FCMP procedure in the *Base SAS Procedures Guide*.
- You must specify either the PDF or the LOGPDF function. Similarly, you must specify either the CDF or the LOGCDF function. All other functions are optional, except when necessary for correct definition of the distribution. It is strongly recommended that you define the PARMINIT subroutine to provide a good set of initial values for the parameters. The information provided by PROC HPSEVERITY to the PARMINIT subroutine enables you to use popular initialization approaches based on the method of moments and the method of percentile matching, but you can implement any algorithm to initialize the parameters by using the values of the response variable and the estimate of its empirical distribution function.
- The LOWERBOUNDS subroutines should be defined if the lower bound on at least one distribution parameter is different from the default lower bound of 0. If you define a LOWERBOUNDS subroutine but do not set a lower bound for some parameter inside the subroutine, then that parameter is assumed to have no lower bound (or a lower bound of $-\infty$). Hence, it is recommended that you explicitly return the lower bound for each parameter when you define the LOWERBOUNDS subroutine.

- The UPPERBOUNDS subroutines should be defined if the upper bound on at least one distribution parameter is different from the default upper bound of ∞. If you define an UPPERBOUNDS subroutine but do not set an upper bound for some parameter inside the subroutine, then that parameter is assumed to have no upper bound (or a upper bound of ∞). Hence, it is recommended that you explicitly return the upper bound for each parameter when you define the UPPERBOUNDS subroutine.

- If you want to use the distribution in a model with regression effects, then make sure that the first parameter of the distribution is the scale parameter itself or a log-transformed scale parameter. If the first parameter is a log-transformed scale parameter, then you must define the SCALETRANSFORM function.

- In general, it is not necessary to define the gradient and Hessian functions, because the HPSEVERITY procedure uses an internal system to evaluate the required derivatives. The internal system typically computes the derivatives analytically. But it might not be able to do so if your function definitions use other functions that it cannot differentiate analytically. In such cases, derivatives are approximated using a finite difference method and a note is written to the SAS log to indicate the components that are differentiated using such approximations. PROC HPSEVERITY does reasonably well with these finite difference approximations. But, if you know of a way to compute the derivatives of such components analytically, then you should define the gradient and Hessian functions.

In order to use your distribution with PROC HPSEVERITY, you need to record the FCMP library that contains the functions and subroutines for your distribution and other FCMP libraries that contain FCMP functions or subroutines used within your distribution's functions and subroutines. Specify all those libraries in the CMPLIB= system option by using the OPTIONS global statement. For more information about the OPTIONS statement, see *SAS Statements: Reference*. For more information about the CMPLIB= system option, see *SAS System Options: Reference*.

Each predefined distribution mentioned in the section "Predefined Distributions" on page 627 has a distribution model associated with it. The functions and subroutines of all those models are available in the Sashelp.Hpsevdst library. The order of the parameters in the signatures of the functions and subroutines is the same as listed in Table 24.2. You do not need to use the CMPLIB= option in order to use the predefined distributions with PROC HPSEVERITY. However, if you need to use the functions or subroutines of the predefined distributions in SAS statements other than the PROC HPSEVERITY step (such as in a DATA step), then specify the Sashelp.Hpsevdst library in the CMPLIB= system option by using the OPTIONS global statement prior to using them.

Table 24.6 shows functions and subroutines that define a distribution model, and subsections after the table provide more detail. The functions are listed in alphabetical order of the keyword suffix.

Table 24.6 List of Functions and Subroutines That Define a Distribution Model

Name	Type	Required	Expected to Return
*dist*_CDF	Function	YES[1]	Cumulative distribution function value
*dist*_CDFGRADIENT	Subroutine	NO	Gradient of the CDF
*dist*_CDFHESSIAN	Subroutine	NO	Hessian of the CDF
*dist*_CONSTANTPARM	Subroutine	NO	Constant parameters
*dist*_DESCRIPTION	Function	NO	Description of the distribution
*dist*_LOGCDF	Function	YES[1]	Log of cumulative distribution function value
*dist*_LOGCDFGRADIENT	Subroutine	NO	Gradient of the LOGCDF
*dist*_LOGCDFHESSIAN	Subroutine	NO	Hessian of the LOGCDF
*dist*_LOGPDF	Function	YES[2]	Log of probability density function value
*dist*_LOGPDFGRADIENT	Subroutine	NO	Gradient of the LOGPDF
*dist*_LOGPDFHESSIAN	Subroutine	NO	Hessian of the LOGPDF
*dist*_LOGSDF	Function	NO	Log of survival function value
*dist*_LOGSDFGRADIENT	Subroutine	NO	Gradient of the LOGSDF
*dist*_LOGSDFHESSIAN	Subroutine	NO	Hessian of the LOGSDF
*dist*_LOWERBOUNDS	Subroutine	NO	Lower bounds on parameters
*dist*_PARMINIT	Subroutine	NO	Initial values for parameters
*dist*_PDF	Function	YES[2]	Probability density function value
*dist*_PDFGRADIENT	Subroutine	NO	Gradient of the PDF
*dist*_PDFHESSIAN	Subroutine	NO	Hessian of the PDF
*dist*_SCALETRANSFORM	Function	NO	Type of relationship between the first distribution parameter and the scale parameter
*dist*_SDF	Function	NO	Survival function value
*dist*_SDFGRADIENT	Subroutine	NO	Gradient of the SDF
*dist*_SDFHESSIAN	Subroutine	NO	Hessian of the SDF
*dist*_UPPERBOUNDS	Subroutine	NO	Upper bounds on parameters

Notes:
1. Either the *dist*_CDF or the *dist*_LOGCDF function must be defined.
2. Either the *dist*_PDF or the *dist*_LOGPDF function must be defined.

The signature syntax and semantics of each function or subroutine are as follows:

***dist*_CDF**

defines a function that returns the value of the cumulative distribution function (CDF) of the distribution at the specified values of the random variable and distribution parameters.

- *Type*: Function
- *Required*: YES

- *Number of arguments*: $m + 1$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  x Numeric value of the random variable at which the CDF value should be evaluated

  p1 Numeric value of the first parameter

  p2 Numeric value of the second parameter

  .....

  p*m* Numeric value of the *m*th parameter

- *Return value*: Numeric value that contains the CDF value $F(x; p_1, p_2, \ldots, p_m)$

If you want to consider this distribution as a candidate distribution when you estimate a response variable model with regression effects, then the first parameter of this distribution must be a scale parameter or log-transformed scale parameter. In other words, if the distribution has a scale parameter, then the following equation must be satisfied:

$$F(x; p_1, p_2, \ldots, p_m) = F(\frac{x}{p_1}; 1, p_2, \ldots, p_m)$$

If the distribution has a log-transformed scale parameter, then the following equation must be satisfied:

$$F(x; p_1, p_2, \ldots, p_m) = F(\frac{x}{\exp(p_1)}; 0, p_2, \ldots, p_m)$$

Here is a sample structure of the function for a distribution named 'FOO':

```
function FOO_CDF(x, P1, P2);
    /* Code to compute CDF by using x, P1, and P2 */

    F = <computed CDF>;
    return (F);
endsub;
```

*dist*_CONSTANTPARM

defines a subroutine that specifies constant parameters. A parameter is *constant* if it is required for defining a distribution but is not subject to optimization in PROC HPSEVERITY. Constant parameters are required to be part of the model in order to compute the PDF or the CDF of the distribution. Typically, values of these parameters are known a priori or estimated using some means other than the maximum likelihood method used by PROC HPSEVERITY. You can estimate them inside the *dist*_PARMINIT subroutine. Once initialized, the parameters remain constant in the context of PROC HPSEVERITY; that is, they retain their initial value. PROC HPSEVERITY estimates only the nonconstant parameters.

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: k, where k is the number of constant parameters

- *Sequence and type of arguments*:

  constant parameter 1 Name of the first constant parameter

  . . . . .

  constant parameter k Name of the kth constant parameter

- *Return value*: None

Here is a sample structure of the subroutine for a distribution named 'FOO' that has P3 and P5 as its constant parameters, assuming that distribution has at least three parameters:

```
subroutine FOO_CONSTANTPARM(p5, p3);
endsub;
```

Note the following points when you specify the constant parameters:

- At least one distribution parameter must be free to be optimized; that is, if a distribution has total m parameters, then k must be strictly less than m.
- If you want to use this distribution for modeling regression effects, then the first parameter must not be a constant parameter.
- The order of arguments in the signature of this subroutine does not matter as long as each argument's name matches the name of one of the parameters that are defined in the signature of the *dist*_PDF function.
- The constant parameters must be specified in signatures of all the functions and subroutines that accept distribution parameters as their arguments.
- You must provide a nonmissing initial value for each constant parameter by using one of the supported parameter initialization methods.

*dist*_DESCRIPTION

defines a function that returns a description of the distribution.

- *Type*: Function
- *Required*: NO
- *Number of arguments*: None
- *Sequence and type of arguments*: Not applicable
- *Return value*: Character value containing a description of the distribution

Here is a sample structure of the function for a distribution named 'FOO':

```
function FOO_DESCRIPTION() $48;
    length desc $48;
    desc = "A model for a continuous distribution named foo";
    return (desc);
endsub;
```

There is no restriction on the length of the description (the length of 48 used in the previous example is for illustration purposes only). However, if the length is greater than 256, then only the first 256 characters appear in the displayed output and in the _DESCRIPTION_ variable of the OUTMODELINFO= data set. Hence, the recommended length of the description is less than or equal to 256.

*dist*_**LOG***core*

defines a function that returns the natural logarithm of the specified *core* function of the distribution at the specified values of the random variable and distribution parameters. The *core* keyword can be PDF, CDF, or SDF.

- *Type*: Function
- *Required*: YES only if *core* is PDF or CDF and you have not defined that *core* function; otherwise, NO
- *Number of arguments*: $m + 1$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  x Numeric value of the random variable at which the natural logarithm of the *core* function should be evaluated

  p1 Numeric value of the first parameter

  p2 Numeric value of the second parameter

  . . . .

  p*m* Numeric value of the *m*th parameter

- *Return value*: Numeric value that contains the natural logarithm of the *core* function

Here is a sample structure of the function for the core function PDF of a distribution named 'FOO':

```
function FOO_LOGPDF(x, P1, P2);
    /* Code to compute LOGPDF by using x, P1, and P2 */

    l = <computed LOGPDF>;
    return (l);
endsub;
```

*dist*_**LOWERBOUNDS**

defines a subroutine that returns lower bounds for the parameters of the distribution. If this subroutine is not defined for a given distribution, then the HPSEVERITY procedure assumes a lower bound of 0 for each parameter. If a lower bound of l_i is returned for a parameter p_i, then the HPSEVERITY procedure assumes that $l_i < p_i$ (strict inequality). If a missing value is returned for some parameter, then the HPSEVERITY procedure assumes that there is no lower bound for that parameter (equivalent to a lower bound of $-\infty$).

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: m, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  p1 Output argument that returns the lower bound on the first parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

  p2 Output argument that returns the lower bound on the second parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

  . . . .

p*m* Output argument that returns the lower bound on the *m*th parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

- *Return value*: The results, lower bounds on parameter values, should be returned in the parameter arguments of the subroutine.

Here is a sample structure of the subroutine for a distribution named 'FOO':

```
subroutine FOO_LOWERBOUNDS(p1, p2);
    outargs p1, p2;

    p1 = <lower bound for P1>;
    p2 = <lower bound for P2>;
endsub;
```

*dist*_PARMINIT

defines a subroutine that returns the initial values for the distribution's parameters given an empirical distribution function (EDF) estimate.

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: $m + 4$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

dim Input numeric value that contains the dimension of the x, nx, and F array arguments.

x{*} Input numeric array of dimension *dim* that contains values of the random variables at which the EDF estimate is available. It can be assumed that x contains values in an increasing order. In other words, if $i < j$, then x[i] < x[j].

nx{*} Input numeric array of dimension *dim*. Each nx[i] contains the number of observations in the original data that have the value x[i].

F{*} Input numeric array of dimension *dim*. Each F[i] contains the EDF estimate for x[i]. This estimate is computed by the HPSEVERITY procedure based on the options specified in the LOSS statement.

Ftype Input numeric value that contains the type of the EDF estimate that is stored in x and F. See the section "Supplying EDF Estimates to Functions and Subroutines" on page 652 for definition of types.

p1 Output argument that returns the initial value of the first parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

p2 Output argument that returns the initial value of the second parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

. . . .

p*m* Output argument that returns the initial value of the *m*th parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

- *Return value*: The results, initial values of the parameters, should be returned in the parameter arguments of the subroutine.

Here is a sample structure of the subroutine for a distribution named 'FOO':

```
subroutine FOO_PARMINIT(dim, x{*}, nx{*}, F{*}, Ftype, p1, p2);
    outargs p1, p2;

    /* Code to initialize values of P1 and P2 by using
       dim, x, nx, and F */

    p1 = <initial value for p1>;
    p2 = <initial value for p2>;
endsub;
```

***dist*_PDF**

defines a function that returns the value of the probability density function (PDF) of the distribution at the specified values of the random variable and distribution parameters.

- *Type*: Function
- *Required*: YES
- *Number of arguments*: $m + 1$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  x Numeric value of the random variable at which the PDF value should be evaluated

  p1 Numeric value of the first parameter

  p2 Numeric value of the second parameter

  .....

  pm Numeric value of the mth parameter

- *Return value*: Numeric value that contains the PDF value $f(x; p_1, p_2, \ldots, p_m)$

If you want to consider this distribution as a candidate distribution when you estimate a response variable model with regression effects, then the first parameter of this distribution must be a scale parameter or log-transformed scale parameter. In other words, if the distribution has a scale parameter, then the following equation must be satisfied:

$$f(x; p_1, p_2, \ldots, p_m) = \frac{1}{p_1} f(\frac{x}{p_1}; 1, p_2, \ldots, p_m)$$

If the distribution has a log-transformed scale parameter, then the following equation must be satisfied:

$$f(x; p_1, p_2, \ldots, p_m) = \frac{1}{\exp(p_1)} f(\frac{x}{\exp(p_1)}; 0, p_2, \ldots, p_m)$$

Here is a sample structure of the function for a distribution named 'FOO':

```
function FOO_PDF(x, P1, P2);
    /* Code to compute PDF by using x, P1, and P2 */

    f = <computed PDF>;
    return (f);
endsub;
```

*dist*_SCALETRANSFORM

defines a function that returns a keyword to identify the transform that needs to be applied to the scale parameter to convert it to the first parameter of the distribution.

If you want to use this distribution for modeling regression effects, then the first parameter of this distribution must be a scale parameter. However, for some distributions, a typical or convenient parameterization might not have a scale parameter, but one of the parameters can be a simple transform of the scale parameter. As an example, consider a typical parameterization of the lognormal distribution with two parameters, location μ and shape σ, for which the PDF is defined as follows:

$$f(x;\mu,\sigma) = \frac{1}{x\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{\log(x)-\mu}{\sigma}\right)^2}$$

You can reparameterize this distribution to contain a parameter θ instead of the parameter μ such that $\mu = \log(\theta)$. The parameter θ would then be a scale parameter. However, if you want to specify the distribution in terms of μ and σ (which is a more recognized form of the lognormal distribution) and still allow it as a candidate distribution for estimating regression effects, then instead of writing another distribution with parameters θ and σ, you can simply define the distribution with μ as the first parameter and specify that it is the logarithm of the scale parameter.

- *Type*: Function
- *Required*: NO
- *Number of arguments*: None
- *Sequence and type of arguments*: Not applicable
- *Return value*: Character value that contains one of the following keywords:

LOG	specifies that the first parameter is the logarithm of the scale parameter.
IDENTITY	specifies that the first parameter is a scale parameter without any transformation.

If this function is not specified, then the IDENTITY transform is assumed.

Here is a sample structure of the function for a distribution named 'FOO':

```
function FOO_SCALETRANSFORM() $8;
    length xform $8;
    xform = "IDENTITY";
    return (xform);
endsub;
```

*dist*_SDF

defines a function that returns the value of the survival distribution function (SDF) of the distribution at the specified values of the random variable and distribution parameters.

- *Type*: Function
- *Required*: NO
- *Number of arguments*: $m + 1$, where m is the number of distribution parameters

- *Sequence and type of arguments*:

  x Numeric value of the random variable at which the SDF value should be evaluated

  p1 Numeric value of the first parameter

  p2 Numeric value of the second parameter

  ....

  p*m* Numeric value of the *m*th parameter

- *Return value*: Numeric value that contains the SDF value $S(x; p_1, p_2, \ldots, p_m)$

If you want to consider this distribution as a candidate distribution when estimating a response variable model with regression effects, then the first parameter of this distribution must be a scale parameter or log-transformed scale parameter. In other words, if the distribution has a scale parameter, then the following equation must be satisfied:

$$S(x; p_1, p_2, \ldots, p_m) = S(\frac{x}{p_1}; 1, p_2, \ldots, p_m)$$

If the distribution has a log-transformed scale parameter, then the following equation must be satisfied:

$$S(x; p_1, p_2, \ldots, p_m) = S(\frac{x}{\exp(p_1)}; 0, p_2, \ldots, p_m)$$

Here is a sample structure of the function for a distribution named 'FOO':

```
function FOO_SDF(x, P1, P2);
    /* Code to compute SDF by using x, P1, and P2 */

    S = <computed SDF>;
    return (S);
endsub;
```

*dist*_UPPERBOUNDS

defines a subroutine that returns upper bounds for the parameters of the distribution. If this subroutine is not defined for a given distribution, then the HPSEVERITY procedure assumes that there is no upper bound for any of the parameters. If an upper bound of u_i is returned for a parameter p_i, then the HPSEVERITY procedure assumes that $p_i < u_i$ (strict inequality). If a missing value is returned for some parameter, then the HPSEVERITY procedure assumes that there is no upper bound for that parameter (equivalent to an upper bound of ∞).

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: m, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  p1 Output argument that returns the upper bound on the first parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

  p2 Output argument that returns the upper bound on the second parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

  ....

p*m* Output argument that returns the upper bound on the *m*th parameter. This must be specified in the OUTARGS statement inside the subroutine's definition.

- *Return value*: The results, upper bounds on parameter values, should be returned in the parameter arguments of the subroutine.

Here is a sample structure of the subroutine for a distribution named 'FOO':

```
subroutine FOO_UPPERBOUNDS(p1, p2);
    outargs p1, p2;

    p1 = <upper bound for P1>;
    p2 = <upper bound for P2>;
endsub;
```

*dist_core*GRADIENT

defines a subroutine that returns the gradient vector of the specified *core* function of the distribution at the specified values of the random variable and distribution parameters. The *core* keyword can be PDF, CDF, SDF, LOGPDF, LOGCDF, or LOGSDF.

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: $m + 2$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

  x Numeric value of the random variable at which the gradient should be evaluated

  p1 Numeric value of the first parameter

  p2 Numeric value of the second parameter

  .....

  p*m* Numeric value of the *m*th parameter

  grad{*} Output numeric array of size m that contains the gradient vector evaluated at the specified values. If h denotes the value of the *core* function, then the expected order of the values in the array is as follows: $\frac{\partial h}{\partial p_1}\ \frac{\partial h}{\partial p_2} \cdots \frac{\partial h}{\partial p_m}$

- *Return value*: Numeric array that contains the gradient evaluated at x for the parameter values $(p_1, p_2, \ldots, p_m)$

Here is a sample structure of the function for the core function CDF of a distribution named 'FOO':

```
subroutine FOO_CDFGRADIENT(x, P1, P2, grad{*});
    outargs grad;

    /* Code to compute gradient by using x, P1, and P2 */
    grad[1] = <partial derivative of CDF w.r.t. P1
               evaluated at x, P1, P2>;
    grad[2] = <partial derivative of CDF w.r.t. P2
               evaluated at x, P1, P2>;
endsub;
```

*dist_core*__HESSIAN__

defines a subroutine that returns the Hessian matrix of the specified *core* function of the distribution at the specified values of the random variable and distribution parameters. The *core* keyword can be PDF, CDF, SDF, LOGPDF, LOGCDF, or LOGSDF.

- *Type*: Subroutine
- *Required*: NO
- *Number of arguments*: $m + 2$, where m is the number of distribution parameters
- *Sequence and type of arguments*:

x	Numeric value of the random variable at which the Hessian matrix should be evaluated
p1	Numeric value of the first parameter
p2	Numeric value of the second parameter
	…..
p*m*	Numeric value of the *m*th parameter
hess{*}	Output numeric array of size $m(m+1)/2$ that contains the lower triangular portion of the Hessian matrix in a packed vector form, evaluated at the specified values. If h denotes the value of the *core* function, then the expected order of the values in the array is as follows: $\frac{\partial^2 h}{\partial p_1^2} \mid \frac{\partial^2 h}{\partial p_1 \partial p_2} \; \frac{\partial^2 h}{\partial p_2^2} \mid \cdots \mid \frac{\partial^2 h}{\partial p_1 \partial p_m} \; \frac{\partial^2 h}{\partial p_2 \partial p_m} \cdots \frac{\partial^2 h}{\partial p_m^2}$

- *Return value*: Numeric array that contains the lower triangular portion of the Hessian matrix evaluated at x for the parameter values $(p_1, p_2, \ldots, p_m)$

Here is a sample structure of the subroutine for the core function LOGSDF of a distribution named 'FOO':

```
subroutine FOO_LOGSDFHESSIAN(x, P1, P2, hess{*});
    outargs hess;

    /* Code to compute Hessian by using x, P1, and P2 */
    hess[1] = <second order partial derivative of LOGSDF
               w.r.t. P1 evaluated at x, P1, P2>;
    hess[2] = <second order partial derivative of LOGSDF
               w.r.t. P1 and P2 evaluated at x, P1, P2>;
    hess[3] = <second order partial derivative of LOGSDF
               w.r.t. P2 evaluated at x, P1, P2>;
endsub;
```

Predefined Utility Functions

The following predefined utility functions are provided with the HPSEVERITY procedure and are available in the Sashelp.Hpsevdst library:

SVRTUTIL_EDF:

This function computes the empirical distribution function (EDF) estimate at the specified value of the random variable given the EDF estimate for a sample.

- *Type*: Function
- *Signature*: SVRTUTIL_EDF(y, n, x{*}, F{*}, Ftype)
- *Argument Description*:

  y — Value of the random variable at which the EDF estimate is desired.

  n — Dimension of the *x* and *F* input arrays.

  x{*} — Input numeric array of dimension *n* that contains values of the random variable observed in the sample. These values are sorted in nondecreasing order.

  F{*} — Input numeric array of dimension *n* in which each F[*i*] contains the EDF estimate for x[*i*]. These values must be sorted in nondecreasing order.

  Ftype — Type of the empirical estimate that is stored in the *x* and *F* arrays. See the section "Supplying EDF Estimates to Functions and Subroutines" on page 652 for definition of types.

- *Return value*: The EDF estimate at y.

The type of the sample EDF estimate determines how the EDF estimate at y is computed. For more information, see the section "Supplying EDF Estimates to Functions and Subroutines" on page 652.

SVRTUTIL_EMPLIMMOMENT:

This function computes the empirical estimate of the limited moment of specified order for the specified upper limit, given the EDF estimate for a sample.

- *Type*: Function
- *Signature*: SVRTUTIL_EMPLIMMOMENT(k, u, n, x{*}, F{*}, Ftype)
- *Argument Description*:

  k — Order of the desired empirical limited moment.

  u — Upper limit on the value of the random variable to be used in the computation of the desired empirical limited moment.

  n — Dimension of the *x* and *F* input arrays.

  x{*} — Input numeric array of dimension *n* that contains values of the random variable observed in the sample. These values are sorted in nondecreasing order.

  F{*} — Input numeric array of dimension *n* in which each F[*i*] contains the EDF estimate for x[*i*]. These values must be sorted in nondecreasing order.

Ftype — Type of the empirical estimate that is stored in the *x* and *F* arrays. See the section "Supplying EDF Estimates to Functions and Subroutines" on page 652 for definition of types.

- *Return value*: The desired empirical limited moment.

The empirical limited moment is computed by using the empirical estimate of the CDF. If $F_n(x)$ denotes the EDF at x, then the empirical limited moment of order k with upper limit u is defined as

$$E_n[(X \wedge u)^k] = k \int_0^u (1 - F_n(x)) x^{k-1} dx$$

The SVRTUTIL_EMPLIMMOMENT function uses the piecewise linear nature of $F_n(x)$ as described in the section "Supplying EDF Estimates to Functions and Subroutines" on page 652 to compute the integration.

SVRTUTIL_HILLCUTOFF:

This function computes an estimate of the value where the right tail of a distribution is expected to begin. The function implements the algorithm described in Danielsson et al. 2001. The description of the algorithm uses the following notation:

n	Number of observations in the original sample.
B	Number of bootstrap samples to draw.
m_1	Size of the bootstrap sample in the first step of the algorithm ($m_1 < n$).
$x_{(i)}^{j,m}$	ith order statistic of jth bootstrap sample of size m ($1 \le i \le m, 1 \le j \le B$).
$x_{(i)}$	ith order statistic of the original sample ($1 \le i \le n$).

Given the input sample x and values of B and m_1, the steps of the algorithm are as follows:

1. Take B bootstrap samples of size m_1 from the original sample.
2. Find the integer k_1 that minimizes the bootstrap estimate of the mean squared error:

$$k_1 = \arg \min_{1 \le k < m_1} Q(m_1, k)$$

3. Take B bootstrap samples of size $m_2 = m_1^2/n$ from the original sample.
4. Find the integer k_2 that minimizes the bootstrap estimate of the mean squared error:

$$k_2 = \arg \min_{1 \le k < m_2} Q(m_2, k)$$

5. Compute the integer k_{opt}, which is used for computing the cutoff point:

$$k_{\text{opt}} = \frac{k_1^2}{k_2} \left(\frac{\log(k_1)}{2\log(m_1) - \log(k_1)} \right)^{2 - 2\log(k_1)/\log(m_1)}$$

6. Set the cutoff point equal to $x_{(k_{\text{opt}}+1)}$.

The bootstrap estimate of the mean squared error is computed as

$$Q(m,k) = \frac{1}{B}\sum_{j=1}^{B} \mathrm{MSE}_j(m,k)$$

The mean squared error of jth bootstrap sample is computed as

$$\mathrm{MSE}_j(m,k) = (M_j(m,k) - 2(\gamma_j(m,k))^2)^2$$

where $M_j(m,k)$ is a control variate proposed by Danielsson et al. 2001,

$$M_j(m,k) = \frac{1}{k}\sum_{i=1}^{k}\left(\log(x^{j,m}_{(m-i+1)}) - \log(x^{j,m}_{(m-k)})\right)^2$$

and $\gamma_j(m,k)$ is the Hill's estimator of the tail index (Hill 1975),

$$\gamma_j(m,k) = \frac{1}{k}\sum_{i=1}^{k}\log(x^{j,m}_{(m-i+1)}) - \log(x^{j,m}_{(m-k)})$$

This algorithm has two tuning parameters, B and m_1. The number of bootstrap samples B is chosen based on the availability of computational resources. The optimal value of m_1 is chosen such that the following ratio, $R(m_1)$, is minimized:

$$R(m_1) = \frac{(Q(m_1,k_1))^2}{Q(m_2,k_2)}$$

The SVRTUTIL_HILLCUTOFF utility function implements the preceding algorithm. It uses the grid search method to compute the optimal value of m_1.

- *Type*: Function
- *Signature*: SVRTUTIL_HILLCUTOFF(n, x{*}, b, s, status)
- *Argument Description*:

  n — Dimension of the array *x*.

  x{*} — Input numeric array of dimension n that contains the sample.

  b — Number of bootstrap samples used to estimate the mean squared error. If *b* is less than 10, then a default value of 50 is used.

  s — Approximate number of steps used to search the optimal value of m_1 in the range $[n^{0.75}, n-1]$. If *s* is less than or equal to 1, then a default value of 10 is used.

  status — Output argument that contains the status of the algorithm. If the algorithm succeeds in computing a valid cutoff point, then *status* is set to 0. If the algorithm fails, then *status* is set to 1.

- *Return value*: The cutoff value where the right tail is estimated to start. If the size of the input sample is inadequate ($n \leq 5$), then a missing value is returned and *status* is set to a missing value. If the algorithm fails to estimate a valid cutoff value (*status* = 1), then the fifth largest value in the input sample is returned.

SVRTUTIL_PERCENTILE:

This function computes the specified empirical percentile given the EDF estimates.

- *Type*: Function
- *Signature*: SVRTUTIL_PERCENTILE(p, n, x{*}, F{*}, Ftype)
- *Argument Description*:

  p — Desired percentile. The value must be in the interval (0,1). The function returns the $100p$th percentile.

  n — Dimension of the x and F input arrays.

  x{*} — Input numeric array of dimension n that contains values of the random variable observed in the sample. These values are sorted in nondecreasing order.

  F{*} — Input numeric array of dimension n in which each F[i] contains the EDF estimate for x[i]. These values must be sorted in nondecreasing order.

  Ftype — Type of the empirical estimate that is stored in the x and F arrays. See the section "Supplying EDF Estimates to Functions and Subroutines" on page 652 for definition of types.

- *Return value*: The $100p$th percentile of the input sample.

The method used to compute the percentile depends on the type of the EDF estimate (Ftype argument).

Ftype = 1 — Smoothed empirical estimates are computed using the method described in Klugman, Panjer, and Willmot (1998). Let $\lfloor x \rfloor$ denote the greatest integer less than or equal to x. Define $g = \lfloor p(n+1) \rfloor$ and $h = p(n+1) - g$. Then the empirical percentile $\hat{\pi}_p$ is defined as

$$\hat{\pi}_p = (1-h)x[g] + hx[g+1]$$

This method does not work if $p < 1/(n+1)$ or $p > n/(n+1)$. If $p < 1/(n+1)$, then the function returns $\hat{\pi}_p = x[1]/2$, which assumes that the EDF is 0 in the interval $[0, x[1])$. If $p > n/(n+1)$, then $\hat{\pi}_p = x[n]$.

Ftype = 2 — If $p < F[1]$, then $\hat{\pi}_p = x[1]/2$, which assumes that the EDF is 0 in the interval $[0, x[1])$. If $|p - F[i]| < \epsilon$ for some value of i and $i < n$, then $\hat{\pi}_p$ is computed as

$$\hat{\pi}_p = \frac{x[i] + x[i+1]}{2}$$

where ϵ is a machine-precision constant as returned by the SAS function CONSTANT('MACEPS'). If $F[i-1] < p < F[i]$, then $\hat{\pi}_p$ is computed as

$$\hat{\pi}_p = x[i]$$

If $p \geq F[n]$, then $\hat{\pi}_p = x[n]$.

SVRTUTIL_RAWMOMENTS:

This subroutine computes the raw moments of a sample.

- *Type*: Subroutine
- *Signature*: SVRTUTIL_RAWMOMENTS(n, x{*}, nx{*}, nRaw, raw{*})

- *Argument Description*:

  n — Dimension of the *x* and *nx* input arrays.

  x{*} — Input numeric array of dimension *n* that contains distinct values of the random variable that are observed in the sample.

  nx{*} — Input numeric array of dimension *n* in which each *nx*[*i*] contains the number of observations in the sample that have the value x[*i*].

  nRaw — Desired number of raw moments. The output array *raw* contains the first *nRaw* raw moments.

  raw{*} — Output array of raw moments. The kth element in the array (raw{k}) contains the kth raw moment, where $1 \leq k \leq$ nRaw.

- *Return value*: Numeric array *raw* that contains the first *nRaw* raw moments. The array contains missing values if the sample has no observations (that is, if all the values in the *nx* array add up to zero).

SVRTUTIL_SORT:

This function sorts the given array of numeric values in an ascending or descending order.

- *Type*: Subroutine
- *Signature*: SVRTUTIL_SORT(n, x{*}, flag)
- *Argument Description*:

  n — Dimension of the input array *x*.

  x{*} — Numeric array that contains the values to be sorted at input. The subroutine uses the same array to return the sorted values.

  flag — A numeric value that controls the sort order. If *flag* is 0, then the values are sorted in an ascending order. If *flag* has any value other than 0, then the values are sorted in descending order.

- *Return value*: Numeric array *x*, which is sorted in place (that is, the sorted array is stored in the same storage area occupied by the input array *x*).

You can use the following predefined functions when you use the FCMP procedure to define functions and subroutines. They are summarized here for your information. For more information, see the FCMP procedure documentation in *Base SAS Procedures Guide*.

INVCDF:

This function computes the quantile from any continuous probability distribution by numerically inverting the CDF of that distribution. You need to specify the CDF function of the distribution, the values of its parameters, and the cumulative probability to compute the quantile.

LIMMOMENT:

This function computes the limited moment of order k with upper limit u for any continuous probability distribution. The limited moment is defined as

$$\begin{aligned} E[(X \wedge u)^k] &= \int_0^u x^k f(x)dx + \int_u^\infty u^k f(x)dx \\ &= \int_0^u x^k f(x)dx + u^k(1 - F(u)) \end{aligned}$$

where $f(x)$ and $F(x)$ denote the PDF and the CDF of the distribution, respectively. The LIMMOMENT function uses the following alternate definition, which can be derived using integration-by-parts:

$$E[(X \wedge u)^k] = k \int_0^u (1 - F(x))x^{k-1}dx$$

You need to specify the CDF function of the distribution, the values of its parameters, and the values of k and u to compute the limited moment.

Custom Objective Functions (Experimental)

You can use a series of programming statements that use variables in the input data set specified by DATA= option in the PROC HPSEVERITY statement to assign a value to an objective function symbol. The objective function symbol must be specified using the OBJECTIVE= option in the PROC HPSEVERITY statement.

The objective function can be programmed such that it is applicable to any distribution that is used in the model. For that purpose, PROC HPSEVERITY recognizes the following *keyword* functions in the programming statements:

PDF(x) returns the probability density function (PDF) of a distribution evaluated at the current value of a data set variable x.

CDF(x) returns the cumulative distribution function (CDF) of a distribution evaluated at the current value of a data set variable x.

SDF(x) returns the survival distribution function (SDF) of a distribution evaluated at the current value of a data set variable x.

LOGPDF(x) returns the natural logarithm of the PDF of a distribution evaluated at the current value of a data set variable x.

LOGCDF(x) returns the natural logarithm of the CDF of a distribution evaluated at the current value of a data set variable x.

LOGSDF(x) returns the natural logarithm of the SDF of a distribution evaluated at the current value of a data set variable x.

EDF(x) returns the empirical distribution function (EDF) estimate evaluated at the current value of a data set variable x. Internally, PROC HPSEVERITY computes the estimate using the SVRTUTIL_EDF function as described in the section "Predefined Utility Functions" on page 672. The EDF estimate required by the SVRTUTIL_EDF function is computed using the response variable values in the current BY group or in the entire input data set if no BY statement is specified.

EMPLIMMOMENT(k, u) returns the empirical limited moment of order k evaluated at the current value of a data set variable u that represents the upper limit of the limited moment. The order k can also be a data set variable. Internally, PROC HPSEVERITY computes the moment

using the SVRTUTIL_EMPLIMMOMENT function as described in the section "Predefined Utility Functions" on page 672. The EDF estimate required by the SVRTUTIL_EMPLIMMOMENT function is computed using the response variable values in the current BY group or in the entire input data set if no BY statement is specified.

LIMMOMENT(k, u)
returns the limited moment of order k evaluated at the current value of a data set variable u that represents the upper limit of the limited moment. The order k can be a data set variable or a constant. Internally, for each candidate distribution, PROC HPSEVERITY computes the moment using the LIMMOMENT function as described in the section "Predefined Utility Functions" on page 672.

All the preceding functions are right-hand side functions. They act as placeholders for distribution-specific functions, with the exception of _EDF_ and _EMPLIMMOMENT_ functions. As an example, let the data set Work.Test contain a response variable Y and a left-truncation threshold variable T. The following statements use the values in this data set to fit a model with distribution D such that the parameters of the model minimize the value of the objective function symbol MYOBJ:

```
options cmplib=(work.mydist);
proc hpseverity data=work.test objective=myobj;
    loss y / lt=t;

    myobj = -_LOGPDF_(y);
    if (not(missing(t))) then
        myobj = myobj + log(1-_CDF_(t));

    dist d;
run;
```

The symbol MYOBJ is designated as an objective function symbol by using the OBJECTIVE= option in the PROC HPSEVERITY statement. The response variable Y and left-truncation variable T are specified in the LOSS statement. The distribution D is specified in the DIST statement. The remaining statements constitute a program that computes the value of the MYOBJ symbol.

Let the distribution D have parameters P1 and P2. In order to estimate the model for this distribution, PROC HPSEVERITY internally converts the generic program to the following program specific to distribution D:

```
myobj = -D_LOGPDF(y, p1, p2);
if (not(missing(t))) then
    myobj = myobj + log(1-D_CDF(t, p1, p2));
```

Note that the generic keyword functions _LOGPDF_ and _CDF_ have been replaced with distribution-specific functions D_LOGPDF and D_CDF, respectively, with appropriate distribution parameters. The D_LOGPDF and D_CDF functions must have been defined previously and are assumed to be available in the Work.Mydist library specified in the CMPLIB= option.

The program is executed for each observation in Work.Test to compute the value of MYOBJ by using the values of variables Y and T in that observation and internally computed values of the model parameters P1 and P2. The values of MYOBJ are then added over all the observations of the data set or over all the observations of the current BY group if a BY statement is specified. The resulting aggregate value is the

value of the objective function, and it is supplied to the optimizer. If the optimizer requires derivatives of the objective function, then PROC HPSEVERITY automatically differentiates MYOBJ with respect to the parameters P1 and P2. The optimizer iterates over various combinations of the values of parameters P1 and P2, each time computing a new value of the objective function and the needed derivatives of it, until it finds a combination that minimizes the objective function.

Note the following points when you define your own program to compute the custom objective function:

- The value of the objective function is always minimized by PROC HPSEVERITY. If you want to maximize the value of a certain objective, then add a statement that assigns the negated value of the maximization objective to the objective function symbol specified in the OBJECTIVE= option. Minimization of the negated objective is equivalent to the maximization of the original objective.
- The contributions of individual observations are always added to compute the overall objective function in a given iteration of the optimizer. If you have specified the WEIGHT statement, then the contribution of each observation is weighted by multiplying it with the normalized value of the weight variable for that observation.
- If you are fitting multiple distributions in one PROC HPSEVERITY step and use any of the keyword functions in your program, then it is recommended that you do not explicitly use the parameters of any of the specified distributions in your programming statements.
- If you use a specific keyword function in your programming statements, then the corresponding distribution functions must be defined in a library specified in the CMPLIB= system option or in Sashelp.Hpsevdst, the predefined functions library. In the preceding example, it is assumed that the functions D_LOGPDF and D_CDF are defined in the Work.Mydist library specified in the CMPLIB= option.
- You can use most DATA step statements and functions in your program. The DATA step file and the data set I/O statements (for example, INPUT, FILE, SET, and MERGE) are not available. However, some functionality of the PUT statement is supported. See the section "PROC FCMP and DATA Step Differences" in *Base SAS Procedures Guide* for more information. In addition to the differences listed in that section, the following differences exist:
  - Only numeric-valued variables can be used in PROC HPSEVERITY programming statements. This restriction also implies that you cannot use SAS functions or call routines that require character-valued arguments, unless you pass those arguments as constant (literal) strings or characters.
  - You cannot use functions that create lagged versions of a variable in PROC HPSEVERITY programming statements. If you need lagged versions, then you can use a DATA step prior to the PROC HPSEVERITY step to add those versions to the input data set.
- When coding your programming statements, avoid defining variables that begin with an underscore (_), because they might conflict with internal variables created by PROC HPSEVERITY.

Custom Objective Functions and Regression Effects

If you have specified regressors using the SCALEMODEL statement, then PROC HPSEVERITY automatically adds a statement prior to your programming statements to compute the value of the scale parameter or the log-transformed scale parameter of the distribution using the values of the regression variables and internally created regression parameters. For example, if you have specified three regressors x1, x2, and x3 in the SCALEMODEL statement, then for a model that contains the distribution D with scale parameter S, PROC HPSEVERITY prepends your program with a statement that is equivalent to the following statement:

```
S = _SEVTHETA0 * exp(_SEVBETA1 * x1 + _SEVBETA2 * x2 + _SEVBETA3 * x3);
```

If a model contains a distribution D1 with a log-transformed scale parameter M, PROC HPSEVERITY prepends your program with a statement that is equivalent to the following statement:

```
M = _SEVTHETA0 + _SEVBETA1 * x1 + _SEVBETA2 * x2 + _SEVBETA3 * x3;
```

The _SEVTHETA0, _SEVBETA1, _SEVBETA2, and _SEVBETA3 are the internal regression parameters associated with the intercept and the regressors x1, x2, and x3, respectively.

Since the names of the internal regression parameters start with a prefix _SEV, if you use a variable in your program with a name that begins with _SEV, then PROC HPSEVERITY writes an error message to the SAS log and stops processing.

Input Data Sets

PROC HPSEVERITY accepts DATA= and INEST= data sets as input data sets. This section details the information they are expected to contain.

DATA= Data Set

The DATA= data set is expected to contain the values of the analysis variables specified in the LOSS statement and the SCALEMODEL statement.

INEST= Data Set

The INEST= data set is expected to contain the initial values of the parameters for the parameter estimation process. The data set must contain the following variables:

MODEL identifying name of the distribution for which the estimates are provided.

TYPE type of the estimate. The value of this variable must be EST for an observation to be valid.

<Parameter 1> . . . <Parameter M>
M variables, named after the parameters of all candidate distributions, that contain initial values of the respective parameters. M is the cardinality of the union of parameter name sets from all candidate distributions. In an observation, estimates are read only from variables for parameters that correspond to the distribution specified by the _MODEL_ variable.

If you specify a missing value for some parameters, then default initial values are used unless the parameter is initialized by using the INIT= option in the DIST statement. If you want to use the *dist*_PARMINIT subroutine for initializing the parameters of a model, then you should either not specify the model in the INEST= data set or specify missing values for all the distribution parameters in the INEST= data set and not use the INIT= option in the DIST statement.

If regressors are specified, then the initial value provided for the first parameter of each distribution must be the base value of the scale or log-transformed scale parameter. For more information, see the section "Estimating Regression Effects" on page 643.

<Regressor 1> ... <Regressor K>
If K regressors are specified in the SCALEMODEL statement, then the INEST= data set must contain K variables that are named for each regressor. The variables contain initial values of the respective regression coefficients. If a regressor is linearly dependent on other regressors, then you can indicate this by providing a special missing value of .R for the respective variable. If a variable is marked as linearly dependent for one model, then it must be marked so for all the models. Similarly, if a variable is not marked as linearly dependent for one model, then it must be marked so for all the models.

Output Data Sets

PROC HPSEVERITY writes the OUTEST=, OUTMODELINFO=, and OUTSTAT= data sets when requested by their respective options. The data sets and their contents are described in the following sections.

OUTEST= Data Set

The OUTEST= data set records the estimates of the model parameters. It also contains estimates of their standard errors and optionally their covariance structure.

If the COVOUT option is not specified, then the data set contains the following variables:

MODEL identifying name of the distribution model. The observation contains information about this distribution.

TYPE type of the estimates reported in this observation. It can take one of the following two values:

EST	point estimates of model parameters
STDERR	standard error estimates of model parameters

STATUS status of the reported estimates. The possible values are listed in the section "_STATUS_ Variable Values" on page 683.

<Parameter 1> ... <Parameter M>
M variables, named after the parameters of all candidate distributions, that contain estimates of the respective parameters. M is the cardinality of the union of parameter name sets from all candidate distributions. In an observation, estimates are populated only for parameters that correspond to the distribution specified by the _MODEL_ variable. If _TYPE_ is EST, then the estimates are missing if the model does not converge.

If _TYPE_ is STDERR, then the estimates are missing if covariance estimates cannot be obtained.

If regressors are specified, then the estimate reported for the first parameter of each distribution is the estimate of the base value of the scale or log-transformed scale parameter. For more information, see the section "Estimating Regression Effects" on page 643.

<Regressor 1> ... <Regressor K>
If K regressors are specified in the SCALEMODEL statement, then the OUTEST= data set contains K variables that are named for each regressor. The variables contain estimates for their respective regression coefficients. If a regressor is deemed to be linearly dependent on other regressors, then a warning message is printed to the SAS log and a special missing value of .R is written in the respective variable. If _TYPE_ is EST, then the estimates are missing if the model does not converge. If _TYPE_ is STDERR, then the estimates are missing if covariance estimates cannot be obtained.

If the COVOUT option is specified, then the OUTEST= data set contains additional observations that contain the estimates of the covariance structure. Given the symmetric nature of the covariance structure, only the lower triangular portion is reported. In addition to the variables listed and described previously, the data set contains the following variables that are either new or have a modified description:

TYPE type of the estimates reported in this observation. For observations that contain rows of the covariance structure, the value is COV.

STATUS status of the reported estimates. For observations that contain rows of the covariance structure, the status is 0 if covariance estimation was successful. If estimation fails, the status is 1 and a single observation is reported with _TYPE_=COV and missing values for all the parameter variables.

NAME Name of the parameter for the row of covariance matrix reported in the current observation.

OUTMODELINFO= Data Set

The OUTMODELINFO= data set records the information about each specified distribution. It contains the following variables:

MODEL identifying name of the distribution model. The observation contains information about this distribution.

DESCRIPTION descriptive name of the model. This has a nonmissing value only if the DESCRIPTION function has been defined for this model.

VALID validity of the model. This has a value of 1 for valid models and a value of 0 for invalid models.

_PARMNAME1 ... _PARMNAMEM
M variables that contain names of parameters of the distribution model, where M is the maximum number of parameters across all the specified distribution models. For a given distribution with m parameters, values of variables _PARMNAMEj ($j > m$) are missing.

OUTSTAT= Data Set

The OUTSTAT= data set records statistics of fit and model selection information. The data set contains the following variables:

MODEL	identifying name of the distribution model. The observation contains information about this distribution.
NMODELPARM	number of parameters in the distribution.
NESTPARM	number of estimated parameters. This includes the regression parameters, if any regressors are specified.
NOBS	number of nonmissing observations used for parameter estimation.
STATUS	status of the parameter estimation process for this model. The possible values are listed in the section "_STATUS_ Variable Values" on page 683.
SELECTED	indicator of the best distribution model. If the value is 1, then this model is the best model according to the specified model selection criterion. This value is missing if the parameter estimation process does not converge for this model.
Neg2LogLike	value of the log likelihood, multiplied by –2, that is attained at the end of the parameter estimation process. This value is missing if the parameter estimation process does not converge for this model.
AIC	value of the Akaike's information criterion (AIC) that is attained at the end of the parameter estimation process. This value is missing if the parameter estimation process does not converge for this model.
AICC	value of the corrected Akaike's information criterion (AICC) that is attained at the end of the parameter estimation process. This value is missing if the parameter estimation process does not converge for this model.
BIC	value of the Schwarz Bayesian information criterion (BIC) that is attained at the end of the parameter estimation process. This value is missing if the parameter estimation process does not converge for this model.
KS	value of the Kolmogorov-Smirnov (KS) statistic that is attained at the end of the parameter estimation process. This value is missing if parameter estimation process does not converge for this model.
AD	value of the Anderson-Darling (AD) statistic that is attained at the end of the parameter estimation process. This value is missing if parameter estimation process does not converge for this model.
CVM	value of the Cramér-von Mises (CvM) statistic that is attained at the end of the parameter estimation process. This value is missing if parameter estimation process does not converge for this model.

STATUS Variable Values

The _STATUS_ variable in the OUTEST= and OUTSTAT= data sets contains a value that indicates the status of the parameter estimation process for the respective distribution model. The variable can take the following values in the OUTEST= data set for _TYPE_=EST observations and in the OUTSTAT= data set:

0 The parameter estimation process converged for this model.

301 The parameter estimation process might not have converged for this model because there is no improvement in the objective function value. This might indicate that the initial values of the parameters are optimal, or you can try different convergence criteria in the NLOPTIONS statement.

302 The parameter estimation process might not have converged for this model because the number of iterations exceeded the maximum allowed value. You can try setting a larger value for the MAXITER= options in the NLOPTIONS statement.

303 The parameter estimation process might not have converged for this model because the number of objective function evaluations exceeded the maximum allowed value. You can try setting a larger value for the MAXFUNC= options in the NLOPTIONS statement.

304 The parameter estimation process might not have converged for this model because the time taken by the process exceeded the maximum allowed value. You can try setting a larger value for the MAXTIME= option in the NLOPTIONS statement.

400 The parameter estimation process did not converge for this model.

The _STATUS_ variable can take the following values in the OUTEST= data set for _TYPE_=STDERR and _TYPE_=COV observations:

0 The covariance and standard error estimates are available and valid.

1 The covariance and standard error estimates are not available, because the process of computing covariance estimates failed.

Displayed Output

The HPSEVERITY procedure optionally produces displayed output by using the Output Delivery System (ODS). All output is controlled by the PRINT= option in the PROC HPSEVERITY statement. Table 24.7 relates the ODS tables to PRINT= options.

Table 24.7 ODS Tables Produced in PROC HPSEVERITY

ODS Table Name	Description	Option
AllFitStatistics	Statistics of fit for all the distribution models	PRINT=ALLFITSTATS
ConvergenceStatus	Convergence status of parameter estimation process	PRINT=CONVSTATUS
DescStats	Descriptive statistics for the response variable	PRINT=DESCSTATS
DistributionInfo	Distribution information	PRINT=DISTINFO
EstimationDetails	Details of the estimation process for all the distribution models	PRINT=ESTIMATIONDETAILS
InitialValues	Initial parameter values and bounds	PRINT=INITIALVALUES

Table 24.7 *continued*

ODS Table Name	Description	Option
IterationHistory	Optimization iteration history	PRINT=NLOHISTORY
ModelSelection	Model selection summary	PRINT=SELECTION
OptimizationSummary	Optimization summary	PRINT=NLOSUMMARY
ParameterEstimates	Final parameter estimates	PRINT=ESTIMATES
PerformanceInfo	Execution environment information that pertains to the computational performance	Default
RegDescStats	Descriptive statistics for the regressor variables	PRINT=DESCSTATS
StatisticsOfFit	Statistics of fit	PRINT=STATISTICS
Timing	Timing information for various computational stages of the procedure	DETAILS (PERFORMANCE statement)

PRINT= Option

If the PRINT= option is not specified, then by default PROC HPSEVERITY produces the ModelSelection, PerformanceInfo, ConvergenceStatus, OptimizationSummary, StatisticsOfFit, and ParameterEstimates ODS tables.

You can specify the following values for the PRINT= option:

PRINT=ALLFITSTATS
displays the comparison of all the statistics of fit for all the models in one table. The table does not include the models whose parameter estimation process does not converge. If all the models fail to converge, then this table is not produced. If the table contains more than one model, then the best model according to each statistic is indicated with an asterisk (*) in that statistic's column.

PRINT=CONVSTATUS
displays the convergence status of the parameter estimation process.

PRINT=DESCSTATS
displays the descriptive statistics for the response variable. If regressor variables are specified, a table with their descriptive statistics is also displayed.

PRINT=DISTINFO
displays the information about all the candidate distribution. It includes the name, the description, the number of distribution parameters, and whether the distribution is valid for the specified modeling task.

PRINT=ESTIMATES
displays the final estimates of parameters. The estimates are not displayed for models whose parameter estimation process does not converge.

PRINT=ESTIMATIONDETAILS
displays the comparative details of the estimation process that is used to fit each candidate distribution. If you specify the DETAILS option in the PERFORMANCE statement, then this table contains a column that indicates the time taken to estimate each candidate model.

PRINT=INITIALVALUES
displays the initial values and bounds used for estimating each model.

PRINT=NLOHISTORY
displays the iteration history of the nonlinear optimization process used for estimating the parameters.

PRINT=NLOSUMMARY
displays the summary of the nonlinear optimization process used for estimating the parameters.

PRINT=SELECTION
displays the model selection table. The table shows the convergence status of each candidate model, and the value of the selection criterion along with an indication of the selected model.

PRINT=STATISTICS
displays the statistics of fit for each model. The statistics of fit are not displayed for models whose parameter estimation process does not converge.

Performance Information

The "Performance Information" table is produced by default and displays information about the grid host for distributed execution and about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of compute nodes and threads are also displayed, depending on the environment.

Timing Information

If you specify the DETAILS option in the PERFORMANCE statement, the procedure also produces a "Timing" table in which the elapsed and relative times for each main task of the procedure is displayed.

Examples: HPSEVERITY Procedure

Example 24.1: Defining a Model for Gaussian Distribution

Suppose you want to fit a distribution model other than one of the predefined ones available to you. Suppose you want to define a model for the Gaussian distribution with the following typical parameterization of the PDF (f) and CDF (F):

$$f(x;\mu,\sigma) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right)$$
$$F(x;\mu,\sigma) = \frac{1}{2}\left(1 + \operatorname{erf}\left(\frac{x-\mu}{\sigma\sqrt{2}}\right)\right)$$

For PROC HPSEVERITY, a *distribution model* consists of a set of functions and subroutines that are defined with the FCMP procedure. Each function and subroutine should be written following certain rules. For more information, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660.

NOTE: The Gaussian distribution is not a commonly used severity distribution. It is used in this example primarily to illustrate the process of defining your own distribution models. Although the distribution has a support over the entire real line, you can fit the distribution with PROC HPSEVERITY only if the input sample contains nonnegative values.

The following SAS statements define a distribution model named NORMAL for the Gaussian distribution. The OUTLIB= option in the PROC FCMP statement stores the compiled versions of the functions and subroutines in the 'models' package of the Work.Sevexmpl library. The LIBRARY= option in the PROC FCMP statement enables this PROC FCMP step to use the SVRTUTIL_RAWMOMENTS utility subroutine that is available in the Sashelp.Hpsevdst library. The subroutine is described in the section "Predefined Utility Functions" on page 672.

```
/*-------- Define Normal Distribution with PROC FCMP  ----------*/
proc fcmp library=sashelp.hpsevdst outlib=work.sevexmpl.models;
   function normal_pdf(x,Mu,Sigma);
      /* Mu    : Location */
      /* Sigma : Standard Deviation */
      return ( exp(-(x-Mu)**2/(2 * Sigma**2)) /
             (Sigma * sqrt(2*constant('PI'))) );
   endsub;

   function normal_cdf(x,Mu,Sigma);
      /* Mu    : Location */
      /* Sigma : Standard Deviation */
      z = (x-Mu)/Sigma;
      return (0.5 + 0.5*erf(z/sqrt(2)));
   endsub;

   subroutine normal_parminit(dim, x[*], nx[*], F[*], Ftype, Mu, Sigma);
      outargs Mu, Sigma;
      array m[2] / nosymbols;

      /* Compute estimates by using method of moments */
      call svrtutil_rawmoments(dim, x, nx, 2, m);
      Mu    = m[1];
      Sigma = sqrt(m[2] - m[1]**2);
   endsub;

   subroutine normal_lowerbounds(Mu, Sigma);
      outargs Mu, Sigma;
      Mu = .;   /* Mu has no lower bound */
      Sigma = 0; /* Sigma > 0 */
   endsub;
quit;
```

The statements define the two functions required of any distribution model (NORMAL_PDF and NORMAL_CDF) and two optional subroutines (NORMAL_PARMINIT and NORMAL_LOWERBOUNDS). The name of each function or subroutine must follow a specific structure. It should start with the model's

short or identifying name, which is 'NORMAL' in this case, followed by an underscore '_', followed by a keyword suffix such as 'PDF'. Each function or subroutine has a specific purpose. For more information about all the functions and subroutines that you can define for a distribution model, see the section "Defining a Severity Distribution Model with the FCMP Procedure" on page 660. Following is the description of each function and subroutine defined in this example:

- The PDF and CDF suffixes define functions that return the probability density function and cumulative distribution function values, respectively, given the values of the random variable and the distribution parameters.
- The PARMINIT suffix defines a subroutine that returns the initial values for the parameters by using the sample data or the empirical distribution function (EDF) estimate computed from it. In this example, the parameters are initialized by using the method of moments. Hence, you do not need to use the EDF estimates, which are available in the F array. The first two raw moments of the Gaussian distribution are as follows:

  $$E[x] = \mu,\ E[x^2] = \mu^2 + \sigma^2$$

  Given the sample estimates, m_1 and m_2, of these two raw moments, you can solve the equations $E[x] = m_1$ and $E[x^2] = m_2$ to get the following estimates for the parameters: $\hat{\mu} = m_1$ and $\hat{\sigma} = \sqrt{m_2 - m_1^2}$. The NORMAL_PARMINIT subroutine implements this solution. It uses the SVRTUTIL_RAWMOMENTS utility subroutine to compute the first two raw moments.
- The LOWERBOUNDS suffix defines a subroutine that returns the lower bounds on the parameters. PROC HPSEVERITY assumes a default lower bound of 0 for all the parameters when a LOWERBOUNDS subroutine is not defined. For the parameter μ (*Mu*), there is no lower bound, so you need to define the NORMAL_LOWERBOUNDS subroutine. It is recommended that you assign bounds for all the parameters when you define the LOWERBOUNDS subroutine or its counterpart, the UPPERBOUNDS subroutine. Any unassigned value is returned as a missing value, which PROC HPSEVERITY interprets to mean that the parameter is unbounded, and that might not be what you want.

You can now use this distribution model with PROC HPSEVERITY. Let the following DATA step statements simulate a normal sample with $\mu = 10$ and $\sigma = 2.5$:

```
/*-------- Simulate a Normal sample ----------*/
data testnorm(keep=y);
   call streaminit(12345);
   do i=1 to 100;
      y = rand('NORMAL', 10, 2.5);
      output;
   end;
run;
```

Prior to using your distribution with PROC HPSEVERITY, you must communicate the location of the library that contains the definition of the distribution and the locations of libraries that contain any functions and subroutines used by your distribution model. The following OPTIONS statement sets the CMPLIB= system option to include the FCMP library Work.Sevexmpl in the search path used by PROC HPSEVERITY to find FCMP functions and subroutines.

```
/*--- Set the search path for functions defined with PROC FCMP ---*/
options cmplib=(work.sevexmpl);
```

Now, you are ready to fit the NORMAL distribution model with PROC HPSEVERITY. The following statements fit the model to the values of Y in the Work.Testnorm data set:

```
/*--- Fit models with PROC HPSEVERITY ---*/
proc hpseverity data=testnorm print=all;
   loss y;
   dist Normal;
run;
```

The DIST statement specifies the identifying name of the distribution model, which is 'NORMAL'. Neither is the INEST= option specified in the PROC HPSEVERITY statement nor is the INIT= option specified in the DIST statement. So, PROC HPSEVERITY initializes the parameters by invoking the NORMAL_PARMINIT subroutine.

Some of the results prepared by the preceding PROC HPSEVERITY step are shown in Output 24.1.1 and Output 24.1.2. The descriptive statistics of variable Y and the "Model Selection Table," which includes just the normal distribution, are shown in Output 24.1.1.

Output 24.1.1 Summary of Results for Fitting the Normal Distribution

The HPSEVERITY Procedure

Input Data Set

Name WORK.TESTNORM

Descriptive Statistics for Variable y

Number of Observations	100
Number of Observations Used for Estimation	100
Minimum	3.88249
Maximum	16.00864
Mean	10.02059
Standard Deviation	2.37730

Model Selection Table

Distribution	Converged	-2 Log Likelihood	Selected
Normal	Yes	455.97541	Yes

The initial values for the parameters, the optimization summary, and the final parameter estimates are shown in Output 24.1.2. No iterations are required to arrive at the final parameter estimates, which are identical to the initial values. This confirms the fact that the maximum likelihood estimates for the Gaussian distribution are identical to the estimates obtained by the method of moments that was used to initialize the parameters in the NORMAL_PARMINIT subroutine.

Output 24.1.2 Details of the Fitted Normal Distribution Model

The HPSEVERITY Procedure

Distribution Information

Name	Normal
Number of Distribution Parameters	2

Initial Parameter Values and Bounds for Normal Distribution

Parameter	Initial Value	Lower Bound	Upper Bound
Mu	10.02059	-Infty	Infty
Sigma	2.36538	1.05367E-8	Infty

Optimization Summary for Normal Distribution

Optimization Technique	Trust Region
Number of Iterations	0
Number of Function Evaluations	4
Log Likelihood	-227.98770

Parameter Estimates for Normal Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Mu	10.02059	0.23894	41.94	<.0001
Sigma	2.36538	0.16896	14.00	<.0001

The NORMAL distribution defined and illustrated here has no scale parameter, because all the following inequalities are true:

$$f(x;\mu,\sigma) \neq \frac{1}{\mu} f(\frac{x}{\mu};1,\sigma)$$
$$f(x;\mu,\sigma) \neq \frac{1}{\sigma} f(\frac{x}{\sigma};\mu,1)$$
$$F(x;\mu,\sigma) \neq F(\frac{x}{\mu};1,\sigma)$$
$$F(x;\mu,\sigma) \neq F(\frac{x}{\sigma};\mu,1)$$

This implies that you cannot estimate the effect of regressors on a model for the response variable based on this distribution.

Example 24.2: Defining a Model for the Gaussian Distribution with a Scale Parameter

If you want to estimate the effects of regressors, then the model needs to be parameterized to have a scale parameter. Although this might not be always possible, it is possible for the Gaussian distribution by replacing the location parameter μ with another parameter, $\alpha = \mu/\sigma$, and defining the PDF (f) and the CDF (F) as follows:

$$f(x;\sigma,\alpha) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{1}{2}\left(\frac{x}{\sigma} - \alpha\right)^2\right)$$
$$F(x;\sigma,\alpha) = \frac{1}{2}\left(1 + \operatorname{erf}\left(\frac{1}{\sqrt{2}}\left(\frac{x}{\sigma} - \alpha\right)\right)\right)$$

You can verify that σ is the scale parameter, because both of the following equalities are true:

$$f(x;\sigma,\alpha) = \frac{1}{\sigma} f(\frac{x}{\sigma};1,\alpha)$$
$$F(x;\sigma,\alpha) = F(\frac{x}{\sigma};1,\alpha)$$

NOTE: The Gaussian distribution is not a commonly used severity distribution. It is used in this example primarily to illustrate the concept of parameterizing a distribution such that it has a scale parameter. Although the distribution has a support over the entire real line, you can fit the distribution with PROC HPSEVERITY only if the input sample contains nonnegative values.

The following statements use the alternate parameterization to define a new model named NORMAL_S. The definition is stored in the Work.Sevexmpl library.

```
/*-------- Define Normal Distribution With Scale Parameter  ----------*/
proc fcmp library=sashelp.hpsevdst outlib=work.sevexmpl.models;
   function normal_s_pdf(x, Sigma, Alpha);
      /* Sigma : Scale & Standard Deviation */
      /* Alpha : Scaled mean */
      return ( exp(-(x/Sigma - Alpha)**2/2) /
             (Sigma * sqrt(2*constant('PI'))) );
   endsub;

   function normal_s_cdf(x, Sigma, Alpha);
      /* Sigma : Scale & Standard Deviation */
      /* Alpha : Scaled mean */
      z = x/Sigma - Alpha;
      return (0.5 + 0.5*erf(z/sqrt(2)));
   endsub;

   subroutine normal_s_parminit(dim, x[*], nx[*], F[*], Ftype, Sigma, Alpha);
      outargs Sigma, Alpha;
      array m[2] / nosymbols;

      /* Compute estimates by using method of moments */
```

```
      call svrtutil_rawmoments(dim, x, nx, 2, m);
      Sigma = sqrt(m[2] - m[1]**2);
      Alpha = m[1]/Sigma;
   endsub;

   subroutine normal_s_lowerbounds(Sigma, Alpha);
      outargs Sigma, Alpha;
      Alpha = .; /* Alpha has no lower bound */
      Sigma = 0; /* Sigma > 0 */
   endsub;
quit;
```

An important point to note is that the scale parameter *Sigma* is the first distribution parameter (after the 'x' argument) listed in the signatures of NORMAL_S_PDF and NORMAL_S_CDF functions. *Sigma* is also the first distribution parameter listed in the signatures of other subroutines. This is required by PROC HPSEVERITY, so that it can identify which is the scale parameter. When regressor variables are specified, PROC HPSEVERITY checks whether the first parameter of each candidate distribution is a scale parameter (or a log-transformed scale parameter if *dist*_SCALETRANSFORM subroutine is defined for the distribution with LOG as the transform). If it is not, then an appropriate message is written the SAS log and that distribution is not fitted.

Let the following DATA step statements simulate a sample from the normal distribution where the parameter σ is affected by the regressors as follows:

$$\sigma = \exp(1 + 0.5\ \mathrm{X1} + 0.75\ \mathrm{X3} - 2\ \mathrm{X4} + \mathrm{X5})$$

The sample is simulated such that the regressor X2 is linearly dependent on regressors X1 and X3.

```
/*--- Simulate a Normal sample affected by Regressors ---*/
data testnorm_reg(keep=y x1-x5 Sigma);
   array x{*} x1-x5;
   array b{6} _TEMPORARY_ (1 0.5 . 0.75 -2 1);
   call streaminit(34567);
   label y='Normal Response Influenced by Regressors';

   do n = 1 to 100;
      /* simulate regressors */
      do i = 1 to dim(x);
         x(i) = rand('UNIFORM');
      end;
      /* make x2 linearly dependent on x1 */
      x(2) = 5 * x(1);

      /* compute log of the scale parameter */
      logSigma = b(1);
      do i = 1 to dim(x);
         if (i ne 2) then
            logSigma = logSigma + b(i+1) * x(i);
      end;

      Sigma = exp(logSigma);
      y = rand('NORMAL', 25, Sigma);

      output;
   end;
run;
```

The following statements use PROC HPSEVERITY to fit the NORMAL_S distribution model along with some of the predefined distributions to the simulated sample:

```
/*--- Set the search path for functions defined with PROC FCMP ---*/
options cmplib=(work.sevexmpl);

/*-------- Fit models with PROC HPSEVERITY --------*/
proc hpseverity data=testnorm_reg print=all;
   loss y;
   scalemodel x1-x5;
   dist Normal_s burr logn pareto weibull;
run;
```

The "Model Selection Table" in Output 24.2.1 indicates that all the models, except the Burr distribution model, have converged. Also, only three models, Normal_s, Burr, and Weibull, seem to have a good fit for the data. The table that compares all the fit statistics indicates that Normal_s model is the best according to the likelihood-based statistics.

Output 24.2.1 Summary of Results for Fitting the Normal Distribution with Regressors

The HPSEVERITY Procedure

Input Data Set

Name WORK.TESTNORM_REG

Model Selection Table

Distribution	Converged	-2 Log Likelihood	Selected
Normal_s	Yes	603.95786	Yes
Burr	Maybe	612.80861	No
Logn	Yes	749.20125	No
Pareto	Yes	841.07013	No
Weibull	Yes	612.77496	No

Output 24.2.1 *continued*

All Fit Statistics Table

Distribution	−2 Log Likelihood	AIC	AICC	BIC	KS
Normal_s	603.95786*	615.95786*	616.86108*	631.58888*	1.52388
Burr	612.80861	626.80861	628.02600	645.04480	1.50356*
Logn	749.20125	761.20125	762.10448	776.83227	2.88110
Pareto	841.07013	853.07013	853.97336	868.70115	4.83810
Weibull	612.77496	624.77496	625.67819	640.40598	1.50490

All Fit Statistics Table

Distribution	AD	CvM
Normal_s	4.00152	0.70769
Burr	3.90098*	0.63396*
Logn	16.20558	3.04825
Pareto	31.60567	6.84045
Weibull	3.90559	0.63458

This prompts you to further evaluate why the model with Burr distribution has not converged. The initial values, convergence status, and the optimization summary for the Burr distribution are shown in Output 24.2.2. The initial values table indicates that the regressor X2 is redundant, which is expected. More importantly, the convergence status indicates that it requires more than 50 iterations. PROC HPSEVERITY enables you to change several settings of the optimizer by using the NLOPTIONS statement. In this case, you can increase the limit of 50 on the iterations, change the convergence criterion, or change the technique to something other than the default trust-region technique.

Output 24.2.2 Details of the Fitted Burr Distribution Model

The HPSEVERITY Procedure

Distribution Information

Name	Burr
Description	Burr Distribution
Number of Distribution Parameters	3
Number of Regression Parameters	4

Output 24.2.2 *continued*

Initial Parameter Values and Bounds for Burr Distribution

Parameter	Initial Value	Lower Bound	Upper Bound
Theta	25.75198	1.05367E-8	Infty
Alpha	2.00000	1.05367E-8	Infty
Gamma	2.00000	1.05367E-8	Infty
x1	0.07345	-709.78271	709.78271
x2	Redundant	.	.
x3	-0.14056	-709.78271	709.78271
x4	0.27064	-709.78271	709.78271
x5	-0.23230	-709.78271	709.78271

Convergence Status for Burr Distribution

Needs more than 50 iterations.

Optimization Summary for Burr Distribution

Optimization Technique	Trust Region
Number of Iterations	50
Number of Function Evaluations	132
Log Likelihood	-306.40430

The following PROC HPSEVERITY step uses the NLOPTIONS statement to change the convergence criterion and the limits on the iterations and function evaluations, exclude the lognormal and Pareto distributions that have been confirmed previously to fit the data poorly, and exclude the redundant regressor X2 from the model:

```
/*--- Refit and compare models with higher limit on iterations ---*/
proc hpseverity data=testnorm_reg print=all;
   loss y;
   scalemodel x1 x3-x5;
   dist Normal_s burr weibull;
   nloptions absfconv=2.0e-5 maxiter=100 maxfunc=500;
run;
```

The results shown in Output 24.2.3 indicate that the Burr distribution has now converged and that the Burr and Weibull distributions have an almost identical fit for the data. The NORMAL_S distribution is still the best distribution according to the likelihood-based criteria.

Output 24.2.3 Summary of Results after Changing Maximum Number of Iterations

The HPSEVERITY Procedure

Input Data Set

Name WORK.TESTNORM_REG

Output 24.2.3 *continued*

Model Selection Table

Distribution	Converged	-2 Log Likelihood	Selected
Normal_s	Yes	603.95786	Yes
Burr	Yes	612.78605	No
Weibull	Yes	612.77496	No

All Fit Statistics Table

Distribution	-2 Log Likelihood	AIC	AICC	BIC	KS
Normal_s	603.95786*	615.95786*	616.86108*	631.58888*	1.52388
Burr	612.78605	626.78605	628.00344	645.02224	1.50479*
Weibull	612.77496	624.77496	625.67819	640.40598	1.50490

All Fit Statistics Table

Distribution	AD	CvM
Normal_s	4.00152	0.70769
Burr	3.90430*	0.63442*
Weibull	3.90559	0.63458

Example 24.3: Defining a Model for Mixed-Tail Distributions

In some applications, a few severity values tend to be extreme as compared to the typical values. The extreme values represent the worst case scenarios and cannot be discarded as outliers. Instead, their distribution must be modeled to prepare for their occurrences. In such cases, it is often useful to fit one distribution to the non-extreme values and another distribution to the extreme values. The *mixed-tail* distribution mixes two distributions: one for the *body* region, which contains the non-extreme values, and another for the *tail* region, which contains the extreme values. The tail distribution is typically a generalized Pareto distribution (GPD), because it is usually good for modeling the conditional excess severity above a threshold. The body distribution can be any distribution. The following definitions are used in describing a generic formulation of a mixed-tail distribution:

$g(x)$	PDF of the body distribution
$G(x)$	CDF of the body distribution
$h(x)$	PDF of the tail distribution
$H(x)$	CDF of the tail distribution
θ	scale parameter for the body distribution
Ω	set of nonscale parameters for the body distribution
ξ	shape parameter for the GPD tail distribution
x_r	normalized value of the response variable at which the tail starts
p_n	mixing probability

Given these notations, the PDF $f(x)$ and the CDF $F(x)$ of the mixed-tail distribution are defined as

$$f(x) = \begin{cases} \frac{p_n}{G(x_b)} g(x) & \text{if } x \le x_b \\ (1 - p_n) h(x - x_b) & \text{if } x > x_b \end{cases}$$

$$F(x) = \begin{cases} \frac{p_n}{G(x_b)} G(x) & \text{if } x \le x_b \\ p_n + (1 - p_n) H(x - x_b) & \text{if } x > x_b \end{cases}$$

where $x_b = \theta x_r$ is the value of the response variable at which the tail starts.

These definitions indicate the following:

- The body distribution is conditional on $X \le x_b$, where X denotes the random response variable.
- The tail distribution is the generalized Pareto distribution of the $(X - x_b)$ values.
- The probability that a response variable value belongs to the body is p_n. Consequently the probability that the value belongs to the tail is $(1 - p_n)$.

The parameters of this distribution are θ, Ω, ξ, x_r, and p_n. The scale of the GPD tail distribution θ_t is computed as

$$\theta_t = \frac{G(x_b; \theta, \Omega)}{g(x_b; \theta, \Omega)} \frac{(1 - p_n)}{p_n} = \theta \frac{G(x_r; \theta = 1, \Omega)}{g(x_r; \theta = 1, \Omega)} \frac{(1 - p_n)}{p_n}$$

The parameter x_r is typically estimated using a tail index estimation algorithm. One such algorithm is the Hill's algorithm (Danielsson et al. 2001), which is implemented by the predefined utility function SVRTUTIL_HILLCUTOFF available to you in the Sashelp.Hpsevdst library. The algorithm and the utility function are described in detail in the section "Predefined Utility Functions" on page 672. The function computes an estimate of x_b, which can be used to compute an estimate of x_r because $x_r = x_b / \hat{\theta}$, where $\hat{\theta}$ is the estimate of the scale parameter of the body distribution.

The parameter p_n is typically determined by the domain expert based on the fraction of losses that are expected to belong to the tail.

The following SAS statements define the LOGNGPD distribution model for a mixed-tail distribution with the lognormal distribution as the body distribution and GPD as the tail distribution:

```
/*------- Define Lognormal Body-GPD Tail Mixed Distribution -------*/
proc fcmp library=sashelp.hpsevdst outlib=work.sevexmpl.models;
   function LOGNGPD_DESCRIPTION() $256;
      length desc $256;
      desc1 = "Lognormal Body-GPD Tail Distribution.";
      desc2 = " Mu, Sigma, and Xi are free parameters.";
      desc3 = " Xr and Pn are constant parameters.";
      desc = desc1 || desc2 || desc3;
      return(desc);
   endsub;

   function LOGNGPD_SCALETRANSFORM() $3;
      length xform $3;
      xform = "LOG";
      return (xform);
   endsub;
```

```
subroutine LOGNGPD_CONSTANTPARM(Xr,Pn);
endsub;

function LOGNGPD_PDF(x, Mu,Sigma,Xi,Xr,Pn);
   cutoff = exp(Mu) * Xr;
   p = CDF('LOGN',cutoff, Mu, Sigma);
   if (x < cutoff + constant('MACEPS')) then do;
      return ((Pn/p)*PDF('LOGN', x, Mu, Sigma));
   end;
   else do;
      gpd_scale = p*((1-Pn)/Pn)/PDF('LOGN', cutoff, Mu, Sigma);
      h = (1+Xi*(x-cutoff)/gpd_scale)**(-1-(1/Xi))/gpd_scale;
      return ((1-Pn)*h);
   end;
endsub;

function LOGNGPD_CDF(x, Mu,Sigma,Xi,Xr,Pn);
   cutoff = exp(Mu) * Xr;
   p = CDF('LOGN',cutoff, Mu, Sigma);
   if (x < cutoff + constant('MACEPS')) then do;
      return ((Pn/p)*CDF('LOGN', x, Mu, Sigma));
   end;
   else do;
      gpd_scale = p*((1-Pn)/Pn)/PDF('LOGN', cutoff, Mu, Sigma);
      H = 1 - (1 + Xi*((x-cutoff)/gpd_scale))**(-1/Xi);
      return (Pn + (1-Pn)*H);
   end;
endsub;

subroutine LOGNGPD_PARMINIT(dim,x[*],nx[*],F[*],Ftype,
                     Mu,Sigma,Xi,Xr,Pn);
   outargs Mu,Sigma,Xi,Xr,Pn;
   array xe[1] / nosymbols;
   array nxe[1] / nosymbols;

   eps = constant('MACEPS');

   Pn = 0.8; /* Set mixing probability */
   _status_ = .;
   call streaminit(56789);
   Xb = svrtutil_hillcutoff(dim, x, 100, 25, _status_);
   if (missing(_status_) or _status_ = 1) then
      Xb = svrtutil_percentile(Pn, dim, x, F, Ftype);

   /* prepare arrays for excess values */
   i = 1;
   do while (i <= dim and x[i] < Xb+eps);
      i = i + 1;
   end;
   dime = dim-i+1;
   call dynamic_array(xe, dime);
   call dynamic_array(nxe, dime);
   j = 1;
```

```
      do while(i <= dim);
         xe[j] = x[i] - Xb;
         nxe[j] = nx[i];
         i = i + 1;
         j = j + 1;
      end;

      /* Initialize lognormal parameters */
      call logn_parminit(dim, x, nx, F, Ftype, Mu, Sigma);
      if (not(missing(Mu))) then
         Xr = Xb/exp(Mu);
      else
         Xr = .;

      /* Initialize GPD's shape parameter using excess values */
      call gpd_parminit(dime, xe, nxe, F, Ftype, theta_gpd, Xi);
   endsub;

   subroutine LOGNGPD_LOWERBOUNDS(Mu,Sigma,Xi,Xr,Pn);
      outargs Mu,Sigma,Xi,Xr,Pn;

      Mu   = .; /* Mu has no lower bound */
      Sigma = 0; /* Sigma > 0 */
      Xi   = 0; /* Xi > 0 */
   endsub;
quit;
```

Note the following points about the LOGNGPD definition:

- The parameters x_r and p_n are not estimated with the maximum likelihood method used by PROC HPSEVERITY, so you need to specify them as *constant* parameters by defining the *dist*_CONSTANTPARM subroutine. The signature of LOGNGPD_CONSTANTPARM subroutine lists only the constant parameters *Xr* and *Pn*.
- The parameter x_r is estimated by first using the SVRTUTIL_HILLCUTOFF utility function to compute an estimate of the cutoff point $\hat{x}_b$ and then computing $x_r = \hat{x}_b / e^{\hat{\mu}}$. If SVRTUTIL_HILLCUTOFF fails to compute a valid estimate, then the SVRTUTIL_PERCENTILE utility function is used to set $\hat{x}_b$ to the p_nth percentile of the data. The parameter p_n is fixed to 0.8.
- The Sashelp.Hpsevdst library is specified with the LIBRARY= option in the PROC FCMP statement to enable the LOGNGPD_PARMINIT subroutine to use the predefined utility functions (SVRTUTIL_HILLCUTOFF and SVRTUTIL_PERCENTILE) and parameter initialization subroutines (LOGN_PARMINIT and GPD_PARMINIT).
- The LOGNGPD_LOWERBOUNDS subroutine defines the lower bounds for all parameters. This subroutine is required because the parameter *Mu* has a non-default lower bound. The bounds for *Sigma* and *Xi* must be specified. If they are not specified, they are returned as missing values, which PROC HPSEVERITY interprets as having no lower bound. You need not specify any bounds for the constant parameters *Xr* and *Pn*, because they are not subject to optimization.

The following DATA step statements simulate a sample from a mixed-tail distribution with a lognormal body and GPD tail. The parameter p_n is fixed to 0.8, the same value used in the LOGNGPD_PARMINIT subroutine defined previously.

```
/*----- Simulate a sample for the mixed-tail distribution -----*/
data testmixdist(keep=y label='Lognormal Body-GPD Tail Sample');
   call streaminit(45678);
   label y='Response Variable';
   N = 100;
   Mu = 1.5;
   Sigma = 0.25;
   Xi = 1.5;
   Pn = 0.8;

   /* Generate data comprising the lognormal body */
   Nbody = N*Pn;
   do i=1 to Nbody;
      y = exp(Mu) * rand('LOGNORMAL')**Sigma;
      output;
   end;

   /* Generate data comprising the GPD tail */
   cutoff = quantile('LOGNORMAL', Pn, Mu, Sigma);
   gpd_scale = (1-Pn) / pdf('LOGNORMAL', cutoff, Mu, Sigma);
   do i=Nbody+1 to N;
      y = cutoff + ((1-rand('UNIFORM'))**(-Xi) - 1)*gpd_scale/Xi;
      output;
   end;
run;
```

The following statements use PROC HPSEVERITY to fit the LOGNGPD distribution model to the simulated sample. They also fit three other predefined distributions (BURR, LOGN, and GPD). The final parameter estimates are written to the Work.Parmest data set.

```
/*--- Set the search path for functions defined with PROC FCMP ---*/
options cmplib=(work.sevexmpl);

/*-------- Fit LOGNGPD model with PROC HPSEVERITY --------*/
proc hpseverity data=testmixdist print=all outest=parmest;
   loss y;
   dist logngpd burr logn gpd;
run;
```

Some of the results prepared by PROC HPSEVERITY are shown in Output 24.3.1 and Output 24.3.2. The "Model Selection Table" in Output 24.3.1 indicates that all models converged. The last table in Output 24.3.1 shows that the model with LOGNGPD distribution has the best fit according to almost all the statistics of fit. The Burr distribution model is the closest contender to the LOGNGPD model, but the GPD distribution model fits the data very poorly.

Output 24.3.1 Summary of Fitting Mixed-Tail Distribution

The HPSEVERITY Procedure

Input Data Set

Name	WORK.TESTMIXDIST
Label	Lognormal Body-GPD Tail Sample

Model Selection Table

Distribution	Converged	-2 Log Likelihood	Selected
logngpd	Yes	418.78232	Yes
Burr	Yes	424.93728	No
Logn	Yes	459.43471	No
Gpd	Yes	558.13444	No

All Fit Statistics Table

Distribution	-2 Log Likelihood	AIC	AICC	BIC	KS
logngpd	418.78232*	428.78232*	429.42062*	441.80817	0.62140*
Burr	424.93728	430.93728	431.18728	438.75280*	0.71373
Logn	459.43471	463.43471	463.55842	468.64505	1.55267
Gpd	558.13444	562.13444	562.25815	567.34478	3.43470

All Fit Statistics Table

Distribution	AD	CvM
logngpd	0.31670*	0.04972*
Burr	0.57649	0.07860
Logn	3.27122	0.48448
Gpd	16.74156	3.31860

The detailed results for the LOGNGPD distribution are shown in Output 24.3.2. The initial values table indicates the values computed by LOGNGPD_PARMINIT subroutine for the *Xr* and *Pn* parameters. It also uses the bounds columns to indicate the constant parameters. The last table in the figure shows the final parameter estimates. The estimates of all free parameters are significantly different than 0. As expected, the final estimates of the constant parameters *Xr* and *Pn* have not changed from their initial values.

Output 24.3.2 Detailed Results for the LOGNGPD Distribution

The HPSEVERITY Procedure

Distribution Information

Name	logngpd
Description	Lognormal Body-GPD Tail Distribution. Mu, Sigma, and Xi are free parameters. Xr and Pn are constant parameters.
Number of Distribution Parameters	5

Initial Parameter Values and Bounds for logngpd Distribution

Parameter	Initial Value	Lower Bound	Upper Bound
Mu	1.49954	-Infty	Infty
Sigma	0.76306	1.05367E-8	Infty
Xi	0.36661	1.05367E-8	Infty
Xr	1.27395	Constant	Constant
Pn	0.80000	Constant	Constant

Convergence Status for logngpd Distribution

Convergence criterion (GCONV=1E-8) satisfied.

Optimization Summary for logngpd Distribution

Optimization Technique	Trust Region
Number of Iterations	11
Number of Function Evaluations	33
Number of Failed Function Evaluations	1
Log Likelihood	-209.39116

Parameter Estimates for logngpd Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Mu	1.57921	0.06426	24.57	<.0001
Sigma	0.31868	0.04459	7.15	<.0001
Xi	1.03771	0.38205	2.72	0.0078
Xr	1.27395	Constant	.	.
Pn	0.80000	Constant	.	.

The following SAS statements use the parameter estimates to compute the value where the tail region is estimated to start ($x_b = e^{\hat{\mu}}\hat{x_r}$) and the scale of the GPD tail distribution ($\theta_t = \frac{G(x_b)}{g(x_b)}\frac{(1-p_n)}{p_n}$):

```
/*-------- Compute tail cutoff and tail distribution's scale --------*/
data xb_thetat(keep=x_b theta_t);
   set parmest(where=(_MODEL_='logngpd' and _TYPE_='EST'));
   x_b = exp(Mu) * Xr;
   theta_t = (CDF('LOGN',x_b,Mu,Sigma)/PDF('LOGN',x_b,Mu,Sigma)) *
             ((1-Pn)/Pn);
run;

proc print data=xb_thetat noobs;
run;
```

Output 24.3.3 Start of the Tail and Scale of the GPD Tail Distribution

x_b	theta_t
6.18005	1.27865

The computed values of x_b and θ_t are shown as *x_b* and *theta_t* in Output 24.3.3. Equipped with this additional derived information, you can now interpret the results of fitting the mixed-tail distribution as follows:

- The tail starts at $y \approx 6.18$. The primary benefit of using the scale-normalized cutoff (x_r) as the constant parameter instead of using the actual cutoff (x_b) is that the absolute cutoff is optimized by virtue of optimizing the scale of the body region ($\theta = e^{\mu}$).
- The values $y \leq 6.18$ follow the lognormal distribution with parameters $\mu \approx 1.58$ and $\sigma \approx 0.32$. These parameter estimates are reasonably close to the parameters used for simulating the sample.
- The values $y_t = y - 6.18$ ($y_t > 0$) follow the GPD distribution with scale $\theta_t \approx 1.28$ and shape $\xi \approx 1.04$.

Example 24.4: Fitting a Scaled Tweedie Model with Regressors

The Tweedie distribution is often used in the insurance industry to explain the effect of independent variables (regressors) on the distribution of losses. PROC HPSEVERITY provides a predefined scaled Tweedie distribution (STWEEDIE) that enables you to model the regression effects on the scale parameter. The scale regression model has its own advantages such as the ability to easily account for inflation effects. This example illustrates how that model can be used to evaluate the effect of regressors on the *mean* of the Tweedie distribution, which is useful in problems such rate-making and pure premium modeling.

Assume a Tweedie process, whose mean μ is affected by k regressors x_j, $j = 1, \ldots, k$ as follows:

$$\mu = \mu_0 \exp\left(\sum_{j=1}^{k} \beta_j x_j\right)$$

where μ_0 represents the base value of the mean (you can think of μ_0 as $\exp(\beta_0)$, where β_0 is the intercept). This model for the mean is identical to the popular generalized linear model for the mean with a logarithmic link function.

More interestingly, it parallels the model used by PROC HPSEVERITY for the scale parameter θ,

$$\theta = \theta_0 \exp\left(\sum_{j=1}^{k} \beta_j x_j\right)$$

where θ_0 represents the base value of the scale parameter. As described in the section "Tweedie Distributions" on page 629, for the parameter range $p \in (1, 2)$, the mean of the Tweedie distribution is given by

$$\mu = \theta\lambda\frac{2-p}{p-1}$$

where λ is the Poisson mean parameter of the scaled Tweedie distribution. This relationship enables you to use the scale regression model to infer the effect of regressors on the mean of the distribution.

Let the data set Work.Test_Sevtw contain a sample generated from a Tweedie distribution with dispersion parameter $\phi = 0.5$, index parameter $p = 1.75$, and the mean parameter that is affected by three regression variables x1, x2, and x3 as follows:

$$\mu = 5\ \exp(0.25\,\mathrm{x1} - \mathrm{x2} + 3\,\mathrm{x3})$$

Thus, the population values of regression parameters are $\mu_0 = 5$, $\beta_1 = 0.25$, $\beta_2 = -1$, and $\beta_3 = 3$. You can find the code used to generate the sample in the PROC HPSEVERITY sample program *hpseve04.sas*.

The following PROC HPSEVERITY step uses the sample in Work.Test_Sevtw data set to estimate the parameters of the scale regression model for the predefined scaled Tweedie distribution (STWEEDIE) with the dual quasi-Newton (QUANEW) optimization technique:

```
proc hpseverity data=test_sevtw outest=estw covout print=all;
   loss y;
   scalemodel x1-x3;

   dist stweedie;
   nloptions tech=quanew;
run;
```

The dual quasi-Newton technique is used because it requires only the first-order derivatives of the objective function, and it is harder to compute reasonably accurate estimates of the second-order derivatives of Tweedie distribution's PDF with respect to the parameters.

Some of the key results prepared by PROC HPSEVERITY are shown in Output 24.4.1 and Output 24.4.2. The distribution information and the convergence results are shown in Output 24.4.1.

Output 24.4.1 Convergence Results for the STWEEDIE Model with Regressors

```
                        The HPSEVERITY Procedure

                        Distribution Information

Name                                                          stweedie
Description                          Tweedie Distribution with Scale Parameter
Number of Distribution Parameters                                     3
Number of Regression Parameters                                       3
```

Output 24.4.1 *continued*

```
Convergence Status for stweedie Distribution

Convergence criterion (FCONV=2.220446E-16) satisfied.


Optimization Summary for stweedie Distribution

Optimization Technique            Dual Quasi-Newton
Number of Iterations                             42
Number of Function Evaluations                  218
Log Likelihood                              -1044.3
```

The final parameter estimates of the STWEEDIE regression model are shown in Output 24.4.2. The estimate that is reported for the parameter Theta is the estimate of the base value θ_0. The estimates of regression coefficients β_1, β_2, and β_3 are indicated by the rows of x1, x2, and x3, respectively.

Output 24.4.2 Parameter Estimates for the STWEEDIE Model with Regressors

Parameter Estimates for stweedie Distribution

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Theta	0.82888	0.26940	3.08	0.0023
Lambda	16.57174	13.23304	1.25	0.2115
P	1.75440	0.20370	8.61	<.0001
x1	0.27970	0.09878	2.83	0.0050
x2	-0.76715	0.10318	-7.43	<.0001
x3	3.03225	0.10143	29.89	<.0001

If your goal is to explain the effect of regressors on the scale parameter, then the output displayed in Output 24.4.2 is sufficient. But, if you want to compute the effect of regressors on the mean of the distribution, then you need to do some postprocessing. Using the relationship between μ and θ, μ can be written in terms of the parameters of the STWEEDIE model as

$$\mu = \theta_0 \exp\left(\sum_{j=1}^{k} \beta_j x_j\right) \lambda \frac{2-p}{p-1}$$

This shows that the parameters β_j are identical for the mean and the scale model, and the base value μ_0 of the mean model is

$$\mu_0 = \theta_0 \lambda \frac{2-p}{p-1}$$

The estimate of μ_0 and the standard error associated with it can be computed by using the property of the functions of maximum likelihood estimators (MLE). If $g(\Omega)$ represents a totally differentiable function of parameters Ω, then the MLE of g has an asymptotic normal distribution with mean $g(\hat{\Omega})$ and covariance

$C = (\partial \mathbf{g})' \Sigma (\partial \mathbf{g})$, where $\hat{\Omega}$ is the MLE of Ω, Σ is the estimate of covariance matrix of Ω, and $\partial \mathbf{g}$ is the gradient vector of g with respect to Ω evaluated at $\hat{\Omega}$. For μ_0, the function is $g(\Omega) = \theta_0 \lambda (2-p)/(p-1)$. The gradient vector is

$$\begin{aligned} \partial \mathbf{g} &= \left(\frac{\partial g}{\partial \theta_0} \quad \frac{\partial g}{\partial \lambda} \quad \frac{\partial g}{\partial p} \quad \frac{\partial g}{\partial \beta_1} \cdots \frac{\partial g}{\partial \beta_k} \right) \\ &= \left(\frac{\mu_0}{\theta_0} \quad \frac{\mu_0}{\lambda} \quad \frac{-\mu_0}{(p-1)(2-p)} \quad 0 \ldots 0 \right) \end{aligned}$$

You can write a DATA step that implements these computations by using the parameter and covariance estimates prepared by PROC HPSEVERITY step. The DATA step program is available in the sample program *sevex04.sas*. The estimates of μ_0 prepared by that program are shown in Output 24.4.3. These estimates and the estimates of β_j as shown in Output 24.4.2 are reasonably close (that is, within one or two standard errors) to the parameters of the population from which the sample in Work.Test_Sevtw data set was drawn.

Output 24.4.3 Estimate of the Base Value Mu0 of the Mean Parameter

Parameter	Estimate	Standard Error	t Value	Approx Pr > |t|
Mu0	4.47179	0.42253	10.5835	0

Another effect of using the scaled Tweedie distribution to model the regression effects is that the regressors also affect the variance V of the Tweedie distribution. The variance is related to the mean as $V = \phi \mu^p$, where ϕ is the dispersion parameter. Using the relationship between the parameters TWEEDIE and STWEEDIE distributions as described in the section "Tweedie Distributions" on page 629, the regression model for the dispersion parameter is

$$\begin{aligned} \log(\phi) &= (2-p)\log(\mu) - \log(\lambda(2-p)) \\ &= ((2-p)\log(\mu_0) - \log(\lambda(2-p))) + (2-p)\sum_{j=1}^{k} \beta_j x_j \end{aligned}$$

Subsequently, the regression model for the variance is

$$\begin{aligned} \log(V) &= 2\log(\mu) - \log(\lambda(2-p)) \\ &= (2\log(\mu_0) - \log(\lambda(2-p))) + 2\sum_{j=1}^{k} \beta_j x_j \end{aligned}$$

In summary, PROC HPSEVERITY enables you to estimate regression effects on various parameters and statistics of the Tweedie model.

Example 24.5: Fitting Distributions to Interval-Censored Data

In some applications, the data available for modeling might not be exact. A commonly encountered scenario is the use of grouped data from an external agency, which for several reasons, including privacy, does not

provide information about individual loss events. The losses are grouped into disjoint bins, and you know only the range and number of values in each bin. Each group is essentially interval-censored, because you know that a loss magnitude is in certain interval, but you do not know the exact magnitude. This example illustrates how you can use PROC HPSEVERITY to model such data.

The following DATA step generates sample grouped data for dental insurance claims, which is taken from Klugman, Panjer, and Willmot (1998):

```
/* Grouped dental insurance claims data
    (Klugman, Panjer, and Willmot, 1998) */
data gdental;
   input lowerbd upperbd count @@;
   datalines;
0 25 30  25 50 31  50 100 57  100 150 42  150 250 65  250 500 84
500 1000 45  1000 1500 10  1500 2500 11  2500 4000 3
;
run;
```

The following PROC HPSEVERITY step fits all the predefined distributions to the data in Work.Gdental data set:

```
/* Fit all predefined distributions */
proc hpseverity data=gdental edf=turnbull print=all criterion=aicc;
   loss / rc=lowerbd lc=upperbd;
   weight count;
   dist _predef_;
   performance nthreads=1;
run;
```

The EDF= option in the PROC HPSEVERITY statement specifies that the Turnbull's method be used for EDF estimation. The LOSS statement specifies the left and right boundaries of each group as the right-censoring and left-censoring limits, respectively. The variable count records the number of losses in each group and is specified in the WEIGHT statement. Note that no response variable is specified in the LOSS statement, which is allowed as long as each observation in the input data set is censored. The PERFORMANCE statement specifies that just one thread of execution be used, to minimize the overhead associated with multithreading, because the input data set is very small.

Some of the key results prepared by PROC HPSEVERITY are shown in Output 24.5.1. According to the "Model Selection Table" in Output 24.5.1, all distribution models have converged. The "All Fit Statistics Table" in Output 24.5.1 indicates that the exponential distribution (EXP) has the best fit for data according to a majority of the likelihood-based statistics.

Output 24.5.1 Statistics of Fit for Interval-Censored Data

```
The HPSEVERITY Procedure

Input Data Set

Name     WORK.GDENTAL
```

Output 24.5.1 *continued*

Model Selection Table

Distribution	Converged	Corrected Akaike's Information Criterion	Selected
Burr	Yes	51.41112	No
Exp	Yes	44.64768	Yes
Gamma	Yes	47.63969	No
Igauss	Yes	48.05874	No
Logn	Yes	47.34027	No
Pareto	Yes	47.16908	No
Gpd	Yes	47.16908	No
Weibull	Yes	47.47700	No

All Fit Statistics Table

Distribution	-2 Log Likelihood	AIC	AICC	BIC	KS
Burr	41.41112*	47.41112	51.41112	48.31888	0.08974*
Exp	42.14768	44.14768*	44.64768*	44.45026*	0.26412
Gamma	41.92541	45.92541	47.63969	46.53058	0.19569
Igauss	42.34445	46.34445	48.05874	46.94962	0.34514
Logn	41.62598	45.62598	47.34027	46.23115	0.16853
Pareto	41.45480	45.45480	47.16908	46.05997	0.11423
Gpd	41.45480	45.45480	47.16908	46.05997	0.11423
Weibull	41.76272	45.76272	47.47700	46.36789	0.17238

All Fit Statistics Table

Distribution	AD	CvM
Burr	0.00103*	0.0000816*
Exp	0.09936	0.01866
Gamma	0.04608	0.00759
Igauss	0.12301	0.02562
Logn	0.01884	0.00333
Pareto	0.00739	0.0009084
Gpd	0.00739	0.0009084
Weibull	0.03293	0.00472

Example 24.6: Benefits of Distributed and Multithreaded Computing

One of the key features of the HPSEVERITY procedure is that is takes advantage of the distributed and multithreaded computing machinery in order to solve a given problem faster. This example illustrates the benefits of using multithreading and distributed computing.

The example uses a simulated data set Work.Largedata, which contains 10,000,000 observations, some of which are right-censored or left-truncated. The losses are affected by three external effects. The DATA step

program that generates this data set is available in the accompanying sample program *hpseve06.sas*.

The following PROC HPSEVERITY step fits all the predefined distributions to the data in Work.Largedata data set on the client machine with just one thread of computation:

```
/* Fit all predefined distributions without any multithreading or
   distributed computing */
proc hpseverity data=largedata criterion=aicc initsample(size=20000);
   loss y / lt=threshold rc=limit;
   scalemodel x1-x3;
   dist _predef_;
   performance nthreads=1 bufsize=1000000 details;
run;
```

The NTHREADS=1 option in the PERFORMANCE statement specifies that just one thread of computation be used. The absence of the NODES= option in the PERFORMANCE statement specifies that the client mode of execution be used. That is, this step does not use any multithreading or distributed computing. The BUFSIZE= option in the PERFORMANCE statement specifies the number of observations to read at one time. Specifying a larger value tends to decrease the time it takes to load the data. The DETAILS option in the performance statement enables generation of the Timing table. The INITSAMPLE option in the PROC HPSEVERITY statement specifies that a uniform random sample of maximum 20,000 observations be used for parameter initialization.

The PerformanceInfo and Timing tables prepared by PROC HPSEVERITY are shown in Output 24.6.1. The machine used to obtain these results has a Windows operating system and is powered by eight CPU cores, each with a clock speed of 3.4 GHz.

Output 24.6.1 Performance for Client Mode with No Multithreading

The HPSEVERITY Procedure

Performance Information

Execution Mode	On client
Number of Threads	1

Procedure Task Timing

Task	Time (sec.)	
Load and Prepare Models	1.40	0.06%
Load and Prepare Data	2.10	0.09%
Initialize Parameters	1.46	0.06%
Estimate Parameters	2287.91	99.7%
Compute Statistics of Fit	2.51	0.11%

The "Performance Information Table" contains the information about the execution environment. The "Procedure Task Timing" indicates the total time and relative time taken by each of the four main steps of PROC HPSEVERITY. As the "Procedure Task Timing" table shows, it takes around 38 minutes for the task of estimating parameters, which is typically the most time-consuming task of all the tasks.

If the grid appliance is not available, you can improve the performance by enabling multiple threads of computation, which is in fact the default. The following PROC HPSEVERITY step fits all the predefined distributions using all available CPU cores of the machine:

```
/* Fit all predefined distributions with multithreading, but no
   distributed computing */
proc hpseverity data=largedata criterion=aicc initsample(size=20000);
   loss y / lt=threshold rc=limit;
   scalemodel x1-x3;
   dist _predef_;
   performance bufsize=1000000 details;
run;
```

When you do not specify the NTHREADS= option in the PERFORMANCE statement, the HPSEVERITY procedure uses the value of the CPUCOUNT= system option to decide how many threads to use. By default, the CPUCOUNT= value is equal to the number of physical CPU cores present in the machine where the SAS software is running. This machine is the client node for the SMP mode of execution and the grid node for the MPP mode of execution. In this case, the default value is 8, which is reflected in the "Performance Information" table shown in Output 24.6.2.

Output 24.6.2 Performance for Client Mode with 8 Threads

The HPSEVERITY Procedure

Performance Information

Execution Mode	On client
Number of Threads	8

Procedure Task Timing

Task	Time (sec.)	
Load and Prepare Models	1.00	0.19%
Load and Prepare Data	1.85	0.35%
Initialize Parameters	1.07	0.20%
Estimate Parameters	520.87	98.9%
Compute Statistics of Fit	1.91	0.36%

The results in Output 24.6.2 indicate that threading improves the performance. The time to estimate parameters has been reduced to about 8.7 minutes.

When a grid appliance is available, the performance can be further improved by using more than one node in the MPP mode of execution. Typically, large data sets are distributed on the grid appliance that hosts a distributed database before the procedure is run. In other words, large problems are best suited for the alongside-the-database model of execution. However, for the purpose of illustration, this example assumes that the data set is available on the client machine and is then distributed to the grid nodes by the HPSEVERITY procedure according to the options that are specified in the PERFORMANCE statement.

The next few PROC HPSEVERITY steps are run on a grid appliance by varying the number of nodes and the number of threads that are used within each node.

First, the following statements are submitted to specify the appliance host (GRIDHOST= system option) and the install location of High-Performance Analytics shared libraries on the appliance (GRIDINSTALLLOC= system option):

```
option set=GRIDHOST      ="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";
```

To run the preceding statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to macro variables with the appropriate values. For more information about the GRIDHOST= and GRIDINSTALLLOC= options, see the section "PERFORMANCE Statement" on page 38.

In order to establish a reference point for the performance, the results of using just one node of the grid appliance without any multithreading are presented first. The particular grid appliance that is used to obtain these results has 16 nodes. Each node is running a 64-bit Linux OS and has 24 CPU cores with clock speed of 3.33 GHz. The following PROC HPSEVERITY step fits all the predefined distributions to the data in the Work.Largedata data set using just one node for computation and one computation thread within that node:

```
/* Fit all predefined distributions on 1 grid node without
   any multithreading */
proc hpseverity data=largedata criterion=aicc initsample(size=20000);
   loss y / lt=threshold rc=limit;
   scalemodel x1-x3;
   dist _predef_;
   performance nthreads=1 nodes=1 details;
run;
```

The PERFORMANCE statement specifies that just one node be used to fit the models with just one thread of computation on that node. The "Performance Information Table" and "Procedure Timing Table" prepared by PROC HPSEVERITY are shown in Output 24.6.3. It takes around 35 minutes to complete the task of estimating parameters.

The computations and time taken to fit each model is also shown in the "Estimation Details Table," which is generated whenever you specify the DETAILS option in the PERFORMANCE statement. This table can be useful for comparing the relative effort required to fit each model and draw some broader conclusions. For example, even if the Pareto distribution takes a larger number of iterations, function calls, gradient, and Hessian updates than the gamma distribution, it takes less time to complete, which indicates that the individual PDF and CDF computations for the gamma distribution are more expensive than that of Pareto distribution.

Output 24.6.3 Performance on One Grid Appliance Node with No Multithreading

```
                    The HPSEVERITY Procedure

                    Performance Information

Host Node                       << your grid host >>
Execution Mode                  Distributed
Number of Compute Nodes         1
Number of Threads per Node      1
```

Output 24.6.3 *continued*

Estimation Details Table
Optimization Technique: Trust Region

Distribution	Converged	Iterations	Function Calls	Gradient Updates	Hessian Updates	Time (sec.)
Burr	Yes	15	35	170	152	324.25
Exp	Maybe	2	25	13	9	43.57
Gamma	Yes	4	12	27	20	719.43
Igauss	Yes	4	12	27	20	358.54
Logn	Yes	4	12	27	20	128.49
Pareto	Yes	32	83	629	594	263.94
Gpd	Yes	15	34	170	152	185.74
Weibull	Yes	5	22	35	27	92.08

Procedure Task Timing

Task	Time (sec.)	
Load and Prepare Models	0.62	0.03%
Load and Prepare Data	0.70	0.03%
Initialize Parameters	1.19	0.06%
Estimate Parameters	2118.04	99.8%
Compute Statistics of Fit	2.10	0.10%

To obtain the next reference point for performance, the following PROC HPSEVERITY step specifies that 24 computation threads be used on one node of the grid appliance:

```
/* Fit all predefined distributions on 1 grid node with multithreading */
proc hpseverity data=largedata criterion=aicc initsample(size=20000);
   loss y / lt=threshold rc=limit;
   scalemodel x1-x3;
   dist _predef_;
   performance nthreads=24 nodes=1 details;
run;
```

The performance tables prepared by the preceding statements are shown in Output 24.6.4. As the "Procedure Task Timing" table shows, use of multithreading has improved the performance significantly over the single-threaded case. Now, it takes around 7 minutes to complete the task of estimating parameters.

Output 24.6.4 Performance Information with Multithreading, but No Distributed Computing

The HPSEVERITY Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	1
Number of Threads per Node	24

Output 24.6.4 *continued*

Procedure Task Timing

Task	Time (sec.)	
Load and Prepare Models	0.35	0.08%
Load and Prepare Data	0.47	0.11%
Initialize Parameters	1.03	0.24%
Estimate Parameters	424.02	99.2%
Compute Statistics of Fit	1.78	0.42%

The power of multithreading and distributed computing can be combined by specifying that multiple nodes of the grid and all available threads of execution within each node be used to accomplish the task. The following PROC HPSEVERITY step specifies that all 16 nodes of the grid appliance be used with 24 parallel computation threads on each node:

```
/* Fit all predefined distributions with distributed computing and
   multithreading within each node */
proc hpseverity data=largedata criterion=aicc initsample(size=20000);
   loss y / lt=threshold rc=limit;
   scalemodel x1-x3;
   dist _predef_;
   performance nthreads=24 nodes=16 details;
run;
```

The performance tables prepared by the preceding statements are shown in Output 24.6.5. These tables can be compared to the tables in Output 24.6.3 and Output 24.6.4 to determine the benefit of combining multithreading and distributed computed. A task that would have taken around 38 minutes on a single node with no multithreading can now be solved in around 45 seconds by using the full computational resources of the grid appliance.

Output 24.6.5 Performance Information with Distributed Computing and Multithreading

The HPSEVERITY Procedure

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	16
Number of Threads per Node	24

Output 24.6.5 *continued*

Procedure Task Timing

Task	Time (sec.)	
Load and Prepare Models	0.88	1.78%
Load and Prepare Data	0.05	0.09%
Initialize Parameters	1.23	2.51%
Estimate Parameters	45.44	92.6%
Compute Statistics of Fit	1.48	3.02%

Example 24.7: Estimating Parameters Using Cramér-von Mises Estimator

PROC HPSEVERITY enables you to estimate model parameters by minimizing your own objective function. This example illustrates how you can use PROC HPSEVERITY to implement the Cramér-von Mises estimator. Let $F(y_i;\Theta)$ denote the estimate of CDF at y_i for a distribution with parameters Θ, and let $F_n(y_i)$ denote the empirical estimate of CDF (EDF) at y_i that is computed from a sample y_i, $1 \le i \le N$. Then, the Cramér-von Mises estimator of the parameters is defined as

$$\hat{\Theta} = \arg\min_{\Theta} \sum_{i=1}^{N} (F(y_i;\Theta) - F_n(y_i))^2$$

This estimator belongs to the class of minimum distance estimators. It attempts to estimate the parameters such that the squared distance between the CDF and EDF estimates is minimized.

The following PROC HPSEVERITY step uses the Cramér-von Mises estimator to fit four candidate distribution models, including the LOGNGPD mixed-tail distribution model that was defined in "Example 24.3: Defining a Model for Mixed-Tail Distributions" on page 696. The input sample is the same as is used in that example.

```
options cmplib=(work.sevexmpl);

proc hpseverity data=testmixdist obj=cvmobj print=all;
   loss y;
   dist logngpd burr logn gpd;

   * Cramer-von Mises estimator (minimizes the distance *
   * between parametric and nonparametric estimates)    *;
   cvmobj = _cdf_(y);
   cvmobj = (cvmobj -_edf_(y))**2;
run;
```

The OBJ= option in the PROC HPSEVERITY statement specifies that the objective function cvmobj should be minimized. The programming statements compute the contribution of each observation in the input data set to the objective function cvmobj. The use of keyword functions _CDF_ and _EDF_ makes the program applicable to all the distributions.

Some of the key results prepared by PROC HPSEVERITY are shown in Output 24.7.1. The "Model Selection Table" indicates that all models converged. When you specify a custom objective function, the default selection criterion is the value of the custom objective function. The "All Fit Statistics Table" indicates that LOGNGPD is the best distribution according to all the statistics of fit. Comparing the fit statistics of Output 24.7.1 with those of Output 24.3.1 indicates that the use of the Cramér-von Mises estimator has resulted in smaller values for all the EDF-based statistics of fit for all the models, which is expected from a minimum distance estimator.

Output 24.7.1 Summary of Cramér-von Mises Estimation

The HPSEVERITY Procedure

Input Data Set

Name	WORK.TESTMIXDIST
Label	Lognormal Body-GPD Tail Sample

Model Selection Table

Distribution	Converged	Custom Objective	Selected
logngpd	Yes	0.02694	Yes
Burr	Yes	0.03325	No
Logn	Yes	0.03633	No
Gpd	Yes	2.96090	No

All Fit Statistics Table

Distribution	Custom	-2 Log Likelihood	AIC	AICC	BIC
logngpd	0.02694*	419.49635*	429.49635*	430.13464*	442.52220*
Burr	0.03325	436.58823	442.58823	442.83823	450.40374
Logn	0.03633	491.88659	495.88659	496.01030	501.09693
Gpd	2.96090	560.35409	564.35409	564.47780	569.56443

All Fit Statistics Table

Distribution	KS	AD	CvM
logngpd	0.51332*	0.21563*	0.03030*
Burr	0.53084	0.82875	0.03807
Logn	0.52469	2.08312	0.04173
Gpd	2.99095	15.51378	2.97806

References

D'Agostino, R. and Stephens, M. (1986), *Goodness-of-Fit Techniques,* New York: Marcel Dekker, Inc.

Danielsson, J., De Haan, L., Peng, L., and de Vries, C. G. (2001), "Using a Bootstrap Method to Choose the Sample Fraction in Tail Index Estimation," *Journal of Multivariate Analysis,* 76, 226–248.

Dunn, P. K. and Smyth, G. K. (2005), "Series Evaluation of Tweedie Exponential Dispersion Model Densities," *Statistics and Computing,* 15(4), 267–280.

Frydman, H. (1994), "A Note on Nonparametric Estimation of the Distribution Function from Interval-Censored and Truncated Observations," *Journal of Royal Statistical Society, Series B,* 56(1), 71–74.

Gentleman, R. and Geyer, C. J. (1994), "Maximum Likelihood for Interval Censored Data: Consistency and Computation," *Biometrika,* 81(3), 618–623.

Hill, B. M. (1975), "A Simple General Approach to Inference about the Tail of a Distribution," *Annals of Statistics,* 3(5), 1163–1174.

Jørgensen, B. (1987), "Exponential Dispersion Models (with Discussion)," *Journal of Royal Statistical Society, Series B,* 49(2), 127–162.

Kaplan, E. L. and Meier, P. (1958), "Nonparametric Estimation from Incomplete Observations," *Journal of American Statistical Association,* 53, 457–481.

Klein, J. P. and Moeschberger, M. L. (1997), *Survival Analysis: Techniques for Censored and Truncated Data,* New York: Springer-Verlag.

Klugman, S. A., Panjer, H. H., Willmot, G. E. (1998), *Loss Models: From Data to Decisions,* New York: John Wiley & Sons.

Koziol, J. A. and Green, S. B. (1976), "A Cramér-von Mises Statistic for Randomly Censored Data," *Biometrika,* 63, 466–474.

Lai, T. L. and Ying, Z. (1991), "Estimating A Distribution Function with Truncated and Censored Data," *Annals of Statistics,* 19(1), 417–442.

Lynden-Bell, D. (1971), "A Method of Allowing for Known Observational Selection in Small Samples Applied to 3CR Quasars," *Monthly Notices of the Royal Astronomical Society,* 155, 95–118.

Turnbull, B. W. (1976), "The Empirical Distribution Function with Arbitrarily Grouped, Censored, and Truncated Data," *Journal of Royal Statistical Society, Series B,* 38, 290–295.

Tweedie, M. C. K. (1984), "An Index Which Distinguishes between Some Important Exponential Families," *Statistics: Applications and New Directions, Proceedings of the Indian Statistical Institute Golden Jubilee International Conference, J. K. Ghosh and J. Roy (Eds.),* 579–604.

Chapter 25
The HPSUMMARY Procedure

Contents

Overview: HPSUMMARY Procedure **717**
PROC HPSUMMARY Features 718
Client and Grid Execution Modes 718
PROC HPSUMMARY Contrasted with Other Procedures 719
Getting Started: HPSUMMARY Procedure **719**
Syntax: HPSUMMARY Procedure **720**
PROC HPSUMMARY Statement 721
Statistic Keywords 724
CLASS Statement 725
FREQ Statement 726
OUTPUT Statement 726
PERFORMANCE Statement 728
TYPES Statement 728
VAR Statement 729
WAYS Statement 730
WEIGHT Statement 731
Details: HPSUMMARY Procedure **732**
How PROC HPSUMMARY Groups Data 732
Computational Resources 733
Statistical Computations 734
Results 736
Keywords and Formulas 738
References **745**

Overview: HPSUMMARY Procedure

The HPSUMMARY procedure enables you to summarize data on a SAS High Performance Analytics grid for parallel execution. The output data created by PROC HPSUMMARY can then be written in parallel back to the grid data store.

Although it is possible to use PROC HPSUMMARY on data that do not reside on the grid or produce result tables that do not reside on the grid, this usage is not recommended for production due to the overhead of transferring data to and from the grid.

PROC HPSUMMARY is a high-performance version of the SUMMARY procedure in Base SAS software. For more information about the SUMMARY procedure, see the *Base SAS 9.3 Procedures Guide*.

PROC HPSUMMARY Features

PROC HPSUMMARY provides data summarization tools to compute descriptive statistics for variables across all observations and within groups of observations. For example, PROC HPSUMMARY does the following:

- calculates descriptive statistics based on moments
- calculates and estimates quantiles, which includes the median
- calculates confidence limits for the mean
- identifies extreme values
- performs a *t* test

PROC HPSUMMARY does not display output. You can use the OUTPUT statement to store the statistics in a SAS data set.

PROC HPSUMMARY provides a vehicle for the parallel execution of summarization in a distributed computing environment. The following list summarizes the basic features of PROC HPSUMMARY:

- provides the ability to execute summarization in parallel
- enables you to control the level of parallelism per execution node and the number of nodes to engage
- is highly multithreaded
- manages data migration to the location of execution and movement back to the client machine as needed

Client and Grid Execution Modes

With the HPSUMMARY procedure you can read and write data in distributed form and perform analyses in massively parallel processing (MPP) and symmetric multiprocessing (SMP) mode. See the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics," for details about how to affect the execution mode of SAS High-Performance Analytics procedures.

PROC HPSUMMARY controls the execution of summarization in two dimensions. You can control both the number of parallel threads per execution node and also the number of compute nodes to engage.

Alternatively, PROC HPSUMMARY can be executed on the High-Performance Analytics grid. In grid mode, one or more copies of the summarization code are executed in parallel on each grid node.

The grid mode of execution has two variations:

- In the client-data (local-data) model of grid execution, the input data are not stored on the appliance but are distributed to the distributed computing environment during execution of the HPSUMMARY procedure.

- In the alongside-the-database model of grid execution, the data source is the database on the appliance. The data are stored in the distributed database, and the summarization code running on each node can read and write the data in parallel during execution of the procedure. Instead of data being moved across the network and possibly back to the client machine, data are passed locally between the processes on each node of the appliance. In general, especially with large data sets, the best PROC HPSUMMARY performance can be achieved if execution is alongside the database.

PROC HPSUMMARY Contrasted with Other Procedures

By default, PROC SUMMARY generates all CLASS variable combination types and requires the NWAY option to generate only the *n*-way. By default, PROC HPSUMMARY generates only the *n*-way, and requires the ALLTYPES option to generate all of the types.

Getting Started: HPSUMMARY Procedure

This example illustrates a simple use of the HPSUMMARY procedure to summarize using the grid in MPP mode. The following DATA step creates a data set that consists of test scores:

```
data gridlib.grades;
   input Name $ 1-8 Gender $ 11 Status $13 Year $ 15-16
         Section $ 18 Score 20-21 FinalGrade 23-24;
   datalines;
Abbott    F 2 97 A 90 87
Branford  M 1 98 A 92 97
Crandell  M 2 98 B 81 71
Dennison  M 1 97 A 85 72
Edgar     F 1 98 B 89 80
Faust     M 1 97 B 78 73
Greeley   F 2 97 A 82 91
Hart      F 1 98 B 84 80
Isley     M 2 97 A 88 86
Jasper    M 1 97 B 91 93
;
run;
```

The following statements read this data set and analyze the data for the two-way combination of CLASS variables and across all observations. To run these statements successfully, you need to set the macro variables GRIDHOST and GRIDINSTALLLOC to resolve to appropriate values, or you can replace the references to the macro variables in the example with the appropriate values.

```
proc hpsummary data=gridlib.grades;
   performance host="&GRIDHOST" install="&GRIDINSTALLLOC";
   var Score;
   class Status Year;
   types () status*year;
   output out=gridlib.result;
run;
```

```
proc print data=gridlib.result;
run;
```

Figure 25.1 displays the table produced by the HPSUMMARY procedure. The "Performance Information" table shows that HPSUMMARY was executed alongside the database on the grid.

Figure 25.1 HPSUMMARY Output

Performance Information

Host Node	<< your grid host >>
Execution Mode	Distributed
Number of Compute Nodes	4
Number of Threads per Node	8

Obs	Status	Year	_TYPE_	_FREQ_	_STAT_	Score
1			0	10	N	10.0000
2			0	10	MIN	78.0000
3			0	10	MAX	92.0000
4			0	10	MEAN	86.0000
5			0	10	STD	4.7140
6	1	98	3	3	N	3.0000
7	1	98	3	3	MIN	84.0000
8	1	98	3	3	MAX	92.0000
9	1	98	3	3	MEAN	88.3333
10	1	98	3	3	STD	4.0415
11	2	97	3	3	N	3.0000
12	2	97	3	3	MIN	82.0000
13	2	97	3	3	MAX	90.0000
14	2	97	3	3	MEAN	86.6667
15	2	97	3	3	STD	4.1633
16	2	98	3	1	N	1.0000
17	2	98	3	1	MIN	81.0000
18	2	98	3	1	MAX	81.0000
19	2	98	3	1	MEAN	81.0000
20	2	98	3	1	STD	.
21	1	97	3	3	N	3.0000
22	1	97	3	3	MIN	78.0000
23	1	97	3	3	MAX	91.0000
24	1	97	3	3	MEAN	84.6667
25	1	97	3	3	STD	6.5064

Syntax: HPSUMMARY Procedure

The following statements are available in the HPSUMMARY procedure:

```
PROC HPSUMMARY < options > < statistic-keywords > ;
    CLASS variables < / options > ;
    FREQ variable ;
    OUTPUT  < OUT=SAS-data-set > < output-statistic-specifications > < / AUTONAME > ;
    PERFORMANCE performance-options ;
    TYPES requests ;
    VAR variables < / WEIGHT=weight-variable > ;
    WAYS list ;
    WEIGHT variable ;
```

You can also use the ATTRIB, FORMAT, LABEL, and WHERE statements and any global statements. For more information, see *SAS Statements: Reference*.

PROC HPSUMMARY Statement

```
PROC HPSUMMARY < options > < statistic-keywords > ;
```

The PROC HPSUMMARY statement invokes the procedure. The HPSUMMARY procedure computes descriptive statistics for variables across all observations or within groups of observations.

Table 25.1 summarizes the available *options* in the PROC HPSUMMARY statement by function. The *options* are then described fully in alphabetical order in the section "Optional Arguments" on page 722. For information about the *statistic-keywords*, see the section "Statistic Keywords" on page 724.

Table 25.1 PROC HPSUMMARY Statement Options

Option	Description
Basic Options	
DATA=	Specifies the input data set
PCTLDEF=	Specifies the mathematical definition used to compute quantiles
Option Related to Classification Level	
MISSING	Uses missing values as valid values to create combinations of classification variables
Options Related to the Output Data Set	
ALLTYPES	Computes statistics for all combinations of classification variables (not just the n-way)
CHARTYPE	Specifies that the _TYPE_ variable contain character values
Options Related to Statistical Analysis	
ALPHA=	Specifies the confidence level for the confidence limits
EXCLNPWGT	Excludes observations with nonpositive weights from the analysis
QMARKERS=	Specifies the sample size to use for the P2 quantile estimation method
QMETHOD=	Specifies the quantile estimation method
QNTLDEF=	Specifies the mathematical definition used to compute quantiles
statistic-keywords	Selects the statistics
VARDEF=	Specifies the variance divisor

Optional Arguments

You can specify the following *options* in the PROC HPSUMMARY statement:

ALLTYPES

ALLWAYS

requests that PROC HPSUMMARY compute descriptive statistics for all combinations of classification variables. By default, PROC HPSUMMARY generates only the n-way. For more information, see the section "How PROC HPSUMMARY Groups Data" on page 732.

ALPHA=*value*

specifies the confidence level to compute the confidence limits for the mean. The percentage for the confidence limits is 100(1–*value*). For example, ALPHA=0.05 results in a 95% confidence limit. You can specify any *value* between 0 and 1. The default is 0.05. To compute confidence limits, specify the *statistic-keyword* CLM, LCLM, or UCLM. See the section "Confidence Limits" on page 734.

CHARTYPE

specifies that the _TYPE_ variable in the output data set is a character representation of the binary value of _TYPE_. The length of the variable equals the number of classification variables. When you specify more than 32 classification variables, _TYPE_ automatically becomes a character variable. See the section "Output Data Set" on page 737.

DATA=*SAS-data-set*

names the SAS data set to be used as the input data set. The default is the most recently created data set.

EXCLNPWGT

EXCLNPWGTS

excludes observations with nonpositive weight values (0 or negative) from the analysis. By default, PROC HPSUMMARY treats observations with negative weights like observations with zero weights and counts them in the total number of observations. See the WEIGHT= option and the section "WEIGHT Statement" on page 731.

MISSING

considers missing values as valid values to create the combinations of classification variables. Special missing values that represent numeric values—the letters A through Z and the underscore (_) character—are each considered as a separate value. If you omit MISSING, then PROC HPSUMMARY excludes the observations with a missing classification variable value from the analysis. See *SAS Language Reference: Concepts* for a discussion of missing values that have special meanings.

PCTLDEF=1 | 2 | 3 | 4 | 5

is an alias for the QNTLDEF= option.

QMARKERS=*number*

specifies the default number of markers to use for the P^2 quantile estimation method. The number of markers controls the size of fixed memory space.

The value of *number* must be an odd integer greater than 3. The default value depends on which quantiles you request. For the median (P50), *number* is 7. For the quantiles (P25 and P50), *number* is 25. For the quantiles P1, P5, P10, P75 P90, P95, or P99, *number* is 105. If you request several quantiles, then PROC HPSUMMARY uses the largest value of *number*.

You can improve the accuracy of the estimate by increasing the number of markers above the default settings; you can conserve memory and computing time by reducing the number of markers. See the section "Quantiles" on page 735.

QMETHOD=OS | P2

specifies the method that PROC HPSUMMARY uses to process the input data when it computes quantiles. If the number of observations is less than or equal to the QMARKERS= value and QNTLDEF=5, then both methods produce the same results. The QMETHOD= option can take either of the following values:

OS specifies that PROC HPSUMMARY use order statistics.

NOTE: This technique can be very memory-intensive.

P2 specifies that PROC HPSUMMARY use the P^2 method to approximate the quantile. When QMETHOD=P2, PROC HPSUMMARY does not compute MODE or weighted quantiles. In addition, reliable estimations of some quantiles (P1, P5, P95, P99) might not be possible for some data sets.

The default is OS. See the section "Quantiles" on page 735 for more information.

QNTLDEF=1 | 2 | 3 | 4 | 5

PCTLDEF=1 | 2 | 3 | 4 | 5

specifies the mathematical definition that PROC HPSUMMARY uses to calculate quantiles when QMETHOD=OS. The default is 5. To use QMETHOD=P2, you must use QNTLDEF=5. See the section "Quantile and Related Statistics" on page 742.

VARDEF=*divisor*

specifies the divisor to use in the calculation of the variance and standard deviation. Table 25.2 shows the possible values for *divisor* and their associated formulas.

Table 25.2 Values for VARDEF= Option

divisor	**Description**	**Formula for Divisor**
DF	Degrees of freedom	$n - 1$
N	Number of observations	n
WDF	Sum of weights minus one	$\left(\sum_i w_i\right) - 1$
WEIGHT | WGT	Sum of weights	$\sum_i w_i$

The procedure computes the variance as CSS divided by *divisor*, where the corrected sum of squares CSS is defined by the following formula:

$$\text{CSS} = \sum (x_i - \bar{x})^2$$

When you weight the analysis variables, the formula for CSS is

$$\text{CSS} = \sum w_i \, (x_i - \bar{x}_w)^2$$

where $\bar{x}_w$ is the weighted mean.

The default is DF. To compute the standard error of the mean, confidence limits for the mean, or the Student's t-test, you must use this default value.

When you use the WEIGHT statement and VARDEF=DF, the variance is an estimate of σ^2 , where the variance of the ith observation is $\text{var}(x_i) = \sigma^2/w_i$ and w_i is the weight for the ith observation. This method yields an estimate of the variance of an observation with unit weight. When you use the WEIGHT statement and VARDEF=WGT, the computed variance is asymptotically (for large n) an estimate of $\sigma^2/\bar{w}$, where $\bar{w}$ is the average weight. This method yields an asymptotic estimate of the variance of an observation with average weight. See the section "Keywords and Formulas" on page 738.

Statistic Keywords

Optional *statistic-keywords* specify which statistics to compute and the order to display them in the output. Table 25.3 lists the keywords that are available in the PROC HPSUMMARY statement. The definitions of the keywords and the formulas for the associated statistics are listed in the section "Keywords and Formulas" on page 738.

Table 25.3 Statistic Keywords in the PROC HPSUMMARY Statement

Descriptive Statistic Keywords:	
CLM	NMISS
CSS	RANGE
CV	SKEWNESS | SKEW
KURTOSIS | KURT	STDDEV | STD
LCLM	STDERR
MAX	SUM
MEAN	SUMWGT
MIN	UCLM
MODE	USS
N	VAR
Quantile Statistic Keywords:	
MEDIAN | P50	Q3 | P75
P1	P90
P5	P95
P10	P99
P20	P30
P40	P60
P70	P80
Q1 | P25	QRANGE
Hypothesis Testing Keywords:	
PROBT | PRT	T

The default values are N, MEAN, STD, MIN, and MAX. To compute standard error, confidence limits for the mean, and the Student's t-test, you must use the default value of the VARDEF= option, which is DF. To compute skewness or kurtosis, you must use VARDEF=N or VARDEF=DF. Use CLM or both LCLM and UCLM to compute a two-sided confidence limit for the mean. Use only LCLM or UCLM to compute

a one-sided confidence limit. The definitions of the keywords and the formulas for the associated statistics are listed in the section "Keywords and Formulas" on page 738.

CLASS Statement

CLASS *variables* < / *options* > **;**

The CLASS statement names the classification variables to be used as explanatory variables in the analysis. These variables enter the analysis not through their values, but through levels to which the unique values are mapped. See the section "Levelization of Classification Variables" on page 41 of Chapter 3, "Shared Concepts and Topics" for details about these mappings.

Levels of classification variables are ordered by their external formatted values, except for numeric variables with no explicit format, which are ordered by their unformatted (internal) values.

Required Argument

variables

specifies one or more variables that the procedure uses to group the data. Variables in a CLASS statement are referred to as *classification variables*. Classification variables are numeric or character. Classification variables can have continuous values, but they typically have a few discrete values that define levels of the variable. You do not have to sort the data by classification variables.

Use the TYPES statement or the WAYS statement to control which classification variables PROC HPSUMMARY uses to group the data. See the section "How PROC HPSUMMARY Groups Data" on page 732.

To reduce the number of classification variable levels, use a FORMAT statement to combine variable values. When a format combines several internal values into one formatted value, PROC HPSUMMARY outputs the lowest internal value.

Optional Arguments

GROUPINTERNAL

specifies that formats are not to be applied to the classification variables when PROC HPSUMMARY groups the values to create combinations of classification variables. This option saves computer resources when the numeric classification variables contain discrete values. See the section "Computational Resources" on page 733.

MISSING

considers missing values as valid values for the classification variable levels. Special missing values that represent numeric values—the letters A through Z and the underscore (_) character—are each considered as a separate value. If you omit the MISSING option, then PROC HPSUMMARY excludes the observations with a missing classification variable value from the analysis.

By default, if an observation contains a missing value for any classification variable, then PROC HPSUMMARY excludes that observation from the analysis. If you specify the MISSING option in the PROC HPSUMMARY statement, then the procedure considers missing values as valid levels for the combination of classification variables.

Specifying the MISSING option in the CLASS statement enables you to control the acceptance of missing values for individual classification variables.

See *SAS Language Reference: Concepts* for a discussion of missing values that have special meaning.

FREQ Statement

FREQ *variable* **;**

The FREQ statement specifies a numeric variable that contains the frequency of each observation.

Required Argument

variable

specifies a numeric variable whose value represents the frequency of the observation. If you use the FREQ statement, then the procedure assumes that each observation represents *n* observations, where *n* is the value of *variable*. If *n* is not an integer, then SAS truncates it. If *n* is less than 1 or is missing, then the procedure does not use that observation to calculate statistics.

The sum of the frequency variable represents the total number of observations.

OUTPUT Statement

OUTPUT < **OUT=***SAS-data-set* > < *output-statistic-specifications* > < / **AUTONAME** > **;**

The OUTPUT statement writes statistics to a new SAS data set. You can use multiple OUTPUT statements to create several OUT= data sets.

Optional Arguments

OUT=*SAS-data-set*

names the new output data set. If *SAS-data-set* does not exist, then PROC HPSUMMARY creates it. If you omit the OUT= option, then the data set is named DATA*n*, where *n* is the smallest integer that makes the name unique.

output-statistic-specifications

specifies the statistics to store in the OUT= data set and names one or more variables that contain the statistics. The form of the *output-statistic-specification* is

statistic-keyword < **(***variable-list***)** >**=**< *names* >

where

statistic-keyword

specifies which statistic to store in the output data set. Table 25.4 lists the *statistic-keywords* that are available in the OUTPUT statement.

Table 25.4 Statistics Keywords in the OUTPUT Statement

Descriptive Statistic Keywords:	
CSS	RANGE
CV	SKEWNESS | SKEW
KURTOSIS | KURT	STDDEV | STD
LCLM	STDERR
MAX	SUM
MEAN	SUMWGT
MIN	UCLM
MODE	USS
N	VAR
NMISS	
Quantile Statistic Keywords:	
MEDIAN | P50	Q3 | P75
P1	P90
P5	P95
P10	P99
P20	P30
P40	P60
P70	P80
Q1 | P25	QRANGE
Hypothesis Testing Keywords:	
PROBT | PRT	T

By default the statistics in the output data set automatically inherit the analysis variable's format, informat, and label. However, statistics computed for N, NMISS, SUMWGT, USS, CSS, VAR, CV, T, PROBT, PRT, SKEWNESS, and KURTOSIS do not inherit the analysis variable's format because this format might be invalid for these statistics (for example, dollar or datetime formats). If you omit a *variable-list* and *names*, then PROC HPSUMMARY allows the *statistic-keyword* only once in a single OUTPUT statement, unless you also use the AUTONAME option.

The definitions of the keywords and the formulas for the associated statistics are listed in the section "Keywords and Formulas" on page 738.

variable-list

specifies the names of one or more numeric analysis variables whose statistics you want to store in the output data set. By default, statistics are stored for all numeric analysis variables.

names

specifies one or more names for the variables in output data set to contain the analysis variable statistics. The first name contains the statistic for the first analysis variable; the second name contains the statistic for the second analysis variable; and so on. The default value is the analysis variable name. If you specify the AUTONAME option, then the default is the combination of the analysis variable name and the *statistic-keyword*. If you use the CLASS statement and an OUTPUT statement without an *output-statistic-specification*, then the output data set contains five observations for each combination of classification variables: the value of N, MIN,

MAX, MEAN, and STD. If you use the WEIGHT statement or the WEIGHT option in the VAR statement, then the output data set also contains an observation with the sum of weights (SUMWGT) for each combination of classification variables.

If you specify *variable-list*, then PROC HPSUMMARY uses the order in which you specify the analysis variables to store the statistics in the output data set variables. You can use the AUTONAME option to request that PROC HPSUMMARY generate unique names for multiple variables and statistics.

AUTONAME

requests that PROC HPSUMMARY create a unique variable name for an output statistic when you do not assign the variable name in the OUTPUT statement. This action is accomplished by appending the *statistic-keyword* to the input variable name. For example, the following statement produces the x_Min variable in the output data set:

```
output min(x)=/autoname;
```

AUTONAME activates the SAS internal mechanism that automatically resolves conflicts in the variable names in the output data set so that duplicate variables do not generate errors. As a result, the following statement produces two variables, x_Min and x_Min2, in the output data set:

```
output min(x)= min(x)=/autoname;
```

PERFORMANCE Statement

PERFORMANCE *performance-options* **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of a High-Performance Analytics procedure.

With the PERFORMANCE statement, you can also control whether a High-Performance Analytics procedure executes in SMP or MPP mode.

It is important to remember the distinction between the NODES= and NTHREADS= options. The NODES= option specifies the number of separate grid nodes that participate in the HPSUMMARY execution, while the NTHREADS= option influences how many threads are used by the HPSUMMARY procedure instance that runs on each node. If the data are located on the grid, then all nodes must be engaged; therefore, the NODES= option might be overridden. Setting NODES=0 causes PROC HPSUMMARY to execute on the client side only. Setting the NTHREADS= option to a value that is greater than the CPU count on each grid node is not likely to improve overall throughput.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

TYPES Statement

TYPES *requests* **;**

The TYPES statement identifies which of the possible combinations of classification variables to generate. The TYPES statement requires the specification of a CLASS statement.

Required Argument

requests

specifies which of the 2^k combinations of classification variables PROC HPSUMMARY uses to create the types, where k is the number of classification variables. A *request* includes one classification variable name, several classification variable names separated by asterisks, or ().

To request classification variable combinations quickly, use a grouping syntax by placing parentheses around several variables and joining other variables or variable combinations. The examples in Table 25.5 illustrate grouping syntax:

Table 25.5 Examples of Grouping Syntax

Request	Equivalent To
`types A*(B C);`	`types A*B A*C;`
`types (A B)*(C D);`	`types A*C A*D B*C B*D;`
`types (A B C)*D;`	`types A*D B*D C*D;`

You can use parentheses () to request the overall total (_TYPE_=0). If you do not need all types in the output data set, then use the TYPES statement to specify particular subtypes rather than applying a WHERE clause to the data set. Doing so saves time and computer memory.

Order of Analyses in the Output

The SUMMARY procedure writes analyses to the output in order of increasing values of the _TYPE_ variable. When PROC HPSUMMARY executes on the grid, the order of observations within the output is not deterministic because the output is returned in parallel. You can sort the output as follows:

- If output is directed back to the client, then to achieve an output order that is similar to the output of PROC SUMMARY, you need to subsequently sort the data by _TYPE_ and the classification variables.
- If output is directed back to the grid (so that the results are distributed), then there is no order within the output. To retrieve the observations in order, you can execute an SQL query, specifying that the selecting rows be returned in order by _TYPE_ and the classification variables.

The _TYPE_ variable is calculated even if no output data set is requested. For more information about the _TYPE_ variable, see the section "Output Data Set" on page 737.

VAR Statement

VAR *variables* < / **WEIGHT=***weight-variable* > **;**

The VAR statement identifies the analysis variables and their order in the output. If you omit the VAR statement, then PROC HPSUMMARY analyzes all numeric variables that are not listed in the other statements.

When all variables are character variables, PROC SUMMARY produces a simple count of observations. You can use multiple VAR statements.

Required Argument

variables
identifies one or more analysis variables and specifies their order in the results.

Optional Argument

WEIGHT=*weight-variable*
specifies a numeric variable whose values weight the values of the *variables*. The *weight-variable* does not have to be an integer. Table 25.6 describes how PROC HPSUMMARY treats various values of the *weight-variable*.

Table 25.6 Responses to Values of *weight-variable*

Value	PROC HPSUMMARY Response
0	Counts the observation in the total number of observations
Less than 0	Converts the value to zero and counts the observation in the total number of observations
Missing	Excludes the observation

To exclude observations that contain negative and zero weights from the analysis, use the EXCLNPWGT option in the PROC HPSUMMARY statement.

The *weight-variable* does not change how the procedure determines the range, extreme values, or number of missing values.

To compute weighted quantiles, use QMETHOD=OS in the PROC HPSUMMARY statement. Skewness and kurtosis are not available with the WEIGHT= option.

When you use the WEIGHT= option, consider which value of the VARDEF= option is appropriate. Use the WEIGHT= option in multiple VAR statements to specify different weights for the analysis variables.

WAYS Statement

WAYS *list* **;**

The WAYS statement specifies the number of ways to make unique combinations of classification variables. You can use the TYPES statement to specify additional combinations of classification variables.

Required Argument

list

specifies one or more integers that define the number of classification variables to combine to form all the unique combinations of classification variables. For example, you can specify 2 for all possible pairs and 3 for all possible triples. The *list* can be specified in the following ways:

- *m*
- *m1 m2 ... mn*
- *m1*,*m2*,...,*mn*
- *m* TO *n* <BY *increment*>
- *m1*,*m2*, TO *m3* <BY *increment*>,*m4*

The range of *list* is from 0 to the maximum number of classification variables.

The following statements are an example of creating two-way types for the classification variables A, B, and C:

```
class A B C ;
ways 2;
```

The WAYS statement in this example is equivalent to specifying **A*B**, **A*C**, and **B*C** in the TYPES statement.

WEIGHT Statement

WEIGHT *weight-variable* **;**

The WEIGHT statement specifies weights for observations in the statistical calculations.

Required Argument

weight-variable

specifies a numeric *weight-variable* whose values weight the values of the analysis variables. The values of *weight-variable* do not have to be integers. Table 25.7 describes how PROC HPSUMMARY treats various values of *weight-variable*.

Table 25.7 Responses to Values of *weight-variable*

Value	PROC HPSUMMARY Response
0	Counts the observation in the total number of observations
Less than 0	Converts the value to zero and counts the observation in the total number of observations
Missing	Excludes the observation

To exclude observations that contain negative and zero weights from the analysis, use the EXCLNPWGT option in the PROC HPSUMMARY statement.

CAUTION: Single extreme weight values can cause inaccurate results. When one (and only one) weight value is many orders of magnitude larger than the other weight values (for example, 49 weight values of 1 and one weight value of 1×10^{14}), certain statistics might not be within acceptable accuracy limits. The affected statistics are based on the second moment (such as standard deviation, corrected sum of squares, variance, and standard error of the mean). Under certain circumstances, no warning is written to the SAS log.

To compute weighted quantiles, you must use QMETHOD=OS in the PROC statement. Skewness and kurtosis are not available with the WEIGHT statement.

PROC HPSUMMARY does not compute MODE when a weight variable is active. Instead, you can try using the UNIVARIATE procedure when MODE needs to be computed and a weight variable is active.

If you use the WEIGHT= option in a VAR statement to specify a weight variable, then PROC HPSUMMARY uses this variable instead to weight those VAR statement variables.

When you use the WEIGHT statement, consider which value of the VARDEF= option is appropriate. See the section "Keywords and Formulas" on page 738 for more information.

Details: HPSUMMARY Procedure

How PROC HPSUMMARY Groups Data

Groups of observations are defined by specifying certain variables as classification variables in the CLASS statement. Unique values of the n CLASS variables are used to partition the input data, and the resulting summarized data (one observation per group) is called the "n-way."

PROC HPSUMMARY can also combine the partitioned groups into larger groups by removing one or more CLASS variables from consideration when grouping. There are 2^n different groupings that can be generated from n CLASS variables. Each of these groupings is a "type," which appears in the output data set as a variable named _TYPE_. Type 0 includes no CLASS variables and summarizes the entire input data set, Type 1 includes only the last CLASS variable specified, and so on to Type $2^n - 1$, which is the n-way.

By default, PROC HPSUMMARY generates only the n-way. The option ALLTYPES (or ALLWAYS) in the PROC HPSUMMARY statement generates all 2^n types. You can also use either of the following statements to choose which types appear in the output data set:

- The WAYS statement specifies how many CLASS variables appear in each output type. For example, WAYS 1 produces types for each CLASS variable individually, WAYS 2 generates all $\binom{n}{2}$ possible pairs, and so on.
- The TYPES statement explicitly specifies the desired types by CLASS variable name, such as TYPES A A*B C (), where A*B might specify Type 6 and "()" specifies Type 0.

The TYPES statement controls which of the available classification variables PROC HPSUMMARY uses to subgroup the data. The unique combinations of these active classification variable values that occur together in any single observation of the input data set determine the data subgroups. Each subgroup that PROC HPSUMMARY generates for a given type is called a level of that type. For all types, the inactive classification variables can still affect the total observation count of the rejection of observations with missing values. When you use a WAYS statement, PROC HPSUMMARY generates types that correspond to every possible unique combination of n classification variables chosen from the complete set of classification variables. For example

```
proc hpsummary;
   class a b c d e;
   ways 2 3;
   output out=results;
run;
```

is equivalent to

```
proc hpsummary;
   class a b c d e;
   types a*b a*c a*d a*e b*c b*d b*e c*d c*e d*e
         a*b*c a*b*d a*b*e a*c*d a*c*e a*d*e
         b*c*d b*c*e c*d*e;
   output out=results;
run;
```

If you omit the TYPES statement and the WAYS statement, then PROC HPSUMMARY uses all classification variables to subgroup the data (the NWAY type) for the output data set.

Computational Resources

The total of unique classification values that PROC HPSUMMARY allows depends on the amount of computer memory that is available. PROC HPSUMMARY uses the same memory allocation scheme across all operating environments. When classification variables are involved, PROC HPSUMMARY must keep a copy of each unique value of each classification variable in memory. You can estimate the memory requirements to group the classification variable by calculating

$$Nc_1(Lc_1 + K) + Nc_2(Lc_2 + K) + \ldots + Nc_n(Lc_n + K)$$

where Nc_i is the number of unique values for the classification variable, Lc_i is the combined unformatted and formatted length of c_i, and K is some constant on the order of 32 bytes (64 for 64-bit architectures). When you use the GROUPINTERNAL option in the CLASS statement, Lc_i is simply the unformatted length of c_i.

The GROUPINTERNAL option can improve computer performance because the grouping process is based on the internal values of the classification variables. If a numeric classification variable is not assigned a format and you do not specify GROUPINTERNAL, then PROC HPSUMMARY uses the default format, BEST12., to format numeric values as character strings. Then PROC HPSUMMARY groups these numeric variables by their character values, which takes additional time and computer memory.

Each unique combination of classification variables $c_{1_i}\ c_{2_j}$ for a given type forms a level in that type. See the section "TYPES Statement" on page 728. You can estimate the maximum potential space require-

ments for all levels of a given type, when all combinations actually exist in the data (a complete type), by calculating

$$W * Nc_1 * Nc_2 * \ldots * Nc_n$$

where W is a constant based on the number of variables analyzed and the number of statistics calculated (unless you request QMETHOD=OS to compute the quantiles) and $Nc_1 \ldots Nc_n$ are the number of unique levels for the active classification variables of the given type.

Clearly, the memory requirements of the levels overwhelm the levels of the classification variables. For information about how to adjust your computation resource parameters, see the SAS documentation for your operating environment.

Another way to enhance performance is by carefully applying the TYPES or WAYS statement, limiting the computations to only those combinations of classification variables that you are interested in.

Statistical Computations

Computation of Moment Statistics

PROC HPSUMMARY uses single-pass algorithms to compute the moment statistics (such as mean, variance, skewness, and kurtosis). See the section "Keywords and Formulas" on page 738 for the statistical formulas.

The computational details for confidence limits, hypothesis test statistics, and quantile statistics follow.

Confidence Limits

With the *statistic-keywords* CLM, LCLM, and UCLM, you can compute confidence limits for the mean. A confidence limit is a range (constructed around the value of a sample statistic) that contains the corresponding true population value with given probability (ALPHA=) in repeated sampling. A two-sided $100(1-\alpha)\%$ confidence interval for the mean has upper and lower limits

$$\bar{x} \pm t_{(1-\alpha/2;n-1)} \frac{s}{\sqrt{n}}$$

where $s = \sqrt{\frac{1}{n-1}\sum(x_i - \bar{x})^2}$ and $t_{(1-\alpha/2;n-1)}$ is the $(1-\alpha/2)$ critical value of the Student's t statistic with $n-1$ degrees of freedom.

A one-sided $100(1-\alpha)\%$ confidence interval is computed as

$$\bar{x} + t_{(1-\alpha;n-1)} \frac{s}{\sqrt{n}} \qquad \text{(upper)}$$

$$\bar{x} - t_{(1-\alpha;n-1)} \frac{s}{\sqrt{n}} \qquad \text{(lower)}$$

A two-sided $100(1-\alpha)\%$ confidence interval for the standard deviation has lower and upper limits

$$s\sqrt{\frac{n-1}{\chi^2_{(1-\alpha/2;n-1)}}}, \quad s\sqrt{\frac{n-1}{\chi^2_{(\alpha/2;n-1)}}}$$

where $\chi^2_{(1-\alpha/2;n-1)}$ and $\chi^2_{(\alpha/2;n-1)}$ are the $(1-\alpha/2)$ and $\alpha/2$ critical values of the chi-square statistic with $n-1$ degrees of freedom. A one-sided $100(1-\alpha)\%$ confidence interval is computed by replacing $\alpha/2$ with α.

A $100(1-\alpha)\%$ confidence interval for the variance has upper and lower limits that are equal to the squares of the corresponding upper and lower limits for the standard deviation.

If you use the WEIGHT statement or the WEIGHT= option in a VAR statement and the default value of the VARDEF= option (which is DF), the $100(1-\alpha)\%$ confidence interval for the weighted mean has upper and lower limits

$$\bar{y}_w \pm t_{(1-\alpha/2)} \frac{s_w}{\sqrt{\sum_{i=1}^{n} w_i}}$$

where $\bar{y}_w$ is the weighted mean, s_w is the weighted standard deviation, w_i is the weight for the ith observation, and $t_{(1-\alpha/2)}$ is the $(1-\alpha/2)$ critical value for the Student's t distribution with $n-1$ degrees of freedom.

Student's t Test

PROC HPSUMMARY calculates the t statistic as

$$t = \frac{\bar{x} - \mu_0}{s/\sqrt{n}}$$

where $\bar{x}$ is the sample mean, n is the number of nonmissing values for a variable, and s is the sample standard deviation. Under the null hypothesis, the population mean equals μ_0. When the data values are approximately normally distributed, the probability under the null hypothesis of a t statistic as extreme as, or more extreme than, the observed value (the p-value) is obtained from the t distribution with $n-1$ degrees of freedom. For large n, the t statistic is asymptotically equivalent to a z test.

When you use the WEIGHT statement or the WEIGHT= option in a VAR statement and the default value of the VARDEF= option (which is DF), the Student's t statistic is calculated as

$$t_w = \frac{\bar{y}_w - \mu_0}{s_w \Big/ \sqrt{\sum_{i=1}^{n} w_i}}$$

where $\bar{y}_w$ is the weighted mean, s_w is the weighted standard deviation, and w_i is the weight for the ith observation. The t_w statistic is treated as having a Student's t distribution with $n-1$ degrees of freedom. If you specify the EXCLNPWGT option in the PROC HPSUMMARY statement, then n is the number of nonmissing observations when the value of the WEIGHT variable is positive. By default, n is the number of nonmissing observations for the WEIGHT variable.

Quantiles

The options QMETHOD=, QNTLDEF=, and QMARKERS= determine how PROC HPSUMMARY calculates quantiles. The QNTLDEF= option deals with the mathematical definition of a quantile. See the section "Quantile and Related Statistics" on page 742. The QMETHOD= option specifies how PROC HPSUMMARY handles the input data: When QMETHOD=OS, PROC HPSUMMARY reads all data into

memory and sorts it by unique value. When QMETHOD=P2, PROC HPSUMMARY accumulates all data into a fixed sample size that is used to approximate the quantile.

If data set A has 100 unique values for a numeric variable X and data set B has 1,000 unique values for numeric variable X, then QMETHOD=OS for data set B requires 10 times as much memory as it does for data set A. If QMETHOD=P2, then both data sets A and B require the same memory space to generate quantiles.

The QMETHOD=P2 technique is based on the piecewise-parabolic (P^2) algorithm invented by Jain and Chlamtac (1985). P^2 is a one-pass algorithm to determine quantiles for a large data set. It requires a fixed amount of memory for each variable for each level within the type. However, using simulation studies, reliable estimations of some quantiles (P1, P5, P95, P99) cannot be possible for some data sets such as data sets with heavily tailed or skewed distributions.

If the number of observations is less than the QMARKERS= value, then QMETHOD=P2 produces the same results as QMETHOD=OS when QNTLDEF=5. To compute weighted quantiles, you must use QMETHOD=OS.

Results

Missing Values

PROC HPSUMMARY excludes missing values for the analysis variables before calculating statistics. Each analysis variable is treated individually; a missing value for an observation in one variable does not affect the calculations for other variables. PROC HPSUMMARY handles missing values as follows:

- If a classification variable has a missing value for an observation, then PROC HPSUMMARY excludes that observation from the analysis unless you use the MISSING option in the PROC statement or CLASS statement.
- If a FREQ variable value is missing or nonpositive, then PROC HPSUMMARY excludes the observation from the analysis.
- If a WEIGHT variable value is missing, then PROC HPSUMMARY excludes the observation from the analysis.

PROC HPSUMMARY tabulates the number of the missing values. Before the number of missing values are tabulated, PROC HPSUMMARY excludes observations with frequencies that are nonpositive when you use the FREQ statement and observations with weights that are missing or nonpositive (when you use the EXCLNPWGT option) when you use the WEIGHT statement. To report this information in the procedure output use the NMISS *statistic-keyword* in the PROC HPSUMMARY statement.

The N Obs Statistic

By default when you use a CLASS statement, PROC HPSUMMARY displays an additional statistic called N Obs. This statistic reports the total number of observations or the sum of the observations of the FREQ variable that PROC HPSUMMARY processes for each class level. PROC HPSUMMARY might omit observations from this total because of missing values in one or more classification variables. Because of this action and the exclusion of observations when the *weight-variable* (specified in the WEIGHT statement

or in the WEIGHT= option in the VAR statement) contains missing values, there is not always a direct relationship between N Obs, N, and NMISS.

In the output data set, the value of N Obs is stored in the _FREQ_ variable.

Output Data Set

PROC HPSUMMARY creates one output data set. The procedure does not print the output data set. Use the PRINT procedure, the REPORT procedure, or another SAS reporting tool to display the output data set.

NOTE: By default, the statistics in the output data set automatically inherit the analysis variable's format and label. However, statistics computed for N, NMISS, SUMWGT, USS, CSS, VAR, CV, T, PROBT, PRT, SKEWNESS, and KURTOSIS do not inherit the analysis variable's format because this format can be invalid for these statistics.

The output data set can contain these variables:

- the variables specified in the CLASS statement.
- the variable _TYPE_ that contains information about the classification variables. By default _TYPE_ is a numeric variable. If you specify CHARTYPE in the PROC statement, then _TYPE_ is a character variable. When you use more than 32 classification variables, _TYPE_ is automatically a character variable.
- the variable _FREQ_ that contains the number of observations that a given output level represents.
- the variables requested in the OUTPUT statement that contain the output statistics and extreme values.
- the variable _STAT_ that contains the names of the default statistics if you omit statistic keywords.

The value of _TYPE_ indicates which combination of the classification variables PROC HPSUMMARY uses to compute the statistics. The character value of _TYPE_ is a series of zeros and ones, where each value of one indicates an active classification variable in the type. For example, with three classification variables, PROC HPSUMMARY represents type 1 as 001, type 5 as 101, and so on.

Usually, the output data set contains one observation per level per type. However, if you omit *statistic-keywords* in the OUTPUT statement, then the output data set contains five observations per level (six if you specify a WEIGHT variable). Therefore, the total number of observations in the output data set is equal to the sum of the levels for all the types that you request multiplied by 1, 5, or 6, whichever is applicable.

If you omit the CLASS statement (_TYPE_= 0), then there is always exactly one level of output per output data set. If you use a CLASS statement, then the number of levels for each type that you request has an upper bound equal to the number of observations in the input data set. By default, PROC HPSUMMARY generates all possible types. In this case the total number of levels for each output data set has an upper bound equal to

$$m \cdot (2^k - 1) \cdot n + 1$$

where k is the number of classification variables, n is the number of observations in the input data set, and m is 1, 5, or 6.

PROC HPSUMMARY determines the actual number of levels for a given type from the number of unique combinations of each active classification variable. A single level consists of all input observations whose formatted class values match.

Table 25.8 shows the values of _TYPE_ and the number of observations in the data set when you specify one, two, and three classification variables.

Table 25.8 The Effect of Classification Variables on the OUTPUT Data Set

CLASS Variables							
C	B	A	_WAY_	_TYPE_	Subgroup defined by	Number of observations of this _TYPE_ and _WAY_ in the data set	Total number of observations in the data set
0	0	0	0	0	Total	1	
0	0	1	1	1	A	a	1+a
0	1	0	1	2	B	b	
0	1	1	2	3	A*B	a*b	1+a+b+a*b
1	0	0	1	4	C	c	
1	0	1	2	5	A*C	a*c	
1	1	0	2	6	B*C	b*c	1+a+b+a*b+c
1	1	1	3	7	A*B*C	a*b*c	+a*c+b*c+a*b*c
Character binary equivalent of _TYPE_ (CHARTYPE option in the PROC HPSUMMARY statement)						a,b,c = number of levels of A, B, C, respectively	

Keywords and Formulas

Simple Statistics

The HPSUMMARY procedure uses a standardized set of keywords to refer to statistics. You specify these keywords in SAS statements to request the statistics to be displayed or stored in an output data set.

In the following notation, summation is over observations that contain nonmissing values of the analyzed variable and, except where shown, over nonmissing weights and frequencies of one or more:

x_i
: is the nonmissing value of the analyzed variable for observation i.

f_i
: is the frequency that is associated with x_i if you use a FREQ statement. If you omit the FREQ statement, then $f_i = 1$ for all i.

w_i
: is the weight that is associated with x_i if you use a WEIGHT statement. The HPSUMMARY procedure automatically excludes the values of x_i with missing weights from the analysis.

By default, the HPSUMMARY procedure treats a negative weight as if it is equal to 0. However, if you use the EXCLNPWGT option in the PROC HPSUMMARY statement, then the procedure also excludes those values of with nonpositive weights.

If you omit the WEIGHT statement, then $w_i = 1$ for all i.

n

is the number of nonmissing values of x_i, $\sum f_i$. If you use the EXCLNPWGT option and the WEIGHT statement, then n is the number of nonmissing values with positive weights.

$\bar{x}$

is the mean

$$\sum w_i x_i \Big/ \sum w_i$$

s^2

is the variance

$$\frac{1}{d} \sum w_i (x_i - \bar{x})^2$$

where d is the variance divisor (the VARDEF= option) that you specify in the PROC HPSUMMARY statement. Valid values are as follows:

When VARDEF=	d **equals**
N	n
DF	$n - 1$
WEIGHT | WGT	$\sum_i w_i$
WDF	$\left(\sum_i w_i\right) - 1$

The default is DF.

z_i

is the standardized variable

$$(x_i - \bar{x})/s$$

PROC HPSUMMARY calculates the following simple statistics:

- number of missing values
- number of nonmissing values
- number of observations
- sum of weights
- mean
- sum
- extreme values
- minimum
- maximum
- range

- uncorrected sum of squares
- corrected sum of squares
- variance
- standard deviation
- standard error of the mean
- coefficient of variation
- skewness
- kurtosis
- confidence limits of the mean
- median
- mode
- percentiles/deciles/quartiles
- t test for mean=0

The standard keywords and formulas for each statistic follow. Some formulas use keywords to designate the corresponding statistic.

Descriptive Statistics

The keywords for descriptive statistics are as follows:

CSS
is the sum of squares corrected for the mean, computed as

$$\sum w_i (x_i - \bar{x})^2$$

CV
is the percent coefficient of variation, computed as

$$(100s)/\bar{x}$$

KURTOSIS | KURT
is the kurtosis, which measures heaviness of tails. When VARDEF=DF, the kurtosis is computed as

$$c_{4_n} \sum z_i^4 - \frac{3\,(n-1)^2}{(n-2)\,(n-3)}$$

where c_{4_n} is $\frac{n(n+1)}{(n-1)(n-2)(n-3)}$
When VARDEF=N, the kurtosis is computed as

$$\frac{1}{n} \sum z_i^4 - 3$$

The formula is invariant under the transformation $w_i^* = z w_i$, $z > 0$. When you use VARDEF=WDF or VARDEF=WEIGHT, the kurtosis is set to missing.

MAX
: is the maximum value of x_i.

MEAN
: is the arithmetic mean $\bar{x}$.

MIN
: is the minimum value of x_i.

MODE
: is the most frequent value of x_i.

  NOTE: When QMETHOD=P2, PROC HPSUMMARY does not compute MODE.

N
: is the number of x_i values that are not missing. Observations with $f_i < 1$ and w_i equal to missing or $w_i \leq 0$ (when you use the EXCLNPWGT option) are excluded from the analysis and are not included in the calculation of N.

NMISS
: is the number of x_i values that are missing. Observations with $f_i < 1$ and w_i equal to missing or $w_i \leq 0$ (when you use the EXCLNPWGT option) are excluded from the analysis and are not included in the calculation of NMISS.

NOBS
: is the total number of observations and is calculated as the sum of N and NMISS. However, if you use the WEIGHT statement, then NOBS is calculated as the sum of N, NMISS, and the number of observations excluded because of missing or nonpositive weights.

RANGE
: is the range and is calculated as the difference between maximum value and minimum value.

SKEWNESS | SKEW
: is skewness, which measures the tendency of the deviations to be larger in one direction than in the other. When VARDEF=DF, the skewness is computed as

$$c_{3_n} \sum z_i^3$$

  where c_{3_n} is $\frac{n}{(n-1)(n-2)}$.
  When VARDEF=N, the skewness is computed as

$$\frac{1}{n} \sum z_i^3$$

  The formula is invariant under the transformation $w_i^* = z w_i$, $z > 0$. When you use VARDEF=WDF or VARDEF=WEIGHT, the skewness is set to missing.

STDDEV | STD
: is the standard deviation s and is computed as the square root of the variance, s^2.

STDERR | STDMEAN
: is the standard error of the mean, computed as

$$\frac{s}{\sqrt{\sum w_i}}$$

  when VARDEF=DF, which is the default. Otherwise, STDERR is set to missing.

SUM
is the sum, computed as

$$\sum w_i x_i$$

SUMWGT
is the sum of the weights, W, computed as

$$\sum w_i$$

USS
is the uncorrected sum of squares, computed as

$$\sum w_i x_i^2$$

VAR
is the variance s^2.

Quantile and Related Statistics

The keywords for quantiles and related statistics are as follows:

MEDIAN
is the middle value.

P*n*
is the n^{th} percentile. For example, P1 is the first percentile, P5 is the fifth percentile, P50 is the 50^{th} percentile, and P99 is the 99^{th} percentile.

Q1
is the lower quartile (25^{th} percentile).

Q3
is the upper quartile (75^{th} percentile).

QRANGE
is interquartile range and is calculated as

$$Q_3 - Q_1$$

You use the QNTLDEF= option to specify the method that the HPSUMMARY procedure uses to compute percentiles. Let n be the number of nonmissing values for a variable, and let $x_1, x_2, \ldots, x_n$ represent the ordered values of the variable such that x_1 is the smallest value, x_2 is the next smallest value, and x_n is the largest value. For the tth percentile between 0 and 1, let $p = t/100$. Then define j as the integer part of np and g as the fractional part of np or $(n+1)p$, so that

$$\begin{aligned} np &= j + g \quad \text{when QNTLDEF=1, 2, 3, or 5} \\ (n+1)p &= j + g \quad \text{when QNTLDEF=4} \end{aligned}$$

Here, QNTLDEF= specifies the method that the procedure uses to compute the tth percentile, as shown in Table 25.10.

When you use the WEIGHT statement, the tth percentile is computed as

$$y = \begin{cases} \frac{1}{2}(x_i + x_{i+1}) & \text{if } \sum_{j=1}^{i} w_j = pW \\ x_{i+1} & \text{if } \sum_{j=1}^{i} w_j < pW < \sum_{j=1}^{i+1} w_j \end{cases}$$

where w_j is the weight associated with x_i and $W = \sum_{i=1}^{n} w_i$ is the sum of the weights. When the observations have identical weights, the weighted percentiles are the same as the unweighted percentiles with QNTLDEF=5.

Table 25.10 Methods for Computing Quantile Statistics

QNTLDEF=	Description	Formula	
1	Weighted average at x_{np}	$y = (1-g)x_j + gx_{j+1}$ where x_0 is taken to be x_1	
2	Observation numbered closest to np	$y = x_i$	if $g \neq \frac{1}{2}$
		$y = x_j$	if $g = \frac{1}{2}$ and j is even
		$y = x_{j+1}$	if $g = \frac{1}{2}$ and j is odd
		where i is the integer part of $np + \frac{1}{2}$	
3	Empirical distribution function	$y = x_j$	if $g = 0$
		$y = x_{j+1}$	if $g > 0$
4	Weighted average aimed at $x_{(n+1)p}$	$y = (1-g)x_j + gx_{j+1}$ where x_{n+1} is taken to be x_n	
5	Empirical distribution function with averaging	$y = \frac{1}{2}(x_j + x_{j+1})$	if $g = 0$
		$y = x_{j+1}$	if $g > 0$

Hypothesis Testing Statistics

The keywords for hypothesis testing statistics are as follows:

T

is the Student's t statistic to test the null hypothesis that the population mean is equal to μ_0 and is calculated as

$$\frac{\bar{x} - \mu_0}{s \Big/ \sqrt{\sum w_i}}$$

By default, μ_0 is equal to zero. You must use VARDEF=DF, which is the default variance divisor; otherwise T is set to missing.

By default, when you use a WEIGHT statement, the procedure counts the x_i values with nonpositive weights in the degrees of freedom. Use the EXCLNPWGT option in the PROC HPSUMMARY statement to exclude values with nonpositive weights.

PROBT | PRT
: is the two-tailed p-value for the Student's t statistic, T, with $n-1$ degrees of freedom. This value is the probability under the null hypothesis of obtaining a more extreme value of T than is observed in this sample.

Confidence Limits for the Mean

The keywords for confidence limits are as follows:

CLM
: is the two-sided confidence limit for the mean. A two-sided $100(1-\alpha)$ percent confidence interval for the mean has upper and lower limits

$$\bar{x} \pm t_{(1-\alpha/2;n-1)} \frac{s}{\sqrt{\sum w_i}}$$

where s is $\sqrt{\frac{1}{n-1}\sum(x_i-\bar{x})^2}$, $t_{(1-\alpha/2;n-1)}$ is the $(1-\alpha/2)$ critical value of the Student's t statistic with $n-1$ degrees of freedom, and α is the value of the ALPHA= option which by default is 0.05. Unless you use VARDEF=DF (which is the default variance divisor), CLM is set to missing.

LCLM
: is the one-sided confidence limit below the mean. The one-sided $100(1-\alpha)$ percent confidence interval for the mean has the lower limit

$$\bar{x} - t_{(1-\alpha;n-1)} \frac{s}{\sqrt{\sum w_i}}$$

Unless you use VARDEF=DF (which is the default variance divisor), LCLM is set to missing.

UCLM
: is the one-sided confidence limit above the mean. The one-sided $100(1-\alpha)$ percent confidence interval for the mean has the upper limit

$$\bar{x} + t_{(1-\alpha;n-1)} \frac{s}{\sqrt{\sum w_i}}$$

Unless you use VARDEF=DF (which is the default variance divisor), UCLM is set to missing.

Data Requirements for the HPSUMMARY Procedure

The following are the minimal data requirements to compute unweighted statistics and do not describe recommended sample sizes. Statistics are reported as missing if VARDEF=DF (the default) and the following requirements are not met:

- N and NMISS are computed regardless of the number of missing or nonmissing observations.
- SUM, MEAN, MAX, MIN, RANGE, USS, and CSS require at least one nonmissing observation.
- VAR, STD, STDERR, CV, T, PRT, and PROBT require at least two nonmissing observations.
- SKEWNESS requires at least three nonmissing observations.

- KURTOSIS requires at least four nonmissing observations.
- SKEWNESS, KURTOSIS, T, PROBT, and PRT require that STD is greater than zero.
- CV requires that MEAN is not equal to zero.
- CLM, LCLM, UCLM, STDERR, T, PRT, and PROBT require that VARDEF=DF.

References

Jain, R. and Chlamtac, I. (1985), "The P^2 Algorithm for Dynamic Calculation of Quantiles and Histograms without Storing Observations," *Communications of the ACM*, 28, 1076–1085.

Chapter 26
The HPTMINE Procedure (Experimental)

Contents

Overview: HPTMINE Procedure **748**
PROC HPTMINE Features 748
PROC HPTMINE Contrasted with Other SAS Procedures 749
Getting Started: HPTMINE Procedure **749**
Syntax: HPTMINE Procedure **754**
PROC HPTMINE Statement 754
DOC_ID Statement 754
PARSE Statement 755
PERFORMANCE Statement 758
SVD Statement 758
VARIABLE Statement 760
Details: HPTMINE Procedure **760**
Natural Language Processing 760
Stemming 760
Part-of-Speech Tagging 760
Noun Group Extraction 761
Entity Identification 761
Multiword Terms Handling 762
Language Support 762
Term and Cell Weighting 762
Singular Value Decomposition 763
Applications in Text Mining 763
Computation 764
Output Data Sets 764
The OUTCONFIG= Data Set 764
The OUTDOCPRO= Data Set 765
The OUTPARENT= Data Set 765
The OUTCHILD= Data Set 766
The OUTTERMS= Data Set 766
Displayed Output 768
Performance Information 768
Procedure Task Timing 768
ODS Table Names 768
Configuration for Distributed Mode 768
Examples: HPTMINE Procedure **769**

Example 26.1: Parsing with No Options Turned On 769
Example 26.2: Parsing with Stemming Turned On 771
Example 26.3: Adding Entities and Noun Groups 773
Example 26.4: Adding Part-of-Speech Tagging 775
Example 26.5: Adding Synonyms 777
Example 26.6: Adding a Stop List 779
Example 26.7: Adding a Multiterm List 781
Example 26.8: Running in Distributed Mode 783

Overview: HPTMINE Procedure

The experimental HPTMINE procedure is a high-performance procedure that analyzes large-scale textual data. PROC HPTMINE provides the SAS High-Performance Analytics platform an essential capability for text mining and supports a wide range of fundamental text analysis features, which include tokenizing, stemming, part-of-speech tagging, noun group extraction, default or customized stop or start lists, entity parsing, multiword tokens, synonym lists, term weighting, term-by-document matrix creation, and dimension reduction by term filtering and singular value decomposition (SVD).

PROC HPTMINE integrates the functionalities provided by the TGPARSE, TMUTIL, and SPSVD procedures from SAS Text Miner, and achieves high efficiency and scalability through parallel processing. The HPTMINE procedure can also generate results that can be used to facilitate scoring by the HPTMSCORE procedure. These results include a configuration data set, a term data set, and a data set that contains the SVD projection matrix.

You can use the HPTMINE procedure to read data in distributed form and perform text analysis in parallel in symmetric multiprocessing (SMP) or massively parallel processing (MPP) mode. For more information about how to configure the execution mode of SAS High-Performance Analytics procedures, see the section "SMP and MPP Modes" on page 16 in Chapter 3, "Shared Concepts and Topics."

PROC HPTMINE Features

The HPTMINE procedure processes large-scale textual data in parallel to achieve efficiency and scalability. The following list summarizes the basic features of PROC HPTMINE:

- Functionalities that are related to document parsing, term-by-document matrix creation, and dimension reduction are integrated into one procedure to process data more efficiently.
- Parsing supports essential natural language processing (NLP) features, which include tokenizing, stemming, part-of-speech tagging, noun group extraction, default or customized stop or start lists, entity parsing, multiword tokens, synonym lists.
- Term weighting and filtering are supported for term-by-document matrix creation.
- Parsing and term-by-document matrix creation is parallelized.

- Computation of singular value decomposition (SVD) is parallelized.
- Analysis can be performed on a massively parallel SAS high-performance appliance.
- All phases of processing make use of a high degree of multithreading.
- Input data can be read in parallel when the data source is the appliance database.

PROC HPTMINE Contrasted with Other SAS Procedures

For general contrasts between High-Performance Analytics procedures and other SAS procedures, see the section "SAS High-Performance Analytics Procedures Contrasted with Other SAS Procedures" on page 16. The following remarks compare the HPTMINE procedure with the TGPARSE, TMUTIL, and SPSVD procedures in SAS Text Miner software.

PROC HPTMINE maximizes performance by combining the key functionalities found in the TGPARSE, TMUTIL, and SPSVD procedures. By functioning as an "all-in-one" procedure, PROC HPTMINE avoids expensive I/O operations. The PARSE option in the HPTMINE procedure effectively replaces the necessary options provided by the combination of PROC TGPARSE followed by PROC TMUTIL in the conventional SAS environment. You can use the PARSE option to control parsing, accumulation, and ultimately the construction of the underlying weighted term-document frequency matrix. This matrix serves as input for singular value decomposition, which is controlled by the SVD statement in the HPTMINE procedure.

PROC HPTMINE's functionality also replaces many of the core functions that were available in the SPSVD procedure. Both PROC HPTMINE and PROC SPSVD produce an output that holds the reduced dimensional representation for the input documents. They also generate an output **U** matrix that can be used to project new documents in this same reduced space during scoring.

Getting Started: HPTMINE Procedure

The following DATA step contains 36 observations with two variables. The text variable contains the input documents, and the did variable contains the ID of the documents. Each row in the data set created below represents a document for analysis.

```
data getstart;
    infile cards delimiter='|' missover;
    length text $150;
    input text$ did$;
    cards;
        High-performance analytics hold the key to |d01
        unlocking the unprecedented business value of big data.|d02
        Organizations looking for optimal ways to gain insights|d03
        from big data in shorter reporting windows are turning to SAS.|d04
        As the gold-standard leader in business analytics |d05
        for more than 36 years,|d06
        SAS frees enterprises from the limitations of |d07
        traditional computing and enables them |d08
```

```
            to draw instant benefits from big data.|d09
            Faster Time to Insight.|d10
            From banking to retail to health care to insurance, |d11
            SAS is helping industries glean insights from data |d12
            that once took days or weeks in just hours, minutes or seconds.|d13
            It's all about getting to and analyzing relevant data faster.|d14
            Revealing previously unseen patterns, sentiments and relationships.|d15
            Identifying unknown risks.|d16
            And speeding the time to insights.|d17
            High-Performance Analytics from SAS Combining industry-leading |d18
            analytics software with high-performance computing technologies|d19
            produces fast and precise answers to unsolvable problems|d20
            and enables our customers to gain greater competitive advantage.|d21
            SAS In-Memory Analytics eliminate the need for disk-based processing|d22
            allowing for much faster analysis.|d23
            SAS In-Database executes analytic logic into the database itself |d24
            for improved agility and governance.|d25
            SAS Grid Computing creates a centrally managed,|d26
            shared environment for processing large jobs|d27
            and supporting a growing number of users efficiently.|d28
            Together, the components of this integrated, |d29
            supercharged platform are changing the decision-making landscape|d30
            and redefining how the world solves big data business problems.|d31
            Big data is a popular term used to describe the exponential growth,|d32
            availability and use of information,|d33
            both structured and unstructured.|d34
            Much has been written on the big data trend and how it can |d35
            serve as the basis for innovation, differentiation and growth.|d36
run;
```

The following statements use singular value decomposition to parse the input text data and generate a lower dimensional representation of the documents. The statements specify that only the terms that appear at least twice in the document collection are kept for generating the term-by-document matrix. The summary information about the terms in the document collection be stored in a SAS data set named terms. The SVD statement requests that the top 10 singular values and singular vectors are computed. The projection of the documents is stored in a SAS data set named docpro.

```
proc hptmine data=getstart;
doc_id      did;
variable    text;
parse
            outterms  = terms
            reducef   = 2;
svd
            k         = 10
            outdocpro = docpro;
performance details;
run;
```

The output from this analysis is presented in Figure 26.1 through Figure 26.5.

Figure 26.1 shows the "Performance Information" table, which indicates that PROC HPTMINE executes in client mode. That is, PROC HPTMINE runs on the machine where the SAS system is running. The table also shows that two threads are used for computing.

Figure 26.1 Performance Information

Performance Information

Execution Mode	On client
Number of Threads	2

Figure 26.2 shows the "Procedure Task Timing" table, which provides details about how much time is used by each processing step.

Figure 26.2 Procedure Task Timing

Procedure Task Timing

Task	Time (sec.)	
Parse documents	0.92	90.9%
Analyze terms	0.00	0.03%
Obtain term frequency	0.03	3.20%
Filter terms	0.02	1.61%
Generate term-document matrix	0.01	1.40%
Output OUTTERMS table	0.01	1.41%
Compute SVD	0.01	1.14%
Output OUTDOCPRO table	0.00	0.26%

Figure 26.3 shows the SAS log that is generated by PROC HPTMINE; the log provides information about the default configurations used by the procedure, about where the procedure runs, and about the input and output files. The log shows that the terms data set contains 271 observations. This means that the HPTMINE procedure identified 271 individual terms in the input document collection. Because K=10 in the SVD statement, the docpro data set contains 11 variables: the first variable is the document ID, and the remaining 10 variables are obtained by projecting the original document to the 10 left singular vectors that are computed by the singular value decomposition.

Figure 26.3 SAS Log

```
NOTE: Stemming will be used in parsing.
NOTE: Tagging will be used in parsing.
NOTE: Noun groups will be used in parsing.
NOTE: No TERMWGT option is specified. TERMWGT=ENTROPY will be run by default.
NOTE: No CELLWGT option is specified. CELLWGT=LOG will be run by default.
NOTE: No ENTITIES option is specified.ENTITIES=STD will be run by default.
NOTE: The HPTMINE procedure is executing on the client.
NOTE: There were 36 observations read from the data set WORK.GETSTART.
NOTE: The data set WORK.TERMS has 271 observations and 11 variables.
NOTE: The data set WORK.DOCPRO has 36 observations and 11 variables.
```

The following statements use PROC PRINT to show the content of the first 10 rows of the docpro data set that is generated by the HPTMINE procedure:

```
proc print data = docpro (obs=10) round;
run;
```

Figure 26.4 shows the output of PROC PRINT. For information about the output of the OUTDOCPRO= option, see the section "The OUTDOCPRO= Data Set" on page 765.

Figure 26.4 The docpro Data Set

Obs	did	COL1	COL2	COL3	COL4	COL5	COL6	COL7	COL8	COL9	COL10
1	d01	0.26	-0.76	0.21	-0.22	0.33	-0.18	0.25	0.08	-0.01	-0.24
2	d02	0.74	0.24	0.39	-0.04	-0.15	-0.02	-0.09	-0.09	-0.45	-0.01
3	d03	0.22	-0.23	-0.62	-0.23	-0.17	0.07	-0.48	-0.04	0.03	-0.44
4	d04	0.74	-0.01	0.13	0.35	0.08	-0.13	-0.41	0.19	0.18	0.23
5	d05	0.30	-0.23	0.49	-0.54	-0.30	-0.18	-0.19	0.38	0.06	0.14
6	d06	0.11	-0.24	-0.30	-0.23	-0.62	0.46	-0.08	-0.10	0.42	-0.11
7	d07	0.42	-0.33	0.06	0.40	-0.23	0.07	-0.18	-0.06	-0.55	0.39
8	d08	0.09	-0.16	-0.12	-0.40	0.26	-0.14	-0.24	-0.71	0.06	0.37
9	d09	0.85	0.10	-0.03	0.36	0.16	-0.23	-0.20	0.05	-0.06	-0.09
10	d10	0.23	-0.08	-0.60	-0.28	0.22	0.08	0.15	0.53	-0.16	0.34

The following statements use PROC SORT and PROC PRINT to show the content of the terms data set that is generated by the HPTMINE procedure. In the output, only the terms with a key value from 1 to 35 are shown. And for these terms only the value of the variables term, role, freq, numdocs, key, and parent are displayed.

```
proc sort data = terms; by key; run;
proc print data = terms (obs=35);
var term role freq numdocs key parent;
run;
```

Figure 26.5 shows the output of PROC PRINT, which provides details about the terms that are identified by the HPTMINE procedure. For example, it shows the key of "problems" is 32 and its parent's key is 9, which is the term "problem." The HPTMINE procedure also identified that "sas" is a proper noun and that "big data" and "high-performance analytics" are noun groups. For information about the output of the OUTTERMS= option, see the section "The OUTTERMS= Data Set" on page 766.

Figure 26.5 The terms Data Set

Obs	Term	Role	Freq	numdocs	Key	Parent
1	high-performance	Adj	3	3	1	.
2	big data	NOUN_GROUP	5	5	2	.
3	to	Prep	13	11	3	.
4	fast	Adj	4	4	4	4
5	fast	Adj	1	1	4	.
6	data	Noun	8	8	5	.
7	gain	Verb	2	2	6	.
8	big	Adj	6	6	7	.
9	for	Prep	6	6	8	.
10	problem	Noun	2	2	9	9
11	as	Prep	2	2	10	.
12	business	Noun	3	3	11	.
13	analytics	Prop	2	2	12	.
14	the	Det	13	13	13	.
15	time	Noun	2	2	14	.
16	in	Prep	3	3	15	.
17	process	Verb	2	2	16	16
18	and	Conj	13	13	17	.
19	insight	Noun	3	3	18	18
20	a	Det	3	3	19	.
21	compute	Verb	2	2	20	20
22	be	Verb	3	3	21	21
23	high-performance analytics	NOUN_GROUP	2	2	22	.
24	be	Aux	3	3	23	23
25	from	Prep	6	6	24	.
26	how	Conj	2	2	25	.
27	growth	Noun	2	2	26	.
28	it	Pron	2	2	27	.
29	enable	Verb	2	2	28	28
30	of	Prep	5	5	29	.
31	analytics	Noun	3	3	30	.
32	sas	Prop	7	7	31	.
33	problems	Noun	2	2	32	9
34	insights	Noun	3	3	33	18
35	enables	Verb	2	2	34	28

Syntax: HPTMINE Procedure

The following statements are available in the HPTMINE procedure:

PROC HPTMINE < *options* > **;**
  VARIABLE *variable* **;**
  DOC_ID *variable* **;**
  PARSE < *parse-options* > **;**
  SVD < *svd-options* > **;**
  PERFORMANCE *performance-options* **;**

PROC HPTMINE Statement

PROC HPTMINE < *options* > **;**

The PROC HPTMINE statement invokes the procedure. Table 26.1 summarizes the *options* in the statement by function. The *options* are then described fully in alphabetical order.

Table 26.1 PROC HPTMINE Statement Options

option	**Description**
Basic Options	
DATA | DOC=	Specifies the input document data set
Output Options	
NOPRINT	Suppresses ODS output

You can specify the following *options* in the PROC HPTMINE statement:

DATA=*SAS-data-set*

DOC=*SAS-data-set*
names the input SAS data set of documents to be used by PROC HPTMINE. The default is the most recently created data set. If PROC HPTMINE executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. When data are already distributed, PROC HPTMINE reads the data alongside the distributed database. See the sections "SMP and MPP Modes" on page 16 and "Alongside-the-Database Execution" on page 22. Each row of the input data set must contain one text field and one ID field that correspond to the text and the unique ID of a document, respectively.

NOPRINT
suppresses the generation of ODS output.

DOC_ID Statement

DOC_ID *variable* **;**

This statement specifies the *variable* that contains the ID of each document. In the input data set, each row corresponds to one document. The ID of each document must be unique; it can be either a number or a string of characters.

PARSE Statement

PARSE < *parse-options* > **;**

The PARSE statement specifies the options for parsing the input documents and creating the term-by-document matrix. Table 26.2 summarizes the *parse-options* in the statement by function. The *parse-options* are then described fully in alphabetical order.

Table 26.2 PARSE Statement Options

parse-option	**Description**
Parsing Options	
NOSTEMMING	Specifies no stemming in parsing
NOTAGGING	Specifies no part-of-speech tagging in parsing
NONOUNGROUPS | NONG	Specifies no noun group extraction in parsing
ENTITIES=	Specifies whether to extract entities in parsing
STOP=	Specifies the stop list
START=	Specifies the start list
MULTITERM=	Specifies the multiword term list
SYNONYM | SYN=	Specifies the synonym list
Term-by-document Matrix Creation Options	
TERMWGT=	Specifies how terms are weighted
CELLWGT=	Specifies how cells are weighted
REDUCEF=	Specifies the frequency for term filtering
Output Options	
OUTPARENT=	Specifies the data set to contain the term-by-document frequency matrix. Child terms are not represented in the data set. The frequencies of child terms are attributed to their corresponding parents.
OUTCHILD=	Specifies a secondary choice to contain the term-by-document frequency matrix. All kept terms, whether or not they are child terms, are represented in the data set with their corresponding frequency.
OUTTERMS=	Specifies the data set to contain the summary information about the terms in the document collection.
OUTCONFIG=	Specifies the data set to contain the option settings used by PROC HPTMIME in the current run.

You can specify the following *options* in the PROC HPTMINE statement:

CELLWGT=LOG | NONE
specifies how the elements in the term-by-document matrix are weighted. The available cell weights are as follows:

LOG	specifies that cells be weighted by using the LOG formulation.
NONE	specifies that no cell weight be applied.

For information about the LOG formulation for cell weighting, see the section "Term and Cell Weighting" on page 762.

ENTITIES=STD | NONE
determines whether the entity extractor should use the standard list of entities. When ENTITIES=STD, entity extraction is turned on and standard entities are used; terms such as "George W. Bush" are recognized as an entity and given the corresponding entity role and attribute. For this example, the entity role is PERSON and the attribute is Entity. While the entity is treated as the single term, "george w. bush," the individual tokens "george," "w," and "bush" are also included. By default, ENTITIES=NONE.

MULTITERM=*OS-file-reference*
specifies the path to a file that contains a list of multiword terms. These terms are case-sensitive and are treated as a single entry by the HPTMINE procedure. Thus, the terms "Thank You" and "thank you" are processed differently. Consequently, you must convert all text strings to lowercase or add each of the multiterm's case variations to the list before using the HPTMINE procedure to create consistent multiword terms. The multiterm file can be any file type as long as it is formatted in the following manner:

```
multiterm: 3: pos
```

Specifically, the first item is the mutliword term itself followed by a colon, the second item is a number that is specific to Teragram and represents the token type followed by a colon, and the third item is the part of speech that the multiword term represents. **NOTE:** The token type 3 is the most common token type for multiterm lists and represents compound words.

NONOUNGROUPS | NONG
determines whether the noun group extractor should be used. When this option is not specified, noun group are extracted and the HPTMINE procedure returns maximal groups and subgroups (which do not include groups that contain determiners or prepositions). If stemming is turned on, then noun group elements are also stemmed.

NOSTEMMING
determines whether words should be stemmed. When this option is not specified, words are stemmed and terms such as "advises" and "advising" are mapped to the parent term "advise."

NOTAGGING
determines whether terms should be tagged. When this option is not specified, terms are tagged and the HPTMINE procedure identifies a term's part of speech based on context clues. The identified part of speech is provided in the Role variable of the OUTTERMS= data set.

OUTCHILD=*SAS-data-set*

specifies the data set to contain a compressed representation of the sparse term-by-document frequency matrix. The term counts cannot be weighted. The data set saves only the kept, representative terms. The child frequencies are not attributed to their corresponding parent (as they are in the OUTPARENT= data set). For more information about the compressed representation of the sparse term-by-document frequency matrix, see the section "Output Data Sets" on page 764.

OUTCONFIG=*SAS-data-set*

specifies the data set to contain configuration information that is used for the current run of PROC HPTMINE. The primary purpose of this data set is to relay the configuration information from the HPTMINE procedure to the HPTMSCORE procedure. The HPTMSCORE procedure is forced to use options that are consistent with the HPTMINE procedure. Thus, the data set created with the OUTCONFIG= option becomes an input data set for PROC HPTMSCORE and ensures that the parsing options are consistent between the two runs. For more information about this data set, see the section "Output Data Sets" on page 764.

OUTPARENT=*SAS-data-set*

specifies the data set to contain a compressed representation of the sparse term-by-document frequency matrix. The term counts can be weighted, if requested. The data set contains only the kept, representative terms, and the child frequencies are attributed to the corresponding parent. To obtain information about the children, use the OUTCHILD= option. For more information about the compressed representation of the sparse term-by-document frequency matrix, see the section "Output Data Sets" on page 764.

OUTTERMS=*SAS-data-set*

specifies the data set to contain the summary information about the terms in the document collection. For more information about this data set, see the section "Output Data Sets" on page 764.

REDUCEF=*n*

removes terms that are not in at least *n* documents. The value of *n* must be a positive integer. By default, REDUCEF=4.

START=*SAS-data-set*

specifies the data set that contains the terms that are to be kept for the analysis. These terms are displayed in the OUTTERMS= data set with a keep status of Y, and all other terms have a keep status of N. The START data set must have a Term variable and can also have a Role variable. You cannot specify both the START and the STOP options.

STOP=*SAS-data-set*

specifies the data set that contains the terms to exclude from the analysis. These terms are displayed in the OUTTERMS= data set with a keep status of N. They are not identified as parents or children. The STOP data set must have a Term variable and can also have a Role variable. You cannot specify both the START and the STOP options.

SYNONYM=*SAS-data-set*

SYN=*SAS-data-set*

specifies the data set that contains user-defined synonyms to be used in the analysis. The data set specifies parent-child relationships that enable you to map child terms to a representative parent. The synonym relationship is indicated in the data set that is specified in the OUTTERMS= option and is also reflected in the term-by-document data set that is specified in the OUTPARENT= option. The

input synonym data set must have either the two variables Term and Parent, or the four variables Term, Parent, Termrole, and Parentrole. When stemming is turned on, this list overrides any relationships that are identified when terms are stemmed.

TERMWGT=ENTROPY | NONE
specifies how terms are weighted. The available term weights are as follows:

ENTROPY specifies that terms be weighted using the entropy formulation.

NONE specifies that no term weight is applied.

For more information about the entropy formulation for term weighting, see the section "Term and Cell Weighting" on page 762.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPTMINE procedure. You can also use the PERFORMANCE statement to control whether the HPTMINE procedure executes in SMP or MPP mode. The PERFORMANCE statement for High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

SVD Statement

SVD < *svd-options* > **;**

The SVD statement specifies the options for calculating a truncated singular value decomposition (SVD) of the large, sparse term-by-document frequency matrix that was created during the parsing phase of PROC HPTMINE. Table 26.3 summarizes the *svd-options* in the statement by function. The *svd-options* are then described fully in alphabetical order.

Table 26.3 SVD Statement Options

svd-option	**Description**
SVD Computation Options	
K=	Specifies the number of dimensions to be extracted by SVD
MAX_K=	Specifies the maximum number of dimensions to be extracted by SVD
TOL=	Specifies the maximum allowable tolerance for the singular value
RESOLUTION | RES=	Specifies the recommended number of dimensions (resolution) extracted by SVD, when the MAX_K= option is used
Output Options	
SVDU=	Specifies the U matrix, which contains the left singular vectors

Table 26.3 *continued*

svd-option	**Description**
SVDV=	Specifies the V matrix, which contains the right singular vectors
SVDS=	Specifies the S matrix, whose diagonal elements are the singular values
OUTDOCPRO=	Specifies the projections of the documents

You can specify the following *svd-options* in the SVD statement.

K=*k*

specifies the number of columns in the matrices U, V, and S. This value is the number of dimensions of the data set after the SVD is performed. If the value of *k* is too large, then the HPTMINE procedure runs for an unnecessarily long time. You cannot specify both this option and the MAX_K= option.

MAX_K=*n*

specifies the maximum value that the HPTMINE procedure should return as the recommended value of *n*. If the RES= argument is specified to recommend the value of *k*, this option limits that value to at most *n*. The HPTMINE procedure attempts to calculate (as opposed to recommends) *k* dimensions when it performs SVD. You cannot specify both this option and the K= option.

OUTDOCPRO=*SAS-data-set*

specifies the data set to contain the projections of the columns of the term-by-document frequency matrix onto the columns of U. Since each column of the term-by-document frequency matrix corresponds to a document, the output forms a new representation of the input documents in a space with much lower dimensionality.

RESOLUTION=LOW | MED | HIGH

RES=LOW | MED | HIGH

specifies the recommended number of dimensions (resolution) for the singular value decomposition. If you specify this option, you must also specify the MAX_K= option. A low-resolution singular value decomposition returns fewer dimensions than a high-resolution singular value decomposition. This option recommends the value of k heuristically based on the value specified in the MAX_K= option. Assume that the MAX_K= option is set to be *n* and a singular value decomposition with *n* dimensions accounts for $t\%$ of the total variance. The option HIGH always recommends the maximum number of dimensions, that is, $k = n$. The option MED recommends a k that explains $(5/6) * t\%$ of the total variance. The option LOW recommends a k that explains $(2/3) * t\%$ of the total variance.

SVDS=*SAS-data-set*

specifies the data set to contain the calculated singular values.

SVDU=*SAS-data-set*

specifies the data set to contain the calculated left singular vectors.

SVDV=*SAS-data-set*

specifies the data set to contain the calculated right singular vectors.

TOL=ϵ

specifies the maximum allowable tolerance for the singular value. Let $\mathbf{A}$ be a matrix. Suppose λ_i is the ith singular value of $\mathbf{A}$ and ξ_i is the corresponding right singular vector. The SVD computation terminates when $\forall i \in \{1, \ldots, k\}$, λ_i and $_{0i}$ satisfy $\|\mathbf{A}^\top \mathbf{A}\xi - \lambda\xi\|^2 \leq \epsilon$. The default value of ϵ is 10^{-6}, which is more than adequate for most text mining problems.

VARIABLE Statement

VARIABLE *variable* **;**

VAR *variable* **;**

This statement specifies the *variable* that contains the text to be processed.

Details: HPTMINE Procedure

PROC HPTMINE integrates the functionalities from both natural language processing and statistical analysis to provide essential support for high-performance text mining. This section provides details about various perspectives of the HPTMINE procedure.

Natural Language Processing

Natural language processing (NLP) techniques can be used to extracting meaningful information from natural language input. The following sections describe features from SAS linguistic technologies that are supported in the HPTMINE procedure to support nature language processing.

Stemming

Stemming (a special case of morphological analysis) identifies the possible root form for an inflected word. For example, the word "talk" is the stem of the words "talk," "talks," "talking," and "talked." In this case "talk" is the parent, and "talk," "talks," "talking," and "talked" are its children.

Part-of-Speech Tagging

Using SAS linguistic technologies, tagging identifies, or disambiguates, the grammatical category of a word by analyzing it within its context. For example:

```
I like to bank at the local branch of my bank.
```

In this case the first "bank" is tagged with the verb (V), and the second "bank" is tagged with noun (N). Table 26.4 shows all possible part-of-speech tags:

Table 26.4 All Part-of-Speech Tag

Part-of-Speech Tag	Description
ABBR	Abbreviations

Table 26.4 *continued*

Part-of-Speech Tag	Description
ADJ	Adjectives
ADV	Adverbs
AUX	Auxiliary or modal terms
CONJ	Conjunctions
DET	Determiners
INTERJ	Interjections
NOUN	Nouns
NOUN_GROUP	Compound nouns
NUM	Numbers or numeric expressions
PART	Infinitive markers, negative participles, or possessive markers
PREF	Prefixes
PREP	Prepositions
PRON	Pronouns
PROP	Proper nouns
PUNCT	Punctuation
VERB	Verbs
VERBADJ	Verb adjectives

Noun Group Extraction

Noun groups provide more relevant information than simple nouns. A noun group is defined as a sequence nouns and their modifiers. Noun group extraction uses part-of-speech tagging to identify nouns and their related words that together form a noun group. Examples of noun groups are "weeklong cruises" and "middle Eastern languages."

Entity Identification

Entity identification uses SAS linguistic technologies to classify sequences of words into predefined classes. These classes are assigned as roles for the corresponding sequences. For example, "Person," "Location," "Company," and "Measurement" are identified as classes for "George W. Bush," "Boston," "SAS Institute," "2.5 inches," respectively. Table 26.5 shows all possible entities that are valid only for English.

Table 26.5 All Valid English Entities

Entities	Description
ADDRESS	Postal address or number and street name
COMPANY	Company name
CURRENCY	Currency or currency expression
INTERNET	E-mail address or URL
LOCATION	City, county, state, political or geographical place or region
MEASURE	Measurement or measurement expression
NOUN_GROUP	Phrases that contain multiple words
ORGANIZATION	Government, legal, or service agency
PERCENT	Percentage or percentage expression

Table 26.5 *continued*

Entities	Description
PERSON	Person's name
PHONE	Telephone number
PROP_MISC	Proper noun with an ambiguous classification
SSN	Social Security number
TIME	Time or time expression
TIME_PERIOD	Measure of time expressions
TITLE	Person's title or position
VEHICLE	Motor vehicle, including color, year, make, and model

Multiword Terms Handling

By default, SAS linguistic technologies tokenize the text to individual words and operate at the word level. Multiword terms provide a control that enables you to specify sequences of words to be interpreted as individual units. For example, "greater than," "in spite of," and "as well as" can be defined as multiword terms.

Language Support

In the current release, English is the only supported language. By turning off some of the advanced parsing functionality, you might be able to use PROC HPTMINE effectively with other space-delimited languages.

Term and Cell Weighting

The TERMWGT= option and the CELLWGT= option control how to weight the frequencies in the compressed term-by-document matrix. The term weight is a positive number that is assigned to each term based on the distribution of that term in the document collection. This weight can be interpreted as an indication of the importance of that term to the document collection. The cell weight is a function that is applied to every entry in the term-by-document matrix; it moderates the effect of a term that is repeated within a document.

Let $f_{i,j}$ be the entry in the ith row and jth column of the term-by-document matrix, which indicates the time of appearance of term i in document j. Assuming that the term weight of term i is w_i and the cell weight function is $g(x)$, the weighted frequency of each entry in the term-by-document matrix is given by $w_i \times g(f_{i,j})$.

When the CELLWGT=LOG option is specified, the following equation is used to weight cells:

$$g(x) = \log_2(f_{i,j} + 1)$$

The equation reduces the influence of highly frequent terms by applying the log function.

When the TERMWGT=ENTROPY option is specified, the following equation is used to weight terms:

$$w_i = 1 + \sum_j \frac{p_{i,j} \log_2(p_{i,j})}{\log_2(n)}$$

In this equation, n is the number of documents, and $p_{i,j}$ is the probability that term i appears in document j, which can be estimated by $p_{i,j} = \frac{f_{i,j}}{g_i}$, where g_i is is the global term frequency for term i.

Singular Value Decomposition

The singular value decomposition (SVD) of a matrix $\mathbf{A}$ factors $\mathbf{A}$ into three matrices such that $\mathbf{A} = \mathbf{U}\Sigma\mathbf{V}^\top$. The singular value decomposition also requires that the columns of $\mathbf{U}$ and $\mathbf{V}$ be orthogonal and that Σ be a real-valued diagonal matrix with monotonically decreasing, nonnegative entries. The entries of Σ are called singular values. The columns of $\mathbf{U}$ and $\mathbf{V}$ are called left and right singular vectors, respectively. A truncated singular value decomposition calculates only the first k singular values and their corresponding left and right singular vectors. In information retrieval, singular value decomposition is also known as latent semantic indexing (LSI).

Applications in Text Mining

Let $\mathbf{A} \in \mathbb{R}^{m \times n}$ be a term-by-document matrix, where m is the number of terms and n is the number of documents. The SVD statement has two main functions: to calculate a truncated singular value decomposition (SVD) of $\mathbf{A}$, and to project the columns of $\mathbf{A}$ onto the left singular vectors to generate a new representation of the documents with much lower dimensionality. The output of the SVD statement is a truncated singular value decomposition of $\mathbf{A}$, for which you specify the parameter k to define how many singular values and singular vectors to compute. A singular value decomposition reduces the dimension of the term-by-document matrix and reveals themes that are present in the document collection.

In general, the value of k must be large enough to capture the meaning of the document collection, yet small enough to ignore the noise. You can specify this value explicitly or accept a value that is recommended by the HPTMINE procedure. A value between 50 and 200 should work well for a document collection that contains thousands of documents.

An important purpose of a singular value decomposition is to reduce a high-dimensional term-by-document matrix into a low-dimensional representation that reveals information about the document collection. The columns of the $\mathbf{A}$ form the coordinates for the document space, and the rows form the coordinates of the term space. Each document in the collection is represented as a vector in m-dimensional space and each term as a vector in n-dimensional space. The singular value decomposition captures this same information with a smaller number of basis vectors than would be necessary if you analyzed $\mathbf{A}$ directly.

For example, consider the columns of $\mathbf{A}$, which represent the document space. By construction, the columns of $\mathbf{U}$ also reside in m-dimensional space. If $\mathbf{U}$ has only one column, the line between that vector and the origin would form the best fit line, in a least squares sense, to the original document space. If $\mathbf{U}$ has two columns, then these columns would form the best fit plane to the original document space. In general, the first k columns of $\mathbf{U}$ form the best fit k-dimensional subspace for the document space. Thus, you can project the columns of $\mathbf{A}$ onto the first k columns of $\mathbf{U}$ in order to optimally reduce the dimension of the document space from m to k.

The projection of a document $\mathbf{d}$ (one column of $\mathbf{A}$) onto $\mathbf{U}$ results in k real numbers that are defined by the inner product $\mathbf{d}$ with each column of $\mathbf{U}$. That is, $p_i = \mathbf{d}^\top \mathbf{u}_i$. With this representation, each document forms a k-dimensional vector that can be considered a theme in the document collection. You can then calculate the Euclidean distance between each document and each column of $\mathbf{U}$ to determine the documents that are described by this theme.

In a similar fashion, you can repeat the previous process with the rows of $\mathbf{A}$ and the first k columns of $\mathbf{V}$. This generates a best fit k-dimensional subspace for the term space. This representation is used to group terms into similar clusters. These clusters also represent concepts that are prevalent in the document collection. Thus, the singular value decomposition can be used to cluster both the terms and documents into meaningful representations of the entire document collection.

Computation

The computation of the singular vector decomposition is fully parallelized in PROC HPTMINE to support both SMP via multithreading and MPP via distributed computing. In the current release, computing singular value decomposition requires the input data to contain at least 25 documents and at least as many documents as there are nodes in the grid. If p nodes are used for computing singular value decomposition in a distributed computing environment, then the input data must contain at least $\max(p, 25)$ documents. Computing the singular value decomposition is an iterative process that involves considerable communication among the computer nodes in a distributed computing environment. Therefore, adding more computer nodes for computing singular value decomposition might not always improve efficiency. Conversely, when the data size is not large enough, adding too many computer nodes for computation might lead to a noticeable increase in communication time and sometimes might even slow down the overall computation.

Output Data Sets

This section describes the output data sets that PROC HPTMINE produces when you specify the corresponding option.

The OUTCONFIG= Data Set

The OUTCONFIG= option specifies a SAS data set to contain the configuration used by PROC HPTMINE in the current run. The primary purpose of this data set is to relay the configuration information from the HPTMINE procedure to the HPTMSCORE procedure. Thus, the HPTMSCORE procedure can use the options that are consistent with the HPTMINE procedure during scoring.

Table 26.6 shows the configuration information that is contained in this data set.

Table 26.6 The Fields in The OUTCONFIG= Data Set

Field	Indicates
namedfile	Whether the parsed variable is in an external file or in the input data set (this field is not applicable in the current release)
language	The source language of the documents ("English" is the only supported language)
encoding	The encoding of the documents ("wlatin1" is the only supported encoding)
plugin	The plug-in used to parse the document collection ("Teragram" is the only supported plug-in)
stemming	Whether stemming is used: "Y" indicates that stemming is used, and "N" indicates that it is not used
tagging	Whether tagging is used: "Y" indicates that tagging is used, and "N" indicates that it is not used

Table 26.6 *continued*

Field	Description
NG	Whether noun group is used: "Y" indicates that noun group is used, and "N" indicates that it is not used
entities	Whether entities should be extracted: "STD" indicates that entities should be extracted, and "N" indicates that entities should not be extracted
entList	The entities that are kept (this field is not applicable in the current release)
attributes	Whether attributes are kept or dropped: "Y" indicates that attributes are kept, and "N" indicates that attributes are dropped
attrList	The attributes that are kept or dropped (this field is not applicable in the current release)
pos	Whether parts of speech are kept or dropped (this field is not applicable in the current release)
posList	The parts of speech that are kept or dropped (this field is not applicable in the current release)
multiterm	The path to the multiterm list file
litiList	The path to your custom entities (this field is not applicable in the current release)
cellwgt	How the cells of the term-by-document frequency matrix are weighted

The content of this data set is case sensitive.

The OUTDOCPRO= Data Set

The OUTDOCPRO= option specifies a SAS data set to contain the projections of the columns of the term-by-document frequency matrix onto the columns of U. Since each column of the term-by-document frequency matrix corresponds to a document, the output forms a new representation of the input documents in a space with much lower dimensionality. If the K= option in the SVD statement is set to k and the input data set contains n documents, the output will have n rows and $k + 1$ columns. Each row of the output corresponds to a document. The first column of the output contains the ID of the documents, and the name of the column is the same as the variable specified in the DOC_ID statement. The remaining k columns are the projections and are named "COL1" to "COLk."

The OUTPARENT= Data Set

The OUTPARENT= option specifies a SAS data set to contain a compressed representation of the sparse term-by-document frequency matrix. The term-by-document frequency frequency matrix is usually very sparse[1]. To save space, the transactional style is used as a compressed representation to store the sparse matrix. In this format, the matrix is represented as a set of triples $(i,\ j,\ x)$, where x is an entry in the matrix and i and j denote its row and column indices, respectively. The transactional style can also be used when the output contains too many columns to fit in a data set. For example, in most database systems the maximum number of columns in a table is usually limited to several thousand. If an output matrix contains

[1] Many elements of the matrix are 0.

more columns than the limit, you must use the transactional style to avoid errors that would arise from writing too many columns to the table. When the transactional style is used, all 0 entries in the matrix are ignored in the output, thereby saving storing space when the matrix is sparse.

The data set of the OUTPARENT= option contains three columns: _TERMNUM_, _DOCUMENT_, and _COUNT_. The _TERMNUM_ column contains the ID of the terms, which corresponds to the "Key" column of the data set that is generated by the OUTTERMS= option. The _DOCUMENT_ column contains the ID of the documents, and the _COUNT_ column contains the term counts. For example, (**t1 d1 k**) means term **t1** appears **k** times in document **d1**.

The term counts can be weighted, if requested. The data set saves only the terms that are marked as kept in the data set that is specified in the OUTTERMS= option of the PARSE statement. In the data set the child frequencies are attributed to the corresponding parent. For example, if "said" has term ID **t1** and appears eight times in the document **d1**, "say" has term ID **t2** and appears one time in the document **d1**. Assume that "say" is the parent of "said" and that neither cell weighting nor term weighting is applied. Then the data set that is specified in the OUTPARENT= option will have an entry

```
t2     d1     9
```

The term count of "said" in **d1** is attributed to its parent "say".

The OUTCHILD= Data Set

The OUTCHILD= option specifies the data set to contain a compressed representation of the sparse term-by-document frequency matrix, which is usually very sparse. To save storage space, the transactional style is used as a compressed representation to store the sparse matrix. Like the the data set specified in the OUTPARENT= option, the data set specified in the OUTCHILD= option also contains three columns: _TERMNUM_, _DOCUMENT_, and _COUNT_. The _TERMNUM_ column contains the ID of the terms, which corresponds to the "Key" column of the data set generated by the OUTTERMS= option. The _DOCUMENT_ column contains the ID of the documents, and the _COUNT_ column contains the term counts. For example, (**t1 d1 k**) means that term **t1** appears **k** times in document **d1**.

The data set saves only the terms that are marked as kept in the data set specified in the OUTTERMS= option of the PARSE statement. The child frequencies are not attributed to their corresponding parent (as they are in data set specified in the OUTPARENT= option). Using the example in the previous section, the data set generated by the OUTCHILD= option will have two entries:

```
t1     d1     8
t2     d1     1
```

The term count of "said" in **d1** is not attributed to its parent "say." The data set specified in the OUTCHILD= option can be combined with the data set specified in the OUTTERMS= option to construct the data set specified in the OUTPARENT= option.

The OUTTERMS= Data Set

The data set specified in the OUTTERMS= option contains the summary information about the terms in the document collection.

Table 26.7 shows the fields in this data.

Table 26.7 The Fields in The OUTTERMS= Data Set

Fields	Description
Term	A lowercase version of the term
Role	The term's part of speech (this variable is empty if the NOTAGGING option is specified in the PARSE statement)
Attribute	An indication of the characters that compose the term. Possible attributes are: Alpha — only alphabetic characters Mixed — a combination of attributes Num — only numbers Punct — punctuation characters Entity — an identified entity
Freq	The frequency of a term in the entire document collection
numdocs	The number of documents that contain the term
_keep	The keep status of the term: "Y" indicates that the term is kept for analysis, and "N" indicates that the term should be dropped in later stages of analysis
Key	The assigned term number (each unique term in the parsed documents and each unique parent term has a unique Key value)
Parent	The Key value of the term's parent or a "." (period): • If a term has a parent, this variable gives the term number of that parent. • If a term does not have a parent, this value is a "." (period). • If the values of Key, Parent, and Parent_id are identical, the parent occurs as itself. • If the values of Parent and Parent_id are identical but differ from Key, the observation is a child.
Parent_id	Another description of the term's parent: Parent gives the parent's term number if a term is a child, but Parent_id gives this value for all terms
_ispar	An indication of term's status as a parent, child, or neither: • A "+" (plus sign) indicates that the term is a parent. • A "." (period) indicates that the term is a child. • A missing value indicates that the term is neither a parent nor a child
Weight	The weights of the terms

Displayed Output

The following sections describe the output that PROC HPTMINE produces. The output is organized into various tables, which are discussed in the order of appearance.

Performance Information

The "Performance Information" table is produced by default; it displays information about the grid host for distributed execution and information about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of computing nodes and threads are also displayed, depending on the environment.

Procedure Task Timing

When the DETAILS option is specified in the PERFORMANCE statement, PROC HPTMINE produces a "Procedure Task Timing" table, which displays the elapsed time (absolute and relative) for the main tasks.

ODS Table Names

Each table created by the HPTMINE procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 26.8.

Table 26.8 ODS Tables Produced by PROC HPTMINE

Table Name	Description	Required Statement / Option
PerformanceInfo	Information about the high-performance computing environment	Default output
Timing	Absolute and relative times for tasks performed by the procedure	DETAILS option in the PERFORMANCE statement

Configuration for Distributed Mode

When PROC HPTMINE runs in distributed mode, it needs to locate on the grid the language binary files that are used in parsing text. You can use the GRID_TEXTANALYTICS_BIN_LOC macro to tell the HPTMINE procedure where to find these binary files. Assume that the grid administrator has copied the language binary files to a directory named **/rdstore/tktg/misc**, which is accessible to all nodes of the gird. You can insert the following statement before the statements that call the HPTMINE procedure to tell it the location of the binary files:

```
%let GRID_TEXTANALYTICS_BIN_LOC=/global_dir/tktg/misc;
```

To optimize resources and performance, the grid administrator must decide between using a shared location to store the binary resource files or placing a copy of the resource files on each node. The binary files are very large, and a shared location takes up less space to store them. However, using a shared location

means that the files need to be distributed to the grid when PROC HPTMINE runs, and this can be time consuming. On the other hand, placing copies of the files on each node and using a relative pathname for the GRID_TEXTANALYTICS_BIN_LOC macro variable ensures optimal performance. For example, the grid administrator can create a directory with the path **/local_dir/tktg/misc** on each node and store the binary files in this directory. When the following statement is specified, the HPTMINE procedure goes to the directory **/local_dir/tktg/misc** on each node to load the binary files:

```
%let GRID_TEXTANALYTICS_BIN_LOC=/local_dir/tktg/misc;
```

Examples: HPTMINE Procedure

Example 26.1: Parsing with No Options Turned On

This example parses five documents, which are in a generated data set. The following DATA step generates the five documents:

```
/* 1)  create data set */

data CarNominations;
infile cards delimiter='|' missover;
length text $70 ;
input text$ i;
cards;
    The Ford Taurus is the World Car of the Year. |1
    Hyundai won the award last year. |2
    Toyota sold the Toyota Tacoma in bright green. |3
    The Ford Taurus is sold in all colors except for lime green. |4
    The Honda Insight was World Car of the Year in 2008. |5
    ;
run;
```

The following statements run PROC HPTMINE to parse the documents. Because no host for distributed computing is specified and the NODES option is not specified in the PERFORMANCE statement, PROC HPTMINE runs automatically in soloist mode.

```
/* 2) starting code */
proc hptmine data=work.CarNominations;
doc_id i;
var text;
parse
    nostemming notagging nonoungroups
    termwgt        = none
    cellwgt        = none
    reducef        = 0
    entities       = none
    outparent      = outparent
    outterms       = outterms
    outchild       = outchild
```

```
    outconfig      = outconfig
    ;
performance details;
run;

/* 3) print outterms data set */
proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.1.1 shows the content of the outterms data set. In this example, none of the following parsing options are turned on: stemming, part-of-speech tagging, noun group extraction, entity identification, term and cell weighting, and term filtering. No synonym list, multiterms word list, or stop list is specified. As a result of this configuration, there is no child term in the outterms data set. Also the outparent data set and the outchild data set are exactly the same. The HPTMINE procedure automatically drops punctuation and numbers. For example, in the outterms data set the "." (period) term has a "keep" value of "N".

Output 26.1.1 The outterms Data Set

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id	_ispar	Weight
1	.	Punct	5	1	N	27	.	27			1
2	all	Alpha	1	1	Y	1	.	1			1
3	toyota	Alpha	2	1	Y	2	.	2			1
4	ford	Alpha	2	1	Y	3	.	3			1
5	tacoma	Alpha	1	1	Y	4	.	4			1
6	year	Alpha	3	1	Y	5	.	5			1
7	taurus	Alpha	2	1	Y	6	.	6			1
8	won	Alpha	1	1	Y	7	.	7			1
9	honda	Alpha	1	1	Y	8	.	8			1
10	bright	Alpha	1	1	Y	9	.	9			1
11	sold	Alpha	2	1	Y	10	.	10			1
12	colors	Alpha	1	1	Y	11	.	11			1
13	lime	Alpha	1	1	Y	12	.	12			1
14	except	Alpha	1	1	Y	13	.	13			1
15	hyundai	Alpha	1	1	Y	14	.	14			1
16	in	Alpha	3	1	Y	15	.	15			1
17	is	Alpha	2	1	Y	16	.	16			1
18	for	Alpha	1	1	Y	17	.	17			1
19	world	Alpha	2	1	Y	18	.	18			1
20	green	Alpha	2	1	Y	19	.	19			1
21	the	Alpha	8	1	Y	20	.	20			1
22	of	Alpha	2	1	Y	21	.	21			1
23	award	Alpha	1	1	Y	22	.	22			1
24	was	Alpha	1	1	Y	23	.	23			1
25	2008	Num	1	1	N	28	.	28			1
26	car	Alpha	2	1	Y	24	.	24			1
27	insight	Alpha	1	1	Y	25	.	25			1
28	last	Alpha	1	1	Y	26	.	26			1

Example 26.2: Parsing with Stemming Turned On

This example uses the data set that is generated in Example 26.1. The following statements run PROC HPTMINE to parse the documents. Because the NOSTEMMING option is not specified in the PARSE statement, words are stemmed (the default).

```
proc hptmine data=work.CarNominations;
doc_id i;
var text;
parse
    notagging nonoungroups
    termwgt  = none
    cellwgt  = none
    reducef  = 0
    entities = none

    outparent= outparent
    outterms = outterms
    outchild = outchild
    outconfig= outconfig
    ;
performance details;
run;

proc print data = outterms; title "OUTTERMS Data Set"; run;
```

Output 26.2.1 shows the content of the outterms data set. In this example, words are stemmed. You can see that the term "sold" now stems to have a parent term "sell." Also the outparent data set and the outchild data set are different. The parent term "sell" shows up in outparent (key=11), but not the child term "sold" (key=26). Only "sold" appears in the outchild data set, and "sell" does not appear.

Output 26.2.1 The outterms Data Set with Stemming

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id	_ispar	Weight
1	.	Punct	5	1	N	30	.	30			1
2	all	Alpha	1	1	Y	1	.	1			1
3	toyota	Alpha	2	1	Y	2	.	2			1
4	ford	Alpha	2	1	Y	3	.	3			1
5	tacoma	Alpha	1	1	Y	4	.	4			1
6	year	Alpha	3	1	Y	5	.	5			1
7	taurus	Alpha	2	1	Y	6	.	6			1
8	won	Alpha	1	1	Y	7	.	7			1
9	honda	Alpha	1	1	Y	8	.	8			1
10	bright	Alpha	1	1	Y	9	.	9			1
11	be	Alpha	3	1	Y	10	10	10		+	1
12	sold	Alpha	2	1	Y	26	11	11		.	1
13	sell	Alpha	2	1	Y	11	11	11		+	1
14	colors	Alpha	1	1	Y	27	23	23		.	1
15	lime	Alpha	1	1	Y	12	.	12			1
16	except	Alpha	1	1	Y	13	.	13			1
17	hyundai	Alpha	1	1	Y	14	.	14			1
18	in	Alpha	3	1	Y	15	.	15			1
19	is	Alpha	2	1	Y	28	10	10		.	1
20	for	Alpha	1	1	Y	16	.	16			1
21	world	Alpha	2	1	Y	17	.	17			1
22	green	Alpha	2	1	Y	18	.	18			1
23	the	Alpha	8	1	Y	19	.	19			1
24	of	Alpha	2	1	Y	20	.	20			1
25	award	Alpha	1	1	Y	21	.	21			1
26	was	Alpha	1	1	Y	29	10	10		.	1
27	2008	Num	1	1	N	31	.	31			1
28	car	Alpha	2	1	Y	22	.	22			1
29	color	Alpha	1	1	Y	23	23	23		+	1
30	insight	Alpha	1	1	Y	24	.	24			1
31	last	Alpha	1	1	Y	25	.	25			1

Example 26.3: Adding Entities and Noun Groups

This example uses the data set that is generated in Example 26.1. The following statements run PROC HPTMINE to parse the documents. Because the NONOUNGROUP option is not specified in the PARSE statement, noun group extraction is turned on, and because the ENTITIES option is not specified, entity identification is turned on.

```
proc hptmine data=work.CarNominations;
doc_id i;
var text;
PARSE
    notagging
    termwgt   = none
    cellwgt   = none
    reducef   = 0
    entities  = std
    outparent = outparent
    outterms  = outterms
    outchild  = outchild
    outconfig = outconfig
    ;
performance details;
run;

proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.3.1 shows the content of the outterms data set. Compared to Output 26.2.1, the outterms data set is longer, because it contains entities and noun groups. For example, “honda insight” is included in the outterms data set as an entity with Role=Vehicle, and “bright green” is also included in the outterms data set as a Noun_Group.

Output 26.3.1 The outterms Data Set with Noun Group Extraction and Entity Identification

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id
1	lime green	NOUN_GROUP	Alpha	1	1	Y	1	.	1
2	.		Punct	5	1	N	37	.	37
3	all		Alpha	1	1	Y	2	.	2
4	toyota		Alpha	1	1	Y	3	.	3
5	ford		Alpha	2	1	Y	4	.	4
6	toyota tacoma	VEHICLE	Entity	1	1	Y	5	.	5
7	tacoma		Alpha	1	1	Y	6	.	6
8	year		Alpha	3	1	Y	7	.	7
9	taurus		Alpha	2	1	Y	8	.	8
10	won		Alpha	1	1	Y	9	.	9
11	honda		Alpha	1	1	Y	10	.	10
12	bright		Alpha	1	1	Y	11	.	11
13	be		Alpha	3	1	Y	12	12	12
14	sold		Alpha	2	1	Y	33	15	15
15	bright green	NOUN_GROUP	Alpha	1	1	Y	13	.	13
16	ford taurus	VEHICLE	Entity	2	1	Y	14	.	14
17	sell		Alpha	2	1	Y	15	15	15
18	hyundai	COMPANY	Entity	1	1	Y	16	.	16
19	colors		Alpha	1	1	Y	34	30	30
20	lime		Alpha	1	1	Y	17	.	17
21	except		Alpha	1	1	Y	18	.	18
22	honda insight	VEHICLE	Entity	1	1	Y	19	.	19
23	in		Alpha	3	1	Y	20	.	20
24	is		Alpha	2	1	Y	35	12	12
25	for		Alpha	1	1	Y	21	.	21
26	toyota	COMPANY	Entity	1	1	Y	22	.	22
27	world		Alpha	2	1	Y	23	.	23
28	green		Alpha	2	1	Y	24	.	24
29	the		Alpha	8	1	Y	25	.	25
30	of		Alpha	2	1	Y	26	.	26
31	world car	PROP_MISC	Entity	2	1	Y	27	.	27
32	award		Alpha	1	1	Y	28	.	28
33	was		Alpha	1	1	Y	36	12	12
34	2008		Num	1	1	N	38	.	38
35	car		Alpha	2	1	Y	29	.	29
36	color		Alpha	1	1	Y	30	30	30
37	insight		Alpha	1	1	Y	31	.	31
38	last		Alpha	1	1	Y	32	.	32

Example 26.4: Adding Part-of-Speech Tagging

This example uses the data set that is generated in Example 26.1. The following statements run PROC HPTMINE to parse the documents. Because the NOTAGGING option is not specified in the PARSE statement, PROC HPTMINE uses context clues to determine a term's part of speech.

```
proc hptmine data=work.CarNominations;
doc_id i;
var text;
PARSE
    termwgt   = none
    cellwgt   = none
    reducef   = 0
    entities  = std
    outparent = outparent
    outterms  = outterms
    outchild  = outchild
    outconfig = outconfig
    ;
performance details;
run;

proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.4.1 shows the content of the outterms data set. Compared to Output 26.3.1, the outterms data set also contains the part-of-speech tag for the terms.

Output 26.4.1 The outterms Data Set with Part-of-Speech Tagging

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id
1	car	Prop	Alpha	1	1	Y	1	.	1
2	lime green	NOUN_GROUP	Alpha	1	1	Y	2	.	2
3	last	Adj	Alpha	1	1	Y	3	.	3
4	lime	Adj	Alpha	1	1	Y	4	.	4
5	sell	Verb	Alpha	2	1	Y	5	5	5
6	won	Noun	Alpha	1	1	Y	6	.	6
7	toyota tacoma	VEHICLE	Entity	1	1	Y	7	.	7
8	bright	Adj	Alpha	1	1	Y	8	.	8
9	honda	Prop	Alpha	1	1	Y	9	.	9
10	sold	Verb	Alpha	2	1	Y	34	5	5
11	colors	Noun	Alpha	1	1	Y	35	12	12
12	for	Prep	Alpha	1	1	Y	10	.	10
13	award	Verb	Alpha	1	1	Y	11	.	11
14	color	Noun	Alpha	1	1	Y	12	12	12
15	2008	Num	Num	1	1	N	38	.	38
16	bright green	NOUN_GROUP	Alpha	1	1	Y	13	.	13
17	the	Det	Alpha	8	1	Y	14	.	14
18	is	Verb	Alpha	2	1	Y	36	26	26
19	ford taurus	VEHICLE	Entity	2	1	Y	15	.	15
20	hyundai	COMPANY	Entity	1	1	Y	16	.	16
21	toyota	Prop	Alpha	1	1	Y	17	.	17
22	car	Noun	Alpha	1	1	Y	18	.	18
23	except	Verb	Alpha	1	1	Y	19	.	19
24	in	Prep	Alpha	3	1	Y	20	.	20
25	was	Verb	Alpha	1	1	Y	37	26	26
26	honda insight	VEHICLE	Entity	1	1	Y	21	.	21
27	insight	Noun	Alpha	1	1	Y	22	.	22
28	ford	Prop	Alpha	2	1	Y	23	.	23
29	world	Prop	Alpha	2	1	Y	24	.	24
30	.	Punct	Punct	5	1	N	39	.	39
31	year	Noun	Alpha	3	1	Y	25	.	25
32	be	Verb	Alpha	3	1	Y	26	26	26
33	all	Adj	Alpha	1	1	Y	27	.	27
34	toyota	COMPANY	Entity	1	1	Y	28	.	28
35	taurus	Noun	Alpha	2	1	Y	29	.	29
36	world car	PROP_MISC	Entity	2	1	Y	30	.	30
37	of	Prep	Alpha	2	1	Y	31	.	31
38	tacoma	Prop	Alpha	1	1	Y	32	.	32
39	green	Noun	Alpha	2	1	Y	33	.	33

Example 26.5: Adding Synonyms

This example uses the data set that is generated in Example 26.1. So far, by looking at the outterms data sets generated by Example 26.1 to Example 26.4, you can see that the data are very "vehicle focused." But suppose what you really care about are the Companies. You can use a synonym list in parsing to map each vehicle to the company that produces it. The following statements show this mapping.

```
data synds;
infile cards delimiter=',';
length TERM $13;
input TERM $ TERMROLE $ PARENT $ parentrole$;
cards;
    honda insight, VEHICLE , honda,  COMPANY,
    ford taurus,   VEHICLE,  ford,   COMPANY,
    toyota tacoma, VEHICLE,  toyota, COMPANY,
;
run;

proc hptmine data=work.CarNominations;
doc_id i;
var text;
parse
    termwgt   = none
    cellwgt   = none
    reducef   = 0
    entities  = std
    synonym   = synds
    outparent = outparent
    outterms  = outterms
    outchild  = outchild
    outconfig = outconfig
    ;
PERFORMANCE details;
RUN;

proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.5.1 shows the content of the outterms data set. You can see that the term "honda insight" (key=39) is assigned the parent term "honda" (key=5). Only the term "honda" appears in the outparent data set.

Output 26.5.1 The outterms Data Set with Synonym Mapping

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id
1	car	Prop	Alpha	1	1	Y	1	.	1
2	lime green	NOUN_GROUP	Alpha	1	1	Y	2	.	2
3	last	Adj	Alpha	1	1	Y	3	.	3
4	lime	Adj	Alpha	1	1	Y	4	.	4
5	honda	COMPANY	Entity	1	1	Y	5	5	5
6	sell	Verb	Alpha	2	1	Y	6	6	6
7	won	Noun	Alpha	1	1	Y	7	.	7
8	toyota tacoma	VEHICLE	Entity	1	1	Y	33	26	26
9	bright	Adj	Alpha	1	1	Y	8	.	8
10	honda	Prop	Alpha	1	1	Y	9	.	9
11	sold	Verb	Alpha	2	1	Y	34	6	6
12	colors	Noun	Alpha	1	1	Y	35	12	12
13	for	Prep	Alpha	1	1	Y	10	.	10
14	award	Verb	Alpha	1	1	Y	11	.	11
15	color	Noun	Alpha	1	1	Y	12	12	12
16	2008	Num	Num	1	1	N	40	.	40
17	bright green	NOUN_GROUP	Alpha	1	1	Y	13	.	13
18	the	Det	Alpha	8	1	Y	14	.	14
19	is	Verb	Alpha	2	1	Y	36	24	24
20	ford taurus	VEHICLE	Entity	2	1	Y	37	27	27
21	hyundai	COMPANY	Entity	1	1	Y	15	.	15
22	toyota	Prop	Alpha	1	1	Y	16	.	16
23	car	Noun	Alpha	1	1	Y	17	.	17
24	except	Verb	Alpha	1	1	Y	18	.	18
25	in	Prep	Alpha	3	1	Y	19	.	19
26	was	Verb	Alpha	1	1	Y	38	24	24
27	honda insight	VEHICLE	Entity	1	1	Y	39	5	5
28	insight	Noun	Alpha	1	1	Y	20	.	20
29	ford	Prop	Alpha	2	1	Y	21	.	21
30	world	Prop	Alpha	2	1	Y	22	.	22
31	.	Punct	Punct	5	1	N	41	.	41
32	year	Noun	Alpha	3	1	Y	23	.	23
33	be	Verb	Alpha	3	1	Y	24	24	24
34	all	Adj	Alpha	1	1	Y	25	.	25
35	toyota	COMPANY	Entity	2	1	Y	26	26	26
36	toyota	COMPANY	Entity	1	1	Y	26	.	26
37	ford	COMPANY	Entity	2	1	Y	27	27	27
38	taurus	Noun	Alpha	2	1	Y	28	.	28
39	world car	PROP_MISC	Entity	2	1	Y	29	.	29
40	of	Prep	Alpha	2	1	Y	30	.	30
41	tacoma	Prop	Alpha	1	1	Y	31	.	31
42	green	Noun	Alpha	2	1	Y	32	.	32

Example 26.6: Adding a Stop List

This example uses the data set that is generated in Example 26.1. If you want to eliminate TOYOTA from the analysis, you can enter the parent term "Toyota" with role=COMPANY in a stop list. When this stop list is an input, PROC HPTMIME drops the term "Toyota" (role=COMPANY) and all its children terms in the outterms data set by marking Keep=N for these terms.

```
data synds;
infile cards delimiter=',';
length TERM $13;
input TERM $ TERMROLE $ PARENT $ parentrole$;
cards;
    honda insight, VEHICLE , honda,  COMPANY,
    ford taurus,   VEHICLE,  ford,   COMPANY,
    toyota tacoma, VEHICLE,  toyota, COMPANY,
;
run;

/* create stop list*/
data stopList;
infile cards delimiter='|' missover;
length term $25 role $40;
input term$ role$ ;
    cards;
        toyota| COMPANY
    ;
run;

proc hptmine data=work.CarNominations;
doc_id i;
var text;
parse
    termwgt    = none
    cellwgt    = none
    reducef    = 0
    entities   = std
    synonym    = synds
    stop       = stopList
    outparent  = outparent
    outterms   = outterms
    outchild   = outchild
    outconfig  = outconfig
    ;
performance details;
run;

proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.6.1 shows the content of the outterms data set. You can see that the term "Toyota" (key=40) and the term "Toyota Tacoma" (key=41) are assigned Keep=N. The outparent data set is shorter than the one generated in Example 26.5.

Output 26.6.1 The outterms Data Set Filtered Using Stop List

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id
1	car	Prop	Alpha	1	1	Y	1	.	1
2	lime green	NOUN_GROUP	Alpha	1	1	Y	2	.	2
3	last	Adj	Alpha	1	1	Y	3	.	3
4	lime	Adj	Alpha	1	1	Y	4	.	4
5	honda	COMPANY	Entity	1	1	Y	5	5	5
6	sell	Verb	Alpha	2	1	Y	6	6	6
7	won	Noun	Alpha	1	1	Y	7	.	7
8	toyota tacoma	VEHICLE	Entity	1	1	N	41	40	40
9	bright	Adj	Alpha	1	1	Y	8	.	8
10	honda	Prop	Alpha	1	1	Y	9	.	9
11	sold	Verb	Alpha	2	1	Y	31	6	6
12	colors	Noun	Alpha	1	1	Y	32	12	12
13	for	Prep	Alpha	1	1	Y	10	.	10
14	award	Verb	Alpha	1	1	Y	11	.	11
15	color	Noun	Alpha	1	1	Y	12	12	12
16	2008	Num	Num	1	1	N	37	.	37
17	bright green	NOUN_GROUP	Alpha	1	1	Y	13	.	13
18	the	Det	Alpha	8	1	Y	14	.	14
19	is	Verb	Alpha	2	1	Y	33	23	23
20	ford taurus	VEHICLE	Entity	2	1	Y	34	25	25
21	hyundai	COMPANY	Entity	1	1	Y	15	.	15
22	toyota	Prop	Alpha	1	1	N	38	.	38
23	car	Noun	Alpha	1	1	Y	16	.	16
24	except	Verb	Alpha	1	1	Y	17	.	17
25	in	Prep	Alpha	3	1	Y	18	.	18
26	was	Verb	Alpha	1	1	Y	35	23	23
27	honda insight	VEHICLE	Entity	1	1	Y	36	5	5
28	insight	Noun	Alpha	1	1	Y	19	.	19
29	ford	Prop	Alpha	2	1	Y	20	.	20
30	world	Prop	Alpha	2	1	Y	21	.	21
31	.	Punct	Punct	5	1	N	39	.	39
32	year	Noun	Alpha	3	1	Y	22	.	22
33	be	Verb	Alpha	3	1	Y	23	23	23
34	all	Adj	Alpha	1	1	Y	24	.	24
35	toyota	COMPANY	Entity	2	1	N	40	40	40
36	toyota	COMPANY	Entity	1	1	N	40	.	40
37	ford	COMPANY	Entity	2	1	Y	25	25	25
38	taurus	Noun	Alpha	2	1	Y	26	.	26
39	world car	PROP_MISC	Entity	2	1	Y	27	.	27
40	of	Prep	Alpha	2	1	Y	28	.	28
41	tacoma	Prop	Alpha	1	1	Y	29	.	29
42	green	Noun	Alpha	2	1	Y	30	.	30

Example 26.7: Adding a Multiterm List

A multiterm list can be used to define words with multiple terms. This example uses the data set that is generated in Example 26.1 to show how to use MULTITERM option.

```
data synds;
infile cards delimiter=',';
length TERM $13;
input TERM $ TERMROLE $ PARENT $ parentrole$;
cards;
    honda insight, VEHICLE , honda,  COMPANY,
    ford taurus,   VEHICLE,  ford,   COMPANY,
    toyota tacoma, VEHICLE,  toyota, COMPANY,
;
run;

data stopList;
infile cards delimiter='|' missover;
length term $25 role $40;
input term$ role$ ;
    cards;
        toyota| COMPANY
    ;
run;

/* create multiterms list*/
data _null_ ;
    FILE  'encomp.txt' ;
    PUT 'except for :3:Prep';
run ;

proc hptmine data=work.CarNominations;
doc_id i;
var text;
parse
    termwgt    = none
    cellwgt    = none
    reducef    = 0
    entities   = std
    synonym    = synds
    stop       = stopList
    multiterm  ="encomp.txt"
    outparent  = outparent
    outterms   = outterms
    outchild   = outchild
    outconfig  = outconfig
    ;
performance details;
run;

proc print data=outterms; title "OUTTERMS Data Set"; run;
```

Output 26.7.1 shows the content of the outterms data set. In the preceding statements, "except for" is defined as an individual term. In the outterms data set, you can see that the two terms "except" and "for" have become one term, "except for."

Output 26.7.1 The outterms Data Set

Obs	Term	Role	Attribute	Freq	numdocs	_keep	Key	Parent	Parent_id
1	car	Prop	Alpha	1	1	Y	1	.	1
2	lime green	NOUN_GROUP	Alpha	1	1	Y	2	.	2
3	last	Adj	Alpha	1	1	Y	3	.	3
4	lime	Adj	Alpha	1	1	Y	4	.	4
5	honda	COMPANY	Entity	1	1	Y	5	5	5
6	sell	Verb	Alpha	2	1	Y	6	6	6
7	won	Noun	Alpha	1	1	Y	7	.	7
8	toyota tacoma	VEHICLE	Entity	1	1	N	40	39	39
9	bright	Adj	Alpha	1	1	Y	8	.	8
10	honda	Prop	Alpha	1	1	Y	9	.	9
11	sold	Verb	Alpha	2	1	Y	30	6	6
12	colors	Noun	Alpha	1	1	Y	31	12	12
13	award	Verb	Alpha	1	1	Y	10	.	10
14	except for	Pre	Entity	1	1	Y	11	.	11
15	color	Noun	Alpha	1	1	Y	12	12	12
16	2008	Num	Num	1	1	N	36	.	36
17	bright green	NOUN_GROUP	Alpha	1	1	Y	13	.	13
18	the	Det	Alpha	8	1	Y	14	.	14
19	is	Verb	Alpha	2	1	Y	32	22	22
20	ford taurus	VEHICLE	Entity	2	1	Y	33	24	24
21	hyundai	COMPANY	Entity	1	1	Y	15	.	15
22	toyota	Prop	Alpha	1	1	N	37	.	37
23	car	Noun	Alpha	1	1	Y	16	.	16
24	in	Prep	Alpha	3	1	Y	17	.	17
25	was	Verb	Alpha	1	1	Y	34	22	22
26	honda insight	VEHICLE	Entity	1	1	Y	35	5	5
27	insight	Noun	Alpha	1	1	Y	18	.	18
28	ford	Prop	Alpha	2	1	Y	19	.	19
29	world	Prop	Alpha	2	1	Y	20	.	20
30	.	Punct	Punct	5	1	N	38	.	38
31	year	Noun	Alpha	3	1	Y	21	.	21
32	be	Verb	Alpha	3	1	Y	22	22	22
33	all	Adj	Alpha	1	1	Y	23	.	23
34	toyota	COMPANY	Entity	2	1	N	39	39	39
35	toyota	COMPANY	Entity	1	1	N	39	.	39
36	ford	COMPANY	Entity	2	1	Y	24	24	24
37	taurus	Noun	Alpha	2	1	Y	25	.	25
38	world car	PROP_MISC	Entity	2	1	Y	26	.	26
39	of	Prep	Alpha	2	1	Y	27	.	27
40	tacoma	Prop	Alpha	1	1	Y	28	.	28
41	green	Noun	Alpha	2	1	Y	29	.	29

Example 26.8: Running in Distributed Mode

This example uses the data set that is generated in the section "Getting Started: HPTMINE Procedure" on page 749. When a host for distributed computing is specified and the NODES option in the PERFORMANCE statement is specified, PROC HPTMINE uses the specified host for computing and runs in distributed mode.

```
%let GRID_TEXTANALYTICS_BIN_LOC=&GRIDTXTBIN;

option set=GRIDHOST="&GRIDHOST";
option set=GRIDINSTALLLOC="&GRIDINSTALLLOC";

proc hptmine data=getstart;
doc_id      did;
variable    text;
parse
            outterms  = terms
            reducef   = 2;
svd
            k         = 10
            outdocpro = docpro;
performance nodes=2 details;
run;
```

In the preceding statements, the macro variable GRID_TEXTANALYTICS_BIN_LOC specifies the location on the grid where the language binary files are installed. These files are used by the HPTMINE procedure in parsing text.

Chapter 27
The HPTMSCORE Procedure (Experimental)

Contents

Overview: HPTMSCORE Procedure **785**
PROC HPTMSCORE Features 785
PROC HPTMSCORE Contrasted with Other SAS Procedures 786
Getting Started: HPTMSCORE Procedure **786**
Syntax: HPTMSCORE Procedure **789**
PROC HPTMSCORE Statement 790
DOC_ID Statement 791
PERFORMANCE Statement 791
VARIABLE Statement 792
Details: HPTMSCORE Procedure **792**
Displayed Output 792
Performance Information 792
Procedure Task Timing 792
ODS Table Names 792
Configuration for Distributed Mode 793

Overview: HPTMSCORE Procedure

For high-performance text mining, scoring is the process of applying the parsing and SVD projections to new textual data. The HPTMSCORE procedure performs this scoring of new documents, and its primary output is a document data set Outdocpro, which holds the reduced dimensional representation of the score collection. PROC HPTMSCORE uses some of the output data sets of the HPTMINE procedure as input data to ensure consistency between scoring and training. During scoring, the new textual data must be parsed with the same settings that the training data were parsed with, indexed using only the subset of terms that were used during training, and projected onto the reduced dimensional subspace of the singular value decomposition that was derived from the training data. The three data sets, Outconfig, Outterms and Svdu, which were created with PROC HPTMINE facilitate this process and serve as input to PROC HPTMSCORE with the CONFIG=, TERMS=, and SVDU= options, respectively. The purpose of these three data sets are summarized below under their respective options.

PROC HPTMSCORE Features

The HPTMSCORE procedure processes large-scale textual data in parallel to achieve efficiency and scalability. The following list summarizes the basic features of PROC HPTMSCORE:

- Functionalities related to document parsing, term-by-document matrix creation, and dimension reduction are integrated into one procedure to process data more efficiently.
- Parsing and term-by-document matrix creation are performed in parallel.
- Computation of document projection is performed in parallel.
- Analysis can be performed on a massively parallel SAS high-performance appliance.
- All phases of processing make use of a high degree of multithreading.
- Input data can be read in parallel when the data source is the appliance database.

PROC HPTMSCORE Contrasted with Other SAS Procedures

The high-performance PROC HPTMSCORE functionality replaces what has in the past been done by using the DATA step function TGSCORE and following this with a call to the SPSVD procedure. The TGSCORE function was used to parse each document and to append each document's term counts to an Outparent data set. After this had been applied to all the score documents, then PROC SPSVD applied the document projections. PROC HPTMSCORE combines these aspects into a single parallel procedure. For PROC HPTMSCORE, you provide the necessary inputs to perform the parsing, term-by-document table creation, and document projections in a single call. The primary output data set of PROC HPTMSCORE contains the document projections and is specified in the SVDDOCPRO= option.

Getting Started: HPTMSCORE Procedure

The following DATA steps generate two data sets. The getstart data set contains 36 observations, and the getstart_score data set contains 31 observations. Both data sets have two variables. The text variable contains the input documents, and the did variable contains the ID of the documents. Each row in the data sets represents a "document" for analysis.

```
data getstart;
    infile cards delimiter='|' missover;
    length text $150;
    input text$ did$;
    cards;
        High-performance analytics hold the key to |d01
        unlocking the unprecedented business value of big data.|d02
        Organizations looking for optimal ways to gain insights|d03
        from big data in shorter reporting windows are turning to SAS.|d04
        As the gold-standard leader in business analytics |d05
        for more than 36 years,|d06
        SAS frees enterprises from the limitations of |d07
        traditional computing and enables them |d08
        to draw instant benefits from big data.|d09
        Faster Time to Insight.|d10
        From banking to retail to health care to insurance, |d11
```

```
        SAS is helping industries glean insights from data |d12
        that once took days or weeks in just hours, minutes or seconds.|d13
        It's all about getting to and analyzing relevant data faster.|d14
        Revealing previously unseen patterns, sentiments and relationships.|d15
        Identifying unknown risks.|d16
        And speeding the time to insights.|d17
        High-Performance Analytics from SAS Combining industry-leading |d18
        analytics software with high-performance computing technologies|d19
        produces fast and precise answers to unsolvable problems|d20
        and enables our customers to gain greater competitive advantage.|d21
        SAS In-Memory Analytics eliminate the need for disk-based processing|d22
        allowing for much faster analysis.|d23
        SAS In-Database executes analytic logic into the database itself |d24
        for improved agility and governance.|d25
        SAS Grid Computing creates a centrally managed,|d26
        shared environment for processing large jobs|d27
        and supporting a growing number of users efficiently.|d28
        Together, the components of this integrated, |d29
        supercharged platform are changing the decision-making landscape|d30
        and redefining how the world solves big data business problems.|d31
        Big data is a popular term used to describe the exponential growth,|d32
        availability and use of information,|d33
        both structured and unstructured.|d34
        Much has been written on the big data trend and how it can |d35
        serve as the basis for innovation, differentiation and growth.|d36
run;

data getstart_score;
    infile cards delimiter='|' missover;
    length text $150;
    input text$ did$;
    cards;
        Big data according to SAS|d1
        At SAS, we consider two other dimensions|d2
        when thinking about big data:|d3
        Variability. In addition to the|d4
        increasing velocities and varieties of data, data|d5
        flows can be highly inconsistent with periodic peaks.|d6
        Is something big trending in the social media?|d7
        Perhaps there is a high-profile IPO looming.|d8
        Maybe swimming with pigs in the Bahamas is suddenly|d9
        the must-do vacation activity. Daily, seasonal and|d10
        event-triggered peak data loads can be challenging|d11
        to manage - especially with social media involved.|d12
        Complexity. When you deal with huge volumes of data,|d13
        it comes from multiple sources. It is quite an|d14
        undertaking to link, match, cleanse and|d15
        transform data across systems. However,|d16
        it is necessary to connect and correlate|d17
        relationships, hierarchies and multiple data|d18
        linkages or your data can quickly spiral out of|d19
        control. Data governance can help you determine|d20
        how disparate data relates to common definitions|d21
        and how to systematically integrate structured|d22
```

```
        and unstructured data assets to produce|d23
        high-quality information that is useful,|d24
        appropriate and up-to-date.|d25
        Ultimately, regardless of the factors involved,|d26
        we believe that the term big data is relative|d27
        it applies (per Gartner's assessment)|d28
        whenever an organization's ability|d29
        to handle, store and analyze data|d30
        exceeds its current capacity.|d31
run;
```

The following statements use PROC HPTMINE for processing the input text data set getstart and create three data sets, outconfig, outterms and svdu, which can be used in PROC HPTMSCORE for scoring. The statements then use PROC HPTMSCORE to score the input text data set getstart_score. The statements take the three data sets generated by PROC HPTMINE as input and create a SAS data set named docpro, which contains the projection of the documents in the input data set getstart_score.

```
proc hptmine data     = getstart;
doc_id      did;
variable    text;
parse
            outterms  = outterms
            outconfig = outconfig
            reducef   = 2;
svd
            k         = 10
            svdu      = svdu;
performance details;
run;

proc hptmscore
            data      = getstart_score
            terms     = outterms
            config    = outconfig
            svdu      = svdu
            svddocpro = docpro;
doc_id      did;
variable    text;
performance details;
run;
```

The output from this analysis is presented in Figure 27.1 through Figure 27.3.

Figure 27.1 shows the "Performance Information" table, which indicates that PROC HPTMSCORE executes in client mode. That is, PROC HPTMSCORE runs on the machine where the SAS system is running. The table also shows that two threads are used for computing.

Figure 27.1 Performance Information

```
Performance Information

Execution Mode       On client
Number of Threads    2
```

Figure 27.2 shows the "Procedure Task Timing" table, which provides details about how much time is used by each processing step.

Figure 27.2 Procedure Task Timing

Procedure Task Timing

Task	Time (sec.)	
Parse documents	0.71	96.7%
Generate term-document matrix	0.01	1.65%
Compute SVD	0.01	1.34%
Output OUTDOCPRO table	0.00	0.30%

The following statements use PROC PRINT to show the content of the first 10 rows of the docpro data set that is generated by the HPTMSCORE procedure.

```
proc print data = docpro (obs=10) round; run;
```

Figure 27.3 shows the output of PROC PRINT. For more information about the output of the OUTDOCPRO= option, see the description of the SVDDOCPRO= option.

Figure 27.3 The DOCPRO Data Set

Obs	did	COL1	COL2	COL3	COL4	COL5	COL6	COL7	COL8	COL9	COL10
1	d1	0.90	0.09	-0.01	0.37	0.06	-0.13	-0.14	-0.03	-0.03	-0.04
2	d2	0.29	-0.84	0.14	0.36	0.12	0.10	0.11	-0.10	-0.09	0.08
3	d3	0.82	0.36	0.20	0.27	0.08	-0.17	-0.06	-0.12	0.05	-0.18
4	d4	0.50	-0.38	0.13	-0.21	0.00	-0.27	-0.36	0.47	0.14	0.32
5	d5	0.69	-0.12	0.11	-0.01	0.12	-0.04	0.21	-0.34	-0.54	0.19
6	d6	0.27	-0.62	0.01	0.01	0.32	-0.28	0.54	-0.10	0.07	-0.24
7	d7	0.67	-0.48	0.26	-0.02	0.14	-0.37	0.21	0.14	0.16	-0.04
8	d8	0.35	-0.10	-0.26	0.16	-0.21	-0.49	0.64	-0.25	-0.11	0.00
9	d9	0.49	-0.64	0.18	-0.07	0.13	-0.39	0.26	0.19	0.19	0.04
10	d10	0.36	-0.68	0.20	-0.32	0.27	0.05	0.33	-0.24	-0.06	-0.15

Syntax: HPTMSCORE Procedure

The following statements are available in the HPTMSCORE procedure:

PROC HPTMSCORE < *options* > ;
  VARIABLE *variable* ;
  DOC_ID *variable* ;
  PERFORMANCE *performance-options* ;

PROC HPTMSCORE Statement

PROC HPTMSCORE < *options* > **;**

The PROC HPTMSCORE statement invokes the procedure. Table 27.1 summarizes the *options* in the statement by function. The *options* are then described fully in alphabetical order.

Table 27.1 PROC HPTMSCORE Statement Options

option	**Description**
Basic Options	
DATA | DOC=	Specifies the input document data set
TERMS=	Specifies the data set that contains the summary information about the terms that are to be used for scoring
CONFIG=	Specifies the data set that contains the option settings that are to be used for scoring
SVDU=	Specifies the data set that contains the U matrix whose columns are the left singular vectors
Output Options	
NOPRINT	Suppresses ODS output
OUTPARENT=	Specifies the term-by-document frequency matrix used to model the document collection, in which the child terms are not represented and child terms' frequencies are attributed to their corresponding parents
SVDDOCPRO=	Specifies the projections of the documents

You can specify the following *options* in the PROC HPTMSCORE statement.

CONFIG=*SAS-data-set*

specifies the input SAS data set that contains configuration information for PROC HPTMSCORE. The data set used for this option should be the one generated by the OUTCONFIG option in the PARSE statement of the HPTMINE procedure during training. For more information about this data set, see the section "The OUTCONFIG= Data Set" on page 764 of Chapter 26, "The HPTMINE Procedure (Experimental)."

DATA | DOC=*SAS-data-set*

specifies the input SAS data set of documents to be used by PROC HPTMSCORE. The default is the most recently created data set. If PROC HPTMSCORE executes in MPP mode, the input data are distributed to memory on the appliance nodes and analyzed in parallel, unless the data are already distributed in the appliance database. When data are already distributed, PROC HPTMSCORE reads the data alongside the distributed database. See the sections "SMP and MPP Modes" on page 16 and "Alongside-the-Database Execution" on page 22. Each row of the input data set must contain one text field and one ID field, which correspond to the text and the unique ID of a document, respectively.

NOPRINT
suppresses the generation of ODS output.

OUTPARENT=*SAS-data-set*
specifies the output data set to contain a compressed representation of the sparse term-by-document frequency matrix. The data set contains only the kept, representative terms, and the child frequencies are attributed to the corresponding parent. For more information about the compressed representation of the sparse term-by-document frequency matrix, see the section "The OUTPARENT= Data Set" on page 765 of Chapter 26, "The HPTMINE Procedure (Experimental)."

SVDDOCPRO=*SAS-data-set*
specifies the output data set to contain the reduced dimensional projections for each document. The contents of this data set are formed by multiplying the term-by-document frequency matrix by the input data set that is specified in the SVDU= option and then normalizing the result.

SVDU=*SAS-data-set*
specifies the input data set that contains the **U** matrix, which is created during training by PROC HPTMINE. The data set contains the information needed to project each document into the reduced dimensional space. For more information about the contents of this data set, see the SVDU= option in Chapter 26, "The HPTMINE Procedure (Experimental)."

TERMS=*SAS-data-set*
specifies the input SAS data set of terms to be used by PROC HPTMSCORE. The data set used for this option should be the one generated by the OUTTERMS= option in the PARSE statement of the HPTMINE procedure during training. This data set conveys to PROC HPTMSCORE which terms should be used in the analysis, if they should be mapped to a parent, and assigns them a key that corresponds to the key used on the input data set that is specified by the SVDU= option. For more information about this data set, see the section "The OUTTERMS= Data Set" on page 766 of Chapter 26, "The HPTMINE Procedure (Experimental)."

DOC_ID Statement

DOC_ID *variable* **;**

This statement specifies the variable that contains the ID of each document. In the input data set, each row corresponds to one document. The ID of each document must be unique; it can be either a number or a string of characters.

PERFORMANCE Statement

PERFORMANCE < *performance-options* > **;**

The PERFORMANCE statement defines performance parameters for multithreaded and distributed computing, passes variables about the distributed computing environment, and requests detailed results about the performance characteristics of the HPTMSCORE procedure.

You can also use the PERFORMANCE statement to control whether the HPTMSCORE procedure executes in SMP or MPP mode.

The PERFORMANCE statement for High-Performance Analytics procedures is documented in the section "PERFORMANCE Statement" on page 38 of Chapter 3, "Shared Concepts and Topics."

VARIABLE Statement

VARIABLE | VAR *variable* **;**

This statement specifies the variable that contains the text to be processed.

Details: HPTMSCORE Procedure

For details about the techniques used for nature language processing, term processing, and singular value decomposition, see the section "Details: HPTMINE Procedure" on page 760 of Chapter 26, "The HPTMINE Procedure (Experimental)."

Displayed Output

The following sections describe the output that PROC HPTMSCORE produces. The output is organized into various tables, which are discussed in the order of appearance.

Performance Information

The "Performance Information" table is produced by default. It displays information about the grid host for distributed execution and information about whether the procedure executes in client mode, distributed mode, or alongside-the-database mode. The number of computing nodes and threads are also displayed, depending on the environment.

Procedure Task Timing

When the DETAILS option is specified in the PERFORMANCE statement, the procedure produces a "Procedure Task Timing" table, which displays the elapsed time (absolute and relative) for the main tasks.

ODS Table Names

Each table created by the HPTMSCORE procedure has a name associated with it, and you must use this name to refer to the table when you use ODS statements. These names are listed in Table 27.2.

Table 27.2 ODS Tables Produced by PROC HPTMINE

Table Name	Description	Required Statement / Option
PerformanceInfo	Information about the high-performance computing environment	Default output

Table 27.2 *continued*

Table Name	Description	Required Statement / Option
Timing	Absolute and relative times for tasks that are performed by the procedure	DETAILS option in the PERFORMANCE statement

Configuration for Distributed Mode

When PROC HPTMSCORE runs in the distributed mode, it needs to locate on the grid the language binary files that are used in parsing text. You can use the GRID_TEXTANALYTICS_BIN_LOC macro to tell the HPTMSCORE procedure where to find these binary files. If the grid administrator has copied the language binary files to a directory named **/rdstore/tktg/misc**, which is accessible to all computer nodes of the grid, then you can insert the following statement before the statements that call the HPTMINE procedure to tell it the location of the binary files.

```
%let GRID_TEXTANALYTICS_BIN_LOC=/global_dir/tktg/misc;
```

For more information about this macro variable, see the section "Configuration for Distributed Mode" on page 768 of Chapter 26, "The HPTMINE Procedure (Experimental)."

Subject Index

2D geometric anisotropic structure
    HPLMIXED procedure, 295

adaptive lasso selection
    High-Performance Analytics procedures, SELECTION statement, 60
Adjusting Statistics When Sampling Target Classes Unevenly
    HPFOREST procedure, 234
Akaike's information criterion
    MIXED procedure, 312
Akaike's information criterion (finite sample corrected version)
    MIXED procedure, 312
Algorithm
    HPFOREST procedure, 233
alpha level
    HPLMIXED procedure, 291, 294
    HPLOGISTIC procedure, 337
ANCOVA effects
    Shared Concepts, 47
ANOVA effects
    Shared Concepts, 47
ANOVA table
    HPREG procedure, 563
ANTE(1) structure
    HPLMIXED procedure, 295
antedependence structure
    HPLMIXED procedure, 295
AR(1) structure
    HPLMIXED procedure, 295
at sign (@) operator
    Shared Concepts, 45, 49
autoregressive moving-average structure
    HPLMIXED procedure, 295
autoregressive structure
    HPLMIXED procedure, 295

backward elimination
    High-Performance Analytics procedures, SELECTION statement, 55
Bagging the Data
    HPFOREST procedure, 226
banded Toeplitz structure
    HPLMIXED procedure, 295
bar (|) operator
    Shared Concepts, 45, 48, 49
bar (|) operator
    Shared Concepts, 48
Bard function, 411
Base SAS software, 11
Bernoulli distribution
    HPNLIN procedure, 448
Bias and Correlation
    HPFOREST procedure, 246
binary distribution
    HPNLIN procedure, 448
binomial distribution
    HPNLIN procedure, 448
BLUE
    HPLMIXED procedure, 308
BLUP
    HPLMIXED procedure, 308
boundary constraints, 446
    HPLMIXED procedure, 292, 293
bounds
    HPNLIN procedure, 446
bounds on parameter estimates, 480
BOUNDS statement, 480
Branin function, 377

candidates for addition or removal
    HPREG procedure, 562
censored regression models
    HPQLIM procedure, 489
CLASS level
    HPREDUCE procedure, 518, 525
Class Level
    HPSAMPLE procedure, 585
class level
    HPLMIXED procedure, 289
    HPLOGISTIC procedure, 332, 351
    HPREG procedure, 546, 561
    MIXED procedure, 310
CLASS statement
    Shared Concepts, 41
classification variables
    Shared Concepts, 41
CODE statement, 107
colon (:) operator
    Shared Concepts, 46
compound symmetry structure
    example (HPLMIXED), 302
    HPLMIXED procedure, 295
computation, 108
computational method
    HPLMIXED procedure, 309

HPLOGISTIC procedure, 347
HPNEURAL procedure, 432
HPNLIN procedure, 457
HPREDUCE procedure, 523
HPREG procedure, 559
confidence limits
model parameters (HPLOGISTIC), 337
constraints
boundary (HPLMIXED), 292, 293
continuous-by-class effects
Shared Concepts, 50
continuous-nesting-class effects
Shared Concepts, 50
Controlling for Variable Selection Bias
HPFOREST procedure, 227
convergence criterion
HPLMIXED procedure, 286, 287
HPLOGISTIC procedure, 329–331
HPNLIN procedure, 442–444
MIXED procedure, 311
convergence status
HPLOGISTIC procedure, 353
MIXED procedure, 312
corrected sums of squares and crossproducts, 127
correlation coefficients, 123
printing, for each variable, 127
suppressing probabilities, 127
covariance parameter estimates
MIXED procedure, 312
covariance structure
antedependence (HPLMIXED), 297
autoregressive (HPLMIXED), 297
autoregressive moving average (HPLMIXED), 297
banded (HPLMIXED), 299
compound symmetry (HPLMIXED), 298
equi-correlation (HPLMIXED), 298
examples (HPLMIXED), 296
factor-analytic (HPLMIXED), 298
heterogeneous autoregressive (HPLMIXED), 297
heterogeneous compound symmetry (HPLMIXED), 298
heterogeneous Toeplitz (HPLMIXED), 299
HPLMIXED procedure, 280, 295
Huynh-Feldt (HPLMIXED), 298
simple (HPLMIXED), 299
Toeplitz (HPLMIXED), 299
unstructured (HPLMIXED), 299
unstructured, correlation (HPLMIXED), 299
variance components (HPLMIXED), 299
covariances, 127
covariates
heteroscedasticity models, 482
Criteria
HPFOREST procedure, 232
crossed effects
Shared Concepts, 48

dash (-) operator
Shared Concepts, 46
decision matrix
HPDECIDE procedure, 181
decomposition algorithm
example, 80
SAS/OR, 80
degrees of freedom
HPLMIXED procedure, 291
infinite (HPLMIXED), 291
method (HPLMIXED), 291
residual method (HPLMIXED), 291
derivative-free optimization
HPLSO procedure, 375
details
HPLSO procedure, 387
Diagnostic Statistics
HPREG procedure, 555
dimension information
MIXED procedure, 310
dimensions
HPLOGISTIC procedure, 353
HPREG procedure, 562
direct product structure
HPLMIXED procedure, 295
displayed output
HP4SCORE procedure, 97
HPDECIDE procedure, 182
HPFOREST procedure, 248
HPIMPUTE procedure, 271
HPLMIXED procedure, 310
HPLOGISTIC procedure, 351
HPNEURAL procedure, 434
HPNLIN procedure, 461
HPREDUCE procedure, 524
HPREG procedure, 561
HPSAMPLE procedure, 585
HPTMINE procedure, 768
HPTMSCORE procedure, 792
displayed output to log
HPLSO procedure, 387, 398
distributed computing
HPLMIXED procedure, 309
distribution functions
HPNLIN procedure, 455
double dash (- -) operator
Shared Concepts, 46

effect

name length (HPLMIXED), 288
name length (HPLOGISTIC), 332
name length (HPREDUCE), 518
name length (HPREG), 546
empirical Bayes estimate
HPNLIN procedure, 451
estimation
mixed model (HPLMIXED), 306
estimation methods
HPLMIXED procedure, 288
examples
Example 1, 112
Example 2, 115
Example 3, 120
Example 4, 121
HPLSO procedure, 401
examples, HPLMIXED
compound symmetry, G-side setup, 303
compound symmetry, R-side setup, 302
holding covariance parameters fixed, 292
specifying lower bounds, 292
split-plot design, 304
subject and no-subject formulation, 303
unstructured covariance, G-side, 295
examples, HPNLIN
boundary specification, 446
enzyme data, 439
gamma distribution, 456
starting values, data set, 450
starting values, grid, 449
examples, NLIN
conditional model expression, 466
join point, 466
plateau model, 466
predicted values, 466
segmented model, 466

factor analytic structures
HPLMIXED procedure, 295
FCMP basics
HPLSO procedure, 387
Fit Criteria
HPREG procedure, 554
fit statistics
HPLOGISTIC procedure, 354
HPREG procedure, 563
fixed effects
HPLMIXED procedure, 279
fixed-effects parameters
HPLMIXED procedure, 301
formula, 108
Formulas for Adjusting Statistics when Sampling Unevenly
HPFOREST procedure, 235
forward selection
High-Performance Analytics procedures, SELECTION statement, 52
forward swap selection
High-Performance Analytics procedures, SELECTION statement, 58
FREQ statement, 107
frequency information table
HPSAMPLE procedure, 586
frequency variable
High-Performance Analytics procedures, 32
HPDECIDE procedure, 179
HPFOREST procedure, 224
HPIMPUTE procedure, 269
HPLOGISTIC procedure, 334
HPREG procedure, 548
function caching
HPLSO procedure, 397
functional summary
HPLSO procedure, 382

G matrix
HPLMIXED procedure, 280, 293, 301, 302
gamma distribution
HPNLIN procedure, 448
Gaussian distribution
HPNLIN procedure, 447
general distribution
HPNLIN procedure, 448
general effects
Shared Concepts, 50
general linear covariance structure
HPLMIXED procedure, 295
generalized inverse, 308
genetic algorithms, 394
global tests
HPLOGISTIC procedure, 354
gradient
MIXED procedure, 311
growth curve analysis
example (HPLMIXED), 302

Handling Missing Values
HPFOREST procedure, 241
Handling Values That Are Absent from Training Data
HPFOREST procedure, 243
Hessian matrix
HPLMIXED procedure, 311
heterogeneous
AR(1) structure (HPLMIXED), 295
compound-symmetry structure (HPLMIXED), 295
covariance structure (HPLMIXED), 299
Toeplitz structure (HPLMIXED), 295

heteroscedasticity models
covariates, 482
High-Performance Analytics procedures, SELECTION statement
adaptive lasso selection, 60
backward elimination, 55
forward selection, 52
forward swap selection, 58
LAR selection, 58
LASSO selection, 59
stepwise selection, 56
histogram, 111
Hosmer-Lemeshow test
HPLOGISTIC procedure, 338, 346, 354
HP4SCORE procedure, 93
displayed output, 97
input data sets, 96
input model file, 97
output data set, 98
hpbin info, 111
HPCORR procedure
concepts, 130
details, 130
examples, 134
multithreading, 129, 131
ODS table names, 133
output, 132
output data sets, 132
overview, 123
syntax, 126
task tables, 127
HPCOUNTREG procedure
bounds on parameter estimates, 147
multi-threading, 150
output table names, 165
restrictions on parameter estimates, 151
syntax, 143
HPDECIDE procedure, 173
code file, 178
code metabase, 178
code residual, 178
cost options, 179
decision data sets, 178
decision matrix, 181
decision variables, 179
displayed output, 182
input data sets, 177
ODS table name, 182
old prior variable, 179
outfit data sets, 177
output data sets, 177
prior variable, 179
role of data set, 177
variables, 181
HPDMDB procedure, 189
multi-threading, 194
HPDS2 procedure, 199
input data sets, 204
multi-threading, 204
HPFOREST procedure, 214
Adjusting Statistics When Sampling Target Classes Unevenly, 234
Algorithm, 233
association test number of categories, 221
association test significance level, 221
Bagging the Data, 226
Bias and Correlation, 246
candidate variables to try, 223
Controlling for Variable Selection Bias , 227
Criteria, 232
displayed output, 248
Formulas for Adjusting Statistics when Sampling Unevenly, 235
Handling Missing Values, 241
Handling Values That Are Absent from Training Data, 243
Illustrations of Adjusting when Sampling Unevenly, 236
input data sets, 221
maxdepth constraint, 222
maximum number of trees , 222
Measuring Variable Importance, 243
minimum missing values to use in split search, 222
missing values, 222
ODS table names, 248
random number seed, 223
Rules, 232
save file, 225
score out, 225
Searching for a Splitting Rule, 232
Selecting a Splitting Variable, 230
split search exhaustive method, 221
split search leaffraction constraint, 221
split search leafsize constraint, 222
split search mincatsize constraint, 222
split search splitsize constraint, 223
Technical Derivations of Adjustments Formulas, 240
train fraction, 223
train n, 223
Training a Decision Tree, 226
within node sample, 222
HPIMPUTE procedure, 265
displayed output, 271
DMDB catalog, 268
input data sets, 268
multithreading, 270

ODS table names, 271
output data sets, 268
HPLMIXED procedure, 278
2D geometric anisotropic structure, 295
alpha level, 291, 294
ANTE(1) structure, 295
antedependence structure, 295
AR(1) structure, 295
ARMA structure, 295
autoregressive moving-average structure, 295
autoregressive structure, 295
banded Toeplitz structure, 295
BLUE, 286, 308
BLUP, 286, 308
boundary constraints, 292, 293
chi-square test, 291
class level, 289
compound symmetry structure, 295, 302
computational method, 309
confidence interval, 294
confidence limits, 291, 294
convergence criterion, 286, 287
covariance structure, 280, 295, 296
degrees of freedom, 291
direct product structure, 295
displayed output, 310
distributed computing, 309
EBLUPs, 294, 308
effect name length, 288
estimation methods, 288
factor analytic structures, 295
fixed effects, 279
fixed-effects parameters, 291, 301
function-based convergence criteria, 286, 287
G matrix, 280, 293, 301, 302
general linear covariance structure, 295
generalized inverse, 308
gradient-based convergence criteria, 286, 287
grid search, 291
growth curve analysis, 302
Hessian matrix, 311
heterogeneous AR(1) structure, 295
heterogeneous compound-symmetry structure, 295
heterogeneous covariance structures, 299
heterogeneous Toeplitz structure, 295
Huynh-Feldt structure, 295
infinite degrees of freedom, 291
infinite likelihood, 300
initial values, 291
input data sets, 287
intercept effect, 291, 293
Kronecker product structure, 295
linear covariance structure, 295
Matérn covariance structure, 295
matrix notation, 301
mixed model, 301
mixed model equations, 307
mixed model theory, 300
multi-threading, 293
multithreading, 309
Newton-Raphson algorithm, 307
ODS table names, 313
optimization information, 311
parameter constraints, 292
parameter-based convergence criteria, 289
performance information, 310
R matrix, 280, 299, 301, 302
random effects, 279, 293
random-effects parameters, 294, 301
repeated measures, 299
residual method, 291
restricted maximum likelihood (REML), 279
ridging, 307
spatial anisotropic exponential structure, 295
split-plot design, 304
standard linear model, 280
statement positions, 284
subject effect, 294, 300
summary of commands, 284
table names, 313
timing, 313
Toeplitz structure, 295
unstructured correlations, 295
unstructured covariance matrix, 295
variance components, 295
variance ratios, 292
HPLOGISTIC procedure, 319
alpha level, 337
class level, 332, 351
computational method, 347
confidence limits, 337
convergence criterion, 329–331
convergence status, 353
dimensions, 353
displayed output, 351
effect name length, 332
fit statistics, 354
function-based convergence criteria, 329, 330
global tests, 354
gradient-based convergence criteria, 330, 331
Hosmer-Lemeshow test, 338, 346, 354
input data sets, 330
iteration history, 353
link function, 338
model information, 351
model options summary, 335
multithreading, 341, 347

number of observations, 352
ODS table names, 355
optimization technique, 348
parameter estimates, 354
performance information, 351
response level ordering, 336
response profile, 352
response variable options, 335
selected effects, 353
selection information, 352
selection reason, 352
selection summary, 352
stop reason, 352
user-defined formats, 330
weighting, 342
XML input stream, 330
HPLSO examples
bound-constrained optimization, 377
introductory examples, 377, 379, 380
linear constraint, 379
maximum-likelihood estimates, 380
nonlinear constraints, 379
HPLSO procedure
details, 387
displayed output to log, 387, 398
examples, 401
FCMP basics, 387
function caching, 397
functional summary, 382
linear constraints, 392
nonlinear constraints, 393
objective, 388
ODS tables, 399
options classified by function, 382
overview, 375, 394
procedure termination messages, 398
specifying trial points, 396
table of syntax elements, 382
time limit, 385
HPNEURAL procedure, 417
computational method, 432
displayed output, 434
input data distribution, 425
input data sets, 424
multithreading, 428, 433
ODS table names, 435
output data set, 433
HPNLIN procedure, 437
additional estimates, 447, 463
additional estimates correlation, 464
additional estimates covariance, 464
ANOVA, 463
Bernoulli distribution, 448
binary distribution, 448
binomial distribution, 448
bounds, 446
computational method, 457
convergence criterion, 442–444
convergence status, 462
correlation, 464
covariance, 463
dimensions, 462
displayed output, 461
distribution functions, 455
empirical Bayes estimate, 451
fit statistics, 463
function-based convergence criteria, 442, 444
gamma distribution, 448
Gaussian distribution, 447
general distribution, 448
gradient-based convergence criteria, 443, 444
initial values, 448
input data sets, 443
iteration history, 462
lag functionality, 453
least squares, 454
least squares distribution, 447
linear constraints, 462
log-likelihood functions, 455
multi-threading, 451
multithreading, 457
negative binomial distribution, 448
normal distribution, 447
number of observations, 461
ODS table names, 464
optimization technique, 458
output data sets, 446
parameter estimates, 463
parameters, 462
performance information, 461
Poisson distribution, 448
prediction, 451
procedure task timing, 464
programming statements, 452
residual distribution, 447
restrict, 452
segmented model example, 465
specifications, 461
starting values, 448
user-defined formats, 444, 446
XML input stream, 444, 446
HPQLIM Procedure, 472
logit, 472
probit, 472
selection, 472
Tobit, 472
HPQLIM procedure
censored regression models, 489

frontier, 490
heteroscedasticity, 493
limited dependent variable models, 489
multithreading, 486
output, 494
output table names, 499
syntax, 475
tests on parameters, 493
truncated regression models, 490
HPREDUCE procedure, 507
CLASS level, 518, 525
computational method, 523
computes correlations, 518, 519
computes covariances, 518
displayed output, 524
effect name length, 518
input data sets, 518
maximum effects, 520
maximum steps, 520
minimal explained variance increment, 521
model information, 525
multi-threading, 521
number of observations, 525
ODS table names, 526
performance information, 524
prints the time used by each variable selection iteration, 519
Procedure Task Timing, 525
reduce options, 520
reduce options summary, 520
selected effects, 525
selection summary, 525
user-defined formats, 518
variance explained, 520
XML input stream, 518
HPREG procedure, 536
ANOVA table, 563
candidates for addition or removal, 562
class level, 546, 561
computational method, 559
Diagnostic Statistics, 555
dimensions, 562
displayed output, 561
effect name length, 546
Fit Criteria, 554
fit statistics, 563
input data sets, 545
introductory example, 538
model information, 561
multi-threading, 550
multithreading, 559
number of observations, 561
ODS table names, 565
output data set, 560
parameter estimates, 564
performance information, 561
random number seed, 546
selected effects, 563
selection information, 561
selection reason, 563
selection summary, 562
stop reason, 562
test data, 558
timing, 564
user-defined formats, 545
validation, 558
weighting, 553
XML input stream, 545
HPSAMPLE procedure, 581
Class Level, 585
displayed output, 585
frequency information table, 586
ODS table names, 586
performance information, 585
single-threading, 584
timing table, 585
HPSUMMARY procedure, 717
analysis variable, 730
classification variables, 725
confidence level, 722
input data sets, 722
missing values, 722
multi-threading, 728
HPTMINE procedure, 748
cell weight, 756
configuration for distributed mode, 768
displayed output, 768
entity, 756
filtering term by frequency, 757
GRID_TEXTANALYTICS_BIN_LOC macro, 768
input data sets, 754
multiterm words list, 756
multithreading, 758
noun groups, 756
ODS table names, 768
performance information, 768
procedure task timing, 768
sparse matrix, 765
start list, 757
stemming, 756
stop list, 757
SVD, singular value decomposition, 763
synonym list, 757
tagging, 756
term weight, 758
transactional style, 765
HPTMSCORE procedure, 785

configuration for distributed mode, 793
displayed output, 792
GRID_TEXTANALYTICS_BIN_LOC macro, 793
input data sets, 790
multithreading, 791
ODS table names, 792
performance information, 792
procedure task timing, 792
Huynh-Feldt
structure (HPLMIXED), 295

ID, 107
ID statement, 107
Illustrations of Adjusting when Sampling Unevenly
HPFOREST procedure, 236
infinite likelihood
HPLMIXED procedure, 300
initial values
HPLMIXED procedure, 291
HPNLIN procedure, 448
input variables
HPNEURAL procedure, 427
interaction effects
Shared Concepts, 48
intercept
Shared Concepts, 48
iteration history
HPLOGISTIC procedure, 353
MIXED procedure, 311
iterations
history (MIXED), 311

Kronecker product structure
HPLMIXED procedure, 295

lag functionality
HPNLIN procedure, 453
Lagrange multiplier test
nonlinear hypotheses, 494
LAR selection
High-Performance Analytics procedures, SELECTION statement, 58
LASSO selection
High-Performance Analytics procedures, SELECTION statement, 59
least squares
HPNLIN procedure, 454
least squares distribution
HPNLIN procedure, 447
level mapping, 111
levelization
Shared Concepts, 41
limited dependent variable models
HPQLIM procedure, 489
linear constraints
HPLSO procedure, 392
linear covariance structure
HPLMIXED procedure, 295
link function
HPLOGISTIC procedure, 338
local search optimization, 387, 401
log-likelihood functions
HPNLIN procedure, 455
logit
HPQLIM Procedure, 472

ORHPLSO
ORHPLSO, 400
main effects
Shared Concepts, 48
Matérn covariance structure
HPLMIXED procedure, 295
matrix
notation, theory (HPLMIXED), 301
maximum likelihood estimation
mixed model (HPLMIXED), 307
meantable, 111
measures of association, 134
nonparametric, 123
Measuring Variable Importance
HPFOREST procedure, 243
mixed model (HPLMIXED)
estimation, 306
formulation, 301
maximum likelihood estimation, 307
notation, 279
theory, 300
mixed model (MIXED)
objective function, 311
mixed model equations
HPLMIXED procedure, 307
MIXED procedure
Akaike's information criterion, 312
Akaike's information criterion (finite sample corrected version), 312
class level, 310
convergence criterion, 311
convergence status, 312
covariance parameter estimates, 312
dimension information, 310
fitting information, 312
gradient, 311
iteration history, 311
iterations, 311
model information, 310
number of observations, 311
Schwarz's Bayesian information criterion, 312
model

information (HPLOGISTIC), 351
information (HPREDUCE), 525
information (HPREG), 561
specification (HPNLIN, 447
model information
MIXED procedure, 310
multi-threading
HPCOUNTREG procedure, 150
HPDMDB procedure, 194
HPDS2 procedure, 204
HPLMIXED procedure, 293
HPNLIN procedure, 451
HPREDUCE procedure, 521
HPREG procedure, 550
HPSUMMARY procedure, 728
multistart algorithm
example, 86
SAS/OR, 86
multithreading
HPCORR procedure, 129, 131
HPIMPUTE procedure, 270
HPLMIXED procedure, 309
HPLOGISTIC procedure, 341, 347
HPNEURAL procedure, 428, 433
HPNLIN procedure, 457
HPQLIM procedure, 486
HPREG procedure, 559
HPTMINE procedure, 758
HPTMSCORE procedure, 791

negative binomial distribution
HPNLIN procedure, 448
nested effects
Shared Concepts, 49
nested versus crossed effects
Shared Concepts, 49
Newton-Raphson
optimization methods, 147, 480
Newton-Raphson algorithm
HPLMIXED procedure, 307
Newton-Raphson method, 147, 480
nonlinear constraints
HPLSO procedure, 393
nonlinear hypotheses
Lagrange multiplier test, 494
Wald test, 494
nonlinear programming, 86
nonparametric measures of association, 123
normal distribution
HPNLIN procedure, 447
number of hidden neurons
HPNEURAL procedure, 426
number of observations
HPLOGISTIC procedure, 352
HPREDUCE procedure, 525
HPREG procedure, 561
MIXED procedure, 311

objective
HPLSO procedure, 388
objective function
mixed model (MIXED), 311
ODS (Output Delivery System)
HPCORR procedure and, 133
ODS tables, 110
HPLSO procedure, 399
optimization information
HPLMIXED procedure, 311
optimization methods
Newton-Raphson, 147, 480
quasi-Newton, 147, 480
trust region, 147, 480
optimization technique
HPLOGISTIC procedure, 348
HPNLIN procedure, 458
option tuner
example, 89
SAS/OR, 89
options classified by function, *see* functional summary
options summary
MODEL statement (HPLMIXED), 290
PARSE statement, 755
PROC HPLMIXED statement, 285
PROC HPLOGISTIC statement, 328
PROC HPNLIN statement, 441
PROC HPREDUCE statement, 517
PROC HPREG statement, 545
PROC HPSUMMARY statement, 721
PROC HPTMINE statement, 754
PROC HPTMSCORE statement, 790
RANDOM statement (HPLMIXED), 294
REPEATED statement (HPLMIXED), 300
SVD statement, 758
ordering
of class levels (Shared Concepts), 42
output
ouput table details, 110
output data set
HP4SCORE procedure, 98
HPNEURAL procedure, 433
HPREG procedure, 560
output table names
HPCOUNTREG procedure, 165
HPQLIM procedure, 499
overview
HPLSO procedure, 394

parameter constraints

HPLMIXED procedure, 292
parameter estimates
HPLOGISTIC procedure, 354
HPREG procedure, 564
parameterization
Shared Concepts, 44
Pearson correlation statistics, 123
example, 134, 135
in output data set, 127
Pearson product-moment correlation, 127, 130, 134
Pearson weighted product-moment correlation, 130
probability values, 130
suppressing, 127
performance, 111
performance information
HPLMIXED procedure, 310
HPLOGISTIC procedure, 351
HPREDUCE procedure, 524
HPREG procedure, 561
HPSAMPLE procedure, 585
HPTMINE procedure, 768
HPTMSCORE procedure, 792
PERFORMANCE statement, 108
Poisson distribution
HPNLIN procedure, 448
polynomial effects
Shared Concepts, 48
posterior variables
HPDECIDE procedure, 180
predicted variable
HPDECIDE procedure, 180
prediction
HPNLIN procedure, 451
probit
HPQLIM Procedure, 472
PROC HPBIN, 101
PROC HPBIN features, 102
PROC HPBIN methods
bucket, 102
pseudo–quantile, 103
Winsor, 103
PROC HPBIN statement, 105
COMPUTEQUANTILE option, 106
COMPUTESTATS option, 106
input data, 106
METHOD option, 106
NOPRINT, 107
NUMBIN option, 107
OUTPUT option, 107
REPLACE data, 107
PROC HPBIN syntax, 105
procedure output, 110
Procedure Task Timing
HPREDUCE procedure, 525
procedure task timing
HPTMINE procedure, 768
HPTMSCORE procedure, 792
procedure termination messages
HPLSO procedure, 398
programming statements
HPNLIN procedure, 452

quantile, 111
quasi-Newton
optimization methods, 147, 480
quasi-Newton method, 147, 480

R matrix
HPLMIXED procedure, 280, 299, 301, 302
random effects
HPLMIXED procedure, 279, 293
random numbers
seed, 386
random-effects parameters
HPLMIXED procedure, 301
reduce options
HPREDUCE procedure, 520
regression effects
Shared Concepts, 47, 48
repeated measures
HPLMIXED procedure, 299
residual distribution
HPNLIN procedure, 447
residual maximum likelihood (REML)
HPLMIXED procedure, 307
response level ordering
HPLOGISTIC procedure, 336
response profile
HPLOGISTIC procedure, 352
response variable options
HPLOGISTIC procedure, 335
restrict
HPNLIN procedure, 452
restricted maximum likelihood
HPLMIXED procedure, 279
restricted maximum likelihood (REML)
HPLMIXED procedure, 307
reverse response level ordering
HPLOGISTIC procedure, 336
ridging
HPLMIXED procedure, 307
Rules
HPFOREST procedure, 232

SAS/ETS software, 12
SAS/GRAPH software, 12
SAS/IML software, 10

SAS/IML Studio, 10
SAS/OR
  decomposition algorithm, 80
  multistart algorithm, 86
  option tuner, 89
  SAS High-Performance Analytics features, 79
SAS/OR software, 12
SAS/QC software, 13
SAS/STAT software, 13
Schwarz's Bayesian information criterion
  MIXED procedure, 312
Searching for a Splitting Rule
  HPFOREST procedure, 232
selected effects
  HPLOGISTIC procedure, 353
  HPREDUCE procedure, 525
  HPREG procedure, 563
Selecting a Splitting Variable
  HPFOREST procedure, 230
selection
  HPQLIM Procedure, 472
selection information
  HPLOGISTIC procedure, 352
  HPREG procedure, 561
selection reason
  HPLOGISTIC procedure, 352
  HPREG procedure, 563
selection summary
  HPLOGISTIC procedure, 352
  HPREDUCE procedure, 525
  HPREG procedure, 562
Shared Concepts
  ANCOVA effects, 47
  ANOVA effects, 47
  at sign (@) operator, 45, 49
  bar (|) operator, 45, 48, 49
  bar (|) operator, 48
  CLASS statement, 41
  classification variables, 41
  colon (:) operator, 46
  continuous-by-class effects, 50
  continuous-nesting-class effects, 50
  crossed effects, 48
  dash (-) operator, 46
  double dash (- -) operator, 46
  general effects, 50
  interaction effects, 48
  intercept, 48
  levelization, 41
  main effects, 48
  missing values, class variables, 43
  nested effects, 49
  nested versus crossed effects, 49
  ORDER= option, 42
  ordering of class levels, 42
  parameterization, 44
  polynomial effects, 48
  regression effects, 47, 48
  singular parameterization, 48
  sort order of class levels, 42
single-threading
  HPSAMPLE procedure, 584
singular parameterization
  Shared Concepts, 48
singularity of variables, 127
sort order
  of class levels (Shared Concepts), 42
sparse matrix
  HPTMINE procedure, 765
spatial anisotropic exponential structure
  HPLMIXED procedure, 295
specifying trial points
  HPLSO procedure, 396
split-plot design
  HPLMIXED procedure, 304
standard deviation, 127
standard linear model
  HPLMIXED procedure, 280
starting values
  HPNLIN procedure, 448
stepwise selection
  High-Performance Analytics procedures,
    SELECTION statement, 56
stop reason
  HPLOGISTIC procedure, 352
  HPREG procedure, 562
subject effect
  HPLMIXED procedure, 294, 300
summary of commands
  HPLMIXED procedure, 284
sums of squares and crossproducts, 127
syntax
  HPLSO procedure, 382

table names
  HPLMIXED procedure, 313
table of syntax elements, *see* functional summary
target variables
  HPNEURAL procedure, 429
Technical Derivations of Adjustments Formulas
  HPFOREST procedure, 240
termination criteria
  time limit, 385
test data
  HPREG procedure, 558
timing
  HPLMIXED procedure, 313
  HPREG procedure, 564

timing table
    HPSAMPLE procedure, 585
Tobit
    HPQLIM Procedure, 472
Toeplitz structure
    HPLMIXED procedure, 295
Training a Decision Tree
    HPFOREST procedure, 226
transactional style
    HPTMINE procedure, 765
trim statistics, 111
truncated regression models
    HPQLIM procedure, 490
trust region
    optimization methods, 147, 480
trust region method, 147, 480

unstructured correlations
    HPLMIXED procedure, 295
unstructured covariance matrix
    HPLMIXED procedure, 295

validation
    HPREG procedure, 558
VAR statement, 108
    PROC HPBIN variables, 108
variable statistic, 111
variables
    HPDECIDE procedure, 181
variance components
    HPLMIXED procedure, 295
variance ratios
    HPLMIXED procedure, 292
variances, 127

Wald test
    nonlinear hypotheses, 494
weight variable
    HPNEURAL procedure, 431
weighting
    HPLOGISTIC procedure, 342
    HPREG procedure, 553
Winsor statistics, 111

Syntax Index

ABSCONV option
PROC HPLMIXED statement, 286
PROC HPLOGISTIC statement, 329
PROC HPNLIN statement, 442
ABSFCONV option
PROC HPLMIXED statement, 286
PROC HPLOGISTIC statement, 329
PROC HPNLIN statement, 442
ABSFCONV= option
PROC HPLSO statement, 385
ABSGCONV option
PROC HPLMIXED statement, 286
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 443
ABSGTOL option
PROC HPLMIXED statement, 286
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 443
ABSOLUTE option
PROC HPLMIXED statement, 311
ABSTOL option
PROC HPLMIXED statement, 286
PROC HPLOGISTIC statement, 329
PROC HPNLIN statement, 442
ADAPTIVE option
SELECTION statement (High-Performance Analytics), 34
ALL option
TEST statement (HPQLIM), 487
ALLTYPES option
PROC HPSUMMARY statement, 722
ALLWAYS option
PROC HPSUMMARY statement, 722
ALPHA option
PROC HPCORR statement, 127
ALPHA= option
ESTIMATE statement (HPNLIN), 447
MODEL statement (HPLOGISTIC), 337
PREDICT statement (HPNLIN), 451
PROC HPFOREST statement, 221
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 443
PROC HPREG statement, 545
PROC HPSEVERITY statement, 614
PROC HPSUMMARY statement, 722
RANDOM statement (HPLMIXED), 294
analysis variable
VAR statement (HPSUMMARY), 730

ARCHITECTURE statement
HPNEURAL procedure, 425
AUTONAME option
OUTPUT statement (HPSUMMARY), 728

BEST= option
PROC HPCORR statement, 127
BLUP option
PROC HPLMIXED statement, 286
BOUNDS statement
HPCOUNTREG procedure, 147
HPNLIN procedure, 446
HPQLIM procedure, 480
BY statement
HPREG procedure, 546

C= option
PROC HPSEVERITY statement, 614
CACHEIN= option
PROC HPLSO statement, 383
CACHEMAX= option
PROC HPLSO statement, 386
CACHEOUT= option
PROC HPLSO statement, 384
CACHETOL= option
PROC HPLSO statement, 386
CATBINS= option
PROC HPFOREST statement, 221
CELLWGT= option
PARSE statement, 756
CENSORED option
ENDOGENOUS statement (HPQLIM), 481, 484
CHARTYPE= option
PROC HPSUMMARY statement, 722
CHOOSE= option
MODEL statement (High-Performance Analytics), 34
CL option
MODEL statement (HPLMIXED), 291
MODEL statement (HPLOGISTIC), 337
RANDOM statement (HPLMIXED), 294
CLASS Statement, *see* HPDMDB procedure, *see* HPSAMPLE procedure
HPDMDB procedure, 193
HPSAMPLE procedure, 584
CLASS statement, *see* HPSUMMARY procedure
High-Performance Analytics procedures, 28
HPLMIXED procedure, 290
HPLOGISTIC procedure, 334

HPREDUCE procedure, 519
HPREG procedure, 547
HPSUMMARY procedure, 725
MIXED procedure, 310
classification variables
CLASS statement (HPSUMMARY), 725
CLB option
MODEL statement (HPREG), 548
CODE statement, 107
HPDECIDE procedure, 178
HPIMPUTE procedure, 268
HPNEURAL procedure, 426
HPREG procedure, 547
COMMIT= option
PERFORMANCE statement (High-Performance Analytics), 38
COMPETITIVE option
SELECTION statement (High-Performance Analytics), 34
CONDITIONAL
OUTPUT statement (HPQLIM), 485
CONFIG= option
HPTMSCORE statement, 790
CONVF option
PROC HPLMIXED statement, 311
CONVG option
PROC HPLMIXED statement, 311
CONVH option
PROC HPLMIXED statement, 311
CORR
PROC HPREDUCE statement, 518
CORR option
PROC HPNLIN statement, 443
CORRB option
HPQLIM procedure, 478
MODEL statement, 149
PROC HPCOUNTREG statement, 146
CORROUT option
PROC HPQLIM statement, 477
COST option
ENDOGENOUS statement (HPQLIM), 482, 485
COST= option
PROC HPDECIDE statement, 179
COV
PROC HPREDUCE statement, 518
COV option
PROC HPCORR statement, 127
PROC HPNLIN statement, 443
COVB option
HPQLIM procedure, 478
MODEL statement, 149
PROC HPCOUNTREG statement, 146
COVEST= option
HPQLIM procedure, 478
PROC HPCOUNTREG statement, 146
COVOUT option
PROC HPCOUNTREG statement, 146
PROC HPQLIM statement, 477
PROC HPSEVERITY statement, 610
CPUCOUNT= option
PERFORMANCE statement (High-Performance Analytics), 38
CRITERION= option
PROC HPSEVERITY statement, 613
SELECTION statement (High-Performance Analytics), 34
CSSCP option
PROC HPCORR statement, 127

DATA statement, *see* HPDS2 procedure
HPDS2 procedure, 204
DATA= option
OUTPUT statement (HPLOGISTIC), 340
OUTPUT statement (HPREG), 551
PROC HP4SCORE statement, 96
PROC HPCORR statement, 127
PROC HPCOUNTREG statement, 145
PROC HPDECIDE statement, 177
PROC HPDS2 statement, 204
PROC HPFOREST statement, 221
PROC HPIMPUTE statement, 268
PROC HPLMIXED statement, 287
PROC HPLOGISTIC statement, 330
PROC HPNEURAL statement, 424
PROC HPNLIN statement, 443
PROC HPQLIM statement, 477
PROC HPREDUCE statement, 518
PROC HPREG statement, 545
PROC HPSEVERITY statement, 610, 613
PROC HPSUMMARY statement, 722
PROC HPTMINE statement, 754
PROC HPTMSCORE statement, 790
DATASERVER= option
PERFORMANCE statement (High-Performance Analytics), 39
DDFM= option
MODEL statement (HPLMIXED), 291
MODEL statement (HPLOGISTIC), 337
DECDATA= option
PROC HPDECIDE statement, 178
DECISION statement
HPDECIDE procedure, 178
DECOMP= option
LP solver (OPTMODEL procedure), 80
MILP solver (OPTMODEL procedure), 80
OPTLP procedure, 80
OPTMILP procedure, 80
DECVARS= option

PROC HPDECIDE statement, 179
DESCENDING option
CLASS statement (High-Performance Analytics), 28
MODEL statement (HPLOGISTIC), 336
DETAILS option
PERFORMANCE statement (High-Performance Analytics), 39
PERFORMANCE statement (HPCOUNTREG), 150
PERFORMANCE statement (HPQLIM), 486
DETAILS= option
SELECTION statement (High-Performance Analytics), 36
DF= option
ESTIMATE statement (HPNLIN), 447
PREDICT statement (HPNLIN), 451
PROC HPNLIN statement, 443
DFMIXTURE= option
SCALEMODEL statement, 625
DIST statement
HPSEVERITY procedure, 616
DIST= option
HPCOUNTREG statement (HPCOUNTREG), 148
MODEL statement (HPCOUNTREG), 148
DISTR option
PROC HPNEURAL statement, 425
DMDBCAT= option
PROC HPIMPUTE statement, 268
DOC= option
PROC HPTMINE statement, 754
PROC HPTMSCORE statement, 790
DOC_ID statement
HPTMINE procedure, 754
HPTMSCORE procedure, 791

ECORR option
PROC HPNLIN statement, 443
ECOV option
PROC HPNLIN statement, 444
EDF=AUTO option
PROC HPSEVERITY statement, 614
EDF=KAPLANMEIER option
PROC HPSEVERITY statement, 614
EDF=MODIFIEDKM option
PROC HPSEVERITY statement, 614
EDF=NOTURNBULL option
PROC HPSEVERITY statement, 615
EDF=STANDARD option
PROC HPSEVERITY statement, 615
EDF=TURNBULL option
PROC HPSEVERITY statement, 615
EMPIRICALCDF= option
PROC HPSEVERITY statement, 614
ENDDATA statement, *see* HPDS2 procedure
HPDS2 procedure, 204
ENSUREMLE option
PROC HPSEVERITY statement, 615
ENTITIES= option
PARSE statement, 756
EPS= option
PROC HPSEVERITY statement, 615
EQCONS= option
PARMS statement (HPLMIXED), 292
ERRSTD
OUTPUT statement (HPQLIM), 485
ESTIMATE statement
HPNLIN procedure, 447
EXCLNPWGT option
PROC HPCORR statement, 128
PROC HPSUMMARY statement, 722
EXCLNPWGTS option, *see* EXCLNPWGT option
EXHAUSTIVE= option
PROC HPFOREST statement, 221
EXPECTED
OUTPUT statement (HPQLIM), 486

FAST option
SELECTION statement (High-Performance Analytics), 35
FCONV option
PROC HPLMIXED statement, 287
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 444
FEASTOL= option
PROC HPLSO statement, 385
FILE= option
PROC HP4SCORE statement, 97
PROC HPDECIDE statement, 178
FIRSTGEN= option
PROC HPLSO statement, 383
FMTLIBXML= option
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 444
PROC HPREDUCE statement, 518
PROC HPREG statement, 545
FRACTION option
HPREG procedure, PARTITION statement, 550
FREQ Statement, *see* HPDMDB procedure
HPDMDB procedure, 194
FREQ statement, 107, *see* HPSUMMARY procedure
High-Performance Analytics procedures, 32
HPCORR procedure, 129
HPCOUNTREG procedure, 147
HPDECIDE procedure, 179
HPFOREST procedure, 224
HPIMPUTE procedure, 269

HPLOGISTIC procedure, 334
HPREG procedure, 548
HPSUMMARY procedure, 726
frequency variable
FREQ statement (HPSUMMARY), 726
FRONTIER option
ENDOGENOUS statement (HPQLIM), 481, 485
FTOL option
PROC HPLMIXED statement, 287
PROC HPLOGISTIC statement, 330
PROC HPNLIN statement, 444

GCONV option
PROC HPLMIXED statement, 287
PROC HPLOGISTIC statement, 331
PROC HPNLIN statement, 444
GRIDTIMEOUT= option
PERFORMANCE statement (High-Performance Analytics), 39
GROUPINTERNAL option
CLASS statement (HPSUMMARY), 725
GTOL option
PROC HPLMIXED statement, 287
PROC HPLOGISTIC statement, 331
PROC HPNLIN statement, 444

HIDDEN statement
HPNEURAL procedure, 426
HIERARCHY= option
SELECTION statement (High-Performance Analytics), 37
High-Performance Analytics procedures
FREQ statement, 32
ID statement, 32
VAR statement, 41
WEIGHT statement, 41
High-Performance Analytics procedures, CLASS statement, 28
DESCENDING option, 28
MISSING option, 31
ORDER= option, 29
PARAM= option, 31
REF= option, 29
TRUNCATE= option, 31
High-Performance Analytics procedures, FREQ statement, 32
High-Performance Analytics procedures, ID statement, 32
High-Performance Analytics procedures, PERFORMANCE statement, 38
COMMIT= option, 38
CPUCOUNT= option, 38
DATASERVER= option, 39
DETAILS option, 39
GRIDTIMEOUT= option, 39
HOST= option, 39
INSTALL= option, 39
INSTALLLOC= option, 39
NNODES= option, 39
NODES= option, 39
NTHREADS= option, 41
High-Performance Analytics procedures, SELECTION statement, 32
ADAPTIVE option, 34
CHOOSE= option, 34
COMPETITIVE option, 34
CRITERION= option, 34
DETAILS= option, 36
HIERARCHY= option, 37
LSCOEFFS option, 35
MAXEFFECTS= option, 35
MAXSTEP= option, 35
METHOD= option, 33
MINEFFECTS= option, 35
SELECT= option, 35
SELECTION= option, 37
SLE= option, 35
SLENTRY= option, 35
SLS= option, 36
SLSTAY= option, 36
STOP= option, 36
STOPHORIZON= option, 37
High-Performance Analytics procedures, VAR statement, 41
High-Performance Analytics procedures, WEIGHT statement, 41
HOLD= option
PARMS statement (HPLMIXED), 292
HOST= option
PERFORMANCE statement (High-Performance Analytics), 39
HP4SCORE procedure, 96
syntax, 96
HP4SCORE procedure, PROC HP4SCORE statement
DATA= option, 96
FILE= option, 97
OUT= option, 97
HP4SCORE procedure, SCORE statement, 97
HP4SCOREC procedure, ID statement, 96
HP4SCOREC procedure, PROC HP4SCORE statement, 96
HPCORR procedure
PERFORMANCE statement, 129
syntax, 126
HPCORR procedure, FREQ statement, 129
HPCORR procedure, PERFORMANCE statement, 129
HPCORR procedure, PROC HPCORR statement, 127

ALPHA option, 127
BEST= option, 127
COV option, 127
CSSCP option, 127
DATA= option, 127
EXCLNPWGT option, 128
NOCORR option, 128
NOMISS option, 128
NOPRINT option, 128
NOPROB option, 128
NOSIMPLE option, 128
OUT= option, 128
OUTP= option, 128
RANK option, 128
SSCP option, 128
VARDEF= option, 128
HPCORR procedure, VAR statement, 129
HPCORR procedure, WEIGHT statement, 130
HPCOUNTREG procedure, 143
PERFORMANCE statement, 150
syntax, 143
HPCOUNTREG procedure, PERFORMANCE statement, 150
HPCOUNTREG procedure, WEIGHT statement, 151
HPDECIDE procedure, 176
CODE statement, 178
DECISION statement, 178
FREQ statement, 179
ID statement, 179
PERFORMANCE statement, 180
POSTERIORS statement, 180
PREDICTED statement, 180
PROC HPDECIDE statement, 177
syntax, 176
TARGET statement, 181
HPDECIDE procedure, PROC HPDECIDE statement
COST= option, 179
DATA= option, 177
DECDATA= option, 178
DECVARS= option, 179
FILE= option, 178
METABASE= option, 178
OLDPRIORVAR= option, 179
OUT= option, 177
OUTFIT= option, 177
PRIORVAR= option, 179
RESIDUAL, 178
ROLE=*option*, 177
HPDMDB procedure, 192
CLASS Statement, 193
FREQ Statement, 194
PERFORMANCE statement, 194
PROC HPDMDB statement, 192
syntax, 192
VAR Statement, 195
WEIGHT Statement, 195
HPDMDB procedure, CLASS Statement, 193
HPDMDB procedure, FREQ Statement, 194
HPDMDB procedure, PERFORMANCE statement, 194
HPDMDB procedure, PROC HPDMDB statement, 192
HPDMDB procedure, VAR Statement, 195
HPDMDB procedure, WEIGHT Statement, 195
HPDS2 procedure, 203
DATA statement, 204
ENDDATA statement, 204
PERFORMANCE statement, 204
PROC HPDS2 statement, 204
QUIT statement, 205
RUN CANCEL statement, 205
RUN statement, 205
syntax, 203
HPDS2 procedure, DATA statement, 204
HPDS2 procedure, ENDDATA statement, 204
HPDS2 procedure, PERFORMANCE statement, 204
HPDS2 procedure, PROC HPDS2 statement
DATA= option, 204
IN= option, 204
HPDS2 procedure, QUIT statement, 205
HPDS2 procedure, RUN CANCEL statement, 205
HPDS2 procedure, RUN statement, 205
HPDS2C procedure, PROC HPDS2 statement, 204
HPFOREST procedure, 220
FREQ statement, 224
INPUT statement, 224
PROC HPFOREST statement, 221
SAVE statement, 225
SCORE statement, 225
syntax, 220
TARGET statement, 225
HPFOREST procedure, FREQ statement, 224
HPFOREST procedure, PROC HPFOREST statement
ALPHA= option, 221
CATBINS= option, 221
DATA= option, 221
EXHAUSTIVE= option, 221
LEAFFRACTION= option, 221
LEAFSIZE= option, 222
MAXDEPTH= option, 222
MAXTREES= option, 222
MINCATSIZE= option, 222
MINUSEINSEARCH= option, 222
MISSING= option, 222
NODESIZE= option, 222
SEED= option, 223
SPLITSIZE= option, 223
TRAINFRACTION= option, 223

TRAINN= option, 223
VARS_TO_TRY= option, 223
HPFORESTC procedure, PROC HPFOREST statement, 221
HPIMPUTE procedure, 268
CODE statement, 268
FREQ statement, 269
ID statement, 269
IMPUTE statement, 269
INPUT statement, 270
PERFORMANCE statement, 270
PROC HPIMPUTE statement, 268
syntax, 268
HPIMPUTE procedure, PROC HPIMPUTE statement
DATA= option, 268
DMDBCAT= option, 268
OUT= option, 268
HPLMIXED procedure, 284
PERFORMANCE statement, 293
PROC HPLMIXED statement, 285
syntax, 284
HPLMIXED procedure, CLASS statement, 290
HPLMIXED procedure, MODEL statement, 290
CL option, 291
DDFM= option, 291
NOINT option, 291
SOLUTION option, 291
HPLMIXED procedure, PARMS statement, 291
EQCONS= option, 292
HOLD= option, 292
LOWERB= option, 292
NOITER option, 293
PARMSDATA= option, 293
PDATA= option, 293
UPPERB= option, 293
HPLMIXED procedure, PERFORMANCE statement, 293
HPLMIXED procedure, PROC HPLMIXED statement
ABSCONV option, 286
ABSFCONV option, 286
ABSFTOL option, 286
ABSGCONV option, 286
ABSGTOL option, 286
ABSTOL option, 286
BLUP option, 286
DATA= option, 287
FCONV option, 287
FTOL option, 287
GCONV option, 287
GTOL option, 287
MAXCLPRINT= option, 287
MAXFUNC= option, 288
MAXITER= option, 288
MAXTIME= option, 288
METHOD= option, 288
NAMELEN= option, 288
NOCLPRINT option, 289
NOPRINT option, 289
SINGCHOL= option, 289
SINGSWEEP= option, 289
SINGULAR= option, 289
TECHNIQUE= option, 289
XCONV option, 289
XTOL option, 289
HPLMIXED procedure, RANDOM statement, 293
ALPHA= option, 294
CL option, 294
SOLUTION option, 294
SUBJECT= option, 294
TYPE= option, 295
HPLMIXED procedure, REPEATED statement, 299
SUBJECT= option, 300
TYPE= option, 300
HPLMIXEDC procedure, PROC HPLMIXED statement, 285
HPLOGISTIC procedure, 328
CLASS statement, 334
FREQ statement, 334
ID statement, 334
MODEL statement, 335
OUTPUT statement, 339
PERFORMANCE statement, 341
PROC HPLOGISTIC statement, 328
SELECTION statement, 341
syntax, 328
WEIGHT statement, 342
HPLOGISTIC procedure, CLASS statement, 334
UPCASE option, 334
HPLOGISTIC procedure, FREQ statement, 334
HPLOGISTIC procedure, ID statement, 334
HPLOGISTIC procedure, MODEL statement, 335
ALPHA= option, 337
CL option, 337
DDFM= option, 337
DESCENDING option, 336
INCLUDE option, 338
LACKFIT option, 338
LINK= option, 338
NOINT option, 339
OFFSET= option, 339
ORDER= option, 336
RSQUARE option, 339
START option, 339
HPLOGISTIC procedure, OUTPUT statement, 339
DATA= option, 340
keyword= option, 340
OBSCAT option, 340

OUT= option, 340
HPLOGISTIC procedure, PERFORMANCE statement, 341
HPLOGISTIC procedure, PROC HPLOGISTIC statement, 328
ABSCONV option, 329
ABSFCONV option, 329
ABSFTOL option, 329
ABSGCONV option, 330
ABSGTOL option, 330
ABSTOL option, 329
ALPHA= option, 330
DATA= option, 330
FCONV option, 330
FMTLIBXML= option, 330
FTOL option, 330
GCONV option, 331
GTOL option, 331
ITDETAILS option, 331
ITSELECT option, 331
MAXFUNC= option, 331
MAXITER= option, 332
MAXTIME= option, 332
NAMELEN= option, 332
NOCLPRINT option, 332
NOITPRINT option, 332
NOPRINT option, 332
NORMALIZE= option, 332
NOSTDERR option, 333
SINGCHOL= option, 333
SINGSWEEP= option, 333
SINGULAR= option, 333
TECHNIQUE= option, 333
HPLOGISTIC procedure, PROC HPREDUCE statement
NOPRINT option, 518
HPLOGISTIC procedure, SELECTION statement, 341
HPLOGISTIC procedure, WEIGHT statement, 342
HPLSO procedure
PROC HPLSO statement, 382
HPNEURAL procedure, 424
ARCHITECTURE statement, 425
CODE statement, 426
HIDDEN statement, 426
ID statement, 427
INPUT statement, 427
PARTITION statement, 428
PERFORMANCE statement, 428
PROC HPNEURAL statement, 424
SCORE statement, 429
syntax, 424
TARGET statement, 429
TRAIN statement, 430
WEIGHT statement, 431
HPNEURAL procedure, ID statement, 427
HPNEURAL procedure, PERFORMANCE statement, 428
HPNEURAL procedure, PROC HPNEURAL statement, 424
DATA= option, 424
DISTR= option, 425
NOPRINT option, 425
HPNEURAL procedure, TRAIN statement
MAXITER= option, 431
NUMTRIES= option, 430
OUTMODEL= option, 431
VALID= option, 431
HPNEURAL procedures, ARCHITECTURE statement, 425
HPNEURAL procedures, CODE statement, 426
HPNEURAL procedures, HIDDEN statement, 426
HPNEURAL procedures, INPUT statement, 427
HPNEURAL procedures, PARTITION statement, 428
HPNEURAL procedures, SCORE statement, 429
HPNEURAL procedures, TARGET statement, 429
HPNEURAL procedures, TRAIN statement, 430
HPNEURAL procedures, WEIGHT statement, 431
HPNLIN procedure, 441
PERFORMANCE statement, 451
PROC HPNLIN statement, 441
syntax, 441
HPNLIN procedure, BOUNDS statement, 446
HPNLIN procedure, ESTIMATE statement, 447
ALPHA= option, 447
DF= option, 447
HPNLIN procedure, MODEL statement, 447
HPNLIN procedure, PARAMETERS statement, 448
HPNLIN procedure, PERFORMANCE statement, 451
HPNLIN procedure, PREDICT statement, 451
ALPHA= option, 451
DF= option, 451
LOWER= option, 451
PRED= option, 451
PROBT= option, 451
STDERR= option, 452
TVALUE= option, 452
UPPER= option, 452
HPNLIN procedure, PROC HPNLIN statement, 441
ABSCONV option, 442
ABSFCONV option, 442
ABSFTOL option, 442
ABSGCONV option, 443
ABSGTOL option, 443
ABSTOL option, 442
ALPHA= option, 443
CORR option, 443

COV option, 443
DATA= option, 443
DF= option, 443
ECORR option, 443
ECOV option, 444
FCONV option, 444
FMTLIBXML= option, 444
FTOL option, 444
GCONV option, 444
GTOL option, 444
MAXFUNC= option, 445
MAXITER= option, 445
MAXTIME= option, 445
NOITPRINT option, 445
NOPRINT option, 445
OUT= option, 446
SINGULAR= option, 446
TECHNIQUE= option, 446
XMLFORMAT= option, 446
HPNLIN procedure, RESTRICT statement, 452
HPQLIM procedure, 475
PERFORMANCE statement, 486
syntax, 475
HPQLIM procedure, FREQ statement, 482
HPQLIM procedure, PERFORMANCE statement, 486
HPQLIM procedure, TEST statement, 487
HPQLIM procedure, WEIGHT statement, 488
HPREDUCE procedure, 517
PERFORMANCE statement, 521
PROC HPREDUCE statement, 517
REDUCE statement, 520
syntax, 517
HPREDUCE procedure, CLASS statement, 519
HPREDUCE procedure, PERFORMANCE statement, 521
HPREDUCE procedure, PROC HPREDUCE statement
CORR, 518
COV, 518
DATA= option, 518
FMTLIBXML= option, 518
NAMELEN= option, 518
NOCLPRINT option, 518
NOSUMPRINT option, 518
OUTCP=SAS-data-set<**/LIST**<(**EPS =** *number*)>>, 518
SSCP, 519
TECHNIQUE= option, 519
TIMEPRINT, 519
HPREDUCE procedure, REDUCE statement, 520
MAXEFFECTS option, 520
MAXSTEPS option, 520
MINVARIANCEINCREMENT option, 521
VAREXP option, 520
VARIANCEEXPLAINED option, 520
VARINC option, 521
HPREDUCEC procedure, PROC HPREDUCE statement, 517
HPREG procedure
FREQ statement, 548
ID statement, 548
MODEL statement, 548
OUTPUT statement, 551
PARTITION statement, 550
PERFORMANCE statement, 550
PROC HPREG statement, 545
WEIGHT statement, 553
HPREG procedure, BY statement, 546
HPREG procedure, CLASS statement, 547
SPLIT option, 30
UPCASE option, 547
HPREG procedure, ID statement, 548
HPREG procedure, MODEL statement, 548
CLB option, 548
INCLUDE option, 549
NOINT option, 549
ORDERSELECT option, 549
START option, 549
STB option, 549
TOL option, 549
VIF option, 549
HPREG procedure, OUTPUT statement, 551
DATA= option, 551
keyword= option, 552
OUT= option, 551
HPREG procedure, PARTITION statement, 550
FRACTION option, 550
ROLEVAR= option, 550
HPREG procedure, PERFORMANCE statement, 550
HPREG procedure, PROC HPREG statement, 545
ALPHA= option, 545
DATA= option, 545
FMTLIBXML= option, 545
NAMELEN= option, 546
NOCLPRINT option, 546
NOPRINT option, 546
SEED= option, 546
HPREG procedure, SELECTION statement, 550
HPREG procedure, WEIGHT statement, 553
HPREG procedures, FREQ statement, 548
HPREG procedure, CODE statement, 547
HPSAMPLE procedure, 583
CLASS Statement, 584
PERFORMANCE statement, 584
PROC HPSAMPLE statement, 583
syntax, 583
TARGET Statement, 585

VAR Statement, 585
HPSAMPLE procedure, CLASS Statement, 584
HPSAMPLE procedure, PERFORMANCE statement, 584
HPSAMPLE procedure, PROC HPSAMPLE statement, 583
HPSAMPLE procedure, TARGET Statement, 585
HPSAMPLE procedure, VAR Statement, 585
HPSEVERITY procedure, 607
syntax, 607
HPSUMMARY procedure, 720
CLASS statement, 725
FREQ statement, 726
OUTPUT statement, 726
PERFORMANCE statement, 728
PROC HPSUMMARY statement, 721
syntax, 720
TYPES statement, 728
VAR statement, 729
WAYS statement, 730
WEIGHT statement, 731
HPSUMMARY procedure, CLASS statement, 725
GROUPINTERNAL option, 725
HPSUMMARY procedure, FREQ statement, 726
frequency variable, 726
HPSUMMARY procedure, OUTPUT statement, 726
AUTONAME option, 728
OUT= option, 726
output statistic specification, 726
HPSUMMARY procedure, PERFORMANCE statement, 728
HPSUMMARY procedure, PROC HPSUMMARY statement, 721
ALLTYPES option, 722
ALLWAYS option, 722
ALPHA= option, 722
CHARTYPE= option, 722
classification variables, 725
DATA= option, 722
EXCLNPWGT option, 722
MISSING option, 722
PCTLDEF= option, 723
QMARKERS= option, 722
QMETHOD= option, 723
QNTLDEF= option, 723
statistics keywords, 724
VARDEF= option, 723
HPSUMMARY procedure, TYPES statement, 728
requests, 729
HPSUMMARY procedure, VAR statement, 729
analysis variable, 730
WEIGHT= option, 730
HPSUMMARY procedure, WAYS statement, 730
list, 731
HPSUMMARY procedure, WEIGHT statement, 731
HPTM procedure
PERFORMANCE statement, 791
HPTMINE procedure, 754
PARSE statement, 755
PERFORMANCE statement, 758
PROC HPTMINE statement, 754
SVD statement, 758
syntax, 754
HPTMINE procedure, DOC_ID statement, 754
HPTMINE procedure, PARSE statement, 755
CELLWGT= option, 756
ENTITIES= option, 756
MULTITERM= option, 756
NONG option, 756
NONOUNGROUPS option, 756
NOSTEMMING option, 756
NOTAGGING option, 756
OUTCHILD= option, 757
OUTCONFIG= option, 757
OUTPARENT= option, 757
OUTTERMS= option, 757
REDUCEF= option, 757
START= option, 757
STOP= option, 757
SYNONYM= option, 757
TERMWGT= option, 758
HPTMINE procedure, PERFORMANCE statement, 758
HPTMINE procedure, PROC HPTMINE statement, 754
DATA= option, 754
DOC= option, 754
NOPRINT option, 754
HPTMINE procedure, SVD statement, 758
K= option, 759
MAX_K= option, 759
OUTDOCPRO= option, 759
RES= option, 759
RESOLUTION= option, 759
SVDS= option, 759
SVDU= option, 759
SVDV= option, 759
TOL= option, 760
HPTMINE procedure, VAR statement, 760
HPTMINE procedure, VARIABLE statement, 760
HPTMSCORE procedure, 789
PROC HPTMSCORE statement, 790
syntax, 789
HPTMSCORE procedure, DOC_ID statement, 791
HPTMSCORE procedure, HPTMSCORE statement
CONFIG= option, 790
HPTMSCORE procedure, PERFORMANCE statement, 791

HPTMSCORE procedure, PROC HPTMSCORE statement, 790
DATA= option, 790
DOC= option, 790
NOPRINT option, 791
OUTPARENT= option, 791
SVDDOCPRO= option, 791
SVDU= option, 791
TERMS= option, 791
HPTMSCORE procedure, VAR statement, 792
HPTMSCORE procedure, VARIABLE statement, 792

ID statement, 107
High-Performance Analytics procedures, 32
HPDECIDE procedure, 179
HPIMPUTE procedure, 269
HPLOGISTIC procedure, 334
HPNEURAL procedure, 427
HPREG procedure, 548
IMPUTE statement
HPIMPUTE procedure, 269
IN= option
PROC HPDS2 statement, 204
INCLUDE option
MODEL statement (HPLOGISTIC), 338
MODEL statement (HPREG), 549
INEST= option
PROC HPSEVERITY statement, 610
INIT statement
HPCOUNTREG procedure, 148
HPQLIM procedure, 483
INIT= option
DIST statement, 617
INITSAMPLE option
PROC HPSEVERITY statement, 610
INPUT statement
HPFOREST procedure, 224
HPIMPUTE procedure, 270
HPNEURAL procedure, 427
INSTALL= option
PERFORMANCE statement (High-Performance Analytics), 39
INSTALLLOC= option
PERFORMANCE statement (High-Performance Analytics), 39
ITDETAILS option
PROC HPLOGISTIC statement, 331
ITPRINT option
HPQLIM procedure, 478
MODEL statement, 149
PROC HPCOUNTREG statement, 146
ITSELECT option
PROC HPLOGISTIC statement, 331

K= option
SVD statement, 759
keyword= option
OUTPUT statement (HPLOGISTIC), 340
OUTPUT statement (HPREG), 552

LACKFIT option
MODEL statement (HPLOGISTIC), 338
LASTGEN= option
PROC HPLSO statement, 384
LEAFFRACTION= option
PROC HPFOREST statement, 221
LEAFSIZE= option
PROC HPFOREST statement, 222
LEFTCENSORED= option
LOSS statement, 618
LEFTTRUNCATED= option
LOSS statement, 619
LINCON= option
PROC HPLSO statement, 383
LINK= option
MODEL statement (HPLOGISTIC), 338
list
WAYS statement (HPSUMMARY), 731
LISTONLY option
DIST statement, 617
LM option
TEST statement (HPQLIM), 487
LOGFREQ= option
PROC HPLSO statement, 386
LOGLEVEL= option
PROC HPLSO statement, 386
LOSS statement
HPSEVERITY procedure, 618
LOWER= option
PREDICT statement (HPNLIN), 451
LOWERB= option
PARMS statement (HPLMIXED), 292
LOWERBOUND= option
ENDOGENOUS statement (HPQLIM), 481, 484
LP solver (OPTMODEL procedure)
DECOMP= option, 80
LR option
TEST statement (HPQLIM), 487
LSCOEFFS option
SELECTION statement (High-Performance Analytics), 35

MARGINAL
OUTPUT statement (HPQLIM), 486
MAX_K= option
SVD statement, 759
MAXCLPRINT= option
PROC HPLMIXED statement, 287
MAXDEPTH= option

PROC HPFOREST statement, 222
MAXEFFECTS option
REDUCE statement, 520
MAXEFFECTS= option
SELECTION statement (High-Performance Analytics), 35
MAXFUNC= option
PROC HPLMIXED statement, 288
PROC HPLOGISTIC statement, 331
PROC HPLSO statement, 385
PROC HPNLIN statement, 445
MAXGEN= option
PROC HPLSO statement, 385
MAXITER= option
PROC HPLMIXED statement, 288
PROC HPLOGISTIC statement, 332
PROC HPNLIN statement, 445
PROC HPSEVERITY statement, 615
TRAIN statement, 431
MAXSTEPS option
REDUCE statement, 520
MAXSTEPS= option
SELECTION statement (High-Performance Analytics), 35
MAXTIME= option
PROC HPLMIXED statement, 288
PROC HPLOGISTIC statement, 332
PROC HPLSO statement, 385
PROC HPNLIN statement, 445
MAXTREES= option
PROC HPFOREST statement, 222
METABASE= option
PROC HPDECIDE statement, 178
METHOD= option
PROC HPCOUNTREG statement, 147
PROC HPLMIXED statement, 288
PROC HPQLIM statement, 480
SELECTION statement (High-Performance Analytics), 33
MILP solver (OPTMODEL procedure)
DECOMP= option, 80
MINCATSIZE= option
PROC HPFOREST statement, 222
MINEFFECTS= option
SELECTION statement (High-Performance Analytics), 35
MINUSEINSEARCH= option
PROC HPFOREST statement, 222
MINVARIANCEINCREMENT option
REDUCE statement, 521
MISSING option
CLASS statement (High-Performance Analytics), 31
PROC HPSUMMARY statement, 722
MISSING= option
PROC HPFOREST statement, 222
MIXED procedure, CLASS statement, 310
MIXED procedure, PROC HPLMIXED statement
ABSOLUTE option, 311
CONVF option, 311
CONVG option, 311
CONVH option, 311
MODEL statement
HPCOUNTREG procedure, 148
HPLMIXED procedure, 290
HPLOGISTIC procedure, 335
HPNLIN procedure, 447
HPQLIM procedure, 484
HPREG procedure, 548
MPSDATA= option
PROC HPLSO statement, 383
MULTISTART option
NLP solver (OPTMODEL procedure), 86
MULTITERM= option
PARSE statement, 756

NAMELEN= option
PROC HPLMIXED statement, 288
PROC HPLOGISTIC statement, 332
PROC HPREDUCE statement, 518
PROC HPREG statement, 546
NGLOBAL= option
PROC HPLSO statement, 385
NLINCON= option
PROC HPLSO statement, 384
NLOPTIONS statement
HPSEVERITY procedure, 620
NLP solver (OPTMODEL procedure)
MULTISTART option, 86
NNODES= option
PERFORMANCE statement (High-Performance Analytics), 39
NOCLPRINT option
PROC HPLMIXED statement, 289
PROC HPLOGISTIC statement, 332
PROC HPREDUCE statement, 518
PROC HPREG statement, 546
NOCORR option
PROC HPCORR statement, 128
NODES option
PERFOMRANCE statement (HPCOUNTREG), 150
PERFOMRANCE statement (HPQLIM), 486
NODES= option
PERFORMANCE statement (High-Performance Analytics), 39
NODESIZE= option
PROC HPFOREST statement, 222

NOINT option
MODEL statement (HPCOUNTREG), 148
MODEL statement (HPLMIXED), 291
MODEL statement (HPLOGISTIC), 339
MODEL statement (HPQLIM), 484
MODEL statement (HPREG), 549
NOITER option
PARMS statement (HPLMIXED), 293
NOITPRINT option
PROC HPLOGISTIC statement, 332
PROC HPNLIN statement, 445
NOMISS option
PROC HPCORR statement, 128
NONG option
PARSE statement, 756
NONORMALIZE option
WEIGHT statement (HPCOUNTREG), 151
WEIGHT statement (HPQLIM), 488
NONOUNGROUPS option
PARSE statement, 756
NOPRINT option
PROC HPCORR statement, 128
PROC HPCOUNTREG statement, 146, 149
PROC HPLMIXED statement, 289
PROC HPLOGISTIC statement, 332
PROC HPNEURAL statement, 425
PROC HPNLIN statement, 445
PROC HPQLIM statement, 477
PROC HPREDUCE statement, 518
PROC HPREG statement, 546
PROC HPSEVERITY statement, 611
PROC HPTMINE statement, 754
PROC HPTMSCORE statement, 791
NOPROB option
PROC HPCORR statement, 128
NORMALIZE= option
PROC HPLOGISTIC statement, 332
NOSIMPLE option
PROC HPCORR statement, 128
NOSTDERR option
PROC HPLOGISTIC statement, 333
NOSTEMMING option
PARSE statement, 756
NOSUMPRINT option
PROC HPREDUCE statement, 518
NOTAGGING option
PARSE statement, 756
NTHREADS option
PERFOMRANCE statement (HPCOUNTREG), 150
PERFOMRANCE statement (HPQLIM), 486
NTHREADS= option
PERFORMANCE statement (High-Performance Analytics), 41
NUMTRIES= option
TRAIN statement, 430

OBJECTIVE= option
PROC HPLSO statement, 384
PROC HPSEVERITY statement, 616
OBSCAT option
OUTPUT statement (HPLOGISTIC), 340
OFFSET= option
MODEL statement (HPCOUNTREG), 148
MODEL statement (HPLOGISTIC), 339
OLDPRIORVAR= option
PROC HPDECIDE statement, 179
OPTLP procedure
DECOMP= option, 80
OPTMILP procedure
DECOMP= option, 80
TUNER statement, 89
ORDER= option
CLASS statement (High-Performance Analytics), 29
CLASS statement (HPREG), 30
MODEL statement (HPLOGISTIC), 336
ORDERSELECT option
MODEL statement (HPREG), 549
OUT= option
OUTPUT statement (HPCOUNTREG), 149
OUTPUT statement (HPLOGISTIC), 340
OUTPUT statement (HPQLIM), 485
OUTPUT statement (HPREG), 551
OUTPUT statement (HPSUMMARY), 726
PROC HP4SCORE statement, 97
PROC HPCORR statement, 128
PROC HPDECIDE statement, 177
PROC HPDS2 statement, 204
PROC HPIMPUTE statement, 268
PROC HPNLIN statement, 446
OUTCHILD= option
PARSE statement, 757
OUTCONFIG= option
PARSE statement, 757
OUTCP= option
PROC HPREDUCE statement, 518
OUTDOCPRO= option
SVD statement, 759
OUTEST= option
PROC HPCOUNTREG statement, 146
PROC HPQLIM statement, 477
PROC HPSEVERITY statement, 611
OUTFIT= option
PROC HPDECIDE statement, 177
OUTMODEL= option
TRAIN statement, 431
OUTMODELINFO= option

PROC HPSEVERITY statement, 611
OUTP= option
PROC HPCORR statement, 128
OUTPARENT= option
PARSE statement, 757
PROC HPTMSCORE statement, 791
OUTPUT statement, *see* HPSUMMARY procedure
HPCOUNTREG procedure, 149
HPLOGISTIC procedure, 339
HPQLIM procedure, 485
HPREG procedure, 551
HPSUMMARY procedure, 726
output statistic specification
OUTPUT statement (HPSUMMARY), 726
OUTPUT= option
PROC HPDS2 statement, 204
OUTSTAT= option
PROC HPSEVERITY statement, 611
OUTTERMS= option
PARSE statement, 757
OUTVAR
OUTPUT statement (HPCOUNTREG), 149
OUTPUT statement (HPQLIM), 486

PARAM= option
CLASS statement (High-Performance Analytics), 31
PARAMETERS statement
HPNLIN procedure, 448
PARMS statement
HPLMIXED procedure, 291
PARMSDATA= option
PARMS statement (HPLMIXED), 293
PARSE statement
HPTMINE procedure, 755
PARTITION statement
HPNEURAL procedure, 428
HPREG procedure, 550
PCTLDEF= option
PROC HPSUMMARY statement, 723
PDATA= option
PARMS statement (HPLMIXED), 293
PERFORMANCE statement, 108
High-Performance Analytics procedures, 38
HPCORR procedure, 129
HPCOUNTREG procedure, 150
HPDECIDE procedure, 180
HPDMDB procedure, 194
HPDS2 procedure, 204
HPIMPUTE procedure, 270
HPLMIXED procedure, 293
HPLOGISTIC procedure, 341
HPLSO procedure, 386
HPNEURAL procedure, 428
HPNLIN procedure, 451
HPQLIM procedure, 486
HPREDUCE procedure, 521
HPREG procedure, 550
HPSAMPLE procedure, 584
HPSEVERITY procedure, 624
HPSUMMARY procedure, 728
HPTM procedure, 791
HPTMINE procedure, 758
POPSIZE= option
PROC HPLSO statement, 385
POSTERIORS statement
HPDECIDE procedure, 180
pred
OUTPUT statement (HPCOUNTREG), 150
PRED= option
PREDICT statement (HPNLIN), 451
PREDICT statement
HPNLIN procedure, 451
PREDICTED
OUTPUT statement (HPQLIM), 486
PREDICTED statement
HPDECIDE procedure, 180
PRIMALIN= option
PROC HPLSO statement, 384
PRIMALOUT= option
PROC HPLSO statement, 385
PRINT= option
PROC HPSEVERITY statement, 611
PRINTALL option
MODEL statement, 149
PROC HPCOUNTREG statement, 146
PROC HPQLIM statement, 477
PRINTLEVEL= option
PROC HPLSO statement, 386
PRIORVAR= option
PROC HPDECIDE statement, 179
PROB
OUTPUT statement (HPCOUNTREG), 150
PROBT= option
PREDICT statement (HPNLIN), 451
PROBZERO
OUTPUT statement (HPCOUNTREG), 150
PROC HPBIN statement, 105
COMPUTEQUANTILE option, 106
COMPUTESTATS option, 106
input data, 106
METHOD option, 106
NOPRINT, 107
NUMBIN option, 107
OUTPUT option, 107
REPLACE data, 107
PROC HPCORR statement, 127, *see* HPCORR procedure

HPCORR procedure, 127
PROC HPDECIDE statement
HPDECIDE procedure, 177
PROC HPDMDB statement, *see* HPDMDB procedure
HPDMDB procedure, 192
PROC HPDS2 statement, *see* HPDS2 procedure
HPDS2 procedure, 204
PROC HPFOREST statement
HPFOREST procedure, 221
PROC HPIMPUTE statement
HPIMPUTE procedure, 268
PROC HPLMIXED statement, *see* HPLMIXED procedure
HPLMIXED procedure, 285
PROC HPLOGISTIC statement, *see* HPLOGISTIC procedure
PROC HPLSO statement
input data set options, 383
optimization control options, 385
output data set options, 384
statement options, 382
stopping condition options, 385
technical options, 386
PROC HPNEURAL statement, *see* HPNEURAL procedure
HPNEURAL procedure, 424
PROC HPNLIN statement, *see* HPNLIN procedure
HPNLIN procedure, 441
PROC HPREDUCE statement, *see* HPREDUCE procedure
HPREDUCE procedure, 517
PROC HPREG statement, *see* HPREG procedure
HPREG procedure, 545
PROC HPSAMPLE statement, *see* HPSAMPLE procedure
HPSAMPLE procedure, 583
PROC HPSEVERITY statement, 610
PROC HPSUMMARY statement, *see* HPSUMMARY procedure
HPSUMMARY procedure, 721
PROC HPTMINE statement, *see* HPTMINE procedure
HPTMINE procedure, 754
PROC HPTMSCORE statement, *see* HPTMSCORE procedure
HPTMSCORE procedure, 790
PRODUCTION option
ENDOGENOUS statement (HPQLIM), 482, 485

QMARKERS= option
PROC HPSUMMARY statement, 722
QMETHOD= option
PROC HPSUMMARY statement, 723
QNTLDEF= option
PROC HPSUMMARY statement, 723
QPSDATA= option
PROC HPLSO statement, 384
QUIT statement, *see* HPDS2 procedure
HPDS2 procedure, 205

RANDOM statement
HPLMIXED procedure, 293
RANK option
PROC HPCORR statement, 128
REDUCE statement
HPREDUCE procedure, 520
REDUCEF= option
PARSE statement, 757
REF= option
CLASS statement (High-Performance Analytics), 29
REPEATED statement
HPLMIXED procedure, 299
requests
TYPES statement (HPSUMMARY), 729
RES= option
SVD statement, 759
RESIDUAL
OUTPUT statement (HPQLIM), 486
PROC HPDECIDE statement, 178
RESOLUTION= option
SVD statement, 759
RESTRICT statement
HPCOUNTREG procedure, 151
HPNLIN procedure, 452
HPQLIM procedure, 487
RIGHTCENSORED= option
LOSS statement, 619
RIGHTTRUNCATED= option
LOSS statement, 620
ROLE= option
PROC HPDECIDE statement, 177
ROLEVAR= option
HPREG procedure, PARTITION statement, 550
RSLB= option
PROC HPSEVERITY statement, 615
RSQUARE option
MODEL statement (HPLOGISTIC), 339
RUN CANCEL statement, *see* HPDS2 procedure
HPDS2 procedure, 205
RUN statement, *see* HPDS2 procedure
HPDS2 procedure, 205

SAVE statement
HPFOREST procedure, 225
SCALEMODEL statement
HPSEVERITY procedure, 625
SCORE statement

HPFOREST procedure, 225
HPNEURAL procedure, 429
SEED= option
PROC HPFOREST statement, 223
PROC HPLSO statement, 386
PROC HPREG statement, 546
SELECT= option
SELECTION statement (High-Performance Analytics), 35
SELECTION statement
High-Performance Analytics procedures, 32
HPLOGISTIC procedure, 341
HPREG procedure, 550
SELECTION= option
SELECTION statement (High-Performance Analytics), 37
SINGCHOL= option
PROC HPLMIXED statement, 289
PROC HPLOGISTIC statement, 333
SINGSWEEP= option
PROC HPLMIXED statement, 289
PROC HPLOGISTIC statement, 333
SINGULAR= option
PROC HPLMIXED statement, 289
PROC HPLOGISTIC statement, 333
PROC HPNLIN statement, 446
SLE= option
SELECTION statement (High-Performance Analytics), 35
SLENTRY= option
SELECTION statement (High-Performance Analytics), 35
SLS= option
SELECTION statement (High-Performance Analytics), 36
SLSTAY= option
SELECTION statement (High-Performance Analytics), 36
SOLUTION option
MODEL statement (HPLMIXED), 291
RANDOM statement (HPLMIXED), 294
SPLITSIZE= option
PROC HPFOREST statement, 223
SSCP
PROC HPREDUCE statement, 519
SSCP option
PROC HPCORR statement, 128
START option
MODEL statement (HPLOGISTIC), 339
MODEL statement (HPREG), 549
START= option
PARSE statement, 757
statistics keywords
PROC HPSUMMARY statement, 724
STB option
MODEL statement (HPREG), 549
STDERR= option
PREDICT statement (HPNLIN), 452
STOP= option
PARSE statement, 757
SELECTION statement (High-Performance Analytics), 36
STOPHORIZON= option
SELECTION statement (High-Performance Analytics), 37
SUBJECT= option
RANDOM statement (HPLMIXED), 294
REPEATED statement (HPLMIXED), 300
SVD statement
HPTMINE procedure, 758
SVDDOCPRO= option
PROC HPTMSCORE statement, 791
SVDS= option
SVD statement, 759
SVDU= option
PROC HPTMSCORE statement, 791
SVD statement, 759
SVDV= option
SVD statement, 759
SYNONYM= option
PARSE statement, 757
syntax
HP4SCORE procedure, 96
HPDECIDE procedure, 176
HPDMDB procedure, 192
HPDS2 procedure, 203
HPFOREST procedure, 220
HPIMPUTE procedure, 268
HPLOGISTIC procedure, 328
HPNLIN procedure, 441
HPREDUCE procedure, 517
HPSAMPLE procedure, 583
HPSUMMARY procedure, 720
HPTMINE procedure, 754
HPTMSCORE procedure, 789

TARGET Statement, *see* HPSAMPLE procedure
HPSAMPLE procedure, 585
TARGET statement
HPDECIDE procedure, 181
HPFOREST procedure, 225
HPNEURAL procedure, 429
TE1
OUTPUT statement (HPQLIM), 486
TE2
OUTPUT statement (HPQLIM), 486
TECHNIQUE= option
PROC HPLMIXED statement, 289

PROC HPLOGISTIC statement, 333
PROC HPNLIN statement, 446
PROC HPREDUCE statement, 519
TERMS= option
PROC HPTMSCORE statement, 791
TERMWGT= option
PARSE statement, 758
TIMEPRINT
PROC HPREDUCE statement, 519
TOL option
MODEL statement (HPREG), 549
TOL= option
SVD statement, 760
TRAIN statement
HPNEURAL procedure, 430
TRAINFRACTION= option
PROC HPFOREST statement, 223
TRAINN= option
PROC HPFOREST statement, 223
TRUNCATE= option
CLASS statement (High-Performance Analytics), 31
TRUNCATED option
ENDOGENOUS statement (HPQLIM), 481, 484
TUNER statement
OPTMILP procedure, 89
TVALUE= option
PREDICT statement (HPNLIN), 452
TYPE= option
RANDOM statement (HPLMIXED), 295
REPEATED statement (HPLMIXED), 300
TYPES statement, *see* HPSUMMARY procedure
HPSUMMARY procedure, 728

UPCASE option
CLASS statement (HPLOGISTIC), 334
CLASS statement (HPREG), 547
UPPER= option
PREDICT statement (HPNLIN), 452
UPPERB= option
PARMS statement (HPLMIXED), 293
UPPERBOUND= option
ENDOGENOUS statement (HPQLIM), 481, 484

VALID= option
TRAIN statement, 431
VALIDATEONLY option
DIST statement, 617
VAR Statement, *see* HPDMDB procedure, *see* HPSAMPLE procedure
HPDMDB procedure, 195
HPSAMPLE procedure, 585
VAR statement, 108, *see* HPSUMMARY procedure
High-Performance Analytics procedures, 41
HPCORR procedure, 129
HPSUMMARY procedure, 729
HPTMINE procedure, 760
HPTMSCORE procedure, 792
VARDEF= option
PROC HPCORR statement, 128
PROC HPSEVERITY statement, 612
PROC HPSUMMARY statement, 723
VAREXP option
REDUCE statement, 520, 521
VARIABLE statement
HPTMINE procedure, 760
HPTMSCORE procedure, 792
VARIABLES= option
PROC HPLSO statement, 384
VARIANCEEXPLAINED option
REDUCE statement, 520
VARS_TO_TRY= option
PROC HPFOREST statement, 223
VIF option
MODEL statement (HPREG), 549

WALD option
TEST statement (HPQLIM), 488
WAYS statement, *see* HPSUMMARY procedure
HPSUMMARY procedure, 730
WEIGHT Statement, *see* HPDMDB procedure
HPDMDB procedure, 195
WEIGHT statement, *see* HPSUMMARY procedure
High-Performance Analytics procedures, 41
HPCORR procedure, 130
HPLOGISTIC procedure, 342
HPNEURAL procedure, 431
HPREG procedure, 553
HPSEVERITY procedure, 626
HPSUMMARY procedure, 731
WEIGHT= option
VAR statement (HPSUMMARY), 730

XBETA
OUTPUT statement (HPCOUNTREG), 150
OUTPUT statement (HPQLIM), 486
XCONV option
PROC HPLMIXED statement, 289
XMLFORMAT= option
PROC HPNLIN statement, 446
XTOL option
PROC HPLMIXED statement, 289

ZEROMODEL statement
HPCOUNTREG procedure, 151
ZEROPROB= option
PROC HPSEVERITY statement, 615
ZGAMMA
OUTPUT statement (HPCOUNTREG), 150

Your Turn

We welcome your feedback.

- If you have comments about this book, please send them to **yourturn@sas.com**. Include the full title and page numbers (if applicable).
- If you have comments about the software, please send them to **suggest@sas.com**.

SAS® Publishing Delivers!

Whether you are new to the work force or an experienced professional, you need to distinguish yourself in this rapidly changing and competitive job market. SAS® Publishing provides you with a wide range of resources to help you set yourself apart. Visit us online at support.sas.com/bookstore.

SAS® Press

Need to learn the basics? Struggling with a programming problem? You'll find the expert answers that you need in example-rich books from SAS Press. Written by experienced SAS professionals from around the world, SAS Press books deliver real-world insights on a broad range of topics for all skill levels.

support.sas.com/saspress

SAS® Documentation

To successfully implement applications using SAS software, companies in every industry and on every continent all turn to the one source for accurate, timely, and reliable information: SAS documentation. We currently produce the following types of reference documentation to improve your work experience:

- Online help that is built into the software.
- Tutorials that are integrated into the product.
- Reference documentation delivered in HTML and PDF – **free** on the Web.
- Hard-copy books.

support.sas.com/publishing

SAS® Publishing News

Subscribe to SAS Publishing News to receive up-to-date information about all new SAS titles, author podcasts, and new Web site features via e-mail. Complete instructions on how to subscribe, as well as access to past issues, are available at our Web site.

support.sas.com/spn

sas® THE POWER TO KNOW®

SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration. Other brand and product names are trademarks of their respective companies. © 2009 SAS Institute Inc. All rights reserved. 518177_1US.0109