

SAS/OR[®] 14.1 User's Guide: Mathematical Programming The Linear Programming Solver



This document is an individual chapter from *SAS/OR® 14.1 User's Guide: Mathematical Programming*.

The correct bibliographic citation for this manual is as follows: SAS Institute Inc. 2015. *SAS/OR® 14.1 User's Guide: Mathematical Programming*. Cary, NC: SAS Institute Inc.

SAS/OR® 14.1 User's Guide: Mathematical Programming

Copyright © 2015, SAS Institute Inc., Cary, NC, USA

All Rights Reserved. Produced in the United States of America.

For a hard-copy book: No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc.

For a web download or e-book: Your use of this publication shall be governed by the terms established by the vendor at the time you acquire this publication.

The scanning, uploading, and distribution of this book via the Internet or any other means without the permission of the publisher is illegal and punishable by law. Please purchase only authorized electronic editions and do not participate in or encourage electronic piracy of copyrighted materials. Your support of others' rights is appreciated.

U.S. Government License Rights; Restricted Rights: The Software and its documentation is commercial computer software developed at private expense and is provided with RESTRICTED RIGHTS to the United States Government. Use, duplication, or disclosure of the Software by the United States Government is subject to the license terms of this Agreement pursuant to, as applicable, FAR 12.212, DFAR 227.7202-1(a), DFAR 227.7202-3(a), and DFAR 227.7202-4, and, to the extent required under U.S. federal law, the minimum restricted rights as set out in FAR 52.227-19 (DEC 2007). If FAR 52.227-19 is applicable, this provision serves as notice under clause (c) thereof and no other notice is required to be affixed to the Software or documentation. The Government's rights in Software and documentation shall be only those set forth in this Agreement.

SAS Institute Inc., SAS Campus Drive, Cary, NC 27513-2414

July 2015

SAS® and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Other brand and product names are trademarks of their respective companies.

Chapter 7

The Linear Programming Solver

Contents

Overview: LP Solver	256
Getting Started: LP Solver	256
Syntax: LP Solver	259
Functional Summary	259
LP Solver Options	260
Details: LP Solver	266
Presolve	266
Pricing Strategies for the Primal and Dual Simplex Algorithms	266
The Network Simplex Algorithm	266
The Interior Point Algorithm	267
Iteration Log for the Primal and Dual Simplex Algorithms	269
Iteration Log for the Network Simplex Algorithm	270
Iteration Log for the Interior Point Algorithm	271
Iteration Log for the Crossover Algorithm	271
Concurrent LP	272
Parallel Processing	272
Problem Statistics	272
Variable and Constraint Status	273
Irreducible Infeasible Set	274
Macro Variable _OROPTMODEL_	275
Examples: LP Solver	278
Example 7.1: Diet Problem	278
Example 7.2: Reoptimizing the Diet Problem Using BASIS=WARMSTART	280
Example 7.3: Two-Person Zero-Sum Game	289
Example 7.4: Finding an Irreducible Infeasible Set	292
Example 7.5: Using the Network Simplex Algorithm	295
Example 7.6: Migration to OPTMODEL: Generalized Networks	303
Example 7.7: Migration to OPTMODEL: Maximum Flow	307
Example 7.8: Migration to OPTMODEL: Production, Inventory, Distribution	310
Example 7.9: Migration to OPTMODEL: Shortest Path	318
References	321

Overview: LP Solver

The OPTMODEL procedure provides a framework for specifying and solving linear programs (LPs). A standard linear program has the following formulation:

$$\begin{array}{ll} \min & \mathbf{c}^T \mathbf{x} \\ \text{subject to} & \mathbf{Ax} \{ \geq, =, \leq \} \mathbf{b} \\ & \mathbf{l} \leq \mathbf{x} \leq \mathbf{u} \end{array}$$

where

- $\mathbf{x} \in \mathbb{R}^n$ is the vector of decision variables
- $\mathbf{A} \in \mathbb{R}^{m \times n}$ is the matrix of constraints
- $\mathbf{c} \in \mathbb{R}^n$ is the vector of objective function coefficients
- $\mathbf{b} \in \mathbb{R}^m$ is the vector of constraints right-hand sides (RHS)
- $\mathbf{l} \in \mathbb{R}^n$ is the vector of lower bounds on variables
- $\mathbf{u} \in \mathbb{R}^n$ is the vector of upper bounds on variables

The following LP algorithms are available in the OPTMODEL procedure:

- primal simplex algorithm
- dual simplex algorithm
- network simplex algorithm
- interior point algorithm

The primal and dual simplex algorithms implement the two-phase simplex method. In phase I, the algorithm tries to find a feasible solution. If no feasible solution is found, the LP is infeasible; otherwise, the algorithm enters phase II to solve the original LP. The network simplex algorithm extracts a network substructure, solves this using network simplex, and then constructs an advanced basis to feed to either primal or dual simplex. The interior point algorithm implements a primal-dual predictor-corrector interior point algorithm. If any of the decision variables are constrained to be integer-valued, then the relaxed version of the problem is solved.

Getting Started: LP Solver

The following example illustrates how you can use the OPTMODEL procedure to solve linear programs. Suppose you want to solve the following problem:

$$\begin{array}{llllll} \max & x_1 & + & x_2 & + & x_3 \\ \text{subject to} & 3x_1 & + & 2x_2 & - & x_3 & \leq & 1 \\ & -2x_1 & - & 3x_2 & + & 2x_3 & \leq & 1 \\ & & & x_1, & x_2, & x_3 & \geq & 0 \end{array}$$

You can use the following statements to call the OPTMODEL procedure for solving linear programs:

```
proc optmodel;
  var x{i in 1..3} >= 0;
  max f =    x[1] +    x[2] +    x[3];
  con c1: 3*x[1] + 2*x[2] -    x[3] <= 1;
  con c2: -2*x[1] - 3*x[2] + 2*x[3] <= 1;
  solve with lp / algorithm = ps presolver = none logfreq = 1;
  print x;
quit;
```

The optimal solution and the optimal objective value are displayed in [Figure 7.1](#).

Figure 7.1 Solution Summary
The OPTMODEL Procedure

Problem Summary	
Objective Sense	Maximization
Objective Function	f
Objective Type	Linear
Number of Variables	3
Bounded Above	0
Bounded Below	3
Bounded Below and Above	0
Free	0
Fixed	0
Number of Constraints	2
Linear LE (<=)	2
Linear EQ (=)	0
Linear GE (>=)	0
Linear Range	0
Constraint Coefficients	6
Performance Information	
Execution Mode	Single-Machine
Number of Threads	1

Figure 7.1 *continued*

Solution Summary	
Solver	LP
Algorithm	Primal Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	8
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	4
Presolve Time	0.00
Solution Time	0.00

[1] x
1 0
2 3
3 5

The iteration log displaying problem statistics, progress of the solution, and the optimal objective value is shown in [Figure 7.2](#).

Figure 7.2 Log

NOTE: Problem generation will use 4 threads.					
NOTE: The problem has 3 variables (0 free, 0 fixed).					
NOTE: The problem has 2 linear constraints (2 LE, 0 EQ, 0 GE, 0 range).					
NOTE: The problem has 6 linear constraint coefficients.					
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).					
NOTE: The LP presolver value NONE is applied.					
NOTE: The LP solver is called.					
NOTE: The Primal Simplex algorithm is used.					
Phase	Iteration	Objective Value	Time	Entering Variable	Leaving Variable
P 1	1	0.000000E+00	0		
P 2	2	0.000000E+00	0	x[3]	c2 (S)
P 2	3	5.000000E-01	0	x[2]	c1 (S)
P 2	4	8.000000E+00	0		
NOTE: Optimal.					
NOTE: Objective = 8.					
NOTE: The Primal Simplex solve time is 0.00 seconds.					

Syntax: LP Solver

The following statement is available in the OPTMODEL procedure:

SOLVE WITH LP *</ options>* ;

Functional Summary

Table 7.1 summarizes the list of options available for the SOLVE WITH LP statement, classified by function.

Table 7.1 Options for the LP Solver

Description	Option
Solver Options	
Specifies the type of algorithm	ALGORITHM=
Specifies the type of algorithm called after network simplex	ALGORITHM2=
Enables or disables IIS detection	IIS=
Presolve Option	
Specifies the type of presolve	PRESOLVER=
Controls the dualization of the problem	DUALIZE=
Control Options	
Specifies the feasibility tolerance	FEASTOL=
Specifies the frequency of printing solution progress	LOGFREQ=
Specifies the detail of solution progress printed in log	LOGLEVEL=
Specifies the maximum number of iterations	MAXITER=
Specifies the time limit for the optimization process	MAXTIME=
Specifies the optimality tolerance	OPTTOL=
Specifies units of CPU time or real time	TIMETYPE=
Simplex Algorithm Options	
Specifies the type of initial basis	BASIS=
Specifies the type of pricing strategy	PRICETYPE=
Specifies the queue size for determining entering variable	QUEUESIZE=
Enables or disables scaling of the problem	SCALE=
Specifies the initial seed for the random number generator	SEED=
Interior Point Algorithm Options	
Enables or disables interior crossover	CROSSOVER=
Specifies the stopping criterion based on duality gap	STOP_DG=
Specifies the stopping criterion based on dual infeasibility	STOP_DI=
Specifies the stopping criterion based on primal infeasibility	STOP_PI=

Table 7.1 (continued)

Description	Option
Decomposition Algorithm Options	
Enables decomposition algorithm and specifies general control options	DECOMP=()
Specifies options for the master problem	DECOMP_MASTER=()
Specifies options for the subproblem	DECOMP_SUBPROB=()

LP Solver Options

This section describes the options recognized by the LP solver. These options can be specified after a forward slash (/) in the SOLVE statement, provided that the LP solver is explicitly specified using a WITH clause.

If the LP solver terminates before reaching an optimal solution, an intermediate solution is available. You can access this solution by using the .sol variable suffix in the OPTMODEL procedure. See the section “[Suffixes](#)” on page 134 for details.

Solver Options

IIS=*number* | *string*

specifies whether the LP solver attempts to identify a set of constraints and variables that form an irreducible infeasible set (IIS). [Table 7.2](#) describes the valid values of the IIS= option.

Table 7.2 Values for IIS= Option

<i>number</i>	<i>string</i>	Description
0	OFF	Disables IIS detection.
1	ON	Enables IIS detection.

If an IIS is found, information about the infeasibilities can be found in the .status values of the constraints and variables. The default value of this option is OFF. See the section “[Irreducible Infeasible Set](#)” on page 274 for details about the IIS= option. See “[Suffixes](#)” on page 134 for details about the .status suffix.

ALGORITHM=*option*

SOLVER=*option*

SOL=*option*

specifies one of the following LP algorithms:

Option	Description
PRIMAL (PS)	Uses primal simplex algorithm.
DUAL (DS)	Uses dual simplex algorithm.
NETWORK (NS)	Uses network simplex algorithm.
INTERIORPOINT (IP)	Uses interior point algorithm.
CONCURRENT (CON)	Uses several different algorithms in parallel.

The valid abbreviated value for each option is indicated in parentheses. By default, the dual simplex algorithm is used.

ALGORITHM2=option

SOLVER2=option

specifies one of the following LP algorithms if **ALGORITHM=NS**:

Option	Description
PRIMAL (PS)	Uses primal simplex algorithm (after network simplex).
DUAL (DS)	Uses dual simplex algorithm (after network simplex).

The valid abbreviated value for each option is indicated in parentheses. By default, the LP solver decides which algorithm is best to use after calling the network simplex algorithm on the extracted network.

Presolve Options

PRESOLVER=number | string

specifies one of the following presolve options:

<i>number</i>	<i>string</i>	Description
-1	AUTOMATIC	Applies presolver by using default settings.
0	NONE	Disables the presolver.
1	BASIC	Performs basic presolve such as removing empty rows, columns, and fixed variables.
2	MODERATE	Performs basic presolve and applies other inexpensive presolve techniques.
3	AGGRESSIVE	Performs moderate presolve and applies other aggressive (but expensive) presolve techniques.

The default option is AUTOMATIC. See the section “[Presolve](#)” on page 266 for details.

DUALIZE=number | string

controls the dualization of the problem:

<i>number</i>	<i>string</i>	Description
-1	AUTOMATIC	The presolver uses a heuristic to decide whether to dualize the problem or not.
0	OFF	Disables dualization. The optimization problem is solved in the form that you specify.
1	ON	The presolver formulates the dual of the linear optimization problem.

Dualization is usually helpful for problems that have many more constraints than variables. You can use this option with all simplex algorithms in the SOLVE WITH LP statement, but it is most effective with the primal and dual simplex algorithms.

The default option is AUTOMATIC.

Control Options

FEASTOL= ϵ

specifies the feasibility tolerance, $\epsilon \in [1\text{E-}9, 1\text{E-}4]$, for determining the feasibility of a variable. The default value is $1\text{E-}6$.

LOGFREQ= k

PRINTFREQ= k

specifies that the printing of the solution progress to the iteration log is to occur after every k iterations. The print frequency, k , is an integer between zero and the largest four-byte signed integer, which is $2^{31} - 1$.

The value $k = 0$ disables the printing of the progress of the solution. If the primal or dual simplex algorithms are used, the default value of this option is determined dynamically according to the problem size. If the network simplex algorithm is used, the default value of this option is 10,000. If the interior point algorithm is used, the default value of this option is 1.

LOGLEVEL=*number* | *string*

PRINTLEVEL2=*number* | *string*

controls the amount of information displayed in the SAS log by the LP solver, from a short description of presolve information and summary to details at each iteration. Table 7.7 describes the valid values for this option.

Table 7.7 Values for LOGLEVEL= Option

<i>number</i>	<i>string</i>	Description
0	NONE	Turns off all solver-related messages to SAS log.
1	BASIC	Displays a solver summary after stopping.
2	MODERATE	Prints a solver summary and an iteration log by using the interval dictated by the LOGFREQ= option.
3	AGGRESSIVE	Prints a detailed solver summary and an iteration log by using the interval dictated by the LOGFREQ= option.

The default value is MODERATE.

MAXITER= k

specifies the maximum number of iterations. The value k can be any integer between one and the largest four-byte signed integer, which is $2^{31} - 1$. If you do not specify this option, the procedure does not stop based on the number of iterations performed. For network simplex, this iteration limit corresponds to the algorithm called after network simplex (either primal or dual simplex).

MAXTIME=*t*

specifies an upper limit of *t* units of time for the optimization process, including problem generation time and solution time. The value of the **TIMETYPE=** option determines the type of units used. If you do not specify the **MAXTIME=** option, the solver does not stop based on the amount of time elapsed. The value of *t* can be any positive number; the default value is the positive number that has the largest absolute value that can be represented in your operating environment.

OPTTOL= ϵ

specifies the optimality tolerance, $\epsilon \in [1\text{E-}9, 1\text{E-}4]$, for declaring optimality. The default value is $1\text{E-}6$.

TIMETYPE=*number* | *string*

specifies the units of time used by the **MAXTIME=** option and reported by the **PRESOLVE_TIME** and **SOLUTION_TIME** terms in the **_OROPTMODEL_** macro variable. Table 7.8 describes the valid values of the **TIMETYPE=** option.

Table 7.8 Values for **TIMETYPE=** Option

<i>number</i>	<i>string</i>	Description
0	CPU	Specifies units of CPU time.
1	REAL	Specifies units of real time.

The “Optimization Statistics” table, an output of the **OPTMODEL** procedure if you specify **PRINT-LEVEL=2** in the **PROC OPTMODEL** statement, also includes the same time units for Presolver Time and Solver Time. The other times (such as Problem Generation Time) in the “Optimization Statistics” table are also in the same units.

The default value of the **TIMETYPE=** option depends on the algorithm used and on various options. When the solver is used with distributed or multithreaded processing, then by default **TIMETYPE=REAL**. Otherwise, by default **TIMETYPE=CPU**. Table 7.9 describes the detailed logic for determining the default; the first context in the table that applies determines the default value. The **NTHREADS=** and **NODES=** options are specified in the **PERFORMANCE** statement of the **OPTMODEL** procedure. For more information about the **NTHREADS=** and **NODES=** options, see the section “**PERFORMANCE Statement**” on page 21 in Chapter 4, “**Shared Concepts and Topics**.”

Table 7.9 Default Value for **TIMETYPE=** Option

Context	Default
Solver is invoked in an OPTMODEL COFOR loop	REAL
NODES= value is nonzero for the decomposition algorithm	REAL
NTHREADS= value is greater than 1 and NODES=0 for the decomposition algorithm	REAL
NTHREADS= value is greater than 1 and ALGORITHM=IP or ALGORITHM=CON	REAL
Otherwise CPU	

Simplex Algorithm Options

BASIS=*number* | *string*

specifies the following options for generating an initial basis:

<i>number</i>	<i>string</i>	Description
0	CRASH	Generate an initial basis by using crash techniques (Maros 2003). The procedure creates a triangular basic matrix consisting of both decision variables and slack variables.
1	SLACK	Generate an initial basis by using all slack variables.
2	WARMSTART	Start the primal and dual simplex algorithms with the available basis.

The default option is determined automatically based on the problem structure. For network simplex, this option has no effect.

PRICETYPE=*number* | *string*

specifies one of the following pricing strategies for the primal and dual simplex algorithms:

<i>number</i>	<i>string</i>	Description
0	HYBRID	Use hybrid Devex and steepest-edge pricing strategies. Available for primal simplex algorithm only.
1	PARTIAL	Use partial pricing strategy. Optionally, you can specify QUEUESIZE =. Available for primal simplex algorithm only.
2	FULL	Use the most negative reduced cost pricing strategy.
3	DEVEX	Use Devex pricing strategy.
4	STEEPESTEDGE	Use steepest-edge pricing strategy.

The default option is determined automatically based on the problem structure. For the network simplex algorithm, this option applies only to the algorithm specified by the **ALGORITHM2**= option. See the section “Pricing Strategies for the Primal and Dual Simplex Algorithms” on page 266 for details.

QUEUESIZE=*k*

specifies the queue size, $k \in [1, n]$, where n is the number of decision variables. This queue is used for finding an entering variable in the simplex iteration. The default value is chosen adaptively based on the number of decision variables. This option is used only when **PRICETYPE**=PARTIAL.

SCALE=*number* | *string*

specifies one of the following scaling options:

<i>number</i>	<i>string</i>	Description
0	NONE	Disable scaling.
-1	AUTOMATIC	Automatically apply scaling procedure if necessary.

The default option is AUTOMATIC.

SEED=number

specifies the initial seed for the random number generator. Because the seed affects the perturbation in the simplex algorithms, the result might be a different optimal solution and a different solver path, but the effect is usually negligible. The value of *number* can be any positive integer up to the largest four-byte signed integer, which is $2^{31} - 1$. By default, SEED=100.

Interior Point Algorithm Options

CROSSOVER=number | string

specifies whether to convert the interior point solution to a basic simplex solution. The values of this option are:

<i>number</i>	<i>string</i>	Description
0	OFF	Disable crossover.
1	ON	Apply the crossover algorithm to the interior point solution.

If the interior point algorithm terminates with a solution, the crossover algorithm uses the interior point solution to create an initial basic solution. After performing primal fixing and dual fixing, the crossover algorithm calls a simplex algorithm to locate an optimal basic solution. The default value of the CROSSOVER= option is ON.

STOP_DG= δ

specifies the desired relative duality gap, $\delta \in [1\text{E-}9, 1\text{E-}4]$. This is the relative difference between the primal and dual objective function values and is the primary solution quality parameter. The default value is 1E-6. See the section “[The Interior Point Algorithm](#)” on page 267 for details.

STOP_DI= β

specifies the maximum allowed relative dual constraints violation, $\beta \in [1\text{E-}9, 1\text{E-}4]$. The default value is 1E-6. See the section “[The Interior Point Algorithm](#)” on page 267 for details.

STOP_PI= α

specifies the maximum allowed relative bound and primal constraints violation, $\alpha \in [1\text{E-}9, 1\text{E-}4]$. The default value is 1E-6. See the section “[The Interior Point Algorithm](#)” on page 267 for details.

Decomposition Algorithm Options

The following options are available for the decomposition algorithm in the LP solver. For information about the decomposition algorithm, see Chapter 15, “[The Decomposition Algorithm](#).”

DECOMP=(options)

enables the decomposition algorithm and specifies overall control options for the algorithm. For more information about this option, see Chapter 15, “[The Decomposition Algorithm](#).”

DECOMP_MASTER=(options)

specifies options for the master problem. For more information about this option, see Chapter 15, “[The Decomposition Algorithm](#).”

DECOMP_SUBPROB=(options)

specifies option for the subproblem. For more information about this option, see Chapter 15, “The Decomposition Algorithm.”

Details: LP Solver

Presolve

Presolve in the simplex LP algorithms of PROC OPTMODEL uses a variety of techniques to reduce the problem size, improve numerical stability, and detect infeasibility or unboundedness (Andersen and Andersen 1995; Gondzio 1997). During presolve, redundant constraints and variables are identified and removed. Presolve can further reduce the problem size by substituting variables. Variable substitution is a very effective technique, but it might occasionally increase the number of nonzero entries in the constraint matrix.

In most cases, using presolve is very helpful in reducing solution times. You can enable presolve at different levels or disable it by specifying the **PRESOLVER=** option.

Pricing Strategies for the Primal and Dual Simplex Algorithms

Several pricing strategies for the primal and dual simplex algorithms are available. Pricing strategies determine which variable enters the basis at each simplex pivot. These can be controlled by specifying the **PRICETYPE=** option.

The primal simplex algorithm has the following five pricing strategies:

PARTIAL	scans a queue of decision variables to find an entering variable. You can optionally specify the QUEUE SIZE= option to control the length of this queue.
FULL	uses Dantzig’s most violated reduced cost rule (Dantzig 1963). It compares the reduced cost of all decision variables, and selects the variable with the most violated reduced cost as the entering variable.
DEVEX	implements the Devex pricing strategy developed by Harris (1973).
STEEPESTEDGE	uses the steepest-edge pricing strategy developed by Forrest and Goldfarb (1992).
HYBRID	uses a hybrid of the Devex and steepest-edge pricing strategies.

The dual simplex algorithm has only three pricing strategies available: **FULL**, **DEVEX**, and **STEEPESTEDGE**.

The Network Simplex Algorithm

The network simplex algorithm in PROC OPTMODEL attempts to leverage the speed of the network simplex algorithm to more efficiently solve linear programs by using the following process:

1. It heuristically extracts the largest possible network substructure from the original problem.
2. It uses the network simplex algorithm to solve for an optimal solution to this substructure.
3. It uses this solution to construct an advanced basis to warm-start either the primal or dual simplex algorithm on the original linear programming problem.

The network simplex algorithm is a specialized version of the simplex algorithm that uses spanning-tree bases to more efficiently solve linear programming problems that have a pure network form. Such LPs can be modeled using a formulation over a directed graph, as a minimum-cost flow problem. Let $G = (N, A)$ be a directed graph, where N denotes the nodes and A denotes the arcs of the graph. The decision variable x_{ij} denotes the amount of flow sent from node i to node j . The cost per unit of flow on the arcs is designated by c_{ij} , and the amount of flow sent across each arc is bounded to be within $[l_{ij}, u_{ij}]$. The demand (or supply) at each node is designated as b_i , where $b_i > 0$ denotes a supply node and $b_i < 0$ denotes a demand node. The corresponding linear programming problem is as follows:

$$\begin{aligned} \min \quad & \sum_{(i,j) \in A} c_{ij} x_{ij} \\ \text{subject to} \quad & \sum_{(i,j) \in A} x_{ij} - \sum_{(j,i) \in A} x_{ji} = b_i \quad \forall i \in N \\ & x_{ij} \leq u_{ij} \quad \forall (i,j) \in A \\ & x_{ij} \geq l_{ij} \quad \forall (i,j) \in A. \end{aligned}$$

The network simplex algorithm used in PROC OPTMODEL is the primal network simplex algorithm. This algorithm finds the optimal primal feasible solution and a dual solution that satisfies complementary slackness. Sometimes the directed graph G is disconnected. In this case, the problem can be decomposed into its weakly connected components, and each minimum-cost flow problem can be solved separately. After solving each component, the optimal basis for the network substructure is augmented with the non-network variables and constraints from the original problem. This advanced basis is then used as a starting point for the primal or dual simplex method. The solver automatically selects the algorithm to use after network simplex. However, you can override this selection with the `ALGORITHM2=` option.

The network simplex algorithm can be more efficient than the other algorithms on problems that have a large network substructure. The size of this network structure can be seen in the log.

The Interior Point Algorithm

The interior point LP algorithm in PROC OPTMODEL implements an infeasible primal-dual predictor-corrector interior point algorithm. To illustrate the algorithm and the concepts of duality and dual infeasibility, consider the following LP formulation (the primal):

$$\begin{aligned} \min \quad & \mathbf{c}^T \mathbf{x} \\ \text{subject to} \quad & \mathbf{Ax} \geq \mathbf{b} \\ & \mathbf{x} \geq \mathbf{0} \end{aligned}$$

The corresponding dual is as follows:

$$\begin{aligned} \max \quad & \mathbf{b}^T \mathbf{y} \\ \text{subject to} \quad & \mathbf{A}^T \mathbf{y} + \mathbf{w} = \mathbf{c} \\ & \mathbf{y} \geq \mathbf{0} \\ & \mathbf{w} \geq \mathbf{0} \end{aligned}$$

where $\mathbf{y} \in \mathbb{R}^m$ refers to the vector of dual variables and $\mathbf{w} \in \mathbb{R}^n$ refers to the vector of dual slack variables.

The dual makes an important contribution to the certificate of optimality for the primal. The primal and dual constraints combined with complementarity conditions define the first-order optimality conditions, also known as KKT (Karush-Kuhn-Tucker) conditions, which can be stated as follows:

$$\begin{aligned}
 \mathbf{Ax} - \mathbf{s} &= \mathbf{b} && \text{(Primal Feasibility)} \\
 \mathbf{A}^T \mathbf{y} + \mathbf{w} &= \mathbf{c} && \text{(Dual Feasibility)} \\
 \mathbf{W} \mathbf{X} \mathbf{e} &= \mathbf{0} && \text{(Complementarity)} \\
 \mathbf{S} \mathbf{Y} \mathbf{e} &= \mathbf{0} && \text{(Complementarity)} \\
 \mathbf{x}, \mathbf{y}, \mathbf{w}, \mathbf{s} &\geq \mathbf{0}
 \end{aligned}$$

where $\mathbf{e} \equiv (1, \dots, 1)^T$ of appropriate dimension and $\mathbf{s} \in \mathbb{R}^m$ is the vector of primal *slack* variables.

NOTE: Slack variables (the \mathbf{s} vector) are automatically introduced by the algorithm when necessary; it is therefore recommended that you not introduce any slack variables explicitly. This enables the algorithm to handle slack variables much more efficiently.

The letters \mathbf{X} , \mathbf{Y} , \mathbf{W} , and \mathbf{S} denote matrices with corresponding x , y , w , and s on the main diagonal and zero elsewhere, as in the following example:

$$\mathbf{X} \equiv \begin{bmatrix} x_1 & 0 & \cdots & 0 \\ 0 & x_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & x_n \end{bmatrix}$$

If $(\mathbf{x}^*, \mathbf{y}^*, \mathbf{w}^*, \mathbf{s}^*)$ is a solution of the previously defined system of equations representing the KKT conditions, then \mathbf{x}^* is also an optimal solution to the original LP model.

At each iteration the interior point algorithm solves a large, sparse system of linear equations as follows:

$$\begin{bmatrix} \mathbf{Y}^{-1} \mathbf{S} & \mathbf{A} \\ \mathbf{A}^T & -\mathbf{X}^{-1} \mathbf{W} \end{bmatrix} \begin{bmatrix} \Delta \mathbf{y} \\ \Delta \mathbf{x} \end{bmatrix} = \begin{bmatrix} \Xi \\ \Theta \end{bmatrix}$$

where $\Delta \mathbf{x}$ and $\Delta \mathbf{y}$ denote the vector of *search directions* in the primal and dual spaces, respectively; Θ and Ξ constitute the vector of the right-hand sides.

The preceding system is known as the reduced KKT system. The interior point algorithm uses a preconditioned quasi-minimum residual algorithm to solve this system of equations efficiently.

An important feature of the interior point algorithm is that it takes full advantage of the sparsity in the constraint matrix, thereby enabling it to efficiently solve large-scale linear programs.

The interior point algorithm works simultaneously in the primal and dual spaces. It attains optimality when both primal and dual feasibility are achieved and when complementarity conditions hold. Therefore it is of interest to observe the following four measures:

- Relative primal infeasibility measure α :

$$\alpha = \frac{\|\mathbf{Ax} - \mathbf{b} - \mathbf{s}\|_2}{\|\mathbf{b}\|_2 + 1}$$

- Relative dual infeasibility measure β :

$$\beta = \frac{\|\mathbf{c} - \mathbf{A}^T \mathbf{y} - \mathbf{w}\|_2}{\|\mathbf{c}\|_2 + 1}$$

- Relative duality gap δ :

$$\delta = \frac{|\mathbf{c}^T \mathbf{x} - \mathbf{b}^T \mathbf{y}|}{|\mathbf{c}^T \mathbf{x}| + 1}$$

- Absolute complementarity γ :

$$\gamma = \sum_{i=1}^n x_i w_i + \sum_{i=1}^m y_i s_i$$

where $\|v\|_2$ is the Euclidean norm of the vector v . These measures are displayed in the iteration log.

Iteration Log for the Primal and Dual Simplex Algorithms

The primal and dual simplex algorithms implement a two-phase simplex algorithm. Phase I finds a feasible solution, which phase II improves to an optimal solution.

When **LOGFREQ=1**, the following information is printed in the iteration log:

Algorithm	indicates which simplex method is running by printing the letter P (primal) or D (dual).
Phase	indicates whether the algorithm is in phase I or phase II of the simplex method.
Iteration	indicates the iteration number.
Objective Value	indicates the current amount of infeasibility in phase I and the primal objective value of the current solution in phase II.
Time	indicates the time elapsed (in seconds).
Entering Variable	indicates the entering pivot variable. A slack variable that enters the basis is indicated by the corresponding row name followed by "(S)". If the entering nonbasic variable has distinct and finite lower and upper bounds, then a "bound swap" can take place in the primal simplex method.
Leaving Variable	indicates the leaving pivot variable. A slack variable that leaves the basis is indicated by the corresponding row name followed by "(S)". The leaving variable is the same as the entering variable if a bound swap has taken place.

When you omit the **LOGFREQ=** option or specify a value larger than 1, only the algorithm, phase, iteration, objective value, and time information is printed in the iteration log.

The behavior of objective values in the iteration log depends on both the current phase and the chosen algorithm. In phase I, both simplex methods have artificial objective values that decrease to 0 when a feasible solution is found. For the dual simplex method, phase II maintains a dual feasible solution, so a minimization problem has increasing objective values in the iteration log. For the primal simplex method,

phase II maintains a primal feasible solution, so a minimization problem has decreasing objective values in the iteration log.

During the solution process, some elements of the LP model might be perturbed to improve performance. In this case the objective values that are printed correspond to the perturbed problem. After reaching optimality for the perturbed problem, the LP solver solves the original problem by switching from the primal simplex method to the dual simplex method (or from the dual simplex method to the primal simplex method). Because the problem might be perturbed again, this process can result in several changes between the two algorithms.

Iteration Log for the Network Simplex Algorithm

After finding the embedded network and formulating the appropriate relaxation, the network simplex algorithm uses a primal network simplex algorithm. In the case of a connected network, with one (weakly connected) component, the log will show the progress of the simplex algorithm. The following information is displayed in the iteration log:

Iteration	indicates the iteration number.
PrimalObj	indicates the primal objective value of the current solution.
Primal Infeas	indicates the maximum primal infeasibility of the current solution.
Time	indicates the time spent on the current component by network simplex.

The frequency of the simplex iteration log is controlled by the **LOGFREQ=** option. The default value of the **LOGFREQ=** option is 10,000.

If the network relaxation is disconnected, the information in the iteration log shows progress at the component level. The following information is displayed in the iteration log:

Component	indicates the component number being processed.
Nodes	indicates the number of nodes in this component.
Arcs	indicates the number of arcs in this component.
Iterations	indicates the number of simplex iterations needed to solve this component.
Time	indicates the time spent so far in network simplex.

The frequency of the component iteration log is controlled by the **LOGFREQ=** option. In this case, the default value of the **LOGFREQ=** option is determined by the size of the network.

The **LOGLEVEL=** option adjusts the amount of detail shown. By default, **LOGLEVEL=MODERATE** and reports as in the preceding description. If **LOGLEVEL=NONE**, no information is shown. If **LOGLEVEL=BASIC**, the only information shown is a summary of the network relaxation and the time spent solving the relaxation. If **LOGLEVEL=AGGRESSIVE**, in the case of one component, the log displays as in the preceding description; in the case of multiple components, for each component, a separate simplex iteration log is displayed.

Iteration Log for the Interior Point Algorithm

The interior point algorithm implements an infeasible primal-dual predictor-corrector interior point algorithm. The following information is displayed in the iteration log:

Iter	indicates the iteration number
Complement	indicates the (absolute) complementarity
Duality Gap	indicates the (relative) duality gap
Primal Infeas	indicates the (relative) primal infeasibility measure
Bound Infeas	indicates the (relative) bound infeasibility measure
Dual Infeas	indicates the (relative) dual infeasibility measure
Time	indicates the time elapsed (in seconds).

If the sequence of solutions converges to an optimal solution of the problem, you should see all columns in the iteration log converge to zero or very close to zero. If they do not, it can be the result of insufficient iterations being performed to reach optimality. In this case, you might need to increase the value specified in the option `MAXITER=` or `MAXTIME=`. If the complementarity and/or the duality gap do not converge, the problem might be infeasible or unbounded. If the infeasibility columns do not converge, the problem might be infeasible.

Iteration Log for the Crossover Algorithm

The crossover algorithm takes an optimal solution from the interior point algorithm and transforms it into an optimal basic solution. The iterations of the crossover algorithm are similar to simplex iterations; this similarity is reflected in the format of the iteration logs.

When `LOGFREQ=1`, the following information is printed in the iteration log:

Phase	indicates whether the primal crossover (PC) or dual crossover (DC) technique is used.
Iteration	indicates the iteration number.
Objective Value	indicates the total amount by which the superbasic variables are off their bound. This value decreases to 0 as the crossover algorithm progresses.
Time	indicates the time elapsed (in seconds).
Entering Variable	indicates the entering pivot variable. A slack variable that enters the basis is indicated by the corresponding row name followed by "(S)".
Leaving Variable	indicates the leaving pivot variable. A slack variable that leaves the basis is indicated by the corresponding row name followed by "(S)".

When you omit the `LOGFREQ=` option or specify a value greater than 1, only the phase, iteration, objective value, and time information are printed in the iteration log.

After all the superbasic variables have been eliminated, the crossover algorithm continues with regular primal or dual simplex iterations.

Concurrent LP

The `ALGORITHM=CON` option starts several different linear optimization algorithms in parallel in a single-machine mode. The LP solver automatically determines which algorithms to run and how many threads to assign to each algorithm. If sufficient resources are available, the solver runs all four standard algorithms. When the first algorithm finishes, the LP solver returns the results from that algorithm and terminates any other algorithms that are still running. If you specify a value of `DETERMINISTIC` for the `PARALLELMODE=` option in the `PERFORMANCE` statement in the `OPTMODEL` procedure, the algorithm for which the results are returned is not necessarily the one that finished first. The LP solver deterministically selects the algorithm for which the results are returned. For more information about the `PERFORMANCE` statement, see the section “[PERFORMANCE Statement](#)” on page 21. Regardless of which mode (deterministic or nondeterministic) is in effect, terminating algorithms that are still running might take a significant amount of time.

During concurrent optimization, the procedure displays the iteration log for the dual simplex algorithm. See the section “[Iteration Log for the Primal and Dual Simplex Algorithms](#)” on page 269 for more information about this iteration log. Upon termination, the solver displays the iteration log for the algorithm that finishes first, unless the dual simplex algorithm finishes first. If you specify `LOGLEVEL=AGGRESSIVE`, the LP solver displays the iteration logs for all algorithms that were run concurrently.

If you specify `PRINTLEVEL=2` in the `PROC OPTMODEL` statement and `ALGORITHM=CON` in the `SOLVE WITH LP` statement, the LP solver produces an ODS table called `ConcurrentSummary`. This table contains a summary of the solution statuses of all algorithms that are run concurrently.

Parallel Processing

The interior point and concurrent LP algorithms can be run in single-machine mode (in single-machine mode, the computation is executed by multiple threads on a single computer). The decomposition algorithm can be run in either single-machine or distributed mode (in distributed mode, the computation is executed on multiple computing nodes in a distributed computing environment).

NOTE: Distributed mode requires SAS High-Performance Optimization.

You can specify options for parallel processing in the `PERFORMANCE` statement, which is documented in the section “[PERFORMANCE Statement](#)” on page 21 in Chapter 4, “[Shared Concepts and Topics](#).”

Problem Statistics

Optimizers can encounter difficulty when solving poorly formulated models. Information about data magnitude provides a simple gauge to determine how well a model is formulated. For example, a model whose constraint matrix contains one very large entry (on the order of 10^9) can cause difficulty when the remaining entries are single-digit numbers. The `PRINTLEVEL=2` option in the `OPTMODEL` procedure causes the ODS table “`ProblemStatistics`” to be generated when the LP solver is called. This table provides basic data magnitude information that enables you to improve the formulation of your models.

The example output in [Figure 7.3](#) demonstrates the contents of the ODS table “`ProblemStatistics`.”

Figure 7.3 ODS Table ProblemStatistics**The OPTMODEL Procedure**

Problem Statistics	
Number of Constraint Matrix Nonzeros	6
Maximum Constraint Matrix Coefficient	3
Minimum Constraint Matrix Coefficient	1
Average Constraint Matrix Coefficient	2.166666667
Number of Objective Nonzeros	3
Maximum Objective Coefficient	1
Minimum Objective Coefficient	1
Average Objective Coefficient	1
Number of RHS Nonzeros	2
Maximum RHS	1
Minimum RHS	1
Average RHS	1
Maximum Number of Nonzeros per Column	2
Minimum Number of Nonzeros per Column	2
Average Number of Nonzeros per Column	2
Maximum Number of Nonzeros per Row	3
Minimum Number of Nonzeros per Row	3
Average Number of Nonzeros per Row	3

Variable and Constraint Status

Upon termination of the LP solver, the .status suffix of each decision variable and constraint stores information about the status of that variable or constraint. For more information about suffixes in the OPTMODEL procedure, see the section “[Suffixes](#)” on page 134.

Variable Status

The .status suffix of a decision variable specifies the status of that decision variable. The suffix can take one of the following values:

- B basic variable
- L nonbasic variable at its lower bound
- U nonbasic variable at its upper bound
- F free variable
- A superbasic variable (a nonbasic variable that has a value strictly between its bounds)
- I LP model infeasible (all decision variables have .status equal to I)

For the interior point algorithm with **IIS= OFF**, .status is blank.

The following values can appear only if **IIS= ON**. See the section “Irreducible Infeasible Set” on page 274 for details.

I_L the lower bound of the variable is needed for the IIS

I_U the upper bound of the variable is needed for the IIS

I_F both bounds of the variable are needed for the IIS (the variable is fixed or has conflicting bounds)

Constraint Status

The .status suffix of a constraint specifies the status of the slack variable for that constraint. The suffix can take one of the following values:

B basic variable

L nonbasic variable at its lower bound

U nonbasic variable at its upper bound

F free variable

A superbasic variable (a nonbasic variable that has a value strictly between its bounds)

I LP model infeasible (all decision variables have .status equal to I)

The following values can appear only if option **IIS= ON**. See the section “Irreducible Infeasible Set” on page 274 for details.

I_L the “GE” (\geq) condition of the constraint is needed for the IIS

I_U the “LE” (\leq) condition of the constraint is needed for the IIS

I_F both conditions of the constraint are needed for the IIS (the constraint is an equality or a range constraint with conflicting bounds)

Irreducible Infeasible Set

For a linear programming problem, an irreducible infeasible set (IIS) is an infeasible subset of constraints and variable bounds that will become feasible if any single constraint or variable bound is removed. It is possible to have more than one IIS in an infeasible LP. Identifying an IIS can help isolate the structural infeasibility in an LP.

The presolver in the LP algorithms can detect infeasibility, but it identifies only the variable bound or constraint that triggers the infeasibility.

The **IIS=ON** option directs the LP solver to search for an IIS in a specified LP. You should specify the **OPTMODEL** option **PRESOLVER=NONE** when you specify **IIS=ON**; otherwise the IIS results can be incomplete. The LP solver does not apply the LP presolver to the problem during the IIS search. If the LP solver detects an IIS, it updates the .status suffix of the decision variables and constraints, and then it stops. The number of iterations that are reported in the macro variable and the ODS table is the total number of

simplex iterations. This total includes the initial LP solve and all subsequent iterations during the constraint deletion phase.

The `IIS=` option can add special values to the `.status` suffixes of variables and constraints. (For more information, see the section “[Variable and Constraint Status](#)” on page 273.) For constraints, a status of “`I_L`”, “`I_U`”, or “`I_F`” indicates that the “`GE`” (\geq), “`LE`” (\leq), or “`EQ`” ($=$) constraint, respectively, is part of the IIS. For range constraints, a status of “`I_L`” or “`I_U`” indicates that the lower or upper bound, respectively, of the constraint is needed for the IIS, and “`I_F`” indicates that the bounds in the constraint are conflicting. For variables, a status of “`I_L`”, “`I_U`”, or “`I_F`” indicates that the lower, upper, or both bounds, respectively, of the variable are needed for the IIS. From this information, you can identify both the names of the constraints (variables) in the IIS and the corresponding bound where infeasibility occurs.

Making any one of the constraints or variable bounds in the IIS nonbinding removes the infeasibility from the IIS. In some cases, changing a right-hand side or bound by a finite amount removes the infeasibility. However, the only way to guarantee removal of the infeasibility is to set the appropriate right-hand side or bound to ∞ or $-\infty$. Because it is possible for an LP to have multiple irreducible infeasible sets, simply removing the infeasibility from one set might not make the entire problem feasible. To make the entire problem feasible, you can specify `IIS=ON` and rerun the LP solver after removing the infeasibility from an IIS. Repeating this process until the LP solver no longer detects an IIS results in a feasible problem. This approach to infeasibility repair can produce different end problems depending on which right-hand sides and bounds you choose to relax.

The `IIS=` option in the LP solver uses two different methods to identify an IIS:

1. Based on the result of the initial solve, the *sensitivity filter* removes several constraints and variable bounds immediately while still maintaining infeasibility. This phase is quick and dramatically reduces the size of the IIS.
2. Next, the *deletion filter* removes each remaining constraint and variable bound one by one to check which of them are needed to obtain an infeasible system. This second phase is more time consuming, but it ensures that the IIS set that the LP solver returns is indeed irreducible. The progress of the deletion filter is reported at regular intervals. The sensitivity filter might be called again during the deletion filter to improve performance.

See [Example 7.4](#) for an example that demonstrates the use of the `IIS=` option in locating and removing infeasibilities.

Macro Variable `_OROPTMODEL_`

The `OPTMODEL` procedure always creates and initializes a SAS macro called `_OROPTMODEL_`. This variable contains a character string. After each `PROC OROPTMODEL` run, you can examine this macro by specifying `%put &_OROPTMODEL_;` and check the execution of the most recently invoked solver from the value of the macro variable. The various terms of the variable after the LP solver is called are interpreted as follows.

STATUS

indicates the solver status at termination. It can take one of the following values:

OK	The solver terminated normally.
SYNTAX_ERROR	Incorrect syntax was used.
DATA_ERROR	The input data were inconsistent.
OUT_OF_MEMORY	Insufficient memory was allocated to the procedure.
IO_ERROR	A problem occurred in reading or writing data.
SEMANTIC_ERROR	An evaluation error, such as an invalid operand type, occurred.
ERROR	The status cannot be classified into any of the preceding categories.

ALGORITHM

indicates the algorithm that produces the solution data in the macro variable. This term appears only when STATUS=OK. It can take one of the following values:

PS	The primal simplex algorithm produced the solution data.
DS	The dual simplex algorithm produced the solution data.
NS	The network simplex algorithm produced the solution data.
IP	The interior point algorithm produced the solution data.
DECOMP	The decomposition algorithm produced the solution data.

When you run algorithms concurrently (**ALGORITHM=CON**), this term indicates which algorithm is the first to terminate.

SOLUTION_STATUS

indicates the solution status at termination. It can take one of the following values:

OPTIMAL	The solution is optimal.
CONDITIONAL_OPTIMAL	The solution is optimal, but some infeasibilities (primal, dual or bound) exceed tolerances due to scaling or pre-processing.
FEASIBLE	The problem is feasible.
INFEASIBLE	The problem is infeasible.
UNBOUNDED	The problem is unbounded.
INFEASIBLE_OR_UNBOUNDED	The problem is infeasible or unbounded.
BAD_PROBLEM_TYPE	The problem type is unsupported by the solver.
ITERATION_LIMIT_REACHED	The maximum allowable number of iterations was reached.
TIME_LIMIT_REACHED	The solver reached its execution time limit.
FUNCTION_CALL_LIMIT_REACHED	The solver reached its limit on function evaluations.
INTERRUPTED	The solver was interrupted externally.
FAILED	The solver failed to converge, possibly due to numerical issues.

When SOLUTION_STATUS has a value of OPTIMAL, CONDITIONAL_OPTIMAL, ITERATION_LIMIT_REACHED, or TIME_LIMIT_REACHED, all terms of the _OROPTMODEL_ macro variable are present; for other values of SOLUTION_STATUS, some terms do not appear.

OBJECTIVE

indicates the objective value obtained by the solver at termination.

PRIMAL_INFEASIBILITY

indicates, for the primal simplex and dual simplex algorithms, the maximum (absolute) violation of the primal constraints by the primal solution. For the interior point algorithm, this term indicates the relative violation of the primal constraints by the primal solution.

DUAL_INFEASIBILITY

indicates, for the primal simplex and dual simplex algorithms, the maximum (absolute) violation of the dual constraints by the dual solution. For the interior point algorithm, this term indicates the relative violation of the dual constraints by the dual solution.

BOUND_INFEASIBILITY

indicates, for the primal simplex and dual simplex algorithms, the maximum (absolute) violation of the lower or upper bounds by the primal solution. For the interior point algorithm, this term indicates the relative violation of the lower or upper bounds by the primal solution.

DUALITY_GAP

indicates the (relative) duality gap. This term appears only if the option **ALGORITHM=INTERIORPOINT** is specified in the SOLVE statement.

COMPLEMENTARITY

indicates the (absolute) complementarity. This term appears only if the option **ALGORITHM=INTERIORPOINT** is specified in the SOLVE statement.

ITERATIONS

indicates the number of iterations taken to solve the problem. When the network simplex **algorithm** is used, this term indicates the number of network simplex iterations taken to solve the network relaxation. When crossover is enabled, this term indicates the number of interior point iterations taken to solve the problem.

ITERATIONS2

indicates the number of simplex iterations performed by the secondary algorithm. The network simplex algorithm selects the secondary algorithm automatically unless a value has been specified for the **ALGORITHM2=** option. When crossover is enabled, the secondary algorithm is selected automatically. This term appears only if the network simplex algorithm is used or if crossover is enabled.

PRESOLVE_TIME

indicates the time (in seconds) used in preprocessing.

SOLUTION_TIME

indicates the time (in seconds) taken to solve the problem, including preprocessing time.

NOTE: The time reported in PRESOLVE_TIME and SOLUTION_TIME is either CPU time or real time. The type is determined by the **TIMETYPE=** option.

When `SOLUTION_STATUS` has a value of `OPTIMAL`, `CONDITIONAL_OPTIMAL`, `ITERATION_LIMIT_REACHED`, or `TIME_LIMIT_REACHED`, all terms of the `_OROPTMODEL_` macro variable are present; for other values of `SOLUTION_STATUS`, some terms do not appear.

Examples: LP Solver

Example 7.1: Diet Problem

Consider the problem of diet optimization. There are six different foods: bread, milk, cheese, potato, fish, and yogurt. The cost and nutrition values per unit are displayed in [Table 7.14](#).

Table 7.14 Cost and Nutrition Values

	Bread	Milk	Cheese	Potato	Fish	Yogurt
Cost	2.0	3.5	8.0	1.5	11.0	1.0
Protein, g	4.0	8.0	7.0	1.3	8.0	9.2
Fat, g	1.0	5.0	9.0	0.1	7.0	1.0
Carbohydrates, g	15.0	11.7	0.4	22.6	0.0	17.0
Calories	90	120	106	97	130	180

The following SAS code creates the data set `fooddata` of [Table 7.14](#):

```
data fooddata;
  infile datalines;
  input name $ cost prot fat carb cal;
  datalines;
Bread 2 4 1 15 90
Milk 3.5 8 5 11.7 120
Cheese 8 7 9 0.4 106
Potato 1.5 1.3 0.1 22.6 97
Fish 11 8 7 0 130
Yogurt 1 9.2 1 17 180
;
```

The objective is to find a minimum-cost diet that contains at least 300 calories, not more than 10 grams of protein, not less than 10 grams of carbohydrates, and not less than 8 grams of fat. In addition, the diet should contain at least 0.5 unit of fish and no more than 1 unit of milk.

You can model the problem and solve it by using `PROC OPTMODEL` as follows:

```
proc optmodel;
  /* declare index set */
  set<str> FOOD;

  /* declare variables */
  var diet{FOOD} >= 0;

  /* objective function */
```

```

num cost{FOOD};
min f=sum{i in FOOD}cost[i]*diet[i];

/* constraints */
num prot{FOOD};
num fat{FOOD};
num carb{FOOD};
num cal{FOOD};
num min_cal, max_prot, min_carb, min_fat;
con cal_con: sum{i in FOOD}cal[i]*diet[i] >= 300;
con prot_con: sum{i in FOOD}prot[i]*diet[i] <= 10;
con carb_con: sum{i in FOOD}carb[i]*diet[i] >= 10;
con fat_con: sum{i in FOOD}fat[i]*diet[i] >= 8;

/* read parameters */
read data fooddata into FOOD=[name] cost prot fat carb cal;

/* bounds on variables */
diet['Fish'].lb = 0.5;
diet['Milk'].ub = 1.0;

/* solve and print the optimal solution */
solve with lp/logfreq=1; /* print each iteration to log */
print diet;

```

The optimal solution and the optimal objective value are displayed in [Output 7.1.1](#).

Output 7.1.1 Optimal Solution to the Diet Problem

Problem Summary	
Objective Sense	Minimization
Objective Function	f
Objective Type	Linear
Number of Variables	6
Bounded Above	0
Bounded Below	5
Bounded Below and Above	1
Free	0
Fixed	0
Number of Constraints	4
Linear LE (<=)	1
Linear EQ (=)	0
Linear GE (>=)	3
Linear Range	0
Constraint Coefficients	23

Output 7.1.1 *continued*

Performance Information	
Execution Mode	Single-Machine
Number of Threads	1
Solution Summary	
Solver	LP
Algorithm	Dual Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	12.081337881
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	6
Presolve Time	0.00
Solution Time	0.00
[1]	diet
Bread	0.000000
Cheese	0.449499
Fish	0.500000
Milk	0.053599
Potato	1.865168
Yogurt	0.000000

Example 7.2: Reoptimizing the Diet Problem Using BASIS=WARMSTART

After an LP is solved, you might want to change a set of the parameters of the LP and solve the problem again. This can be done efficiently in PROC OPTMODEL. The warm start technique uses the optimal solution of the solved LP as a starting point and solves the modified LP problem faster than it can be solved again from scratch. This example illustrates reoptimizing the diet problem described in [Example 7.1](#).

Assume the optimal solution is found by the SOLVE statement. Instead of quitting the OPTMODEL procedure, you can continue to solve several variations of the original problem.

Suppose the cost of cheese increases from 8 to 10 per unit and the cost of fish decreases from 11 to 7 per serving unit. You can change the parameters and solve the modified problem by submitting the following code:

```
cost['Cheese']=10; cost['Fish']=7;
solve with lp/presolver=none
      basis=warmstart
      algorithm=ps
      logfreq=1;
print diet;
```

Note that the primal simplex algorithm is preferred because the primal solution to the last-solved LP is still feasible for the modified problem in this case. The solutions to the original diet problem and the modified problem are shown in [Output 7.2.1](#).

Output 7.2.1 Optimal Solutions to the Original Diet Problem and the Diet Problem with Modified Objective Function

The OPTMODEL Procedure

Problem Summary	
Objective Sense	Minimization
Objective Function	f
Objective Type	Linear
Number of Variables	6
Bounded Above	0
Bounded Below	5
Bounded Below and Above	1
Free	0
Fixed	0
Number of Constraints	4
Linear LE (\leq)	1
Linear EQ ($=$)	0
Linear GE (\geq)	3
Linear Range	0
Constraint Coefficients	23
Performance Information	
Execution Mode	Single-Machine
Number of Threads	1
Solution Summary	
Solver	LP
Algorithm	Dual Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	12.081337881
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	6
Presolve Time	0.00
Solution Time	0.00

Output 7.2.1 *continued*

[1]	diet
Bread	0.000000
Cheese	0.449499
Fish	0.500000
Milk	0.053599
Potato	1.865168
Yogurt	0.000000

Problem Summary	
Objective Sense	Minimization
Objective Function	f
Objective Type	Linear
Number of Variables	6
Bounded Above	0
Bounded Below	5
Bounded Below and Above	1
Free	0
Fixed	0
Number of Constraints	4
Linear LE (\leq)	1
Linear EQ ($=$)	0
Linear GE (\geq)	3
Linear Range	0
Constraint Coefficients	23

Performance Information	
Execution Mode	Single-Machine
Number of Threads	1

Solution Summary	
Solver	LP
Algorithm	Primal Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	10.98033514
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	1
Presolve Time	0.00
Solution Time	0.00

Output 7.2.1 *continued*

[1]	diet
Bread	0.000000
Cheese	0.449499
Fish	0.500000
Milk	0.053599
Potato	1.865168
Yogurt	0.000000

The following iteration log indicates that it takes the LP solver no more iterations to solve the modified problem by using BASIS=WARMSTART, since the optimal solution to the original problem remains optimal after the objective function is changed.

Output 7.2.2 Log

NOTE: There were 6 observations read from the data set WORK.FOODDATA.
 NOTE: Problem generation will use 4 threads.
 NOTE: The problem has 6 variables (0 free, 0 fixed).
 NOTE: The problem has 4 linear constraints (1 LE, 0 EQ, 3 GE, 0 range).
 NOTE: The problem has 23 linear constraint coefficients.
 NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
 NOTE: The LP presolver value AUTOMATIC is applied.
 NOTE: The LP presolver removed 0 variables and 0 constraints.
 NOTE: The LP presolver removed 0 constraint coefficients.
 NOTE: The presolved problem has 6 variables, 4 constraints, and 23 constraint coefficients.
 NOTE: The LP solver is called.
 NOTE: The Dual Simplex algorithm is used.

		Objective	
Phase	Iteration	Value	Time
D 1	1	0.000000E+00	0
D 2	2	5.500000E+00	0
D 2	6	1.208134E+01	0

NOTE: Optimal.
 NOTE: Objective = 12.081337881.
 NOTE: The Dual Simplex solve time is 0.00 seconds.
 NOTE: Problem generation will use 4 threads.
 NOTE: The problem has 6 variables (0 free, 0 fixed).
 NOTE: The problem has 4 linear constraints (1 LE, 0 EQ, 3 GE, 0 range).
 NOTE: The problem has 23 linear constraint coefficients.
 NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
 NOTE: The LP presolver value NONE is applied.
 NOTE: The LP solver is called.
 NOTE: The Primal Simplex algorithm is used.

		Objective		Entering	Leaving
Phase	Iteration	Value	Time	Variable	Variable
P 2	1	1.098034E+01	0		

NOTE: Optimal.
 NOTE: Objective = 10.980335514.
 NOTE: The Primal Simplex solve time is 0.00 seconds.

Next, restore the original coefficients of the objective function and consider the case that you need a diet that supplies at least 150 calories. You can change the parameters and solve the modified problem by submitting the following code:

```
cost['Cheese']=8; cost['Fish']=11; cal_con.lb=150;
solve with lp/presolver=none
        basis=warmstart
        algorithm=ds
        logfreq=1;
print diet;
```


Note that the dual simplex algorithm is preferred because the dual solution to the last-solved LP is still feasible for the modified problem in this case. The solution is shown in [Output 7.2.3](#).

Output 7.2.3 Optimal Solution to the Diet Problem with Modified RHS

The OPTMODEL Procedure

Problem Summary	
Objective Sense	Minimization
Objective Function	f
Objective Type	Linear
Number of Variables	6
Bounded Above	0
Bounded Below	5
Bounded Below and Above	1
Free	0
Fixed	0
Number of Constraints	4
Linear LE (\leq)	1
Linear EQ ($=$)	0
Linear GE (\geq)	3
Linear Range	0
Constraint Coefficients	23
Performance Information	
Execution Mode	Single-Machine
Number of Threads	1
Solution Summary	
Solver	LP
Algorithm	Dual Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	9.1744131985
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	2
Presolve Time	0.00
Solution Time	0.00

Output 7.2.3 *continued*

[1]	diet
Bread	0.00000
Cheese	0.18481
Fish	0.50000
Milk	0.56440
Potato	0.14702
Yogurt	0.00000

The following iteration log indicates that it takes the LP solver just one more phase II iteration to solve the modified problem by using BASIS=WARMSTART.

Output 7.2.4 Log

NOTE: There were 6 observations read from the data set WORK.FOODDATA.
 NOTE: Problem generation will use 4 threads.
 NOTE: The problem has 6 variables (0 free, 0 fixed).
 NOTE: The problem has 4 linear constraints (1 LE, 0 EQ, 3 GE, 0 range).
 NOTE: The problem has 23 linear constraint coefficients.
 NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
 NOTE: Problem generation will use 4 threads.
 NOTE: The problem has 6 variables (0 free, 0 fixed).
 NOTE: The problem has 4 linear constraints (1 LE, 0 EQ, 3 GE, 0 range).
 NOTE: The problem has 23 linear constraint coefficients.
 NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
 NOTE: The LP presolver value NONE is applied.
 NOTE: The LP solver is called.
 NOTE: The Dual Simplex algorithm is used.

Phase	Iteration	Objective Value	Time	Entering Variable	Leaving Variable
D 2	1	8.813205E+00	0	carb_con (S)	cal_con (S)
D 2	2	9.174413E+00	0		

NOTE: Optimal.
 NOTE: Objective = 9.1744131985.
 NOTE: The Dual Simplex solve time is 0.00 seconds.

Next, restore the original constraint on calories and consider the case that you need a diet that supplies no more than 550 mg of sodium per day. The following row is appended to [Table 7.14](#).

	Bread	Milk	Cheese	Potato	Fish	Yogurt
sodium, mg	148	122	337	186	56	132

You can change the parameters, add the new constraint, and solve the modified problem by submitting the following code:

```
cal_con.lb=300;
num sod{FOOD}=[148 122 337 186 56 132];
con sodium: sum{i in FOOD}sod[i]*diet[i] <= 550;
solve with lp/presolver=none
        basis=warmstart
        logfreq=1;
print diet;
```

The solution is shown in [Output 7.2.5](#).

Output 7.2.5 Optimal Solution to the Diet Problem with Additional Constraint

The OPTMODEL Procedure

Problem Summary	
Objective Sense	Minimization
Objective Function	f
Objective Type	Linear
Number of Variables	6
Bounded Above	0
Bounded Below	5
Bounded Below and Above	1
Free	0
Fixed	0
Number of Constraints	5
Linear LE (<=)	2
Linear EQ (=)	0
Linear GE (>=)	3
Linear Range	0
Constraint Coefficients	29
Performance Information	
Execution Mode	Single-Machine
Number of Threads	1

Output 7.2.5 *continued*

Solution Summary	
Solver	LP
Algorithm	Dual Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	12.081337881
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	1
Presolve Time	0.00
Solution Time	0.00

[1]	diet
Bread	0.000000
Cheese	0.449499
Fish	0.500000
Milk	0.053599
Potato	1.865168
Yogurt	0.000000

The following iteration log indicates that it takes the LP solver no more iterations to solve the modified problem by using the BASIS=WARMSTART option, since the optimal solution to the original problem remains optimal after one more constraint is added.

Output 7.2.6 Log

```
NOTE: There were 6 observations read from the data set WORK.FOODDATA.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 6 variables (0 free, 0 fixed).
NOTE: The problem has 4 linear constraints (1 LE, 0 EQ, 3 GE, 0 range).
NOTE: The problem has 23 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 6 variables (0 free, 0 fixed).
NOTE: The problem has 5 linear constraints (2 LE, 0 EQ, 3 GE, 0 range).
NOTE: The problem has 29 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The LP presolver value NONE is applied.
NOTE: The LP solver is called.
NOTE: The Dual Simplex algorithm is used.
```

Phase	Iteration	Objective Value	Time	Entering Variable	Leaving Variable
D 2	1	1.208134E+01	0		

```
NOTE: Optimal.
NOTE: Objective = 12.081337881.
NOTE: The Dual Simplex solve time is 0.00 seconds.
```

Example 7.3: Two-Person Zero-Sum Game

Consider a two-person zero-sum game (where one person wins what the other person loses). The players make moves simultaneously, and each has a choice of actions. There is a *payoff* matrix that indicates the amount one player gives to the other under each combination of actions:

$$\text{Player I plays } i \quad \begin{matrix} & \text{Player II plays } j \\ & \begin{matrix} 1 & 2 & 3 & 4 \end{matrix} \\ \begin{pmatrix} -5 & 3 & 1 & 8 \\ 5 & 5 & 4 & 6 \\ -4 & 6 & 0 & 5 \end{pmatrix} \end{matrix}$$

If player I makes move i and player II makes move j , then player I wins (and player II loses) a_{ij} . What is the best strategy for the two players to adopt? This example is simple enough to be analyzed from observation. Suppose player I plays 1 or 3; the best response of player II is to play 1. In both cases, player I loses and player II wins. So the best action for player I is to play 2. In this case, the best response for player II is to play 3, which minimizes the loss. In this case, $(2, 3)$ is a *pure-strategy Nash equilibrium* in this game.

For illustration, consider the following mixed strategy case. Assume that player I selects i with probability p_i , $i = 1, 2, 3$, and player II selects j with probability q_j , $j = 1, 2, 3, 4$. Consider player II's problem of minimizing the maximum expected payout:

$$\min_{\mathbf{q}} \left\{ \max_i \sum_{j=1}^4 a_{ij} q_j \right\} \quad \text{subject to} \quad \sum_{j=1}^4 q_j = 1, \quad \mathbf{q} \geq 0$$

This is equivalent to

$$\begin{aligned} \min_{\mathbf{q}, v} \quad & v \quad \text{subject to} \quad \sum_{j=1}^4 a_{ij} q_j \leq v \quad \forall i \\ & \sum_{j=1}^4 q_j = 1 \\ & \mathbf{q} \geq 0 \end{aligned}$$

The problem can be transformed into a more standard format by making a simple change of variables: $x_j = q_j/v$. The preceding LP formulation now becomes

$$\begin{aligned} \min_{\mathbf{x}, v} \quad & v \quad \text{subject to} \quad \sum_{j=1}^4 a_{ij} x_j \leq 1 \quad \forall i \\ & \sum_{j=1}^4 x_j = 1/v \\ & \mathbf{x} \geq 0 \end{aligned}$$

which is equivalent to

$$\max_{\mathbf{x}} \sum_{j=1}^4 x_j \quad \text{subject to} \quad A\mathbf{x} \leq \mathbf{1}, \quad \mathbf{x} \geq 0$$

where A is the payoff matrix and $\mathbf{1}$ is a vector of 1's. It turns out that the corresponding optimization problem from player I's perspective can be obtained by solving the dual problem, which can be written as

$$\min_{\mathbf{y}} \sum_{i=1}^3 y_i \quad \text{subject to} \quad A^T \mathbf{y} \geq \mathbf{1}, \quad \mathbf{y} \geq 0$$

You can model the problem and solve it by using PROC OPTMODEL as follows:

```
proc optmodel;
  num a{1..3, 1..4}=[-5 3 1 8
                    5 5 4 6
                    -4 6 0 5];
  var x{1..4} >= 0;
  max f = sum{i in 1..4} x[i];
  con c{i in 1..3}: sum{j in 1..4} a[i,j]*x[j] <= 1;
  solve with lp / algorithm = ps presolver = none logfreq = 1;
  print x;
  print c.dual;
quit;
```

The optimal solution is displayed in [Output 7.3.1](#).

Output 7.3.1 Optimal Solutions to the Two-Person Zero-Sum Game**The OPTMODEL Procedure**

Problem Summary	
Objective Sense	Maximization
Objective Function	f
Objective Type	Linear
Number of Variables	4
Bounded Above	0
Bounded Below	4
Bounded Below and Above	0
Free	0
Fixed	0
Number of Constraints	3
Linear LE (\leq)	3
Linear EQ ($=$)	0
Linear GE (\geq)	0
Linear Range	0
Constraint Coefficients	11

Performance Information	
Execution Mode	Single-Machine
Number of Threads	1

Solution Summary	
Solver	LP
Algorithm	Primal Simplex
Objective Function	f
Solution Status	Optimal
Objective Value	0.25
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	3
Presolve Time	0.00
Solution Time	0.00

[1]	x
1	0.00
2	0.00
3	0.25
4	0.00

Output 7.3.1 *continued*

[1] c.DUAL	
1	0.00
2	0.25
3	0.00

The optimal solution $\mathbf{x}^* = (0, 0, 0.25, 0)$ with an optimal value of 0.25. Therefore the optimal strategy for player II is $\mathbf{q}^* = \mathbf{x}^*/0.25 = (0, 0, 1, 0)$. You can check the optimal solution of the dual problem by using the constraint suffix “.dual”. So $\mathbf{y}^* = (0, 0.25, 0)$ and player I’s optimal strategy is $(0, 1, 0)$. The solution is consistent with our intuition from observation.

Example 7.4: Finding an Irreducible Infeasible Set

This example demonstrates the use of the IIS= option to locate an irreducible infeasible set. Suppose you want to solve a linear program that has the following simple formulation:

$$\begin{array}{llllll}
 \min & x_1 & + & x_2 & + & x_3 & & (\text{cost}) \\
 \text{subject to} & x_1 & + & x_2 & & & \geq & 10 \quad (\text{con1}) \\
 & x_1 & & & + & x_3 & \leq & 4 \quad (\text{con2}) \\
 & 4 \leq & & x_2 & + & x_3 & \leq & 5 \quad (\text{con3}) \\
 & & & & x_1, & x_2 & \geq & 0 \\
 & & 0 & \leq & x_3 & \leq & 3
 \end{array}$$

It is easy to verify that the following three constraints (or rows) and one variable (or column) bound form an IIS for this problem:

$$\begin{array}{llll}
 x_1 & + & x_2 & \geq 10 \quad (\text{con1}) \\
 x_1 & & + & x_3 \leq 4 \quad (\text{con2}) \\
 & x_2 & + & x_3 \leq 5 \quad (\text{con3}) \\
 & & & x_3 \geq 0
 \end{array}$$

You can formulate the problem and call the LP solver by using the following statements:

```

proc optmodel presolver=none;
  /* declare variables */
  var x{1..3} >=0;

  /* upper bound on variable x[3] */
  x[3].ub = 3;

  /* objective function */
  min obj = x[1] + x[2] + x[3];

  /* constraints */
  con c1: x[1] + x[2] >= 10;

```



```

con c2: x[1] + x[3] <= 4;
con c3: 4 <= x[2] + x[3] <= 5;

solve with lp / iis = on;

print x.status;
print c1.status c2.status c3.status;

```

The notes printed in the log appear in [Output 7.4.1](#).

Output 7.4.1 Finding an IIS: Log

```

NOTE: Problem generation will use 4 threads.
NOTE: The problem has 3 variables (0 free, 0 fixed).
NOTE: The problem has 3 linear constraints (1 LE, 0 EQ, 1 GE, 1 range).
NOTE: The problem has 6 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The IIS= option is enabled.

```

Objective			
Phase	Iteration	Value	Time
P 1	1	1.400000E+01	0
P 1	3	1.000000E+00	0

```

NOTE: Applying the IIS sensitivity filter.
NOTE: The sensitivity filter removed 1 constraints and 3 variable bounds.
NOTE: Applying the IIS deletion filter.
NOTE: Processing constraints.

```

Processed	Removed	Time
0	0	0
1	0	0
2	0	0
3	0	0

```

NOTE: Processing variable bounds.

```

Processed	Removed	Time
0	0	0
1	0	0
2	0	0
3	0	0

```

NOTE: The deletion filter removed 0 constraints and 0 variable bounds.
NOTE: The IIS= option found this problem to be infeasible.
NOTE: The IIS= option found an irreducible infeasible set with 1 variables and
      3 constraints.
NOTE: The IIS solve time is 0.00 seconds.

```

The output of the PRINT statements appears in [Output 7.4.2](#). The value of the .status suffix for the variables x[1] and x[2] is missing, so the variable bounds for x[1] and x[2] are not in the IIS.

Output 7.4.2 Solution Summary, Variable Status, and Constraint Status

The OPTMODEL Procedure

Solution Summary	
Solver	LP
Algorithm	IIS
Objective Function	obj
Solution Status	Infeasible
Iterations	13
Presolve Time	0.00
Solution Time	0.00
<u>[1] x.STATUS</u>	
1	
2	
3 I_L	

The value of c3.status is I_U, which indicates that $x_2 + x_3 \leq 5$ is an element of the IIS. The original constraint is c3, a range constraint with a lower bound of 4. If you choose to remove the constraint $x_2 + x_3 \leq 5$, you can change the value of c3.ub to the largest positive number representable in your operating environment. You can specify this number by using the CONSTANT function.

The modified LP problem is specified and solved by adding the following lines to the original PROC OPTMODEL call.

```
/* relax upper bound on constraint c3 */
c3.ub = constant('BIG');

solve with lp / iis = on;
```

Because one element of the IIS has been removed, the modified LP problem should no longer contain the infeasible set. Due to the size of this problem, there should be no additional irreducible infeasible sets.

The notes shown in [Output 7.4.3](#) are printed to the log.

Output 7.4.3 Infeasibility Removed: Log

NOTE: Problem generation will use 4 threads.

NOTE: The problem has 3 variables (0 free, 0 fixed).

NOTE: The problem has 3 linear constraints (1 LE, 0 EQ, 2 GE, 0 range).

NOTE: The problem has 6 linear constraint coefficients.

NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).

NOTE: The IIS= option is enabled.

		Objective	
Phase	Iteration	Value	Time
P 1	1	1.400000E+01	0
P 1	3	0.000000E+00	0

NOTE: The IIS= option found this problem to be feasible.

NOTE: The IIS solve time is 0.00 seconds.


The solution summary and primal solution are displayed in [Output 7.4.4](#).

Output 7.4.4 Infeasibility Removed: Solution**The OPTMODEL Procedure**

Solution Summary	
Solver	LP
Algorithm	IIS
Objective Function	obj
Solution Status	Feasible
Iterations	3
Presolve Time	0.00
Solution Time	0.00

Example 7.5: Using the Network Simplex Algorithm

This example demonstrates how you can use the network simplex algorithm to find the minimum-cost flow in a directed graph. Consider the directed graph in [Figure 7.4](#), which appears in Ahuja, Magnanti, and Orlin (1993).

Figure 7.4 Minimum-Cost Network Flow Problem: Data

You can use the following SAS statements to create the input data sets `nodedata` and `arcdata`:

```

data nodedata;
  input _node_ $ _sd_;
  datalines;
1    10
2    20
3     0
4    -5
5     0
6     0
7   -15
8   -10
;

data arcdata;
  input _tail_ $ _head_ $ _lo_ _capac_ _cost_;
  datalines;
1    4    0    15    2
2    1    0    10    1
2    3    0    10    0
2    6    0    10    6
3    4    0     5    1
3    5    0    10    4
4    7    0    10    5
5    6    0    20    2
5    7    0    15    7
6    8    0    10    8
7    8    0    15    9
;

```

You can use the following call to PROC OPTMODEL to find the minimum-cost flow:

```
proc optmodel;
  set <str> NODES;
  num supply_demand {NODES};

  set <str,str> ARCS;
  num arcLower {ARCS};
  num arcUpper {ARCS};
  num arcCost {ARCS};

  read data arcdata into ARCS=[_tail_ _head_]
    arcLower=_lo_ arcUpper=_capac_ arcCost=_cost_;
  read data nodedata into NODES=[_node_] supply_demand=_sd_;

  var flow {<i,j> in ARCS} >= arcLower[i,j] <= arcUpper[i,j];
  min obj = sum {<i,j> in ARCS} arcCost[i,j] * flow[i,j];
  con balance {i in NODES}:
    sum {<(i),j> in ARCS} flow[i,j] - sum {<j,(i)> in ARCS} flow[j,i]
      = supply_demand[i];
  solve with lp / algorithm=ns scale=none logfreq=1;
  print flow;
quit;
%put &_OROPTMODEL_;
```

The optimal solution is displayed in [Output 7.5.1](#).

Output 7.5.1 Network Simplex Algorithm: Primal Solution Output

The OPTMODEL Procedure

Problem Summary	
Objective Sense	Minimization
Objective Function	obj
Objective Type	Linear
Number of Variables	11
Bounded Above	0
Bounded Below	0
Bounded Below and Above	11
Free	0
Fixed	0
Number of Constraints	8
Linear LE (<=)	0
Linear EQ (=)	8
Linear GE (>=)	0
Linear Range	0
Constraint Coefficients	22


Output 7.5.1 continued

Performance Information	
Execution Mode	Single-Machine
Number of Threads	1
Solution Summary	
Solver	LP
Algorithm	Network Simplex
Objective Function	obj
Solution Status	Optimal
Objective Value	270
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	8
Iterations2	0
Presolve Time	0.00
Solution Time	0.00

[1]	[2]	flow
1	4	10
2	1	0
2	3	10
2	6	10
3	4	5
3	5	5
4	7	10
5	6	0
5	7	5
6	8	10
7	8	0

The optimal solution is represented graphically in Figure 7.5.

Figure 7.5 Minimum-Cost Network Flow Problem: Optimal Solution



The iteration log is displayed in [Output 7.5.2](#).

Output 7.5.2 Log: Solution Progress

```
NOTE: There were 11 observations read from the data set WORK.ARCDATA.
NOTE: There were 8 observations read from the data set WORK.NODEDATA.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 11 variables (0 free, 0 fixed).
NOTE: The problem has 8 linear constraints (0 LE, 8 EQ, 0 GE, 0 range).
NOTE: The problem has 22 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The problem is a pure network instance; PRESOLVER=NONE is used.
NOTE: The LP presolver value NONE is applied.
NOTE: The LP solver is called.
NOTE: The Network Simplex algorithm is used.
NOTE: The network has 8 rows (100.00%), 11 columns (100.00%), and 1 component.
NOTE: The network extraction and setup time is 0.00 seconds.
```

	Primal	Primal	Dual	
Iteration	Objective	Infeasibility	Infeasibility	Time
1	0.000000E+00	2.000000E+01	8.900000E+01	0.00
2	0.000000E+00	2.000000E+01	8.900000E+01	0.00
3	5.000000E+00	1.500000E+01	8.400000E+01	0.00
4	5.000000E+00	1.500000E+01	8.300000E+01	0.00
5	7.500000E+01	1.500000E+01	8.300000E+01	0.00
6	7.500000E+01	1.500000E+01	7.900000E+01	0.00
7	1.300000E+02	1.000000E+01	7.600000E+01	0.00
8	2.700000E+02	0.000000E+00	0.000000E+00	0.00

```
NOTE: The Network Simplex solve time is 0.00 seconds.
NOTE: The total Network Simplex solve time is 0.00 seconds.
NOTE: Optimal.
NOTE: Objective = 270.
NOTE: The PROCEDURE OPTMODEL printed pages 1-2.
STATUS=OK ALGORITHM=NS SOLUTION_STATUS=OPTIMAL OBJECTIVE=270
PRIMAL_INFEASIBILITY=0 DUAL_INFEASIBILITY=0 BOUND_INFEASIBILITY=0 ITERATIONS=8
ITERATIONS2=0 PRESOLVE_TIME=0.00 SOLUTION_TIME=0.00
```

Now, suppose there is a budget on the flow that comes out of arc 2: the total arc cost of flow that comes out of arc 2 cannot exceed 50. You can use the following call to PROC OPTMODEL to find the minimum-cost flow:

```
proc optmodel;
  set <str> NODES;
  num supply_demand {NODES};

  set <str,str> ARCS;
  num arcLower {ARCS};
  num arcUpper {ARCS};
  num arcCost {ARCS};

  read data arcdata into ARCS=[_tail_ _head_]

```

```
arcLower=_lo_ arcUpper=_capac_ arcCost=_cost_;
read data nodedata into NODES=[_node_] supply_demand=_sd_;

var flow {<i,j> in ARCS} >= arcLower[i,j] <= arcUpper[i,j];
min obj = sum {<i,j> in ARCS} arcCost[i,j] * flow[i,j];
con balance {i in NODES}:
    sum {<(i),j> in ARCS} flow[i,j] - sum {<j,(i)> in ARCS} flow[j,i]
    = supply_demand[i];
con budgetOn2:
    sum {<i,j> in ARCS: i='2'} arcCost[i,j] * flow[i,j] <= 50;
solve with lp / algorithm=ns scale=none logfreq=1;
print flow;
quit;
%put &_OROPTMODEL_;
```

The optimal solution is displayed in [Output 7.5.3](#).

Output 7.5.3 Network Simplex Algorithm: Primal Solution Output

The OPTMODEL Procedure	
Problem Summary	
Objective Sense	Minimization
Objective Function	obj
Objective Type	Linear
Number of Variables	11
Bounded Above	0
Bounded Below	0
Bounded Below and Above	11
Free	0
Fixed	0
Number of Constraints	9
Linear LE (<=)	1
Linear EQ (=)	8
Linear GE (>=)	0
Linear Range	0
Constraint Coefficients	24
Performance Information	
Execution Mode	Single-Machine
Number of Threads	1


Output 7.5.3 *continued*

Solution Summary	
Solver	LP
Algorithm	Network Simplex
Objective Function	obj
Solution Status	Optimal
Objective Value	274
Primal Infeasibility	0
Dual Infeasibility	0
Bound Infeasibility	0
Iterations	7
Iterations2	2
Presolve Time	0.00
Solution Time	0.00

[1]	[2]	flow
1	4	12
2	1	2
2	3	10
2	6	8
3	4	3
3	5	7
4	7	10
5	6	2
5	7	5
6	8	10
7	8	0

The optimal solution is represented graphically in [Figure 7.6](#).

Figure 7.6 Minimum-Cost Network Flow Problem: Optimal Solution (with Budget Constraint)



The iteration log is displayed in [Output 7.5.4](#). Note that the network simplex algorithm extracts a subnetwork in this case.

Output 7.5.4 Log: Solution Progress

NOTE: There were 11 observations read from the data set WORK.ARCDATA.
 NOTE: There were 8 observations read from the data set WORK.NODEDATA.
 NOTE: Problem generation will use 4 threads.
 NOTE: The problem has 11 variables (0 free, 0 fixed).
 NOTE: The problem has 9 linear constraints (1 LE, 8 EQ, 0 GE, 0 range).
 NOTE: The problem has 24 linear constraint coefficients.
 NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
 NOTE: The LP presolver value AUTOMATIC is applied.
 NOTE: The LP presolver removed 4 variables and 4 constraints.
 NOTE: The LP presolver removed 7 constraint coefficients.
 NOTE: The presolved problem has 7 variables, 5 constraints, and 17 constraint coefficients.
 NOTE: The LP solver is called.
 NOTE: The Network Simplex algorithm is used.
 NOTE: The network has 4 rows (80.00%), 7 columns (100.00%), and 1 component.
 NOTE: The network extraction and setup time is 0.00 seconds.

	Primal	Primal	Dual	
Iteration	Objective	Infeasibility	Infeasibility	Time
1	8.015000E+01	1.006000E+01	5.500000E+01	0.00
2	1.053000E+02	5.030000E+00	5.400000E+01	0.00
3	1.053000E+02	5.030000E+00	5.400000E+01	0.00
4	1.353000E+02	3.000000E-02	4.900000E+01	0.00
5	1.356300E+02	0.000000E+00	4.700000E+01	0.00
6	1.356300E+02	0.000000E+00	0.000000E+00	0.00
7	2.700000E+02	0.000000E+00	0.000000E+00	0.00

NOTE: The Network Simplex solve time is 0.00 seconds.
 NOTE: The total Network Simplex solve time is 0.00 seconds.
 NOTE: The Dual Simplex algorithm is used.

	Objective	Entering	Leaving
Phase Iteration	Value	Time Variable	Variable
D 2 1	2.700000E+02	0	flow['5','6']
budgetOn2 (S)			
D 2 2	2.740000E+02	0	

NOTE: Optimal.
 NOTE: Objective = 274.
 NOTE: The Simplex solve time is 0.00 seconds.
 NOTE: The PROCEDURE OPTMODEL printed pages 4-5.
 STATUS=OK ALGORITHM=NS SOLUTION_STATUS=OPTIMAL OBJECTIVE=274
 PRIMAL_INFEASIBILITY=0 DUAL_INFEASIBILITY=0 BOUND_INFEASIBILITY=0 ITERATIONS=7
 ITERATIONS2=2 PRESOLVE_TIME=0.00 SOLUTION_TIME=0.00

Example 7.6: Migration to OPTMODEL: Generalized Networks

The following example shows how to use PROC OPTMODEL to solve the example “Generalized Networks: Using the EXCESS= Option” in Chapter 5, “The NETFLOW Procedure” (*SAS/OR User’s Guide: Mathematical Programming Legacy Procedures*). The input data sets are the same as in the PROC NETFLOW example.

```

title 'Generalized Networks';

data garcs;
  input _from_ $ _to_ $ _cost_ _mult_;
  datalines;
s1 d1 1 .
s1 d2 8 .
s2 d1 4 2
s2 d2 2 2
s2 d3 1 2
s3 d2 5 0.5
s3 d3 4 0.5
;

data gnodes;
  input _node_ $ _sd_ ;
  datalines;
s1 5
s2 20
s3 10
d1 -5
d2 -10
d3 -20
;

```

The following PROC OPTMODEL statements read the data sets, build the linear programming model, solve the model, and output the optimal solution to a SAS data set called GNETOUT:

```

proc optmodel;
  set <str> NODES;
  num _sd_ {NODES} init 0;
  read data gnodes into NODES=[_node_] _sd_;

  set <str,str> ARCS;
  num _lo_ {ARCS} init 0;
  num _capac_ {ARCS} init .;
  num _cost_ {ARCS};
  num _mult_ {ARCS} init 1;
  read data garcs nomiss into ARCS=[_from_ _to_] _cost_ _mult_;
  NODES = NODES union (union {<i,j> in ARCS} {i,j});

```

```

var Flow {<i,j> in ARCS} >= _lo_[i,j];
min obj = sum {<i,j> in ARCS} _cost_[i,j] * Flow[i,j];
con balance {i in NODES}: sum {<i,j> in ARCS} Flow[i,j]
    - sum {<j,i> in ARCS} _mult_[j,i] * Flow[j,i] = _sd_[i];

num infinity = constant('BIG');
/* change equality constraint to le constraint for supply nodes */
for {i in NODES: _sd_[i] > 0} balance[i].lb = -infinity;

solve;

num _supply_ {<i,j> in ARCS} = (if _sd_[i] ne 0 then _sd_[i] else .);
num _demand_ {<i,j> in ARCS} = (if _sd_[j] ne 0 then -_sd_[j] else .);
num _fcost_ {<i,j> in ARCS} = _cost_[i,j] * Flow[i,j].sol;

create data gnetout from [_from_ _to_]
    _cost_ _capac_ _lo_ _mult_ _supply_ _demand_ _flow_ = Flow _fcost_;
quit;

```

To solve a generalized network flow problem, the usual balance constraint is altered to include the arc multiplier “_mult_[i,j]” in the second sum. The balance constraint is initially declared as an equality, but to mimic the EXCESS=SUPPLY option in PROC NETFLOW, the sense of this constraint is changed to “ \leq ” by relaxing the constraint’s lower bound for supply nodes. The output data set is displayed in [Output 7.6.1](#).

Output 7.6.1 Optimal Solution with Excess Supply

Obs	_from_	_to_	_cost_	_capac_	_lo_	_mult_	_supply_	_demand_	_flow_	_fcost_
1	s1	d1	1	.	0	1.0	5	5	5	5
2	s1	d2	8	.	0	1.0	5	10	0	0
3	s2	d1	4	.	0	2.0	20	5	0	0
4	s2	d2	2	.	0	2.0	20	10	5	10
5	s2	d3	1	.	0	2.0	20	20	10	10
6	s3	d2	5	.	0	0.5	10	10	0	0
7	s3	d3	4	.	0	0.5	10	20	0	0

The log is displayed in [Output 7.6.2](#).

Output 7.6.2 OPTMODEL Log

```

NOTE: There were 6 observations read from the data set WORK.GNODES.
NOTE: There were 7 observations read from the data set WORK.GARCS.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 7 variables (0 free, 0 fixed).
NOTE: The problem has 6 linear constraints (3 LE, 3 EQ, 0 GE, 0 range).
NOTE: The problem has 14 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The OPTMODEL presolver is disabled for linear problems.
NOTE: The LP presolver value AUTOMATIC is applied.
NOTE: The LP presolver removed 2 variables and 2 constraints.
NOTE: The LP presolver removed 4 constraint coefficients.
NOTE: The presolved problem has 5 variables, 4 constraints, and 10 constraint
      coefficients.
NOTE: The LP solver is called.
NOTE: The Dual Simplex algorithm is used.

```

			Objective	
	Phase	Iteration	Value	Time
	D	1	0.000000E+00	0
	D	2	1.500000E+01	0
	D	2	2.500000E+01	0

```

NOTE: Optimal.
NOTE: Objective = 25.
NOTE: The Dual Simplex solve time is 0.00 seconds.
NOTE: The data set WORK.GNETOUT has 7 observations and 10 variables.

```

Now consider the previous example but with a slight modification to the arc multipliers, as in the PROC NETFLOW example:

```

data garcs1;
  input _from_ $ _to_ $ _cost_ _mult_;
  datalines;
s1 d1 1 0.5
s1 d2 8 0.5
s2 d1 4 .
s2 d2 2 .
s2 d3 1 .
s3 d2 5 0.5
s3 d3 4 0.5
;

```

The following PROC OPTMODEL statements are identical to the preceding example, except for the balance constraint. The balance constraint is still initially declared as an equality, but to mimic the PROC NETFLOW EXCESS=DEMAND option, the sense of this constraint is changed to “ \geq ” by relaxing the constraint’s upper bound for demand nodes.

```

proc optmodel;
  set <str> NODES;
  num _sd_ {NODES} init 0;
  read data gnodes into NODES=[_node_] _sd_;

  set <str,str> ARCS;
  num _lo_ {ARCS} init 0;
  num _capac_ {ARCS} init .;
  num _cost_ {ARCS};
  num _mult_ {ARCS} init 1;
  read data garcs1 nomiss into ARCS=[_from_ _to_] _cost_ _mult_;
  NODES = NODES union (union {<i,j> in ARCS} {i,j});

  var Flow {<i,j> in ARCS} >= _lo_[i,j];
  for {<i,j> in ARCS: _capac_[i,j] ne .} Flow[i,j].ub = _capac_[i,j];
  min obj = sum {<i,j> in ARCS} _cost_[i,j] * Flow[i,j];
  con balance {i in NODES}: sum {<(i),j> in ARCS} Flow[i,j]
    - sum {<j,(i)> in ARCS} _mult_[j,i] * Flow[j,i] = _sd_[i];

  num infinity = constant('BIG');
  /* change equality constraint to ge constraint */
  for {i in NODES: _sd_[i] < 0} balance[i].ub = infinity;

  solve;

  num _supply_ {<i,j> in ARCS} = (if _sd_[i] ne 0 then _sd_[i] else .);
  num _demand_ {<i,j> in ARCS} = (if _sd_[j] ne 0 then -_sd_[j] else .);
  num _fcost_ {<i,j> in ARCS} = _cost_[i,j] * Flow[i,j].sol;

  create data gnetout1 from [_from_ _to_]
    _cost_ _capac_ _lo_ _mult_ _supply_ _demand_ _flow_ =Flow _fcost_;
quit;

```

The output data set is displayed in [Output 7.6.3](#).

Output 7.6.3 Optimal Solution with Excess Demand

Obs	_from_	_to_	_cost_	_capac_	_lo_	_mult_	_supply_	_demand_	_flow_	_fcost_
1	s1	d1	1	.	0	0.5	5	5	5	5
2	s1	d2	8	.	0	0.5	5	10	0	0
3	s2	d1	4	.	0	1.0	20	5	0	0
4	s2	d2	2	.	0	1.0	20	10	5	10
5	s2	d3	1	.	0	1.0	20	20	15	15
6	s3	d2	5	.	0	0.5	10	10	0	0
7	s3	d3	4	.	0	0.5	10	20	10	40

The log is displayed in [Output 7.6.4](#).

Output 7.6.4 OPTMODEL Log

```

NOTE: There were 6 observations read from the data set WORK.GNODES.
NOTE: There were 7 observations read from the data set WORK.GARCS1.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 7 variables (0 free, 0 fixed).
NOTE: The problem has 6 linear constraints (0 LE, 3 EQ, 3 GE, 0 range).
NOTE: The problem has 14 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The OPTMODEL presolver is disabled for linear problems.
NOTE: The LP presolver value AUTOMATIC is applied.
NOTE: The LP presolver removed 2 variables and 2 constraints.
NOTE: The LP presolver removed 4 constraint coefficients.
NOTE: The presolved problem has 5 variables, 4 constraints, and 10 constraint
      coefficients.
NOTE: The LP solver is called.
NOTE: The Dual Simplex algorithm is used.

```

		Objective	
Phase	Iteration	Value	Time
D 1	1	0.000000E+00	0
D 2	2	4.997000E+01	0
D 2	4	7.000000E+01	0

```

NOTE: Optimal.
NOTE: Objective = 70.
NOTE: The Dual Simplex solve time is 0.00 seconds.
NOTE: The data set WORK.GNETOUT1 has 7 observations and 10 variables.
NOTE: The PROCEDURE OPTMODEL printed pages 7-8.

```

Example 7.7: Migration to OPTMODEL: Maximum Flow

The following example shows how to use PROC OPTMODEL to solve the example “Maximum Flow Problem” in Chapter 5, “The NETFLOW Procedure” (*SAS/OR User’s Guide: Mathematical Programming Legacy Procedures*). The input data set is the same as in that example.

```

title 'Maximum Flow Problem';

data arcs;
  input _from_ $ _to_ $ _cost_ _capac_;
  datalines;
S a . .
S b . .
a c 1 7
b c 2 9
a d 3 5
b d 4 8
c e 5 15
d f 6 20
e g 7 11

```

```

f g 8 6
e h 9 12
f h 10 4
g T . .
h T . .
;

```

The following PROC OPTMODEL statements read the data sets, build the linear programming model, solve the model, and output the optimal solution to a SAS data set called GOUT3:

```

proc optmodel;
  str source = 'S';
  str sink = 'T';

  set <str> NODES;
  num _supdem_ {i in NODES} = (if i in {source, sink} then . else 0);

  set <str,str> ARCS;
  num _lo_ {ARCS} init 0;
  num _capac_ {ARCS} init .;
  num _cost_ {ARCS} init 0;
  read data arcs nomiss into ARCS=[_from_ _to_] _cost_ _capac_;
  NODES = (union {<i,j> in ARCS} {i,j});

  var Flow {<i,j> in ARCS} >= _lo_[i,j];
  for {<i,j> in ARCS: _capac_[i,j] ne .} Flow[i,j].ub = _capac_[i,j];
  max obj = sum {<i,j> in ARCS: j = sink} Flow[i,j];
  con balance {i in NODES diff {source, sink}}:
    sum {<(i),j> in ARCS} Flow[i,j]
    - sum {<j,(i)> in ARCS} Flow[j,i] = _supdem_[i];

  solve;

  num _supply_ {<i,j> in ARCS} =
    (if _supdem_[i] ne 0 then _supdem_[i] else .);
  num _demand_ {<i,j> in ARCS} =
    (if _supdem_[j] ne 0 then -_supdem_[j] else .);
  num _fcost_ {<i,j> in ARCS} = _cost_[i,j] * Flow[i,j].sol;

  create data gout3 from [_from_ _to_]
    _cost_ _capac_ _lo_ _supply_ _demand_ _flow_=Flow _fcost_;
quit;

```

To solve a maximum flow problem, you solve a network flow problem that has a zero supply or demand at all nodes other than the source and sink nodes, as specified in the declaration of the `_SUPDEM_` numeric parameter and the balance constraint. The objective declaration uses the logical condition `J = SINK` to maximize the flow into the sink node. The output data set is displayed in [Output 7.7.1](#).

Output 7.7.1 Optimal Solution

Obs	from	to	cost	capac	lo	supply	demand	flow	fcost
1	S	a	0	.	0	.	.	12	0
2	S	b	0	.	0	.	.	13	0
3	a	c	1	7	0	.	.	7	7
4	b	c	2	9	0	.	.	8	16
5	a	d	3	5	0	.	.	5	15
6	b	d	4	8	0	.	.	5	20
7	c	e	5	15	0	.	.	15	75
8	d	f	6	20	0	.	.	10	60
9	e	g	7	11	0	.	.	3	21
10	f	g	8	6	0	.	.	6	48
11	e	h	9	12	0	.	.	12	108
12	f	h	10	4	0	.	.	4	40
13	g	T	0	.	0	.	.	9	0
14	h	T	0	.	0	.	.	16	0

The log is displayed in [Output 7.7.2](#).

Output 7.7.2 OPTMODEL Log

NOTE: There were 14 observations read from the data set WORK.ARCS.

NOTE: Problem generation will use 4 threads.

NOTE: The problem has 14 variables (0 free, 0 fixed).

NOTE: The problem has 8 linear constraints (0 LE, 8 EQ, 0 GE, 0 range).

NOTE: The problem has 24 linear constraint coefficients.

NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).

NOTE: The OPTMODEL presolver is disabled for linear problems.

NOTE: The problem is a pure network instance. The ALGORITHM=NETWORK option is recommended for solving problems with this structure.

NOTE: The LP presolver value AUTOMATIC is applied.

NOTE: The LP presolver removed 10 variables and 6 constraints.

NOTE: The LP presolver removed 20 constraint coefficients.

NOTE: The presolved problem has 4 variables, 2 constraints, and 4 constraint coefficients.

NOTE: The LP solver is called.

NOTE: The Dual Simplex algorithm is used.

		Objective	
Phase	Iteration	Value	Time
D 1	1	0.000000E+00	0
D 2	2	2.500000E+01	0
P 2	5	2.500000E+01	0

NOTE: Optimal.

NOTE: Objective = 25.

NOTE: The Dual Simplex solve time is 0.00 seconds.

NOTE: The data set WORK.GOUT3 has 14 observations and 9 variables.

NOTE: The PROCEDURE OPTMODEL printed pages 10-11.

Example 7.8: Migration to OPTMODEL: Production, Inventory, Distribution

The following example shows how to use PROC OPTMODEL to solve the example “Production, Inventory, Distribution Problem” in Chapter 5, “The NETFLOW Procedure” (*SAS/OR User’s Guide: Mathematical Programming Legacy Procedures*). The input data sets are the same as in that example.

```

title 'Minimum-Cost Flow Problem';
title2 'Production Planning/Inventory/Distribution';

data node0;
  input _node_ $ _supdem_ ;
  datalines;
fact1_1 1000
fact2_1 850
fact1_2 1000
fact2_2 1500
shop1_1 -900
shop2_1 -900
shop1_2 -900
shop2_2 -1450
;

data arc0;
  input _tail_ $ _head_ $ _cost_ _capac_ _lo_
        diagonal factory key_id $10. mth_made $ _name_&$17.;
  datalines;
fact1_1 f1_mar_1 127.9 500 50 19 1 production March prod f1 19 mar
fact1_1 f1_apr_1 78.6 600 50 19 1 production April prod f1 19 apl
fact1_1 f1_may_1 95.1 400 50 19 1 production May .
f1_mar_1 f1_apr_1 15 50 . 19 1 storage March .
f1_apr_1 f1_may_1 12 50 . 19 1 storage April .
f1_apr_1 f1_mar_1 28 20 . 19 1 backorder April back f1 19 apl
f1_may_1 f1_apr_1 28 20 . 19 1 backorder May back f1 19 may
f1_mar_1 f2_mar_1 11 . . 19 . f1_to_2 March .
f1_apr_1 f2_apr_1 11 . . 19 . f1_to_2 April .
f1_may_1 f2_may_1 16 . . 19 . f1_to_2 May .
f1_mar_1 shop1_1 -327.65 250 . 19 1 sales March .
f1_apr_1 shop1_1 -300 250 . 19 1 sales April .
f1_may_1 shop1_1 -285 250 . 19 1 sales May .
f1_mar_1 shop2_1 -362.74 250 . 19 1 sales March .
f1_apr_1 shop2_1 -300 250 . 19 1 sales April .
f1_may_1 shop2_1 -245 250 . 19 1 sales May .
fact2_1 f2_mar_1 88.0 450 35 19 2 production March prod f2 19 mar
fact2_1 f2_apr_1 62.4 480 35 19 2 production April prod f2 19 apl
fact2_1 f2_may_1 133.8 250 35 19 2 production May .
f2_mar_1 f2_apr_1 18 30 . 19 2 storage March .
f2_apr_1 f2_may_1 20 30 . 19 2 storage April .
f2_apr_1 f2_mar_1 17 15 . 19 2 backorder April back f2 19 apl
f2_may_1 f2_apr_1 25 15 . 19 2 backorder May back f2 19 may
f2_mar_1 f1_mar_1 10 40 . 19 . f2_to_1 March .
f2_apr_1 f1_apr_1 11 40 . 19 . f2_to_1 April .
f2_may_1 f1_may_1 13 40 . 19 . f2_to_1 May .

```

```

f2_mar_1 shop1_1 -297.4 250 . 19 2 sales March .
f2_apr_1 shop1_1 -290 250 . 19 2 sales April .
f2_may_1 shop1_1 -292 250 . 19 2 sales May .
f2_mar_1 shop2_1 -272.7 250 . 19 2 sales March .
f2_apr_1 shop2_1 -312 250 . 19 2 sales April .
f2_may_1 shop2_1 -299 250 . 19 2 sales May .
fact1_2 f1_mar_2 217.9 400 40 25 1 production March prod f1 25 mar
fact1_2 f1_apr_2 174.5 550 50 25 1 production April prod f1 25 apl
fact1_2 f1_may_2 133.3 350 40 25 1 production May .
f1_mar_2 f1_apr_2 20 40 . 25 1 storage March .
f1_apr_2 f1_may_2 18 40 . 25 1 storage April .
f1_apr_2 f1_mar_2 32 30 . 25 1 backorder April back f1 25 apl
f1_may_2 f1_apr_2 41 15 . 25 1 backorder May back f1 25 may
f1_mar_2 f2_mar_2 23 . . 25 . f1_to_2 March .
f1_apr_2 f2_apr_2 23 . . 25 . f1_to_2 April .
f1_may_2 f2_may_2 26 . . 25 . f1_to_2 May .
f1_mar_2 shop1_2 -559.76 . . 25 1 sales March .
f1_apr_2 shop1_2 -524.28 . . 25 1 sales April .
f1_may_2 shop1_2 -475.02 . . 25 1 sales May .
f1_mar_2 shop2_2 -623.89 . . 25 1 sales March .
f1_apr_2 shop2_2 -549.68 . . 25 1 sales April .
f1_may_2 shop2_2 -460.00 . . 25 1 sales May .
fact2_2 f2_mar_2 182.0 650 35 25 2 production March prod f2 25 mar
fact2_2 f2_apr_2 196.7 680 35 25 2 production April prod f2 25 apl
fact2_2 f2_may_2 201.4 550 35 25 2 production May .
f2_mar_2 f2_apr_2 28 50 . 25 2 storage March .
f2_apr_2 f2_may_2 38 50 . 25 2 storage April .
f2_apr_2 f2_mar_2 31 15 . 25 2 backorder April back f2 25 apl
f2_may_2 f2_apr_2 54 15 . 25 2 backorder May back f2 25 may
f2_mar_2 f1_mar_2 20 25 . 25 . f2_to_1 March .
f2_apr_2 f1_apr_2 21 25 . 25 . f2_to_1 April .
f2_may_2 f1_may_2 43 25 . 25 . f2_to_1 May .
f2_mar_2 shop1_2 -567.83 500 . 25 2 sales March .
f2_apr_2 shop1_2 -542.19 500 . 25 2 sales April .
f2_may_2 shop1_2 -461.56 500 . 25 2 sales May .
f2_mar_2 shop2_2 -542.83 500 . 25 2 sales March .
f2_apr_2 shop2_2 -559.19 500 . 25 2 sales April .
f2_may_2 shop2_2 -489.06 500 . 25 2 sales May .
;

```

The following PROC OPTMODEL statements read the data sets, build the linear programming model, solve the model, and output the optimal solution to SAS data sets called ARC1 and NODE2:

```

proc optmodel;
  set <str> NODES;
  num _supdem_ {NODES} init 0;
  read data node0 into NODES=[_node_] _supdem_;

  set <str,str> ARCS;
  num _lo_ {ARCS} init 0;
  num _capac_ {ARCS} init .;
  num _cost_ {ARCS};
  num diagonal {ARCS};
  num factory {ARCS};

```

```

str key_id {ARCS};
str mth_made {ARCS};
str _name_ {ARCS};
read data arc0 nomiss into ARCS=[_tail_ _head_] _lo_ _capac_ _cost_
    diagonal factory key_id mth_made _name_;
NODES = NODES union (union {<i,j> in ARCS} {i,j});

var Flow {<i,j> in ARCS} >= _lo_[i,j];
for {<i,j> in ARCS: _capac_[i,j] ne .} Flow[i,j].ub = _capac_[i,j];
min obj = sum {<i,j> in ARCS} _cost_[i,j] * Flow[i,j];
con balance {i in NODES}: sum {<(i),j> in ARCS} Flow[i,j]
    - sum {<j,(i)> in ARCS} Flow[j,i] = _supdem_[i];

num infinity = constant('BIG');
num excess = sum {i in NODES} _supdem_[i];
if (excess > 0) then do;
    /* change equality constraint to le constraint for supply nodes */
    for {i in NODES: _supdem_[i] > 0} balance[i].lb = -infinity;
end;
else if (excess < 0) then do;
    /* change equality constraint to ge constraint for demand nodes */
    for {i in NODES: _supdem_[i] < 0} balance[i].ub = infinity;
end;

solve;

num _supply_ {<i,j> in ARCS} =
    (if _supdem_[i] ne 0 then _supdem_[i] else .);
num _demand_ {<i,j> in ARCS} =
    (if _supdem_[j] ne 0 then -_supdem_[j] else .);
num _fcost_ {<i,j> in ARCS} = _cost_[i,j] * Flow[i,j].sol;

create data arc1 from [_tail_ _head_]
    _cost_ _capac_ _lo_ _name_ _supply_ _demand_ _flow_=Flow _fcost_
    _rcost_ =
    (if Flow[_tail_,_head_].rc ne 0 then Flow[_tail_,_head_].rc else .)
    _status_ = Flow.status diagonal factory key_id mth_made;
create data node2 from [_node_]
    _supdem_ = (if _supdem_[_node_] ne 0 then _supdem_[_node_] else .)
    _dual_ = balance.dual;
quit;

```

The PROC OPTMODEL statements use both single-dimensional (NODES) and multiple-dimensional (ARCS) index sets, which are populated from the corresponding data set variables in the READ DATA statements. The `_SUPDEM_`, `_LO_`, and `_CAPAC_` parameters are given initial values, and the NOMISS option in the READ DATA statement tells PROC OPTMODEL to read only the nonmissing values from the input data set. The balance constraint is initially declared as an equality, but depending on the total supply or demand, the sense of this constraint is changed to “ \leq ” or “ \geq ” by relaxing the constraint’s lower or upper bound, respectively. The ARC1 output data set contains most of the same information as in the NETFLOW example, including reduced cost, basis status, and dual values. The `_ANUMB_` and `_TNUMB_` values do not apply here.

The PROC PRINT statements are similar to the PROC NETFLOW example:

```
options ls=80 ps=54;
proc print data=arc1 heading=h width=min;
  var _tail_ _head_ _cost_ _capac_ _lo_ _name_
      _supply_ _demand_ _flow_ _fcost_;
  sum _fcost_;
run;
proc print data=arc1 heading=h width=min;
  var _rcost_ _status_ diagonal factory key_id mth_made;
run;
proc print data=node2;
run;
```

The output data sets are displayed in [Output 7.8.1](#).

Output 7.8.1 Output Data Sets

Obs	_tail_	_head_	_cost_	_capac_	_lo_	_name_	_supply_	_demand_	_flow_	_fcost_
1	fact1_1	f1_mar_1	127.90	500	50	prod f1 19 mar	1000	.	345	44125.50
2	fact1_1	f1_apr_1	78.60	600	50	prod f1 19 apl	1000	.	600	47160.00
3	fact1_1	f1_may_1	95.10	400	50		1000	.	50	4755.00
4	f1_mar_1	f1_apr_1	15.00	50	0		.	.	0	0.00
5	f1_apr_1	f1_may_1	12.00	50	0		.	.	50	600.00
6	f1_apr_1	f1_mar_1	28.00	20	0	back f1 19 apl	.	.	20	560.00
7	f1_may_1	f1_apr_1	28.00	20	0	back f1 19 may	.	.	0	0.00
8	f1_mar_1	f2_mar_1	11.00	.	0		.	.	0	0.00
9	f1_apr_1	f2_apr_1	11.00	.	0		.	.	30	330.00
10	f1_may_1	f2_may_1	16.00	.	0		.	.	100	1600.00
11	f1_mar_1	shop1_1	-327.65	250	0		.	900	155	-50785.75
12	f1_apr_1	shop1_1	-300.00	250	0		.	900	250	-75000.00
13	f1_may_1	shop1_1	-285.00	250	0		.	900	0	0.00
14	f1_mar_1	shop2_1	-362.74	250	0		.	900	250	-90685.00
15	f1_apr_1	shop2_1	-300.00	250	0		.	900	250	-75000.00
16	f1_may_1	shop2_1	-245.00	250	0		.	900	0	0.00
17	fact2_1	f2_mar_1	88.00	450	35	prod f2 19 mar	850	.	290	25520.00
18	fact2_1	f2_apr_1	62.40	480	35	prod f2 19 apl	850	.	480	29952.00
19	fact2_1	f2_may_1	133.80	250	35		850	.	35	4683.00
20	f2_mar_1	f2_apr_1	18.00	30	0		.	.	0	0.00
21	f2_apr_1	f2_may_1	20.00	30	0		.	.	15	300.00
22	f2_apr_1	f2_mar_1	17.00	15	0	back f2 19 apl	.	.	0	0.00
23	f2_may_1	f2_apr_1	25.00	15	0	back f2 19 may	.	.	0	0.00
24	f2_mar_1	f1_mar_1	10.00	40	0		.	.	40	400.00
25	f2_apr_1	f1_apr_1	11.00	40	0		.	.	0	0.00
26	f2_may_1	f1_may_1	13.00	40	0		.	.	0	0.00
27	f2_mar_1	shop1_1	-297.40	250	0		.	900	250	-74350.00
28	f2_apr_1	shop1_1	-290.00	250	0		.	900	245	-71050.00
29	f2_may_1	shop1_1	-292.00	250	0		.	900	0	0.00
30	f2_mar_1	shop2_1	-272.70	250	0		.	900	0	0.00
31	f2_apr_1	shop2_1	-312.00	250	0		.	900	250	-78000.00
32	f2_may_1	shop2_1	-299.00	250	0		.	900	150	-44850.00
33	fact1_2	f1_mar_2	217.90	400	40	prod f1 25 mar	1000	.	400	87160.00
34	fact1_2	f1_apr_2	174.50	550	50	prod f1 25 apl	1000	.	550	95975.00
35	fact1_2	f1_may_2	133.30	350	40		1000	.	40	5332.00
36	f1_mar_2	f1_apr_2	20.00	40	0		.	.	0	0.00
37	f1_apr_2	f1_may_2	18.00	40	0		.	.	0	0.00
38	f1_apr_2	f1_mar_2	32.00	30	0	back f1 25 apl	.	.	30	960.00
39	f1_may_2	f1_apr_2	41.00	15	0	back f1 25 may	.	.	15	615.00
40	f1_mar_2	f2_mar_2	23.00	.	0		.	.	0	0.00
41	f1_apr_2	f2_apr_2	23.00	.	0		.	.	0	0.00
42	f1_may_2	f2_may_2	26.00	.	0		.	.	0	0.00
43	f1_mar_2	shop1_2	-559.76	.	0		.	900	0	0.00
44	f1_apr_2	shop1_2	-524.28	.	0		.	900	0	0.00
45	f1_may_2	shop1_2	-475.02	.	0		.	900	25	-11875.50
46	f1_mar_2	shop2_2	-623.89	.	0		.	1450	455	-283869.95
47	f1_apr_2	shop2_2	-549.68	.	0		.	1450	535	-294078.80
48	f1_may_2	shop2_2	-460.00	.	0		.	1450	0	0.00

Output 7.8.1 *continued*

[illegible]

Output 7.8.1 *continued*

Obs	_rcost_	_status_	diagonal	factory	key_id	mth_made
1	.	B	19	1	production	March
2	-0.65	U	19	1	production	April
3	0.85	L	19	1	production	May
4	63.65	L	19	1	storage	March
5	-3.00	U	19	1	storage	April
6	-20.65	U	19	1	backorder	April
7	43.00	L	19	1	backorder	May
8	50.90	L	19	.	f1_to_2	March
9	.	B	19	.	f1_to_2	April
10	.	B	19	.	f1_to_2	May
11	.	B	19	1	sales	March
12	-21.00	U	19	1	sales	April
13	9.00	L	19	1	sales	May
14	-46.09	U	19	1	sales	March
15	-32.00	U	19	1	sales	April
16	38.00	L	19	1	sales	May
17	.	B	19	2	production	March
18	-27.85	U	19	2	production	April
19	23.55	L	19	2	production	May
20	15.75	L	19	2	storage	March
21	.	B	19	2	storage	April
22	19.25	L	19	2	backorder	April
23	45.00	L	19	2	backorder	May
24	-29.90	U	19	.	f2_to_1	March
25	22.00	L	19	.	f2_to_1	April
26	29.00	L	19	.	f2_to_1	May
27	-9.65	U	19	2	sales	March
28	.	B	19	2	sales	April
29	18.00	L	19	2	sales	May
30	4.05	L	19	2	sales	March
31	-33.00	U	19	2	sales	April
32	.	B	19	2	sales	May
33	-45.16	U	25	1	production	March
34	-14.35	U	25	1	production	April
35	2.11	L	25	1	production	May
36	94.21	L	25	1	storage	March
37	75.66	L	25	1	storage	April
38	-42.21	U	25	1	backorder	April
39	-16.66	U	25	1	backorder	May
40	104.06	L	25	.	f1_to_2	March
41	13.49	L	25	.	f1_to_2	April
42	28.96	L	25	.	f1_to_2	May
43	47.13	L	25	1	sales	March
44	8.40	L	25	1	sales	April
45	.	B	25	1	sales	May
46	.	B	25	1	sales	March
47	.	B	25	1	sales	April
48	32.02	L	25	1	sales	May

Output 7.8.1 *continued*

Obs	_rcost_	_status_	diagonal	factory	key_id	month_made
49	.	B	25	2	production	March
50	-1.66	U	25	2	production	April
51	73.17	L	25	2	production	May
52	11.64	L	25	2	storage	March
53	108.13	L	25	2	storage	April
54	47.36	L	25	2	backorder	April
55	-16.13	U	25	2	backorder	May
56	-61.06	U	25	.	f2_to_1	March
57	30.51	L	25	.	f2_to_1	April
58	40.04	L	25	.	f2_to_1	May
59	-42.00	U	25	2	sales	March
60	.	B	25	2	sales	April
61	10.50	L	25	2	sales	May
62	.	B	25	2	sales	March
63	.	B	25	2	sales	April
64	.	B	25	2	sales	May

Obs	_node_	_supdem_	_dual_
1	fact1_1	1000	0.00
2	fact2_1	850	0.00
3	fact1_2	1000	0.00
4	fact2_2	1500	0.00
5	shop1_1	-900	199.75
6	shop2_1	-900	188.75
7	shop1_2	-900	343.83
8	shop2_2	-1450	360.83
9	f1_mar_1	.	-127.90
10	f1_apr_1	.	-79.25
11	f1_may_1	.	-94.25
12	f2_mar_1	.	-88.00
13	f2_apr_1	.	-90.25
14	f2_may_1	.	-110.25
15	f1_mar_2	.	-263.06
16	f1_apr_2	.	-188.85
17	f1_may_2	.	-131.19
18	f2_mar_2	.	-182.00
19	f2_apr_2	.	-198.36
20	f2_may_2	.	-128.23

The log is displayed in [Output 7.8.2](#).

Output 7.8.2 OPTMODEL Log

```

NOTE: There were 8 observations read from the data set WORK.NODE0.
NOTE: There were 64 observations read from the data set WORK.ARC0.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 64 variables (0 free, 0 fixed).
NOTE: The problem has 20 linear constraints (4 LE, 16 EQ, 0 GE, 0 range).
NOTE: The problem has 128 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The OPTMODEL presolver is disabled for linear problems.
NOTE: The LP presolver value AUTOMATIC is applied.
NOTE: The LP presolver removed 0 variables and 0 constraints.
NOTE: The LP presolver removed 0 constraint coefficients.
NOTE: The presolved problem has 64 variables, 20 constraints, and 128
      constraint coefficients.
NOTE: The LP solver is called.
NOTE: The Dual Simplex algorithm is used.

```

		Objective	
Phase	Iteration	Value	Time
D 1	1	0.000000E+00	0
D 2	2	-4.020320E+06	0
D 2	32	-1.281110E+06	0

```

NOTE: Optimal.
NOTE: Objective = -1281110.35.
NOTE: The Dual Simplex solve time is 0.00 seconds.
NOTE: The data set WORK.ARC1 has 64 observations and 16 variables.
NOTE: The data set WORK.NODE2 has 20 observations and 3 variables.
NOTE: The PROCEDURE OPTMODEL printed pages 13-14.

```

Example 7.9: Migration to OPTMODEL: Shortest Path

The following example shows how to use PROC OPTMODEL to solve the example “Shortest Path Problem” in Chapter 5, “The NETFLOW Procedure” (*SAS/OR User’s Guide: Mathematical Programming Legacy Procedures*). The input data set is the same as in that example.

```

title 'Shortest Path Problem';
title2 'How to get Hawaiian Pineapples to a London Restaurant';

data aircost1;
  input ffrom&$13. tto&$15. _cost_;
  datalines;
Honolulu      Chicago      105
Honolulu      San Francisco  75
Honolulu      Los Angeles   68
Chicago       Boston       45
Chicago       New York      56
San Francisco Boston       71
San Francisco New York      48
San Francisco Atlanta      63
Los Angeles   New York      44

```

Los Angeles	Atlanta	57
Boston	Heathrow London	88
New York	Heathrow London	65
Atlanta	Heathrow London	76

;

The following PROC OPTMODEL statements read the data sets, build the linear programming model, solve the model, and output the optimal solution to a SAS data set called SPATH:

```
proc optmodel;
  str sourcenode = 'Honolulu';
  str sinknode = 'Heathrow London';

  set <str> NODES;
  num _supdem_ {i in NODES} = (if i = sourcenode then 1
    else if i = sinknode then -1 else 0);

  set <str,str> ARCS;
  num _lo_ {ARCS} init 0;
  num _capac_ {ARCS} init .;
  num _cost_ {ARCS};
  read data aircost1 into ARCS=[ffrom tto] _cost_;
  NODES = (union {<i,j> in ARCS} {i,j});

  var Flow {<i,j> in ARCS} >= _lo_[i,j];
  min obj = sum {<i,j> in ARCS} _cost_[i,j] * Flow[i,j];
  con balance {i in NODES}: sum {<(i),j> in ARCS} Flow[i,j]
    - sum {<j,(i)> in ARCS} Flow[j,i] = _supdem_[i];
  solve;

  num _supply_ {<i,j> in ARCS} =
    (if _supdem_[i] ne 0 then _supdem_[i] else .);
  num _demand_ {<i,j> in ARCS} =
    (if _supdem_[j] ne 0 then -_supdem_[j] else .);
  num _fcost_ {<i,j> in ARCS} = _cost_[i,j] * Flow[i,j].sol;

  create data spath from [ffrom tto]
    _cost_ _capac_ _lo_ _supply_ _demand_ _flow_=Flow _fcost_
    _rcost_=(if Flow[ffrom,tto].rc ne 0 then Flow[ffrom,tto].rc else .)
    _status_=Flow.status;
quit;
```

The statements use both single-dimensional (NODES) and multiple-dimensional (ARCS) index sets. The ARCS index set is populated from the ffrom and tto data set variables in the READ DATA statement. To solve a shortest path problem, you solve a minimum-cost network flow problem that has a supply of one unit at the source node, a demand of one unit at the sink node, and zero supply or demand at all other nodes, as specified in the declaration of the _SUPDEM_ numeric parameter. The SPATH output data set contains most of the same information as in the PROC NETFLOW example, including reduced cost and basis status. The _ANUMB_ and _TNUMB_ values do not apply here.

The PROC PRINT statements are similar to the PROC NETFLOW example:

```
proc print data=spath;
  sum _fcost_;
run;
```

The output is displayed in [Output 7.9.1](#).

Output 7.9.1 Output Data Set

Obs	ffrom	tto	_cost_	_capac_	_lo_	_supply_	_demand_	_flow_	_fcost_	_rcost_	_status_
1	Honolulu	Chicago	105	.	0	1	.	0	0	.	B
2	Honolulu	San Francisco	75	.	0	1	.	0	0	.	B
3	Honolulu	Los Angeles	68	.	0	1	.	1	68	.	B
4	Chicago	Boston	45	.	0	.	.	0	0	61	L
5	Chicago	New York	56	.	0	.	.	0	0	49	L
6	San Francisco	Boston	71	.	0	.	.	0	0	57	L
7	San Francisco	New York	48	.	0	.	.	0	0	11	L
8	San Francisco	Atlanta	63	.	0	.	.	0	0	37	L
9	Los Angeles	New York	44	.	0	.	.	1	44	.	B
10	Los Angeles	Atlanta	57	.	0	.	.	0	0	24	L
11	Boston	Heathrow London	88	.	0	.	1	0	0	.	B
12	New York	Heathrow London	65	.	0	.	1	1	65	.	B
13	Atlanta	Heathrow London	76	.	0	.	1	0	0	.	B
177											

The log is displayed in [Output 7.9.2](#).

Output 7.9.2 OPTMODEL Log

```
NOTE: There were 13 observations read from the data set WORK.AIRCOST1.
NOTE: Problem generation will use 4 threads.
NOTE: The problem has 13 variables (0 free, 0 fixed).
NOTE: The problem has 8 linear constraints (0 LE, 8 EQ, 0 GE, 0 range).
NOTE: The problem has 26 linear constraint coefficients.
NOTE: The problem has 0 nonlinear constraints (0 LE, 0 EQ, 0 GE, 0 range).
NOTE: The OPTMODEL presolver is disabled for linear problems.
NOTE: The problem is a pure network instance. The ALGORITHM=NETWORK option is
      recommended for solving problems with this structure.
NOTE: The LP presolver value AUTOMATIC is applied.
NOTE: The LP presolver removed all variables and constraints.
NOTE: Optimal.
NOTE: Objective = 177.
NOTE: The data set WORK.SPATH has 13 observations and 11 variables.
NOTE: The PROCEDURE OPTMODEL printed pages 16-17.
```

References

- Ahuja, R. K., Magnanti, T. L., and Orlin, J. B. (1993). *Network Flows: Theory, Algorithms, and Applications*. Englewood Cliffs, NJ: Prentice-Hall.
- Andersen, E. D., and Andersen, K. D. (1995). “Presolving in Linear Programming.” *Mathematical Programming* 71:221–245.
- Dantzig, G. B. (1963). *Linear Programming and Extensions*. Princeton, NJ: Princeton University Press.
- Forrest, J. J., and Goldfarb, D. (1992). “Steepest-Edge Simplex Algorithms for Linear Programming.” *Mathematical Programming* 5:1–28.
- Gondzio, J. (1997). “Presolve Analysis of Linear Programs Prior to Applying an Interior Point Method.” *INFORMS Journal on Computing* 9:73–91.
- Harris, P. M. J. (1973). “Pivot Selection Methods in the Devex LP Code.” *Mathematical Programming* 57:341–374.
- Maros, I. (2003). *Computational Techniques of the Simplex Method*. Boston: Kluwer Academic.

Subject Index

- algorithm, 260
- basis, 264
- concurrent LP, 272
- constraint status
 - LP solver, 273
- decomposition algorithm
 - LP solver, 265
- dualization, 261
- feasibility tolerance, 262
- IIS option
 - OPTMODEL procedure, LP solver, 274
- irreducible infeasible set
 - OPTMODEL procedure, LP solver, 274
- iteration log
 - crossover algorithm, 271
 - interior point algorithm, 271
 - LP solver, 269–271
 - network simplex algorithm, 270
 - primal and dual simplex algorithms, 269
- linear programming, *see also* OPTMODEL procedure
- LP solver
 - concurrent LP, 272
 - constraint status, 273
 - iteration log, 269–271
 - problem statistics, 272
 - variable status, 273
- LP solver examples
 - diet problem, 278
 - finding an irreducible infeasible set, 292
 - generalized networks, 303
 - maximum flow, 307
 - production, inventory, distribution, 310
 - shortest path, 318
 - two-person zero-sum game, 289
 - using the network simplex algorithm, 295
- macro variable
 - _OROPTMODEL_, 275
- migration to PROC OPTMODEL
 - from PROC NETFLOW, 303, 307, 310, 318
- OPTMODEL procedure
 - dualization, 261
- OPTMODEL procedure, LP solver
 - algorithm2, 261
 - basis, 264
 - feasibility tolerance, 262
 - functional summary, 259
 - IIS option, 274
 - introductory example, 256
 - macro variable _OROPTMODEL_, 275
 - network simplex algorithm, 266
 - preprocessing, 261
 - presolver, 261
 - pricing, 264
 - queue size, 264
 - scaling, 264
 - solver, 260
 - _OROPTMODEL_ macro variable, 275
- presolver, 261
- pricing, 264
- queue size, 264
- random seed, 265
- scaling, 264
- SOLVE WITH LP statement
 - crossover, 265
 - dual infeasibility, 265
 - duality gap, 265
 - primal infeasibility, 265
- variable status
 - LP solver, 273

Syntax Index

ALGORITHM2= option
 SOLVE WITH LP statement, 261
ALGORITHM= option
 SOLVE WITH LP statement, 260

BASIS= option
 SOLVE WITH LP statement, 264

CROSSOVER= option
 SOLVE WITH LP statement, 265

DECOMP_MASTER=() option
 SOLVE WITH LP statement, 265
DECOMP=() option
 SOLVE WITH LP statement, 265
DECOMP_SUBPROB=() option
 SOLVE WITH LP statement, 266
DUALIZE= option
 SOLVE WITH LP statement, 261

FEASTOL= option
 SOLVE WITH LP statement, 262

IIS= option
 SOLVE WITH LP statement, 260

LOGFREQ= option
 SOLVE WITH LP statement, 262
LOGLEVEL= option
 SOLVE WITH LP statement, 262

MAXITER= option
 SOLVE WITH LP statement, 262
MAXTIME= option
 SOLVE WITH LP statement, 263

OPTMODEL procedure, LP solver
 syntax, 259
OPTTOL= option
 SOLVE WITH LP statement, 263

PRESOLVER= option
 SOLVE WITH LP statement, 261
PRICETYPE= option
 SOLVE WITH LP statement, 264
PRINTFREQ= option
 SOLVE WITH LP statement, 262
PRINTLEVEL2= option
 SOLVE WITH LP statement, 262

QUEUESIZE= option
 SOLVE WITH LP statement, 264

SCALE= option
 SOLVE WITH LP statement, 264
SEED= option
 SOLVE WITH LP statement, 265
SOL= option
 SOLVE WITH LP statement, 260
SOLVE WITH LP statement
 ALGORITHM2= option, 261
 ALGORITHM= option, 260
 BASIS= option, 264
 CROSSOVER= option, 265
 DECOMP_MASTER=() option, 265
 DECOMP=() option, 265
 DECOMP_SUBPROB=() option, 266
 DUALIZE= option, 261
 FEASTOL= option, 262
 IIS= option, 260
 LOGFREQ= option, 262
 LOGLEVEL= option, 262
 MAXITER= option, 262
 MAXTIME= option, 263
 OPTTOL= option, 263
 PRESOLVER= option, 261
 PRICETYPE= option, 264
 PRINTFREQ= option, 262
 PRINTLEVEL2= option, 262
 QUEUESIZE= option, 264
 SCALE= option, 264
 SEED= option, 265
 SOL= option, 260
 SOLVER2= option, 261
 SOLVER= option, 260
 STOP_DG= option, 265
 STOP_DI= option, 265
 STOP_PI= option, 265
 TIMETYPE= option, 263
SOLVER2= option
 SOLVE WITH LP statement, 261
SOLVER= option
 SOLVE WITH LP statement, 260
STOP_DG= option
 SOLVE WITH LP statement, 265
STOP_DI= option
 SOLVE WITH LP statement, 265
STOP_PI= option

SOLVE WITH LP statement, [265](#)

TIMETYPE= option

SOLVE WITH LP statement, [263](#)