



Understanding Why Your Macros Don't Work

M. Michelle Buchecker
SAS Chicago

THE
POWER
TO KNOW®

Copyright © 2006, SAS Institute Inc. All rights reserved.

Legal Mumbo Jumbo

All material contained in this presentation is copyright
2007 by SAS Institute, Inc.

No piece of this presentation in whole or in part may be
distributed electronically or by other means to any person
without express written consent by SAS Institute.

In other words, NO SHARING!

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives

- When and where you should put quotes
- Describe why you sometimes need extra periods
- Identify why extra ampersands are needed
- Determine the difference between %LET and CALL SYMPUT
- Figuring how and why a macro variable can't be found even though you **know** you created it
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives

- **When and where you should put quotes**
- Describe why you sometimes need extra periods
- Identify why extra ampersands are needed
- Determine the difference between %LET and CALL SYMPUT
- Figuring how and why a macro variable can't be found even though you **know** you created it
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Once Upon a Time....

Macro variables are used to

- substitute code for code
- create dynamic maintenance-free programs
- have been around since _____.

Version 6

Version 5

Version 4

SAS 82

SAS 76

FOREVER!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

%LET Statement

%LET is a simple way to create a macro variable.

¯o-variable-name is a simple way to resolve a macro variable.

```
%LET dwarfs=7;
```

```
DATA awards;  
    statues=7;
```

```
RUN;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quiz

What is the title on the report in the following example?

```
%LET dwarfs=7;
```

```
PROC PRINT data=awards;
```

```
  title 'There were &dwarfs small statues  
awarded in 1939';
```

```
RUN;
```

- A. There were &dwarfs small statues awarded in 1939
- B. There were 7 small statues awarded in 1939

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quote Me On This!

The macro facility does not "peek inside" code with single quotes to resolve macro variables.

You should use double quotes to resolve text that needs quotation marks.

Title "There were &dwarfs small statues awarded in 1939";

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quote Me On This!

The macro facility does not "peek inside" code with single quotes to resolve macro variables.

```
%let year=1939;  
Data awards;  
  year1=&year;          year1=1939; → num, 1939  
  year2='&year';       year2='&year'; → char, &year  
  year3="&year";       year3="1939"; → char, 1939  
Run;
```

What are the values and types (char or num) of each variable?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quote Me On This – Part Deux

What if quotes are part of the value?

```
%let year='1939';  
Data awards;  
  year1=&year;          year1='1939'; → char, 1939  
  year2='&year';       year2='&year'; → char, &year  
  year3="&year";       year3="'1939"'; → char, '1939'  
Run;
```

What are the values and types (char or num) of each variable?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quote Me On This

Is that a problem?

```
%let year='1939';
```

Write a Title statement that says:

Presented in 1939 by Shirley Temple

(notice there are no quotes around 1939)

```
Title 'Presented in ' &year ' by Shirley Temple';
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quote Me On This

Easier to code

```
%let year=1939;
```

```
Title "Presented in &year by Shirley Temple";
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

More to Quote on

There is a misleading, unwritten rule that states if a quote giving advice comes from someone famous, very old, or Greek, then it must be good advice.


- Bo Bennett

There is a misleading, unwritten rule that states if you put a quote around text, then it must be good for your macro code.

- Michelle Buchecker

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip




Avoid putting quotes around values in %LET statements



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Your Quoteth Runneth Over

A frequent question is:



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Your Quoteth Runneth Over

```
%let d=Disney;
```

```
%let r=Roy;
```

```
Desired title:
```

```
    R&D created Walt Disney World
```

```
Title "R&D created Walt Disney World";
```

```
Results in
```


```
    RDisney created Walt Disney World
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip



Only use double quotes when necessary.



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives

- When and where you should put quotes
- **Describe why you sometimes need extra periods**
- Identify why extra ampersands are needed
- Determine the difference between %LET and CALL SYMPUT
- Figuring how and why a macro variable can't be found even though you **know** you created it
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

Remember the purpose of the Macro Facility is to do code or text substitution.

For example:


```
Libname company 'c:\my data';  
Proc print data=company.MAR2007;  
    var revenuecanada revenueus;  
Run;  
Proc means data=company.MAR2007;  
    var revenuecanada revenueus;  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip



Hardcode everything first and make sure it works!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;  
Libname company 'c:\my data';  
Proc print data=company.MAR&year;  
    var revenuecanada revenueus;  
Run;  
Proc means data=company.MAR&year;  
    var revenuecanada revenueus;  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;  
%let month=MAR;  
Libname company 'c:\my data';  
Proc print data=company.&month&year;  
    var revenuecanada revenueus;  
Run;  
Proc means data=company.&month&year;  
    var revenuecanada revenueus;  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.&month&year;
  var &typecanada.&typeus;
Run;
Proc means data=company.&month&year;
  var &typeca
Run;
```

Apparent Symbolic
Reference Not Resolved

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.&month&year;
  var &type canada &type us;
Run;
Proc means data=company.&month&year;
  var &type canada &type us;
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.MAR2007;
  var revenue canada revenue us;
Run;
Proc means data=company.MAR2007;
  var revenue canada revenue us;
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

RULE!




Whenever SAS encounters a period after a macro variable reference, the period is treated as a way to end the macro variable and then the period is thrown away.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.&month&year;
  var &type.canada &type.us;
Run;
Proc means data=company.&month&year;
  var &type.canada &type.us;
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.MAR2007;
  var revenuecanada revenueus;
Run;
Proc means data=company.MAR2007;
  var revenuecanada revenueus;
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

QUIZ! Is this OK???

```
%let year=2007;
%let month=MAR;
%let type=revenue;
Libname company 'c:\my data';
Proc print data=company.&month.&year.;
    var &type.canada &type.us;
Run;
Proc means data=company.&month.&year.;
    var &type.canada &type.us;
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Reprise

Whenever SAS encounters a period after a macro variable reference, the period is treated as a way to end the macro variable and then the period is thrown away.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

School of Thought

Some SAS programmers like to always put periods after **all** macro variable references.

Some SAS programmers only like to put periods when they are needed.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company;
Libname &libinfo 'c:\my data';
Proc print data= &libinfo.&month&year;
    var &type.canada &type.us;
Run;
Proc means data= &libinfo.&month&year;
    var &type.canada &type.us;
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

One Dot, Two Dot, Red Dot, Blue Dot

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company;
Libname company 'c:\my data';
Proc print data=companyMAR2007;
var revenuecanada revenueus;
run;
Proc means data=companyMAR2007;
var revenuecanada revenueus;
Run;
```

Good

Not Good

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #1

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company.;
Libname &libinfo 'c:\my data';
Proc print data= &libinfo.&month&year;
var &type.canada &type.us;
Run;
Proc means data= &libinfo.&month&year;
var &type.canada &type.us;
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #1

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company.;
Libname company. 'c:\my data';
Proc print data=company.MAR2007;
    var revenuecanada revenueus;
Run;

Proc means data=company.MAR2007;
    var revenuecanada revenueus;
Run;
```

Not Good

Good

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #2

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company;
Libname &libinfo 'c:\my data';
Proc print data= &libinfo.&month&year;
    var &type.canada &type.us;
Run;
Proc means data= &libinfo.&month&year;
    var &type.canada &type.us;
Run;
```

If one dot's not
enough, use
TWO!

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #2

```
%let year=2007;
%let month=MAR;
%let type=revenue;
%let libinfo=company;
Libname company 'c:\my data';
Proc print data=company.MAR2007;
var revenuecanada revenueus;
Proc means data=company.MAR2007;
var revenuecanada revenueus;
Run;
```

Good

Also Good

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Reprise (Again!)

Whenever SAS encounters a period after a macro variable reference, the period is treated as a way to end the macro variable and then the period is thrown away.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives


- When and where you should put quotes
- Describe why you sometimes need extra periods
- **Identify why extra ampersands are needed**
- Determine the difference between %LET and CALL SYMPUT
- Figuring how and why a macro variable can't be found even though you **know** you created it
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip



Hardcode everything first and make sure it works!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Hardcoded

```
Proc print data=work.all_movies;  
  where star='Mickey';  
  title 'Mickey is my favorite character';  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Common Mistakes

```
%let mouse=Mickey;  
Proc print data=work.all_movies;  
  where star=&mouse;  
  title '&mouse is my favorite character';  
Run;
```

What are the two mistakes made?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

What the Compiler Sees

No quotes so SAS thinks this is a variable name.

```
Proc print data=work.all_movies;  
  where star=Mickey;  
  title '&mouse is my favorite character';  
Run;
```

Remember, the macro facility never peeks inside single quotes.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip



After the hardcoding works, punch holes in the program and put in your macro variable references.

If you punch a hole inside of a quoted string, change the single quotes to double quotes.

NEVER add or delete quotes from the hardcoded program!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.



Correct Code

```
%let mouse=Mickey;  
Proc print data=work.all_movies;  
  where star="&mouse";  
  title "&mouse is my favorite character";  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Poll!

Who is **your** favorite character?



All Disney names, characters, trademarks, images, parks, and attractions noted are owned by the Walt Disney Company.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Master List of Characters

```
%let mouse=Mickey;  
%let duck=Donald;  
%let princess=Cinderella;  
%let tiger=Tigger;  
%let dog=Goofy;  
%let fairy=Tinkerbell;  
%let imagination=Figment;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Correct Code


```
%let type=mouse;  
Proc print data=work.all_movies;  
  where star="?????";  
  title "????? is my favorite character";  
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #1

```
%let type=mouse;
Proc print data=work.all_movies;
  where star="&type";
  title "&type is my favorite character";
Run;
```

```
Proc print data=work.all_movies;
  where star="";
  title "mouse is my favorite character";
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #2

```
%let type=mouse;
Proc print data=work.all_movies;
  where star="&mouse";
  title "&mouse is my favorite character";
Run;
```

```
Proc print data=work.all_movies;
  where star="Mickey";
  title "Mickey is my favorite character";
Run;
```

OK so far, but no
different than before

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #2 Continued

```
%let type=duck;  
Proc print data=work.all_mov  
  where star="&duck";  
  title "&duck is my favori  
Run;  
  
Proc print data=work.all_movies;  
  where star="Donald";  
  title "Donald is my favorite character";  
Run;
```

This statement is never even used

TWO changes needed if you want to change the value

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #2 Continued

```
%let type=duck;  
Proc print data=work.all_mov  
  where star="????";  
  title "???? is my favorite character";  
Run;
```

Somehow need to reference &type here

And here


Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #3

```
%let type=duck;
Proc print data=work.all_movies;
  where star="&type";
  title "&type is my favorite character";
Run;
```

Oh yeah we tried that back on attempt #1. It still doesn't work.

```
Proc print data=work.all_movies;
  where star="";
  title "duck is my favorite character";
Run;
```




Attempt #4

```
%let type=duck;
Proc print data=work.all_movies;
  where star="&&type";
  title "&&type is my favorite character";
Run;
```


If one & isn't enough use two!

```
Proc print data=work.all_movies;
  where star="duck";
  title "duck is my favorite character";
Run;
```



WHAT?!?!?

RULE!




Whenever SAS encounters two ampersands in a row they resolve down to one ampersand.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

```
%let type=duck;
```




If two &'s aren't enough use three!

Whenever SAS encounters two ampersands in a row they resolve down to one ampersand.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Triple Threat

```
%let type=duck;
```



Whenever SAS encounters **two** ampersands in a row they resolve down to one ampersand.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Attempt #5 (and Final)

```
%let type=duck;  
Proc print data=work.all_movies;  
  where star="&&&type";  
  title "&&&type is my favorite character";  
Run;
```

```
Proc print data=work.all_movies;  
  where star="Donald";  
  title "Donald is my favorite character";  
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

&&?



So why would you ever need to use only 2 ampersands?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Master List of Mouses

```
%let mouse1=Mickey;  
%let mouse2=Minnie;  
%let mouse3=Stuart Little;  
%let mouse4=Timothy Q. Mouse;  
%let mouse5=Gus from Cinderella;  
%let mouse6=Miss Bianca;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Hardcoded

```
Proc print data=work.all_movies;  
  where star='Minnie';  
  title 'Minnie is my favorite character';  
Run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

What we want:

```
title 'Minnie is my favorite character';
```

What we have:

```
%let num=2;
```

```
%let mouse2=Minnie;
```

Is there any macro variable that gives us all or part of
Minnie is my favorite character?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

Punch a hole, and change single quotes to double quotes:

```
title "&mouse2 is my favorite character";
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

Currently:

```
title "&mouse2 is my favorite character";
```

What we have:

```
%let num=2;
```

```
%let mouse2=Minnie;
```

Is there any macro variable that gives us all or part of **mouse2**?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

Currently:

```
title "&mouse2 is my favorite character";
```

Punch a hole, and change single ampersand to double ampersand :

```
title "&&mouse&num is my favorite character";
```


Is there any macro variable that gives us all or part of **num**?

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Double Threat

```
%let mouse2=Minnie;
```

```
%let num=2;
```



Whenever SAS encounters two ampersands in a row they resolve down to one ampersand.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

&&

```
%let num=2;
Proc print data=work.all_movies;
  where star="&&mouse&num";
  title "&&mouse&num is my favorite
character";
Run;

Proc print data=work.all_movies;
  where star="Minnie";
  title "Minnie is my favorite character";
Run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Let's Get Fancy!

```
%macro mouses;
  %do num=1 %to 6;
    Proc print data=work.all_movies;
      where star="&&mouse&num";
      title "&&mouse&num is my favorite
character";

    Run;
  %end;
%mend;

%mouses
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quiz 1

What is the title on the report in the following example?

```
%let dwarf1=Dopey;  
%let dwarf2=Doc;  
%let dwarf3=Sneezy;  
%let dwarf4=Bashful was the hardest working dwarf  
%let dwarf5=Bashful;  
%let dwarf6=Grumpy;  
%let dwarf7=Happy;  
%LET dwarfs=5;  
  
PROC PRINT data=awards;  
  title "&dwarf&dwarfs was the hardest working dwarf";  
RUN;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quiz 2

What is the title on the report in the following example?


```
%let dwarf1=Dopey;  
%let dwarf2=Doc;  
%let dwarf3=Sneezy;  
%let dwarf4=  
%let dwarf5=&dwarf8 was the hardest working dwarf  
%let dwarf6=Grumpy;  
%let dwarf7=Happy;  
%LET dwarfs=8;  
  
PROC PRINT data=awards;  
  title "&dwarf&dwarfs was the hardest working dwarf";  
RUN;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Tip



Hardcode everything first and make sure it works!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives

- When and where you should put quotes
- Describe why you sometimes need extra periods
- Identify why extra ampersands are needed
- **Determine the difference between %LET and CALL SYMPUT**
- Figuring how and why a macro variable can't be found even though you **know** you created it
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Goal

Read in data into a DATA step and create a macro variable based on a condition of the data.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Avoiding Crowds

- Read in 1 month worth of crowd calendar data.
- Crowds are rated from 1 (lowest) to 10 (highest).



- If a crowd level is above a 7, increment a counter.
- If there are more than 15 days of the month where the crowd level is above a 7, create a macro variable that says "Stay Home".
- Otherwise create a macro variable that says "Bring your ears!"

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
run;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't
work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
end;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
  level is above a 7 then create a macro variable
  that says "stay home". Otherwise create a macro
  variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
run;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
    input dow $ 1-3 day 6-7
    crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
  level is above a 7 then create a macro variable
  that says "stay home". Otherwise create a macro
  variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
end;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd
  level exceeds a "7" */
  if crowd_level > 7 then
    counter + 1;
  /* if there are more than 15 days where the crowd
  level is above a 7 then create a macro variable
  that says "stay home". Otherwise create a macro
  variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
  end;

```

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15
  days where the crowd level is
  above a 7 then create a macro
  variable that says "stay home".
  Otherwise create a macro
  variable that says "Bring your
  ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
  end;

```

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
run;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
end;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your
ears!;
    end;
  end;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then do;
      %let vacation=stay home;
    end;
    else do;
      %let vacation=Bring your ears!;
    end;
    %let days=counter;
  end;
run;


```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```
proc print data=crowds;  
title "For this vacation we are going to  
      &vacation";  
title2 "Because only &days had large  
        crowds";  
footnote 'April 07 Data retrieved from  
          touringplans.com';  
run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



crowds.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


Problems

Two problems

1. There were 18 days of high crowd levels, yet title said to bring our ears
2. The number of days should have been in title2.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Debug



- Check to see if IF statements are True or False

Back to SAS session

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Debug


1. Check to see if IF statements are True or False – IF statements are working properly.

Time to learn some "behind-the-scenes" workings of SAS.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

How the Macro Processor Works


Program is put into area of memory called **Input Stack**.



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


How the Macro Processor Works

SAS scans 1 word ("token") at a time using the [Word Scanner](#). The Word Scanner usually passes the tokens to the compiler.




How the Macro Processor Works

Word scanning continues one statement at a time.




How the Macro Processor Works

Word scanning continues until a macro trigger is found. A **macro trigger** is an **&** or **%** followed by a name.




How the Macro Processor Works

Word scanning continues until a macro trigger is found. A **macro trigger** is an **&** or **%** followed by a name.




How the Macro Processor Works

When a macro trigger is encountered, it is passed to the macro processor for evaluation.




How the Macro Processor Works

`%LET` is the keyword of a macro statement that creates a macro variable. The macro processor requests tokens until a semicolon is encountered.




How the Macro Processor Works

When the %LET statement executes, a macro variable AMT is given the value 1.1 and stored in a memory location called a *symbol table*.



How the Macro Processor Works

When a step boundary is recognized, the DATA step compilation phase ends and execution begins.



Question




Did the Compiler ever see the %LET statement?

No! %LET like all macro triggers happen during the TOKENIZATION phase.


Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

How the Macro Processor Works




Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works



How the Macro Processor Works



How the Macro Processor Works



```
data crowds;
infile "c:\sugi\macros don't work\crowd calendar.dat"
end=last;
input dow $ 1-3 day 6-7 crowd_level 18-19;
/* count number of days crowd level exceeds a "7" */
if crowd_level > 7 then counter + 1;
/* if there are more than 15 days where the crowd
level is above a 7 then create a macro variable
that says "Bring your ears!" */
variable that says "Bring your ears:";
if last then do;
if counter > 15 then do;
end;
else do;
end;
end;
run;
```

What the compiler saw....

CALL SYMPUT

Instead of creating a macro variable with %LET, you can use CALL SYMPUT.

The SYMPUT routine

- is an **executable** DATA step statement
- assigns to a macro variable any value available to the DATA step during execution time
- can create macro variables with
 - static values
 - dynamic (data dependent) values
 - dynamic (data dependent) names.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The SYMPUT Routine

You can specify macro-variable or text as a

- Literal `call symput('dog','spot');`
- DATA step variable `call symput('dog',x);`
- DATA step expression `call symput('dog',sum(x,y));`

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Dynamically Creating Macro Variables

```
data _null_;  
  mickey = 'Mouse';  
  goofy = 'Dog';  
  call symput('goofy',mickey);  
run;
```

What is the macro variable? `goofy`

What is the value? `Mouse`

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Dynamically Creating Macro Variables

```
data _null_;  
  mickey = 'Mouse';  
  goofy = 'Dog';  
  call symput(goofy,mickey);  
run;
```

What is the macro variable? `Dog`

What is the value? `Mouse`

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro
    variable that says "Bring your ears!" */
  if last then do;
    if counter > 15 then
      call symput('vacation', 'stay home');
    else
      call symput('vacation', 'Bring your ears!');
      call symput('days', counter);
  end;
run;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```

data crowds;
  infile "c:\sugi\macros don't work\crowd calendar.dat"
    end=last;
  input dow $ 1-3 day 6-7 crowd_level 18-19;
  /* count number of days crowd level exceeds a "7" */
  if crowd_level > 7 then counter + 1;
  /* if there are more than 15 days where the crowd
    level is above a 7 then create a macro variable
    that says "stay home". Otherwise create a macro

```

```

if counter > 15 then
  call symput('vacation', 'stay home');
else
  call symput('vacation', 'Bring your
ears!');
  call symput('days', counter);

```


```

run;

```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



crowds symput.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Playing the "WHAT IF..." Game!



Show it!

what if.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


Playing the "WHAT IF..." Game!

What will the titles on the report be?

- A) For this vacation we are going to stay home
Because only 18 days had large crowds
- B) For this vacation we are going to &vacation2
Because only &days2 days had large crowds
- C) For this vacation we are going to Bring your ears!
Because only 18 days had large crowds

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



what if.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

What??? WHY?????



CALL SYMPUT is a DATA step statement.

The DATA step executes when it hits a step boundary like

- RUN;
- a new DATA step
- a new PROC step.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

What??? WHY?????




¯o-variable is a macro trigger.


It gets resolved during **tokenization**.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works




How the Macro Processor Works



How the Macro Processor Works



RULE! Rule of "Slide 130"



When creating a macro variable with CALL SYMPUT, there **MUST** be a step boundary before using it in a macro variable reference (ie. &var)

So....

Use a **RUN;** at the end of the data step!

Objectives


- When and where you should put quotes
- Describe why you sometimes need extra periods
- Identify why extra ampersands are needed
- Determine the difference between %LET and CALL SYMPUT
- **Figuring how and why a macro variable can't be found even though you know you created it**
- When to use Quoting Functions

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

```
%macro create_date;  
  /* This is a generic macro that supplies  
    today's date in the Month-name day, year  
    format and puts that into a macro  
    variable */  
  %let today1=%sysfunc(today(), worddate.);  
%mend;  
  
proc print data=crowds;  
  %create_date  
  title "Report created &today1 by me";  
run;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


Run it!



create date let.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



create date symput.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Perplexing

So %LET did not work,
CALL SYMPUT was stable.
Looks like we need to discuss
Global and local symbol table



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Global Symbol Table

If you are outside a macro definition all macro variables are placed in the GLOBAL symbol table.

Which means the macro variable is available for the duration of your SAS session.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Local Symbol Table

If you are inside a macro definition all bets are off.

First, SAS sees if there is a macro variable by that name already that it can change the value of.

If there is not a macro variable by that name then the fun begins!



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Local Symbol Table and %LET

%LET always puts new macro variables into the LOCAL symbol table.

A LOCAL symbol table means the macro variables stored in here are only around for the duration that the macro is executing.

Once the macro finishes execution, BYE-BYE local symbol table and the macro variables in it!

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Creating Macro Variables

Outside a Macro Definition

- Call Symput
- INTO clause in PROC SQL
- %LET

Global Symbol Table



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Creating Macro Variables

Inside a Macro Definition

- Call Symput
- INTO clause in PROC SQL
- %LET

Global Symbol Table



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Creating Macro Variables

Inside a Macro Definition

- Call Symput
- INTO clause in PROC SQL
- %LET

Global Symbol Table



Local Symbol Table



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Creating Macro Variables

Inside a Macro Definition

- Call Symput
- INTO clause in PROC SQL
- %LET

Global Symbol Table



Local Symbol Table



IF a Local Symbol Table Exists

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Macro Finishes Execution

Inside a Macro Definition

- Call Symput
- INTO clause in PROC SQL
- %LET

Global Symbol Table



Local Symbol Table



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Local Symbol Table and %LET

```
%macro create_date;  
  /* This is a generic macro that supplies  
    today's date in the Month-name day, year  
    format and puts that into a macro  
    variable */  
  %let today1=%sysfunc(today(), worddate.);  
%mend;  
  
proc print data=crowds;  
  %create_date  
  title "Report created &today1 by me";  
run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

CALL SYMPUT

```
%macro create_date;  
data _null_;  
  call symput ('today2',  
              put(today(),worddate.));  
  
run;  
%mend;  
  
%create_date  
proc print data=crowds;  
  title "Report created &today2 by me";  
run;
```



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

CALL SYMPUT

```
%macro create_date;  
data _null_;  
  call symput ('today3',  
              put(today(),worddate.));  
  
run;  
%mend;  
  
proc print data=crowds;  
%create_date  
  title "This is the new date &today3";  
run;
```

Moved call to macro from
before PROC PRINT
statement to after

Changed Title




Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

An Admission

Not intentional that I created this example!!!

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



create date symput 2.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

What??? AGAIN???? WHY???? WHY?????



Think about what the compiler sees:

```
proc print data=crowds;  
  %create_date  
  data _null_;  
  call symput ('today3',  
              put(today(),date9.));  
run;
```

Start of new step
causes **Execution**
of previous step!

Then Macro Variable
gets created

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

What??? AGAIN???? WHY???? WHY?????



Think about what the compiler sees:

```
proc print data=crowds;  
  
  data _null_;  
  call symput ('  
  
run;  
  
title "This is the new date &today3";  
run;
```

Then Title gets set for
next report

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Objectives

- When and where you should put quotes
- Describe why you sometimes need extra periods
- Identify why extra ampersands are needed
- Determine the difference between %LET and CALL SYMPUT
- Figuring how and why a macro variable can't be found even though you know you created it
- **When to use Quoting Functions**

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

The Crux of It All

What is the SAS Macro Language?



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Well Not Quite...

There are certain tokens that have special meaning.

- Blank
- Comma
- &
- %
- others

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.


When is a Comma a Comma?

Sometimes you need to mask the normal meaning of a token and have it just be treated as text.



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



aCOMMAAdating.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

QUIZ!

Given the following program:

```
%let Minnie=Mouse;  
data _null_;  
  call symput('couple', 'Mickey&Minnie');  
run;
```

HINT: Only 1 of these is correct!!!


Which statement correctly displays:

couple is Mickey&Minnie

- a) **%put couple is &couple;**
- b) **%put couple is %bquote(&couple);**
- c) **%put couple is %superq(couple);**

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Run it!



couple.sas

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Opposites Attract

What if you wanted to do the complete opposite???

Using %LET, create one macro variable to have a value of **Mickey&Minnie**

Create a second macro variable to have a value of **Mouse**

Be able to selectively display either

Mickey&Minnie

or

MickeyMouse

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Opposites Attract

Problem #1: Creating the macro variable

What's wrong with:

```
%let Minnie=Mouse;
```

```
%let couple=Mickey&Minnie;
```

Always get MickeyMouse

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Always Have Protection

We need to protect &Minnie so it doesn't get resolved when the text is stored.

The macro quoting function of **%NRSTR** treats % and & as text (a "quoted" value).

```
%let Minnie=Mouse;
```

```
%let couple=%nrstr(Mickey&Minnie);
```

```
%put The value is &couple;
```

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Always Have Protection

We need to protect &Minnie so it doesn't get resolved when the text is stored.

The macro quoting function of **%NRSTR** treats % and & as text (a "quoted" value).

```
%let Minnie=Mouse;  
%let couple=%nrstr(Mickey&Minnie);  
%put The value is &couple;
```

Now treated
as TEXT

The value is Mickey&Minnie

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

And Make a Resolution

We now **need** for &Minnie to resolve!!!

Remember our ultimate goal is:

The value is MickeyMouse

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Quiz!

Fill in the blank:

If we used a quoting function to protect the &, we should use a(n) unquoting function to unprotect the &.

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Unquoting

The macro unquoting function is **%UNQUOTE** and it treats % and & as macro triggers.

```
%let Minnie=Mouse;  
%let couple=%nrstr(Mickey&Minnie);  
%put The value is %unquote(&couple);
```

Now macro
variable
resolves!!!

The value is MickeyMouse

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

And You Programmed Happily Ever After...



Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Credits, Questions, Contact Info

Michelle.Buchecker@sas.com

Copyright © 2007, SAS Institute Inc. All rights reserved. SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.