

Configuring Integrated Windows Authentication for IBM WebSphere with SAS[®] 9.2 Web Applications



Copyright Notice

The correct bibliographic citation for this manual is as follows: SAS Institute Inc., *Configuring Integrated Windows Authentication for IBM WebSphere with SAS 9.2*, Cary, NC: SAS Institute Inc., 2010.

Configuring Integrated Windows Authentication for IBM WebSphere with SAS 9.2
Copyright © 2010, SAS Institute Inc., Cary, NC, USA.

All rights reserved. Printed in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, by any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc. Limited permission is granted to store the copyrighted material in your system and display it on terminals, print only the number of copies required for use by those persons responsible for installing and supporting the SAS programming and licensed programs for which this material has been provided, and to modify the material to meet specific installation requirements. The SAS Institute copyright notice must appear on all printed versions of this material or extracts thereof and on the display medium when the material is displayed. Permission is not granted to reproduce or distribute the material except as stated above.

U.S. Government Restricted Rights Notice. Use, duplication, or disclosure of the software by the government is subject to restrictions as set forth in FAR 52.227-19 Commercial Computer Software-Restricted Rights (June 1987).

SAS Institute Inc., SAS Campus Drive, Cary, North Carolina 27513.

SAS and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries.

® indicates USA registration.

Other brand and product names are trademarks of their respective companies.

Table of Contents

Integrated Windows Authentication	3
Overview of Integrated Windows Authentication.....	3
Integrated Windows Authentication for WebSphere	3
Configuration Tasks on the Active Directory Domain Controller	
Machine	4
Create a Group in the Microsoft Active Directory	4
Create a User Account in the Microsoft Active Directory	4
Configure Kerberos SPN for WebSphere Application Server	5
Create the Kerberos Keytab File Used by SPNEGO	6
Configuration Tasks on WebSphere	7
Configure Lightweight Third Party Authentication	7
Enable the Trust Association and Configure the SPNEGO TAI.....	7
Enable the SPNEGO TAI	8
Install the Keytab File	8
Create a Kerberos Configuration File	8
Verify the Kerberos Authentication.....	9
Configuring the Client Browser to Use SPNEGO	9
Configure Local Intranet Domains	9
Configure Intranet Authentication	9
Verify the Proxy Settings	10
Specify Integrated Authentication for Internet Explorer	10
Testing SPNEGO Support From a Domain Client PC	10
Verifying IWA	10
Recommended Reading	11

Integrated Windows Authentication

Overview of Integrated Windows Authentication

Integrated Windows Authentication (IWA) is a Microsoft technology that is used in an intranet environment where users have Windows domain accounts. With IWA, the credentials (user name and password) are hashed before being sent across the network. The client browser proves its knowledge of the password through a cryptographic exchange with your Web application server.

The key components of IWA include an Active Directory Controller machine (either Windows 2000 or higher server), Kerberos Key Distribution Center (KDC) in a Domain Controller machine, a machine with a client browser, and a Web application server.

When used in conjunction with Kerberos, IWA enables the delegation of security credentials. *Kerberos* is an industry-standard authentication protocol that is used to verify user or host identity. The Kerberos protocol uses strong cryptography so that a client can prove its identity to a server (and vice versa) across an insecure network connection. After a client and server has used Kerberos to provide their identity, they can also encrypt all of their communications to assure privacy and data integrity.

If Active Directory is installed on a Domain Controller running Windows 2000 or higher server, and the client browser supports the Kerberos authentication protocol, Kerberos authentication is used. Note that IWA does not work over HTTP proxy connections.

Use of the Kerberos protocol is guided by the following requirements:

- The client must have a direct connection to Active Directory
- Both the client and the server must have a trusted connection to a Key Distribution Center (KDC) and be Active Directory-compatible
- Service Principal Names (SPNs) are required for multiple worker processes.

Integrated Windows Authentication for WebSphere

When IWA is configured, HTTP clients use Windows login user name to access the SAS Web applications deployed in the WebSphere application server without any authentication challenge.

To configure IWA for WebSphere and create a single sign-on for HTTP requests using the Simple and Protected GSS-API Negotiation Mechanism (SPNEGO), the following requirements should be met:

- SAS 9.2 or the October 2009 release of SAS 9.2 is installed.
- Web authentication is configured. For instructions on configuring Web authentication for WebSphere, see [“Configuring IBM WebSphere Application Server 7 for Web Authentication with SAS 9.2 Web Applications.”](#)

- An Active Directory Controller machine is running Microsoft Windows 2000 Server or higher.
- Machine with a client browser. This is a Microsoft Windows 2000 (or higher) domain member that has a browser client and supports the SPNEGO authentication mechanism. Microsoft Internet Explorer Version 7.0 or later qualifies as the client.
- WebSphere should be running and SAS Web applications should be deployed. Users on the active directory must have access to WebSphere. WebSphere should be enabled for application security, and configured to use the Active Directory as the user registry.
- The clock on all three machines should be synchronized to within five minutes.

Configuration Tasks on the Active Directory Domain Controller Machine

To perform tasks on the Microsoft Active Directory domain controller machine, you should be familiar with Active Directory Users and Computer on a Windows server. This task is required to process single sign on browser requests to the WebSphere application server and the SPNEGO trust association interceptor (TAI).

For instructions on how to use the Active Directory Users and Directory, refer to the product's online Help. Complete the following tasks on the Microsoft Active Directory domain controller machine.

Create a Group in the Microsoft Active Directory

Create an organizational unit or group for user accounts, for example, SASIWAUsers, in the Active Directory on the Windows server. Active Directory users who will be allowed to access SAS Web applications will require membership in this group. Later in the configuration, it will be mapped to a JAAS authorization role, which, in turn, is used by the Web application server for determining authorization to the SAS Web applications.

Create a User Account in the Microsoft Active Directory

1. (Optional). On the domain controller machine, run the following command to find the principals for all users:
dsquery user
2. Create a user account within the Active Directory Users and Directory window, and add this user account to the group that you created. This user account will be mapped to the Kerberos service principal name (SPN). IBM's convention is to use the host name of the WebSphere server for the user name. For example, if the WebSphere server was running redwood2.sas.com, use the ID redwood2. Make sure that the following options are selected when you create the user: **User cannot change password** and **Password never expires**.

Note the password you defined when creating the user account. You will need it later.

3. Configure the new user account to comply with the Kerberos protocol.
 - a. Right-click the name of the user account in the Users tree in the left pane and select **Properties**.
 - b. In the Properties dialog box for the user, click **Account** tab.
 - c. Under Account Options, select the following:
 - Password never expires**
 - Use DES Encryption types for this Account** (*Do NOT select this option if you are running Windows 2008.*)
 - Do not require Kerberos preauthentication**

Note that selecting “**Do not require Kerberos preauthentication**” is optional.
4. Setting the encryption type might corrupt the password. Therefore, reset the user password by right-clicking the name of the user account, selecting **Reset Password**, and re-entering the same password specified earlier.
5. Add the user to the group that you created.

Configure Kerberos SPN for WebSphere Application Server

The Microsoft Active Directory provides support for service principal names (SPN), which are a key component in Kerberos authentication. SPNs are unique identifiers for services running on servers. Every service that uses Kerberos authentication needs to have an SPN set for it so that clients can identify the service on the network. An SPN usually looks something like name@YOUR.REALM. You need to define an SPN to represent your WebSphere Server in the Kerberos realm. If an SPN is not set for a service, clients have no way of locating that service. Without correctly set SPNs, Kerberos authentication is not possible.

1. On the Active Directory Controller, access the command prompt window to use the **setspn** commands.
2. Before executing the **setspn** commands, verify that there are no additional mappings already configured for the users:

```
setspn -l HTTP/fully-qualified-host
```

No Service Principal Names should be presented.

3. Enter the following commands for SPNs by using correct capitalization of letters and substituting the host name and user name that you created earlier:

```
setspn -a HTTP/hostname username
setspn -a HTTP/fully-qualified-host-name username
```

Here is an example of the use of the **setspn** commands:

```
setspn -a HTTP/redwood2.abc.sas.com iwauser
setspn -a HTTP/redwood2 iwauser
```

4. Run the **setspn** command to view the SPNs you created:

```
setspn -| username
```

This is an important step. If the same service is linked to different accounts in the Active Directory server, the client will not send a Kerberos ticket to the server.

Create the Kerberos Keytab File Used by SPNEGO

A *keytab* is a file containing pairs of Kerberos principals and encrypted keys (these are derived from the Kerberos password). The keytab file contains the requisite information for the WebLogic Server to authenticate to the Key Distribution Center (KDC). Keytab files are copied to the WebLogic Server and must be readable by the user account running the WebLogic Server.

Create the Kerberos keytab file for SPNEGO and make it available to the WebSphere application server. Use the **ktpass** command to create a user mapping and the Kerberos keytab file:

```
ktpass -out C:\hostname.host.keytab -mapuser username -princ HTTP/fully-qualified-  
domain-name@URL address -pass password -ptype KRB5_NT_PRINCIPAL
```

The **ktpass** command creates the **hostname.host.keytab** file.

Here is an example of the use of the **ktpass** command and the options which create the **redwood2.host.keytab** file:

```
ktpass -out C:\redwood2.host.keytab -mapuser redwood2 -princ  
HTTP/redwood2.abc.sas.com@ABC.SAS.COM -pass password-of-logged-user -ptype  
KRB5_NT_PRINCIPAL
```

The following table explains the options used with the **ktpass** command.

Option	Explanation
-out	The key is written to this output file.
-mapuser	The key is mapped to this user.
-princ	Principal name.
-pass	This option denotes the password for the user ID.
-ptype KRB5_NT_PRINCIPAL	This option specifies the KRB5_NT_PRINCIPAL principal value. Specify this option to avoid warning messages.

The **ktpass** command offers many options. Use the command with the help option, **ktpass /?**, to view these options.

Configuration Tasks on WebSphere

To enable the use of SPNEGO for WebSphere, the Kerberos configuration must be completed. Configuration tasks on WebSphere include copying the keytab file to the appropriate directory, and creating the Kerberos configuration files, **krb5.ini** (on Windows) and **krb5login.conf** (on UNIX).

- Configure Lightweight Third Party Authentication (LTPA)
- Enable trust association and configure the SPNEGO Trust Association Interceptor (TAI)
- Enable the SPNEGO TAI
- Install the Kerberos keytab file on the WebSphere host
- Create a Kerberos configuration file
- Verify the Kerberos Authentication

Configure Lightweight Third Party Authentication

To configure LTPA, see IBM's documentation for WebSphere 7.0 at [Configuring the Lightweight Third Party Authentication mechanism](#) and for WebSphere 6.1 at [Configuring the Lightweight Third Party Authentication mechanism](#).

Enable the Trust Association and Configure the SPNEGO TAI

Perform the following steps to enable the SPNEGO Trust Association Interceptor:

1. In the WebSphere administration console, navigate to **Security ► Security administration, applications, and infrastructure ► Web security ► Trust association**.
2. Enable the **Enable trust association** check box, and click **OK**.
3. Return to the **Trust association** page and click **Interceptors**.
4. Click **com.ibm.ws.security.spnego.TrustAssociationInterceptorImpl** (the first link in the list).
5. On the target page, click **Custom properties**.
6. Add a new property named `com.ibm.ws.security.spnego.SPN1.hostName`, and use the fully qualified domain name of the WebSphere host as the value. For example, `redwood2.sas.com`. Then, click **OK**.

This is the minimum level of configuration. The interceptor supports many other properties that you might choose to configure. For a list of the properties, see the IBM documentation for WebSphere 7.0 at [SPNEGO TAI custom properties configuration](#) and for WebSphere 6.1 at [SPNEGO TAI custom properties configuration](#).

Two properties that are especially useful are:

```
com.ibm.ws.security.spnego.SPN1.filterClass
com.ibm.ws.security.spnego.SPN1.filter.
```

By default, the SPNEGO TAI intercepts all HTTP requests. You can change this by modifying the following property from

```
com.ibm.ws.security.spnego.SPN1.filterClass to  
com.ibm.ws.security.spnego.HTTPHeaderFilter
```

Then specify `com.ibm.ws.security.spnego.SPN1.filter` to an expression built by using information in the HTTP headers of a request and the operators listed in the IBM documentation for for WebSphere 7.0 at [SPNEGO TAI custom properties configuration](#) and for WebSphere 6.1 at [SPNEGO TAI custom properties configuration](#).

Enable the SPNEGO TAI

To enable SPNEGO TAI that you just configured, complete these steps:

1. In the WebSphere administration console, navigate to **Servers ► Application servers ► *server-name* ► Java and Process Management ► Process Definition ► Java Virtual Machine ► Custom properties**.
2. Create a new custom property `com.ibm.ws.security.spnego.isEnabled` and set a value of `true`.
3. Click **OK**.

Install the Keytab File

Copy the keytab file you created earlier from the Domain Controller to the WebSphere host, and put it in a known location such as the `C:\WINNT` directory.

Create a Kerberos Configuration File

Create a Kerberos configuration file, **krb5.ini** by following the instructions in the topic [“Kerberos Configuration File”](#) at the IBM Web site.

Your **krb5.ini** file should resemble the content in the following example:

```
[libdefaults]
    default_realm = SAS.COM
    default_keytab_name = FILE:c:\winnt\krb5.ini
    default_tkt_enctypes = des-cbc-md5 rc4-hmac
    default_tgs_enctypes = des-cbc-md5 rc4-hmac
    kdc_default_options = 0x54800000
#    forwardable = true
#    proxiable = true
#    noaddresses = true
[realms]
    ABC.SAS.COM = {
        kdc = redwood2.abc.sas.com:88
        default_domain = abc.sas.com
    }
[domain_realm]
    .ABC.SAS.com = ABC.SAS.COM
```

If you have a Windows 2000 server, the rc4-hmac encryption is not supported. For Windows 2000 server, do not specify the rc4-hmac encryption. The default encryption will be used.

Note: The machine `redwood2.abc.sas.com` is the Domain Controller.

At the end of this step, restart WebSphere.

Verify the Kerberos Authentication

A Ticket Granting Ticket (TGT) could expire or get lost from the cache. To ensure that a valid TGT is available in the system, use the `kinit` command. The `kinit` command obtains and caches the Kerberos ticket-granting tickets.

1. Bring up a command prompt window, and go to the Java directory where the `kinit` utility resides (for example, `C:\jdk1.5.0.19\bin` directory).
2. On Windows, run the `kinit` utility to make a Kerberos request. Substitute the name of the keytab filename, URL address and domain name:

```
kinit -k -t C:\krb5.keytab\redwood2.host.keytab
HTTP/redwood2.abc.sas.com@ABC.SAS.COM
```

It is important that the following message displays at the end of the output:

“New ticket is stored in cache file C:\Documents and settings...”

Configuring the Client Browser to Use SPNEGO

Complete the following steps on the machine with the client browser application to ensure that your Microsoft Internet Explorer browser is enabled to perform SPNEGO authentication.

Configure Local Intranet Domains

1. In the Internet Explorer window, select **Tools ► Internet Options ► Security**.
2. Under Local Intranet, click **Sites**.
3. Verify that the checkboxes are selected for the following options:
Include all local (Intranet) sites not listed in other zones
Include all sites that bypass the proxy server
4. Add your domain name to the list of websites to ensure that Internet Explorer recognizes any site with your domain name as the intranet.

Configure Intranet Authentication

1. In the Internet Explorer window, select **Tools ► Internet Options ► Security**.
2. Under Local Intranet, click **Sites**.
3. On the **Security** tab, select Local Intranet and click **Custom Level**.
4. In the Security Settings – Local Intranet Zone, under **User Authentication**, select **Automatic Logon only in Intranet Zone** and click **OK**.

Verify the Proxy Settings

1. In the Internet Explorer window, select **Tools ► Internet Options ► Connections** .
2. Click **LAN Settings**.
3. Verify that the proxy server address and port number are correct.
4. Click **Advanced**.
5. In the **Proxy Settings** dialog box, ensure that all desired domain names are entered in the **Exceptions** field.
6. Click **OK** to close the **Proxy Settings** dialog box.

Specify Integrated Authentication for Internet Explorer

1. On the Internet Options window, click the **Advanced** tab and scroll to **Security settings**. Verify that the checkbox is selected for **Enable Integrated Windows Authentication**.
2. Click **OK**. Restart your Microsoft Internet Explorer to activate this configuration.

Testing SPNEGO Support From a Domain Client PC

SPNEGO testing can be done with the sec_con tool, if it is available on the WebLogic machine. You can access the sec_con tool from a domain client PC by specifying the URL address in the browser application. To obtain the sec_con tool, contact SAS Technical Support.

Following is an example of a URL address used to access the sec_con tool:

http://redwood2.abc.sas.com:7501/sec_con/sec_con_03wls.jsp

Verifying IWA

Log on to SAS Web applications to confirm that no prompt is presented for logon credentials, and that the applications load with the current Windows user logged into the application.

Do NOT test from a browser on the middle-tier machine itself (that is, the machine where the application server is installed). This will not work. Testing must be performed on a separate client machine within the Windows domain.

Recommended Reading

IBM Corporation. 2008. *Configuring the client browser to use SPNEGO*. IBM Information Center.

WebSphere 7.0 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v7r0/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/tsec_SPNEGO_config_web.html.

WebSphere 6.1 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v6r1/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/tsec_SPNEGO_config_web.html.

IBM Corporation. 2008. *Configuring the Lightweight Third Party Authentication mechanism*. IBM Information Center.

WebSphere 7.0 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v7r0/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/tsec_ltpa.html.

WebSphere 6.1 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v6r1/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/tsec_ltpa.html.

IBM Corporation. 2008. *Kerberos configuration file*. IBM Information Center.

WebSphere 7.0 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v7r0/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/rsec_SPNEGO_config_krb5.html.

WebSphere 6.1 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v6r1/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/rsec_SPNEGO_config_krb5.html.

IBM Corporation. 2008. *SPNEGO TAI custom properties configuration*. IBM Information Center.

WebSphere 7.0 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v7r0/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/rsec_SPNEGO_tai_attribs.html.

WebSphere 6.1 Available at:

http://publib.boulder.ibm.com/infocenter/wasinfo/v6r1/index.jsp?topic=/com.ibm.websphere.nd.multiplatform.doc/info/ae/ae/rsec_SPNEGO_tai_attribs.html.

Massachusetts Institute of Technology., 2009. *Kerberos: The Network Authentication Protocol*. Available at <http://web.mit.edu/Kerberos>.

SAS Institute, Inc., 2010. *Configuring IBM WebSphere Application Server 7.0 for Web Authentication with SAS 9.2 Web Applications*. Available at <http://support.sas.com/resources/thirdpartysupport/v92m3/appservers/ConfiguringWAS7WebAuth.pdf>.

SAS Institute, Inc., 2009. *SAS 9.2 Intelligence Platform: Security Administration Guide*. Cary, NC. SAS Institute, Inc. Available at <http://support.sas.com/documentation/cdl/en/bisecag/61133/PDF/default/bisecag.pdf>.



support.sas.com

SAS is the world leader in providing software and services that enable customers to transform data from all areas of their business into intelligence. SAS solutions help organizations make better, more informed decisions and maximize customer, supplier, and organizational relationships. For more than 30 years, SAS has been giving customers around the world The Power to Know®. Visit us at **www.sas.com**.