



THE
POWER
TO KNOW.

SAS/STAT® 9.22 User's Guide

The MIANALYZE Procedure

(Book Excerpt)



This document is an individual chapter from *SAS/STAT® 9.22 User's Guide*.

The correct bibliographic citation for the complete manual is as follows: SAS Institute Inc. 2010. *SAS/STAT® 9.22 User's Guide*. Cary, NC: SAS Institute Inc.

Copyright © 2010, SAS Institute Inc., Cary, NC, USA

All rights reserved. Produced in the United States of America.

For a Web download or e-book: Your use of this publication shall be governed by the terms established by the vendor at the time you acquire this publication.

U.S. Government Restricted Rights Notice: Use, duplication, or disclosure of this software and related documentation by the U.S. government is subject to the Agreement with SAS Institute and the restrictions set forth in FAR 52.227-19, Commercial Computer Software-Restricted Rights (June 1987).

SAS Institute Inc., SAS Campus Drive, Cary, North Carolina 27513.

1st electronic book, May 2010

SAS® Publishing provides a complete selection of books and electronic products to help customers use SAS software to its fullest potential. For more information about our e-books, e-learning products, CDs, and hard-copy books, visit the SAS Publishing Web site at support.sas.com/publishing or call 1-800-727-3228.

SAS® and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Other brand and product names are registered trademarks or trademarks of their respective companies.

Chapter 55

The MIANALYZE Procedure

Contents

Overview: MIANALYZE Procedure	4462
Getting Started: MIANALYZE Procedure	4463
Syntax: MIANALYZE Procedure	4466
PROC MIANALYZE Statement	4466
BY Statement	4469
CLASS Statement	4470
MODELEFFECTS Statement	4470
STDERR Statement	4471
TEST Statement	4471
Details: MIANALYZE Procedure	4473
Input Data Sets	4473
Combining Inferences from Imputed Data Sets	4477
Multiple Imputation Efficiency	4478
Multivariate Inferences	4479
Testing Linear Hypotheses about the Parameters	4481
Examples of the Complete-Data Inferences	4481
ODS Table Names	4483
Examples: MIANALYZE Procedure	4484
Example 55.1: Reading Means and Standard Errors from Variables in a DATA= Data Set	4485
Example 55.2: Reading Means and Covariance Matrices from a DATA= COV Data Set	4488
Example 55.3: Reading Regression Results from a DATA= EST Data Set . . .	4491
Example 55.4: Reading Mixed Model Results from PARMS= and COVB= Data Sets	4493
Example 55.5: Reading Generalized Linear Model Results	4497
Example 55.6: Reading GLM Results from PARMS= and XPXI= Data Sets	4499
Example 55.7: Reading Logistic Model Results from PARMS= and COVB= Data Sets	4500
Example 55.8: Reading Mixed Model Results with Classification Variables .	4503
Example 55.9: Using a TEST statement	4506
Example 55.10: Combining Correlation Coefficients	4508
References	4511

Overview: MIANALYZE Procedure

The MIANALYZE procedure combines the results of the analyses of imputations and generates valid statistical inferences. Multiple imputation provides a useful strategy for analyzing data sets with missing values. Instead of filling in a single value for each missing value, Rubin's (1976, 1987) multiple imputation strategy replaces each missing value with a set of plausible values that represent the uncertainty about the right value to impute.

Multiple imputation inference involves three distinct phases:

1. The missing data are filled in m times to generate m complete data sets.
2. The m complete data sets are analyzed using standard statistical analyses.
3. The results from the m complete data sets are combined to produce inferential results.

A companion procedure, PROC MI, creates multiply imputed data sets for incomplete multivariate data. It uses methods that incorporate appropriate variability across the m imputations.

The analyses of imputations are obtained by using standard SAS procedures (such as PROC REG) for complete data. No matter which complete-data analysis is used, the process of combining results from different imputed data sets is essentially the same and results in valid statistical inferences that properly reflect the uncertainty due to missing values. These results of analyses are combined in the MIANALYZE procedure to derive valid inferences.

The MIANALYZE procedure reads parameter estimates and associated standard errors or covariance matrix that are computed by the standard statistical procedure for each imputed data set. The MIANALYZE procedure then derives valid univariate inference for these parameters. With an additional assumption about the population between and within imputation covariance matrices, multivariate inference based on Wald tests can also be derived.

The MODELEFFECTS statement lists the effects to be analyzed, and the CLASS statement lists the classification variables in the MODELEFFECTS statement. The variables in the MODELEFFECTS statement that are not specified in a CLASS statement are assumed to be continuous.

When each effect in the MODELEFFECTS statement is a continuous variable by itself, a STDERR statement specifies the standard errors when both parameter estimates and associated standard errors are stored as variables in the same data set.

For some parameters of interest, you can use TEST statements to test linear hypotheses about the parameters. For others, it is not straightforward to compute estimates and associated covariance matrices with standard statistical SAS procedures. Examples include correlation coefficients between two variables and ratios of variable means. These special cases are described in the section "[Examples of the Complete-Data Inferences](#)" on page 4481.

Getting Started: MIANALYZE Procedure

Consider the following Fitness data set that has been altered to contain an arbitrary pattern of missingness:

```
*----- Data on Physical Fitness -----*
| These measurements were made on men involved in a physical |
| fitness course at N.C. State University.                    |
| Only selected variables of                                  |
| Oxygen (oxygen intake, ml per kg body weight per minute), |
| Runtime (time to run 1.5 miles in minutes), and            |
| RunPulse (heart rate while running) are used.              |
| Certain values were changed to missing for the analysis.   |
*-----*
```

```
data FitMiss;
  input Oxygen RunTime RunPulse @@;
  datalines;
44.609 11.37 178      45.313 10.07 185
54.297 8.65 156      59.571 . .
49.874 9.22 .        44.811 11.63 176
.      11.95 176      .      10.85 .
39.442 13.08 174      60.055 8.63 170
50.541 . .          37.388 14.03 186
44.754 11.12 176      47.273 . .
51.855 10.33 166      49.156 8.95 180
40.836 10.95 168      46.672 10.00 .
46.774 10.25 .        50.388 10.08 168
39.407 12.63 174      46.080 11.17 156
45.441 9.63 164      .      8.92 .
45.118 11.08 .        39.203 12.88 168
45.790 10.47 186      50.545 9.93 148
48.673 9.40 186      47.920 11.50 170
47.467 10.50 170
;
```

Suppose that the data are multivariate normally distributed and that the missing data are missing at random (see the “Statistical Assumptions for Multiple Imputation” section in the chapter “The MI Procedure” for a description of these assumptions). The following statements use the MI procedure to impute missing values for the FitMiss data set:

```
proc mi data=FitMiss seed=3237851 noprint out=outmi;
  var Oxygen RunTime RunPulse;
run;
```

The MI procedure creates imputed data sets, which are stored in the outmi data set. A variable named `_Imputation_` indicates the imputation numbers. Based on m imputations, m different sets of the point and variance estimates for a parameter can be computed. In this example, $m = 5$ is the default.

The following statements generate regression coefficients for each of the five imputed data sets:

```
proc reg data=outmi outest=outreg covout noprint;
  model Oxygen= RunTime RunPulse;
  by _Imputation_;
run;
```

The following statements display (in [Figure 55.1](#)) output parameter estimates and covariance matrices from PROC REG for the first two imputed data sets:

```
proc print data=outreg (obs=8);
  var _Imputation_ _Type_ _Name_
      Intercept RunTime RunPulse;
  title 'Parameter Estimates from Imputed Data Sets';
run;
```

Figure 55.1 Parameter Estimates

Parameter Estimates from Imputed Data Sets						
Obs	_Imputation_	_TYPE_	_NAME_	Intercept	RunTime	RunPulse
1	1	PARMS		86.544	-2.82231	-0.05873
2	1	COV	Intercept	100.145	-0.53519	-0.55077
3	1	COV	RunTime	-0.535	0.10774	-0.00345
4	1	COV	RunPulse	-0.551	-0.00345	0.00343
5	2	PARMS		83.021	-3.00023	-0.02491
6	2	COV	Intercept	79.032	-0.66765	-0.41918
7	2	COV	RunTime	-0.668	0.11456	-0.00313
8	2	COV	RunPulse	-0.419	-0.00313	0.00264

The following statements combine the five sets of regression coefficients:

```
proc mianalyze data=outreg;
  modeleffects Intercept RunTime RunPulse;
run;
```

The “Model Information” table in [Figure 55.2](#) lists the input data set(s) and the number of imputations.

Figure 55.2 Model Information Table

The MIANALYZE Procedure	
Model Information	
Data Set	WORK.OUTREG
Number of Imputations	5

The “Variance Information” table in [Figure 55.3](#) displays the between-imputation, within-imputation, and total variances for combining complete-data inferences. It also displays the degrees of freedom for the total variance, the relative increase in variance due to missing values, the fraction of missing information, and the relative efficiency for each parameter estimate.

Figure 55.3 Variance Information Table

Variance Information				
-----Variance-----				
Parameter	Between	Within	Total	DF
Intercept	45.529229	76.543614	131.178689	23.059
RunTime	0.019390	0.106220	0.129487	123.88
RunPulse	0.001007	0.002537	0.003746	38.419

Variance Information			
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency
Intercept	0.713777	0.461277	0.915537
RunTime	0.219051	0.192620	0.962905
RunPulse	0.476384	0.355376	0.933641

The “Parameter Estimates” table in [Figure 55.4](#) displays a combined estimate and standard error for each regression coefficient (parameter). Inferences are based on t distributions. The table displays a 95% confidence interval and a t test with the associated p -value for the hypothesis that the parameter is equal to the value specified with the THETA0= option (in this case, zero by default). The minimum and maximum parameter estimates from the imputed data sets are also displayed.

Figure 55.4 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
Intercept	90.837440	11.453327	67.14779	114.5271	23.059
RunTime	-3.032870	0.359844	-3.74511	-2.3206	123.88
RunPulse	-0.068578	0.061204	-0.19243	0.0553	38.419

Parameter Estimates			
Parameter	Minimum	Maximum	
Intercept	83.020730	100.839807	
RunTime	-3.204426	-2.822311	
RunPulse	-0.112840	-0.024910	

Parameter Estimates				
Parameter	Theta0	t for H0:		
		Parameter=Theta0	Pr > t	
Intercept	0	7.93	<.0001	
RunTime	0	-8.43	<.0001	
RunPulse	0	-1.12	0.2695	

Syntax: MIANALYZE Procedure

The following statements are available in PROC MIANALYZE:

```
PROC MIANALYZE < options > ;
  BY variables ;
  CLASS variables ;
  MODELEFFECTS effects ;
  < label: > TEST equation1 < , ... , < equationk > > < / options > ;
  STDERR variables ;
```

The BY statement specifies groups in which separate analyses are performed.

The CLASS statement lists the classification variables in the MODELEFFECTS statement. Classification variables can be either character or numeric.

The required MODELEFFECTS statement lists the effects to be analyzed. The variables in the statement that are not specified in a CLASS statement are assumed to be continuous.

The STDERR statement lists the standard errors associated with the effects in the MODELEFFECTS statement when both parameter estimates and standard errors are saved as variables in the same DATA= data set. The STDERR statement can be used only when each effect in the MODELEFFECTS statement is a continuous variable by itself.

The TEST statement tests linear hypotheses about the parameters. An F statistic is used to jointly test the null hypothesis ($H_0 : \mathbf{L}_c = \mathbf{c}$) specified in a single TEST statement. Several TEST statements can be used.

The PROC MIANALYZE and MODELEFFECTS statements are required for the MIANALYZE procedure. The rest of this section provides detailed syntax information for each of these statements, beginning with the PROC MIANALYZE statement. The remaining statements are in alphabetical order.

PROC MIANALYZE Statement

```
PROC MIANALYZE < options > ;
```

Table 55.1 summarizes the options in the PROC MIANALYZE statement.

Table 55.1 Summary of PROC MIANALYZE Options

Option	Description
Input Data Sets	
DATA=	Specifies the COV, CORR, or EST type data set
DATA=	Specifies the data set for parameter estimates and standard errors
PARMS=	Specifies the data set for parameter estimates
PARMINFO=	Specifies the data set for parameter information

Table 55.1 *continued*

Option	Description
COVB=	Specifies the data set for covariance matrices
XPXI=	Specifies the data set for $(X'X)^{-1}$ matrices
Statistical Analysis	
THETA0=	Specifies parameters under the null hypothesis
ALPHA=	Specifies the level for the confidence interval
EDF=	Specifies the complete-data degrees of freedom
Printed Output	
WCOV	Displays the within-imputation covariance matrix
BCOV	Displays the between-imputation covariance matrix
TCOV	Displays the total covariance matrix
MULT	Displays multivariate inferences

The following options can be used in the PROC MIANALYZE statement. They are listed in alphabetical order.

ALPHA= α

specifies that confidence limits are to be constructed for the parameter estimates with confidence level $100(1 - \alpha)\%$, where $0 < \alpha < 1$. The default is ALPHA=0.05.

BCOV

displays the between-imputation covariance matrix.

COVB <(EFFECTVAR=STACKING | ROWCOL)> =SAS-data-set

names an input SAS data set that contains covariance matrices of the parameter estimates from imputed data sets. If you provide a COVB= data set, you must also provide a PARMS= data set.

The EFFECTVAR= option identifies the variables for parameters displayed in the covariance matrix and is used only when the PARMINFO= option is not specified. The default is EFFECTVAR= STACKING.

See the section “[Input Data Sets](#)” on page 4473 for a detailed description of the COVB= option.

DATA=SAS-data-set

names an input SAS data set.

If the input DATA= data set is not a specially structured SAS data set, the data set contains both the parameter estimates and associated standard errors. The parameter estimates are specified in the MODELEFFECTS statement and the standard errors are specified in the STDERR statement.

If the data set is a specially structured input SAS data set, it must have a TYPE of EST, COV, or CORR that contains estimates from imputed data sets:

- If TYPE=EST, the data set contains the parameter estimates and associated covariance matrices.
- If TYPE=COV, the data set contains the sample means, sample sizes, and covariance matrices. Each covariance matrix for variables is divided by the sample size n to create the covariance matrix for parameter estimates.
- If TYPE=CORR, the data set contains the sample means, sample sizes, standard errors, and correlation matrices. The covariance matrices are computed from the correlation matrices and associated standard errors. Each covariance matrix for variables is divided by the sample size n to create the covariance matrix for parameter estimates.

If you do not specify an input data set with the DATA= or PARMS= option, then the most recently created SAS data set is used as an input DATA= data set. See the section “[Input Data Sets](#)” on page 4473 for a detailed description of the input data sets.

EDF=number

specifies the complete-data degrees of freedom for the parameter estimates. This is used to compute an adjusted degrees of freedom for each parameter estimate. By default, EDF= ∞ and the degrees of freedom for each parameter estimate are not adjusted.

MULT

MULTIVARIATE

requests multivariate inference for the parameters. It is based on Wald tests and is a generalization of the univariate inference. See the section “[Multivariate Inferences](#)” on page 4479 for a detailed description of the multivariate inference.

PARMINFO=SAS-data-set

names an input SAS data set that contains parameter information associated with variables PRM1, PRM2, . . . , and so on. These variables are used as variables for parameters in a COVB= data set. See the section “[Input Data Sets](#)” on page 4473 for a detailed description of the PARMINFO= option.

PARMS <(CLASSVAR= ctype)> =SAS-data-set

names an input SAS data set that contains parameter estimates computed from imputed data sets. When a COVB= data set is not specified, the input PARMS= data set also contains standard errors associated with these parameter estimates. If multivariate inference is requested, you must also provide a COVB= or XPXI= data set.

When the effects contain classification variables, the option CLASSVAR= *ctype* can be used to identify the associated classification variables when reading the classification levels from observations. The available types are FULL, LEVEL, and CLASSVAL. The default is CLASSVAR= FULL. See the section “[Input Data Sets](#)” on page 4473 for a detailed description of the PARMS= option.

TCOV

displays the total covariance matrix derived by assuming that the population between-imputation and within-imputation covariance matrices are proportional to each other.

THETA0=numbers

MU0=numbers

specifies the parameter values θ_0 under the null hypothesis $\theta = \theta_0$ in the t tests for location for the effects. If only one number θ_0 is specified, that number is used for all effects. If more than one number is specified, the specified numbers correspond to effects in the MODELEFFECTS statement in the order in which they appear in the statement. When an effect contains classification variables, the corresponding value is not used and the test is not performed.

WCOV

displays the within-imputation covariance matrices.

XPXI=SAS-data-set

names an input SAS data set that contains the $(X'X)^{-1}$ matrices associated with the parameter estimates computed from imputed data sets. If you provide an XPXI= data set, you must also provide a PARMS= data set. In this case, PROC MIANALYZE reads the standard errors of the estimates from the PARMS= data. The standard errors and $(X'X)^{-1}$ matrices are used to derive the covariance matrices.

BY Statement

BY variables ;

You can specify a BY statement with PROC MIANALYZE to obtain separate analyses on observations in groups that are defined by the BY variables. When a BY statement appears, the procedure expects the input data set to be sorted in order of the BY variables. If you specify more than one BY statement, only the last one specified is used.

If your input data set is not sorted in ascending order, use one of the following alternatives:

- Sort the data by using the SORT procedure with a similar BY statement.
- Specify the NOTSORTED or DESCENDING option in the BY statement for the MIANALYZE procedure. The NOTSORTED option does not mean that the data are unsorted but rather that the data are arranged in groups (according to values of the BY variables) and that these groups are not necessarily in alphabetical or increasing numeric order.
- Create an index on the BY variables by using the DATASETS procedure (in Base SAS software).

You can specify a BY statement with PROC MIANALYZE to obtain separate analyses on observations in groups defined by the BY variables. When a BY statement appears, the procedure expects the input data set to be sorted in order of the BY variables.

If your input data set is not sorted in ascending order, use one of the following alternatives:

- Sort the data by using the SORT procedure with a similar BY statement.

- Specify the BY statement option NOTSORTED or DESCENDING in the BY statement for the MI procedure. The NOTSORTED option does not mean that the data are unsorted but rather that the data are arranged in groups (according to values of the BY variables) and that these groups are not necessarily in alphabetical or increasing numeric order.
- Create an index on the BY variables by using the DATASETS procedure.

For more information about the BY statement, see *SAS Language Reference: Concepts*. For more information about the DATASETS procedure, see the *Base SAS Procedures Guide*.

For more information about BY-group processing, see the discussion in *SAS Language Reference: Concepts*. For more information about the DATASETS procedure, see the discussion in the *Base SAS Procedures Guide*.

CLASS Statement

CLASS *variables* ;

The CLASS statement specifies the classification variables in the MODELEFFECTS statement. Classification variables can be either character or numeric. Classification levels are determined from the formatted values of the classification variables. See “The FORMAT Procedure” in the *Base SAS Procedures Guide* for details.

MODELEFFECTS Statement

MODELEFFECTS *effects* ;

The MODELEFFECTS statement lists the effects in the data set to be analyzed. Each effect is a variable or a combination of variables, and is specified with a special notation that uses variable names and operators.

Each variable is either a classification (or CLASS) variable or a continuous variable. If a variable is not declared in the CLASS statement, it is assumed to be continuous. Crossing and nesting operators can be used in an effect to create crossed and nested effects.

One general form of an effect involving several variables is

$$X1 * X2 * A * B * C (D E)$$

where A, B, C, D, and E are classification variables and X1 and X2 are continuous variables.

When the input DATA= data set is not a specially structured SAS data set, you must also specify standard errors of the parameter estimates in an STDERR statement.

STDERR Statement

STDERR *variables* ;

The STDERR statement lists standard errors associated with effects in the MODELEFFECTS statement, when the input DATA= data set contains both parameter estimates and standard errors as variables in the data set.

With the STDERR statement, only continuous effects are allowed in the MODELEFFECTS statement. The specified standard errors correspond to parameter estimates in the order in which they appear in the MODELEFFECTS statement.

For example, you can use the following MODELEFFECTS and STDERR statements to identify both the parameter estimates and associated standard errors in a SAS data set:

```
proc mianalyze;
  modeleffects y1-y3;
  stderr sy1-sy3;
run;
```

TEST Statement

<label> **TEST** *equation1 <, ..., <equationk > >* *</options>* ;

The TEST statement tests linear hypotheses about the parameters β . An F test is used to jointly test the null hypotheses ($H_0 : \mathbf{L}\beta = \mathbf{c}$) specified in a single TEST statement in which the MULT option is specified.

Each *equation* specifies a linear hypothesis (a row of the \mathbf{L} matrix and the corresponding element of the \mathbf{c} vector); multiple *equations* are separated by commas. The label, which must be a valid SAS name, is used to identify the resulting output. You can submit multiple TEST statements. When a label is not included in a TEST statement, a label of “Test j ” is used for the j th TEST statement.

The form of an *equation* is as follows:

$$term < \pm term \dots > < = \pm term < \pm term \dots > >$$

where *term* is a parameter of the model, or a constant, or a constant times a parameter. When no equal sign appears, the expression is set to 0. Only parameters for regressor effects (continuous variables by themselves) are allowed.

For each TEST statement, PROC MIANALYZE displays a “Test Specification” table of the \mathbf{L} matrix and the \mathbf{c} vector. The procedure also displays a “Variance Information” table of the between-imputation, within-imputation, and total variances for combining complete-data inferences, and a “Parameter Estimates” table of a combined estimate and standard error for each linear component. The linear components are labeled TestPrm1, TestPrm2, ... in the tables.

The following statements illustrate possible uses of the TEST statement:

```
proc mianalyze;
  modeleffects intercept a1 a2 a3;
  test1: test intercept + a2 = 0;
  test2: test intercept + a2;
  test3: test a1=a2=a3;
  test4: test a1=a2, a2=a3;
run;
```

The first and second TEST statements are equivalent and correspond to the specification in Figure 55.5.

Figure 55.5 Test Specification for test1 and test2

The MIANALYZE Procedure					
Test: test1					
Test Specification					
-----L Matrix-----					
Parameter	intercept	a1	a2	a3	C
TestPrm1	1.000000	0	1.000000	0	0

The third and fourth TEST statements are also equivalent and correspond to the specification in Figure 55.6.

Figure 55.6 Test Specification for test3 and test4

The MIANALYZE Procedure					
Test: test3					
Test Specification					
-----L Matrix-----					
Parameter	intercept	a1	a2	a3	C
TestPrm1	0	1.000000	-1.000000	0	0
TestPrm2	0	0	1.000000	-1.000000	0

The ALPHA= and EDF options specified in the PROC MIANALYZE statement are also applied to the TEST statement. You can specify the following options in the TEST statement after a slash(/):

BCOV

displays the between-imputation covariance matrix.

MULT

displays the multivariate inference for parameters.

TCOV

displays the total covariance matrix.

WCOV

displays the within-imputation covariance matrix.

For more information, see the section “Testing Linear Hypotheses about the Parameters” on page 4481.

Details: MIANALYZE Procedure

Input Data Sets

You specify input data sets based on the type of inference you requested. For univariate inference, you can use one of the following options:

- a DATA= data set, which provides both parameter estimates and the associated standard errors
- a DATA=EST, COV, or CORR data set, which provides both parameter estimates and the associated standard errors either explicitly (type CORR) or through the covariance matrix (type EST, COV)
- PARMS= data set, which provides both parameter estimates and the associated standard errors

For multivariate inference, which includes the testing of linear hypotheses about parameters, you can use one of the following option combinations:

- a DATA=EST, COV, or CORR data set, which provides parameter estimates and the associated covariance matrix either explicitly (type EST, COV) or through the correlation matrix and standard errors (type CORR) in a single data set
- PARMS= and COVB= data sets, which provide parameter estimates in a PARMS= data set and the associated covariance matrix in a COVB= data set
- PARMS=, COVB=, and PARMINFO= data sets, which provide parameter estimates in a PARMS= data set, the associated covariance matrix in a COVB= data set with variables named PRM1, PRM2, ..., and the effects associated with these variables in a PARMINFO= data set
- PARMS= and XPXI= data sets, which provide parameter estimates and the associated standard errors in a PARMS= data set and the associated $(X'X)^{-1}$ matrix in an XPXI= data set

The appropriate combination depends on the type of inference and the SAS procedure you used to create the data sets. For instance, if you used PROC REG to create an OUTEST= data set containing the parameter estimates and covariance matrix, you would use the DATA= option to read the OUTEST= data set.

When the input DATA= data set is a specially structured SAS data set, the data set must contain the variable `_Imputation_` to identify the imputation by number. Otherwise, each observation corresponds to an imputation and contains both parameter estimates and associated standard errors.

If you do not specify an input data set with the DATA= or PARMS= option, then the most recently created SAS data set is used as an input DATA= data set. Note that with a DATA= data set, each effect represents a continuous variable; only regressor effects (continuous variables by themselves) are allowed in the MODELEFFECTS statement.

DATA= SAS Data Set

The DATA= data set provides both parameter estimates and the associated standard errors computed from imputed data sets. Such data sets are typically created with an OUTPUT statement in procedures such as PROC MEANS and PROC UNIVARIATE.

The MIANALYZE procedure reads parameter estimates from observations with variables in the MODELEFFECTS statement, and standard errors for parameter estimates from observations with variables in the STDERR statement. The order of the variables for standard errors must match the order of the variables for parameter estimates.

DATA=EST, COV, or CORR SAS Data Set

The specially structured DATA= data set provides both parameter estimates and the associated covariance matrix computed from imputed data sets. Such data sets are created by procedures such as PROC CORR (type COV, CORR) and PROC REG (type EST).

With TYPE=EST, the MIANALYZE procedure reads parameter estimates from observations with `_TYPE_='PARM'`, `_TYPE_='PARMS'`, `_TYPE_='OLS'`, or `_TYPE_='FINAL'`, and covariance matrices for parameter estimates from observations with `_TYPE_='COV'` or `_TYPE_='COVB'`.

With TYPE=COV, the procedure reads sample means from observations with `_TYPE_='MEAN'`, sample size n from observations with `_TYPE_='N'`, and covariance matrices for variables from observations with `_TYPE_='COV'`.

With TYPE=CORR, the procedure reads sample means from observations with `_TYPE_='MEAN'`, sample size n from observations with `_TYPE_='N'`, correlation matrices for variables from observations with `_TYPE_='CORR'`, and standard errors for variables from observations with `_TYPE_='STD'`. The standard errors and correlation matrix are used to generate a covariance matrix for the variables.

Note that with TYPE=COV or CORR, each covariance matrix for the variables is divided by n to create the covariance matrix for the sample means.

PARMS <(CLASSVAR= *ctype*)> = Data Set

The PARMS= data set contains both parameter estimates and the associated standard errors computed from imputed data sets. Such data sets are typically created with an ODS OUTPUT statement in procedures such as PROC GENMOD, PROC GLM, PROC LOGISTIC, and PROC MIXED.

The MIANALYZE procedure reads effect names from observations with the variable *Parameter*, *Effect*, *Variable*, or *Parm*. It then reads parameter estimates from observations with the variable *Estimate* and standard errors for parameter estimates from observations with the variable *StdErr*.

When the effects contain classification variables, the option **CLASSVAR= *ctype*** can be used to identify associated classification variables when reading the classification levels from observations. The available types are **FULL**, **LEVEL**, and **CLASSVAL**. The default is **CLASSVAR= FULL**.

With **CLASSVAR=FULL**, the data set contains the classification variables explicitly. PROC MIANALYZE reads the classification levels from observations with their corresponding classification variables. PROC MIXED generates this type of table.

With **CLASSVAR=LEVEL**, PROC MIANALYZE reads the classification levels for the effect from observations with variables *Level1*, *Level2*, and so on, where the variable *Level1* contains the classification level for the first classification variable in the effect, and the variable *Level2* contains the classification level for the second classification variable in the effect. For each effect, the variables in the crossed list are displayed before the variables in the nested list. The variable order in the **CLASS** statement is used for variables inside each list. PROC GENMOD generates this type of table.

For example, with the following statements, the variable *Level1* has the classification level of the variable *c2* for the effect *c2*:

```
proc mianalyze parms(classvar=Level)= dataparm;
  class c1 c2 c3;
  modeleffects c2 c3(c2 c1);
run;
```

For the effect *c3(c2 c1)*, the variable *Level1* has the classification level of the variable *c3*, *Level2* has the level of *c1*, and *Level3* has the level of *c2*.

Similarly, with **CLASSVAR=CLASSVAL**, PROC MIANALYZE reads the classification levels for the effect from observations with variables *ClassVal0*, *ClassVal1*, and so on, where the variable *ClassVal0* contains the classification level for the first classification variable in the effect, and the variable *ClassVal1* contains the classification level for the second classification variable in the effect. For each effect, the variables in the crossed list are displayed before the variables in the nested list. The variable order in the **CLASS** statement is used for variables inside each list. PROC LOGISTIC generates this type of tables.

PARMS <(CLASSVAR= *ctype*)> = and COVB= Data Sets

The **PARMS=** data set contains parameter estimates, and the **COVB=** data set contains associated covariance matrices computed from imputed data sets. Such data sets are typically created with an **ODS OUTPUT** statement in procedures such as PROC LOGISTIC, PROC MIXED, and PROC REG.

With a **PARMS=** data set, the MIANALYZE procedure reads effect names from observations with the variable *Parameter*, *Effect*, *Variable*, or *Parm*. It then reads parameter estimates from observations with the variable *Estimate*.

When the effects contain classification variables, the option **CLASSVAR= *ctype*** can be used to identify the associated classification variables when reading the classification levels from observations.

The available types are FULL, LEVEL, and CLASSVAL, and they are described in the section “[PARMS <\(CLASSVAR= ctype\)> = Data Set](#)” on page 4474. The default is CLASSVAR= FULL.

The option EFFECTVAR=*etype* identifies the variables for parameters displayed in the covariance matrix. The available types are STACKING and ROWCOL. The default is EFFECTVAR=STACKING.

With EFFECTVAR=STACKING, each parameter is displayed by stacking variables in the effect. Begin with the variables in the crossed list, followed by the continuous list, then followed by the nested list. Each classification variable is displayed with its classification level attached. PROC LOGISTIC generates this type of table.

When each effect is a continuous variable by itself, each stacked parameter name reduces to the effect name. PROC REG generates this type of table.

With EFFECTVAR=STACKING, the MIANALYZE procedure reads parameter names from observations with the variable Parameter, Effect, Variable, Parm, or RowName. It then reads covariance matrices from observations with the stacked variables in a COVB= data set.

With EFFECTVAR=ROWCOL, parameters are displayed by the variables Col1, Col2, ... The parameter associated with the variable Col1 is identified by the observation with value 1 for the variable Row. The parameter associated with the variable Col2 is identified by the observation with value 2 for the variable Row. PROC MIXED generates this type of table.

With EFFECTVAR=ROWCOL, the MIANALYZE procedure reads the parameter indices from observations with the variable Row and the effect names from observations with the variable Parameter, Effect, Variable, Parm, or RowName. It then reads covariance matrices from observations with the variables Col1, Col2, and so on in a COVB= data set.

When the effects contain classification variables, the data set contains the classification variables explicitly and the MIANALYZE procedure also reads the classification levels from their corresponding classification variables.

PARMS <(CLASSVAR= ctype)> =, PARMINFO=, and COVB= Data Sets

The input PARMS= data set contains parameter estimates and the input COVB= data set contains associated covariance matrices computed from imputed data sets. Such data sets are typically created with an ODS OUTPUT statement using procedure such as PROC GENMOD.

With a PARMS= data set, the MIANALYZE procedure reads effect names from observations with the variable Parameter, Effect, Variable, or Parm. It then reads parameter estimates from observations with the variable Estimate.

When the effects contain classification variables, the option CLASSVAR= *ctype* can be used to identify the associated classification variables when reading the classification levels from observations. The available types are FULL, LEVEL, and CLASSVAL, and they are described in the section “[PARMS <\(CLASSVAR= ctype\)> = Data Set](#)” on page 4474. The default is CLASSVAR= FULL.

With a COVB= data set, the MIANALYZE procedure reads parameter names from observations with the variable Parameter, Effect, Variable, Parm, or RowName. It then reads covariance matrices from observations with the variables Prm1, Prm2, and so on.

The parameters associated with the variables Prm1, Prm2, and so on are identified in the PARMINFO= data set. PROC MIANALYZE reads the parameter names from observations with the variable Parameter and the corresponding effect from observations with the variable Effect. When the effects contain classification variables, the data set contains the classification variables explicitly and the MIANALYZE procedure also reads the classification levels from observations with their corresponding classification variables.

PARMS= and XPXI= Data Sets

The input PARMS= data set contains parameter estimates, and the input XPXI= data set contains associated $(X'X)^{-1}$ matrices computed from imputed data sets. Such data sets are typically created with an ODS OUTPUT statement in a procedure such as PROC GLM.

With a PARMS= data set, the MIANALYZE procedure reads parameter names from observations with the variable Parameter, Effect, Variable, or Parm. It then reads parameter estimates from observations with the variable Estimate and standard errors for parameter estimates from observations with the variable StdErr.

With a XPXI= data set, the MIANALYZE procedure reads parameter names from observations with the variable Parameter and $(X'X)^{-1}$ matrices from observations with the parameter variables in the data set.

Note that this combination can be used only when each effect is a continuous variable by itself.

Combining Inferences from Imputed Data Sets

With m imputations, m different sets of the point and variance estimates for a parameter Q can be computed. Suppose that \hat{Q}_i and \hat{W}_i are the point and variance estimates, respectively, from the i th imputed data set, $i = 1, 2, \dots, m$. Then the combined point estimate for Q from multiple imputation is the average of the m complete-data estimates:

$$\bar{Q} = \frac{1}{m} \sum_{i=1}^m \hat{Q}_i$$

Suppose that \bar{W} is the within-imputation variance, which is the average of the m complete-data estimates:

$$\bar{W} = \frac{1}{m} \sum_{i=1}^m \hat{W}_i$$

And suppose that B is the between-imputation variance:

$$B = \frac{1}{m-1} \sum_{i=1}^m (\hat{Q}_i - \bar{Q})^2$$

Then the variance estimate associated with \bar{Q} is the total variance (Rubin 1987)

$$T = \bar{W} + (1 + \frac{1}{m})B$$

The statistic $(Q - \bar{Q})T^{-(1/2)}$ is approximately distributed as t with v_m degrees of freedom (Rubin 1987), where

$$v_m = (m - 1) \left[1 + \frac{\bar{W}}{(1 + m^{-1})B} \right]^2$$

The degrees of freedom v_m depend on m and the ratio

$$r = \frac{(1 + m^{-1})B}{\bar{W}}$$

The ratio r is called the relative increase in variance due to nonresponse (Rubin 1987). When there is no missing information about Q , the values of r and B are both zero. With a large value of m or a small value of r , the degrees of freedom v_m will be large and the distribution of $(Q - \bar{Q})T^{-(1/2)}$ will be approximately normal.

Another useful statistic is the fraction of missing information about Q :

$$\hat{\lambda} = \frac{r + 2/(v_m + 3)}{r + 1}$$

Both statistics r and λ are helpful diagnostics for assessing how the missing data contribute to the uncertainty about Q .

When the complete-data degrees of freedom v_0 are small, and there is only a modest proportion of missing data, the computed degrees of freedom, v_m , can be much larger than v_0 , which is inappropriate. For example, with $m = 5$ and $r = 10\%$, the computed degrees of freedom $v_m = 484$, which is inappropriate for data sets with complete-data degrees of freedom less than 484.

Barnard and Rubin (1999) recommend the use of adjusted degrees of freedom

$$v_m^* = \left[\frac{1}{v_m} + \frac{1}{\hat{v}_{obs}} \right]^{-1}$$

where $\hat{v}_{obs} = (1 - \gamma) v_0 (v_0 + 1) / (v_0 + 3)$ and $\gamma = (1 + m^{-1})B/T$.

If you specify the complete-data degrees of freedom v_0 with the EDF= option, the MIANALYZE procedure uses the adjusted degrees of freedom, v_m^* , for inference. Otherwise, the degrees of freedom v_m are used.

Multiple Imputation Efficiency

The relative efficiency (RE) of using the finite m imputation estimator, rather than using an infinite number for the fully efficient imputation, in units of variance, is approximately a function of m and

λ (Rubin 1987, p. 114):

$$RE = (1 + \frac{\lambda}{m})^{-1}$$

Table 55.2 shows relative efficiencies with different values of m and λ .

Table 55.2 Relative Efficiencies

m	λ				
	10%	20%	30%	50%	70%
3	0.9677	0.9375	0.9091	0.8571	0.8108
5	0.9804	0.9615	0.9434	0.9091	0.8772
10	0.9901	0.9804	0.9709	0.9524	0.9346
20	0.9950	0.9901	0.9852	0.9756	0.9662

The table shows that for situations with little missing information, only a small number of imputations are necessary. In practice, the number of imputations needed can be informally verified by replicating sets of m imputations and checking whether the estimates are stable between sets (Horton and Lipsitz 2001, p. 246).

Multivariate Inferences

Multivariate inference based on Wald tests can be done with m imputed data sets. The approach is a generalization of the approach taken in the univariate case (Rubin 1987, p. 137; Schafer 1997, p. 113). Suppose that $\hat{\mathbf{Q}}_i$ and $\hat{\mathbf{W}}_i$ are the point and covariance matrix estimates for a p -dimensional parameter \mathbf{Q} (such as a multivariate mean) from the i th imputed data set, $i = 1, 2, \dots, m$. Then the combined point estimate for \mathbf{Q} from the multiple imputation is the average of the m complete-data estimates:

$$\bar{\mathbf{Q}} = \frac{1}{m} \sum_{i=1}^m \hat{\mathbf{Q}}_i$$

Suppose that $\bar{\mathbf{W}}$ is the within-imputation covariance matrix, which is the average of the m complete-data estimates:

$$\bar{\mathbf{W}} = \frac{1}{m} \sum_{i=1}^m \hat{\mathbf{W}}_i$$

And suppose that \mathbf{B} is the between-imputation covariance matrix:

$$\mathbf{B} = \frac{1}{m-1} \sum_{i=1}^m (\hat{\mathbf{Q}}_i - \bar{\mathbf{Q}})(\hat{\mathbf{Q}}_i - \bar{\mathbf{Q}})'$$

Then the covariance matrix associated with $\bar{\mathbf{Q}}$ is the total covariance matrix

$$\mathbf{T}_0 = \bar{\mathbf{W}} + (1 + \frac{1}{m})\mathbf{B}$$

The natural multivariate extension of the t statistic used in the univariate case is the F statistic

$$F_0 = (\mathbf{Q} - \bar{\mathbf{Q}})' \mathbf{T}_0^{-1} (\mathbf{Q} - \bar{\mathbf{Q}})$$

with degrees of freedom p and

$$v = (m - 1)(1 + 1/r)^2$$

where

$$r = (1 + \frac{1}{m}) \text{trace}(\mathbf{B}\bar{\mathbf{W}}^{-1})/p$$

is an average relative increase in variance due to nonresponse (Rubin 1987, p. 137; Schafer 1997, p. 114).

However, the reference distribution of the statistic F_0 is not easily derived. Especially for small m , the between-imputation covariance matrix \mathbf{B} is unstable and does not have full rank for $m \leq p$ (Schafer 1997, p. 113).

One solution is to make an additional assumption that the population between-imputation and within-imputation covariance matrices are proportional to each other (Schafer 1997, p. 113). This assumption implies that the fractions of missing information for all components of \mathbf{Q} are equal. Under this assumption, a more stable estimate of the total covariance matrix is

$$\mathbf{T} = (1 + r)\bar{\mathbf{W}}$$

With the total covariance matrix \mathbf{T} , the F statistic (Rubin 1987, p. 137)

$$F = (\mathbf{Q} - \bar{\mathbf{Q}})' \mathbf{T}^{-1} (\mathbf{Q} - \bar{\mathbf{Q}})/p$$

has an F distribution with degrees of freedom p and v_1 , where

$$v_1 = \frac{1}{2}(p + 1)(m - 1)(1 + \frac{1}{r})^2$$

For $t = p(m - 1) \leq 4$, PROC MIANALYZE uses the degrees of freedom v_1 in the analysis. For $t = p(m - 1) > 4$, PROC MIANALYZE uses v_2 , a better approximation of the degrees of freedom given by Li, Raghunathan, and Rubin (1991):

$$v_2 = 4 + (t - 4) \left[1 + \frac{1}{r} \left(1 - \frac{2}{t} \right) \right]^2$$

Testing Linear Hypotheses about the Parameters

Linear hypotheses for parameters β are expressed in matrix form as

$$H_0 : \mathbf{L}\beta = \mathbf{c}$$

where \mathbf{L} is a matrix of coefficients for the linear hypotheses and \mathbf{c} is a vector of constants.

Suppose that $\hat{\mathbf{Q}}_i$ and $\hat{\mathbf{U}}_i$ are the point and covariance matrix estimates, respectively, for a p -dimensional parameter \mathbf{Q} from the i th imputed data set, $i=1, 2, \dots, m$. Then for a given matrix \mathbf{L} , the point and covariance matrix estimates for the linear functions $\mathbf{L}\mathbf{Q}$ in the i th imputed data set are, respectively,

$$\begin{aligned} \mathbf{L}\hat{\mathbf{Q}}_i \\ \mathbf{L}\hat{\mathbf{U}}_i\mathbf{L}' \end{aligned}$$

The inferences described in the section “Combining Inferences from Imputed Data Sets” on page 4477 and the section “Multivariate Inferences” on page 4479 are applied to these linear estimates for testing the null hypothesis $H_0 : \mathbf{L}\beta = \mathbf{c}$.

For each TEST statement, the “Test Specification” table displays the \mathbf{L} matrix and the \mathbf{c} vector, the “Variance Information” table displays the between-imputation, within-imputation, and total variances for combining complete-data inferences, and the “Parameter Estimates” table displays a combined estimate and standard error for each linear component.

With the WCOV and BCOV options in the TEST statement, the procedure displays the within-imputation and between-imputation covariance matrices, respectively.

With the TCOV option, the procedure displays the total covariance matrix derived under the assumption that the population between-imputation and within-imputation covariance matrices are proportional to each other.

With the MULT option in the TEST statement, the “Multivariate Inference” table displays an F test for the null hypothesis $\mathbf{L}\beta = \mathbf{c}$ of the linear components.

Examples of the Complete-Data Inferences

For a given parameter of interest, it is not always possible to compute the estimate and associated covariance matrix directly from a SAS procedure. This section describes examples of parameters with their estimates and associated covariance matrices, which provide the input to the MIANALYZE procedure. Some are straightforward, and others require special techniques.

Means

For a population mean vector μ , the usual estimate is the sample mean vector

$$\bar{\mathbf{y}} = \frac{1}{n} \sum \mathbf{y}_i$$

A variance estimate for \bar{y} is $\frac{1}{n}\mathbf{S}$, where \mathbf{S} is the sample covariance matrix

$$\mathbf{S} = \frac{1}{n-1} \sum (\mathbf{y}_i - \bar{\mathbf{y}})(\mathbf{y}_i - \bar{\mathbf{y}})'$$

These statistics can be computed from a procedure such as PROC CORR. This approach is illustrated in [Example 55.2](#).

Regression Coefficients

Many SAS procedures are available for regression analysis. Among them, PROC REG provides the most general analysis capabilities, and others like PROC LOGISTIC and PROC MIXED provide more specialized analyses.

Some regression procedures, such as REG and LOGISTIC, create an EST type data set that contains both the parameter estimates for the regression coefficients and their associated covariance matrix. You can read an EST type data set in the MIANALYZE procedure with the DATA= option. This approach is illustrated in [Example 55.3](#).

Other procedures, such as GLM, MIXED, and GENMOD, do not generate EST type data sets for regression coefficients. For PROC MIXED and PROC GENMOD, you can use ODS OUTPUT statement to save parameter estimates in a data set and the associated covariance matrix in a separate data set. These data sets are then read in the MIANALYZE procedure with the PARMS= and COVB= options, respectively. This approach is illustrated in [Example 55.4](#) for PROC MIXED and in [Example 55.5](#) for PROC GENMOD.

PROC GLM does not display tables for covariance matrices. However, you can use the ODS OUTPUT statement to save parameter estimates and associated standard errors in a data set and the associated $(X'X)^{-1}$ matrix in a separate data set. These data sets are then read in the MIANALYZE procedure with the PARMS= and XPXI= options, respectively. This approach is illustrated in [Example 55.6](#).

For univariate inference, only parameter estimates and associated standard errors are needed. You can use the ODS OUTPUT statement to save parameter estimates and associated standard errors in a data set. This data set is then read in the MIANALYZE procedure with the PARMS= option. This approach is illustrated in [Example 55.4](#).

Correlation Coefficients

For the population correlation coefficient ρ , a point estimate is the sample correlation coefficient r . However, for nonzero ρ , the distribution of r is skewed.

The distribution of r can be normalized through Fisher's z transformation

$$z(r) = \frac{1}{2} \log \left(\frac{1+r}{1-r} \right)$$

$z(r)$ is approximately normally distributed with mean $z(\rho)$ and variance $1/(n-3)$.

With a point estimate \hat{z} and an approximate 95% confidence interval (z_1, z_2) for $z(\rho)$, a point estimate \hat{r} and a 95% confidence interval (r_1, r_2) for ρ can be obtained by applying the inverse transformation

$$r = \tanh(z) = \frac{e^{2z} - 1}{e^{2z} + 1}$$

to $z = \hat{z}, z_1$, and z_2 .

This approach is illustrated in [Example 55.10](#).

Ratios of Variable Means

For the ratio μ_1/μ_2 of means for variables Y_1 and Y_2 , the point estimate is \bar{y}_1/\bar{y}_2 , the ratio of the sample means. The Taylor expansion and delta method can be applied to the function y_1/y_2 to obtain the variance estimate (Schafer 1997, p. 196)

$$\frac{1}{n} \left[\left(\frac{\bar{y}_1}{\bar{y}_2^2} \right)^2 s_{22} - 2 \left(\frac{\bar{y}_1}{\bar{y}_2} \right) \left(\frac{1}{\bar{y}_2} \right) s_{12} + \left(\frac{1}{\bar{y}_2} \right)^2 s_{11} \right]$$

where s_{11} and s_{22} are the sample variances of Y_1 and Y_2 , respectively, and s_{12} is the sample covariance between Y_1 and Y_2 .

A ratio of sample means will be approximately unbiased and normally distributed if the coefficient of variation of the denominator (the standard error for the mean divided by the estimated mean) is 10% or less (Cochran 1977, p. 166; Schafer 1997, p. 196).

ODS Table Names

PROC MIANALYZE assigns a name to each table it creates. You must use these names to reference tables when using the Output Delivery System (ODS). These names are listed in [Table 55.3](#). For more information about ODS, see Chapter 20, “Using the Output Delivery System.”

Table 55.3 ODS Tables Produced by PROC MIANALYZE

ODS Table Name	Description	Statement	Option
BCov	Between-imputation covariance matrix		BCOV
ModelInfo	Model information		
MultStat	Multivariate inference		MULT
ParameterEstimates	Parameter estimates		
TCov	Total covariance matrix		TCOV
TestBCov	Between-imputation covariance matrix for $\mathbf{L}\boldsymbol{\beta}$	TEST	BCOV
TestMultStat	Multivariate inference for $\mathbf{L}\boldsymbol{\beta}$	TEST	MULT
TestParameterEstimates	Parameter estimates for $\mathbf{L}\boldsymbol{\beta}$	TEST	
TestSpec	Test specification, \mathbf{L} and \mathbf{c}	TEST	
TestTCov	Total covariance matrix for $\mathbf{L}\boldsymbol{\beta}$	TEST	TCOV

Table 55.3 *continued*

ODS Table Name	Description	Statement	Option
TestVarianceInfo	Variance information for $L\beta$	TEST	
TestWCov	Within-imputation covariance matrix for $L\beta$	TEST	WCOV
VarianceInfo	Variance information		
WCov	Within-imputation covariance matrix		WCOV

Examples: MIANALYZE Procedure

The following statements generate five imputed data sets to be used in this section. The data set FitMiss was created in the section “[Getting Started: MIANALYZE Procedure](#)” on page 4463. See “The MI Procedure” chapter for details concerning the MI procedure.

```
proc mi data=FitMiss seed=3237851 noprint out=outmi;
  var Oxygen RunTime RunPulse;
run;
```

The Fish data described in the STEPDISC procedure are measurements of 159 fish of seven species caught in Finland’s lake Laengelmavesi. For each fish, the length, height, and width are measured. Three different length measurements are recorded: from the nose of the fish to the beginning of its tail (Length1), from the nose to the notch of its tail (Length2), and from the nose to the end of its tail (Length3). See Chapter 83, “[The STEPDISC Procedure](#),” for more information.

The Fish2 data set is constructed from the Fish data set and contains two species of fish. Some values have been set to missing, and the resulting data set has a monotone missing pattern in the variables Length3, Height, Width, and Species. Note that some values of the variable Species have also been altered in the data set.

The following statements create the Fish2 data set. It contains two species of fish in the Fish data set.

```
/*----- Fish of Species Bream and Roach -----*/
data Fish2 (drop=HtPct WidthPct);
  title 'Fish Measurement Data';
  input Species $ Length3 HtPct WidthPct @@;
  Height= HtPct*Length3/100;
  Width= WidthPct*Length3/100;
  datalines;
Gp1  30.0 38.4 13.4   Gp1  31.2 40.0 13.8   Gp1  31.1 39.8 15.1
.    33.5 38.0   .    .    34.0 36.6 15.1   Gp1  34.7 39.2 14.2
Gp1  34.5 41.1 15.3   Gp1  35.0 36.2 13.4   Gp1  35.1 39.9 13.8
.    36.2 39.3 13.7   Gp1  36.2 39.4 14.1   .    36.2 39.7 13.3
Gp1  36.4 37.8 12.0   .    37.3 37.3 13.6   Gp1  37.2 40.2 13.9
Gp1  37.2 41.5 15.0   Gp1  38.3 38.8 13.8   Gp1  38.5 38.8 13.5
Gp1  38.6 40.5 13.3   Gp1  38.7 37.4 14.8   Gp1  39.5 38.3 14.1
Gp1  39.2 40.8 13.7   .    39.7 39.1   .    Gp1  40.6 38.1 15.1
Gp1  40.5 40.1 13.8   Gp1  40.9 40.0 14.8   Gp1  40.6 40.3 15.0
Gp1  41.5 39.8 14.1   Gp2  41.6 40.6 14.9   Gp1  42.6 44.5 15.5
```

```

Gp1  44.1 40.9 14.3   Gp1  44.0 41.1 14.3   Gp1  45.3 41.4 14.9
Gp1  45.9 40.6 14.7   Gp1  46.5 37.9 13.7
Gp2  16.2 25.6 14.0   Gp2  20.3 26.1 13.9   Gp2  21.2 26.3 13.7
Gp2  22.2 25.3 14.3   Gp2  22.2 28.0 16.1   Gp2  22.8 28.4 14.7
Gp2  23.1 26.7 14.7   .    23.7 25.8 13.9   Gp2  24.7 23.5 15.2
Gp2  24.3 27.3 14.6   Gp2  25.3 27.8 15.1   Gp2  25.0 26.2 13.3
Gp2  25.0 25.6 15.2   Gp2  27.2 27.7 14.1   Gp2  26.7 25.9 13.6
.    26.8 27.6 15.4   Gp2  27.9 25.4 14.0   Gp2  29.2 30.4 15.4
Gp2  30.6 28.0 15.6   Gp2  35.0 27.1 15.3
;

```

The following statements generate five imputed data sets to be used in this section. The regression method is used to impute missing values in the variable Width and the discriminant function method is used to impute the variable Species.

```

proc mi data=Fish2 seed=1305417 out=outfish;
  class Species;
  monotone reg (Width)
    discrim( Species= Length3 Height Width);
  var Length3 Height Width Species;
run;

```

Example 55.1 through Example 55.6 use different input option combinations to combine parameter estimates computed from different procedures. Example 55.7 and Example 55.8 combine parameter estimates with classification variables. Example 55.9 shows the use of a TEST statement, and Example 55.10 combines statistics that are not directly derived from procedures.

Example 55.1: Reading Means and Standard Errors from Variables in a DATA= Data Set

This example creates an ordinary SAS data set that contains sample means and standard errors computed from imputed data sets. These estimates are then combined to generate valid univariate inferences about the population means.

The following statements use the UNIVARIATE procedure to generate sample means and standard errors for the variables in each imputed data set:

```

proc univariate data=outmi noprint;
  var Oxygen RunTime RunPulse;
  output out=outuni mean=Oxygen RunTime RunPulse
    stderr=SOxygen SRunTime SRunPulse;
  by _Imputation_;
run;

```

The following statements display the output data set from PROC UNIVARIATE shown in [Output 55.1.1](#):

```

proc print data=outuni;
  title 'UNIVARIATE Means and Standard Errors';
run;

```

Output 55.1.1 UNIVARIATE Output Data Set

UNIVARIATE Means and Standard Errors							
Obs	_Imputation_	Oxygen	RunTime	Run Pulse	SOxygen	SRun Time	SRun Pulse
1	1	47.0120	10.4441	171.216	0.95984	0.28520	1.59910
2	2	47.2407	10.5040	171.244	0.93540	0.26661	1.75638
3	3	47.4995	10.5922	171.909	1.00766	0.26302	1.85795
4	4	47.1485	10.5279	171.146	0.95439	0.26405	1.75011
5	5	47.0042	10.4913	172.072	0.96528	0.27275	1.84807

The following statements combine the means and standard errors from imputed data sets. The EDF= option requests that the adjusted degrees of freedom be used in the analysis. For sample means based on 31 observations, the complete-data error degrees of freedom is 30.

```
proc mianalyze data=outuni edf=30;
  modeleffects Oxygen RunTime RunPulse;
  stderr SOxygen SRunTime SRunPulse;
run;
```

The “Model Information” table in [Output 55.1.2](#) lists the input data set(s) and the number of imputations. The “Variance Information” table in [Output 55.1.2](#) displays the between-imputation variance, within-imputation variance, and total variance for each univariate inference. It also displays the degrees of freedom for the total variance. The relative increase in variance due to missing values, the fraction of missing information, and the relative efficiency for each imputed variable are also displayed. A detailed description of these statistics is provided in the section “[Combining Inferences from Imputed Data Sets](#)” on page 4477 and the section “[Multiple Imputation Efficiency](#)” on page 4478.

Output 55.1.2 Variance Information

The MIANALYZE Procedure	
Model Information	
Data Set	WORK.OUTUNI
Number of Imputations	5

Output 55.1.2 *continued*

Variance Information				
-----Variance-----				
Parameter	Between	Within	Total	DF
Oxygen	0.041478	0.930853	0.980626	26.298
RunTime	0.002948	0.073142	0.076679	26.503
RunPulse	0.191086	3.114442	3.343744	25.463
Variance Information				
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
Oxygen	0.053471	0.051977	0.989712	
RunTime	0.048365	0.047147	0.990659	
RunPulse	0.073626	0.070759	0.986046	

The “Parameter Estimates” table in [Output 55.1.3](#) displays the estimated mean and corresponding standard error for each variable. The table also displays a 95% confidence interval for the mean and a t statistic with the associated p -value for testing the hypothesis that the mean is equal to the value specified. You can use the THETA0= option to specify the value for the null hypothesis, which is zero by default. The table also displays the minimum and maximum parameter estimates from the imputed data sets.

Output 55.1.3 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
Oxygen	47.180993	0.990266	45.1466	49.2154	26.298
RunTime	10.511906	0.276910	9.9432	11.0806	26.503
RunPulse	171.517500	1.828591	167.7549	175.2801	25.463

Parameter Estimates			
Parameter	Minimum	Maximum	
Oxygen	47.004201	47.499541	
RunTime	10.444149	10.592244	
RunPulse	171.146171	172.071730	

Parameter Estimates				
Parameter	Theta0	t for H0:		
		Parameter=Theta0	Pr > t	
Oxygen	0	47.64	<.0001	
RunTime	0	37.96	<.0001	
RunPulse	0	93.80	<.0001	

Note that the results in this example could also have been obtained with the MI procedure.

Example 55.2: Reading Means and Covariance Matrices from a DATA= COV Data Set

This example creates a COV-type data set that contains sample means and covariance matrices computed from imputed data sets. These estimates are then combined to generate valid statistical inferences about the population means.

The following statements use the CORR procedure to generate sample means and a covariance matrix for the variables in each imputed data set:

```
proc corr data=outmi cov nocorr noprint out=outcov(type=cov);
  var Oxygen RunTime RunPulse;
  by _Imputation_;
run;
```

The following statements display (in [Output 55.2.1](#)) output sample means and covariance matrices from PROC CORR for the first two imputed data sets:

```
proc print data=outcov(obs=12);
  title 'CORR Means and Covariance Matrices'
        ' (First Two Imputations)';
run;
```

Output 55.2.1 COV Data Set

CORR Means and Covariance Matrices (First Two Imputations)						
Obs	_Imputation_	_TYPE_	_NAME_	Oxygen	RunTime	RunPulse
1	1	COV	Oxygen	28.5603	-7.2652	-11.812
2	1	COV	RunTime	-7.2652	2.5214	2.536
3	1	COV	RunPulse	-11.8121	2.5357	79.271
4	1	MEAN		47.0120	10.4441	171.216
5	1	STD		5.3442	1.5879	8.903
6	1	N		31.0000	31.0000	31.000
7	2	COV	Oxygen	27.1240	-6.6761	-10.217
8	2	COV	RunTime	-6.6761	2.2035	2.611
9	2	COV	RunPulse	-10.2170	2.6114	95.631
10	2	MEAN		47.2407	10.5040	171.244
11	2	STD		5.2081	1.4844	9.779
12	2	N		31.0000	31.0000	31.000

Note that the covariance matrices in the data set outcov are estimated covariance matrices of variables, $V(\mathbf{y})$. The estimated covariance matrix of the sample means is $V(\bar{\mathbf{y}}) = V(\mathbf{y})/n$, where n is the sample size, and is not the same as an estimated covariance matrix for variables.

The following statements combine the results for the imputed data sets, and derive both univariate and multivariate inferences about the means. The EDF= option is specified to request that the adjusted degrees of freedom be used in the analysis. For sample means based on 31 observations, the complete-data error degrees of freedom is 30.

```
proc mianalyze data=outcov edf=30;
  modeleffects Oxygen RunTime RunPulse;
run;
```

The “Variance Information” and “Parameter Estimates” tables display the same results as in [Output 55.1.2](#) and [Output 55.1.3](#), respectively, in [Example 55.1](#).

With the WCOV, BCOV, and TCOV options, as in the following statements, the procedure displays the between-imputation covariance matrix, within-imputation covariance matrix, and total covariance matrix assuming that the between-imputation covariance matrix is proportional to the within-imputation covariance matrix in [Output 55.2.2](#).

```
proc mianalyze data=outcov edf=30 wcov bcov tcov mult;
  modeleffects Oxygen RunTime RunPulse;
run;
```

Output 55.2.2 Covariance Matrices

The MIANALYZE Procedure				
Within-Imputation Covariance Matrix				
	Oxygen	RunTime	RunPulse	
Oxygen	0.930852655	-0.226506411	-0.461022083	
RunTime	-0.226506411	0.073141598	0.080316017	
RunPulse	-0.461022083	0.080316017	3.114441784	
Between-Imputation Covariance Matrix				
	Oxygen	RunTime	RunPulse	
Oxygen	0.0414778123	0.0099248946	0.0183701754	
RunTime	0.0099248946	0.0029478891	0.0091684769	
RunPulse	0.0183701754	0.0091684769	0.1910855259	
Total Covariance Matrix				
	Oxygen	RunTime	RunPulse	
Oxygen	1.202882661	-0.292700068	-0.595750001	
RunTime	-0.292700068	0.094516313	0.103787365	
RunPulse	-0.595750001	0.103787365	4.024598310	

With the MULT option, the procedure assumes that the between-imputation covariance matrix is proportional to the within-imputation covariance matrix and displays a multivariate inference for all the parameters taken jointly.

Output 55.2.3 Multivariate Inference

Multivariate Inference					
Assuming Proportionality of Between/Within Covariance Matrices					
Avg Relative Increase in Variance	Num DF	Den DF	F for H0: Parameter=Theta0	Pr > F	
0.292237	3	122.68	12519.7	<.0001	

The “Multivariate Inference” table in [Output 55.2.3](#) shows a significant p -value for the null hypothesis that the population means are all equal to zero.

Example 55.3: Reading Regression Results from a DATA= EST Data Set

This example creates an EST-type data set that contains regression coefficients and their corresponding covariance matrices computed from imputed data sets. These estimates are then combined to generate valid statistical inferences about the regression model.

The following statements use the REG procedure to generate regression coefficients:

```
proc reg data=outmi outest=outreg covout noprint;
  model Oxygen= RunTime RunPulse;
  by _Imputation_;
run;
```

The following statements display (in [Output 55.3.1](#)) output regression coefficients and their covariance matrices from PROC REG for the first two imputed data sets:

```
proc print data=outreg(obs=8);
  var _Imputation_ _Type_ _Name_
      Intercept RunTime RunPulse;
  title 'REG Model Coefficients and Covariance Matrices'
        ' (First Two Imputations)';
run;
```

Output 55.3.1 EST-Type Data Set

REG Model Coefficients and Covariance Matrices (First Two Imputations)						
Obs	_Imputation_	_TYPE_	_NAME_	Intercept	RunTime	RunPulse
1	1	PARMS		86.544	-2.82231	-0.05873
2	1	COV	Intercept	100.145	-0.53519	-0.55077
3	1	COV	RunTime	-0.535	0.10774	-0.00345
4	1	COV	RunPulse	-0.551	-0.00345	0.00343
5	2	PARMS		83.021	-3.00023	-0.02491
6	2	COV	Intercept	79.032	-0.66765	-0.41918
7	2	COV	RunTime	-0.668	0.11456	-0.00313
8	2	COV	RunPulse	-0.419	-0.00313	0.00264

The following statements combine the results for the imputed data sets. The EDF= option is specified to request that the adjusted degrees of freedom be used in the analysis. For a regression model with three independent variables (including the Intercept) and 31 observations, the complete-data error degrees of freedom is 28.

```
proc mianalyze data=outreg edf=28;
  modeleffects Intercept RunTime RunPulse;
run;
```

Output 55.3.2 Variance Information

The MIANALYZE Procedure				
Variance Information				
Parameter	-----Variance-----			DF
	Between	Within	Total	
Intercept	45.529229	76.543614	131.178689	9.1917
RunTime	0.019390	0.106220	0.129487	18.311
RunPulse	0.001007	0.002537	0.003746	12.137
Variance Information				
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
Intercept	0.713777	0.461277	0.915537	
RunTime	0.219051	0.192620	0.962905	
RunPulse	0.476384	0.355376	0.933641	

The “Variance Information” table in [Output 55.3.2](#) displays the between-imputation, within-imputation, and total variances for combining complete-data inferences.

The “Parameter Estimates” table in [Output 55.3.3](#) displays the estimated mean and standard error of the regression coefficients. The inferences are based on the t distribution. The table also displays a 95% mean confidence interval and a t test with the associated p -value for the hypothesis that the regression coefficient is equal to zero. Since the p -value for RunPulse is 0.1597, this variable can be removed from the regression model.

Output 55.3.3 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
Intercept	90.837440	11.453327	65.01034	116.6645	9.1917
RunTime	-3.032870	0.359844	-3.78795	-2.2778	18.311
RunPulse	-0.068578	0.061204	-0.20176	0.0646	12.137

Parameter Estimates			
Parameter	Minimum	Maximum	
Intercept	83.020730	100.839807	
RunTime	-3.204426	-2.822311	
RunPulse	-0.112840	-0.024910	

Parameter Estimates				
Parameter	Theta0	t for H0:		
		Parameter=Theta0	Pr > t	
Intercept	0	7.93	<.0001	
RunTime	0	-8.43	<.0001	
RunPulse	0	-1.12	0.2842	

Example 55.4: Reading Mixed Model Results from PARMS= and COVB= Data Sets

This example creates data sets containing parameter estimates and covariance matrices computed by a mixed model analysis for a set of imputed data sets. These estimates are then combined to generate valid statistical inferences about the parameters.

The following PROC MIXED statements generate the fixed-effect parameter estimates and covariance matrix for each imputed data set:

```
proc mixed data=outmi;
  model Oxygen= RunTime RunPulse RunTime*RunPulse/solution covb;
  by _Imputation_;
  ods output SolutionF=mixparms CovB=mixcovb;
run;
```

The following statements display (in [Output 55.4.1](#)) output parameter estimates from PROC MIXED for the first two imputed data sets:

```
proc print data=mixparms (obs=8);
  var _Imputation_ Effect Estimate StdErr;
  title 'MIXED Model Coefficients (First Two Imputations)';
run;
```

Output 55.4.1 PROC MIXED Model Coefficients

MIXED Model Coefficients (First Two Imputations)				
Obs	_Imputation_	Effect	Estimate	StdErr
1	1	Intercept	148.09	81.5231
2	1	RunTime	-8.8115	7.8794
3	1	RunPulse	-0.4123	0.4684
4	1	RunTime*RunPulse	0.03437	0.04517
5	2	Intercept	64.3607	64.6034
6	2	RunTime	-1.1270	6.4307
7	2	RunPulse	0.08160	0.3688
8	2	RunTime*RunPulse	-0.01069	0.03664

The following statements display (in [Output 55.4.2](#)) the output covariance matrices associated with the parameter estimates from PROC MIXED for the first two imputed data sets:

```
proc print data=mixcovb (obs=8);
  var _Imputation_ Row Effect Col1 Col2 Col3 Col4;
  title 'Covariance Matrices (First Two Imputations)';
run;
```

Output 55.4.2 PROC MIXED Covariance Matrices

Covariance Matrices (First Two Imputations)						
Obs	_Imputation_	Row Effect	Col1	Col2	Col3	Col4
1	1	1 Intercept	6646.01	-637.40	-38.1515	3.6542
2	1	2 RunTime	-637.40	62.0842	3.6548	-0.3556
3	1	3 RunPulse	-38.1515	3.6548	0.2194	-0.02099
4	1	4 RunTime*RunPulse	3.6542	-0.3556	-0.02099	0.002040
5	2	1 Intercept	4173.59	-411.46	-23.7889	2.3441
6	2	2 RunTime	-411.46	41.3545	2.3414	-0.2353
7	2	3 RunPulse	-23.7889	2.3414	0.1360	-0.01338
8	2	4 RunTime*RunPulse	2.3441	-0.2353	-0.01338	0.001343

Note that the variables Col1, Col2, Col3, and Col4 are used to identify the effects Intercept, RunTime, RunPulse, and RunTime*RunPulse, respectively, through the variable Row.

For univariate inference, only parameter estimates and their associated standard errors are needed. The following statements use the MIANALYZE procedure with the input PARMS= data set to produce univariate results:

```
proc mianalyze parms=mixparms edf=28;
  modeleffects Intercept RunTime RunPulse RunTime*RunPulse;
run;
```


The “Variance Information” table in [Output 55.4.3](#) displays the between-imputation, within-imputation, and total variances for combining complete-data inferences.

Output 55.4.3 Variance Information

The MIANALYZE Procedure				
Variance Information				
Parameter	-----Variance-----			DF
	Between	Within	Total	
Intercept	1972.654530	4771.948777	7139.134213	11.82
RunTime	14.712602	45.549686	63.204808	13.797
RunPulse	0.062941	0.156717	0.232247	12.046
RunTime*RunPulse	0.000470	0.001490	0.002055	13.983
Variance Information				
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
Intercept	0.496063	0.365524	0.931875	
RunTime	0.387601	0.305893	0.942348	
RunPulse	0.481948	0.358274	0.933136	
RunTime*RunPulse	0.378863	0.300674	0.943276	

The “Parameter Estimates” table in [Output 55.4.4](#) displays the estimated mean and standard error of the regression coefficients.

Output 55.4.4 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
Intercept	136.071356	84.493397	-48.3352	320.4779	11.82
RunTime	-7.457186	7.950145	-24.5322	9.6178	13.797
RunPulse	-0.328104	0.481920	-1.3777	0.7215	12.046
RunTime*RunPulse	0.025364	0.045328	-0.0719	0.1226	13.983

Parameter Estimates		
Parameter	Minimum	Maximum
Intercept	64.360719	186.549814
RunTime	-11.514341	-1.127010
RunPulse	-0.602162	0.081597
RunTime*RunPulse	-0.010690	0.047429

Parameter Estimates			
Parameter	Theta0	t for H0:	
		Parameter=Theta0	Pr > t
Intercept	0	1.61	0.1337
RunTime	0	-0.94	0.3644
RunPulse	0	-0.68	0.5089
RunTime*RunPulse	0	0.56	0.5846

Since each covariance matrix contains variables Row, Col1, Col2, Col3, and Col4 for parameters, the EFFECTVAR=ROWCOL option is needed when you specify the COVB= option. The following statements illustrate the use of the MIANALYZE procedure with input PARMS= and COVB(EFFECTVAR=ROWCOL)= data sets:

```
proc mianalyze parms=mixparms edf=28
    covb(effectvar=rowcol)=mixcovb;
    modeleffects Intercept RunTime RunPulse RunTime*RunPulse;
run;
```

Example 55.5: Reading Generalized Linear Model Results

This example creates data sets containing parameter estimates and corresponding covariance matrices computed by a generalized linear model analysis for a set of imputed data sets. These estimates are then combined to generate valid statistical inferences about the model parameters.

The following statements use PROC GENMOD to generate the parameter estimates and covariance matrix for each imputed data set:

```
proc genmod data=outmi;
  model Oxygen= RunTime RunPulse/covb;
  by _Imputation_;
  ods output ParameterEstimates=gmparms
             ParmInfo=gmpinfo
             CovB=gmcovb;
run;
```

The following statements print (in [Output 55.5.1](#)) the output parameter estimates and covariance matrix from PROC GENMOD for the first two imputed data sets:

```
proc print data=gmparms (obs=8);
  var _Imputation_ Parameter Estimate StdErr;
  title 'GENMOD Model Coefficients (First Two Imputations)';
run;
```

Output 55.5.1 PROC GENMOD Model Coefficients

GENMOD Model Coefficients (First Two Imputations)				
Obs	_Imputation_	Parameter	Estimate	StdErr
1	1	Intercept	86.5440	9.5107
2	1	RunTime	-2.8223	0.3120
3	1	RunPulse	-0.0587	0.0556
4	1	Scale	2.6692	0.3390
5	2	Intercept	83.0207	8.4489
6	2	RunTime	-3.0002	0.3217
7	2	RunPulse	-0.0249	0.0488
8	2	Scale	2.5727	0.3267

The following statements display the parameter information table in [Output 55.5.2](#). The table identifies parameter names used in the covariance matrices. The parameters Prm1, Prm2, and Prm3 are used for the effects Intercept, RunTime, and RunPulse, respectively, in each covariance matrix.

```
proc print data=gmpinfo (obs=6);
  title 'GENMOD Parameter Information (First Two Imputations)';
run;
```

Output 55.5.2 PROC GENMOD Model Information

GENMOD Parameter Information (First Two Imputations)				
Obs	_Imputation_	Parameter	Effect	
1	1	Prm1	Intercept	
2	1	Prm2	RunTime	
3	1	Prm3	RunPulse	
4	2	Prm1	Intercept	
5	2	Prm2	RunTime	
6	2	Prm3	RunPulse	

The following statements display (in [Output 55.5.3](#)) the output covariance matrices from PROC GENMOD for the first two imputed data sets. Note that the GENMOD procedure computes maximum likelihood estimates for each covariance matrix.

```
proc print data=gmcovb (obs=8);
  var _Imputation_ RowName Prm1 Prm2 Prm3;
  title 'GENMOD Covariance Matrices (First Two Imputations)';
run;
```

Output 55.5.3 PROC GENMOD Covariance Matrices

GENMOD Covariance Matrices (First Two Imputations)					
Obs	_Imputation_	Row Name	Prm1	Prm2	Prm3
1	1	Prm1	90.453923	-0.483394	-0.497473
2	1	Prm2	-0.483394	0.0973159	-0.003113
3	1	Prm3	-0.497473	-0.003113	0.0030954
4	1	Scale	1.344E-15	-1.09E-17	-6.12E-18
5	2	Prm1	71.383332	-0.603037	-0.378616
6	2	Prm2	-0.603037	0.1034766	-0.002826
7	2	Prm3	-0.378616	-0.002826	0.0023843
8	2	Scale	1.602E-14	1.755E-16	-1.02E-16

The following statements use the MIANALYZE procedure with input PARMS=, PARMINFO=, and COVB= data sets:

```
proc mianalyze parms=gmparms covb=gmcovb parminfo=gmpinfo;
  modeleffects Intercept RunTime RunPulse;
run;
```

Since the GENMOD procedure computes maximum likelihood estimates for the covariance matrix, the EDF= option is not used. The resulting model coefficients are identical to the estimates in [Output 55.3.3](#) in [Example 55.3](#). However, the standard errors are slightly different because in this example, maximum likelihood estimates for the standard errors are combined without the EDF= option, whereas in [Example 55.3](#), unbiased estimates for the standard errors are combined with the EDF= option.

Example 55.6: Reading GLM Results from PARMS= and XPXI= Data Sets

This example creates data sets containing parameter estimates and corresponding $(X'X)^{-1}$ matrices computed by a general linear model analysis for a set of imputed data sets. These estimates are then combined to generate valid statistical inferences about the model parameters.

The following statements use PROC GLM to generate the parameter estimates and $(X'X)^{-1}$ matrix for each imputed data set:

```
proc glm data=outmi;
  model Oxygen= RunTime RunPulse/inverse;
  by _Imputation_;
  ods output ParameterEstimates=glmparms
             InvXPX=glmxpxi;
quit;
```

The following statements display (in [Output 55.6.1](#)) the output parameter estimates and standard errors from PROC GLM for the first two imputed data sets:

```
proc print data=glmparms (obs=6);
  var _Imputation_ Parameter Estimate StdErr;
  title 'GLM Model Coefficients (First Two Imputations)';
run;
```

Output 55.6.1 PROC GLM Model Coefficients

GLM Model Coefficients (First Two Imputations)				
Obs	_Imputation_	Parameter	Estimate	StdErr
1	1	Intercept	86.5440339	10.00726811
2	1	RunTime	-2.8223108	0.32824165
3	1	RunPulse	-0.0587292	0.05854109
4	2	Intercept	83.0207303	8.88996885
5	2	RunTime	-3.0002288	0.33847204
6	2	RunPulse	-0.0249103	0.05137859

The following statements display (in [Output 55.6.2](#)) $(X'X)^{-1}$ matrices from PROC GLM for the first two imputed data sets:

```
proc print data=glmxpxi (obs=8);
  var _Imputation_ Parameter Intercept RunTime RunPulse;
  title 'GLM X'X Inverse Matrices (First Two Imputations)';
run;
```

Output 55.6.2 PROC GLM $(X'X)^{-1}$ Matrices

GLM X'X Inverse Matrices (First Two Imputations)					
Obs	_Imputation_	Parameter	Intercept	RunTime	RunPulse
1	1	Intercept	12.696250656	-0.067849956	-0.069826009
2	1	RunTime	-0.067849956	0.0136594055	-0.000436938
3	1	RunPulse	-0.069826009	-0.000436938	0.0004344762
4	1	Oxygen	86.544033929	-2.822310769	-0.058729234
5	2	Intercept	10.784620785	-0.091107072	-0.057201387
6	2	RunTime	-0.091107072	0.0156332765	-0.000426902
7	2	RunPulse	-0.057201387	-0.000426902	0.0003602208
8	2	Oxygen	83.020730343	-3.000228818	-0.024910305

The standard errors for the estimates in the output glmparms data set are needed to create the covariance matrix from the $(X'X)^{-1}$ matrix. The following statements use the MIANALYZE procedure with input PARMS= and XPXI= data sets to produce the same results as displayed in [Output 55.3.2](#) and [Output 55.3.3](#) in [Example 55.3](#):

```
proc mianalyze parms=glmparms xpxi=glmxpxi edf=28;
  modeleffects Intercept RunTime RunPulse;
run;
```

Example 55.7: Reading Logistic Model Results from PARMS= and COVB= Data Sets

This example creates data sets containing parameter estimates and corresponding covariance matrices computed by a logistic regression analysis for a set of imputed data sets. These estimates are then combined to generate valid statistical inferences about the model parameters.

The following statements use PROC LOGISTIC to generate the parameter estimates and covariance matrix for each imputed data set:

```
proc logistic data=outfish;
  class Species;
  model Species= Height Width Height*Width/ covb;
  by _Imputation_;
  ods output ParameterEstimates=lgsparms
             CovB=lgscovb;
run;
```

The following statements display (in [Output 55.7.1](#)) the output logistic regression coefficients from PROC LOGISTIC for the first two imputed data sets:

```
proc print data=lgsparms (obs=8);
  title 'LOGISTIC Model Coefficients (First Two Imputations)';
run;
```

Output 55.7.1 PROC LOGISTIC Model Coefficients

LOGISTIC Model Coefficients (First Two Imputations)							
Obs	_Imputation_	Variable	DF	Estimate	StdErr	WaldChiSq	Prob ChiSq
1	1	Intercept	1	-22.7507	45.7309	0.2475	0.6188
2	1	Height	1	4.3267	3.7473	1.3332	0.2482
3	1	Width	1	-1.7027	7.8049	0.0476	0.8273
4	1	Height*Width	1	-0.3517	0.5542	0.4028	0.5256
5	2	Intercept	1	-27.2116	26.3744	1.0645	0.3022
6	2	Height	1	4.1833	2.0347	4.2271	0.0398
7	2	Width	1	1.1045	6.1278	0.0325	0.8570
8	2	Height*Width	1	-0.4495	0.3251	1.9116	0.1668

The following statements displays the covariance matrices associated with parameter estimates derived from the first two imputations in [Output 55.7.2](#):

```
proc print data=lgscovb (obs=8);
  title 'LOGISTIC Model Covariance Matrices (First Two Imputations)';
run;
```

Output 55.7.2 PROC LOGISTIC Covariance Matrices

LOGISTIC Model Covariance Matrices (First Two Imputations)						
Obs	_Imputation_	Parameter	Intercept	Height	Width	Height Width
1	1	Intercept	2091.316	-158.686	-330.408	24.9984
2	1	Height	-158.686	14.04241	21.1609	-1.98425
3	1	Width	-330.408	21.1609	60.91617	-3.84737
4	1	HeightWidth	24.9984	-1.98425	-3.84737	0.307092
5	2	Intercept	695.6072	-36.8743	-148.034	7.997264
6	2	Height	-36.8743	4.139861	4.497508	-0.57405
7	2	Width	-148.034	4.497508	37.55025	-1.52686
8	2	HeightWidth	7.997264	-0.57405	-1.52686	0.105678

The following statements use the MIANALYZE procedure with input PARMS= and COVB= data sets:

```
proc mianalyze parms=lgsparms
  covb(effectvar=stacking)=lgscovb;
  modeleffects Intercept Height Width Height*Width;
run;
```

The “Variance Information” table in [Output 55.7.3](#) displays the between-imputation, within-imputation, and total variances for combining complete-data inferences.

Output 55.7.3 Variance Information

The MIANALYZE Procedure				
Variance Information				
Parameter	-----Variance-----			DF
	Between	Within	Total	
Intercept	5.034765	1668.718613	1674.760331	307358
Height	0.024662	11.102796	11.132390	565996
Width	2.258894	53.686948	56.397621	1731.5
Height*Width	0.002655	0.245967	0.249153	24467
Variance Information				
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
Intercept	0.003621	0.003614	0.999278	
Height	0.002666	0.002662	0.999468	
Width	0.050490	0.049161	0.990263	
Height*Width	0.012952	0.012867	0.997433	

The “Parameter Estimates” table in [Output 55.7.4](#) displays the combined parameter estimates with associated standard errors.

Output 55.7.4 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
Intercept	-25.952920	40.923836	-106.162	54.25664	307358
Height	4.367841	3.336524	-2.172	10.90732	565996
Width	-0.321990	7.509835	-15.051	14.40731	1731.5
Height*Width	-0.408057	0.499152	-1.386	0.57031	24467

Parameter Estimates		
Parameter	Minimum	Maximum
Intercept	-28.627325	-22.750660
Height	4.183264	4.570938
Width	-1.702651	1.500299
Height*Width	-0.473804	-0.351718

Parameter Estimates			
Parameter	Theta0	t for H0:	
		Parameter=Theta0	Pr > t
Intercept	0	-0.63	0.5260
Height	0	1.31	0.1905
Width	0	-0.04	0.9658
Height*Width	0	-0.82	0.4137

Example 55.8: Reading Mixed Model Results with Classification Variables

This example creates data sets containing parameter estimates and corresponding covariance matrices with classification variables computed by a mixed regression model analysis for a set of imputed data sets. These estimates are then combined to generate valid statistical inferences about the model parameters.

The following statements use PROC MIXED to generate the parameter estimates and covariance matrix for each imputed data set:

```
proc mixed data=outfish;
  class Species;
  model Length3= Species Height Width/ solution covb;
  by _Imputation_;
  ods output SolutionF=mxparms CovB=mxcovb;
run;
```

The following statements display (in [Output 55.8.1](#)) the output mixed model coefficients from PROC MIXED for the first two imputed data sets:

```
proc print data=mxparms (obs=10);
  var _Imputation_ Effect Species Estimate StdErr;
  title 'MIXED Model Coefficients (First Two Imputations)';
run;
```

Output 55.8.1 PROC MIXED Model Coefficients

MIXED Model Coefficients (First Two Imputations)					
Obs	_Imputation_	Effect	Species	Estimate	StdErr
1	1	Intercept		6.8207	1.0248
2	1	Species	Gp1	-0.00467	0.8550
3	1	Species	Gp2	0	.
4	1	Height		0.9085	0.1964
5	1	Width		3.2744	0.5643
6	2	Intercept		6.9259	0.9823
7	2	Species	Gp1	-0.3542	0.8605
8	2	Species	Gp2	0	.
9	2	Height		0.9630	0.1910
10	2	Width		3.1548	0.5370

The following statements use the MIANALYZE procedure with an input PARMS= data set:

```
proc mianalyze parms(classvar=full)=mxparms;
  class Species;
  modeleffects Intercept Species Height Width;
run;
```

The “Variance Information” table in [Output 55.8.2](#) displays the between-imputation, within-imputation, and total variances for combining complete-data inferences.

Output 55.8.2 Variance Information

The MIANALYZE Procedure					
Variance Information					
-----Variance-----					
Parameter	Species	Between	Within	Total	DF
Intercept		0.013439	1.008137	1.024263	16136
Species	Gp1	0.131130	0.719737	0.877093	124.28
Species	Gp2	0	.	.	.
Height		0.005162	0.037108	0.043302	195.48
Width		0.025787	0.302173	0.333117	463.55
Variance Information					
Parameter	Species	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
Intercept		0.015996	0.015866	0.996837	
Species	Gp1	0.218629	0.192300	0.962964	
Species	Gp2	.	.	.	
Height		0.166925	0.151682	0.970557	
Width		0.102406	0.096781	0.981011	

The “Parameter Estimates” table in [Output 55.8.3](#) displays the combined parameter estimates with associated standard errors.

Output 55.8.3 Parameter Estimates

Parameter Estimates						
Parameter	Species	Estimate	Std Error	95% Confidence Limits		DF
Intercept		6.825324	1.012059	4.84158	8.809072	16136
Species	Gp1	-0.174302	0.936532	-2.02792	1.679317	124.28
Species	Gp2	0
Height		0.927390	0.208091	0.51700	1.337782	195.48
Width		3.242346	0.577163	2.10817	4.376527	463.55

Parameter Estimates				
Parameter	Species	Minimum	Maximum	
Intercept		6.692058	6.956116	
Species	Gp1	-0.726082	0.129023	
Species	Gp2	0	0	
Height		0.860775	1.034011	
Width		3.011865	3.400082	

Parameter Estimates				
Parameter	Species	Theta0	t for H0: Parameter=Theta0	Pr > t
Intercept		0	6.74	<.0001
Species	Gp1	0	-0.19	0.8527
Species	Gp2	0	.	.
Height		0	4.46	<.0001
Width		0	5.62	<.0001

Example 55.9: Using a TEST statement

This example creates an EST-type data set that contains regression coefficients and their corresponding covariance matrices computed from imputed data sets. These estimates are then combined to generate valid statistical inferences about the regression model. A TEST statement is used to test linear hypotheses about the parameters.

The following statements use the REG procedure to generate regression coefficients:

```
proc reg data=outmi outest=outreg covout noprint;
  model Oxygen= RunTime RunPulse;
  by _Imputation_;
run;
```

The following statements combine the results for the imputed data sets. A TEST statement is used to test linear hypotheses of Intercept=0 and RunTime=RunPulse.

```
proc mianalyze data=outreg edf=28;
  modeleffects Intercept RunTime RunPulse;
  test Intercept, RunTime=RunPulse / mult;
run;
```

The “Test Specification” table in [Output 55.9.1](#) displays the **L** matrix and the **c** vector in a TEST statement. Since there is no label specified for the TEST statement, “Test 1” is used as the label.

Output 55.9.1 Test Specification

The MIANALYZE Procedure				
Test: Test 1				
Test Specification				
-----L Matrix-----				
Parameter	Intercept	RunTime	RunPulse	C
TestPrm1	1.000000	0	0	0
TestPrm2	0	1.000000	-1.000000	0

The “Variance Information” table in [Output 55.9.2](#) displays the between-imputation variance, within-imputation variance, and total variance for each univariate inference. A detailed description of these statistics is provided in the section “[Combining Inferences from Imputed Data Sets](#)” on page 4477 and the section “[Multiple Imputation Efficiency](#)” on page 4478.

Output 55.9.2 Variance Information

Variance Information				
-----Variance-----				
Parameter	Between	Within	Total	DF
TestPrm1	45.529229	76.543614	131.178689	9.1917
TestPrm2	0.014715	0.114324	0.131983	20.598
Variance Information				
Parameter	Relative Increase in Variance	Fraction Missing Information	Relative Efficiency	
TestPrm1	0.713777	0.461277	0.915537	
TestPrm2	0.154459	0.141444	0.972490	

The “Parameter Estimates” table in [Output 55.9.3](#) displays the estimated mean and standard error of the linear components. The inferences are based on the t distribution. The table also displays a 95% mean confidence interval and a t test with the associated p -value for the hypothesis that each linear component of $\mathbf{L}\boldsymbol{\beta}$ is equal to zero.

Output 55.9.3 Parameter Estimates

Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
TestPrm1	90.837440	11.453327	65.01034	116.6645	9.1917
TestPrm2	-2.964292	0.363294	-3.72070	-2.2079	20.598
Parameter Estimates					
Parameter	Minimum	Maximum	t for H0:		
			C	Parameter=C	Pr > t
TestPrm1	83.020730	100.839807	0	7.93	<.0001
TestPrm2	-3.091586	-2.763582	0	-8.16	<.0001

With the MULT option, the procedure assumes that the between-imputation covariance matrix is proportional to the within-imputation covariance matrix and displays a multivariate inference for all the linear components taken jointly in [Output 55.9.4](#).

Output 55.9.4 Multivariate Inference

Multivariate Inference					
Assuming Proportionality of Between/Within Covariance Matrices					
Avg Relative Increase in Variance	Num DF	Den DF	F for H0:		
			Parameter=Theta0	Pr > F	
0.419868	2	35.053	60.34	<.0001	

Example 55.10: Combining Correlation Coefficients

This example combines sample correlation coefficients computed from a set of imputed data sets by using Fisher’s z transformation.

Fisher’s z transformation of the sample correlation r is

$$z = \frac{1}{2} \log \left(\frac{1+r}{1-r} \right)$$

The statistic z is approximately normally distributed with mean

$$\log \left(\frac{1 + \rho}{1 - \rho} \right)$$

and variance $1/(n - 3)$, where ρ is the population correlation coefficient and n is the number of observations.

The following statements use the CORR procedure to compute the correlation r and its associated Fisher's z statistic between variables Oxygen and RunTime for each imputed data set. The ODS statement is used to save Fisher's z statistic in an output data set.

```
proc corr data=outmi fisher(biasadj=no);
  var Oxygen RunTime;
  by _Imputation_;
  ods output FisherPearsonCorr= outz;
run;
```

The following statements display the number of observations and Fisher's z statistic for each imputed data set in [Output 55.10.1](#):

```
proc print data=outz;
  title 'Fisher's Correlation Statistics';
  var _Imputation_ NObs ZVal;
run;
```

Output 55.10.1 Output z Statistics

Fisher's Correlation Statistics				
Obs	_Imputation_	NObs	ZVal	
1	1	31	-1.27869	
2	2	31	-1.30715	
3	3	31	-1.27922	
4	4	31	-1.39243	
5	5	31	-1.40146	

The following statements generate the standard error associated with the z statistic, $1/\sqrt{n - 3}$:

```
data outz;
  set outz;
  StdZ= 1. / sqrt(NObs-3);
run;
```

The following statements use the MIANALYZE procedure to generate a combined parameter estimate \hat{z} and its variance, as shown in [Output 55.10.2](#). The ODS statement is used to save the parameter estimates in an output data set.

```
proc mianalyze data=outz;
  ods output ParameterEstimates=parms;
  modeleffects ZVal;
  stderr StdZ;
run;
```

Output 55.10.2 Combining Fisher's z Statistics

The MIANALYZE Procedure					
Parameter Estimates					
Parameter	Estimate	Std Error	95% Confidence Limits		DF
ZVal	-1.331787	0.200327	-1.72587	-0.93771	330.23
Parameter Estimates					
Parameter	Minimum	Maximum			
ZVal	-1.401459	-1.278686			
Parameter Estimates					
Parameter	t for H0:				
	Theta0	Parameter=Theta0	Pr > t		
ZVal	0	-6.65	<.0001		

In addition to the estimate for z , PROC MIANALYZE also generates 95% confidence limits for z , $\hat{z}_{.025}$ and $\hat{z}_{.975}$. The following statements print the estimate and 95% confidence limits for z in [Output 55.10.3](#):

```
proc print data=parms;
  title 'Parameter Estimates with 95% Confidence Limits';
  var Estimate LCLMean UCLMean;
run;
```

Output 55.10.3 Parameter Estimates with 95% Confidence Limits

Parameter Estimates with 95% Confidence Limits				
Obs	Estimate	LCLMean	UCLMean	
1	-1.331787	-1.72587	-0.93771	

An estimate of the correlation coefficient with its corresponding 95% confidence limits is then generated from the following inverse transformation as described in the section “[Correlation Coefficients](#)” on page 4482:

$$r = \tanh(z) = \frac{e^{2z} - 1}{e^{2z} + 1}$$

for $z = \hat{z}$, $\hat{z}_{.025}$, and $\hat{z}_{.975}$.

The following statements generate and display an estimate of the correlation coefficient and its 95% confidence limits, as shown in [Output 55.10.4](#):

```
data corr_ci;
  set parms;
  r=      tanh( Estimate);
  r_lower= tanh( LCLMean);
  r_upper= tanh( UCLMean);
run;
proc print data=corr_ci;
  title 'Estimated Correlation Coefficient'
        ' with 95% Confidence Limits';
  var r r_lower r_upper;
run;
```

Output 55.10.4 Estimated Correlation Coefficient

Estimated Correlation Coefficient with 95% Confidence Limits				
	Obs	r	r_lower	r_upper
	1	-0.86969	-0.93857	-0.73417

References

- Allison, P. D. (2000), “Multiple Imputation for Missing Data: A Cautionary Tale,” *Sociological Methods and Research*, 28, 301–309.
- Allison, P. D. (2001), “Missing Data,” Thousand Oaks, CA: Sage Publications.
- Barnard, J. and Rubin, D. B. (1999), “Small-Sample Degrees of Freedom with Multiple Imputation,” *Biometrika*, 86, 948–955.
- Cochran, W. J. (1977), *Sampling Techniques*, Second Edition, New York: John Wiley & Sons.
- Gadbury, G. L., Coffey, C. S., and Allison, D. B. (2003), “Modern Statistical Methods for Handling Missing Repeated Measurements in Obesity Trial Data: Beyond LOCF,” *Obesity Reviews*, 4, 175–184.

Horton, N. J. and Lipsitz, S. R. (2001), “Multiple Imputation in Practice: Comparison of Software Packages for Regression Models with Missing Variables,” *Journal of the American Statistical Association*, 55, 244–254.

Li, K. H., Raghunathan, T. E., and Rubin, D. B. (1991), “Large-Sample Significance Levels from Multiply Imputed Data Using Moment-Based Statistics and an F Reference Distribution,” *Journal of the American Statistical Association*, 86, 1065–1073.

Little, R. J. A. and Rubin, D. B. (2002), *Statistical Analysis with Missing Data*, Second Edition, New York: John Wiley & Sons.

Rubin, D. B. (1976), “Inference and Missing Data,” *Biometrika*, 63, 581–592.

Rubin, D. B. (1987), *Multiple Imputation for Nonresponse in Surveys*, New York: John Wiley & Sons.

Rubin, D. B. (1996), “Multiple Imputation after 18+ Years,” *Journal of the American Statistical Association*, 91, 473–489.

Schafer, J. L. (1997), *Analysis of Incomplete Multivariate Data*, New York: Chapman and Hall.

Subject Index

- adjusted degrees of freedom
 - MIANALYZE procedure, [4478](#)
- average relative increase in variance
 - MIANALYZE procedure, [4480](#)
- between-imputation covariance matrix
 - MIANALYZE procedure, [4479](#)
- between-imputation variance
 - MIANALYZE procedure, [4477](#)
- combining inferences
 - MIANALYZE procedure, [4477](#)
- degrees of freedom
 - MIANALYZE procedure, [4478](#), [4480](#)
- fraction of missing information
 - MIANALYZE procedure, [4478](#)
- input data sets
 - MIANALYZE procedure, [4473](#)
- MIANALYZE procedure
 - adjusted degrees of freedom, [4478](#)
 - average relative increase in variance, [4480](#)
 - between-imputation covariance matrix, [4479](#)
 - between-imputation variance, [4477](#)
 - combining inferences, [4477](#)
 - degrees of freedom, [4478](#), [4480](#)
 - fraction of missing information, [4478](#)
 - input data sets, [4473](#)
 - introductory example, [4463](#)
 - multiple imputation efficiency, [4478](#)
 - multivariate inferences, [4479](#)
 - ODS table names, [4483](#)
 - relative efficiency, [4478](#)
 - relative increase in variance, [4478](#)
 - syntax, [4466](#)
 - testing linear hypotheses, [4471](#), [4481](#)
 - total covariance matrix, [4480](#)
 - total variance, [4478](#)
 - within-imputation covariance matrix, [4479](#)
 - within-imputation variance, [4477](#)
- multiple imputation efficiency
 - MIANALYZE procedure, [4478](#)
- multiple imputations analysis, [4462](#)
- multivariate inferences
 - MIANALYZE procedure, [4479](#)
- relative efficiency
 - MIANALYZE procedure, [4478](#)
- relative increase in variance
 - MIANALYZE procedure, [4478](#)
- testing linear hypotheses
 - MIANALYZE procedure, [4471](#), [4481](#)
- total covariance matrix
 - MIANALYZE procedure, [4480](#)
- total variance
 - MIANALYZE procedure, [4478](#)
- within-imputation covariance matrix
 - MIANALYZE procedure, [4479](#)
- within-imputation variance
 - MIANALYZE procedure, [4477](#)

Syntax Index

- ALPHA= option
 - PROC MIANALYZE statement, [4467](#)
- BCOV option
 - PROC MIANALYZE statement, [4467](#)
 - TEST statement (MIANALYZE), [4472](#)
- BY statement
 - MIANALYZE procedure, [4469](#)
- CLASS statement
 - MIANALYZE procedure, [4470](#)
- CLASSVAR= option
 - PROC MIANALYZE statement, [4468](#)
- COVB= option
 - PROC MIANALYZE statement, [4467](#)
- DATA= option
 - PROC MIANALYZE statement, [4467](#)
- EDF= option
 - PROC MIANALYZE statement, [4468](#)
- EFFECTVAR= option
 - PROC MIANALYZE statement, [4467](#)
- MIANALYZE procedure, BY statement, [4469](#)
- MIANALYZE procedure, CLASS statement, [4470](#)
- MIANALYZE procedure, MODELEFFECTS statement, [4470](#)
- MIANALYZE procedure, PROC MIANALYZE statement, [4466](#)
 - ALPHA= option, [4467](#)
 - BCOV option, [4467](#)
 - CLASSVAR= option, [4468](#)
 - COVB= option, [4467](#)
 - DATA= option, [4467](#)
 - EDF= option, [4468](#)
 - EFFECTVAR= option, [4467](#)
 - MU0= option, [4469](#)
 - MULT option, [4468](#)
 - PARMINFO= option, [4468](#)
 - PARMS= option, [4468](#)
 - TCOV option, [4468](#)
 - THETA0= option, [4469](#)
 - WCOV option, [4469](#)
 - XPXI= option, [4469](#)
- MIANALYZE procedure, STDERR statement, [4471](#)
- MIANALYZE procedure, TEST statement, [4471](#)
 - BCOV option, [4472](#)
 - MULT option, [4472](#)
 - TCOV option, [4472](#)
 - WCOV option, [4473](#)
- MODELEFFECTS statement
 - MIANALYZE procedure, [4470](#)
- MU0= option
 - PROC MIANALYZE statement, [4469](#)
- MULT option
 - PROC MIANALYZE statement, [4468](#)
 - TEST statement (MIANALYZE), [4472](#)
- PARMINFO= option
 - PROC MIANALYZE statement, [4468](#)
- PARMS= option
 - PROC MIANALYZE statement, [4468](#)
- PROC MIANALYZE statement, *see*
 - MIANALYZE procedure
- STDERR statement
 - MIANALYZE procedure, [4471](#)
- TCOV option
 - PROC MIANALYZE statement, [4468](#)
 - TEST statement (MIANALYZE), [4472](#)
- TEST statement
 - MIANALYZE procedure, [4471](#)
- THETA0= option
 - PROC MIANALYZE statement, [4469](#)
- WCOV option
 - PROC MIANALYZE statement, [4469](#)
 - TEST statement (MIANALYZE), [4473](#)
- XPXI= option
 - PROC MIANALYZE statement, [4469](#)

Your Turn

We welcome your feedback.

- If you have comments about this book, please send them to **`yourturn@sas.com`**. Include the full title and page numbers (if applicable).
- If you have comments about the software, please send them to **`suggest@sas.com`**.

SAS® Publishing Delivers!

Whether you are new to the work force or an experienced professional, you need to distinguish yourself in this rapidly changing and competitive job market. SAS® Publishing provides you with a wide range of resources to help you set yourself apart. Visit us online at support.sas.com/bookstore.

SAS® Press

Need to learn the basics? Struggling with a programming problem? You'll find the expert answers that you need in example-rich books from SAS Press. Written by experienced SAS professionals from around the world, SAS Press books deliver real-world insights on a broad range of topics for all skill levels.

support.sas.com/saspress

SAS® Documentation

To successfully implement applications using SAS software, companies in every industry and on every continent all turn to the one source for accurate, timely, and reliable information: SAS documentation. We currently produce the following types of reference documentation to improve your work experience:

- Online help that is built into the software.
- Tutorials that are integrated into the product.
- Reference documentation delivered in HTML and PDF – **free** on the Web.
- Hard-copy books.

support.sas.com/publishing

SAS® Publishing News

Subscribe to SAS Publishing News to receive up-to-date information about all new SAS titles, author podcasts, and new Web site features via e-mail. Complete instructions on how to subscribe, as well as access to past issues, are available at our Web site.

support.sas.com/spn



**THE
POWER
TO KNOW®**

