

SAS/STAT[®] 14.2 User's Guide

Sashelp Data Sets

This document is an individual chapter from *SAS/STAT® 14.2 User's Guide*.

The correct bibliographic citation for this manual is as follows: SAS Institute Inc. 2016. *SAS/STAT® 14.2 User's Guide*. Cary, NC: SAS Institute Inc.

SAS/STAT® 14.2 User's Guide

Copyright © 2016, SAS Institute Inc., Cary, NC, USA

All Rights Reserved. Produced in the United States of America.

For a hard-copy book: No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc.

For a web download or e-book: Your use of this publication shall be governed by the terms established by the vendor at the time you acquire this publication.

The scanning, uploading, and distribution of this book via the Internet or any other means without the permission of the publisher is illegal and punishable by law. Please purchase only authorized electronic editions and do not participate in or encourage electronic piracy of copyrighted materials. Your support of others' rights is appreciated.

U.S. Government License Rights; Restricted Rights: The Software and its documentation is commercial computer software developed at private expense and is provided with RESTRICTED RIGHTS to the United States Government. Use, duplication, or disclosure of the Software by the United States Government is subject to the license terms of this Agreement pursuant to, as applicable, FAR 12.212, DFAR 227.7202-1(a), DFAR 227.7202-3(a), and DFAR 227.7202-4, and, to the extent required under U.S. federal law, the minimum restricted rights as set out in FAR 52.227-19 (DEC 2007). If FAR 52.227-19 is applicable, this provision serves as notice under clause (c) thereof and no other notice is required to be affixed to the Software or documentation. The Government's rights in Software and documentation shall be only those set forth in this Agreement.

SAS Institute Inc., SAS Campus Drive, Cary, NC 27513-2414

November 2016

SAS® and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries. ® indicates USA registration.

Other brand and product names are trademarks of their respective companies.

SAS software may be provided with certain third-party software, including but not limited to open-source software, which is licensed under its applicable third-party software license agreement. For license information about third-party software distributed with SAS software, refer to <http://support.sas.com/thirdpartylicenses>.

Appendix B

Sashelp Data Sets

Contents

Overview of Sashelp Data Sets	10167
Baseball Data	10169
Tropical Rain Forest Tree Data	10171
Body Mass Index for Men	10174
Isopod Burrows Data	10175
Bone Marrow Transplant Data	10177
Birth Weight Data	10178
Class Data	10179
Comet Data	10180
El Niño–Southern Oscillation Data	10181
Finland’s Lake Laengelmaevesi Fish Catch Data	10182
Exhaust Emissions Data	10184
Fisher (1936) Iris Data	10185
Junk Email Data	10186
Leukemia Data Sets	10189
Margarine Data	10191
Flying Mileages between 10 US Cities Data	10192
Earthquake Locations in the United States	10193
Hot-Spring Locations in the United States	10194
Coal Seam Thickness Data	10195
1980 US Presidential Election Data	10196
References	10197

Overview of Sashelp Data Sets

SAS provides more than 200 data sets in the Sashelp library. These data sets are available for you to use for examples and for testing code. For example, the following step uses the Sashelp.Class data set:

```
proc reg data=sashelp.Class;  
    model weight = height;  
run; quit;
```

You do not need to provide a DATA step to use Sashelp data sets.

The following steps list all the data sets that are available in Sashelp:

```
ods select none;
proc contents data=sashelp._all_;
    ods output members=m;
run;
ods select all;

proc print;
    where memtype = 'DATA';
run;
```

The results of these steps (more than 200 data set names) are not displayed.

The following steps provide detailed information about the Sashelp data sets:

```
proc contents data=sashelp._all_;
run;
```

The results of this step (hundreds of pages of PROC CONTENTS output) are not displayed.

Twenty-one Sashelp data sets are used in SAS/STAT documentation, and the following sections describe these data sets:

Sashelp.Baseball	“Baseball Data” on page 10169
Sashelp.BEI	“Tropical Rain Forest Tree Data” on page 10171
Sashelp.BMIMen	“Body Mass Index for Men” on page 10174
Sashelp.BMT	“Bone Marrow Transplant Data” on page 10177
Sashelp.Burrows	“Isopod Burrows Data” on page 10175
Sashelp.BWeight	“Birth Weight Data” on page 10178
Sashelp.Class	“Class Data” on page 10179
Sashelp.Comet	“Comet Data” on page 10180
Sashelp.ENS0	“El Niño–Southern Oscillation Data” on page 10181
Sashelp.Fish	“Finland’s Lake Laengelmävesi Fish Catch Data” on page 10182
Sashelp.Gas	“Exhaust Emissions Data” on page 10184
Sashelp.Iris	“Fisher (1936) Iris Data” on page 10185
Sashelp.JunkMail	“Junk Email Data” on page 10186
Sashelp.LeuTest	“Leukemia Data Sets” on page 10189
Sashelp.LeuTrain	“Leukemia Data Sets” on page 10189
Sashelp.Margarin	“Margarine Data” on page 10191
Sashelp.Mileages	“Flying Mileages between 10 US Cities Data” on page 10192
Sashelp.Quakes	“Earthquake Locations in the United States” on page 10193
Sashelp.Springs	“Hot-Spring Locations in the United States” on page 10194
Sashelp.Thick	“Coal Seam Thickness Data” on page 10195
Sashelp.Vote1980	“1980 US Presidential Election Data” on page 10196

Baseball Data

The Sashelp.Baseball data set contains salary and performance information for Major League Baseball players (excluding pitchers) who played at least one game in both the 1986 and 1987 seasons (Time Inc. 1987). The salaries are for the 1987 season, and the performance measures are from the 1986 season. The following steps display information about the Sashelp.Baseball data set and create [Figure B.1](#):

```
title 'Baseball Data';
proc contents data=sashelp.Baseball varnum;
    ods select position;
run;

title 'The First Five Observations Out of 322';
proc print data=sashelp.Baseball(obs=5);
run;
```

Figure B.1 Baseball Data

Baseball Data				
Variables in Creation Order				
#	Variable	Type	Len	Label
1	Name	Char	18	Player's Name
2	Team	Char	14	Team at the End of 1986
3	nAtBat	Num	8	Times at Bat in 1986
4	nHits	Num	8	Hits in 1986
5	nHome	Num	8	Home Runs in 1986
6	nRuns	Num	8	Runs in 1986
7	nRBI	Num	8	RBIs in 1986
8	nBB	Num	8	Walks in 1986
9	YrMajor	Num	8	Years in the Major Leagues
10	CrAtBat	Num	8	Career Times at Bat
11	CrHits	Num	8	Career Hits
12	CrHome	Num	8	Career Home Runs
13	CrRuns	Num	8	Career Runs
14	CrRbi	Num	8	Career RBIs
15	CrBB	Num	8	Career Walks
16	League	Char	8	League at the End of 1986
17	Division	Char	8	Division at the End of 1986
18	Position	Char	8	Position(s) in 1986
19	nOuts	Num	8	Put Outs in 1986
20	nAssts	Num	8	Assists in 1986
21	nError	Num	8	Errors in 1986
22	Salary	Num	8	1987 Salary in \$ Thousands
23	Div	Char	16	League and Division
24	logSalary	Num	8	Log Salary

Figure B.1 *continued***The First Five Observations Out of 322**

Obs	Name	Team	nAtBat	nHits	nHome	nRuns	nRBI	nBB	YrMajor	CrAtBat	CrHits	CrHome
1	Allanson, Andy	Cleveland	293	66	1	30	29	14	1	293	66	1
2	Ashby, Alan	Houston	315	81	7	24	38	39	14	3449	835	69
3	Davis, Alan	Seattle	479	130	18	66	72	76	3	1624	457	63
4	Dawson, Andre	Montreal	496	141	20	65	78	37	11	5628	1575	225
5	Galarraga, Andres	Montreal	321	87	10	39	42	30	2	396	101	12

Obs	CrRuns	CrRbi	CrBB	League	Division	Position	nOuts	nAssts	nError	Salary	Div	logSalary
1	30	29	14	American	East	C	446	33	20	.	AE	.
2	321	414	375	National	West	C	632	43	10	475.0	NW	6.16331
3	224	266	263	American	West	1B	880	82	14	480.0	AW	6.17379
4	828	838	354	National	East	RF	200	11	3	500.0	NE	6.21461
5	48	46	33	National	East	1B	805	40	4	91.5	NE	4.51634

NOTE: Multiple versions of the baseball data set, including several revisions, are available from other sources.

Tropical Rain Forest Tree Data

The Sashelp.BEI data set contains the locations of 3,604 trees in a number of tropical rain forests (Condit 1998; Hubbell and Foster 1983; Condit, Hubbell, and Foster 1996). A study window of $1,000 \times 500$ square kilometers is used. The data set also contains covariates, represented by the variables Gradient and Elevation, which were collected at over 20,301 locations on a regular grid across the study region. The variable Trees distinguishes the event observations in the data set. The following steps display information about the data set Sashelp.BEI and create [Figure B.2](#):

```
title 'BEI Data';
proc contents data=sashelp.bei varnum;
    ods select position;
run;

title 'The First Five Observations Out of 23,905';
proc print data=sashelp.bei (obs=5);
run;

title 'The Trees Variable';
proc freq data=sashelp.bei;
    tables Trees;
run;
```

Figure B.2 Tropical Rain Forest Tree Data

BEI Data

Variables in Creation Order			
#	Variable	Type	Length
1	X	Num	8
2	Y	Num	8
3	Elevation	Num	8
4	Gradient	Num	8
5	Aluminum	Num	8
6	Boron	Num	8
7	Calcium	Num	8
8	Copper	Num	8
9	Iron	Num	8
10	Potassium	Num	8
11	Magnesium	Num	8
12	Manganese	Num	8
13	Sodium	Num	8
14	Phosphorus	Num	8
15	Sulphur	Num	8
16	Zinc	Num	8
17	Ammonia	Num	8
18	Nitrate	Num	8
19	TotalNitro	Num	8
20	MinAmmonia	Num	8
21	MinNitrate	Num	8
22	MinNitrogen	Num	8
23	pH	Num	8
24	Trees	Num	8

The First Five Observations Out of 23,905

[illegible]

Figure B.2 *continued***The Trees Variable**

Trees	Frequency	Percent	Cumulative Frequency	Cumulative Percent
0	20601	85.11	20601	85.11
1	3604	14.89	24205	100.00

Body Mass Index for Men

The Sashelp.BMIMen data set was collected from the 1999–2000 and 2001–2002 surveys of men that are published by the National Center for Health Statistics. This data set contains the variables BMI and Age. Body mass index (BMI) is defined as the ratio of weight in kilograms to the square of height in meters. BMI is widely used to categorize individuals as overweight or underweight. The following steps display information about the data set Sashelp.BMIMen and create [Figure B.3](#):

```
title 'BMIMen Data';
proc contents data=sashelp.bmimen varnum;
    ods select position;
run;

title 'The First Five Observations Out of 3,264';
proc print data=sashelp.bmimen(obs=5);
run;
```

Figure B.3 Body Mass Index for Men

BMIMen Data

Variables in Creation Order			
#	Variable	Type	Len
1	Age	Num	8
2	BMI	Num	8

The First Five Observations Out of 3,264

Obs	Age	BMI
1	2.0	18.6
2	2.0	17.1
3	2.0	19.0
4	2.0	16.8
5	2.1	19.0

Isopod Burrows Data

The Sashelp.Burrows data set contains the locations of 2,089 burrows, which are the habitat of isopods (“pill bugs”) in the Negev desert in Israel (Banerjee and Gelfand 2002). Each burrow has a Status variable that records whether a burrow still contains live isopods, has been emptied by an isopod predator, or has failed for some other environmental reason. The data set also contains covariates, which are measured on a square-meter grid over the study region. These covariates include topographical characteristics such as Elevation, Slope, Aspect, and PercentRock (the percentage of rocks). The data set also contains environmental characteristics such as PercentShrub (the percentage of shrubs) and Dew (the time in hours since midnight required to evaporate the dew). The following steps display information about the data set Sashelp.Burrows and create Figure B.4:

```

title 'Burrows Data';
proc contents data=sashelp.burrows varnum;
  ods select position;
run;

title 'The First Five Observations Out of 24,591';
proc print data=sashelp.burrows (obs=5);
run;

proc format;
  value bf -1 = "Killed by Predator" 0 = "Failed" 1 = "Successful";
run;

title 'The Status Variable';
proc freq data=sashelp.burrows;
  tables status;
  format status bf.;
run;

```

Figure B.4 Isopod Burrows Data

Burrows Data

Variables in Creation Order			
#	Variable	Type	Len
1	ID	Num	8
2	X	Num	8
3	Y	Num	8
4	Z	Num	8
5	Status	Num	8
6	Watershed	Num	8
7	BurrowCount	Num	8
8	Elevation	Num	8
9	Aspect	Num	8
10	Slope	Num	8
11	Dew	Num	8
12	PercentRock	Num	8
13	PercentShrub	Num	8
14	Burrow	Num	8

Figure B.4 *continued***The First Five Observations Out of 24,591**

Obs	ID	X	Y	Z	Status	Watershed	BurrowCount	Elevation	Aspect
1	448	128324.66	1031421.00	531.75	1	5	.	.	.
2	679	128344.23	1031391.63	530.79	0	5	.	.	.
3	680	128344.77	1031391.31	530.86	1	5	.	.	.
4	683	128343.09	1031402.81	531.24	0	5	.	.	.
5	686	128343.84	1031415.25	532.11	-1	5	.	.	.

Obs	Slope	Dew	PercentRock	PercentShrub	Burrow
1	.	.	.	.	1
2	.	.	.	.	1
3	.	.	.	.	1
4	.	.	.	.	1
5	.	.	.	.	1

The Status Variable

Status	Frequency	Percent	Cumulative Frequency	Cumulative Percent
Killed by Predator	88	4.21	88	4.21
Failed	1443	69.04	1531	73.25
Successful	559	26.75	2090	100.00
Frequency Missing = 22501				

Bone Marrow Transplant Data

The Sashelp.BMT (bone marrow transplant) data set is used to illustrate survival analysis methods (Klein and Moeschberger 1997). At the time of transplant, each patient is classified into one of three risk categories: ALL (acute lymphoblastic leukemia), AML-Low Risk (acute myelocytic leukemia, low risk), and AML-High Risk. The endpoint of interest is the disease-free survival time, which is the time in days to death, relapse, or the end of the study. In this data set, the variable Group represents the patient's risk category, the variable T represents the disease-free survival time, and the variable Status is the censoring indicator such that the value 1 indicates an event time and the value 0 indicates a censored time. The following steps display information about the Sashelp.BMT data set and create [Figure B.5](#):

```
title 'Bone Marrow Transplant Data';
proc contents data=sashelp.BMT varnum;
  ods select position;
run;

title 'The First Five Observations Out of 137';
proc print data=sashelp.BMT (obs=5);
run;

title 'The Risk Group Variable';
proc freq data=sashelp.BMT;
  tables group;
run;
```

Figure B.5 Bone Marrow Transplant Data

Bone Marrow Transplant Data

Variables in Creation Order				
#	Variable	Type	Len	Label
1	Group	Char	13	Disease Group
2	T	Num	8	Disease-Free Survival Time
3	Status	Num	8	Event Indicator: 1=Event 0=Censored

The First Five Observations Out of 137

Obs	Group	T	Status
1	ALL	2081	0
2	ALL	1602	0
3	ALL	1496	0
4	ALL	1462	0
5	ALL	1433	0

The Risk Group Variable

Disease Group				
Group	Frequency	Percent	Cumulative Frequency	Cumulative Percent
ALL	38	27.74	38	27.74
AML-High Risk	45	32.85	83	60.58
AML-Low Risk	54	39.42	137	100.00

Birth Weight Data

The Sashelp.BWeight data set provides 1997 birth weight data from National Center for Health Statistics (Koenker and Hallock 2001; Abreveya 2001). The data record live, singleton births to mothers between the ages of 18 and 45 in the United States who were classified as black or white. The following steps display information about the Sashelp.BWeight data set and create [Figure B.6](#):

```

title 'Birth Weight Data';
proc contents data=sashelp.BWeight varnum;
    ods select position;
run;

title 'The First Five Observations Out of 50,000';
proc print data=sashelp.BWeight (obs=5);
run;

```

Figure B.6 Birth Weight Data

Birth Weight Data

Variables in Creation Order				
#	Variable	Type	Len	Label
1	Weight	Num	8	Infant Birth Weight
2	Black	Num	8	Black Mother
3	Married	Num	8	Married Mother
4	Boy	Num	8	Baby Boy
5	MomAge	Num	8	Mother's Age
6	MomSmoke	Num	8	Smoking Mother
7	CigsPerDay	Num	8	Cigarettes Per Day
8	MomWtGain	Num	8	Mother's Pregnancy Weight Gain
9	Visit	Num	8	Prenatal Visit
10	MomEdLevel	Num	8	Mother's Education Level

The First Five Observations Out of 50,000

Obs	Weight	Black	Married	Boy	MomAge	MomSmoke	CigsPerDay	MomWtGain	Visit	MomEdLevel
1	4111	0	1	1	-3	0	0	-16	1	0
2	3997	0	1	0	1	0	0	2	3	2
3	3572	0	1	1	0	0	0	-3	3	0
4	1956	0	1	1	-1	0	0	-5	3	2
5	3515	0	1	1	-6	0	0	-20	3	0

Class Data

The Sashelp.Class data set provides information about a small fictitious class of students. Variables include Sex, Age, Height, and Weight. This data set is frequently used in SAS documentation to illustrate basic SAS coding. The following steps display information about the Sashelp.Class data set and create [Figure B.7](#):

```
title 'Class Data';
proc contents data=sashelp.Class varnum;
    ods select position;
run;

title 'The Full Data Set';
proc print data=sashelp.Class;
run;
```

Figure B.7 Class Data

Class Data

Variables in Creation Order			
#	Variable	Type	Len
1	Name	Char	8
2	Sex	Char	1
3	Age	Num	8
4	Height	Num	8
5	Weight	Num	8

The Full Data Set

Obs	Name	Sex	Age	Height	Weight
1	Alfred	M	14	69.0	112.5
2	Alice	F	13	56.5	84.0
3	Barbara	F	13	65.3	98.0
4	Carol	F	14	62.8	102.5
5	Henry	M	14	63.5	102.5
6	James	M	12	57.3	83.0
7	Jane	F	12	59.8	84.5
8	Janet	F	15	62.5	112.5
9	Jeffrey	M	13	62.5	84.0
10	John	M	12	59.0	99.5
11	Joyce	F	11	51.3	50.5
12	Judy	F	14	64.3	90.0
13	Louise	F	12	56.3	77.0
14	Mary	F	15	66.5	112.0
15	Philip	M	16	72.0	150.0
16	Robert	M	12	64.8	128.0
17	Ronald	M	15	67.0	133.0
18	Thomas	M	11	57.5	85.0
19	William	M	15	66.5	112.0

Comet Data

The Sashelp.Comet data set provides information from the following experiment. Twenty-four male rats were divided into four groups. Three groups received a daily oral dose of a 1,2-dimethylhydrazine dihydrochloride in three dose levels (low, medium, and high, respectively); the fourth group was a control group. Three additional animals received a positive control. Cell suspensions for each animal were scored for DNA damage by using a comet assay (Ghebretinsae et al. 2013). The following steps display information about the Sashelp.Comet data set and create [Figure B.8](#):

```
title 'Comet Data';
proc contents data=sashelp.Comet varnum;
  ods select position;
run;

title 'The First Five Observations Out of 4,050';
proc print data=sashelp.Comet (obs=5);
run;
```

Figure B.8 Comet Data

Comet Data

Variables in Creation Order				
#	Variable	Type	Len	Label
1	Dose	Num	8	1,2 Dimethylhydrazine dihydrochloride Dose Level
2	Rat	Num	8	Rat Index
3	Sample	Num	8	Slide Index of Grouped Cells from a Rat
4	Length	Num	8	Tail Length of the Comet

The First Five Observations Out of 4,050

Obs	Dose	Rat	Sample	Length
1	0	1	1	15.3527
2	0	1	1	16.1826
3	0	1	1	14.9378
4	0	1	1	12.4481
5	0	1	1	12.8631

El Niño–Southern Oscillation Data

The Sashelp.ENS0 (El Niño–Southern Oscillation) data set contains measurements of monthly averaged atmospheric pressure differences between Easter Island and Darwin, Australia, for a period of 168 months (National Institute of Standards and Technology 1998). These pressure differences drive the southern trade winds. This data set is used to illustrate fitting nonlinear functions to a scatter plot by using methods such as loess and penalized B-splines. These data show both seasonal variations and variations due to El Niño. The following steps display information about the Sashelp.ENS0 data set and create [Figure B.9](#):

```
title 'El Nino Southern Oscillation Data';
proc contents data=sashelp.ENS0 varnum;
    ods select position;
run;

title 'The First Five Observations Out of 168';
proc print data=sashelp.ENS0 (obs=5);
run;
```

Figure B.9 El Niño–Southern Oscillation Data

El Nino Southern Oscillation Data

Variables in Creation Order		
#	Variable	Type Len
1	Month	Num 8
2	Year	Num 8
3	Pressure	Num 8

The First Five Observations Out of 168

Obs	Month	Year	Pressure
1	1	0.08333	12.9
2	2	0.16667	11.3
3	3	0.25000	10.6
4	4	0.33333	11.2
5	5	0.41667	10.9

Finland's Lake Laengelmaevesi Fish Catch Data

The Sashelp.Fish catch data set contains measurements of 159 fish that were caught in Finland's Lake Laengelmaevesi (Puranen 1917); it is used to illustrate discriminant analysis. For each of the seven species (bream, roach, whitefish, parkki, perch, pike, and smelt), the weight, length, height, and width of each fish are tallied. Three different length measurements are recorded: from the nose of the fish to the beginning of its tail, from the nose to the notch of its tail, and from the nose to the end of its tail. The height and width are recorded as percentages of the third length variable. The following steps display information about the Sashelp.Fish data set and create Figure B.10:

```

title 'Finland's Lake Laengelmaevesi Fish Catch Data';
proc contents data=sashelp.Fish varnum;
    ods select position;
run;

title 'The First Five Observations Out of 159';
proc print data=sashelp.Fish(obs=5);
run;

title 'The Fish Species Variable';
proc freq data=sashelp.Fish;
    tables species;
run;

```

Figure B.10 Finland's Lake Laengelmaevesi Fish Catch Data

Finland's Lake Laengelmaevesi Fish Catch Data

Variables in Creation Order			
#	Variable	Type	Len
1	Species	Char	9
2	Weight	Num	8
3	Length1	Num	8
4	Length2	Num	8
5	Length3	Num	8
6	Height	Num	8
7	Width	Num	8

The First Five Observations Out of 159

Obs	Species	Weight	Length1	Length2	Length3	Height	Width
1	Bream	242	23.2	25.4	30.0	11.5200	4.0200
2	Bream	290	24.0	26.3	31.2	12.4800	4.3056
3	Bream	340	23.9	26.5	31.1	12.3778	4.6961
4	Bream	363	26.3	29.0	33.5	12.7300	4.4555
5	Bream	430	26.5	29.0	34.0	12.4440	5.1340

Figure B.10 *continued***The Fish Species Variable**

Species	Frequency	Percent	Cumulative Frequency	Cumulative Percent
Bream	35	22.01	35	22.01
Parkki	11	6.92	46	28.93
Perch	56	35.22	102	64.15
Pike	17	10.69	119	74.84
Roach	20	12.58	139	87.42
Smelt	14	8.81	153	96.23
Whitefish	6	3.77	159	100.00

Exhaust Emissions Data

The Sashelp.Gas data set contains data from an experiment about gasoline engine exhaust emissions (Brinkman 1981). Nitrogen oxide emissions from a single-cylinder engine are measured for various combinations of fuel, compression ratio, and equivalence ratio. This data set is used to illustrate how to fit models by using nonlinearly transformed data. The following steps display information about the Sashelp.Gas data set and create Figure B.11:

```

title 'Exhaust Emissions Data';
proc contents data=sashelp.Gas varnum;
    ods select position;
run;

title 'The First Five Observations Out of 171';
proc print data=sashelp.Gas (obs=5);
run;

title 'The Fuel Type Variable';
proc freq data=sashelp.Gas;
    tables fuel;
run;

```

Figure B.11 Exhaust Emissions Data

Exhaust Emissions Data

Variables in Creation Order				
#	Variable	Type	Len	Label
1	Fuel	Char	8	
2	CpRatio	Num	8	Compression Ratio
3	EqRatio	Num	8	Equivalence Ratio
4	NOx	Num	8	Nitrogen Oxide

The First Five Observations Out of 171

Obs	Fuel	CpRatio	EqRatio	NOx
1	Ethanol	12	0.907	3.741
2	Ethanol	12	0.761	2.295
3	Ethanol	12	1.108	1.498
4	Ethanol	12	1.016	2.881
5	Ethanol	12	1.189	0.760

The Fuel Type Variable

Fuel	Frequency	Percent	Cumulative Frequency	Cumulative Percent
82rongas	9	5.26	9	5.26
94%Eth	25	14.62	34	19.88
Ethanol	90	52.63	124	72.51
Gasohol	13	7.60	137	80.12
Indolene	22	12.87	159	92.98
Methanol	12	7.02	171	100.00

Fisher (1936) Iris Data

The Sashelp.Iris data set (Fisher 1936) is widely used for examples of discriminant analysis and cluster analysis. The data are measurements in millimeters of the sepal length, sepal width, petal length, and petal width of 50 iris specimens from each of three species: *Iris setosa*, *I. versicolor*, and *I. virginica*. The following steps display information about the Sashelp.Iris data set and create [Figure B.12](#):

```

title 'Fisher (1936) Iris Data';
proc contents data=sashelp.Iris varnum;
    ods select position;
run;

title 'The First Five Observations Out of 150';
proc print data=sashelp.Iris(obs=5);
run;

title 'The Iris Species Variable';
proc freq data=sashelp.Iris;
    tables species;
run;

```

Figure B.12 Fisher (1936) Iris Data

Fisher (1936) Iris Data

Variables in Creation Order			
#	Variable	Type	Len Label
1	Species	Char	10 Iris Species
2	SepalLength	Num	8 Sepal Length (mm)
3	SepalWidth	Num	8 Sepal Width (mm)
4	PetalLength	Num	8 Petal Length (mm)
5	PetalWidth	Num	8 Petal Width (mm)

The First Five Observations Out of 150

Obs	Species	SepalLength	SepalWidth	PetalLength	PetalWidth
1	Setosa	50	33	14	2
2	Setosa	46	34	14	3
3	Setosa	46	36	10	2
4	Setosa	51	33	17	5
5	Setosa	55	35	13	2

The Iris Species Variable

Iris Species				
Species	Frequency	Percent	Cumulative Frequency	Cumulative Percent
Setosa	50	33.33	50	33.33
Versicolor	50	33.33	100	66.67
Virginica	50	33.33	150	100.00

Junk Email Data

The Sashelp.JunkMail data set comes from a study that classifies whether an email is junk email (coded as 1) or not (coded as 0). The data were collected in Hewlett-Packard labs and donated by George Forman. The data set contains 4,601 observations with 59 variables. The response variable is a binary indicator of whether an email is considered spam or not. There are 57 predictor variables that record frequencies of some common words and characters and lengths of uninterrupted sequences of capital letters in emails. The following steps display information about the Sashelp.JunkMail data set and create [Figure B.13](#):

```
title 'Junk Email Data';
proc contents data=sashelp.JunkMail varnum;
    ods select position;
run;

title 'The First Five Observations Out of 4,601';
proc print data=sashelp.JunkMail(obs=5);
run;
```

Figure B.13 Junk Email Data

Variables in Creation Order				
#	Variable	Type	Len	Label
1	Test	Num	8	0 - Training, 1 - Test
2	Make	Num	8	
3	Address	Num	8	
4	All	Num	8	
5	_3D	Num	8	3D
6	Our	Num	8	
7	Over	Num	8	
8	Remove	Num	8	
9	Internet	Num	8	
10	Order	Num	8	
11	Mail	Num	8	
12	Receive	Num	8	
13	Will	Num	8	
14	People	Num	8	
15	Report	Num	8	
16	Addresses	Num	8	
17	Free	Num	8	
18	Business	Num	8	
19	Email	Num	8	
20	You	Num	8	
21	Credit	Num	8	
22	Your	Num	8	
23	Font	Num	8	
24	_000	Num	8	000
25	Money	Num	8	

Figure B.13 *continued***Junk Email Data**

Variables in Creation Order			
#	Variable	Type	Len Label
26	HP	Num	8
27	HPL	Num	8
28	George	Num	8
29	_650	Num	8 650
30	Lab	Num	8
31	Labs	Num	8
32	Telnet	Num	8
33	_857	Num	8 857
34	Data	Num	8
35	_415	Num	8 415
36	_85	Num	8 85
37	Technology	Num	8
38	_1999	Num	8 1999
39	Parts	Num	8
40	PM	Num	8
41	Direct	Num	8
42	CS	Num	8
43	Meeting	Num	8
44	Original	Num	8
45	Project	Num	8
46	RE	Num	8
47	Edu	Num	8
48	Table	Num	8
49	Conference	Num	8
50	Semicolon	Num	8
51	Paren	Num	8
52	Bracket	Num	8
53	Exclamation	Num	8
54	Dollar	Num	8
55	Pound	Num	8
56	CapAvg	Num	8 Capital Run Length Average
57	CapLong	Num	8 Capital Run Length Longest
58	CapTotal	Num	8 Capital Run Length Total
59	Class	Num	8 0 - Not Junk, 1 - Junk

Figure B.13 *continued***The First Five Observations Out of 4,601**

Obs	Test	Make	Address	All	_3D	Our	Over	Remove	Internet	Order	Mail	Receive	Will	People	Report
1	1	0.00	0.64	0.64	0	0.32	0.00	0.00	0.00	0.00	0.00	0.00	0.64	0.00	0.00
2	0	0.21	0.28	0.50	0	0.14	0.28	0.21	0.07	0.00	0.94	0.21	0.79	0.65	0.21
3	1	0.06	0.00	0.71	0	1.23	0.19	0.19	0.12	0.64	0.25	0.38	0.45	0.12	0.00
4	0	0.00	0.00	0.00	0	0.63	0.00	0.31	0.63	0.31	0.63	0.31	0.31	0.31	0.00
5	0	0.00	0.00	0.00	0	0.63	0.00	0.31	0.63	0.31	0.63	0.31	0.31	0.31	0.00

Obs	Addresses	Free	Business	Email	You	Credit	Your	Font	_000	Money	HP	HPL	George	_650	Lab	Labs
1	0.00	0.32	0.00	1.29	1.93	0.00	0.96	0	0.00	0.00	0	0	0	0	0	0
2	0.14	0.14	0.07	0.28	3.47	0.00	1.59	0	0.43	0.43	0	0	0	0	0	0
3	1.75	0.06	0.06	1.03	1.36	0.32	0.51	0	1.16	0.06	0	0	0	0	0	0
4	0.00	0.31	0.00	0.00	3.18	0.00	0.31	0	0.00	0.00	0	0	0	0	0	0
5	0.00	0.31	0.00	0.00	3.18	0.00	0.31	0	0.00	0.00	0	0	0	0	0	0

Obs	Telnet	_857	Data	_415	_85	Technology	_1999	Parts	PM	Direct	CS	Meeting	Original	Project	RE	Edu
1	0	0	0	0	0	0	0.00	0	0	0.00	0	0	0.00	0	0.00	0.00
2	0	0	0	0	0	0	0.07	0	0	0.00	0	0	0.00	0	0.00	0.00
3	0	0	0	0	0	0	0.00	0	0	0.06	0	0	0.12	0	0.06	0.06
4	0	0	0	0	0	0	0.00	0	0	0.00	0	0	0.00	0	0.00	0.00
5	0	0	0	0	0	0	0.00	0	0	0.00	0	0	0.00	0	0.00	0.00

Obs	Table	Conference	Semicolon	Paren	Bracket	Exclamation	Dollar	Pound	CapAvg	CapLong	CapTotal	Class
1	0	0	0.00	0.000	0	0.778	0.000	0.000	3.756	61	278	1
2	0	0	0.00	0.132	0	0.372	0.180	0.048	5.114	101	1028	1
3	0	0	0.01	0.143	0	0.276	0.184	0.010	9.821	485	2259	1
4	0	0	0.00	0.137	0	0.137	0.000	0.000	3.537	40	191	1
5	0	0	0.00	0.135	0	0.135	0.000	0.000	3.537	40	191	1

Leukemia Data Sets

The Sashelp.LeuTrain and Sashelp.LeuTest data sets provide microarray data from (Golub et al. 1999; Zou and Hastie 2005). The Sashelp.LeuTrain data set consists of 7,129 genes and 38 training samples, and the Sashelp.LeuTest data set consists of the same 7,129 genes and 34 testing samples. Among the 38 training samples, 27 are type 1 leukemia (acute lymphoblastic leukemia, coded in the data as 1) and 11 are type 2 leukemia (acute myeloid leukemia, coded in the data as -1).

The following steps display information about Sashelp.LeuTrain data set and create [Figure B.14](#):

```

title 'Leukemia Training Data';
proc contents data=sashelp.LeuTrain varnum;
    ods select position;
run;

title 'The First Five Observations and 11 Variables';
proc print data=sashelp.LeuTrain(obs=5);
    var y x1-x10;
run;

title 'Leukemia Type Variable';
proc freq data=sashelp.LeuTrain;
    tables y;
run;

```

Figure B.14 Leukemia Training Data

The First Five Observations and 11 Variables

Obs	y	x1	x2	x3	x4	x5	x6	x7	x8	x9	x10
1	1	-1.46240	-0.64514	-0.83593	-1.47040	-0.91997	-1.58430	0.71239	-0.54229	1.05090	0.23649
2	1	-0.66480	0.20615	-0.36857	0.25822	-0.47567	-0.35497	-1.11940	-0.29251	-0.37542	-0.38760
3	1	-0.20049	0.37994	-2.38280	0.43960	-1.22700	-1.76220	0.10464	-1.80750	0.49292	-1.67000
4	1	-0.25776	0.27994	1.83920	-1.62950	-1.28750	-1.26510	0.76334	-0.61645	-0.31578	-0.32193
5	1	-0.56457	-0.39588	-0.98372	-0.83741	-0.41477	0.14834	-0.03550	-0.10022	-0.75753	0.37068

Leukemia Type Variable

y	Frequency	Percent	Cumulative Frequency	Cumulative Percent
-1	11	28.95	11	28.95
1	27	71.05	38	100.00

The results of the PROC CONTENTS step are not displayed. The results show that there are 7,130 variables, y and x1–x7129.

The following steps display information about Sashelp.LeuTest data set and create [Figure B.15](#):

```

title 'Leukemia Test Data';
proc contents data=sashelp.LeuTest varnum;
    ods select position;
run;

title 'The First Five Observations and 11 Variables';
proc print data=sashelp.LeuTest (obs=5);
    var y x1-x10;
run;

title 'Leukemia Type Variable';
proc freq data=sashelp.LeuTest;
    tables y;
run;

```

Figure B.15 Leukemia Test Data

The First Five Observations and 11 Variables

Obs	y	x1	x2	x3	x4	x5	x6	x7	x8	x9	x10
1	1	-1.38240	0.06288	0.62252	1.61210	0.52179	0.11516	-1.85270	-0.39956	0.88007	-0.86565
2	1	0.65192	-0.35476	2.29630	1.64980	0.50211	-0.37315	1.76820	-1.74270	1.63080	0.60171
3	1	0.65409	1.41340	0.22593	-0.06719	0.30015	0.76964	-0.26212	0.94481	-0.51884	-0.60999
4	1	1.07220	0.01959	0.16875	0.84779	0.24533	0.79682	0.41442	0.35122	-0.70177	1.85410
5	1	2.12480	1.66370	-0.35986	1.15850	0.89379	0.56310	-0.92476	0.56790	-0.56039	-2.12400

Leukemia Type Variable

y	Frequency	Percent	Cumulative	
			Frequency	Percent
-1	14	41.18	14	41.18
1	20	58.82	34	100.00

The results of the PROC CONTENTS step are not displayed. The results show that there are 7,130 variables, y and x1–x7129.

Margarine Data

The Sashelp.Margarin data set is a scanner panel data set that lists purchases of margarine (Rossi, Allenby, and McCulloch 2005). There are 313 households and a total of 3,405 purchases. The variable HouseID represents the household ID; each household made at least five purchases, which are defined by the choice set variable Set. The variable Choice represents the choice that households made among the six margarine brands for each purchase or choice set. The variable Brand has the value PPK for Parkay stick, PBB for Blue Bonnet stick, PFL for Fleischmann's stick, PHse for the house brand stick, PGen for the generic stick, and PSS for Shedd's Spread tub. The variable LogPrice is the logarithm of the product price. The variables LogInc and FamSize provide information about household income and family size, respectively. The following steps display information about the Sashelp.Margarin data set and create [Figure B.16](#):

```

title 'Margarine Data';
proc contents data=sashelp.Margarin varnum;
    ods select position;
run;

title 'The First Six Observations Out of 20,430';
proc print data=sashelp.Margarin(obs=6);
run;

```

Figure B.16 Margarine Data

Margarine Data

Variables in Creation Order			
#	Variable	Type	Len
1	HouseID	Num	8
2	Set	Num	8
3	Choice	Num	8
4	Brand	Char	8
5	LogPrice	Num	8
6	LogInc	Num	8
7	FamSize	Num	8

The First Six Observations Out of 20,430

Obs	HouseID	Set	Choice	Brand	LogPrice	LogInc	FamSize
1	2100016	1	1	PPK	-0.41552	3.48124	2
2	2100016	1	0	PBB	-0.40048	3.48124	2
3	2100016	1	0	PFI	0.08618	3.48124	2
4	2100016	1	0	PHse	-0.56212	3.48124	2
5	2100016	1	0	PGen	-1.02165	3.48124	2
6	2100016	1	0	PSS	-0.16252	3.48124	2

Flying Mileages between 10 US Cities Data

The Sashelp.Mileages data set contains a table of flying mileages between 10 US cities. This data set is frequently used to illustrate cluster analysis and multidimensional scaling. The following steps display information about the Sashelp.Mileages data set and create [Figure B.17](#):

```
title 'Flying Mileages between 10 US Cities Data';
proc contents data=sashelp.Mileages varnum;
    ods select position;
run;

title 'The Full Data Set';
proc print data=sashelp.Mileages noobs;
    id city;
run;
```

Figure B.17 Flying Mileages between 10 US Cities Data

Flying Mileages between 10 US Cities Data

Variables in Creation Order			
#	Variable	Type	Len
1	Atlanta	Num	8
2	Chicago	Num	8
3	Denver	Num	8
4	Houston	Num	8
5	LosAngeles	Num	8
6	Miami	Num	8
7	NewYork	Num	8
8	SanFrancisco	Num	8
9	Seattle	Num	8
10	WashingtonDC	Num	8
11	City	Char	15

The Full Data Set

City	Atlanta	Chicago	Denver	Houston	LosAngeles	Miami	NewYork	SanFrancisco	Seattle	WashingtonDC
Atlanta	0	.	.	.	.	.	.	.	.	.
Chicago	587	0	.	.	.	.	.	.	.	.
Denver	1212	920	0	.	.	.	.	.	.	.
Houston	701	940	879	0	.	.	.	.	.	.
Los Angeles	1936	1745	831	1374	0	.	.	.	.	.
Miami	604	1188	1726	968	2339	0	.	.	.	.
New York	748	713	1631	1420	2451	1092	0	.	.	.
San Francisco	2139	1858	949	1645	347	2594	2571	0	.	.
Seattle	2182	1737	1021	1891	959	2734	2408	678	0	.
Washington D.C.	543	597	1494	1220	2300	923	205	2442	2329	0

Earthquake Locations in the United States

The Sashelp.Quakes data set provides locations and measurements of earthquakes in the United States. These data are provided courtesy of the United States Geological Service. The following steps display information about the Sashelp.Quakes data set and create [Figure B.18](#):

```

title 'Earthquake Locations in the United States';
proc contents data=sashelp.Quakes varnum;
    ods select position;
run;

title 'The First Five Observations Out of 15,578';
proc print data=sashelp.Quakes(obs=5);
run;

```

Figure B.18 Earthquake Data

Earthquake Locations in the United States

Variables in Creation Order			
#	Variable	Type	Len
1	Latitude	Num	8
2	Longitude	Num	8
3	Depth	Num	8
4	Magnitude	Num	8
5	dNearestStation	Num	8
6	RootMeanSquareTime	Num	8
7	Type	Char	10

The First Five Observations Out of 15,578

Obs	Latitude	Longitude	Depth	Magnitude	dNearestStation	RootMeanSquareTime	Type
1	35.6880	-121.129	6.2500	2.75	0.02121	0.0700	earthquake
2	41.9009	-119.622	0.0000	4.59	0.50700	0.0742	earthquake
3	41.8836	-119.641	0.5329	3.19	0.49300	0.0000	earthquake
4	41.8897	-119.640	0.5077	3.12	0.49400	0.0119	earthquake
5	40.8783	-123.270	33.5700	2.60	0.22160	0.0600	earthquake

Hot-Spring Locations in the United States

The Sashelp.Springs data set provides locations and measurements of hot springs in the United States. These data are provided courtesy of the National Oceanic and Atmospheric Administration. The following steps display information about the Sashelp.Springs data set and create [Figure B.19](#):

```
title 'Hot Spring Locations in the United States';
proc contents data=sashelp.Springs varnum;
    ods select position;
run;

title 'The First Five Observations Out of 1,587';
proc print data=sashelp.Springs (obs=5);
run;
```

Figure B.19 Hot Spring Data

Hot Spring Locations in the United States

Variables in Creation Order			
#	Variable	Type	Len
1	Latitude	Num	8
2	Longitude	Num	8
3	Name	Char	34
4	Area	Char	14
5	Type	Char	9
6	Fahrenheit	Num	8
7	Celsius	Num	8

The First Five Observations Out of 1,587

Obs	Latitude	Longitude	Name	Area	Type	Fahrenheit	Celsius
1	51.925	-177.160	Fumaroles on Kanaga Island	Adak	Hotspring	219	104
2	65.858	-164.710	Serpentine Hot Springs	Bendeleben	Hotspring	171	77
3	53.851	-166.918	Hot Springs Near Makushin Volcano	Unalaska	Hotspring	H	H
4	53.877	-166.448	Hot Springs Near Summer Bay	Unalaska	Hotspring	H	H
5	52.270	-174.042	Hot Springs on Atka Island	Atka	Hotspring	H	H

Coal Seam Thickness Data

The Sashelp.Thick data set simulates measurements of coal seam thickness (in feet) taken over an approximately square area. The variable Thick contains the thickness values. The coordinates are offsets from a point in the southwest corner of the measurement area, where the unit for the north and east distances is 1,000 feet. The following steps display information about the Sashelp.Thick data set and create [Figure B.20](#):

```
title 'Coal Seam Thickness Data';
proc contents data=sashelp.Thick varnum;
    ods select position;
run;

title 'The First Five Observations Out of 75';
proc print data=sashelp.Thick (obs=5);
run;
```

Figure B.20 Coal Seam Thickness Data

Coal Seam Thickness Data

Variables in Creation Order			
#	Variable	Type	Len Label
1	East	Num	8
2	North	Num	8
3	Thick	Num	8 Coal Seam Thickness

The First Five Observations Out of 75

Obs	East	North	Thick
1	0.7	59.6	34.1
2	2.1	82.7	42.2
3	4.7	75.1	39.5
4	4.8	52.8	34.3
5	5.9	67.1	37.0

1980 US Presidential Election Data

The Sashelp.Vote1980 data set contains US county votes-cast proportions and demographic and geographic characteristics for 3,107 US counties in the 1980 presidential election (Pace and Barry 1997). The six explanatory variables are as follows: the population 18 years of age or older (Pop), the population with 12th-grade or higher education (Edu), the number of owned housing units (Houses), the aggregate income (Income), and scaled longitude and latitude of geographic centroids (Longitude, Latitude). The dependent variable LogVoteRate is the logarithm of the proportion of votes cast divided by the variable Pop. The following steps display information about the data set Sashelp.Vote1980 and create Figure B.21:

```
title 'US 1980 Presidential Election Data';
proc contents data=sashelp.vote1980 varnum;
    ods select position;
run;

title 'The First Five Observations Out of 3,107';
proc print data=sashelp.vote1980 (obs=5);
run;
```

Figure B.21 US 1980 Presidential Election Data

US 1980 Presidential Election Data

Variables in Creation Order			
#	Variable	Type	Len Label
1	LogVoteRate	Num	8 Log Votes Cast per County
2	Pop	Num	8 Population of 18 Years and Older
3	Edu	Num	8 Population with 12th Grade and Higher
4	Houses	Num	8 Number of Owned Housing Units
5	Income	Num	8 Aggregate Income
6	Longitude	Num	8 Scaled Longitude
7	Latitude	Num	8 Scaled Latitude

The First Five Observations Out of 3,107

Obs	LogVoteRate	Pop	Edu	Houses	Income	Longitude	Latitude
1	-0.66156	9.9729	9.2463	9.00405	12.1349	-0.86641	0.32542
2	-0.65086	10.9033	10.2212	9.96576	13.0566	-0.87755	0.30655
3	-0.61711	9.7222	8.7535	8.70765	11.6306	-0.85389	0.31863
4	-0.63907	9.2737	8.1831	8.27741	11.2437	-0.87127	0.32997
5	-0.70027	10.1515	9.2077	9.24068	12.1551	-0.86566	0.33980

References

- Abreveya, J. (2001). "The Effects of Demographics and Maternal Behavior on the Distribution of Birth Outcomes." *Journal of Economics* 26:247–257.
- Banerjee, S., and Gelfand, A. E. (2002). "Prediction, Interpolation, and Regression for Spatially Misaligned Data." *Sankhyā* 64:227–245.
- Brinkman, N. D. (1981). "Ethanol Fuel: A Single-Cylinder Engine Study of Efficiency and Exhaust Emissions." *Society of Automotive Engineers Transactions* 90:1410–1424.
- Condit, R. (1998). *Tropical Forest Census Plots: Methods and Results from Barro Colorado Island, Panama, and a Comparison with Other Plots*. Berlin: Springer-Verlag.
- Condit, R., Hubbell, S. P., and Foster, R. B. (1996). "Changes in Tree Species Abundance in a Neotropical Forest: Impact of Climate Change." *Journal of Tropical Ecology* 12:231–256.
- Fisher, R. A. (1936). "The Use of Multiple Measurements in Taxonomic Problems." *Annals of Eugenics* 7:179–188.
- Ghebretinsae, A. H., Faes, C., Molenberghs, G., De Boeck, M., and Geys, H. (2013). "A Bayesian, Generalized Frailty Model for Comet Assays." *Journal of Biopharmaceutical Statistics* 23:618–636.
- Golub, T. R., Slonim, D. K., Tamayo, P., Huard, C., Gaasenbeek, M., Mesirov, J. P., Coller, H., Loh, M., Downing, J. R., Caligiuri, M. A., Bloomfield, C. D., and Lander, E. S. (1999). "Molecular Classification of Cancer: Class Discovery and Class Prediction by Gene Expression." *Science* 286:531–537.
- Hubbell, S. P., and Foster, R. B. (1983). "Diversity of Canopy Trees in a Neotropical Forest and Implications for the Conservation of Tropical Trees." In *Tropical Rain Forest: Ecology and Management*, edited by S. J. Sutton, T. C. Whitmore, and A. C. Chadwick, 25–41. Oxford: Blackwell.
- Klein, J. P., and Moeschberger, M. L. (1997). *Survival Analysis: Techniques for Censored and Truncated Data*. New York: Springer-Verlag.
- Koenker, R., and Hallock, K. (2001). "Quantile Regression: An Introduction." *Journal of Economic Perspectives* 15:143–156.
- National Institute of Standards and Technology (1998). "Statistical Reference Data Sets." Accessed June 6, 2011. <http://www.itl.nist.gov/div898/strd/general/dataarchive.html>.
- Pace, R. K., and Barry, R. (1997). "Quick Computation of Spatial Autoregressive Estimators." *Geographical Analysis* 29:232–247.
- Puranen, J. (1917). "Fish Catch data set (1917)." Journal of Statistics Education Data Archive. Accessed May 22, 2009. <http://www.amstat.org/publications/jse/datasets/fishcatch.txt>.
- Rossi, P. E., Allenby, G. M., and McCulloch, R. (2005). *Bayesian Statistics and Marketing*. Chichester, UK: John Wiley & Sons.
- Time Inc. (1987). "What They Make." *Sports Illustrated* (April 20): 54–81.
- Zou, H., and Hastie, T. (2005). "Regularization and Variable Selection via the Elastic Net." *Journal of the Royal Statistical Society, Series B* 67:301–320.